
Information technology — GS1 Core business vocabulary (CBV)

*Technologies de l'information — Vocabulaire relatif aux activités de
base GS1*



Reference number
ISO/IEC 19988:2015(E)

AVA Documents
Document Sharing Hub
© ISO/IEC 2015



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT), see the following URL: [Foreword — Supplementary information](#).

The committee responsible for this document is ISO/IEC JTC 1, *Information technology*.



Core Business Vocabulary (CBV)

GS1 Standard

Version 1.1, May 2014



Documents

Document Sharing Hub



© 2010–2014 GS1 AISBL

All rights reserved.

GS1 Global Office

Avenue Louise 326, bte 10

B-1050 Brussels, Belgium

Disclaimer

GS1 AISBL (GS1) is providing this document as a free service to interested industries.

This document was developed through a consensus process of interested parties in developing the Standard. Although efforts have been made to assure that the document is correct, reliable, and technically accurate, GS1 makes NO WARRANTY, EXPRESS OR IMPLIED, THAT THIS DOCUMENT IS CORRECT, WILL NOT REQUIRE MODIFICATION AS EXPERIENCE AND TECHNOLOGY DICTATE, OR WILL BE SUITABLE FOR ANY PURPOSE OR WORKABLE IN ANY APPLICATION, OR OTHERWISE. Use of this document is with the understanding that GS1 DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF NON-INFRINGEMENT OF PATENTS OR COPYRIGHTS, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE, THAT THE INFORMATION IS ERROR FREE, NOR SHALL GS1 BE LIABLE FOR DAMAGES OF ANY KIND, INCLUDING DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, ARISING OUT OF USE OR THE INABILITY TO USE INFORMATION CONTAINED HEREIN OR FROM ERRORS CONTAINED HEREIN.



Abstract

This GS1 Standard defines Version 1.1 of the Core Business Vocabulary (CBV). The goal of this standard is to specify the structure of vocabularies and specific values for the vocabulary elements to be utilized in conjunction with the GS1 Electronic Product Code Information Services (EPCIS) standard for data sharing both within and across enterprises. The aim is to standardize these elements across users of EPCIS to improve the understanding of data contained in EPCIS events.

Audience for this document

The target audience for this standard includes:

- Users implementing the EPCIS standard for the purposes of capturing and sharing event data in the supply chain.
- Parties interested in implementing EPCIS Accessing applications.
- Parties interested in implementing EPCIS Capture applications.

Status of this document

This section describes the status of this document at the time of its publication. Other documents may supersede this document. The latest status of this document series is maintained at GS1. See www.gs1.org/gsmf for more information.

This version of the GS1 CBV 1.1 Standard is the ratified version and has completed all GSMP steps.

Comments on this document should be sent to gsmf@gs1.org.

Differences from CBV 1.0

CBV 1.1 is fully backward compatible with CBV 1.0 except as noted below.

CBV 1.1 includes these new or enhanced features:

- A new standard vocabulary for EPCIS source/destination type is added.
- Templates for new user vocabularies for EPCIS source/destination identifier, EPCIS transformation identifier, and object classes are added.
- New business step, disposition, and business transaction type values are added. The definitions of existing values are also clarified.
- Disposition values `non_sellable_expired`, `non_sellable_damaged`, `non_sellable_disposed`, `non_sellable_no_pedigree_match`, and `non_sellable_recalled` defined in CBV 1.0 are deprecated in favor of new



disposition values **expired**, **damaged**, **disposed**, **no_pedigree_match**, and **recalled** introduced in CBV 1.1.

- RFC5870-compliant geocoordinate URIs are now permitted as location identifiers.
- The introductory material is revised to align with the GS1 System Architecture.



65

Table of Contents

66	1	Introduction – Core Business Vocabulary	7
67	2	Relationship to the GS1 System Architecture	8
68	3	Relationship to EPCIS	8
69	3.1	EPCIS Event Structure	8
70	3.2	Vocabulary Kinds	9
71	3.2.1	Standard Vocabulary.....	10
72	3.2.2	User Vocabulary.....	11
73	4	Terminology and Typographical Conventions	11
74	5	Compliance and Compatibility	12
75	5.1	CBV Compliant.....	12
76	5.2	CBV Compatible.....	14
77	6	Use of Uniform Resource Identifiers (URIs)	16
78	6.1	URI Prefix for Standard Vocabularies in the CBV.....	16
79	6.2	Limitation on Use of the URI Prefix.....	16
80	7	Standard Vocabularies.....	17
81	7.1	Business Steps	17
82	7.1.1	URI Structure	17
83	7.1.2	Element Values and Definitions – Business Step.....	17
84	7.2	Dispositions.....	24
85	7.2.1	URI Structure	24
86	7.2.2	Element Values and Definitions – Dispositions	25
87	7.3	Business Transaction Types.....	29
88	7.3.1	URI Structure	29
89	7.3.2	Element Values and Definitions – Business Transaction Types	29
90	7.4	Source/Destination Types.....	30
91	7.4.1	URI Structure	30
92	7.4.2	Element Values and Definitions – Source/Destination Types	30
93	8	User Vocabularies.....	31
94	8.1	General Considerations	31
95	8.1.1	General Considerations for EPC URIs as User Vocabulary Elements.....	33
96	8.1.2	General Considerations for Private or Industry-wide URN as User Vocabulary Elements.....	33
97	8.1.3	General Considerations for HTTP URLs as User Vocabulary Elements.....	34
98	8.2	Physical or Digital Objects (Instance-Level Identification).....	35
99	8.2.1	EPC URI for Instance-level Identification of Objects	35
100	8.2.2	Private or Industry-wide URN for Instance-level Identification of Objects	35
101	8.2.3	HTTP URLs for Instance-level Identification of Objects.....	36
102	8.3	Physical or Digital Objects (Class-Level Identification).....	37
103	8.3.1	EPC URI for Class-level Identification of Objects	37
104	8.3.2	Private or Industry-wide URN for Class-level Identification of Objects.....	39
105	8.3.3	HTTP URLs for Class-level Identification of Objects	39
106	8.4	Locations.....	40
107	8.4.1	EPC URI for Location Identifiers	40

108	8.4.2	Private or Industry-wide URN for Location Identifiers.....	40
109	8.4.3	HTTP URLs for Location Identifiers	41
110	8.4.4	Geographic Location URIs for Location Identifiers	42
111	8.5	Business Transactions	42
112	8.5.1	EPC URI for Business Transaction Identifiers	43
113	8.5.2	GLN-based Identifier for Legacy System Business Transaction Identifiers.....	43
114	8.5.3	Private or Industry-wide URN for Business Transaction Identifiers.....	44
115	8.5.4	HTTP URLs for Business Transaction Identifiers	44
116	8.6	Source/Destination Identifiers	45
117	8.6.1	EPC URI for Source/Destination Identifiers	45
118	8.6.2	Private or Industry-wide URN for Source/Destination Identifiers	46
119	8.6.3	HTTP URLs for Source/Destination Identifiers	46
120	8.7	Transformation Identifiers	47
121	8.7.1	EPC URI for Transformation Identifiers	47
122	8.7.2	GLN-based Identifier for Legacy System Transformation Identifiers.....	48
123	8.7.3	Private or Industry-wide URN for Transformation Identifiers	48
124	8.7.4	HTTP URLs for Transformation Identifiers	49
125	9	Location Master Data.....	49
126	9.1	Location Master Data Constraints.....	50
127	9.2	Location Master Data Names	51
128	9.3	Location Master Data Values.....	51
129	9.3.1	Site Location	51
130	9.3.2	Sub-Site Type	51
131	9.3.3	Sub-Site Attributes	52
132	9.3.4	Sub-Site Detail	55
133	10	Example EPCIS Documents (non-normative)	55
134	10.1	CBV-Compliant Object Event using standard vocabulary	55
135	10.2	CBV-Compliant Object Event using HTTP URLs and Private or Industry-wide URNs.....	56
136	10.3	CBV-Compatible Event	57
137	10.4	Location Master Data.....	57
138	11	References	58
139	12	Acknowledgement of Contributors and Companies Opt'd-in during the Creation of	
140		this Standard (non-normative)	59
141			
142			
143			
144			
145			
146			

1 Introduction – Core Business Vocabulary

This GS1 Standard defines the Core Business Vocabulary (CBV). The goal of this standard is to specify various vocabulary elements and their values for use in conjunction with the EPCIS standard [EPCIS1.1], which defines mechanisms to exchange information both within and across organization boundaries. The vocabulary identifiers and definitions in this standard will ensure that all parties who exchange EPCIS data using the Core Business Vocabulary will have a common understanding of the semantic meaning of that data.

This standard is intended to provide a basic capability that meets the above goal. In particular, this standard is designed to define vocabularies that are *core* to the EPCIS abstract data model and are applicable to a broad set of business scenarios common to many industries that have a desire or requirement to share data. This standard intends to provide a useful set of values and definitions that can be consistently understood by each party in the supply chain.

Additional end user requirements may be addressed by augmenting the vocabulary elements herein with additional vocabulary elements defined for a particular industry or a set of users or a single user. Additional values for the standard vocabulary types defined in this standard may be included in follow-on versions of this standard.

This standard includes identifier syntax and specific vocabulary element values with their definitions for these *Standard Vocabularies*:

- Business step identifiers
- Disposition identifiers
- Business transaction types
- Source/Destination types

This standard provides identifier syntax options for these *User Vocabularies*:

- Objects
- Locations
- Business transactions
- Source/Destination identifiers
- Transformation identifiers

This standard provides *Master Data Attributes and Values* for describing Physical Locations including:

- Site Location
- Sub-Site Type
- Sub-Site Attributes
- Sub-Site Detail

Additional detailed master data regarding locations (addresses, etc) are not defined in this standard.

2 Relationship to the GS1 System Architecture

The Core Business Vocabulary is a companion standard to the EPCIS standard. EPCIS is the standard that defines the technical interfaces for capturing and sharing event data. EPCIS defines a framework data model for event data. The Core Business Vocabulary is a GS1 *data standard* that supplements that framework by defining specific data values that may populate the EPCIS data model. As such, the CBV exists in the “Share” group of GS1 standards.

3 Relationship to EPCIS

This section specifies how the Core Business Vocabulary standard relates to the EPC Information Services (EPCIS) standard.

3.1 EPCIS Event Structure

The EPCIS 1.1 standard [EPCIS1.1] specifies the data elements in an EPCIS event. The following lists these data elements, and indicates where the Core Business Vocabulary provides identifiers that may be used as values for those data elements.

- *The “what” dimension* The *what* dimension for most event types contains one or more unique identifiers for physical or digital objects or classes of physical or digital objects. Identifiers for physical or digital objects in the Core Business Vocabulary are specified in Section 8.2 (instance-level) and Section 8.3 (class-level). In the case of an EPCIS TransformationEvent, an optional TransformationID may be used to link together multiple events that describe the same transformation. The Core Business Vocabulary includes TransformationIDs in Section 8.7.

- *The “when” dimension* The moment in time at which an EPCIS event occurred. Event time is fully specified in the EPCIS standard.

- *The “where” dimension* The “where” dimension consists of two identifiers that describe different aspects of where an event occurred:

- *Read Point* The location where the EPCIS event took place. In the case of an EPCIS event arising from reading a bar code or RFID tag, the Read Point is often the location where the bar code or RFID tag was read. Identifiers for read points in the Core Business Vocabulary are specified in Section 8.3.

Example: A reader is placed at dock door #3 at the London Distribution Center (DC). Product passed through the dock door. Read point = <The identifier that stands for London DC Dock Door #3>

- *Business Location* The location where the subject of the event is assumed to be following an EPCIS event, until a new event takes place that indicates otherwise. Identifiers for business locations in the Core Business Vocabulary are specified in Section 8.3.

Example: A product is read through the sales floor transition door at store #123. The product is now sitting on the sales floor. Business location = <The identifier that stands for store #123 Sales Floor>

- *The “why” dimension* The “why” dimension consists of two identifiers and a list of business transaction identifiers, which collectively provide the business context or “why” the event occurred:
 - *Business Step* Denotes a specific activity within a business process. The business step field of an event specifies what business process step was taking place that caused the event to be captured. Identifiers for business steps in the Core Business Vocabulary are specified in Section 7.1.

Example: an EPCIS event is generated as a product departs the location identified by the Read Point. Business Step = <The identifier that denotes “shipping”>
 - *Disposition* Denotes the business state of an object. The disposition field of an event specifies the business condition of the subject of the event (the things specified in the “what” dimension), subsequent to the event. The disposition is assumed to hold true until another event indicates a change of disposition. Identifiers for dispositions in the Core Business Vocabulary are specified in Section 7.2.

Example: an EPCIS event is generated and afterward the products can be sold as-is and customers can access product for purchase. Disposition = <The identifier that denotes “sellable and accessible”>
 - *Business Transaction References* An EPCIS event may refer to one or more business transaction documents. Each such reference consists of two identifiers:
 - *Business Transaction Type* Denotes a particular kind of business transaction.

Example: the identifier that denotes “purchase order”. Identifiers for business transaction types in the Core Business Vocabulary are specified in Section 7.3.
 - *Business Transaction Identifier* Denotes a specific business transaction document of the type indicated by the Business Transaction Type. *Example: <The identifier that denotes Example Corp purchase order #123456>* Identifiers for business transactions in the Core Business Vocabulary are specified in Section 8.5.
 - *Source and Destination References* An EPCIS event may refer to one or more sources and/or destinations that describe the endpoints of a business transfer of which the event is a part. Each source or destination reference consists of two identifiers:
 - *Source or Destination Type* Denotes a particular kind of source or destination.

Example: the identifier that denotes “owning party”. Identifiers for source and destination types in the Core Business Vocabulary are specified in Section 7.4.
 - *Source or Destination Identifier* Denotes a source or destination of the type indicated by the Business Transaction Type. *Example: <The identifier that denotes Example Corp as an owning party>* Identifiers for sources and destinations in the Core Business Vocabulary are specified in Section 8.6.

3.2 Vocabulary Kinds

(The material in this section is adapted directly from [EPCIS1.1], Section 6.2.)

Vocabularies are used extensively within EPCIS to model conceptual, physical, and digital entities that exist in the real world.

Examples of vocabularies defined in the EPCIS standard are business steps, dispositions, location identifiers, physical or digital object identifiers, business transaction type names, and business transaction identifiers. In each case, a vocabulary represents a finite (though open-ended) set of alternatives that may appear in specific fields of events.

It is useful to distinguish two kinds of vocabularies, which follow different patterns in the way they are defined and extended over time:

- *Standard Vocabulary* A Standard Vocabulary is a set of Vocabulary Elements whose definition and meaning must be agreed to in advance by trading partners who will exchange events using the vocabulary.
- *User Vocabulary* A User Vocabulary is a set of Vocabulary Elements whose definition and meaning are under the control of a single organization.

These concepts are explained in more detail below.

3.2.1 Standard Vocabulary

A Standard Vocabulary is a set of Vocabulary Elements whose definition and meaning must be agreed to in advance by trading partners who will exchange events using the vocabulary. For example, the EPCIS standard defines a vocabulary called “business step,” whose elements are identifiers denoting such things as “shipping,” “receiving,” and so on. One trading partner may generate an event having a business step of “shipping,” and another partner receiving that event through a query can interpret it because of a prior agreement as to what “shipping” means.

Standard Vocabulary elements tend to be defined by organizations of multiple end users, such as GS1, industry consortia outside GS1, private trading partner groups, and so on. The master data associated with Standard Vocabulary elements, if any master data is defined at all, are defined by those same organizations, and tend to be distributed to users as part of a standard or by some similar means. New vocabulary elements within a given Standard Vocabulary tend to be introduced through a very deliberate and occasional process, such as the ratification of a new version of a standard or through a vote of an industry group.

The Standard Vocabularies specified in the Core Business Vocabulary standard are: *business steps* (Section 7.1), *dispositions* (Section 7.2), *business transaction types* (Section 7.3), and *source and destination types* (Section 7.4). The elements and definitions are agreed to by parties prior to exchanging data, and there is general agreement on their meaning.

Example: the following is a business step identifier defined in Section 7.1 herein:

`urn:epcglobal:cbv:bizstep:receiving`

This identifier is defined by the GS1 Core Business Vocabulary standard, and its meaning is known and accepted by those who implement the standard.

While an individual end user organization acting alone may introduce a new Standard Vocabulary element, such an element would have limited use in a data exchange setting, and would probably only be used within an organization’s four walls. On the other hand, an industry consortium or other group of trading partners may define and agree on standard vocabulary

299 elements beyond those defined by the Core Business Vocabulary, and these may be usefully used
300 within that trading group.

301 3.2.2 User Vocabulary

302 A User Vocabulary is a set of Vocabulary Elements whose definition and meaning are under the
303 control of a single organization. For example, the EPCIS standard defines a vocabulary called
304 “business location,” whose elements are identifiers denoting such things as “Acme Corp.
305 Distribution Center #3.” The location identifier and any associated master data is assigned by
306 the user. Acme Corp may generate an event whose business location field contains the identifier
307 that denotes “Acme Corp. Distribution Center #3,” and another partner receiving that event
308 through a query can interpret it either because the partner recognizes the identifier as being
309 identical to the identifier received in other events that took place in the same location, or because
310 the partner consults master data attributes associated with the location identifier, or both.

311 Example:

312 `urn:epc:id:sgln:0614141.12345.400`

313 This identifier is assigned by the End User who owns the GS1 Company Prefix 0614141, and the
314 meaning of the identifier (that is, what location it denotes) is determined exclusively by that end
315 user. Another End User can understand the meaning of this identifier by consulting associated
316 master data.

317 User Vocabulary elements are primarily defined by individual end user organizations acting
318 independently. The master data associated with User Vocabulary elements are typically defined
319 by those same organizations, and are usually distributed to trading partners through the EPCIS
320 Query Interface or other data exchange / data synchronization mechanisms. New vocabulary
321 elements within a given User Vocabulary are introduced at the sole discretion of an end user, and
322 trading partners must be prepared to respond accordingly.

323 While the Core Business Vocabulary standard does not (and as the discussion above makes clear,
324 cannot) specify particular user vocabulary elements, the Core Business Vocabulary does provide
325 syntax templates that are recommended for use by End Users in constructing their own user
326 vocabulary elements. See Section 8.1. The user vocabularies for which templates are specified
327 in this standard are: *physical or digital objects* (Sections 8.2 and 8.3), *locations* which include
328 both read points and business locations (Section 8.4), *business transaction identifiers*
329 (Section 8.5), *source/destination identifiers* (Section 8.6), and *transformation identifiers*
330 (Section 8.7).

331 4 Terminology and Typographical Conventions

332 Within this standard, the terms SHALL, SHALL NOT, SHOULD, SHOULD NOT, MAY,
333 NEED NOT, CAN, and CANNOT are to be interpreted as specified in Annex G of the ISO/IEC
334 Directives, Part 2, 2001, 4th edition [ISODir2]. When used in this way, these terms will always
335 be shown in ALL CAPS; when these words appear in ordinary typeface they are intended to have
336 their ordinary English meaning.

337 All sections of this document, with the exception of Sections 1, 2, and 3, are normative, except
338 where explicitly noted as non-normative.

The following typographical conventions are used throughout the document:

- ALL CAPS type is used for the special terms from [ISODir2] enumerated above.
- Monospace type is used to denote programming language, UML, and XML identifiers, as well as for the text of XML documents.
- Placeholders for changes that need to be made to this document prior to its reaching the final stage of approved GS1 standard are prefixed by a rightward-facing arrowhead, as this paragraph is.

5 Compliance and Compatibility

The GS1 Core Business Vocabulary is designed to facilitate interoperability in EPCIS data exchange by providing standard values for vocabulary elements to be included in EPCIS data. The standard recognizes that the greatest interoperability is achieved when all data conforms to the standard, and also recognizes that individual End Users or groups of trading partners may need to extend the standard in certain situations.

To that end, this standard defines two levels of conformance for EPCIS documents:

- *CBV-Compliant* An EPCIS document that only uses vocabulary identifiers specified in the Core Business Vocabulary standard in the standard fields of EPCIS events.
- *CBV-Compatible* An EPCIS document that uses a combination of vocabulary identifiers specified in the Core Business Vocabulary standard and other identifiers that are outside the standard.

An EPCIS document is neither CBV-Compliant nor CBV-Compatible if it wrongly uses identifiers defined in the Core Business Vocabulary standard or if it violates any other rules specified herein.

The formal definition of these terms is specified below.

5.1 CBV Compliant

A “CBV-Compliant Document” is a document that conforms to the schema and other constraints specified in [EPCIS1.1], and which furthermore conforms to all the normative language in this standard that pertains to a “CBV-Compliant Document.”

A “CBV-Compliant Application” is any application for which both of the following are true:

- If it operates in a mode where it claims to accept a CBV-Compliant Document as an input, the application SHALL accept any document that is a CBV-Compliant Document according to this standard, and furthermore in processing that input SHALL interpret each CBV identifier according to the meaning specified herein.
- If it operates in a mode where it claims to produce a CBV-Compliant Document as an output, the application SHALL only produce a document that is a CBV-Compliant Document according to this standard, and furthermore in generating that output SHALL only use CBV identifiers to denote their meaning as specified herein.

- 375 The following list summarizes the requirements for an EPCIS document to be a “CBV-
376 Compliant Document,” as specified elsewhere in this standard:
- 377 • A CBV-Compliant Document SHALL conform to the schema and other constraints specified
378 in [EPCIS1.1].
 - 379 • A CBV-Compliant Document SHALL NOT use any URI beginning with
380 `urn:epcglobal:cbv:` except as specified in this standard.
 - 381 • Each EPCIS event in a CBV-Compliant Document SHALL include a `bizStep` field, and
382 the value of the `bizStep` field SHALL be a URI consisting of the prefix
383 `urn:epcglobal:cbv:bizstep:` followed by the string specified in the first column of
384 some row of the table in Section 7.1.2.
 - 385 • A CBV-Compliant Document MAY include a `disposition` field. If the `disposition`
386 field is present, the value of the `disposition` field SHALL be a URI consisting of the
387 prefix `urn:epcglobal:cbv:disp:` followed by the string specified in the first column
388 of some row of the table in Section 7.2.2.
 - 389 • Each EPCIS event in a CBV-Compliant Document MAY include one or more
390 `bizTransaction` elements. If `bizTransaction` elements are present, each such
391 element MAY include a `type` attribute. If a given `bizTransaction` element includes a
392 `type` attribute, the value of the `type` attribute SHALL be a URI consisting of the prefix
393 `urn:epcglobal:cbv:btt:` followed by the string specified in the first column of some
394 row of the table in Section 7.3.2.
 - 395 • Each EPCIS event in a CBV-Compliant Document MAY include one or more `source` or
396 `destination` elements. The value of the `type` attribute of each such element SHALL be
397 a URI consisting of the prefix `urn:epcglobal:cbv:sdt:` followed by the string
398 specified in the first column of some row of the table in Section 7.4.2.
 - 399 • URIs defined in the EPC Tag Data Standard SHALL only be used in a CBV-Compliant
400 Document as specified in Section 8.1.1.
 - 401 • A CBV-Compliant document SHALL use one of the three URI forms specified in
402 Section 8.2 to populate instance-level identifiers in the “what” dimension of EPCIS events
403 (that is, the `epcList`, `parentID`, `childEPCs`, `inputEPCList`, and
404 `outputEPCList` fields in EPCIS `ObjectEvents`, `AggregationEvents`,
405 `TransactionEvents`, and `TransformationEvents`), for every such field that is
406 not null. A CBV-Compliant document SHOULD use the EPC URI form as specified in
407 Section 8.2.1 unless there is a strong reason to do otherwise.
 - 408 • A CBV-Compliant document SHALL NOT use an SGLN EPC (`urn:epc:id:sgln:...`) as
409 an object identifier.
 - 410 • A CBV-Compliant document SHALL use one of the three URI forms specified in
411 Section 8.3 to populate class-level identifiers in the “what” dimension of EPCIS events (that
412 is, the `epcClass` fields in all EPCIS event types), for every such field that is not null. A
413 CBV-Compliant document SHOULD use the EPC URI form as specified in Section 8.3.1
414 unless there is a strong reason to do otherwise.

- 415 • A CBV-Compliant document SHALL use one of the four URI forms specified in Section 8.4
416 to populate the “where” dimension of EPCIS events (that is, the `readPoint` and
417 `businessLocation` fields in all EPCIS event types), for every such field that is not null.
418 A CBV-Compliant document SHOULD use the EPC URI form as specified in Section 8.4.1
419 unless there is a strong reason to do otherwise.
- 420 • When using an EPC URI as a location identifier (Section 8.4.1), a CBV-Compliant document
421 SHOULD NOT use EPC schemes other than SGLN (`urn:epc:id:sgln:...`), unless there
422 is a strong reason to do so.
- 423 • A CBV-Compliant document SHALL use one of the four URI forms specified in Section 8.5
424 to populate the business transaction identifier field (that is, the text content of the
425 `bizTransaction` element) of EPCIS events, for every such field that is not null.
- 426 • When using an EPC URI as a business transaction identifier, a CBV-Compliant Documents
427 SHOULD NOT use EPC schemes other than GDTI EPCs (`urn:epc:id:gdti:...`) or
428 GSRN EPCs (`urn:epc:id:gsrn:...`), unless there is a strong reason to do so. GDTI
429 EPCs SHOULD only be used as business transaction identifiers when they have been
430 assigned to denote a business transaction, rather than a physical document not connected with
431 any business transaction.
- 432 • A CBV-Compliant document SHALL use one of the three URI forms specified in
433 Section 8.6 to populate a source or destination identifier field (that is, the text content of a
434 `source` or `destination` element), for every such field that is not null. A CBV-
435 Compliant document SHOULD use the EPC URI form as specified in Section 8.6.1 unless
436 there is a strong reason to do otherwise.
- 437 • When using an EPC URI as a location identifier (Section 8.6.1), a CBV-Compliant document
438 SHOULD NOT use EPC schemes other than SGLN (`urn:epc:id:sgln:...`), unless there
439 is a strong reason to do so.
- 440 • A CBV-Compliant document SHALL use one of the four URI forms specified in Section 8.7
441 to populate the transaction identifier field (that is, the text content of the
442 `transformationID` element) of EPCIS `TransformationEvents`, for every such
443 field that is not null.
- 444 • When using an EPC URI as a transformation identifier, a CBV-Compliant Document
445 SHOULD NOT use EPC schemes other than GDTI EPCs (`urn:epc:id:gdti:...`) unless
446 there is a strong reason to do so. GDTI EPCs SHOULD only be used as transformation
447 identifiers when they have been assigned to denote a transformation, rather than a physical
448 document not connected with any transformation.

449 5.2 CBV Compatible

450 A “CBV-Compatible Document” is a document that conforms to the schema and other
451 constraints specified in [EPCIS1.1], and which furthermore conforms to all the normative
452 language in this standard that pertains to a “CBV-Compatible Document.”

453 A “CBV-Compatible Application” is any application for which both of the following are true:

- If it operates in a mode where it claims to accept a CBV-Compatible Document as an input, the application SHALL accept any document that is a CBV-Compatible Document according to this standard, and furthermore in processing that input SHALL interpret each CBV identifier according to the meaning specified herein.
 - If it operates in a mode where it claims to produce a CBV-Compatible Document as an output, the application SHALL only produce a document that is a CBV-Compatible Document according to this standard, and furthermore in generating that output SHALL only use CBV identifiers to denote their meaning as specified herein.
- The following list summarizes the requirements for an EPCIS document to be a “CBV-Compatible Document,” as specified elsewhere in this standard.
- A CBV-Compatible Document SHALL conform to the schema and other constraints specified in [EPCIS1.1].
 - A CBV-Compatible Document SHALL NOT use any URI beginning with `urn:epcglobal:cbv:` except as specified in this standard.
 - URIs defined in the EPC Tag Data Standard SHALL only be used in a CBV-Compatible Document as specified in Section 8.1.1.
 - A CBV-Compatible Document SHOULD use the EPC URI form as specified in Section 8.2.1 for each instance-level object identifier unless there is a strong reason to do otherwise.
 - A CBV-Compatible Document SHOULD use the EPC URI form as specified in Section 8.3.1 for each class-level object identifier unless there is a strong reason to do otherwise.
 - A CBV-Compatible Document SHALL NOT use an SGLN EPC (`urn:epc:id:sgln:...`) as an object identifier.
 - A CBV-Compatible Document SHOULD use the EPC URI form as specified in Section 8.4.1 for each location identifier unless there is a strong reason to do otherwise.
 - When using an EPC URI as a location identifier (Section 8.4.1), a CBV-Compatible Document SHOULD NOT use EPC schemes other than SGLN (`urn:epc:id:sgln:...`), unless there is a strong reason to do so.
 - When using an EPC URI as a business transaction identifier, a CBV-Compatible Document SHOULD NOT use EPC schemes other than GDTI EPCs (`urn:epc:id:gdti:...`) or GSRN EPCs (`urn:epc:id:gsrn:...`), unless there is a strong reason to do so. GDTI EPCs SHOULD only be used as business transaction identifiers when they have been assigned to denote a business transaction, rather than a physical document not connected with any business transaction.
 - When using an EPC URI as a location identifier (Section 8.6.1), a CBV-Compatible document SHOULD NOT use EPC schemes other than SGLN (`urn:epc:id:sgln:...`), unless there is a strong reason to do so.

- When using an EPC URI as a transformation identifier, a CBV-Compatible Document SHOULD NOT use EPC schemes other than GDTI EPCs (`urn:epc:id:gdti:...`) unless there is a strong reason to do so. GDTI EPCs SHOULD only be used as transformation identifiers when they have been assigned to denote a transformation, rather than a physical document not connected with any transformation.

In general, every CBV-Compliant Document is also a CBV-Compatible Document, though not every CBV-Compatible Document is a CBV-Compliant Document. A CBV-Compatible Document may include an identifier that is compliant with [EPCIS1.1] but which is not permitted for CBV-Compliant Documents, provided that it meets the requirements above. A CBV-Compatible Document may also include an event in which the `bizStep` field is omitted, whereas that field is always required for CBV-Compliant Documents.

6 Use of Uniform Resource Identifiers (URIs)

This section specifies general rules that apply to all uses of URIs in this standard.

6.1 URI Prefix for Standard Vocabularies in the CBV

All URIs for standard vocabulary elements specified in the Core Business Vocabulary standard have the following syntax:

`urn:epcglobal:cbv:qualifier:payload`

where the *qualifier* denotes the type of the vocabulary the vocabulary element belongs to and *payload* the vocabulary element unambiguously identifies an element of the vocabulary.

6.2 Limitation on Use of the URI Prefix

The Core Business Vocabulary standard is the only GS1 standard in which URIs beginning with `urn:epcglobal:cbv:` are defined.

A CBV-Compliant or CBV-Compatible document SHALL NOT use any URI beginning with `urn:epcglobal:cbv:` or `urn:epc:` except as specified in this standard.

Both CBV-Compliant and CBV-Compatible documents MAY contain URIs that do not begin with `urn:epcglobal:cbv:`, provided that the requirements specified elsewhere in this standard are met. These SHALL be used to identify vocabulary elements not defined by the CBV standard. URIs beginning with `urn:epcglobal:` SHALL NOT be used except as specified herein or in another GS1 standard.

Example (Non Normative): Suppose a user needs a new disposition value to stand for "quarantined." The user may NOT use the following URI:

`urn:epcglobal:cbv:disp:quarantined`

In this case the particular URI above is NOT part of this standard and therefore may not be used. Instead a URI like the following could be used and considered CBV-Compatible. However, it must be noted that this vocabulary would have limited meaning to supply chain participants receiving this unless a prior understanding had been established.

`http://epcis.example.com/disp/quarantined`

7 Standard Vocabularies

This section specifies standard vocabulary elements for four EPCIS standard vocabularies: business steps, dispositions, business transaction types, and source/destination types.

7.1 Business Steps

This section specifies standard identifiers for the EPCIS `BusinessStepID` vocabulary. These identifiers populate the `bizStep` field in an EPCIS event, as specified below.

7.1.1 URI Structure

All business step values specified in this section have the following form:

`urn:epcglobal:cbv:bizstep:payload`

where the *payload* part is a string as specified in the next section. Every payload string defined herein contains only lower case letters and the underscore character.

7.1.2 Element Values and Definitions – Business Step

Each EPCIS event in a CBV-Compliant Document SHALL include a `bizStep` field, and the value of the `bizStep` field SHALL be a URI consisting of the prefix

`urn:epcglobal:cbv:bizstep:` followed by the string specified in the first column of some row of the table below. The portion following the prefix SHALL be written exactly as specified in the table below, in all lowercase letters (possibly including underscores, as indicated).

Example (non-normative): the following shows an excerpt of a CBV-Compliant EPCIS document in XML format containing a single event, where the business step of that event is the Core Business Vocabulary “shipping” value:

```
<epcis:EPCISDocument xmlns:epcis="urn:epcglobal:epcis:xsd:1" ...>
  <EPCISBody>
    <EventList>
      <ObjectEvent>
        ...
        <bizStep>urn:epcglobal:cbv:bizstep:shipping</bizStep>
        ...
      </ObjectEvent>
    </EventList>
  </EPCISBody>
</epcis:EPCISDocument>
```

The following example is NOT CBV-Compliant, because it does not use the full URI string in the business step field. It is also not CBV-Compatible, because the value of the business step field is not a URI with an owning authority, as required by Section 6.4 of [EPCIS1.1].

```
<epcis:EPCISDocument xmlns:epcis="urn:epcglobal:epcis:xsd:1" ...>
  <EPCISBody>
    <EventList>
      <ObjectEvent>
        ...
        <bizStep>shipping</bizStep>
```

WRONG