
**Information technology — MPEG audio
technologies —**

**Part 1:
MPEG Surround**

AMENDMENT 1: Conformance testing

Technologies de l'information — Technologies audio MPEG —

Partie 1: Ambiance MPEG

AMENDEMENT 1: Essai de conformité



Reference number
ISO/IEC 23003-1:2007/Amd. 1:2008(E)

AVA Documents
Document Sharing Hub
© ISO/IEC 2008

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Amendment 1 to ISO/IEC 23003-1:2007 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

— *Part 1: MPEG Surround*

Information technology — MPEG audio technologies —

Part 1: MPEG Surround

AMENDMENT 1: Conformance testing

After Clause 7, add a new clause, Conformance testing, as given below:

8 Conformance testing

8.1 Introduction

This clause specifies conformance criteria for both bitstreams and decoders compliant with the MPEG Surround standard as defined in Clauses 1 to 7. This is done to assist implementers and to ensure interoperability.

8.2 Terms and definitions

The terms and definitions as stated in Clause 3 apply. Furthermore, the following terms and definitions will be used throughout this clause.

bitstream – Data encoded according to the MPEG Surround standard.

conformance test bitstream – A bitstream used for testing the conformance of an MPEG Surround decoder.

8.3 MPEG Surround conformance testing

Subclause 4.7 defines the Baseline MPEG Surround profile comprising 6 levels. Some conformance criteria apply to MPEG Surround in general, while others are specific to the Baseline MPEG Surround profile and its levels. Conformance shall be tested for the level of the profile with which a given bitstream or decoder claims to comply.

8.4 Bitstreams

8.4.1 Characteristics

The MPEG Surround AOT can be used in combination with various audio object types.

8.4.2 Test procedure

8.4.2.1 Introduction

An MPEG Surround bitstream shall have the syntax and semantics as specified in Clauses 1 to 7. This subclause defines the conformance criteria that shall be fulfilled by a compliant bitstream. These criteria are specified for the syntactic elements of the bitstream and for some parameters decoded from the MPEG Surround bitstream payload.

8.4.2.2 Configuration header

8.4.2.2.1 SpatialSpecificConfig()

bsSamplingFrequencyIndex

Shall be in the range 0x0..0xc or 0xf. For further restrictions, see 8.4.2.5.

bsSamplingFrequency For restrictions, see 8.4.2.5.

bsFrameLength For restrictions, see 8.4.2.5.

bsFreqRes Shall not be encoded with a value of 0.

bsTreeConfig Shall be in the range 0..6. For further restrictions, see 8.4.2.5.

bsQuantMode Shall not be encoded with a value of 3

bsOneIcc No restrictions apply.

bsArbitraryDownmix No restrictions apply.

bsFixedGainsSur Shall be in the range 0..4.

bsFixedGainsLFE Shall be in the range 0..4.

bsFixedGainsDMX No restrictions apply.

bsMatrixMode No restrictions apply.

bsTempShapeConfig Shall not be encoded with a value of 3.

bsDecorConfig Shall not be encoded with a value of 3.

bs3DAudioMode No restrictions apply.

bsEnvQuantMode Shall be 0.

bs3DAudioHRTFset Shall be 0.

8.4.2.2.2 OttConfig()

bsOttBands Shall not be encoded with a value larger than the value of numBands as given by Table 39.

8.4.2.2.3 TttConfig()

bsTttDualMode No restrictions apply.

bsTttModeLow Shall be in the range 0..5.

bsTttModeHigh Shall be in the range 0..5.

bsTttBandsLow Shall not be encoded with a value larger than the value of numBands as given by Table 39.

8.4.2.2.4 ParamHRTFset()

bsHRTFfreqRes Shall not be encoded with a value of 0.

bsHRTFasymmetric No restrictions apply.

bsHRTFlevelLeft No restrictions apply.

bsHRTFlevelRight No restrictions apply.

bsHRTFphase No restrictions apply.

bsHRTFphaseLR No restrictions apply.

bsHRTFicc No restrictions apply.

bsHRTFiccLR No restrictions apply.

8.4.2.2.5 SpatialExtensionConfig()

bsSacExtType	No restrictions apply. Note that in case of values indicated as “reserved” in Table 54, the parsing function <code>SpatialExtensionConfigData(bsSacExtType)</code> shall return the value 0, such that possibly present data is read as <code>bsFillBits</code> (i.e., skipped) and correct parsing of the bitstream can continue.
bsSacExtLen	No restrictions apply.
bsSacExtLenAdd	No restrictions apply.
bsSacExtLenAddAdd	No restrictions apply.
bsFillBits	No restrictions apply.

8.4.2.2.6 SpatialExtensionConfigData(0)

The syntactic element `SpatialExtensionConfigData(0)` shall not be present if the helper variable `numSlots` has a value that is not listed in Table 55. Furthermore, if this syntactic element is present, the bitstream shall fulfil the requirements outlined in 6.1.13. For further restrictions, see 8.4.2.5.

bsResidualSamplingFrequencyIndex

Shall fulfil the requirements outlined in 6.1.13 and Table 88.

bsResidualFramesPerSpatialFrame

Shall fulfil the requirements outlined in 6.1.13 and Table 87.

8.4.2.2.7 ResidualConfig()

bsResidualPresent No restrictions apply.

bsResidualBands Shall not be encoded with a value larger than the value of **bsOttbands**.

8.4.2.2.8 SpatialExtensionConfigData(1)

The syntactic element `SpatialExtensionConfigData(1)` shall not be present if `bsArbitraryDownmix` is encoded with the value of 0 or the helper variable `numSlots` has a value that is not listed in Table 55. Furthermore, if this syntactic element is present, the bitstream shall fulfil the requirements outlined in 6.1.13.

bsArbitraryDownmixResidualSamplingFrequencyIndex

Shall fulfil the requirements outlined in 6.1.13 and Table 88.

bsArbitraryDownmixResidualFramesPerSpatialFrame

Shall fulfil the requirements outlined in 6.1.13 and Table 87.

bsArbitraryDownmixResidualBands

Shall not be encoded with a value larger than the value of `numBands` as given by Table 39.

8.4.2.2.9 TreeConfig()

bsOttBoxPresent No restrictions apply.

bsOttDefaultCld No restrictions apply.

bsOttModelFe No restrictions apply.

bsOttBands Shall not be encoded with a value larger than the value of `numBands` as given by Table 39.

bsOutputChannelPos Shall be in the range 0..26.

For further restrictions, see 8.4.2.5.

8.4.2.3 Bitstream payload

8.4.2.3.1 SpatialFrame()

bsIndependencyFlag No restrictions apply.

8.4.2.3.2 FramingInfo()

bsFramingType No restrictions apply.

bsNumParamSets For restrictions, see 8.4.2.5.

bsParamSlot[0] Shall be in the range 0..bsFrameLength.

bsDiffParamSlot[ps] Shall be in the range 0..bsFrameLength-bsParamSlot[ps-1]-1.

8.4.2.3.3 OttData()

No restrictions apply.

8.4.2.3.4 TttData()

ICC values of a certain Ttt box shall not be encoded with a value of 0 if (**bsTttModeLow** < 2 || (**bsTttDualMode** == 1 && **bsTttModeHigh** < 2)).

8.4.2.3.5 SmgData()

bsSmoothMode No restrictions apply.

bsSmoothTime No restrictions apply.

bsFreqResStrideSmg No restrictions apply.

bsSmgData No restrictions apply.

8.4.2.3.6 TempShapeData()

bsTempShapeEnable No restrictions apply.

bsTempShapeEnableChannel[ch]
No restrictions apply.

8.4.2.3.7 EnvelopeReshapeHuff()

hcod2D_EnvRes **bsCodeW** shall have a value out of a set of values as defined by column 'codeword' of Table A.25, and shall have a length as defined by the corresponding entry in column 'length'.

8.4.2.3.8 ArbitraryDownmixData()

No restrictions apply.

8.4.2.3.9 EcData()

bsXXXdataMode shall fulfil the requirements outlined in 6.1.13. Shall not be encoded with the value 2 if residual coding is applied.

bsDataPairXXX Shall have the value 0 if setIdx == dataSets-1. No further restrictions apply.

bsQuantCoarseXXX No restrictions apply.

bsFreqResStrideXXX No restrictions apply.

8.4.2.3.10 EcDataPair()**bsPcmCodingXXX** No restrictions apply.**bsPilotCodingXXX** No restrictions apply.**8.4.2.3.11 GroupedPcmData()****bsPcmWord** No restrictions apply.**8.4.2.3.12 DiffHuffData()****hcodPilot_XXX** **bsCodeW** shall have a value out of a set of values as defined by column 'codeword' of Tables A.2, A.3 or A.4, respectively, and shall have a length as defined by the corresponding entry in column 'length'.**bsDiffType** No restrictions apply.**bsCodingScheme** No restrictions apply.**bsPairing** No restrictions apply.**bsDiffTimeDirection** No restrictions apply.**8.4.2.3.13 HuffData1D()****hcodFirstBand_XXX** **bsCodeW** shall have a value out of a set of values as defined by column 'codeword' of Tables A.2, A.3 or A.4, respectively, and shall have a length as defined by the corresponding entry in column 'length'.**hcod1D_XXX_YY** **bsCodeW** shall have a value out of a set of values as defined by column 'codeword' of Tables A.5, A.6 or A.7, respectively, and shall have a length as defined by the corresponding entry in column 'length'.**bsSign** No restrictions apply.**8.4.2.3.14 HuffData2DFreqPair(), HuffData2DTimePair()****hcodLavIdx** **bsCodeW** shall have a value out of a set of values as defined by column 'codeword' of Table A.24, and shall have a length as defined by the corresponding entry in column 'length'.**hcod2D_XXX_YY_ZZ_LL_escape** **bsCodeW** shall have a value out of a set of values as defined by column 'codeword' of Tables A.8, A.9 or A.10, respectively, and shall have a length as defined by the corresponding entry in column 'length'.**hcod2D_XXX_YY_ZZ_LL** **bsCodeW** shall have a value out of a set of values as defined by column 'codeword' of the applicable table out of Tables A.11 to A.22, and shall have a length as defined by the corresponding entry in column 'length'.**8.4.2.3.15 SymmetryData()****bsSymBit[i]** No restrictions apply.**8.4.2.3.16 LsbData()****bsLsb** For restrictions see 8.4.2.3.24.**8.4.2.3.17 SpatialExtensionFrame()**

No restrictions apply. Note that in case of **bsSacExtType** having values indicated as "reserved" in Table 54, the parsing function **SpatialExtensionFrameData(bsSacExtType)** shall return the value 0, such that possibly present data is read as **bsFillBits** (i.e., skipped) and correct parsing of the bitstream can continue.

8.4.2.3.18 SpatialExtensionFrameData(0)

For restrictions see 8.4.2.5.

8.4.2.3.19 ResidualData()

bsIccDiffPresent[pi][ps] No restrictions apply.

hcod1D_ICC_Diff **bsCodeW** shall have a value out of a set of values as defined by column 'codeword' of Table A.23, and shall have a length as defined by the corresponding entry in column 'length'.

IccDiff[pi][ps][pb] The value of **IccDiff**[pi][ps][pb] shall not result in an invalid value for **idxICC**[pi][ps][pb].

individual_channel_stream()
Shall fulfil the restrictions outlined for this syntactic element in 5.1 and 5.2 and Tables 77 and 78.

8.4.2.3.20 SpatialExtensionFrameData(1)

No restrictions apply.

8.4.2.3.21 ArbitraryDownmixResidualData()

bsArbitraryDownmixResidualAbs[i]
No restrictions apply.

bsArbitraryDownmixResidualAlphaUpdateSet[i]
No restrictions apply.

individual_channel_stream()
Shall fulfil the restrictions outlined for this syntactic element in 5.1 and 5.2 and Tables 77 and 78.

channel_pair_element() Shall fulfil the restrictions outlined for this syntactic element in 5.1 and 5.2 and Tables 77 and 78. The parameter **common_window** shall be set to the value of 1.

8.4.2.3.22 SpatialExtensionFrameData(2)

No further restrictions apply.

8.4.2.3.23 ArbitraryTreeData()

No further restrictions apply.

8.4.2.3.24 Restrictions applying to decoded parameters

The following restrictions apply to parameters decoded from the MPEG Surround bitstream.

The helper variable **idxXXX**[pi][ps][pb] shall have values in the ranges as specified in 6.1.2.1 after the corresponding decoding process defined in 6.1.2 was carried out for the present **SpatialFrame()**.

If **bs3DAudioMode** has the value 1, then the absolute value of the determinant of $\mathbf{H}_{\text{Bin}}^{l,k}$ as defined in 6.11.5 shall be larger than or equal to 0.1, i.e.,

$$\left| \det \left(\mathbf{H}_{\text{Bin}}^{l,k} \right) \right| \geq 0.1.$$

8.4.2.4 Transport of MPEG Surround data

8.4.2.4.1 Transport in an MPEG environment

8.4.2.4.1.1 Introduction

In case of transport of MPEG Surround data in an MPEG-4 environment, the following restrictions apply.

In case of `SpatialSpecificConfig()` is conveyed out-of-band, any in-band `SpatialSpecificConfig()` shall be identical to the out-of-band one.

In case of embedding of MPEG Surround data in MPEG-2/4 AAC payloads, the following restrictions apply. There must be at least one `extension_payload()` element with `extension_type==EXT_SAC_DATA` in each AAC frame in order to enable immediate implicit signalling.

In case of embedding of MPEG Surround data in MPEG-1/2 Layer I/II/III bistreams, the following restrictions apply. The first bit of the `ancSyncword` must be byte-aligned with respect to the first bit of the `0xFFF` syncword of the MPEG-1/2 frame header. The `AncDataElement()` must be completely included in the ancillary data of a single MPEG-1/2 frame. There must be at least one `AncDataElement()` in the ancillary data of each MPEG-1/2 frame in order to enable immediate implicit signalling.

8.4.2.4.1.2 `AncDataElement()`

ancSyncword	Shall be <code>0x8E4</code> .
ancType	No restrictions apply.
ancStart	No restrictions apply.
ancStop	No restrictions apply.
ancLenBytes	No restrictions apply.
ancLenBytesAdd	No restrictions apply.
ancCrcWord	Shall have the value as determined by the procedure specified in 7.2.4.
ancDataSegmentByte	A data block formed by concatenation of <code>ancDataSegmentByte</code> as specified in 7.2.4 shall, if <code>ancType==0x0</code> or <code>ancType==0x1</code> , constitute one <code>SacDataFrame()</code> syntax element, padded at the end to obtain an integer number of bytes.

8.4.2.4.1.3 `SacDataFrame(sacHeaderFlag)`

sacHeaderFlag	No restrictions apply.
sacHeaderLen	No restrictions apply.
sacHeaderLenAdd	No restrictions apply.
bsFillBits	No restrictions apply.
sacTimeAlignFlag	No restrictions apply.
sacTimeAlign	Shall have an absolute value no larger than two times the number of samples in the MPEG Surround PCM frame as defined by bsFrameLength and bsSamplingFrequencyIndex or bsSamplingFrequency .

8.4.2.4.2 Transport over PCM channels

8.4.2.4.2.1 Introduction

In case of transport of MPEG Surround data over PCM channels, the following restrictions apply.

The BuriedData() data shall be embedded in the LSBs of the PCM channels. Typically, 16 bit PCM samples are used. However, also other sample precisions shall be supported, e.g. 20 and 24 bits.

8.4.2.4.2.2 BuriedDataHeader()

bsBDSyncword	Shall be 0xAA95.
bsBDChannels	Shall have the value of the number of PCM channels in which the MPEG Surround data is embedded.
bsBDFramelength	Shall define a PCM buried data frame size which is exactly the same as the MPEG Surround PCM frame size defined by bsFrameLength and bsSamplingFrequencyIndex or bsSamplingFrequency .
bdBDSubframes	Shall fulfil the restrictions outlined for this syntactic element in 7.3.3.
bsBDReserved	Shall be 0.
bsBDAlloc[channel][subframe]	Shall not exceed the value of n for n bit PCM samples.
bsBDHeaderCrc	shall fulfil the restrictions outlined for this syntactic element in 7.3.3.
bsBDHeaderPadding	Shall be 0.

8.4.2.4.2.3 BuriedDataFrame()

bsBDFramePadding	Shall be 0.
-------------------------	-------------

8.4.2.4.2.4 BuriedDataElement()

bsBDType	Each BuriedDataFrame() shall at least contain one BuriedDataElement() with bsBDType set to the value of 0 or 1. In the case of file based applications, the first frame shall contain a BuriedDataElement() with bsBDType set to the value of 1.
bsBDID	Shall be set to a value in the range of 0..7, each value shall be used only once in a BuriedDataFrame().
bsBDLengthIdx	No restrictions apply.
bsBDLength	Shall fulfil the restriction outlined for this syntactic element in 7.3.3.
bsBDBytes	Shall contain exactly one SacDataFrame().
bsBDDataCrc	Shall fulfil the restrictions outlined for this syntactic element in 7.3.3.

8.4.2.5 Restrictions depending on profiles and levels

8.4.2.5.1 Introduction

Depending on the profile and level associated with the present MPEG Surround bitstream, further restrictions may apply.

8.4.2.5.2 Baseline MPEG Surround profile

For the Baseline MPEG Surround Profile, the following further restrictions apply.

bsSamplingFrequencyIndex

Shall be encoded with a value listed in Table AMD1.1.

bsSamplingFrequency Shall be encoded with a value listed in Table AMD1.1.

bsFrameLength Shall be in the range 3..71.

bsTreeConfig Shall be encoded with a value listed in Table AMD1.1.

Table AMD1.1 — Restrictions for the Baseline MPEG Surround Profile

	Level 1	Level 2	Level 3	Level 4	Level 5	Level 6
bsSamplingFrequencyIndex	0x3..0xc, 0xf	0x3..0xc, 0xf	0x3..0xc, 0xf	0x3..0xc, 0xf	0x3..0xc, 0xf	0x0..0xc, 0xf
bsSamplingFrequency	<= 48000	<= 48000	<= 48000	<= 48000	<= 48000	<= 96000
bsTreeConfig	0..4	0..4	0..4	0..4	0..6	0..6

TreeConfig() After decoding of the syntactic element **TreeConfig()**, the helper variable **numOutChanAT** shall have a value not larger than 32.

SpatialExtensionConfigData(0) This syntactic element shall not be present in case of Level 1 or Level 2.

SpatialExtensionConfigData(1) This syntactic element shall not be present.

bsNumParamSets Shall have a value not larger than **bsFrameLength/4**, where the division shall be interpreted as an ANSI C integer division.

8.5 Decoders

8.5.1 Characteristics

8.5.1.1 General

The MPEG Surround decoder can be implemented in two different versions:

- High Quality MPEG Surround
- Low Power MPEG Surround

8.5.1.2 Baseline MPEG Surround profile

- The ability to skip over residual data embedded in the MPEG Surround bitstream payload is mandatory for decoders of level 1 and 2. Decoders of level 3 and higher shall be able to decode and apply a residual bitstream payload.

8.5.2 Test procedure

8.5.2.1 Downmix decoders

An MPEG Surround decoder can be used in combination with a downmix decoder. In this case, the downmix decoder shall fulfil the conformance criteria that are applicable to it. If a downmix decoder other than PCM is used, the MPEG Surround conformance test procedure uses a technique that removes the influence of a potentially inaccurate downmix decoder to the maximum extent possible.