

First edition
2010-10-01

AMENDMENT 4
2016-11-01

Information technology — MPEG audio technologies —

Part 2: Spatial Audio Object Coding (SAOC)

AMENDMENT 4: SAOC Conformance

Technologies de l'information — Technologies audio MPEG —

Partie 2: Codage d'objet audio spatial (SAOC)

AMENDEMENT 4: Conformité SAOC



Reference number
ISO/IEC 23003-2:2010/Amd.4:2016(E)

Documents
Document Sharing Hub
© ISO/IEC 2016



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html

The committee responsible for this document is ISO/IEC JTC 1, *Information technology, SC 29, Coding of audio, picture, multimedia and hypermedia information*.

Information technology — MPEG audio technologies —

Part 2: Spatial Audio Object Coding (SAOC)

AMENDMENT 4: SAOC Conformance

Add Clause 10, Conformance testing:

10 Conformance testing

10.1 Introduction

This clause specifies conformance criteria for both bitstreams and decoders compliant with the SAOC standard as defined in Clauses 1 to 9 and Annexes A to G. This is done to assist implementers and to ensure interoperability.

10.2 Terms and definitions

The terms and definitions as stated in Clause 3 apply. Furthermore, the following terms and definitions will be used throughout this clause.

bitstream data encoded according to the SAOC standard

conformance test bitstream bitstream used for testing the conformance of an SAOC decoder.

10.3 SAOC conformance testing

5.5 defines the SAOC profiles and levels. Some conformance criteria apply to SAOC in general, while others are specific to the specific SAOC profile and its levels. Conformance shall be tested for the level of the profile with which a given bitstream or decoder/transcoder claims to comply.

10.4 Bitstreams

10.4.1 Characteristics

The SAOC audio object type (AOT) can be used in combination with various AOTs.

10.4.2 Test procedure

10.4.2.1 Introduction

An SAOC bitstream shall have the syntax and semantics as specified in Clauses 1 to 9 and Annexes A to G. The present subclause defines the conformance criteria that shall be fulfilled by a compliant bitstream. These criteria are specified for the syntactic elements of the bitstream and for some parameters decoded from the SAOC bitstream payload.

10.4.2.2 Configuration header

10.4.2.2.1 SAOCSpecificConfig()/SAOCDESpecificConfig()

bsVersion	For restrictions, see 10.4.2.5.
bsSamplingFrequencyIndex	Shall be in the range 0x0..0xc or 0xf. For further restrictions, see 10.4.2.5.
bsSamplingFrequency	For restrictions, see 10.4.2.5.
bsLowDelayMode	For restrictions, see 10.4.2.5.
bsFreqRes	Shall not be encoded with a value of 0.
bsFrameLength	For restrictions, see 10.4.2.5.
bsNumObjects	For restrictions, see 10.4.2.5.
bsNumFGOs	For restrictions, see 10.4.2.5.
bsRelatedTo[i][j]	No restrictions apply.
bsTransmitAbsNrg	No restrictions apply.
bsNumDmxChannels	For restrictions, see 10.4.2.5.
bsTttDualMode	No restrictions apply.
bsTttBandsLow	Shall not be encoded with a value larger than the value of numBands as given by Table 33.
bsPdgFlag	No restrictions apply.
bsOneIOC	No restrictions apply.
bsDcuFlag	For restrictions, see 10.4.2.5.
bsDcuMandatory	No restrictions apply.
bsDcuDynamic	No restrictions apply.
bsDcuMode	No restrictions apply.
bsDcuParam	No restrictions apply.
bsDeLimitFlag	For restrictions, see 10.4.2.5.
bsDeLimitFgo	No restrictions apply.
bsDeLimitBgo	No restrictions apply.

10.4.2.2.2 SAOExtensionConfigData()

bsSaocExtType	No restrictions apply. Note that in case of values indicated as “N/A” in Table 43, the parsing function SAOExtensionConfigData(bsSaocExtType) shall return the value 0, such that possibly present data is read as bsFillBits (i.e. skipped) and correct parsing of the bitstream can continue.
bsSaocExtLen	No restrictions apply.
bsSaocExtLenAdd	No restrictions apply.
bsSaocExtLenAddAdd	No restrictions apply.
bsFillBits	No restrictions apply.

10.4.2.2.3 SAOExtensionConfigData(0)

The syntactic element SAOExtensionConfigData(0) shall not be present in case of Low Delay profile. This syntactic element shall not be present in case of Baseline and Dialogue Enhancement profiles of Level 1. Furthermore, this syntactic element shall not be present if the helper variable numSlots has a value that is not listed in ISO/IEC 23003-1:2007, Table 55. Furthermore, if this syntactic element is present, the bitstream shall fulfil the requirements outlined in ISO/IEC 23003-1:2007, 6.1.13. For further restrictions, see 10.4.2.5.

bsDeLimitFgoEAO	No restrictions apply.
bsDeLimitBgoEAO	No restrictions apply.
bsDcuFlag2	No restrictions apply.
bsDcuMode2	No restrictions apply.
bsDcuParam2	No restrictions apply.

10.4.2.2.3.1 ResidualConfig()

bsResidualSamplingFrequencyIndex	Shall fulfil the requirements outlined in ISO/IEC 23003-1:2007, 6.1.13 and Table 88.
bsResidualFramesPerSAOCFrame	Shall fulfil the requirements outlined in ISO/IEC 23003-1:2007, 6.1.13 and Table 87
bsNumGroupsFGO	For restrictions, see 10.4.2.5.
bsResidualPresent[i]	No restrictions apply.
bsResidualBands[i]	Shall not be encoded with a value larger than the value of bsTtnBandsLow[i] .
bsTtnDualMode[i]	No restrictions apply.
bsTtnBandsLow[i]	Shall not be encoded with a value larger than the value of numBands as given by Table 33.

10.4.2.2.4 SAOExtensionConfigData(1)

No restrictions apply.

10.4.2.2.5 SAOCEExtensionConfigData(2)

The syntactic element SAOCEExtensionConfigData(2) shall not be present in case of SAOC-DE profile. Shall fulfil the requirements outlined in Table 51.

10.4.2.2.6 SAOCEExtensionConfigData(3)

No restrictions apply.

10.4.2.2.7 SAOCEExtensionConfigData(8)

10.4.2.2.7.1 ObjectMetaData()

bsNumByteMetaData[i] No restrictions apply.

bsMetaData[i][j] Shall be encoded in UTF-8 encoding format.

10.4.2.2.8 SAOCEExtensionConfigData(9)

10.4.2.2.8.1 PresetConfig()

bsNumPresets No restrictions apply.

bsNumBytePresetLabel[i] No restrictions apply.

bsPresetLabel[i][j] Shall be encoded in UTF-8 encoding format.

bsPresetMatrix No restrictions apply.

10.4.2.2.8.2 PresetMatrixData()

bsPresetMatrixType Shall not be encoded with a value of 3.

bsPresetMatrixElements[i][j] No restrictions apply.

10.4.2.2.8.3 PresetMatrixData()

bsPresetUserDataIdentifier[i] Shall be encoded in UTF-8 encoding format.

bsPresetUserDataLen No restrictions apply.

10.4.2.2.9 SAOCEExtensionConfigData(10)

The syntactic element SAOCEExtensionConfigData(10) shall not be present in case of SAOC-DE profile.

10.4.2.2.9.1 SeparationMetaData()

bsNumSeparationPairs No restrictions apply.

bsSeparationMainObjectID[i] No restrictions apply.

bsSeparationSubObjectID[i] No restrictions apply.

10.4.2.3 Bitstream payload

10.4.2.3.1 SAOCFrame()/SAOCDEFrame()

bsIndependencyFlag No restrictions apply.

10.4.2.3.1.1 SAOCFramingInfo()

- bsFramingType** No restrictions apply.
- bsNumParamSets** For restrictions, see 10.4.2.5.
- bsParamSlot[i]** Shall be in the range 0...**bsFrameLength**.

10.4.2.3.1.2 EcDataSaoc()

- bsXXXdataMode[i][j]** Shall fulfil the requirements outlined in ISO/IEC 23003-1:2007, 6.1.13. Shall not be encoded with the value 2 if EAO mode (residual coding) is applied.
- bsDataPairXXX[i][j]** Shall have the value 0 if setIdx == dataSets-1. No further restrictions apply.
- bsQuantCoarseXXX[i][j]** No restrictions apply.
- bsFreqResStrideXXX[i][j]** No restrictions apply.

10.4.2.3.1.3 SAOCEcDataPair()

- bsPcmCodingXXX[i][j]** No restrictions apply.

10.4.2.3.1.4 SAOCDiffHuffData()

- bsDiffType** No restrictions apply.
- bsCodingScheme** No restrictions apply.

10.4.2.3.1.5 SAOCHuffData1D()

- hcodFirstBand_XXX** **bsCodeW** shall have a value out of a set of values as defined by column “code-word” of Tables A.2 and A.3, respectively, and shall have a length as defined by the corresponding entry in column “length”.
- hcod1D_XXX_YY** **bsCodeW** shall have a value out of a set of values as defined by column “code-word” of Tables A.4 and A.5, respectively, and shall have a length as defined by the corresponding entry in column ‘length’.
- bsSign** No restrictions apply.

10.4.2.3.1.6 SAOCHuffData2DFreqPair()

hcodLavIdx	bsCodeW shall have a value out of a set of values as defined by column “code-word” of Table A.24, and shall have a length as defined by the corresponding entry in column “length”.
hcodFirstBand_XXX	bsCodeW shall have a value out of a set of values as defined by column “code-word” of Tables A.2 and A.3, respectively, and shall have a length as defined by the corresponding entry in column “length”.
hcod2D_XXX_YY_FP_LL	bsCodeW shall have a value out of a set of values as defined by column “code-word” of the applicable table out of Tables A.11 to A.22, and shall have a length as defined by the corresponding entry in column “length”.
hcod1D_XXX_YY	bsCodeW shall have a value out of a set of values as defined by column “code-word” of Tables A.4 and A.5, respectively, and shall have a length as defined by the corresponding entry in column “length”.
bsSign	No restrictions apply.

10.4.2.3.2 SAOCExtensionFrame()

No restrictions apply. Note that in case of **bsSaocExtType** having values indicated as “N/A” in Table 43, the parsing function **SAOCExtensionFrameData(bsSaocExtType)** shall return the value 0, such that possibly present data is read as **bsFillBits** (i.e. skipped) and correct parsing of the bitstream can continue.

bsSaocExtLen	No restrictions apply.
bsSaocExtLenAdd	No restrictions apply.
bsFillBits	No restrictions apply.

10.4.2.3.3 SAOCExtensionFrameData(0)

bsDeLimitEaoUpdate	No restrictions apply.
bsDeLimitFgoEAO	No restrictions apply.
bsDeLimitBgoEAO	No restrictions apply.
bsDcuDynamicUpdate2	No restrictions apply.
bsDcuMode2	No restrictions apply.
bsDcuParam2	No restrictions apply.

10.4.2.4 Transport of SAOC data**10.4.2.4.1 Transport in an MPEG environment****10.4.2.4.1.1 Introduction**

In case of transport of SAOC data in an MPEG-4 environment, the following restrictions apply. In case of **SAOCSpecificConfig()** (or **SAOCDESpecificConfig()** for SAOC-DE profile) is conveyed out-of-band, any in-band **SAOCSpecificConfig()** (or **SAOCDESpecificConfig()** for SAOC-DE profile) shall be identical to the out-of-band one.