
**Information technology — MPEG
audio technologies —**

**Part 4:
Dynamic range control**

AMENDMENT 2: Loudness leveling

Technologies de l'information — Technologies audio MPEG —

Partie 4: Contrôle de gamme dynamique

AMENDEMENT 2: Égalisation de l'intensité sonore



Reference number
ISO/IEC 23003-4:2020/Amd. 2:2023(E)

AVA Documents
Document Sharing Hub
© ISO/IEC 2023



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

ISO and IEC draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO and IEC take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO and IEC had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents and <https://patents.iec.ch>. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia, and hypermedia*.

A list of all parts in the ISO/IEC 23003 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

Information technology — MPEG audio technologies —

Part 4: Dynamic range control

AMENDMENT 2: Loudness leveling

Introduction

Replace the fourth sentence in the second paragraph with the following:

The DRC tool includes dedicated sections for clipping prevention, ducking/leveling, and for generating a fade-in and fade-out to supplement the main dynamic range compression functionality.

6.1.1

Add, before the sentence starting with “For ISO/IEC 14496-12, configuration extension”, the following:

An extension payload of type UNIDRCCONFEXT_V1 shall precede an extension payload of type UNIDRCCONFEXT_LEVELING in the bitstream if both payloads are present.

6.1.2.4

Replace last three sentences of the first paragraph with:

If the bit for the “Duck other” or the “Duck/Level self” *drcSetEffect* is set, the DRC set is applied before any downmix specified by the downmix ID, i.e. the DRC set is always applied to the base layout and the downmix is generated thereafter. The *downmixId* 0x7F is not permitted for a DRC set with “Duck other” or “Duck/Level self” effect. In all other cases, the DRC set is applied to the channel configuration indicated by the *downmixId*.

Replace the last sentence in the next-to-last paragraph with:

Similarly, if *duckingScalingPresent* == 1, the scaling factor shall be applied to the associated ducking/leveling gain sequence for that channel group.

6.3.1

Replace the fourth and fifth paragraph with the following:

DRC sets with only a “Fade”, “Duck other” or “Duck/Level self” effect are automatically selected by the decoder without using the three-stage selection process. DRC sets with other features can be requested by using DRC decoder settings as described below.

The pool of DRC sets that is subject to the three-stage selection process comprises not only the DRC sets defined in the bitstream (except for DRC sets with “Fade”, “Duck other” or a “Duck/Level self” effect) but also virtual DRC sets generated in the DRC tool. The virtual DRC sets are placeholders for the cases where no compression is applied to the audio signal, hence their *drcSetEffect* bits are zero and they correspond to the DRC effect request “None”.

6.3.2.1

Replace the first paragraph with the following:

The pre-selection selects all DRC sets that fulfil all requirements listed in Table 10. All available DRC sets are analysed in the given order of steps. If no DRC set is selected, no DRC can be applied except for DRC sets with “Fade”, “Duck other” or “Duck/Level self” effect.

Replace Entry #4 of Table 10 with the following:

4	The DRC set does not only have a “Fade”, “Duck other” or “Duck/Level self” effect enabled.	Always.	DRC sets with “Fade”, “Duck other” or “Duck/Level self” effect are selected automatically. They are not subject to this selection process.
---	--	---------	--

Replace NOTE of Table 10 with the following:

NOTE Pre-selection steps #8 and #9 are interpreted as pre-selection steps #7 and #8 in the first edition of this document (ISO/IEC 23003-4:2015). Pre-selection step #7 related to EQ support is first available with the second edition of this document (ISO/IEC 23003-4:2020).

6.3.2.2.1

Replace the last sentence of the second paragraph, starting with “If no matching downmix IDs can be found...” with the following:

If no matching downmix IDs can be found, no DRC set can be applied except for DRC sets with “Fade”, “Duck other” or a “Duck/Level self” effect.

6.3.4

Replace the first paragraph with the following:

This clause uses the term “multiple DRC sets” for DRC sets that are independent of each other and do not include DRC sets with “Fade”, “Duck other” or a “Duck/Level self” effect.

6.3.5

Replace 6.3.5 with the following:

6.3.5 Applying multiple DRC sets

In the following cases, multiple DRC sets are applied simultaneously. First, if the DRC set selected in 6.3.4 carries a non-zero entry in the *dependsOnDrcSet* field, the depending DRC set is applied together with the selected one. Second, if a DRC set with “Fade”, “Duck other” or “Duck/Level self” effect was automatically selected, it is applied simultaneously with the DRC set selected in 6.3.4. Thus, if the DRC set selected in 6.3.4 has a non-zero *dependsOnDrcSet* value, a total of three DRC sets are applied, which is the maximum number permitted. If all three DRC sets are applied to the same layout (*downmixId*), the DRC set referenced in the *dependsOnDrcSet* field shall be applied first, the DRC set selected in 6.3.4 shall be applied thereafter, and the DRC set with “Fade”, “Duck other” or “Duck/Level self” effect shall be applied last. If none of the applied DRC sets is a parametric DRC (see 6.6), the DRC set with “Fade”, “Duck