

INTERNATIONAL
STANDARD

ISO/IEC
23360-1-4

First edition
2021-10

Linux Standard Base (LSB) —
Part 1-4:
Languages specification



Reference number
ISO/IEC 23360-1-4:2021(E)

AVA Documents
Document Sharing Hub
© ISO/IEC 2021



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see patents.iec.ch).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by the Linux Foundation as Linux Standard Base (LSB): Languages specification and drafted in accordance with its editorial rules. It was assigned to Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 22, *Programming languages, their environments and system software interfaces*, and adopted by National Bodies.

This first edition of ISO/IEC 23360-1-4 cancels and replaces ISO/IEC 23360-1:2006, which has been technically revised.

This document is based on “The GNU Free Documentation License, version 1.1”. The license is available at <https://www.gnu.org/licenses/old-licenses/fdl-1.1.html>.

A list of all parts in the ISO/IEC 23660 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

Contents

Foreword	iii
Introduction	v
I Introductory Elements	1
1 Scope	2
2 Normative References	3
3 Requirements	4
3.1 Relevant Libraries	4
4 Terms and Definitions	5
5 Documentation Conventions	7
II Python Interpreter	8
6 Python Interpreter	9
6.1 Introduction	9
6.2 Python Interpreter Location	9
6.3 Python Interpreter Version	9
6.4 Operators and Functions	9
6.5 Python Modules	9
6.6 Python Interpreter Command	9
III Perl Interpreter	15
7 Perl Interpreter	16
7.1 Introduction	16
7.2 Perl Interpreter Location	16
7.3 Perl Interpreter Version	16
7.4 Perl Operators and Functions	16
7.5 Perl Modules	16
7.6 Perl Interpreter Command	19
IV XML2 library	20
8 Libraries	21
8.1 Interfaces for libxml2	21
8.2 Data Definitions for libxml2	49
V XSLT library	126
9 Libraries	127
9.1 Interfaces for libxslt	127
9.2 Data Definitions for libxslt	132
VI Package Format and Installation	151
10 Software Installation	152
10.1 Package Dependencies	152
Annex A Alphabetical Listing of Interfaces by Library	153
A.1 libxml2	153
A.2 libxslt	181

Introduction

The LSB defines a binary interface for application programs that are compiled and packaged for LSB-conforming implementations on many different hardware architectures. A binary specification must include information specific to the computer processor architecture for which it is intended. To avoid the complexity of conditional descriptions, the specification has instead been divided into generic parts which are augmented by one of several architecture-specific parts, depending on the target processor architecture; the generic part will indicate when reference must be made to the architecture part, and vice versa.

This document should be used in conjunction with the documents it references. This document enumerates the system components it includes, but descriptions of those components may be included entirely or partly in this document, partly in other documents, or entirely in other reference documents. For example, the section that describes system service routines includes a list of the system routines supported in this interface, formal declarations of the data structures they use that are visible to applications, and a pointer to the underlying referenced specification for information about the syntax and semantics of each call. Only those routines not described in standards referenced by this document, or extensions to those standards, are described in the detail. Information referenced in this way is as much a part of this document as is the information explicitly included here.

The specification carries a version number of either the form $x.y$ or $x.y.z$. This version number carries the following meaning:

1. The first number (x) is the major version number. Versions sharing the same major version number shall be compatible in a backwards direction; that is, a newer version shall be compatible with an older version. Any deletion of a library results in a new major version number. Interfaces marked as deprecated may be removed from the specification at a major version change.
2. The second number (y) is the minor version number. Libraries and individual interfaces may be added, but not removed. Interfaces may be marked as deprecated at a minor version change. Other minor changes may be permitted at the discretion of the LSB workgroup.
3. The third number (z), if present, is the editorial level. Only editorial changes should be included in such versions.

Since this specification is a descriptive Application Binary Interface, and not a source level API specification, it is not possible to make a guarantee of 100% backward compatibility between major releases. However, it is the intent that those parts of the binary interface that are visible in the source level API will remain backward compatible from version to version, except where a feature marked as "Deprecated" in one release may be removed from a future release. Implementors are strongly encouraged to make use of symbol versioning to permit simultaneous support of applications conforming to different releases of this specification.

LSB is a trademark of the Linux Foundation. Developers of applications or implementations interested in using the trademark should see the Linux Foundation Certification Policy for details.

I Introductory Elements

1 Scope

The LSB Languages specification defines components for runtime languages which are found on an LSB conforming system.

2 Normative References

The specifications listed below are referenced in whole or in part by the LSB Languages specification. Such references may be normative or informative; a reference to specification shall only be considered normative if it is explicitly cited as such. The LSB Languages specification may make normative references to a portion of these specifications (that is, to define a specific function or group of functions); in such cases, only the explicitly referenced portion of the specification is to be considered normative.

Table 2-1 Informative References

Name	Title	URL
ISO C (1999)	ISO/IEC 9899:1999 - Programming Languages -- C	
Perl Core Modules	Perl 5.8.8 Core Modules	http://perldoc.perl.org/5.8.8/index-modules-A.html
Perl Functions	Perl 5.8.8 Functions	http://perldoc.perl.org/5.8.8/perlfunc.html
Perl Language Reference	Perl 5.8.8 Language Reference	http://perldoc.perl.org/5.8.8/index-language.html
Perl Manual	Perl 5.8.8 Manual Page	http://perldoc.perl.org/5.8.8/perlrun.html
Perl Operators	Perl 5.8.8 Operators and Precedence	http://perldoc.perl.org/5.8.8/perlop.html
Perl Syntax	Perl 5.8.8 Syntax	http://perldoc.perl.org/5.8.8/perlsyn.html
Python Library Reference	Python Library Reference Release 2.4.2	http://www.python.org/doc/2.4.2/lib/lib.html
Python Reference Manual	Python Reference Manual Release 2.4.2	http://www.python.org/doc/2.4.2/ref/ref.html
Reference Manual for libxml2	Reference Manual for libxml2	http://xmlsoft.org/html/index.html
Reference Manual for libxslt	Reference Manual for libxslt	http://xmlsoft.org/xslt/html/index.html

3 Requirements

This specification describes runtime language interpreters which shall be found in specified locations. It also defines a number of runtime modules which shall be in an implementation-defined directory which the interpreters shall search by default.

3.1 Relevant Libraries

The libraries listed in Table 3-1 shall be available on a Linux Standard Base system, with the specified runtime names. This list may be supplemented or amended by the architecture-specific specification.

Table 3-1 Standard Library Names

Library	Runtime Name
libxml2	libxml2.so.2
libxslt	libxslt.so.1

These libraries will be in an implementation-defined directory which the dynamic linker shall search by default.

4 Terms and Definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 2382, ISO 80000-2, and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

4.1

archLSB

Some LSB specification documents have both a generic, architecture-neutral part and an architecture-specific part. The latter describes elements whose definitions may be unique to a particular processor architecture. The term archLSB may be used in the generic part to refer to the corresponding section of the architecture-specific part.

4.2

Binary Standard, ABI

The total set of interfaces that are available to be used in the compiled binary code of a conforming application, including the run-time details such as calling conventions, binary format, C++ name mangling, etc.

4.3

Implementation-defined

Describes a value or behavior that is not defined by this document but is selected by an implementor. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence of the value or behavior. An application that relies on such a value or behavior cannot be assured to be portable across conforming implementations. The implementor shall document such a value or behavior so that it can be used correctly by an application.

4.4

Shell Script

A file that is read by an interpreter (e.g., awk). The first line of the shell script includes a reference to its interpreter binary.

4.5

Source Standard, API

The total set of interfaces that are available to be used in the source code of a conforming application. Due to translations, the Binary Standard and the Source Standard may contain some different interfaces.

4.6

Undefined

Describes the nature of a value or behavior not defined by this document which results from use of an invalid program construct or invalid data input. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming implementations.

4.7

Unspecified

Describes the nature of a value or behavior not specified by this document which results from use of a valid program construct or valid data input. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming implementations.

In addition, for the portions of this specification which build on IEEE Std 1003.1-2001, the definitions given in *IEEE Std 1003.1-2001, Base Definitions, Chapter 3* apply.

5 Documentation Conventions

Throughout this document, the following typographic conventions are used:

`function()`

the name of a function

command

the name of a command or utility

CONSTANT

a constant value

parameter

a parameter

variable

a variable

Throughout this specification, several tables of interfaces are presented. Each entry in these tables has the following format:

name

the name of the interface

(symver)

An optional symbol version identifier, if required.

[refno]

A reference number indexing the table of referenced specifications that follows this table.

For example,

forkpty(GLIBC_2.0) [SUSv4]

refers to the interface named `forkpty()` with symbol version `GLIBC_2.0` that is defined in the reference indicated by the tag `SUSv4`.

Note: For symbols with versions which differ between architectures, the symbol versions are defined in the architecture specific parts of of this module specification only. In the generic part, they will appear without symbol versions.

II Python Interpreter

6 Python Interpreter

6.1 Introduction

The Python interpreter API is described in the Python Library Reference, with the following requirements for an LSB conforming runtime.

6.2 Python Interpreter Location

The Python interpreter binary, or a link to the binary, shall exist at `/usr/bin/python`.

6.3 Python Interpreter Version

The default installed Python version shall be 2.4.2 or greater.

6.4 Operators and Functions

Core Python operators, subroutines, and built-in functions shall be present and shall operate as defined in Python Reference Manual.

6.5 Python Modules

An LSB conforming implementation shall provide the Python modules as described in Table 6-1 with at least the behavior described as mandatory in the referenced underlying specification. Some Python modules may be marked as deprecated, and applications should avoid using these as they may be withdrawn in future releases of this specification.

Table 6-1 Python Modules

array [1]	csv [1]	imp [1]	posix [1]	sys [1]
binascii [1]	datetime [1]	itertools [1]	pwd [1]	syslog [1]
bisect [1]	errno [1]	locale [1]	random [1]	termios [1]
cPickle [1]	exceptions [1]	marshal [1]	re [1]	thread [1]
cStringIO [1]	fcntl [1]	mmap [1]	resource [1]	time [1]
cmath [1]	gc [1]	operator [1]	select [1]	unicodedata [1]
codecs [1]	grp [1]	os [1]	signal [1]	weakref [1]
collections [1]	heapq [1]	ossaudiodev [1]	socket [1]	zipimport [1]
crypt [1]	hotshot [1]	parser [1]	string [1]	zlib [1]

Referenced Specification(s)

[1]. Python Reference Manual

6.6 Python Interpreter Command

This section contains a description of the **python** command.

PYTHON

Name

`python` — an interpreted, interactive, object-oriented programming language

Synopsis

```
python [-d ] [-E ] [-h ] [-i ] [ -m module-name ] [-O ] [ -Q argument ] [-S ] [-t ] [-u ] [-v ] [-V ] [ -W argument ] [-x ] [ -c command | script | - ] [ arguments ]
```

DESCRIPTION

Python is an interpreted, interactive, object-oriented programming language that combines remarkable power with very clear syntax. For an introduction to programming in Python you are referred to the Python Tutorial. The Python Library Reference documents built-in and standard types, constants, functions and modules. Finally, the Python Reference Manual describes the syntax and semantics of the core language in (perhaps too) much detail. (These documents may be located via the INTERNET RESOURCES below; they may be installed on your system as well.)

Python's basic power can be extended with your own modules written in C or C++. On most systems such modules may be dynamically loaded. Python is also adaptable as an extension language for existing applications. See the internal documentation for hints.

Documentation for installed Python modules and packages can be viewed by running the *pydoc* program.

COMMAND LINE OPTIONS

`-c command`

Specify the command to execute (see next section). This terminates the option list (following options are passed as arguments to the command).

`-d`

Turn on parser debugging output (for wizards only, depending on compilation options).

`-E`

Ignore environment variables like PYTHONPATH and PYTHONHOME that modify the behavior of the interpreter.

`-h`

Prints the usage for the interpreter executable and exits.

`-i`

When a script is passed as first argument or the `-c` option is used, enter interactive mode after executing the script or the command. It does not read the \$PYTHONSTARTUP file. This can be useful to inspect global variables or a stack trace when a script raises an exception.

`-m module-name`

Searches *sys.path* for the named module and runs the corresponding .py file as a script.

-O

Turn on basic optimizations. This changes the filename extension for compiled (bytecode) files from .pyc to .pyo. Given twice, causes docstrings to be discarded.

-Q *argument*

Division control; see PEP 238. The argument must be one of "old" (the default, int/int and long/long return an int or long), "new" (new division semantics, i.e. int/int and long/long returns a float), "warn" (old division semantics with a warning for int/int and long/long), or "warnall" (old division semantics with a warning for all use of the division operator). For a use of "warnall", see the Tools/scripts/fixdiv.py script.

-S

Disable the import of the module *site* and the site-dependent manipulations of *sys.path* that it entails.

-t

Issue a warning when a source file mixes tabs and spaces for indentation in a way that makes it depend on the worth of a tab expressed in spaces. Issue an error when the option is given twice.

-u

Force stdin, stdout and stderr to be totally unbuffered. On systems where it matters, also put stdin, stdout and stderr in binary mode. Note that there is internal buffering in *xreadlines()*, *readlines()* and file-object iterators ("for line in *sys.stdin*") which is not influenced by this option. To work around this, you will want to use "*sys.stdin.readline()*" inside a "while 1:" loop.

-v

Print a message each time a module is initialized, showing the place (filename or built-in module) from which it is loaded. When given twice, print a message for each file that is checked for when searching for a module. Also provides information on module cleanup at exit.

-V

Prints the Python version number of the executable and exits.

-W *argument*

Warning control. Python sometimes prints warning message to *sys.stderr*. A typical warning message has the following form: *file:line: category: message*. By default, each warning is printed once for each source line where it occurs. This option controls how often warnings are printed. Multiple -W options may be given; when a warning matches more than one option, the action for the last matching option is performed. Invalid -W options are ignored (a warning message is printed about invalid options when the first warning is issued). Warnings can also be controlled from within a Python program using the *warnings* module.

The simplest form of *argument* is one of the following *action* strings (or a unique abbreviation): *ignore* to ignore all warnings; *default* to explicitly request the default behavior (printing each warning once per source line); *all* to print a warning each time it occurs (this may generate many messages if a warning is triggered repeatedly for the same source line, such as inside a loop); *module* to print each warning only the first time it occurs in each module; *once* to print each warning only the first time it occurs in the program; or *error* to raise an exception instead of printing a warning message.

The full form of *argument* is *action:message:category:module:line*. Here, *action* is as explained above but only applies to messages that match the remaining fields. Empty fields match all values; trailing empty fields may be omitted. The *message* field matches the start of the warning message printed; this match is case-insensitive. The *category* field matches the warning category. This must be a class name; the match test whether the actual warning category of the message is a subclass of the specified warning category. The full class name must be given. The *module* field matches the (fully-qualified) module name; this match is case-sensitive. The *line* field matches the line number, where zero matches all line numbers and is thus equivalent to an omitted line number.

-x

Skip the first line of the source. This is intended for a DOS specific hack only. Warning: the line numbers in error messages will be off by one!

INTERPRETER INTERFACE

The interpreter interface resembles that of the UNIX shell: when called with standard input connected to a tty device, it prompts for commands and executes them until an EOF is read; when called with a file name argument or with a file as standard input, it reads and executes a *script* from that file; when called with *-c command*, it executes the Python statement(s) given as *command*. Here *command* may contain multiple statements separated by newlines. Leading whitespace is significant in Python statements! In non-interactive mode, the entire input is parsed before it is executed.

If available, the script name and additional arguments thereafter are passed to the script in the Python variable *sys.argv*, which is a list of strings (you must first *import sys* to be able to access it). If no script name is given, *sys.argv[0]* is an empty string; if *-c* is used, *sys.argv[0]* contains the string *'-c'*. Note that options interpreted by the Python interpreter itself are not placed in *sys.argv*.

In interactive mode, the primary prompt is *>>>*; the second prompt (which appears when a command is not complete) is *....*. The prompts can be changed by assignment to *sys.ps1* or *sys.ps2*. The interpreter quits when it reads an EOF at a prompt. When an unhandled exception occurs, a stack trace is printed and control returns to the primary prompt; in non-interactive mode, the interpreter exits after printing the stack trace. The interrupt signal raises the *KeyboardInterrupt* exception; other UNIX signals are not caught (except that SIGPIPE is sometimes ignored, in favor of the *IOError* exception). Error messages are written to *stderr*.

FILES AND DIRECTORIES

These are subject to difference depending on local installation conventions; *{prefix}* and *{exec_prefix}* are installation-dependent and should be interpreted as for GNU software; they may be the same. The default for both is */usr/local*.

`${exec_prefix}/bin/python`

Recommended location of the interpreter.

`${prefix}/lib/python<version> ${exec_prefix}/lib/python<version>`

Recommended locations of the directories containing the standard modules.

`${prefix}/include/python<version> ${exec_prefix}/include/python<version>`

Recommended locations of the directories containing the include files needed for developing Python extensions and embedding the interpreter.

`~/.pythonrc.py`

User-specific initialization file loaded by the *user* module; not used by default or by most applications.

ENVIRONMENT VARIABLES

PYTHONHOME

Change the location of the standard Python libraries. By default, the libraries are searched in `${prefix}/lib/python<version>` and `${exec_prefix}/lib/python<version>`, where `${prefix}` and `${exec_prefix}` are installation-dependent directories, both defaulting to `/usr/local`. When `$PYTHONHOME` is set to a single directory, its value replaces both `${prefix}` and `${exec_prefix}`. To specify different values for these, set `$PYTHONHOME` to `${prefix}:${exec_prefix}`.

PYTHONPATH

Augments the default search path for module files. The format is the same as the shell's `$PATH`: one or more directory pathnames separated by colons. Non-existent directories are silently ignored. The default search path is installation dependent, but generally begins with `${prefix}/lib/python<version>` (see `PYTHONHOME` above). The default search path is always appended to `$PYTHONPATH`. If a script argument is given, the directory containing the script is inserted in the path in front of `$PYTHONPATH`. The search path can be manipulated from within a Python program as the variable `sys.path`.

PYTHONSTARTUP

If this is the name of a readable file, the Python commands in that file are executed before the first prompt is displayed in interactive mode. The file is executed in the same name space where interactive commands are executed so that objects defined or imported in it can be used without qualification in the interactive session. You can also change the prompts `sys.ps1` and `sys.ps2` in this file.

PYTHONY2K

Set this to a non-empty string to cause the *time* module to require dates specified as strings to include 4-digit years, otherwise 2-digit years are converted based on rules described in the *time* module documentation.

PYTHONOPTIMIZE

If this is set to a non-empty string it is equivalent to specifying the `-O` option. If set to an integer, it is equivalent to specifying `-O` multiple times.

PYTHONDEBUG

If this is set to a non-empty string it is equivalent to specifying the `-d` option.
If set to an integer, it is equivalent to specifying `-d` multiple times.

PYTHONINSPECT

If this is set to a non-empty string it is equivalent to specifying the `-i` option.

PYTHONUNBUFFERED

If this is set to a non-empty string it is equivalent to specifying the `-u` option.

PYTHONVERBOSE

If this is set to a non-empty string it is equivalent to specifying the `-v` option.
If set to an integer, it is equivalent to specifying `-v` multiple times.

AUTHOR

The Python Software Foundation: <http://www.python.org/psf>

INTERNET RESOURCES

Main website:	http://www.python.org/	Documentation:
http://docs.python.org/	Community website:	http://starship.python.net/
http://www.python.org/dev/	FTP:	
ftp://ftp.python.org/pub/python/	Module repository:	
http://www.vex.net/parnassus/	Newsgroups:	comp.lang.python, comp.lang.python.announce

LICENSING

Python is distributed under an Open Source license. See the file "LICENSE" in the Python source distribution for information on terms & conditions for accessing and otherwise using Python and for a DISCLAIMER OF ALL WARRANTIES.

III Perl Interpreter

7 Perl Interpreter

7.1 Introduction

The Perl interpreter API is described in the Perl Language Reference, with the following requirements for an LSB conforming runtime.

7.2 Perl Interpreter Location

The Perl interpreter binary, or a link to the binary, shall exist at `/usr/bin/perl`.

7.3 Perl Interpreter Version

The default installed Perl version shall be 5.8.8 or greater.

7.4 Perl Operators and Functions

Core Perl operators, subroutines, and built-in functions shall be present and shall operate as defined in Perl Syntax, Perl Operators and Perl Functions.

7.5 Perl Modules

An LSB conforming implementation shall provide the Perl modules as described in Table 7-1 with at least the behavior described as mandatory in the referenced underlying specification. Some Perl modules may be marked as deprecated, and applications should avoid using these as they may be withdrawn in future releases of this specification.

Table 7-1 Perl Modules

AnyDBM_File [1]	Encode::JP [1]	I18N::Collate [1]	Net::Time [1]	Test::More [1]
Attribute::Handlers [1]	Encode::JP::H2Z [1]	I18N::LangTags [1]	Net::hostent [1]	Test::Simple [1]
AutoLoader [1]	Encode::JP::IS7 [1]	I18N::LangTags::Detect [1]	Net::netent [1]	Text::Abbrev [1]
AutoSplit [1]	Encode::KR [1]	I18N::LangTags::List [1]	Net::protoent [1]	Text::Balanced [1]
B::Concise [1]	Encode::KR::2022_KR [1]	I18N::Langinfo [1]	Net::servent [1]	Text::ParseWords [1]
B::Debug [1]	Encode::MIME::Header [1]	IO [1]	O [1]	Text::Soundex [1]
B::Deparse [1]	Encode::Symbol [1]	IO::Dir [1]	Opcode [1]	Text::Tabs [1]
B::Lint [1]	Encode::TW [1]	IO::File [1]	POSIX [1]	Text::Wrap [1]
B::Showlex [1]	Encode::Unicode [1]	IO::Handle [1]	PerlIO [1]	Tie::Array [1]
B::Terse [1]	Encode::Unicode::UTF7 [1]	IO::Pipe [1]	PerlIO::encoding [1]	Tie::File [1]

B::Xref [1]	English [1]	IO::Poll [1]	PerlIO::scalar [1]	Tie::Handle [1]
Benchmark [1]	Env [1]	IO::Seekable [1]	PerlIO::via [1]	Tie::Hash [1]
CGI [1]	Exporter [1]	IO::Select [1]	PerlIO::via::QuotedPrint [1]	Tie::Memoize [1]
CGI::Apache [1]	Exporter::Heavy [1]	IO::Socket [1]	Pod::Checker [1]	Tie::RefHash [1]
CGI::Carp [1]	ExtUtils::Command [1]	IO::Socket::INET [1]	Pod::Find [1]	Tie::Scalar [1]
CGI::Cookie [1]	ExtUtils::Command::MM [1]	IO::Socket::UNIX [1]	Pod::Functions [1]	Tie::SubstrHash [1]
CGI::Pretty [1]	ExtUtils::Install [1]	IPC::Msg [1]	Pod::Html [1]	Time::HiRes [1]
CGI::Push [1]	ExtUtils::Installed [1]	IPC::Open2 [1]	Pod::InputObjects [1]	Time::Local [1]
CGI::Util [1]	ExtUtils::Liblist [1]	IPC::Open3 [1]	Pod::LaTeX [1]	Time::gmtime [1]
CPAN [1]	ExtUtils::Liblist::Kid [1]	IPC::Semaphore [1]	Pod::Man [1]	Time::localtime [1]
CPAN::FirstTime [1]	ExtUtils::MM_Unix [1]	IPC::SysV [1]	Pod::ParseLink [1]	Time::tm [1]
CPAN::Nox [1]	ExtUtils::MY [1]	List::Util [1]	Pod::ParseUtils [1]	Unicode::Collate [1]
Carp [1]	ExtUtils::MakeMaker [1]	Locale::Country [1]	Pod::Parser [1]	Unicode::Normalize [1]
Carp::Heavy [1]	ExtUtils::MakeMaker::Config [1]	Locale::Currency [1]	Pod::Perldoc::ToChecker [1]	Unicode::UCD [1]
Class::Struct [1]	ExtUtils::Manifest [1]	Locale::Language [1]	Pod::Perldoc::ToMan [1]	User::grent [1]
Cwd [1]	ExtUtils::Mkbootstrap [1]	Locale::Maketext [1]	Pod::Perldoc::ToNroff [1]	User::pwent [1]
DB [1]	ExtUtils::Mksymlists [1]	Locale::Script [1]	Pod::Perldoc::ToPod [1]	attributes [1]
DBM_Filter [1]	ExtUtils::Packlist [1]	MIME::Base64 [1]	Pod::Perldoc::ToText [1]	autouse [1]
DBM_Filter::encode [1]	ExtUtils::testlib [1]	MIME::QuotedPrint [1]	Pod::PlainText [1]	base [1]
DBM_Filter::int32 [1]	Fatal [1]	Math::BigFloat [1]	Pod::Select [1]	bigint [1]

DBM_Filter::null [1]	Fcntl [1]	Math::BigInt [1]	Pod::Text [1]	bignum [1]
DBM_Filter::utf8 [1]	File::Basename [1]	Math::BigInt::Calc [1]	Pod::Text::Color [1]	bigrat [1]
Data::Dumper [1]	File::CheckTree [1]	Math::BigInt::CalcEmu [1]	Pod::Text::Overstrike [1]	blib [1]
Devel::PPPort [1]	File::Compare [1]	Math::BigRat [1]	Pod::Text::Termcap [1]	bytes [1]
Devel::Peek [1]	File::Copy [1]	Math::Complex [1]	Pod::Usage [1]	chardnames [1]
Devel::SelfStubber [1]	File::DosGlob [1]	Math::Trig [1]	SDBM_File [1]	constant [1]
Digest [1]	File::Find [1]	Memoize [1]	Safe [1]	diagnostics [1]
Digest::MD5 [1]	File::Glob [1]	Memoize::AnyDBM_File [1]	Scalar::Util [1]	fields [1]
Digest::base [1]	File::Path [1]	Memoize::Expire [1]	Search::Dict [1]	filetest [1]
Digest::file [1]	File::Spec [1]	Memoize::ExpireFile [1]	SelectSaver [1]	if [1]
DirHandle [1]	File::Spec::Functions [1]	Memoize::ExpireTest [1]	SelfLoader [1]	integer [1]
Dumpvalue [1]	File::Spec::Unix [1]	Memoize::SDBM_File [1]	Socket [1]	less [1]
Encode [1]	File::Temp [1]	Memoize::Storable [1]	Storable [1]	locale [1]
Encode::Alias [1]	File::stat [1]	NEXT [1]	Sys::Hostname [1]	open [1]
Encode::Byte [1]	FileCache [1]	Net::Cmd [1]	Sys::Syslog [1]	overload [1]
Encode::CJKConstants [1]	FileHandle [1]	Net::Config [1]	Term::ANSIColor [1]	re [1]
Encode::CN [1]	Filter::Simple [1]	Net::Domain [1]	Term::Complete [1]	sigtrap [1]
Encode::CN::HZ [1]	Filter::Util::Call [1]	Net::FTP [1]	Term::ReadLine [1]	sort [1]
Encode::Config [1]	FindBin [1]	Net::NNTP [1]	Test::Builder [1]	strict [1]
Encode::EBCDIC [1]	GDBM_File [1]	Net::Netrc [1]	Test::Builder::Module [1]	subs [1]

Encode::Encoder [1]	Getopt::Long [1]	Net::POP3 [1]	Test::Builder::Tester [1]	utf8 [1]
Encode::Encoding [1]	Getopt::Std [1]	Net::Ping [1]	Test::Builder::Tester::Color [1]	warnings [1]
Encode::Guess [1]	Hash::Util [1]	Net::SMTP [1]	Test::Harness [1]	warnings::register [1]

Referenced Specification(s)

[1]. Perl Language Reference

7.6 Perl Interpreter Command

The **perl** command is described in Perl Manual.

IV XML2 library

8 Libraries

8.1 Interfaces for libxml2

Table 8-1 defines the library name and shared object name for the libxml2 library

Table 8-1 libxml2 Definition

Library:	libxml2
SONAME:	libxml2.so.2

The behavior of the interfaces in this library is specified by the following specifications:

[libXML2] Reference Manual for libxml2

8.1.1 The XML C parser and toolkit for XML processing

8.1.1.1 Interfaces for The XML C parser and toolkit for XML processing

An LSB conforming implementation shall provide the generic functions for The XML C parser and toolkit for XML processing specified in Table 8-2, with the full mandatory functionality as described in the referenced underlying specification.

Table 8-2 libxml2 - The XML C parser and toolkit for XML processing Function Interfaces

UTF8ToHtml(LIBXML2_2.4.30) [libXML2]	UTF8ToIsolat1(LIBXML2_2.4.30) [libXML2]	__docbDefaultSAXHandler [libXML2]
__htmlDefaultSAXHandler [libXML2]	__oldXMLWDcompatibility [libXML2]	__xmlBufferAllocScheme [libXML2]
__xmlDefaultBufferSize [libXML2]	__xmlDefaultSAXHandler [libXML2]	__xmlDefaultSAXLocator [libXML2]
__xmlDeregisterNodeDefaultValue [libXML2]	__xmlDoValidityCheckingDefaultValue [libXML2]	__xmlGenericError [libXML2]
__xmlGenericErrorContext [libXML2]	__xmlGetWarningsDefaultValue [libXML2]	__xmlIndentTreeOutput [libXML2]
__xmlKeepBlanksDefaultValue [libXML2]	__xmlLastError [libXML2]	__xmlLineNumbersDefaultValue [libXML2]
__xmlLoadExtDtdDefaultValue [libXML2]	__xmlOutputBufferCreateFilenameValue [libXML2]	__xmlParserDebugEntities [libXML2]
__xmlParserInputBufferCreateFilenameValue [libXML2]	__xmlParserVersion [libXML2]	__xmlPedanticParserDefaultValue [libXML2]
__xmlRegisterNodeDefaultValue [libXML2]	__xmlSaveNoEmptyTags [libXML2]	__xmlStructuredError [libXML2]

__xmlSubstituteEntities DefaultValue [libXML2]	__xmlTreeIndentString [libXML2]	docbDefaultSAXHandle rInit(LIBXML2_2.4.30) [libXML2]
htmlAttrAllowed(LIBX ML2_2.5.2) [libXML2]	htmlAutoCloseTag(LIB XML2_2.4.30) [libXML2]	htmlCreateFileParserCt xt(LIBXML2_2.4.30) [libXML2]
htmlCreateMemoryPars erCtxt(LIBXML2_2.5.7) [libXML2]	htmlCreatePushParserC txt(LIBXML2_2.4.30) [libXML2]	htmlCtxtReadDoc(LIBX ML2_2.6.0) [libXML2]
htmlCtxtReadFd(LIBX ML2_2.6.0) [libXML2]	htmlCtxtReadFile(LIBX ML2_2.6.0) [libXML2]	htmlCtxtReadIO(LIBX ML2_2.6.0) [libXML2]
htmlCtxtReadMemory(LIBXML2_2.6.0) [libXML2]	htmlCtxtReset(LIBXML 2_2.6.0) [libXML2]	htmlCtxtUseOptions(LI BXML2_2.6.0) [libXML2]
htmlDefaultSAXHandle rInit(LIBXML2_2.4.30) [libXML2]	htmlDocContentDump FormatOutput(LIBXML 2_2.4.30) [libXML2]	htmlDocContentDump Output(LIBXML2_2.4.3 0) [libXML2]
htmlDocDump(LIBXM L2_2.4.30) [libXML2]	htmlDocDumpMemory (LIBXML2_2.4.30) [libXML2]	htmlElementAllowedH ere(LIBXML2_2.5.2) [libXML2]
htmlElementStatusHere (LIBXML2_2.5.2) [libXML2]	htmlEncodeEntities(LIB XML2_2.4.30) [libXML2]	htmlEntityLookup(LIB XML2_2.4.30) [libXML2]
htmlEntityValueLooku p(LIBXML2_2.4.30) [libXML2]	htmlFreeParserCtxt(LIB XML2_2.4.30) [libXML2]	htmlGetMetaEncoding(LIBXML2_2.4.30) [libXML2]
htmlHandleOmittedEle m(LIBXML2_2.4.30) [libXML2]	htmlInitAutoClose(LIB XML2_2.4.30) [libXML2]	htmlIsAutoClosed(LIBX ML2_2.4.30) [libXML2]
htmlIsBooleanAttr(LIB XML2_2.4.30) [libXML2]	htmlIsScriptAttribute(L IBXML2_2.4.30) [libXML2]	htmlNewDoc(LIBXML2 _2.4.30) [libXML2]
htmlNewDocNoDtD(LI BXML2_2.4.30) [libXML2]	htmlNodeDump(LIBX ML2_2.4.30) [libXML2]	htmlNodeDumpFile(LI BXML2_2.4.30) [libXML2]
htmlNodeDumpFileFor mat(LIBXML2_2.4.30) [libXML2]	htmlNodeDumpFormat Output(LIBXML2_2.4.3 0) [libXML2]	htmlNodeDumpOutput (LIBXML2_2.4.30) [libXML2]
htmlParseCharRef(LIBX ML2_2.4.30) [libXML2]	htmlParseChunk(LIBX ML2_2.4.30) [libXML2]	htmlParseDoc(LIBXML 2_2.4.30) [libXML2]
htmlParseDocument(LI BXML2_2.4.30) [libXML2]	htmlParseElement(LIBX ML2_2.4.30) [libXML2]	htmlParseEntityRef(LIB XML2_2.4.30) [libXML2]
htmlParseFile(LIBXML2 _2.4.30) [libXML2]	htmlReadDoc(LIBXML2 _2.6.0) [libXML2]	htmlReadFd(LIBXML2_ 2.6.0) [libXML2]

htmlReadFile(LIBXML2_2.6.0) [libXML2]	htmlReadIO(LIBXML2_2.6.0) [libXML2]	htmlReadMemory(LIBXML2_2.6.0) [libXML2]
htmlSAXParseDoc(LIBXML2_2.4.30) [libXML2]	htmlSAXParseFile(LIBXML2_2.4.30) [libXML2]	htmlSaveFile(LIBXML2_2.4.30) [libXML2]
htmlSaveFileEnc(LIBXML2_2.4.30) [libXML2]	htmlSaveFileFormat(LIBXML2_2.4.30) [libXML2]	htmlSetMetaEncoding(LIBXML2_2.4.30) [libXML2]
htmlTagLookup(LIBXML2_2.4.30) [libXML2]	initGenericErrorDefaultFunc(LIBXML2_2.4.30) [libXML2]	inputPop(LIBXML2_2.4.30) [libXML2]
inputPush(LIBXML2_2.4.30) [libXML2]	isolate1ToUTF8(LIBXML2_2.4.30) [libXML2]	namePop(LIBXML2_2.4.30) [libXML2]
namePush(LIBXML2_2.4.30) [libXML2]	nodePop(LIBXML2_2.4.30) [libXML2]	nodePush(LIBXML2_2.4.30) [libXML2]
valuePop(LIBXML2_2.4.30) [libXML2]	valuePush(LIBXML2_2.4.30) [libXML2]	xmlACatalogAdd(LIBXML2_2.4.30) [libXML2]
xmlACatalogDump(LIBXML2_2.4.30) [libXML2]	xmlACatalogRemove(LIBXML2_2.4.30) [libXML2]	xmlACatalogResolve(LIBXML2_2.4.30) [libXML2]
xmlACatalogResolvePublic(LIBXML2_2.4.30) [libXML2]	xmlACatalogResolveSystem(LIBXML2_2.4.30) [libXML2]	xmlACatalogResolveURI(LIBXML2_2.4.30) [libXML2]
xmlAddAttributeDecl(LIBXML2_2.4.30) [libXML2]	xmlAddChild(LIBXML2_2.4.30) [libXML2]	xmlAddChildList(LIBXML2_2.4.30) [libXML2]
xmlAddDocEntity(LIBXML2_2.4.30) [libXML2]	xmlAddDtdEntity(LIBXML2_2.4.30) [libXML2]	xmlAddElementDecl(LIBXML2_2.4.30) [libXML2]
xmlAddEncodingAlias(LIBXML2_2.4.30) [libXML2]	xmlAddID(LIBXML2_2.4.30) [libXML2]	xmlAddNextSibling(LIBXML2_2.4.30) [libXML2]
xmlAddNotationDecl(LIBXML2_2.4.30) [libXML2]	xmlAddPrevSibling(LIBXML2_2.4.30) [libXML2]	xmlAddRef(LIBXML2_2.4.30) [libXML2]
xmlAddSibling(LIBXML2_2.4.30) [libXML2]	xmlAllocOutputBuffer(LIBXML2_2.4.30) [libXML2]	xmlAllocParserInputBuffer(LIBXML2_2.4.30) [libXML2]
xmlAttrSerializeTxtContent(LIBXML2_2.6.6) [libXML2]	xmlAutomataCompile(LIBXML2_2.4.30) [libXML2]	xmlAutomataGetInitState(LIBXML2_2.4.30) [libXML2]
xmlAutomataIsDeterminist(LIBXML2_2.4.30) [libXML2]	xmlAutomataNewAllTrans(LIBXML2_2.4.30) [libXML2]	xmlAutomataNewCountTrans(LIBXML2_2.4.30) [libXML2]

xmlAutomataNewCountTrans2(LIBXML2_2.6.14) [libXML2]	xmlAutomataNewCountedTrans(LIBXML2_2.4.30) [libXML2]	xmlAutomataNewCounter(LIBXML2_2.4.30) [libXML2]
xmlAutomataNewCounterTrans(LIBXML2_2.4.30) [libXML2]	xmlAutomataNewEpsilon(LIBXML2_2.4.30) [libXML2]	xmlAutomataNewNegTrans(LIBXML2_2.6.21) [libXML2]
xmlAutomataNewOnceTrans(LIBXML2_2.4.30) [libXML2]	xmlAutomataNewOnceTrans2(LIBXML2_2.6.14) [libXML2]	xmlAutomataNewState(LIBXML2_2.4.30) [libXML2]
xmlAutomataNewTransition(LIBXML2_2.4.30) [libXML2]	xmlAutomataNewTransition2(LIBXML2_2.5.7) [libXML2]	xmlAutomataSetFinalState(LIBXML2_2.4.30) [libXML2]
xmlBoolToText(LIBXML2_2.4.30) [libXML2]	xmlBufferAdd(LIBXML2_2.4.30) [libXML2]	xmlBufferAddHead(LIBXML2_2.4.30) [libXML2]
xmlBufferCCat(LIBXML2_2.4.30) [libXML2]	xmlBufferCat(LIBXML2_2.4.30) [libXML2]	xmlBufferContent(LIBXML2_2.4.30) [libXML2]
xmlBufferCreate(LIBXML2_2.4.30) [libXML2]	xmlBufferCreateSize(LIBXML2_2.4.30) [libXML2]	xmlBufferCreateStatic(LIBXML2_2.6.0) [libXML2]
xmlBufferDump(LIBXML2_2.4.30) [libXML2]	xmlBufferEmpty(LIBXML2_2.4.30) [libXML2]	xmlBufferFree(LIBXML2_2.4.30) [libXML2]
xmlBufferGrow(LIBXML2_2.4.30) [libXML2]	xmlBufferLength(LIBXML2_2.4.30) [libXML2]	xmlBufferResize(LIBXML2_2.4.30) [libXML2]
xmlBufferSetAllocationScheme(LIBXML2_2.4.30) [libXML2]	xmlBufferShrink(LIBXML2_2.4.30) [libXML2]	xmlBufferWriteCHAR(LIBXML2_2.4.30) [libXML2]
xmlBufferWriteChar(LIBXML2_2.4.30) [libXML2]	xmlBufferWriteQuotedString(LIBXML2_2.4.30) [libXML2]	xmlBuildQName(LIBXML2_2.5.7) [libXML2]
xmlBuildRelativeURI(LIBXML2_2.6.11) [libXML2]	xmlBuildURI(LIBXML2_2.4.30) [libXML2]	xmlByteConsumed(LIBXML2_2.6.6) [libXML2]
xmlC14NDocDumpMemory(LIBXML2_2.4.30) [libXML2]	xmlC14NDocSave(LIBXML2_2.4.30) [libXML2]	xmlC14NDocSaveTo(LIBXML2_2.4.30) [libXML2]
xmlC14NExecute(LIBXML2_2.4.30) [libXML2]	xmlCanonicPath(LIBXML2_2.5.4) [libXML2]	xmlCatalogAdd(LIBXML2_2.4.30) [libXML2]
xmlCatalogAddLocal(LIBXML2_2.4.30) [libXML2]	xmlCatalogCleanup(LIBXML2_2.4.30) [libXML2]	xmlCatalogConvert(LIBXML2_2.4.30) [libXML2]
xmlCatalogDump(LIBXML2_2.4.30) [libXML2]	xmlCatalogFreeLocal(LIBXML2_2.4.30) [libXML2]	xmlCatalogGetDefaults(LIBXML2_2.4.30) [libXML2]

xmlCatalogIsEmpty(LIBXML2_2.4.30) [libXML2]	xmlCatalogLocalResolve(LIBXML2_2.4.30) [libXML2]	xmlCatalogLocalResolveURI(LIBXML2_2.4.30) [libXML2]
xmlCatalogRemove(LIBXML2_2.4.30) [libXML2]	xmlCatalogResolve(LIBXML2_2.4.30) [libXML2]	xmlCatalogResolvePublic(LIBXML2_2.4.30) [libXML2]
xmlCatalogResolveSystem(LIBXML2_2.4.30) [libXML2]	xmlCatalogResolveURI(LIBXML2_2.4.30) [libXML2]	xmlCatalogSetDebug(LIBXML2_2.4.30) [libXML2]
xmlCatalogSetDefaultPrefer(LIBXML2_2.4.30) [libXML2]	xmlCatalogSetDefaults(LIBXML2_2.4.30) [libXML2]	xmlCharEncCloseFunc(LIBXML2_2.4.30) [libXML2]
xmlCharEncFirstLine(LIBXML2_2.4.30) [libXML2]	xmlCharEncInFunc(LIBXML2_2.4.30) [libXML2]	xmlCharEncOutFunc(LIBXML2_2.4.30) [libXML2]
xmlCharStrdup(LIBXML2_2.4.30) [libXML2]	xmlCharStrndup(LIBXML2_2.4.30) [libXML2]	xmlCheckFilename(LIBXML2_2.4.30) [libXML2]
xmlCheckHTTPInput(LIBXML2_2.6.0) [libXML2]	xmlCheckUTF8(LIBXML2_2.4.30) [libXML2]	xmlCheckVersion(LIBXML2_2.4.30) [libXML2]
xmlCleanupCharEncodingHandlers(LIBXML2_2.4.30) [libXML2]	xmlCleanupEncodingAliases(LIBXML2_2.4.30) [libXML2]	xmlCleanupGlobals(LIBXML2_2.5.8) [libXML2]
xmlCleanupInputCallbacks(LIBXML2_2.4.30) [libXML2]	xmlCleanupMemory(LIBXML2_2.6.5) [libXML2]	xmlCleanupOutputCallbacks(LIBXML2_2.4.30) [libXML2]
xmlCleanupParser(LIBXML2_2.4.30) [libXML2]	xmlCleanupThreads(LIBXML2_2.4.30) [libXML2]	xmlClearNodeInfoSeq(LIBXML2_2.4.30) [libXML2]
xmlClearParserCtxt(LIBXML2_2.4.30) [libXML2]	xmlConvertSGMLCatalog(LIBXML2_2.4.30) [libXML2]	xmlCopyAttributeTable(LIBXML2_2.4.30) [libXML2]
xmlCopyChar(LIBXML2_2.4.30) [libXML2]	xmlCopyCharMultiByte(LIBXML2_2.4.30) [libXML2]	xmlCopyDoc(LIBXML2_2.4.30) [libXML2]
xmlCopyDocElementContent(LIBXML2_2.6.18) [libXML2]	xmlCopyDtd(LIBXML2_2.4.30) [libXML2]	xmlCopyElementTable(LIBXML2_2.4.30) [libXML2]
xmlCopyEntitiesTable(LIBXML2_2.4.30) [libXML2]	xmlCopyEnumeration(LIBXML2_2.4.30) [libXML2]	xmlCopyError(LIBXML2_2.6.0) [libXML2]
xmlCopyNamespace(LIBXML2_2.4.30) [libXML2]	xmlCopyNamespaceList(LIBXML2_2.4.30) [libXML2]	xmlCopyNode(LIBXML2_2.4.30) [libXML2]

xmlCopyNodeList(LIBXML2_2.4.30) [libXML2]	xmlCopyNotationTable(LIBXML2_2.4.30) [libXML2]	xmlCopyProp(LIBXML2_2.4.30) [libXML2]
xmlCopyPropList(LIBXML2_2.4.30) [libXML2]	xmlCreateDocParserCtxt(LIBXML2_2.4.30) [libXML2]	xmlCreateEntityParserCtxt(LIBXML2_2.4.30) [libXML2]
xmlCreateEnumeration(LIBXML2_2.4.30) [libXML2]	xmlCreateFileParserCtxt(LIBXML2_2.4.30) [libXML2]	xmlCreateIOParserCtxt(LIBXML2_2.4.30) [libXML2]
xmlCreateIntSubset(LIBXML2_2.4.30) [libXML2]	xmlCreateMemoryParserCtxt(LIBXML2_2.4.30) [libXML2]	xmlCreatePushParserCtxt(LIBXML2_2.4.30) [libXML2]
xmlCreateURI(LIBXML2_2.4.30) [libXML2]	xmlCreateURLParserCtxt(LIBXML2_2.6.2) [libXML2]	xmlCtxtGetLastError(LIBXML2_2.6.0) [libXML2]
xmlCtxtReadDoc(LIBXML2_2.6.0) [libXML2]	xmlCtxtReadFd(LIBXML2_2.6.0) [libXML2]	xmlCtxtReadFile(LIBXML2_2.6.0) [libXML2]
xmlCtxtReadIO(LIBXML2_2.6.0) [libXML2]	xmlCtxtReadMemory(LIBXML2_2.6.0) [libXML2]	xmlCtxtReset(LIBXML2_2.6.0) [libXML2]
xmlCtxtResetLastError(LIBXML2_2.6.0) [libXML2]	xmlCtxtResetPush(LIBXML2_2.6.1) [libXML2]	xmlCtxtUseOptions(LIBXML2_2.6.0) [libXML2]
xmlCurrentChar(LIBXML2_2.4.30) [libXML2]	xmlDOMWrapFreeCtxt(LIBXML2_2.6.20) [libXML2]	xmlDOMWrapNewCtxt(LIBXML2_2.6.20) [libXML2]
xmlDebugCheckDocument(LIBXML2_2.6.15) [libXML2]	xmlDebugDumpAttr(LIBXML2_2.4.30) [libXML2]	xmlDebugDumpAttrList(LIBXML2_2.4.30) [libXML2]
xmlDebugDumpDTD(LIBXML2_2.4.30) [libXML2]	xmlDebugDumpDocument(LIBXML2_2.4.30) [libXML2]	xmlDebugDumpDocumentHead(LIBXML2_2.4.30) [libXML2]
xmlDebugDumpEntities(LIBXML2_2.4.30) [libXML2]	xmlDebugDumpNode(LIBXML2_2.4.30) [libXML2]	xmlDebugDumpNodeList(LIBXML2_2.4.30) [libXML2]
xmlDebugDumpOneNode(LIBXML2_2.4.30) [libXML2]	xmlDebugDumpString(LIBXML2_2.4.30) [libXML2]	xmlDefaultSAXHandlerInit(LIBXML2_2.4.30) [libXML2]
xmlDelEncodingAlias(LIBXML2_2.4.30) [libXML2]	xmlDeregisterNodeDefault(LIBXML2_2.5.0) [libXML2]	xmlDetectCharEncoding(LIBXML2_2.4.30) [libXML2]
xmlDictCleanup(LIBXML2_2.6.18) [libXML2]	xmlDictCreate(LIBXML2_2.6.0) [libXML2]	xmlDictCreateSub(LIBXML2_2.6.5) [libXML2]
xmlDictExists(LIBXML2_2.6.17) [libXML2]	xmlDictFree(LIBXML2_2.6.0) [libXML2]	xmlDictLookup(LIBXML2_2.6.0) [libXML2]

xmlDictOwns(LIBXML2_2.6.0) [libXML2]	xmlDictQLookup(LIBXML2_2.6.0) [libXML2]	xmlDictReference(LIBXML2_2.6.0) [libXML2]
xmlDictSize(LIBXML2_2.6.0) [libXML2]	xmlDocCopyNode(LIBXML2_2.4.30) [libXML2]	xmlDocCopyNodeList(LIBXML2_2.6.15) [libXML2]
xmlDocDump(LIBXML2_2.4.30) [libXML2]	xmlDocDumpFormatMemory(LIBXML2_2.4.30) [libXML2]	xmlDocDumpFormatMemoryEnc(LIBXML2_2.4.30) [libXML2]
xmlDocDumpMemory(LIBXML2_2.4.30) [libXML2]	xmlDocDumpMemoryEnc(LIBXML2_2.4.30) [libXML2]	xmlDocFormatDump(LIBXML2_2.4.30) [libXML2]
xmlDocGetRootElement(LIBXML2_2.4.30) [libXML2]	xmlDocSetRootElement(LIBXML2_2.4.30) [libXML2]	xmlDumpAttributeDecl(LIBXML2_2.4.30) [libXML2]
xmlDumpAttributeTable(LIBXML2_2.4.30) [libXML2]	xmlDumpElementDecl(LIBXML2_2.4.30) [libXML2]	xmlDumpElementTable(LIBXML2_2.4.30) [libXML2]
xmlDumpEntitiesTable(LIBXML2_2.4.30) [libXML2]	xmlDumpEntityDecl(LIBXML2_2.4.30) [libXML2]	xmlDumpNotationDecl(LIBXML2_2.4.30) [libXML2]
xmlDumpNotationTable(LIBXML2_2.4.30) [libXML2]	xmlElemDump(LIBXML2_2.4.30) [libXML2]	xmlEncodeEntitiesReentrant(LIBXML2_2.4.30) [libXML2]
xmlEncodeSpecialChars(LIBXML2_2.4.30) [libXML2]	xmlExpCtxtNbCons(LIBXML2_2.6.21) [libXML2]	xmlExpCtxtNbNodes(LIBXML2_2.6.21) [libXML2]
xmlExpDump(LIBXML2_2.6.21) [libXML2]	xmlExpExpDerive(LIBXML2_2.6.21) [libXML2]	xmlExpFree(LIBXML2_2.6.21) [libXML2]
xmlExpFreeCtxt(LIBXML2_2.6.21) [libXML2]	xmlExpGetLanguage(LIBXML2_2.6.21) [libXML2]	xmlExpGetStart(LIBXML2_2.6.21) [libXML2]
xmlExpIsNillable(LIBXML2_2.6.21) [libXML2]	xmlExpMaxToken(LIBXML2_2.6.21) [libXML2]	xmlExpNewAtom(LIBXML2_2.6.21) [libXML2]
xmlExpNewCtxt(LIBXML2_2.6.21) [libXML2]	xmlExpNewOr(LIBXML2_2.6.21) [libXML2]	xmlExpNewRange(LIBXML2_2.6.21) [libXML2]
xmlExpNewSeq(LIBXML2_2.6.21) [libXML2]	xmlExpParse(LIBXML2_2.6.21) [libXML2]	xmlExpRef(LIBXML2_2.6.21) [libXML2]
xmlExpStringDerive(LIBXML2_2.6.21) [libXML2]	xmlExpSubsume(LIBXML2_2.6.21) [libXML2]	xmlFileClose(LIBXML2_2.4.30) [libXML2]
xmlFileMatch(LIBXML2_2.4.30) [libXML2]	xmlFileOpen(LIBXML2_2.4.30) [libXML2]	xmlFileRead(LIBXML2_2.4.30) [libXML2]

xmlFindCharEncodingHandler(LIBXML2_2.4.30) [libXML2]	xmlFreeAttributeTable(LIBXML2_2.4.30) [libXML2]	xmlFreeAutomata(LIBXML2_2.4.30) [libXML2]
xmlFreeCatalog(LIBXML2_2.4.30) [libXML2]	xmlFreeDoc(LIBXML2_2.4.30) [libXML2]	xmlFreeDocElementContent(LIBXML2_2.6.18) [libXML2]
xmlFreeDtd(LIBXML2_2.4.30) [libXML2]	xmlFreeElementTable(LIBXML2_2.4.30) [libXML2]	xmlFreeEntitiesTable(LIBXML2_2.4.30) [libXML2]
xmlFreeEnumeration(LIBXML2_2.4.30) [libXML2]	xmlFreeIDTable(LIBXML2_2.4.30) [libXML2]	xmlFreeInputStream(LIBXML2_2.4.30) [libXML2]
xmlFreeMutex(LIBXML2_2.4.30) [libXML2]	xmlFreeNode(LIBXML2_2.4.30) [libXML2]	xmlFreeNodeList(LIBXML2_2.4.30) [libXML2]
xmlFreeNotationTable(LIBXML2_2.4.30) [libXML2]	xmlFreeNs(LIBXML2_2.4.30) [libXML2]	xmlFreeNsList(LIBXML2_2.4.30) [libXML2]
xmlFreeParserCtxt(LIBXML2_2.4.30) [libXML2]	xmlFreeParserInputBuffer(LIBXML2_2.4.30) [libXML2]	xmlFreePattern(LIBXML2_2.6.3) [libXML2]
xmlFreePatternList(LIBXML2_2.6.3) [libXML2]	xmlFreeProp(LIBXML2_2.4.30) [libXML2]	xmlFreePropList(LIBXML2_2.4.30) [libXML2]
xmlFreeRMutex(LIBXML2_2.4.30) [libXML2]	xmlFreeRefTable(LIBXML2_2.4.30) [libXML2]	xmlFreeStreamCtxt(LIBXML2_2.6.18) [libXML2]
xmlFreeTextReader(LIBXML2_2.4.30) [libXML2]	xmlFreeTextWriter(LIBXML2_2.6.0) [libXML2]	xmlFreeURI(LIBXML2_2.4.30) [libXML2]
xmlFreeValidCtxt(LIBXML2_2.5.8) [libXML2]	xmlGcMemGet(LIBXML2_2.5.7) [libXML2]	xmlGcMemSetup(LIBXML2_2.5.7) [libXML2]
xmlGetBufferAllocationScheme(LIBXML2_2.4.30) [libXML2]	xmlGetCharEncodingHandler(LIBXML2_2.4.30) [libXML2]	xmlGetCharEncodingName(LIBXML2_2.4.30) [libXML2]
xmlGetCompressMode(LIBXML2_2.4.30) [libXML2]	xmlGetDocCompressMode(LIBXML2_2.4.30) [libXML2]	xmlGetDocEntity(LIBXML2_2.4.30) [libXML2]
xmlGetDtdAttrDesc(LIBXML2_2.4.30) [libXML2]	xmlGetDtdElementDesc(LIBXML2_2.4.30) [libXML2]	xmlGetDtdEntity(LIBXML2_2.4.30) [libXML2]
xmlGetDtdNotationDesc(LIBXML2_2.4.30) [libXML2]	xmlGetDtdQAttrDesc(LIBXML2_2.4.30) [libXML2]	xmlGetDtdQElementDesc(LIBXML2_2.4.30) [libXML2]
xmlGetEncodingAlias(LIBXML2_2.4.30) [libXML2]	xmlGetExternalEntityLoader(LIBXML2_2.4.30) [libXML2]	xmlGetGlobalState(LIBXML2_2.4.30) [libXML2]

xmlGetID(LIBXML2_2.4.30) [libXML2]	xmlGetIntSubset(LIBXML2_2.4.30) [libXML2]	xmlGetLastChild(LIBXML2_2.4.30) [libXML2]
xmlGetLastError(LIBXML2_2.6.0) [libXML2]	xmlGetLineNo(LIBXML2_2.4.30) [libXML2]	xmlGetNoNsProp(LIBXML2_2.5.2) [libXML2]
xmlGetNodePath(LIBXML2_2.4.30) [libXML2]	xmlGetNsList(LIBXML2_2.4.30) [libXML2]	xmlGetNsProp(LIBXML2_2.4.30) [libXML2]
xmlGetParameterEntity(LIBXML2_2.4.30) [libXML2]	xmlGetPredefinedEntity(LIBXML2_2.4.30) [libXML2]	xmlGetProp(LIBXML2_2.4.30) [libXML2]
xmlGetRefs(LIBXML2_2.4.30) [libXML2]	xmlGetThreadId(LIBXML2_2.4.30) [libXML2]	xmlGetUTF8Char(LIBXML2_2.4.30) [libXML2]
xmlHasFeature(LIBXML2_2.6.21) [libXML2]	xmlHasNsProp(LIBXML2_2.4.30) [libXML2]	xmlHasProp(LIBXML2_2.4.30) [libXML2]
xmlHashAddEntry(LIBXML2_2.4.30) [libXML2]	xmlHashAddEntry2(LIBXML2_2.4.30) [libXML2]	xmlHashAddEntry3(LIBXML2_2.4.30) [libXML2]
xmlHashCopy(LIBXML2_2.4.30) [libXML2]	xmlHashCreate(LIBXML2_2.4.30) [libXML2]	xmlHashCreateDict(LIBXML2_2.6.18) [libXML2]
xmlHashFree(LIBXML2_2.4.30) [libXML2]	xmlHashLookup(LIBXML2_2.4.30) [libXML2]	xmlHashLookup2(LIBXML2_2.4.30) [libXML2]
xmlHashLookup3(LIBXML2_2.4.30) [libXML2]	xmlHashQLookup(LIBXML2_2.6.0) [libXML2]	xmlHashQLookup2(LIBXML2_2.6.0) [libXML2]
xmlHashQLookup3(LIBXML2_2.6.0) [libXML2]	xmlHashRemoveEntry(LIBXML2_2.4.30) [libXML2]	xmlHashRemoveEntry2(LIBXML2_2.4.30) [libXML2]
xmlHashRemoveEntry3(LIBXML2_2.4.30) [libXML2]	xmlHashScan(LIBXML2_2.4.30) [libXML2]	xmlHashScan3(LIBXML2_2.4.30) [libXML2]
xmlHashScanFull(LIBXML2_2.4.30) [libXML2]	xmlHashScanFull3(LIBXML2_2.4.30) [libXML2]	xmlHashSize(LIBXML2_2.4.30) [libXML2]
xmlHashUpdateEntry(LIBXML2_2.4.30) [libXML2]	xmlHashUpdateEntry2(LIBXML2_2.4.30) [libXML2]	xmlHashUpdateEntry3(LIBXML2_2.4.30) [libXML2]
xmlIOFTPClose(LIBXML2_2.4.30) [libXML2]	xmlIOFTPMatch(LIBXML2_2.4.30) [libXML2]	xmlIOFTPOpen(LIBXML2_2.4.30) [libXML2]
xmlIOFTPRead(LIBXML2_2.4.30) [libXML2]	xmlIOHTTPClose(LIBXML2_2.4.30) [libXML2]	xmlIOHTTPMatch(LIBXML2_2.4.30) [libXML2]
xmlIOHTTPOpen(LIBXML2_2.4.30) [libXML2]	xmlIOHTTPOpenW(LIBXML2_2.4.30) [libXML2]	xmlIOHTTPRead(LIBXML2_2.4.30) [libXML2]

xmlIOParseDTD(LIBXML2_2.4.30) [libXML2]	xmlInitCharEncodingHandlers(LIBXML2_2.4.30) [libXML2]	xmlInitGlobals(LIBXML2_2.5.8) [libXML2]
xmlInitMemory(LIBXML2_2.4.30) [libXML2]	xmlInitNodeInfoSeq(LIBXML2_2.4.30) [libXML2]	xmlInitParser(LIBXML2_2.4.30) [libXML2]
xmlInitParserCtxt(LIBXML2_2.4.30) [libXML2]	xmlInitThreads(LIBXML2_2.4.30) [libXML2]	xmlInitializeCatalog(LIBXML2_2.4.30) [libXML2]
xmlInitializeGlobalState(LIBXML2_2.4.30) [libXML2]	xmlIsBlankNode(LIBXML2_2.4.30) [libXML2]	xmlIsID(LIBXML2_2.4.30) [libXML2]
xmlIsLetter(LIBXML2_2.4.30) [libXML2]	xmlIsMainThread(LIBXML2_2.4.30) [libXML2]	xmlIsMixedElement(LIBXML2_2.4.30) [libXML2]
xmlIsRef(LIBXML2_2.4.30) [libXML2]	xmlIsXHTML(LIBXML2_2.4.30) [libXML2]	xmlKeepBlanksDefault(LIBXML2_2.4.30) [libXML2]
xmlLineNumbersDefault(LIBXML2_2.4.30) [libXML2]	xmlLinkGetData(LIBXML2_2.4.30) [libXML2]	xmlListAppend(LIBXML2_2.4.30) [libXML2]
xmlListClear(LIBXML2_2.4.30) [libXML2]	xmlListCopy(LIBXML2_2.4.30) [libXML2]	xmlListCreate(LIBXML2_2.4.30) [libXML2]
xmlListDelete(LIBXML2_2.4.30) [libXML2]	xmlListDup(LIBXML2_2.4.30) [libXML2]	xmlListEmpty(LIBXML2_2.4.30) [libXML2]
xmlListEnd(LIBXML2_2.4.30) [libXML2]	xmlListFront(LIBXML2_2.4.30) [libXML2]	xmlListInsert(LIBXML2_2.4.30) [libXML2]
xmlListMerge(LIBXML2_2.4.30) [libXML2]	xmlListPopBack(LIBXML2_2.4.30) [libXML2]	xmlListPopFront(LIBXML2_2.4.30) [libXML2]
xmlListPushBack(LIBXML2_2.4.30) [libXML2]	xmlListPushFront(LIBXML2_2.4.30) [libXML2]	xmlListRemoveAll(LIBXML2_2.4.30) [libXML2]
xmlListRemoveFirst(LIBXML2_2.4.30) [libXML2]	xmlListRemoveLast(LIBXML2_2.4.30) [libXML2]	xmlListReverse(LIBXML2_2.4.30) [libXML2]
xmlListReverseSearch(LIBXML2_2.4.30) [libXML2]	xmlListReverseWalk(LIBXML2_2.4.30) [libXML2]	xmlListSearch(LIBXML2_2.4.30) [libXML2]
xmlListSize(LIBXML2_2.4.30) [libXML2]	xmlListSort(LIBXML2_2.4.30) [libXML2]	xmlListWalk(LIBXML2_2.4.30) [libXML2]
xmlLoadACatalog(LIBXML2_2.4.30) [libXML2]	xmlLoadCatalog(LIBXML2_2.4.30) [libXML2]	xmlLoadCatalogs(LIBXML2_2.4.30) [libXML2]
xmlLoadExternalEntity(LIBXML2_2.4.30) [libXML2]	xmlLoadSGMLSuperCatalog(LIBXML2_2.4.30) [libXML2]	xmlLockLibrary(LIBXML2_2.4.30) [libXML2]

xmlLsCountNode(LIBXML2_2.4.30) [libXML2]	xmlLsOneNode(LIBXML2_2.4.30) [libXML2]	xmlMallocAtomicLoc(LIBXML2_2.5.9) [libXML2]
xmlMallocLoc(LIBXML2_2.4.30) [libXML2]	xmlMemBlocks(LIBXML2_2.6.16) [libXML2]	xmlMemDisplay(LIBXML2_2.4.30) [libXML2]
xmlMemFree(LIBXML2_2.4.30) [libXML2]	xmlMemGet(LIBXML2_2.4.30) [libXML2]	xmlMemMalloc(LIBXML2_2.4.30) [libXML2]
xmlMemRealloc(LIBXML2_2.4.30) [libXML2]	xmlMemSetup(LIBXML2_2.4.30) [libXML2]	xmlMemShow(LIBXML2_2.4.30) [libXML2]
xmlMemStrdupLoc(LIBXML2_2.4.30) [libXML2]	xmlMemUsed(LIBXML2_2.4.30) [libXML2]	xmlMemoryDump(LIBXML2_2.4.30) [libXML2]
xmlMemoryStrdup(LIBXML2_2.4.30) [libXML2]	xmlModuleClose(LIBXML2_2.6.17) [libXML2]	xmlModuleFree(LIBXML2_2.6.17) [libXML2]
xmlModuleOpen(LIBXML2_2.6.17) [libXML2]	xmlModuleSymbol(LIBXML2_2.6.17) [libXML2]	xmlMutexLock(LIBXML2_2.4.30) [libXML2]
xmlMutexUnlock(LIBXML2_2.4.30) [libXML2]	xmlNewAutomata(LIBXML2_2.4.30) [libXML2]	xmlNewCDATABlock(LIBXML2_2.4.30) [libXML2]
xmlNewCatalog(LIBXML2_2.4.30) [libXML2]	xmlNewCharEncodingHandler(LIBXML2_2.4.30) [libXML2]	xmlNewCharRef(LIBXML2_2.4.30) [libXML2]
xmlNewChild(LIBXML2_2.4.30) [libXML2]	xmlNewComment(LIBXML2_2.4.30) [libXML2]	xmlNewDoc(LIBXML2_2.4.30) [libXML2]
xmlNewDocComment(LIBXML2_2.4.30) [libXML2]	xmlNewDocElementContent(LIBXML2_2.6.18) [libXML2]	xmlNewDocFragment(LIBXML2_2.4.30) [libXML2]
xmlNewDocNode(LIBXML2_2.4.30) [libXML2]	xmlNewDocNodeEatName(LIBXML2_2.4.30) [libXML2]	xmlNewDocPI(LIBXML2_2.6.15) [libXML2]
xmlNewDocProp(LIBXML2_2.4.30) [libXML2]	xmlNewDocRawNode(LIBXML2_2.4.30) [libXML2]	xmlNewDocText(LIBXML2_2.4.30) [libXML2]
xmlNewDocTextLen(LIBXML2_2.4.30) [libXML2]	xmlNewDtd(LIBXML2_2.4.30) [libXML2]	xmlNewEntityInputStream(LIBXML2_2.4.30) [libXML2]
xmlNewIOInputStream(LIBXML2_2.4.30) [libXML2]	xmlNewInputFromFile(LIBXML2_2.4.30) [libXML2]	xmlNewInputStream(LIBXML2_2.4.30) [libXML2]
xmlNewMutex(LIBXML2_2.4.30) [libXML2]	xmlNewNode(LIBXML2_2.4.30) [libXML2]	xmlNewNodeEatName(LIBXML2_2.4.30) [libXML2]

xmlNewNs(LIBXML2_2.4.30) [libXML2]	xmlNewNsProp(LIBXML2_2.4.30) [libXML2]	xmlNewNsPropEatName(LIBXML2_2.4.30) [libXML2]
xmlNewPI(LIBXML2_2.4.30) [libXML2]	xmlNewParserCtxt(LIBXML2_2.4.30) [libXML2]	xmlNewProp(LIBXML2_2.4.30) [libXML2]
xmlNewRMutex(LIBXML2_2.4.30) [libXML2]	xmlNewReference(LIBXML2_2.4.30) [libXML2]	xmlNewStringInputStream(LIBXML2_2.4.30) [libXML2]
xmlNewText(LIBXML2_2.4.30) [libXML2]	xmlNewTextChild(LIBXML2_2.4.30) [libXML2]	xmlNewTextLen(LIBXML2_2.4.30) [libXML2]
xmlNewTextReader(LIBXML2_2.4.30) [libXML2]	xmlNewTextReaderFilename(LIBXML2_2.4.30) [libXML2]	xmlNewTextWriter(LIBXML2_2.6.0) [libXML2]
xmlNewTextWriterDoc(LIBXML2_2.6.3) [libXML2]	xmlNewTextWriterFilename(LIBXML2_2.6.0) [libXML2]	xmlNewTextWriterMemory(LIBXML2_2.6.0) [libXML2]
xmlNewTextWriterPushParser(LIBXML2_2.6.3) [libXML2]	xmlNewTextWriterTree(LIBXML2_2.6.3) [libXML2]	xmlNewValidCtxt(LIBXML2_2.5.8) [libXML2]
xmlNextChar(LIBXML2_2.4.30) [libXML2]	xmlNoNetExternalEntityLoader(LIBXML2_2.4.30) [libXML2]	xmlNodeAddContent(LIBXML2_2.4.30) [libXML2]
xmlNodeAddContentLen(LIBXML2_2.4.30) [libXML2]	xmlNodeBufGetContent(LIBXML2_2.6.0) [libXML2]	xmlNodeDump(LIBXML2_2.4.30) [libXML2]
xmlNodeDumpOutput(LIBXML2_2.4.30) [libXML2]	xmlNodeGetBase(LIBXML2_2.4.30) [libXML2]	xmlNodeGetContent(LIBXML2_2.4.30) [libXML2]
xmlNodeGetLang(LIBXML2_2.4.30) [libXML2]	xmlNodeGetSpacePreserve(LIBXML2_2.4.30) [libXML2]	xmlNodeIsText(LIBXML2_2.4.30) [libXML2]
xmlNodeListGetRawString(LIBXML2_2.4.30) [libXML2]	xmlNodeListGetString(LIBXML2_2.4.30) [libXML2]	xmlNodeSetBase(LIBXML2_2.4.30) [libXML2]
xmlNodeSetContent(LIBXML2_2.4.30) [libXML2]	xmlNodeSetContentLen(LIBXML2_2.4.30) [libXML2]	xmlNodeSetLang(LIBXML2_2.4.30) [libXML2]
xmlNodeSetName(LIBXML2_2.4.30) [libXML2]	xmlNodeSetSpacePreserve(LIBXML2_2.4.30) [libXML2]	xmlNormalizeURIPath(LIBXML2_2.4.30) [libXML2]
xmlNormalizeWindowsPath(LIBXML2_2.4.30) [libXML2]	xmlOutputBufferClose(LIBXML2_2.4.30) [libXML2]	xmlOutputBufferCreateFd(LIBXML2_2.4.30) [libXML2]

xmlOutputBufferCreateFile(LIBXML2_2.4.30) [libXML2]	xmlOutputBufferCreateFilename(LIBXML2_2.4.30) [libXML2]	xmlOutputBufferCreateFilenameDefault(LIBXML2_2.6.11) [libXML2]
xmlOutputBufferCreateIO(LIBXML2_2.4.30) [libXML2]	xmlOutputBufferFlush(LIBXML2_2.4.30) [libXML2]	xmlOutputBufferWrite(LIBXML2_2.4.30) [libXML2]
xmlOutputBufferWriteEscape(LIBXML2_2.6.10) [libXML2]	xmlOutputBufferWriteString(LIBXML2_2.4.30) [libXML2]	xmlParseAttValue(LIBXML2_2.4.30) [libXML2]
xmlParseAttribute(LIBXML2_2.4.30) [libXML2]	xmlParseAttributeListDecl(LIBXML2_2.4.30) [libXML2]	xmlParseAttributeType(LIBXML2_2.4.30) [libXML2]
xmlParseBalancedChunkMemory(LIBXML2_2.4.30) [libXML2]	xmlParseBalancedChunkMemoryRecover(LIBXML2_2.4.30) [libXML2]	xmlParseCDSect(LIBXML2_2.4.30) [libXML2]
xmlParseCatalogFile(LIBXML2_2.4.30) [libXML2]	xmlParseCharData(LIBXML2_2.4.30) [libXML2]	xmlParseCharEncoding(LIBXML2_2.4.30) [libXML2]
xmlParseCharRef(LIBXML2_2.4.30) [libXML2]	xmlParseChunk(LIBXML2_2.4.30) [libXML2]	xmlParseComment(LIBXML2_2.4.30) [libXML2]
xmlParseContent(LIBXML2_2.4.30) [libXML2]	xmlParseCtxtExternalEntity(LIBXML2_2.4.30) [libXML2]	xmlParseDTD(LIBXML2_2.4.30) [libXML2]
xmlParseDefaultDecl(LIBXML2_2.4.30) [libXML2]	xmlParseDoc(LIBXML2_2.4.30) [libXML2]	xmlParseDocTypeDecl(LIBXML2_2.4.30) [libXML2]
xmlParseDocument(LIBXML2_2.4.30) [libXML2]	xmlParseElement(LIBXML2_2.4.30) [libXML2]	xmlParseElementChildrenContentDecl(LIBXML2_2.4.30) [libXML2]
xmlParseElementContentDecl(LIBXML2_2.4.30) [libXML2]	xmlParseElementDecl(LIBXML2_2.4.30) [libXML2]	xmlParseElementMixedContentDecl(LIBXML2_2.4.30) [libXML2]
xmlParseEncName(LIBXML2_2.4.30) [libXML2]	xmlParseEncodingDecl(LIBXML2_2.4.30) [libXML2]	xmlParseEndTag(LIBXML2_2.4.30) [libXML2]
xmlParseEntity(LIBXML2_2.4.30) [libXML2]	xmlParseEntityDecl(LIBXML2_2.4.30) [libXML2]	xmlParseEntityRef(LIBXML2_2.4.30) [libXML2]
xmlParseEntityValue(LIBXML2_2.4.30) [libXML2]	xmlParseEnumeratedType(LIBXML2_2.4.30) [libXML2]	xmlParseEnumerationType(LIBXML2_2.4.30) [libXML2]
xmlParseExtParsedEnt(LIBXML2_2.4.30) [libXML2]	xmlParseExternalEntity(LIBXML2_2.4.30) [libXML2]	xmlParseExternalID(LIBXML2_2.4.30) [libXML2]

xmlParseExternalSubset(LIBXML2_2.4.30) [libXML2]	xmlParseFile(LIBXML2_2.4.30) [libXML2]	xmlParseInNodeContext(LIBXML2_2.6.12) [libXML2]
xmlParseMarkupDecl(LIBXML2_2.4.30) [libXML2]	xmlParseMemory(LIBXML2_2.4.30) [libXML2]	xmlParseMisc(LIBXML2_2.4.30) [libXML2]
xmlParseName(LIBXML2_2.4.30) [libXML2]	xmlParseNmtoken(LIBXML2_2.4.30) [libXML2]	xmlParseNotationDecl(LIBXML2_2.4.30) [libXML2]
xmlParseNotationType(LIBXML2_2.4.30) [libXML2]	xmlParsePEReference(LIBXML2_2.4.30) [libXML2]	xmlParsePI(LIBXML2_2.4.30) [libXML2]
xmlParsePITarget(LIBXML2_2.4.30) [libXML2]	xmlParsePubidLiteral(LIBXML2_2.4.30) [libXML2]	xmlParseReference(LIBXML2_2.4.30) [libXML2]
xmlParseSDDDecl(LIBXML2_2.4.30) [libXML2]	xmlParseStartTag(LIBXML2_2.4.30) [libXML2]	xmlParseSystemLiteral(LIBXML2_2.4.30) [libXML2]
xmlParseTextDecl(LIBXML2_2.4.30) [libXML2]	xmlParseURI(LIBXML2_2.4.30) [libXML2]	xmlParseURIRaw(LIBXML2_2.6.21) [libXML2]
xmlParseURIReference(LIBXML2_2.4.30) [libXML2]	xmlParseVersionInfo(LIBXML2_2.4.30) [libXML2]	xmlParseVersionNum(LIBXML2_2.4.30) [libXML2]
xmlParseXMLDecl(LIBXML2_2.4.30) [libXML2]	xmlParserAddNodeInfo(LIBXML2_2.4.30) [libXML2]	xmlParserError(LIBXML2_2.4.30) [libXML2]
xmlParserFindNodeInfo(LIBXML2_2.4.30) [libXML2]	xmlParserFindNodeInfoIndex(LIBXML2_2.4.30) [libXML2]	xmlParserGetDirectory(LIBXML2_2.4.30) [libXML2]
xmlParserHandlePEReference(LIBXML2_2.4.30) [libXML2]	xmlParserInputBufferCreateFd(LIBXML2_2.4.30) [libXML2]	xmlParserInputBufferCreateFile(LIBXML2_2.4.30) [libXML2]
xmlParserInputBufferCreateFilename(LIBXML2_2.4.30) [libXML2]	xmlParserInputBufferCreateFilenameDefault(LIBXML2_2.6.11) [libXML2]	xmlParserInputBufferCreateIO(LIBXML2_2.4.30) [libXML2]
xmlParserInputBufferCreateMem(LIBXML2_2.4.30) [libXML2]	xmlParserInputBufferCreateStatic(LIBXML2_2.6.0) [libXML2]	xmlParserInputBufferGrow(LIBXML2_2.4.30) [libXML2]
xmlParserInputBufferPush(LIBXML2_2.4.30) [libXML2]	xmlParserInputBufferRead(LIBXML2_2.4.30) [libXML2]	xmlParserInputGrow(LIBXML2_2.4.30) [libXML2]
xmlParserInputRead(LIBXML2_2.4.30) [libXML2]	xmlParserInputShrink(LIBXML2_2.4.30) [libXML2]	xmlParserPrintFileContent(LIBXML2_2.4.30) [libXML2]

xmlParserPrintFileInfo(LIBXML2_2.4.30) [libXML2]	xmlParserValidityError(LIBXML2_2.4.30) [libXML2]	xmlParserValidityWarning(LIBXML2_2.4.30) [libXML2]
xmlParserWarning(LIBXML2_2.4.30) [libXML2]	xmlPatternFromRoot(LIBXML2_2.6.18) [libXML2]	xmlPatternGetStreamContext(LIBXML2_2.6.18) [libXML2]
xmlPatternMatch(LIBXML2_2.6.3) [libXML2]	xmlPatternMaxDepth(LIBXML2_2.6.18) [libXML2]	xmlPatternMinDepth(LIBXML2_2.6.21) [libXML2]
xmlPatternStreamable(LIBXML2_2.6.18) [libXML2]	xmlPatternCompile(LIBXML2_2.6.3) [libXML2]	xmlPedanticParserDefault(LIBXML2_2.4.30) [libXML2]
xmlPopInput(LIBXML2_2.4.30) [libXML2]	xmlPopInputCallbacks(LIBXML2_2.6.10) [libXML2]	xmlPrintURI(LIBXML2_2.4.30) [libXML2]
xmlPushInput(LIBXML2_2.4.30) [libXML2]	xmlRMutexLock(LIBXML2_2.4.30) [libXML2]	xmlRMutexUnlock(LIBXML2_2.4.30) [libXML2]
xmlReadDoc(LIBXML2_2.6.0) [libXML2]	xmlReadFd(LIBXML2_2.6.0) [libXML2]	xmlReadFile(LIBXML2_2.6.0) [libXML2]
xmlReadIO(LIBXML2_2.6.0) [libXML2]	xmlReadMemory(LIBXML2_2.6.0) [libXML2]	xmlReaderForDoc(LIBXML2_2.6.0) [libXML2]
xmlReaderForFd(LIBXML2_2.6.0) [libXML2]	xmlReaderForFile(LIBXML2_2.6.0) [libXML2]	xmlReaderForIO(LIBXML2_2.6.0) [libXML2]
xmlReaderForMemory(LIBXML2_2.6.0) [libXML2]	xmlReaderNewDoc(LIBXML2_2.6.0) [libXML2]	xmlReaderNewFd(LIBXML2_2.6.0) [libXML2]
xmlReaderNewFile(LIBXML2_2.6.0) [libXML2]	xmlReaderNewIO(LIBXML2_2.6.0) [libXML2]	xmlReaderNewMemory(LIBXML2_2.6.0) [libXML2]
xmlReaderNewWalker(LIBXML2_2.6.0) [libXML2]	xmlReaderWalker(LIBXML2_2.6.0) [libXML2]	xmlReallocLoc(LIBXML2_2.4.30) [libXML2]
xmlReconciliateNs(LIBXML2_2.4.30) [libXML2]	xmlRecoverDoc(LIBXML2_2.4.30) [libXML2]	xmlRecoverFile(LIBXML2_2.4.30) [libXML2]
xmlRecoverMemory(LIBXML2_2.4.30) [libXML2]	xmlRegExecErrInfo(LIBXML2_2.6.17) [libXML2]	xmlRegExecNextValues(LIBXML2_2.6.17) [libXML2]
xmlRegExecPushString(LIBXML2_2.4.30) [libXML2]	xmlRegExecPushString2(LIBXML2_2.5.7) [libXML2]	xmlRegFreeExecCtxt(LIBXML2_2.4.30) [libXML2]
xmlRegFreeRegexp(LIBXML2_2.4.30) [libXML2]	xmlRegNewExecCtxt(LIBXML2_2.4.30) [libXML2]	xmlRegexpCompile(LIBXML2_2.4.30) [libXML2]

xmlRegexpExec(LIBXML2_2.4.30) [libXML2]	xmlRegexpIsDeterministic(LIBXML2_2.4.30) [libXML2]	xmlRegexpPrint(LIBXML2_2.4.30) [libXML2]
xmlRegisterCharEncodingHandler(LIBXML2_2.4.30) [libXML2]	xmlRegisterDefaultInputCallbacks(LIBXML2_2.4.30) [libXML2]	xmlRegisterDefaultOutputCallbacks(LIBXML2_2.4.30) [libXML2]
xmlRegisterHTTPPostCallbacks(LIBXML2_2.4.30) [libXML2]	xmlRegisterInputCallbacks(LIBXML2_2.4.30) [libXML2]	xmlRegisterNodeDefault(LIBXML2_2.5.0) [libXML2]
xmlRegisterOutputCallbacks(LIBXML2_2.4.30) [libXML2]	xmlRelaxNGCleanupTypes(LIBXML2_2.5.2) [libXML2]	xmlRelaxNGDump(LIBXML2_2.5.2) [libXML2]
xmlRelaxNGDumpTree(LIBXML2_2.5.4) [libXML2]	xmlRelaxNGFree(LIBXML2_2.5.2) [libXML2]	xmlRelaxNGFreeParserCtxt(LIBXML2_2.5.2) [libXML2]
xmlRelaxNGFreeValidCtxt(LIBXML2_2.5.2) [libXML2]	xmlRelaxNGGetParserErrors(LIBXML2_2.5.9) [libXML2]	xmlRelaxNGGetValidErrors(LIBXML2_2.5.9) [libXML2]
xmlRelaxNGInitTypes(LIBXML2_2.6.16) [libXML2]	xmlRelaxNGNewDocParserCtxt(LIBXML2_2.5.7) [libXML2]	xmlRelaxNGNewMemParserCtxt(LIBXML2_2.5.2) [libXML2]
xmlRelaxNGNewParserCtxt(LIBXML2_2.5.2) [libXML2]	xmlRelaxNGNewValidCtxt(LIBXML2_2.5.2) [libXML2]	xmlRelaxNGParse(LIBXML2_2.5.2) [libXML2]
xmlRelaxNGSetParserErrors(LIBXML2_2.5.2) [libXML2]	xmlRelaxNGSetValidErrors(LIBXML2_2.5.2) [libXML2]	xmlRelaxNGSetValidStructuredErrors(LIBXML2_2.6.21) [libXML2]
xmlRelaxNGValidateDoc(LIBXML2_2.5.2) [libXML2]	xmlRelaxNGValidateFullElement(LIBXML2_2.5.7) [libXML2]	xmlRelaxNGValidatePopElement(LIBXML2_2.5.7) [libXML2]
xmlRelaxNGValidatePushCData(LIBXML2_2.5.7) [libXML2]	xmlRelaxNGValidatePushElement(LIBXML2_2.5.7) [libXML2]	xmlRelaxParserSetFlag(LIBXML2_2.6.5) [libXML2]
xmlRemoveID(LIBXML2_2.4.30) [libXML2]	xmlRemoveProp(LIBXML2_2.4.30) [libXML2]	xmlRemoveRef(LIBXML2_2.4.30) [libXML2]
xmlReplaceNode(LIBXML2_2.4.30) [libXML2]	xmlResetError(LIBXML2_2.6.0) [libXML2]	xmlResetLastError(LIBXML2_2.6.0) [libXML2]
xmlSAX2AttributeDecl(LIBXML2_2.6.0) [libXML2]	xmlSAX2CDataBlock(LIBXML2_2.6.0) [libXML2]	xmlSAX2Characters(LIBXML2_2.6.0) [libXML2]
xmlSAX2Comment(LIBXML2_2.6.0) [libXML2]	xmlSAX2ElementDecl(LIBXML2_2.6.0) [libXML2]	xmlSAX2EndDocument(LIBXML2_2.6.0) [libXML2]

xmlSAX2EndElement(LIBXML2_2.6.0) [libXML2]	xmlSAX2EndElementNs(LIBXML2_2.6.0) [libXML2]	xmlSAX2EntityDecl(LIBXML2_2.6.0) [libXML2]
xmlSAX2ExternalSubset(LIBXML2_2.6.0) [libXML2]	xmlSAX2GetColumnNumber(LIBXML2_2.6.0) [libXML2]	xmlSAX2GetEntity(LIBXML2_2.6.0) [libXML2]
xmlSAX2GetLineNumber(LIBXML2_2.6.0) [libXML2]	xmlSAX2GetParameterEntity(LIBXML2_2.6.0) [libXML2]	xmlSAX2GetPublicId(LIBXML2_2.6.0) [libXML2]
xmlSAX2GetSystemId(LIBXML2_2.6.0) [libXML2]	xmlSAX2HasExternalSubset(LIBXML2_2.6.0) [libXML2]	xmlSAX2HasInternalSubset(LIBXML2_2.6.0) [libXML2]
xmlSAX2IgnorableWhitespace(LIBXML2_2.6.0) [libXML2]	xmlSAX2InitDefaultSAXHandler(LIBXML2_2.6.0) [libXML2]	xmlSAX2InitDocbDefaultSAXHandler(LIBXML2_2.6.0) [libXML2]
xmlSAX2InitHtmlDefaultSAXHandler(LIBXML2_2.6.0) [libXML2]	xmlSAX2InternalSubset(LIBXML2_2.6.0) [libXML2]	xmlSAX2IsStandalone(LIBXML2_2.6.0) [libXML2]
xmlSAX2NotationDecl(LIBXML2_2.6.0) [libXML2]	xmlSAX2ProcessingInstruction(LIBXML2_2.6.0) [libXML2]	xmlSAX2Reference(LIBXML2_2.6.0) [libXML2]
xmlSAX2ResolveEntity(LIBXML2_2.6.0) [libXML2]	xmlSAX2SetDocumentLocator(LIBXML2_2.6.0) [libXML2]	xmlSAX2StartDocument(LIBXML2_2.6.0) [libXML2]
xmlSAX2StartElement(LIBXML2_2.6.0) [libXML2]	xmlSAX2StartElementNs(LIBXML2_2.6.0) [libXML2]	xmlSAX2UnparsedEntityDecl(LIBXML2_2.6.0) [libXML2]
xmlSAXDefaultVersion(LIBXML2_2.6.0) [libXML2]	xmlSAXParseDTD(LIBXML2_2.4.30) [libXML2]	xmlSAXParseDoc(LIBXML2_2.4.30) [libXML2]
xmlSAXParseEntity(LIBXML2_2.4.30) [libXML2]	xmlSAXParseFile(LIBXML2_2.4.30) [libXML2]	xmlSAXParseFileWithData(LIBXML2_2.4.30) [libXML2]
xmlSAXParseMemory(LIBXML2_2.4.30) [libXML2]	xmlSAXParseMemoryWithData(LIBXML2_2.4.30) [libXML2]	xmlSAXUserParseFile(LIBXML2_2.4.30) [libXML2]
xmlSAXUserParseMemory(LIBXML2_2.4.30) [libXML2]	xmlSAXVersion(LIBXML2_2.6.0) [libXML2]	xmlSaveClose(LIBXML2_2.6.8) [libXML2]
xmlSaveDoc(LIBXML2_2.6.8) [libXML2]	xmlSaveFile(LIBXML2_2.4.30) [libXML2]	xmlSaveFileEnc(LIBXML2_2.4.30) [libXML2]
xmlSaveFileTo(LIBXML2_2.4.30) [libXML2]	xmlSaveFlush(LIBXML2_2.6.8) [libXML2]	xmlSaveFormatFile(LIBXML2_2.4.30) [libXML2]

xmlSaveFormatFileEnc(LIBXML2_2.4.30) [libXML2]	xmlSaveFormatFileTo(LIBXML2_2.4.30) [libXML2]	xmlSaveSetAttrEscape(LIBXML2_2.6.10) [libXML2]
xmlSaveSetEscape(LIBXML2_2.6.10) [libXML2]	xmlSaveToFd(LIBXML2_2.6.8) [libXML2]	xmlSaveToFilename(LIBXML2_2.6.8) [libXML2]
xmlSaveToIO(LIBXML2_2.6.8) [libXML2]	xmlSaveTree(LIBXML2_2.6.8) [libXML2]	xmlSaveUri(LIBXML2_2.4.30) [libXML2]
xmlSchemaCleanupTypes(LIBXML2_2.5.8) [libXML2]	xmlSchemaCollapseString(LIBXML2_2.6.11) [libXML2]	xmlSchemaCompareValues(LIBXML2_2.5.8) [libXML2]
xmlSchemaDump(LIBXML2_2.5.8) [libXML2]	xmlSchemaFree(LIBXML2_2.5.8) [libXML2]	xmlSchemaFreeParserCtxt(LIBXML2_2.5.8) [libXML2]
xmlSchemaFreeValidCtxt(LIBXML2_2.5.8) [libXML2]	xmlSchemaFreeValue(LIBXML2_2.5.8) [libXML2]	xmlSchemaGetBuiltInType(LIBXML2_2.6.11) [libXML2]
xmlSchemaGetCanonValue(LIBXML2_2.6.18) [libXML2]	xmlSchemaGetParserErrors(LIBXML2_2.6.12) [libXML2]	xmlSchemaGetValType(LIBXML2_2.6.19) [libXML2]
xmlSchemaGetValidErrors(LIBXML2_2.6.12) [libXML2]	xmlSchemaInitTypes(LIBXML2_2.5.8) [libXML2]	xmlSchemaIsValid(LIBXML2_2.6.20) [libXML2]
xmlSchemaNewDocParserCtxt(LIBXML2_2.6.2) [libXML2]	xmlSchemaNewMemParserCtxt(LIBXML2_2.5.8) [libXML2]	xmlSchemaNewParserCtxt(LIBXML2_2.5.8) [libXML2]
xmlSchemaNewValidCtxt(LIBXML2_2.5.8) [libXML2]	xmlSchemaParse(LIBXML2_2.5.8) [libXML2]	xmlSchemaSAXPlug(LIBXML2_2.6.20) [libXML2]
xmlSchemaSAXUnplug(LIBXML2_2.6.20) [libXML2]	xmlSchemaSetParserErrors(LIBXML2_2.5.8) [libXML2]	xmlSchemaSetValidErrors(LIBXML2_2.5.8) [libXML2]
xmlSchemaSetValidOptions(LIBXML2_2.6.14) [libXML2]	xmlSchemaSetValidStructuredErrors(LIBXML2_2.6.21) [libXML2]	xmlSchemaValPredefTypeNode(LIBXML2_2.5.8) [libXML2]
xmlSchemaValidCtxtGetOptions(LIBXML2_2.6.14) [libXML2]	xmlSchemaValidateDoc(LIBXML2_2.5.8) [libXML2]	xmlSchemaValidateFile(LIBXML2_2.6.20) [libXML2]
xmlSchemaValidateOneElement(LIBXML2_2.6.14) [libXML2]	xmlSchemaValidateStream(LIBXML2_2.5.8) [libXML2]	xmlSchematronFree(LIBXML2_2.6.21) [libXML2]
xmlSchematronFreeParserCtxt(LIBXML2_2.6.21) [libXML2]	xmlSchematronFreeValidCtxt(LIBXML2_2.6.21) [libXML2]	xmlSchematronNewDocParserCtxt(LIBXML2_2.6.21) [libXML2]

xmlSchematronNewMemParserCtxt(LIBXML2_2.6.21) [libXML2]	xmlSchematronNewParserCtxt(LIBXML2_2.6.21) [libXML2]	xmlSchematronNewValidCtxt(LIBXML2_2.6.21) [libXML2]
xmlSchematronParse(LIBXML2_2.6.21) [libXML2]	xmlSchematronValidateDoc(LIBXML2_2.6.21) [libXML2]	xmlSearchNs(LIBXML2_2.4.30) [libXML2]
xmlSearchNsByHref(LIBXML2_2.4.30) [libXML2]	xmlSetBufferAllocationScheme(LIBXML2_2.4.30) [libXML2]	xmlSetCompressMode(LIBXML2_2.4.30) [libXML2]
xmlSetDocCompressMode(LIBXML2_2.4.30) [libXML2]	xmlSetEntityReferenceFunc(LIBXML2_2.4.30) [libXML2]	xmlSetExternalEntityLoader(LIBXML2_2.4.30) [libXML2]
xmlSetGenericErrorFunc(LIBXML2_2.4.30) [libXML2]	xmlSetListDoc(LIBXML2_2.4.30) [libXML2]	xmlSetNs(LIBXML2_2.4.30) [libXML2]
xmlSetNsProp(LIBXML2_2.4.30) [libXML2]	xmlSetProp(LIBXML2_2.4.30) [libXML2]	xmlSetStructuredErrorFunc(LIBXML2_2.6.0) [libXML2]
xmlSetTreeDoc(LIBXML2_2.4.30) [libXML2]	xmlSetupParserForBuffer(LIBXML2_2.4.30) [libXML2]	xmlShell(LIBXML2_2.4.30) [libXML2]
xmlShellBase(LIBXML2_2.4.30) [libXML2]	xmlShellCat(LIBXML2_2.4.30) [libXML2]	xmlShellDir(LIBXML2_2.4.30) [libXML2]
xmlShellDu(LIBXML2_2.4.30) [libXML2]	xmlShellList(LIBXML2_2.4.30) [libXML2]	xmlShellLoad(LIBXML2_2.4.30) [libXML2]
xmlShellPrintNode(LIBXML2_2.4.30) [libXML2]	xmlShellPrintXPathError(LIBXML2_2.4.30) [libXML2]	xmlShellPrintXPathResult(LIBXML2_2.4.30) [libXML2]
xmlShellPwd(LIBXML2_2.4.30) [libXML2]	xmlShellSave(LIBXML2_2.4.30) [libXML2]	xmlShellValidate(LIBXML2_2.4.30) [libXML2]
xmlShellWrite(LIBXML2_2.4.30) [libXML2]	xmlSkipBlankChars(LIBXML2_2.4.30) [libXML2]	xmlSnprintfElementContent(LIBXML2_2.4.30) [libXML2]
xmlSplitQName(LIBXML2_2.4.30) [libXML2]	xmlSplitQName2(LIBXML2_2.4.30) [libXML2]	xmlSplitQName3(LIBXML2_2.5.9) [libXML2]
xmlStopParser(LIBXML2_2.4.30) [libXML2]	xmlStrEqual(LIBXML2_2.4.30) [libXML2]	xmlStrPrintf(LIBXML2_2.6.0) [libXML2]
xmlStrQEqual(LIBXML2_2.6.0) [libXML2]	xmlStrVPrintf(LIBXML2_2.6.2) [libXML2]	xmlStrcasecmp(LIBXML2_2.4.30) [libXML2]
xmlStrcasestr(LIBXML2_2.4.30) [libXML2]	xmlStrcat(LIBXML2_2.4.30) [libXML2]	xmlStrchr(LIBXML2_2.4.30) [libXML2]
xmlStrcmp(LIBXML2_2.4.30) [libXML2]	xmlStrdup(LIBXML2_2.4.30) [libXML2]	xmlStreamPop(LIBXML2_2.6.18) [libXML2]

xmlStreamPush(LIBXML2_2.6.18) [libXML2]	xmlStreamPushAttr(LIBXML2_2.6.18) [libXML2]	xmlStringCurrentChar(LIBXML2_2.4.30) [libXML2]
xmlStringDecodeEntities(LIBXML2_2.4.30) [libXML2]	xmlStringGetNodeList(LIBXML2_2.4.30) [libXML2]	xmlStringLenDecodeEntities(LIBXML2_2.6.0) [libXML2]
xmlStringLenGetNodeList(LIBXML2_2.4.30) [libXML2]	xmlStrlen(LIBXML2_2.4.30) [libXML2]	xmlStrncasecmp(LIBXML2_2.4.30) [libXML2]
xmlStrncat(LIBXML2_2.4.30) [libXML2]	xmlStrncatNew(LIBXML2_2.6.5) [libXML2]	xmlStrncmp(LIBXML2_2.4.30) [libXML2]
xmlStrndup(LIBXML2_2.4.30) [libXML2]	xmlStrstr(LIBXML2_2.4.30) [libXML2]	xmlStrsub(LIBXML2_2.4.30) [libXML2]
xmlSubstituteEntitiesDefault(LIBXML2_2.4.30) [libXML2]	xmlSwitchEncoding(LIBXML2_2.4.30) [libXML2]	xmlSwitchInputEncoding(LIBXML2_2.6.0) [libXML2]
xmlSwitchToEncoding(LIBXML2_2.4.30) [libXML2]	xmlTextConcat(LIBXML2_2.4.30) [libXML2]	xmlTextMerge(LIBXML2_2.4.30) [libXML2]
xmlTextReaderAttributeCount(LIBXML2_2.4.30) [libXML2]	xmlTextReaderBaseUri(LIBXML2_2.4.30) [libXML2]	xmlTextReaderByteConsumed(LIBXML2_2.6.18) [libXML2]
xmlTextReaderClose(LIBXML2_2.5.0) [libXML2]	xmlTextReaderConstBaseUri(LIBXML2_2.6.0) [libXML2]	xmlTextReaderConstEncoding(LIBXML2_2.6.15) [libXML2]
xmlTextReaderConstLocalName(LIBXML2_2.6.0) [libXML2]	xmlTextReaderConstName(LIBXML2_2.6.0) [libXML2]	xmlTextReaderConstNamespaceUri(LIBXML2_2.6.0) [libXML2]
xmlTextReaderConstPrefix(LIBXML2_2.6.0) [libXML2]	xmlTextReaderConstString(LIBXML2_2.6.0) [libXML2]	xmlTextReaderConstValue(LIBXML2_2.6.0) [libXML2]
xmlTextReaderConstXmlLang(LIBXML2_2.6.0) [libXML2]	xmlTextReaderConstXmlVersion(LIBXML2_2.6.15) [libXML2]	xmlTextReaderCurrentDoc(LIBXML2_2.5.0) [libXML2]
xmlTextReaderCurrentNode(LIBXML2_2.5.0) [libXML2]	xmlTextReaderDepth(LIBXML2_2.4.30) [libXML2]	xmlTextReaderExpand(LIBXML2_2.5.7) [libXML2]
xmlTextReaderGetAttribute(LIBXML2_2.5.0) [libXML2]	xmlTextReaderGetAttributeNo(LIBXML2_2.5.0) [libXML2]	xmlTextReaderGetAttributeNs(LIBXML2_2.5.0) [libXML2]
xmlTextReaderGetErrorHandler(LIBXML2_2.5.2) [libXML2]	xmlTextReaderGetParseColumnNumber(LIBXML2_2.6.17) [libXML2]	xmlTextReaderGetParseLineNumber(LIBXML2_2.6.17) [libXML2]

xmlTextReaderGetParse rProp(LIBXML2_2.5.0) [libXML2]	xmlTextReaderGetRem ainder(LIBXML2_2.5.0) [libXML2]	xmlTextReaderHasAttri butes(LIBXML2_2.4.30) [libXML2]
xmlTextReaderHasValu e(LIBXML2_2.4.30) [libXML2]	xmlTextReaderIsDefaul t(LIBXML2_2.4.30) [libXML2]	xmlTextReaderIsEmpty Element(LIBXML2_2.4. 30) [libXML2]
xmlTextReaderIsNames paceDecl(LIBXML2_2.6. 15) [libXML2]	xmlTextReaderIsValid(LIBXML2_2.5.7) [libXML2]	xmlTextReaderLocalNa me(LIBXML2_2.4.30) [libXML2]
xmlTextReaderLocatorB aseURI(LIBXML2_2.5.2) [libXML2]	xmlTextReaderLocatorL ineNumber(LIBXML2_2 _5.2) [libXML2]	xmlTextReaderLookup Namespace(LIBXML2_ 2.5.0) [libXML2]
xmlTextReaderMoveTo Attribute(LIBXML2_2.5. 0) [libXML2]	xmlTextReaderMoveTo AttributeNo(LIBXML2_ 2.5.0) [libXML2]	xmlTextReaderMoveTo AttributeNs(LIBXML2_ 2.5.0) [libXML2]
xmlTextReaderMoveTo Element(LIBXML2_2.5. 0) [libXML2]	xmlTextReaderMoveTo FirstAttribute(LIBXML2 _2.5.0) [libXML2]	xmlTextReaderMoveTo NextAttribute(LIBXML 2_2.5.0) [libXML2]
xmlTextReaderName(LI BXML2_2.4.30) [libXML2]	xmlTextReaderNamesp aceUri(LIBXML2_2.4.30) [libXML2]	xmlTextReaderNext(LI BXML2_2.5.7) [libXML2]
xmlTextReaderNextSibl ing(LIBXML2_2.6.0) [libXML2]	xmlTextReaderNodeTy pe(LIBXML2_2.4.30) [libXML2]	xmlTextReaderNormali zation(LIBXML2_2.5.0) [libXML2]
xmlTextReaderPrefix(LI BXML2_2.4.30) [libXML2]	xmlTextReaderPreserve (LIBXML2_2.6.0) [libXML2]	xmlTextReaderPreserve Pattern(LIBXML2_2.6.3) [libXML2]
xmlTextReaderQuoteC har(LIBXML2_2.4.30) [libXML2]	xmlTextReaderRead(LI BXML2_2.4.30) [libXML2]	xmlTextReaderReadAtt ributeValue(LIBXML2_ 2.5.0) [libXML2]
xmlTextReaderReadInn erXml(LIBXML2_2.5.0) [libXML2]	xmlTextReaderReadOut erXml(LIBXML2_2.5.0) [libXML2]	xmlTextReaderReadStat e(LIBXML2_2.5.0) [libXML2]
xmlTextReaderReadStri ng(LIBXML2_2.5.0) [libXML2]	xmlTextReaderRelaxN GSetSchema(LIBXML2_ 2.5.7) [libXML2]	xmlTextReaderRelaxN GValidate(LIBXML2_2. 5.7) [libXML2]
xmlTextReaderSchema Validate(LIBXML2_2.6. 20) [libXML2]	xmlTextReaderSetError Handler(LIBXML2_2.5. 2) [libXML2]	xmlTextReaderSetParse rProp(LIBXML2_2.5.0) [libXML2]
xmlTextReaderSetSche ma(LIBXML2_2.6.20) [libXML2]	xmlTextReaderSetStruct uredErrorHandler(LIBX ML2_2.6.6) [libXML2]	xmlTextReaderStandalo ne(LIBXML2_2.6.15) [libXML2]
xmlTextReaderValue(LI BXML2_2.4.30) [libXML2]	xmlTextReaderXmlLan g(LIBXML2_2.4.30) [libXML2]	xmlTextWriterEndAttri bute(LIBXML2_2.6.0) [libXML2]

xmlTextWriterEndCDATA(LIBXML2_2.6.0) [libXML2]	xmlTextWriterEndComment(LIBXML2_2.6.7) [libXML2]	xmlTextWriterEndDTD(LIBXML2_2.6.0) [libXML2]
xmlTextWriterEndDTDAttlist(LIBXML2_2.6.8) [libXML2]	xmlTextWriterEndDTDElement(LIBXML2_2.6.8) [libXML2]	xmlTextWriterEndDTDEntity(LIBXML2_2.6.8) [libXML2]
xmlTextWriterEndDocument(LIBXML2_2.6.0) [libXML2]	xmlTextWriterEndElement(LIBXML2_2.6.0) [libXML2]	xmlTextWriterEndPI(LIBXML2_2.6.0) [libXML2]
xmlTextWriterFlush(LIBXML2_2.6.0) [libXML2]	xmlTextWriterFullEndElement(LIBXML2_2.6.0) [libXML2]	xmlTextWriterSetIndent(LIBXML2_2.6.5) [libXML2]
xmlTextWriterSetIndentString(LIBXML2_2.6.5) [libXML2]	xmlTextWriterStartAttribute(LIBXML2_2.6.0) [libXML2]	xmlTextWriterStartAttributeNS(LIBXML2_2.6.0) [libXML2]
xmlTextWriterStartCDATA(LIBXML2_2.6.0) [libXML2]	xmlTextWriterStartComment(LIBXML2_2.6.7) [libXML2]	xmlTextWriterStartDTD(LIBXML2_2.6.0) [libXML2]
xmlTextWriterStartDTDAAttlist(LIBXML2_2.6.0) [libXML2]	xmlTextWriterStartDTDElement(LIBXML2_2.6.0) [libXML2]	xmlTextWriterStartDTDEntity(LIBXML2_2.6.0) [libXML2]
xmlTextWriterStartDocument(LIBXML2_2.6.0) [libXML2]	xmlTextWriterStartElement(LIBXML2_2.6.0) [libXML2]	xmlTextWriterStartElementNS(LIBXML2_2.6.0) [libXML2]
xmlTextWriterStartPI(LIBXML2_2.6.0) [libXML2]	xmlTextWriterWriteAttribute(LIBXML2_2.6.0) [libXML2]	xmlTextWriterWriteAttributeNS(LIBXML2_2.6.0) [libXML2]
xmlTextWriterWriteBase64(LIBXML2_2.6.0) [libXML2]	xmlTextWriterWriteBinHex(LIBXML2_2.6.0) [libXML2]	xmlTextWriterWriteCDATA(LIBXML2_2.6.0) [libXML2]
xmlTextWriterWriteComment(LIBXML2_2.6.0) [libXML2]	xmlTextWriterWriteDTD(LIBXML2_2.6.0) [libXML2]	xmlTextWriterWriteDTDAAttlist(LIBXML2_2.6.0) [libXML2]
xmlTextWriterWriteDTDElement(LIBXML2_2.6.0) [libXML2]	xmlTextWriterWriteDTDEntity(LIBXML2_2.6.0) [libXML2]	xmlTextWriterWriteDTDEntity(LIBXML2_2.6.0) [libXML2]
xmlTextWriterWriteDTDEntityContent(LIBXML2_2.6.8) [libXML2]	xmlTextWriterWriteDTDInternalEntity(LIBXML2_2.6.0) [libXML2]	xmlTextWriterWriteDTDDNotation(LIBXML2_2.6.0) [libXML2]
xmlTextWriterWriteElement(LIBXML2_2.6.0) [libXML2]	xmlTextWriterWriteElementNS(LIBXML2_2.6.0) [libXML2]	xmlTextWriterWriteFormatAttribute(LIBXML2_2.6.0) [libXML2]
xmlTextWriterWriteFormatAttributeNS(LIBXML2_2.6.0) [libXML2]	xmlTextWriterWriteFormatCDATA(LIBXML2_2.6.0) [libXML2]	xmlTextWriterWriteFormatComment(LIBXML2_2.6.0) [libXML2]

xmlTextWriterWriteFor matDTD(LIBXML2_2.6. 0) [libXML2]	xmlTextWriterWriteFor matDTDAttlist(LIBXM L2_2.6.0) [libXML2]	xmlTextWriterWriteFor matDTDElement(LIBX ML2_2.6.0) [libXML2]
xmlTextWriterWriteFor matDTDInternalEntity(LIBXML2_2.6.0) [libXML2]	xmlTextWriterWriteFor matElement(LIBXML2_ 2.6.0) [libXML2]	xmlTextWriterWriteFor matElementNS(LIBXM L2_2.6.0) [libXML2]
xmlTextWriterWriteFor matPI(LIBXML2_2.6.0) [libXML2]	xmlTextWriterWriteFor matRaw(LIBXML2_2.6. 0) [libXML2]	xmlTextWriterWriteFor matString(LIBXML2_2. 6.0) [libXML2]
xmlTextWriterWritePI(LIBXML2_2.6.0) [libXML2]	xmlTextWriterWriteRa w(LIBXML2_2.6.0) [libXML2]	xmlTextWriterWriteRa wLen(LIBXML2_2.6.0) [libXML2]
xmlTextWriterWriteStri ng(LIBXML2_2.6.0) [libXML2]	xmlTextWriterWriteVF ormatAttribute(LIBXM L2_2.6.0) [libXML2]	xmlTextWriterWriteVF ormatAttributeNS(LIBX ML2_2.6.0) [libXML2]
xmlTextWriterWriteVF ormatCDATA(LIBXML 2_2.6.0) [libXML2]	xmlTextWriterWriteVF ormatComment(LIBXM L2_2.6.0) [libXML2]	xmlTextWriterWriteVF ormatDTD(LIBXML2_2. 6.0) [libXML2]
xmlTextWriterWriteVF ormatDTDAttlist(LIBX ML2_2.6.0) [libXML2]	xmlTextWriterWriteVF ormatDTDElement(LIB XML2_2.6.0) [libXML2]	xmlTextWriterWriteVF ormatDTDInternalEntit y(LIBXML2_2.6.0) [libXML2]
xmlTextWriterWriteVF ormatElement(LIBXML 2_2.6.0) [libXML2]	xmlTextWriterWriteVF ormatElementNS(LIBX ML2_2.6.0) [libXML2]	xmlTextWriterWriteVF ormatPI(LIBXML2_2.6.0) [libXML2]
xmlTextWriterWriteVF ormatRaw(LIBXML2_2. 6.0) [libXML2]	xmlTextWriterWriteVF ormatString(LIBXML2_ 2.6.0) [libXML2]	xmlThrDefBufferAllocS cheme(LIBXML2_2.5.8) [libXML2]
xmlThrDefDefaultBuffe rSize(LIBXML2_2.5.8) [libXML2]	xmlThrDefDeregisterN odeDefault(LIBXML2_2 .5.8) [libXML2]	xmlThrDefDoValidityC heckingDefaultValue(LI BXML2_2.5.8) [libXML2]
xmlThrDefGetWarning sDefaultValue(LIBXML 2_2.5.8) [libXML2]	xmlThrDefIndentTreeO utput(LIBXML2_2.5.8) [libXML2]	xmlThrDefKeepBlanks DefaultValue(LIBXML2 _2.5.8) [libXML2]
xmlThrDefLineNumber sDefaultValue(LIBXML 2_2.5.8) [libXML2]	xmlThrDefLoadExtDtd DefaultValue(LIBXML2 _2.5.8) [libXML2]	xmlThrDefOutputBuffe rCreateFilenameDefault (LIBXML2_2.6.11) [libXML2]
xmlThrDefParserDebug Entities(LIBXML2_2.5.8) [libXML2]	xmlThrDefParserInputB ufferCreateFilenameDef ault(LIBXML2_2.6.11) [libXML2]	xmlThrDefPedanticPars erDefaultValue(LIBXM L2_2.5.8) [libXML2]

xmlThrDefRegisterNodeDefault(LIBXML2_2.5.8) [libXML2]	xmlThrDefSaveNoEmptyTags(LIBXML2_2.5.8) [libXML2]	xmlThrDefSetGenericErrorFunc(LIBXML2_2.5.8) [libXML2]
xmlThrDefSetStructuredErrorFunc(LIBXML2_2.6.0) [libXML2]	xmlThrDefSubstituteEntitiesDefaultValue(LIBXML2_2.5.8) [libXML2]	xmlThrDefTreeIndentString(LIBXML2_2.5.8) [libXML2]
xmlURIEscape(LIBXML2_2.4.30) [libXML2]	xmlURIEscapeStr(LIBXML2_2.4.30) [libXML2]	xmlURIUnescapeString(LIBXML2_2.4.30) [libXML2]
xmlUTF8Charcmp(LIBXML2_2.5.9) [libXML2]	xmlUTF8Size(LIBXML2_2.5.9) [libXML2]	xmlUTF8Strlen(LIBXML2_2.4.30) [libXML2]
xmlUTF8Strloc(LIBXML2_2.4.30) [libXML2]	xmlUTF8Strndup(LIBXML2_2.4.30) [libXML2]	xmlUTF8Strpos(LIBXML2_2.4.30) [libXML2]
xmlUTF8Strsize(LIBXML2_2.4.30) [libXML2]	xmlUTF8Strsub(LIBXML2_2.4.30) [libXML2]	xmlUnlinkNode(LIBXML2_2.4.30) [libXML2]
xmlUnlockLibrary(LIBXML2_2.4.30) [libXML2]	xmlUnsetNsProp(LIBXML2_2.4.30) [libXML2]	xmlUnsetProp(LIBXML2_2.4.30) [libXML2]
xmlValidBuildContentModel(LIBXML2_2.4.30) [libXML2]	xmlValidCtxtNormalizeAttributeValue(LIBXML2_2.4.30) [libXML2]	xmlValidGetPotentialChildren(LIBXML2_2.4.30) [libXML2]
xmlValidGetValidElements(LIBXML2_2.4.30) [libXML2]	xmlValidNormalizeAttributeValue(LIBXML2_2.4.30) [libXML2]	xmlValidateAttributeDecl(LIBXML2_2.4.30) [libXML2]
xmlValidateAttributeValue(LIBXML2_2.4.30) [libXML2]	xmlValidateDocument(LIBXML2_2.4.30) [libXML2]	xmlValidateDocumentFinal(LIBXML2_2.4.30) [libXML2]
xmlValidateDtd(LIBXML2_2.4.30) [libXML2]	xmlValidateDtdFinal(LIBXML2_2.4.30) [libXML2]	xmlValidateElement(LIBXML2_2.4.30) [libXML2]
xmlValidateElementDecl(LIBXML2_2.4.30) [libXML2]	xmlValidateNCName(LIBXML2_2.5.4) [libXML2]	xmlValidateNMTOKEN(LIBXML2_2.5.4) [libXML2]
xmlValidateName(LIBXML2_2.5.4) [libXML2]	xmlValidateNameValue(LIBXML2_2.4.30) [libXML2]	xmlValidateNamesValue(LIBXML2_2.4.30) [libXML2]
xmlValidateNmtokenValue(LIBXML2_2.4.30) [libXML2]	xmlValidateNmtokensValue(LIBXML2_2.4.30) [libXML2]	xmlValidateNotationDecl(LIBXML2_2.4.30) [libXML2]
xmlValidateNotationUse(LIBXML2_2.4.30) [libXML2]	xmlValidateOneAttribute(LIBXML2_2.4.30) [libXML2]	xmlValidateOneElement(LIBXML2_2.4.30) [libXML2]
xmlValidateOneNamespace(LIBXML2_2.4.30) [libXML2]	xmlValidatePopElement(LIBXML2_2.5.0) [libXML2]	xmlValidatePushCData(LIBXML2_2.5.0) [libXML2]