INTERNATIONAL STANDARD

ISO/IEC 8802-3

ANSI/IEEE Std 802.3

Third edition
1992-03-20

Information technology — Local and metropolitan area networks —

Part 3:
Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications

Technologies de l'information — Réseaux locaux et urbains

Partie 3: Accès multiple par surveillance du signal et détection de collision et spécifications pour la couche physique

Reference number
ISO/IEC 8802-3 : 1992 (E)
ANSI/IEEE
Std 802.3, 1992 Edition

Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

The Institute of Electrical and Electronics Engineers, Inc.
345 East 47th Street, New York, NY 10017-2394, USA

ISBN 1-55937-204-4

Copyright © 1992 by
The Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 1992
Printed in the United States of America

*No part of this publication may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.*

March 20, 1992 *SH15123*

Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

International Standard ISO/IEC 8802-3 : 1992
ANSI/IEEE Std 802.3, 1992 Edition

(This edition contains ANSI/IEEE Std 802.3-1988,
ANSI/IEEE Std 802.3c-1985, ANSI/IEEE Std 802.3d-1987,
ANSI/IEEE Std 802.3b-1985 and ANSI/IEEE Std 802.3e-1987)

Information technology—
Local and metropolitan area networks—

Part 3:
Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications

Sponsor

**Technical Committee on Computer Communications
of the
IEEE Computer Society**

Abstract: This Local and Metropolitan Area Network standard, ISO/IEC 8802-3 : 1992 [ANSI/IEEE Std 802.3, 1992], specifies the media access control characteristics for the Carrier Sense Multiple Access with Collision Detection (CSMA/CD) access method. It also specifies the media, Medium Attachment Unit (MAU) and physical layer repeater unit for 10 Mb/s baseband and broadband systems and provides a 1 Mb/s baseband implementation. Specifications for MAU types 10BASE5, 10BASE2, FOIRL (fiber optic inter-repeater link), 10BROAD36, and 1BASE5 are included. Layer and sublayer interface specifications are aligned to the ISO Open Systems Interconnection Basic Reference Model and 8802 models. The 8802-3 internal model is defined and used.
Keywords: data processing, information interchange, local area networks, mode of data transmission, network interconnection, models.



**Adopted as an International Standard by the
International Organization for Standardization
and by the
International Electrotechnical Commission**



**Published by
The Institute of Electrical and Electronics Engineers, Inc.**



Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

International Standard ISO/IEC 8802-3 : 1992

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

In 1985, IEEE Standard 802.3-1985 was adopted by ISO Technical Committee 97, *Information processing systems,* as draft International Standard ISO/DIS 8802-3. Following the procedures described above, the Standard was subsequently approved by ISO and published as ISO 8802-3 : 1989, incorporating ISO 8802-3/DAD 1 which had resulted from the adoption by ISO in 1987 of ANSI/IEEE Std 802.3a.

A further revision was subsequently approved by ISO/IEC JTC 1 in 1990, incorporating ISO/IEC 8802-3/Amendments 2 and 5.

This third edition cancels and replaces ISO/IEC 8802-3 : 1990 and incorporates Amendment 3 : *Broadband medium attachment unit and broadband medium specifications, Type 10BROAD36,* which was approved in 1990, and Amendment 4: *Physical signaling, medium attachment, and baseband medium specifications, Type 1BASE5,* approved in 1991.

For the purpose of assigning global addresses, the Institute of Electrical and Electronics Engineers, Inc., USA, has been designated by the ISO Council as the Registration Authority. Communications on this subject should be addressed to

Registration Authority for ISO/IEC 8802-3
c/o The Institute of Electrical and Electronics Engineers, Inc.
445 Hoes Lane
PO Box 1331
Piscataway, NJ 08855-1331
USA

During the preparation of this International Standard, information was gathered on patents upon which application of the standard might depend. Relevant patents were identified as belonging to Xerox Corporation. However, ISO and IEC cannot give authoritative or comprehensive information about evidence, validity or scope of patent and like rights. The patent-holder has stated that licences will be granted under reasonable terms and conditions and communications on this subject should be addressed to

Xerox Corporation
PO Box 1600
Stamford, CT 06904
USA




International Organization for Standardization/International Electrotechnical Commission
Case postale 56 • CH-1211 Genève 20 • Switzerland

Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

Foreword to International Standard ISO/IEC 8802-3 : 1992

This standard is part of a family of standards for Local and Metropolitan Area Networks. The relationship between this standard and the other members of the family is shown below. (The numbers in the figure refer to ISO standard numbers.)



This family of standards deals with the physical and data link layers as defined by the ISO Open Systems Interconnection Basic Reference Model (ISO 7498 : 1984). The access standards define four types of medium access technologies and associated physical media, each appropriate for particular applications or system objectives. Other types are under investigation.

The standards defining these technologies are as follows:

(1) ISO/IEC 8802-3 [ANSI/IEEE Std 802.3, 1992 Edition], a bus utilizing CSMA/CD as the access method,
(2) ISO/IEC 8802-4 [ANSI/IEEE Std 802.4-1990], a bus utilizing token passing as the access method,
(3) ISO/IEC 8802-5 [IEEE Std 802.5-1992],* a ring utilizing token passing as the access method,
(4) ISO 8802-7, a ring utilizing slotted ring as the access method.

ISO 8802-2 [ANSI/IEEE Std 802.2-1989], Logical Link Control protocol, is used in conjunction with the medium access standards.

The reader of this document is urged to become familiar with the complete family of standards.

The main body of this standard serves for both the ISO/IEC 8802-3 : 1992 and ANSI/IEEE Std 802.3, 1992 Edition standards. ISO and IEEE each have unique foreword sections. The Annex applies to the IEEE standard only. The Appendixes serve as useful reference material to both standards.

* Anticipated publication in Spring 1992.

Documents
Document Sharing Hub
Full document details: ISO_IEC 8802-3_1992

IEEE Standards documents are developed within the Technical Committees of the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Board. Members of the committees serve voluntarily and without compensation. They are not necessarily members of the Institute. The standards developed within IEEE represent a consensus of the broad expertise on the subject within the Institute as well as those activities outside of IEEE which have expressed an interest in participating in the development of the standard.

Use of an IEEE Standard is wholly voluntary. The existence of an IEEE Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE Standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard. Every IEEE Standard is subjected to review at least once every five years for revision or reaffirmation. When a document is more than five years old, and has not been reaffirmed, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE Standard.

Comments for revision of IEEE Standards are welcome from any interested party, regardless of membership affiliation with IEEE. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments.

Interpretations: Occasionally questions may arise regarding the meaning of portions of standards as they relate to specific applications. When the need for interpretations is brought to the attention of IEEE, the Institute will initiate action to prepare appropriate responses. Since IEEE Standards represent a consensus of all concerned interests, it is important to ensure that any interpretation has also received the concurrence of a balance of interests. For this reason IEEE and the members of its technical committees are not able to provide an instant response to interpretation requests except in those cases where the matter has previously received formal consideration.

Comments on standards and requests for interpretations should be addressed to:

Secretary, IEEE Standards Board
345 East 47th Street
New York, NY 10017
USA

IEEE Standards documents are adopted by the Institute of Electrical and Electronics Engineers without regard to whether their adoption may involve patents on articles, materials, or processes. Such adoptions does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the standards documents.


AVA Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

Foreword

(This Foreword is not a part of this International Standard or of ANSI/IEEE 802.3, 1992 Edition.)

This standard is part of a family of standards for local and metropolitan area networks. The relationship between the standard and other members of the family is shown below. (The numbers in the figure refer to IEEE standard numbers.)



* Formerly IEEE Std 802.1A.

This family of standards deals with the physical and data link layers as defined by the ISO Open Systems Interconnection Basic Reference Model (ISO 7498 :1984). The access standards define several types of medium access technologies and associated physical media, each appropriate for particular applications or system objectives. Other types are under investigation.

The standards defining these technologies are as follows:

- IEEE Std 802† : Overview and Architecture. This standard provides an overview to the family of IEEE 802 Standards. This document forms part of the 802.1 scope of work.
- IEEE Std 802.1D: MAC Bridging. Specifies an architecture and protocol for the interconnection of IEEE 802 LANs below the MAC service boundary.

† The 802 Architecture and Overview Specification, originally known as IEEE Std 802.1A, has been renumbered as IEEE Std 802. This has been done to accommodate recognition of the base standard in a family of standards. References to IEEE Std 802.1A should be considered as references to IEEE Std 802.

Documents
Document Sharing Hub
Full document details: ISO_IEC 8802-3_1992

• IEEE Std 802.1E:	System Load Protocol. Specifies a set of services and protocol for those aspects of management concerned with the loading of systems on IEEE 802 LANs.
• ISO 8802-2 [ANSI/IEEE Std 802.2]:	Logical Link Control
• ISO/IEC 8802-3 [ANSI/IEEE Std 802.3]:	CSMA/CD Access Method and Physical Layer Specifications
• ISO/IEC 8802-4 [ANSI/IEEE Std 802.4]:	Token Bus Access Method and Physical Layer Specifications
• IEEE Std 802.5:	Token Ring Access Method and Physical Layer Specifications
• IEEE Std 802.6:	Metropolitan Area Network Access Method and Physical Layer Specifications

In addition to the family of standards the following is a recommended practice for a common technology:

• IEEE Std 802.7:	IEEE Recommended Practice for Broadband Local Area Networks

The reader of this document is urged to become familiar with the complete family of standards.

Conformance Test Methodology

A new standards series, identified by the number 1802, has been established to identify the conformance test methodology documents for the 802 family of standards. This makes the correspondence between the various 802 standards and their applicable conformance test requirements readily apparent. Thus the conformance test documents for 802.3 are numbered 1802.3, the conformance test documents for 802.5 will be 1802.5, and so on. Similarly, ISO will use 11802 to number conformance test standards for 8802 standards.

AVA Documents
Document Sharing Hub
Full document details: ISO_IEC 8802-3_1992

This edition of the standard defines 10 Mb/s baseband and broadband implementations and a 1 Mb/s baseband implementation of the Physical Layer using the CSMA/CD access method. It is anticipated that future editions of the standard may provide additional implementations of the physical layer to support different needs (for example, media, and data rates).

This standard contains state-of-the-art material. The area covered by this standard is undergoing evolution. Revisions are anticipated to this standard within the next few years to clarify existing material, to correct possible errors, and to incorporate new related material.

Readers wishing to know the state of revisions should contact

Secretary
IEEE Standards Board
Institute of Electrical and Electronics Engineers, Inc
PO Box 1331, 445 Hoes Lane
Piscataway, NJ 08855-1331
USA

The IEEE 802.3 Working Group acknowledges and appreciates that many concepts embodied in this standard are based largely upon the CSMA/CD access method earlier described in *The Ethernet* specification as written jointly by individuals from Xerox Corporation, Digital Equipment Corporation, and Intel Corporation. Appreciation is also expressed to Robert M. Metcalfe and David R. Boggs for their pioneering work in establishing the original concepts.

Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

When the IEEE 802.3 Working Group approved the original standard (ANSI/IEEE Std 802.3-1985) in 1983, it had the following membership:

Donald C. Loughry, *Chair*

Phil L. Arst
Robert F. Bridge
Charles Brill
G. J. Clancy
John Davidson
Ralph DeMent
Hank (H. N.) Dorris
Judith Estrin
Richard Fabbri
Ingrid Fromm
Milton C. Harper
Bryan Hoover
George D. Jelatis
Harold W. Katz
Donald E. Kotas
William P. Lidinsky
Laurie Lindsey
William D. Livingston
Andy Luque
Daniel Maltbie
Jerry McDowell
C. Kenneth Miller
Robert L. Morrell
Wendell Nakamine
W. P. Neblett
James Nelson
Thomas L. Phinney
David Potter
Robert S. Printis
Gary S. Robinson
Robert Rosenthal
Gary Stephens
Daniel P. Stokesberry
Ken. F. Sumner
Daniel Sze
Victor J. Tarassov
P. E. Wainwright
Lyle Weiman
Hugh E. White
Choa-Ping Wu
Nick Zades
Mo R. Zonoun

Additional individuals who contributed actively in the development of the original standard (ANSI/IEEE Std 802.3-1985) throughout its elaboration were

Juan Bulnes
Ron Crane
Dane Elliot
Alan Flatman
Maris Graube
Guy Harkins
Dean Lindsay
Then. T. Liu
Robert Moles
Tony Lauck
Joseph St. Amand
Richard Seifert
Nathan Tobol
Mark Townsend
Roger Van Brunt
Bo Vicklund
Chris Wargo
Richard Williams
Ron Yara

The ECMA TC24 Committee on Communication Protocols also provided helpful input in the development of this standard.

When the IEEE 802.3 Working Group approved ANSI/IEEE Std 802.3a-1988 (Section 10) in November 1984, it had the following membership:

Donald C. Loughry, *Chair*
Alan Flatman, *Chair, Type 10BASE2 Task Force*

Menachem Abraham
R. V. Balakrishnan
William Belknap
Charles Brill
Juan Bulnes
Stephen Cooper
Ronald Crane
John Davidson
Mark Devon
Phil Edholm
Gregory Ennis
Judy Estrin
Richard Fransen
Ingrid Fromm
Robert Galin
Rich Graham
Guy Harkins
Greg Hopkins
Joe Kennedy
Hiroshi Kobayashi
Tony Lauck
William Livingston
Hugh Logan
Leland Long
Andy Luque
Daniel Maltbie
Steven Moustakas
Wendell Nakamine
Lloyd Oliver
Aidan Paul
David Potter
Eugene Reilly
Joseph Rickert
Gary Robinson
Robert Rosenthal
Joseph St. Amand
Walter Schreuer
Stephen Soto
Gary Spencer
Robert Summers
Pat Thaler
Geoff Thompson
Wendell Turner
David White
Lawrence White
Rich Williams
Ronald Yara
Mo Zonoun

AVA Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

The following persons were on the balloting committee that approved ANSI/IEEE Std 802.3-1985 for submission to the IEEE Standards Board:

W. Adams
R. Appleby
G. Arnold
Y. Baeg
E. Beauregard
J. Becker
E. Bergaimini
Boorstyn
A. Carrato
G. Carson
S. Chakradarti
S. Chandra
F. Chang
C. Chao
C. Chen
P. Chen
K. Chon
R. Chow
G. Clinque
I. Cotton
D. Cox
R. DeJardins
D. Dickel
C. Eldridge
P. Enslow
J. Fendirch
M. Figuerea
D. Fisher
J. Fletcher
W. Franta
R. Gagliano
D. Gan
M. Graube
M. Greene
R. Gustin
K. Harbaugh
G. Harkins
R. Harrington
H. Heilborn
L. Heselton
D. Hislop
C. Hobbs
S. Hollander
P. Hutton
P. Induiago
T. Ishida
J. Jelemenshy
O. Kahn
S. Kak
K. Katzeff
C. Kessler
D. Kirschen
R. Kolm
T. Kuki
R. Kunkel
W. Lai
V. Lasker
N. Lau
R. Laughlin
F. Lim
T. Liu
J. Loo
K. Loughner
D. Loughry
T. Louhenkillbi
D. Manchester
M. Marco
D. Matters
D. McInode
D. Michels
L. Moraes
D. Morriss
J. Murayama
R. Nelson
D. Ofsevit
C. Ostereicher
M. Papa
S. Peter
D. Phuoc
T. Phinney
G. Power
A. Reddi
M. Repko
F. Restivo
L. Rich
D. Rine
R. Rosenthal
P. Ruosadri
S. Samoylenko
B. Sashi
A. Sauer
N. Schneidewind
O. Serlin
D. Shepard
D. Sloyer
H. Solomon
G. Stephens
C. Stillebroer
K. Sumner
E. Sykas
A. Tantawi
D. Tether
J. Tourret
K. Tu
D. Umbaugh
J. Vorhies
A. Weissberger
W. Wenker
T. Wicklund
T. Wolf
F. Wolff
R. Youg

Documents
Document Sharing Hub
Full document details: ISO_IEC 8802-3_1992

The following persons were on the balloting committee that approved ANSI/IEEE Std 802.3a-1988 (Section 10) for submission to the IEEE Standards Board:

Marshall Abrams
John Adams
William B. Adams
S. R. Ahuja
Kit Athul
William Ayen
Yong-Myung Baeg
Wesley A. Ballenger, Jr.
Edwardo W. Bergamini
Henk F. Boley
Betty Brannick
George S. Carson
Po Chen
L. Y. Cheung
Kilnam Chon
T. Ricky Chow
David Cohen
Allen F. Conrad
Ira W. Cotton
Robert S. Crowder
Michel Diaz
Mitchell G. Duncan
Philip H. Enslow, Jr.
Judith Estrin
John W. Fendrich
Harvey A. Freeman
Patrick Gonia
Ambuj Goyal
Michael D. Graebner
Maris Graube
Nobuhiro Hamada
Joseph L. Hammond
Keith W. Harbaugh
S. M. Harris
J. Scott Haugdahl
Sharon Healy
C. W. Hobbs
Jim P. Hong
Paul L. Hutton
Richard Iliff
George D. Jelatis
Guy Juanole
Siegel L. Junker
Karl H. Kellermayr
Mladen Kezunovic
Samuel Kho
David Kollm
Sastri L. Kota
Hirayr M. Kudyan
Takahiko Kuki
Lee LaBarre
Wai-Sum Lai
Valerie Lasker
Lanse M. Leach
Edward Y. S. Lee
Stephen E. Levin
F. C. Lim
Don C. Loughry
Joseph F. P. Luhukay
Wo-Shun Luk
Marco Marsan
Joseph Massi
Darrell B. McIndoe
Patrick S. McIntosh
Marco Meli
David S. Millman
Aditya N. Mishra
Richard J. Moff
David E. Morgan
Mike Morganti
Kinji Mori
D. J. Morris
H. T. Mouftah
Dale A. Murray
Ruth Nelson
J. Duane Northcutt
Charles Ostereicher
David Ofsevit
Young Oh
George Parowski
Thomas L. Phinney
Nikitas Pimopoulos
David Potter
John Potvcek
Gary S. Robinson
Marya Repko
Robert Rosenthal
Gian Paolo Rossi
David J. Rypka
S. I. Samoylenko
Norman F. Schneidewind
Oscar Sepulveda
Omri Serlin
D. Sheppard
R. M. Simmons
David W. Sloyer

When the IEEE Standards Board approved ANSI/IEEE Std 802.3-1988 on June 9, 1988, and ANSI/IEEE Std 802.3a-1988 (Section 10) on October 20, 1988, it had the following membership:

Donald C. Fleckenstein, *Chair* **Marco Migliaro,** *Vice Chair*
Andrew G. Salem, *Secretary*

Arthur A. Blaisdell
Fletcher J. Buckley
James M. Daly
Stephen R. Dillon
Eugene P. Fogarty
Jay Forster*
Thomas L. Hannan
Kenneth D. Hendrix
Theodore W. Hissey, Jr.
John W. Horch
Jack M. Kinn
Frank D. Kirschner
Frank C. Kitzantides
Joseph L. Koepfinger*
Irving Kolodny
Edward Lohse
John E. May, Jr.
Lawrence V. McCall
L. Bruce McClung
Donald T. Michael*
Richard E. Mosher
L. John Rankine
Gary S. Robinson
Frank L. Rose
Helen M. Wood
Karl H. Zaininger
Donald W. Zipse

*Member emeritus

Documents
Document Sharing Hub
Full document details: ISO_IEC 8802-3_1992

ANSI/IEEE Std 802.3-1988 and ANSI/IEEE Std 802.3a-1988 were approved by the American National Standards Institute on January 12, 1989.

When the IEEE 802.3 Working Group approved ANSI/IEEE Std 802.3c-1985 (9.1–9.8) in July 1985, it had the following membership:

Donald C. Loughry, *Chair*
Geoffrey O. Thompson, *Chair, Repeater Task Force*

Menachem Abraham
Keith Albright
R. V. Balakrishnan
William Belknap
Richard Bennett
Charles Brill
Juan Bulnes
Stephen Cooper
Paul Eastman
Phil Edholm
Gregory Ennis
Alan Flatman
Richard Fransen
Ingrid Fromm
Robert Galin
Sharad Gandhi
Rich Graham
Richard Gumpertz
Hacene Hariti
Guy Harkins
Fred Huang
Stephen Janshego
Donald Johnson
Kwi-Yung Jung
Paul Kellam
Joe Kennedy
Hiroshi Kobayashi
Lee LaBarre
Tony Lauck
John Laynor
William Livingston
Terry Lockyer
James Lucas
Andy Luque
Daniel Maltbie
Steven Moustakas
Lloyd Oliver
Aidan Paul
David Potter
Eric Rawson
Joseph Rickert
Gary Robinson
Timothy Rock
David Roos
Robert Rosenthal
Joseph St. Amand
Walter Schreuer
Semir Sirazi
David Smith
Stephen Soto
Robert Summers
Pat Thaler
Wendell Turner
Marc Warshaw
Ronald Yara

AVA Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

The following persons were on the balloting committee that approved ANSI/IEEE Std 802.3c-1985 (9.1–9.8) for submission to the IEEE Standards Board:

Marshall Abrams
John Adams
William B. Adams
S. R. Ahuja
P. D. Amer
Kit Athul
William Ayen
Yong-Myung Baeg
Wesley A. Ballenger, Jr.
Edwardo W. Bergamini
H. F. Boley
Paul W. Campbell, Jr.
George S. Carson
Po Chen
L. Y. Cheung
Kilnam Chon
T. Ricky Chow
W. F. Chow
David Cohen
Allen F. Conrad
Robert S. Crowder
Michel Diaz
Philip H. Enslow, Jr.
Judith Estrin
John W. Fendrich
Harvey A. Freeman
R. J. Gagliano
Patrick Gonia
Ambuj Goyal
Michael D. Graebner
Maris Graube
Nobushiro Hamada
Joseph L. Hammond
S. M. Harris
J. Scott Haugdahl
C. W. Hobbs
Jim P. Hong
Paul L. Hutton
Richard Iliff
George D. Jelatis
E.D. Jensen
Guy Juanole
Karl H. Kellermayr
Mladen Kozunovic
Samuel Kho
David Kollm
Sastri L. Kota
Hirayr M. Kudyan
Takahiko Kuki
Lee LaBarre
Wai-Sum Lai
Lanse M. Leach
Stephen E. Levin
F. C. Lim
William Livingston
Don C. Loughry
Joseph F. P. Luhukay
Meli Marco
Marco Marsan
Joseph Massi
Darrell B. McIndoe
Patrick S. McIntosh
David S. Millman
Aditya N. Mishra
David E. Morgan
Mike Morganti
Kinji Mori
D. J. Morris
H. T. Mouftah
Dale A. Murray
Ruth Nelson
J. Duane Northcutt
Charles Oestereicher
Young Oh
George Parowski
Thomas L. Phinney
David Potter
John Potvcek
Gary S. Robinson
Marya Repko
Robert Rosenthal
Gian Paolo Rossi
David J. Rypka
S. I. Samoylenko
Norman F. Schneidewind
Oscar Sepulveda
Omri Serlin
D. Sheppard
R. M. Simmons
L. Sintonen
David W. Sloyer
Stephen Soto
Fred Strauss
Bart W. Stuck
Tatsuya Suda
Efstathios D. Sykas
Daniel T. W. Sze
Ahmed N. Tantaui
Mario Tokoro
H. C. Torng
Donald F. Towsley
Wei-Tek Tsai
M. Tsuchiya
Richard Tung
Stanko Turk
L. David Umbaugh
James Vorhies
Pearl S. C. Wang
Don Weir
Alan J. Weissberger
William J. Wenker
Earl J. Whitaker
Michael Willett
Tsong-Ho Wu
Oren Yuen

When the IEEE Standards Board approved ANSI/IEEE Std 802.3c-1985 (9.1–9.8) on December 12, 1985, it had the following membership:

John E. May, *Chair*

John P. Riganati, *Vice Chair*

Sava I. Sherr, *Secretary*

James H. Beall
Fletcher J. Buckley
Rene Castenschiold
Edward Chelotti
Edward J. Cohen
Paul G. Cummings
Donald C. Fleckenstein
Jay Forster
Daniel L. Goldberg
Kenneth D. Hendrix
Irvin N. Howell
Jack Kinn
Joseph L. Koepfinger*
Irving Kolodny
R. F. Lawrence
Lawrence V. McCall
Donald T. Michael*
Frank L. Rose
Clifford O. Swanson
J. Richard Weger
W. B. Wilkens
Charles J. Wylie

*Member emeritus

Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

ANSI/IEEE Std 802.3c-1985 was approved by the American National Standards Institute on June 4, 1986.

When the IEEE 802.3 Working Group approved ANSI/IEEE Std 802.3d-1987 (9.9), it had the following membership:

Donald C. Loughry, *Chair*
Steven Moustakas, *Chair, Task Force*

Menachem Abraham
Keith Albright
Keith Amundsen
Jean-Pierre Astorg
R. V. Balakrishnan
Richard Bennett
Charles Brill
Juan Bulnes
Robert Campbell
Luigi Canavese
Albert Claessen
Peter Dawe
Peter Desaulniers
Raymond Duley
Jeff Ebeling
Gianfranco Enrico
Alan Flatman
Richard Fransen
Ingrid Fromm
Robert Galin
Mark Gerhold
Adi Golbert
Rich Graham
Rich Gumpertz
Hacene Hariti
Lloyd Hasley
Hawming Haung
Charles Hoffner
Michael Hughes
Donald Johnson
Mze Johnson
Kwi-Yung Jung
Matt Kaltenbach
Paul Kellam
Scott Kesler
Hiroshi Kobayashi
Hidetsune Kurokawa
Lee LaBarre
Ed Lare
Wayne Lindquist
Terry Lockyer
Don Loughry
James Lucas
Andy Luque
Lloyd Oliver
Aidan Paul
Roy Pierce
Eric Rawson
Joseph Rickert
Gary Robinson
Timothy Rock
David Roos
Walter Schruer
Semir Sirazi
David Smith
Robert Summers
Pat Thaler
Geoff Thompson
Nathan Tobol
Carlos Tomaszewski
Wendell Turner
Joseph Wiencko
Bruce Williams

OBSERVERS

Allen Cherin
John Decramer
Paul Eastman
Shinji Emori
Jiro Kashio
Michael Lee
Luciano Marchitto
Jim Montrose
Peter Tarrant

The IEC TC83 Committee on Information Technology Equipment also provided very helpful input to the development of the FOIRL Standard (9.9).

AVA Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

The following persons were on the balloting committee that approved ANSI/IEEE Std 802.3d-1987 (9.9) for submission to the IEEE Standards Board:

William B. Adams
S. R. Ahuja
Kit Athul
William Ayen
Eduardo W. Bergamini
Paul W. Campbell, Jr.
George S. Carson
Po Chen
L. Y. Cheung
Kilnam Chon
W. F. Chow
Michael Coden
A. F. Conrad
Robert S. Crowder
Michel Diaz
N. I. Dimopoulos
M. G. Duncan
Philip H. Enslow, Jr.
Judith Estrin
John W. Fendrich
Harvey A. Freeman
Patrick S. Gonia
R. L. Gordon
A. Goyal
M. D. Graebner
Maris Graube
Joseph L. Hammond
Stephen Harris
J. Scott Haugdahl
C. W. Hobbs
Paul Hutton
Richard Illif
E. D. Jenson
Guy Juanole
Karl H. Kellermayr
M. Kezunovic
Samuel Kno
S. E. Kille
David Kollm
Takahiko Kuki
Lee LaBarre
Wai-Sum Lai
Lanse M. Leach
Edward Y. Lee
R. C. Lightburn
F. C. Lim
William D. Livingston
Don C. Loughry
Joseph F. P. Luhukay
Wo-Shun Luk
Marco Ajmone Marsan
Joseph Massi
Marco Meli
Darrel B. McIndoe
P. S. McIntosh
David S. Millman
Aditya N. Mishra
David E. Morgan
Mike Morganti
Kanji Mori
David Morris
H. H. T. Mouftah
Dale N. Murray
R. R. Nelson
J. D. Northcut
Charles Oestereicher
Young Oh
George Parowski
Thomas L. Phinney
J. M. Potucek
Marya Repko
Gary S. Robinson
Robert Rosenthal
Gian Paolo Rossi
David J. Rypka
S. I. Samaylenko
Norman F. Schneidewind
Omri Serlin
D. Sheppard
Ron Simmons
J. B. Sinclair
L. Sintonen
Tom Stack
Carel M. Stillebroer
Fred Strauss
Tatsuya Suda
P. Sugar
Efstathios D. Sykas
Daniel T. W. Sze
Ahmed N. Tantawi
H. C. Torng
D. F. Towsley
Wei-Tek Tsai
Stanko Turk
L. David Umbaugh
J. T. Vorhies
Pearl S. C. Wang
Don Weir
Alan J. Weissburger
W. J. Wenker
Earl J. Whitaker
Bryan Whittle
Michael Willett
David C. Wood
Tsong-Hu Wu
Oren Yuen

When the IEEE Standards Board approved ANSI/IEEE Std 802.3d-1987 (9.9) on December 12, 1985, it had the following membership:

Donald C. Fleckenstein, *Chair* **Marco Migliaro,** *Vice Chair*
Andrew G. Salem, *Secretary*

James H. Beall
Dennis Bodson
Marshall L. Cain
James M. Daly
Stephen R. Dillon
Eugene P. Fogarty
Jay Forster
Kenneth D. Hendrix
Irvin N. Howell
Leslie R. Kerr
Jack Kinn
Irving Kolodny
Joseph L. Koepfinger*
Edward Lohse
John May
Lawrence V. McCall
L. Bruce McClung
Donald T. Michael*
L. John Rankine
John P. Riganati
Gary S. Robinson
Frank L. Rose
Robert E. Rountree
William R. Tackaberry
William B. Wilkens
Helen M. Wood

*Member emeritus

AVA Documents
Document Sharing Hub
Full document details: ISO_IEC 8802-3_1992

ANSI/IEEE Std 802.3d-1987 was approved by the American National Standards Institute on February 9, 1989.

When the IEEE 802.3 Working Group approved ANSI/IEEE Std 802.3b-1985 (Section 11), it had the following membership:

Donald C. Loughry, *Chair*
Menachem Abraham, *Chair, Type 10BROAD36 Task Force*

Keith Albright
R. V. Balakrishnan
William Belknap
Richard Bennett
Charles Brill
Juan Bulnes
Stephen Cooper
Ronald Crane
John Davidson
Mark Devon
Paul Eastman
Phil Edholm
Gregory Ennis
Judy Estrin
Alan Flatman
Richard Fransen
Ingrid Fromm
Robert Galin
Sharad Gandhi
Rich Graham
Richard Gumpertz
Hacene Hariti
Guy Harkins
Gregory Hopkins
Fred Huang
Stephen Janshego
Donald Johnson
Kwi-Yung Jung
Paul Kellam
Joe Kennedy
Hiroshi Kobayashi
Lee LaBarre
Ed Lare
Tony Lauck
John Laynor
William Livingston
Terry Lockyer
Hugh Logan
Leland Long
James Lucas
Andy Luque
Daniel Maltbie
Joseph Mazor
Steven Moustakas
Narayan Murthy
Wendell Nakamine
Lloyd Oliver
Aidan Paul
David Potter
Eric Rawson
Eugene Reilly
Joseph Rickert
Anthony Rizzolo
Gary Robinson
Timothy Rock
David Roos
Robert Rosenthal
Joseph St. Amand
Walter Schreuer
Semir Sirazi
David Smith
Stephen Soto
Gary Spencer
Robert Summers
Pat Thaler
Geoff Thompson
Nathan Tobol
Wendell Turner
Marc Warshaw
David White
Mo Zonoun

The following persons were on the balloting committee that approved ANSI/IEEE Std 802.3b-1985 (Section 11) for submission to the IEEE Standards Board:

Marshall Abrams
John Adams
William B. Adams
S. R. Ahuja
Kit Athul
William Ayen
Yong-Myung Baeg
Wesley A. Ballenger, Jr.
Edwardo W. Bergamini
Henk F. Boley
George S. Carson
Po Chen
L. Y. Cheung
Kilnam Chon
T. Ricky Chow
David Cohen
Allen F. Conrad
Ira W. Cotton
Robert S. Crowder
Michel Diaz
Mitchell G. Duncan
Philip H. Enslow, Jr.
Judith Estrin
John W. Fendrich
Harvey A. Freeman
Patrick Gonia
Ambuj Goyal
Michael D. Graebner
Maris Graube
Nobuhiro Hamada
Joseph L. Hammond
Keith W. Harbaugh
S. M. Harris
J. Scott Haugdahl
Sharon Healy
C. W. Hobbs
Jim P. Hong
Paul L. Hutton
Richard Iliff
George D. Jelatis
E. Douglas Jensen
Guy Juanole
Siegel L. Junker
Karl H. Kellermayr
Mladen Kezunovic
Samuel Kho
David Kollm
Sastri L. Kota
Hirayr M. Kudyan
Takahiko Kuki
Lee LaBarre
Wai-Sum Lai
Valerie Lasker
Lanse M. Leach
Edward Y. S. Lee
Stephen E. Levin
F. C. Lim
Don C. Loughry
Joseph F. P. Luhukay
Wo-Shun Luk

AVA Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

Marco Marsan
Joseph Massi
Darrell B. McIndoe
Patrick S. McIntosh
Marco Meli
David S. Millman
Aditya N. Mishra
Richard J. Moff
David E. Morgan
Mike Morganti
Kinji Mori
D. J. Morris
H. T. Mouftah
Dale A. Murray
Ruth Nelson
J. Duane Northcutt
Charles Oestereicher
David Ofsevit
Young Oh
George Parowski
Thomas L. Phinney
Nikitas Pimopoulos
David Potter
John Potvcek
Gary S. Robinson
Marya Repko
Robert Rosenthal
Gian Paolo Rossi
David J. Rypka
S. I. Samoylenko
Norman F. Schneidewind
Oscar Sepulveda
Omri Serlin
D. Sheppard
R. M. Simmons
David W. Sloyer
Stephen Soto
Tom Stack
Carel M. Stillebroer
Fred Strauss
Bart W. Stuck
Tatsuya Suda
Peter Sugar
Efstathios D. Sykas
Daniel T. W. Sze
Ahmed N. Tantaui
Mario Tokoro
H. C. Torng
Donald F. Towsley
Wei-Tek Tsai
M. Tsuchiya
Richard Tung
Stanko Turk
L. David Umbaugh
James Vorhies
Pearl S. C. Wang
Don Weir
Alan J. Weissberger
William J. Wenker
Earl J. Whitaker
Bryan S. Whittle
Michael Willett
Donald Wittman
George R. Wood
Tsong-Ho Wu

When the IEEE Standards Board approved ANSI/IEEE Std 802.3b-1985 (Section 11) on September 19, 1985, it had the following membership:

John E. May, *Chair* **John P. Riganati,** *Vice Chair*
Sava I. Sherr, *Secretary*

James H. Beall
Fletcher J. Buckley
Rene Castenschiold
Edward Chelotti
Edward J. Cohen
Paul G. Cummings
Donald C. Fleckenstein
Jay Forster
Daniel L. Goldberg
Kenneth D. Hendrix
Irvin N. Howell
Jack Kinn
Joseph L. Koepfinger*
Irving Kolodny
R. F. Lawrence
Lawrence V. McCall
Donald T. Michael*
Frank L. Rose
Clifford 0. Swanson
J. Richard Weger
W. B. Wilkens
Charles J. Wylie

*Member emeritus

ANSI/IEEE Std 802.3b-1985 was approved by the American National Standards Institute on February 28, 1986.

When the IEEE 802.3 Working Group approved ANSI/IEEE Std 802.3e-1987 (Section 12) in November 1986, it had the following membership:

Donald C. Loughry, *Chair*
Robert Galin, *Chair, Type 1BASE5 Task Force*

Menachem Abraham
Keith Albright
Keith Amundsen
Jean-Pierre Astorg
R. V. Balakrishnan
Ian Barker
Charles Brill
Juan Bulnes
Robert Campbell
Luigi Canavese
Albert Claessen
Michael Coden
Bill Cronin
Peter Dawe
Peter Desaulniers
Raymond Duley
Jeff Ebeling
Gianfranco Enrico
Alan Flatman
Richard Fransen
Mark Gerhold
Adi Golbert
Rich Graham
Richard Gumpertz
Hacene Hariti
Lloyd Hasley
Haw Ming Haung

AVA Documents
Document Sharing Hub
Full document details: ISO_IEC 8802-3_1992

Charles Hoffner
Michael Hughes
Donald Johnson
Mize Johnson
Kwi-Yung Jung
Matt Kaltenbach
Paul Kellam
Scott Kesler
Hiroshi Kobayashi
Hidetsune Kurokawa
Michael Lee
Lee LaBarre
Terry Lockyer
James Lucas
Andy Luque
Luciano Marchitto
Steven Moustakas
Lloyd Oliver
Roy Pierce
Bill Poston
Eric Rawson
Joseph Rickert
Gary Robinson
Timothy Rock
David Roos
Ed Sakaguchi
Walter Schreuer
Semir Sirazi
David Smith
Robert Summers
Peter Tarrant
Mark Taylor
Pat Thaler
Geoff Thompson
Nathan Tobol
Carlos Tomaszewski
Jayshree Ullal
Joseph Wiencko
Bruce Williams

The following persons were on the balloting committee that approved ANSI/IEEE Std 802.3e-1987 (Section 12) for submission to the IEEE Standards Board:

Marshall D. Abrams
William B. Adams
S. R. Ahuja
P. D. Amer
Kit Athul
William Ayen
Eduardo W. Bergamini
H. F. Boley
Paul W. Campbell, Jr.
George S. Carson
Po Chen
L. Y. Cheung
Kilnam Chon
W. F. Chow
Michael Coden
A. F. Conrad
Ira Cotton
D. E. Crotty
Robert S. Crowder
Michel Diaz
N. I. Dimopoulos
M. G. Duncan
P. M. Elliot
Philip H. Enslow, Jr.
Judith Estrin
John W. Fendrich
G. A. Foggiato
Harvey A. Freeman
Robert J. Gagliano
T. F. Gannon III
Patrick S. Gonia
R. L. Gordon
A. Goyal
M. D. Graebner
Maris Graube
Joseph L. Hammond
Stephen Harris
J. Scott Haugdahl
C. W. Hobbs
Paul Hutton
Richard Iliff
E. D. Jenson
Guy Juanole
S. L. Junker
Karl H. Kellermayr
M. Kezunovic
Samuel Kho
S. E. Kille
David Kollm
Takahiko Kuki
Lee LaBarre
Wai-Sum Lai
Lanse M. Leach
Edward Y. Lee
S. E. Levin
R. C. Lightburn
F. C. Lim
William D. Livingston
Don C. Loughry
Joseph F. P. Luhukay
Wo-Shun Luk
Marco Ajmone Marsan
Joseph Massi
Marco Meli
Darrel B. McIndoe
P. S. McIntosh
David S. Millman
Aditya N. Mishra
David E. Morgan
Mike Morganti
Kanji Mori
David Morris
H. H. T. Mouftah
Dale N. Murray
R. R. Nelson
J. D. Northcut
Charles Oestereicher
Young Oh
George Parowski
Thomas L. Phinney
David Potter
J. M. Potucek
Marya Repko
Gary S. Robinson
Robert Rosenthal
Gian Paolo Rossi
David J. Rypka
S. I. Samaylenko
Norman F. Schneidewind
Omri Serlin
D. Sheppard
Ron Simmons
J. B. Sinclair
L. Sintonen
Stephen H. Soto
Tom Stack
Carel M. Stillebroer
Fred Strauss
Bart W. Stuck
Tatsuya Suda
P. Sugar
Efstathios D. Sykas
Daniel T. W. Sze
Ahmed N. Tantawi
H. C. Torng
D. F. Towsley
Wei-Tek Tsai
Masahiro Tsuchiya
Stanko Turk
L. David Umbaugh
J. T. Vorhies
Pearl S. C. Wang
Don Weir
Alan J. Weissburger
W. J. Wenker
Earl J. Whitaker
Bryan Whittle
Michael Willett
David C. Wood
Tsong-Hu Wu
Oren Yuen

AVA Documents
Document Sharing Hub
Full document details: ISO_IEC 8802-3_1992

When the IEEE Standards Board approved ANSI/IEEE Std 802.3e-1987 (Section 12) on June 11, 1987, it had the following membership:

Donald C. Fleckenstein, *Chair* **Marco W. Migliaro,** *Vice Chair*
Andrew G. Salem, *Secretary*

James H. Beall	Leslie R. Kerr	L. John Rankine
Dennis Bodson	Jack Kinn	John P. Riganati
Marshall L. Cain	Irving Kolodny	Gary S. Robinson
James M. Daly	Joseph L. Koepfinger*	Frank L. Rose
Stephen R. Dillon	Edward Lohse	Robert E. Rountree
Eugene P. Fogarty	John May	Sava I. Sherr*
Jay Forster	Lawrence V. McCall	William R. Tackaberry
Kenneth D. Hendrix	L. Bruce McClung	William B. Wilkens
Irvin N. Howell	Donald T. Michael*	Helen M. Wood

*Member emeritus

ANSI/IEEE Std 802.3e-1987 was approved by the American National Standards Institute on December 15, 1987.

Documents
Document Sharing Hub
Full document details: ISO_IEC 8802-3_1992

Contents

SECTION PAGE

1. Introduction 31
   1.1 Overview 31
      1.1.1 Basic Concepts 31
      1.1.2 Architectural Perspectives 31
      1.1.3 Layer Interfaces 33
      1.1.4 Application Areas 33
   1.2 Notation 33
      1.2.1 State Diagram Conventions 33
      1.2.2 Service Specification Method and Notation 35
      1.2.3 Physical Layer and Media Notation 36
      1.2.4 Physical Layer Message Notation 36
   1.3 References 37
   1.4 Definitions 38

2. MAC Service Specification 39
   2.1 Scope and Field of Application 39
   2.2 Overview of the Service 39
      2.2.1 General Description of Services Provided by the Layer 39
      2.2.2 Model Used for the Service Specification 40
      2.2.3 Overview of Interactions 40
      2.2.4 Basic Services and Options 40
   2.3 Detailed Service Specification 40
      2.3.1 MA_DATA.request 40
      2.3.2 MA_DATA.indication 41

3. Media Access Control Frame Structure 43
   3.1 Overview 43
      3.1.1 MAC Frame Format 43
   3.2 Elements of the MAC Frame 44
      3.2.1 Preamble Field 44
      3.2.2 Start Frame Delimiter (SFD) Field 44
      3.2.3 Address Fields 44
      3.2.4 Destination Address Field 45
      3.2.5 Source Address Field 46
      3.2.6 Length Field 46
      3.2.7 Data and PAD Fields 46
      3.2.8 Frame Check Sequence Field 46
   3.3 Order of Bit Transmission 47
   3.4 Invalid MAC Frame 47

4. Media Access Control Method 49
   4.1 Functional Model of the Media Access Control Method 49
      4.1.1 Overview 49
      4.1.2 CSMA/CD Operation 49
      4.1.3 Relationships to LLC Sublayer and Physical Layer 52

Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

SECTION PAGE

4.1.4 CSMA/CD Access Method Functional Capabilities..... 52
4.2 CSMA/CD Media Access Control Method (MAC): Precise Specification 54
4.2.1 Introduction 54
4.2.2 Overview of the Procedural Model..... 54
4.2.3 Frame Transmission Model 57
4.2.4 Frame Reception Model 61
4.2.5 Preamble Generation 62
4.2.6 Start Frame Sequence..... 63
4.2.7 Global Declarations..... 63
4.2.8 Frame Transmission 66
4.2.9 Frame Reception 71
4.2.10 Common Procedures 74
4.3 Interfaces to/from Adjacent Layers 74
4.3.1 Overview 74
4.3.2 Services Provided by the MAC Sublayer 74
4.3.3 Services Required from the Physical Layer..... 75
4.4 Specific Implementations..... 77
4.4.1 Compatibility Overview 77
4.4.2 Allowable Implementations 77

5. Network Management 79

6. PLS Service Specifications..... 81
6.1 Scope and Field of Application 81
6.2 Overview of the Service 81
6.2.1 General Description of Services Provided by the Layer.... 81
6.2.2 Model Used for the Service Specification 81
6.2.3 Overview of Interactions 81
6.2.4 Basic Services and Options 81
6.3 Detailed Service Specification 82
6.3.1 Peer-to-Peer Service Primitives..... 82
6.3.2 Sublayer-to-Sublayer Service Primitives 83

7. Physical Signaling (PLS) and Attachment Unit Interface (AUI) Specifications..... 85
7.1 Scope..... 85
7.1.1 Definitions..... 86
7.1.2 Summary of Major Concepts..... 86
7.1.3 Application..... 87
7.1.4 Modes of Operation..... 87
7.1.5 Allocation of Function..... 87
7.2 Functional Specification..... 87
7.2.1 PLS-PMA (DTE-MAU) Interface Protocol..... 87
7.2.2 PLS Interface to MAC and Management Entities 94
7.2.3 Frame Structure 96
7.2.4 PLS Functions 97

AVA Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

SECTION PAGE

7.3 Signal Characteristics 100
7.3.1 Signal Encoding 100
7.3.2 Signaling Rate 105
7.3.3 Signaling Levels 105
7.4 Electrical Characteristics 105
7.4.1 Driver Characteristics 106
7.4.2 Receiver Characteristics 109
7.4.3 AUI Cable Characteristics 111
7.5 Functional Description of Interchange Circuits 113
7.5.1 General 113
7.5.2 Definition of Interchange Circuits 114
7.6 Mechanical Characteristics 117
7.6.1 Definition of Mechanical Interface 117
7.6.2 Line Interface Connector 117
7.6.3 Contact Assignments 118

8. Medium Attachment Unit and Baseband Medium Specifications, Type 10BASE5 121
8.1 Scope 121
8.1.1 Overview 121
8.1.2 Definitions 122
8.1.3 Application Perspective: MAU and MEDIUM Objectives 123
8.2 MAU Functional Specifications 124
8.2.1 MAU Physical Layer Functions 125
8.2.2 MAU Interface Messages 127
8.2.3 MAU State Diagrams 129
8.3 MAU-Medium Electrical Characteristics 130
8.3.1 MAU-to-Coaxial Cable Interface 130
8.3.2 MAU Electrical Characteristics 135
8.3.3 MAU-DTE Electrical Characteristics 136
8.3.4 MAU-DTE Mechanical Connection 136
8.4 Characteristics of the Coaxial Cable 136
8.4.1 Coaxial Cable Electrical Parameters 136
8.4.2 Coaxial Cable Properties 137
8.4.3 Total Segment DC Loop Resistance 139
8.5 Coaxial Trunk Cable Connectors 139
8.5.1 Inline Coaxial Extension Connector 139
8.5.2 Coaxial Cable Terminator 139
8.5.3 MAU-to-Coaxial Cable Connector 140
8.6 System Considerations 141
8.6.1 Transmission System Model 141
8.6.2 Transmission System Requirements 143
8.6.3 Labeling 146
8.7 Environmental Specifications 146

Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

SECTION PAGE

8.7.1 General Safety Requirements 146
8.7.2 Network Safety Requirements....147
8.7.3 Electromagnetic Environment....148
8.7.4 Temperature and Humidity 149
8.7.5 Regulatory Requirements....149

9. Repeater Unit for 10 Mb/s Baseband Networks 151
9.1 Overview....151
9.2 Definitions....152
9.3 References....153
9.4 Compatibility Interface....153
9.4.1 AUI Compatibility....153
9.4.2 Direct Cable Compatibility 153
9.4.3 IRL Compatibility 154
9.5 Basic Functions....154
9.5.1 Repeater Set Network Properties....154
9.5.2 Signal Amplification....154
9.5.3 Signal Symmetry 154
9.5.4 Signal Retiming 154
9.5.5 Data Handling 155
9.5.6 Collision Handling 155
9.5.7 Electrical Isolation....156
9.6 Detailed Repeater Functions and State Diagrams....156
9.6.1 State Diagram Notation 156
9.6.2 Data and Collision Handling 162
9.6.3 Preamble Regeneration 162
9.6.4 Fragment Extension....162
9.6.5 MAU Jabber Lockup Protection 162
9.6.6 Auto-Partitioning/Reconnection (Optional)....162
9.7 Electrical Isolation 165
9.7.1 Environment A Requirements 165
9.7.2 Environment B Requirements 165
9.8 Reliability 165
9.9 Medium Attachment Unit and Baseband Medium Specification for a Vendor-Independent FOIRL....166
9.9.1 Scope....166
9.9.2 FOMAU Functional Specifications 168
9.9.3 FOMAU Electrical Characteristics 178
9.9.4 FOMAU/Optical Medium Interface....179
9.9.5 Characteristics of the Optical Fiber Cable Link Segment....180
9.9.6 System Requirements 181
9.9.7 Environmental Specifications 183

10. Medium Attachment Unit and Baseband Medium Specifications, Type 10BASE2 185

Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

SECTION PAGE

10.1 Scope 185
10.1.1 Overview 185
10.1.2 Definitions 186
10.1.3 Application Perspective: MAU and Medium Objectives 187
10.2 References 188
10.3 MAU Functional Specfications 188
10.3.1 MAU Physical Layer Functional Requirements 189
10.3.2 MAU Interface Messages 192
10.3.3 MAU State Diagrams 194
10.4 MAU-Medium Electrical Characteristics 195
10.4.1 MAU-to-Coaxial Cable Interface 195
10.4.2 MAU Electrical Characteristics 197
10.4.3 MAU-DTE Electrical Characteristics 198
10.5 Characteristics of Coaxial Cable System 198
10.5.1 Coaxial Cable Electrical Parameters 198
10.5.2 Coaxial Cable Physical Parameters 199
10.5.3 Total Segment DC Loop Resistance 201
10.6 Coaxial Trunk Cable Connectors 201
10.6.1 In-Line Coaxial Extension Connector 201
10.6.2 Coaxial Cable Terminator 201
10.6.3 MAU-to-Coaxial Cable Connection 201
10.7 System Considerations 203
10.7.1 Transmission System Model 203
10.7.2 Transmission System Requirements 204
10.8 Environmental Specifications 206
10.8.1 Safety Requirements 206
10.8.2 Electromagnetic Environment 207
10.8.3 Regulatory Requirements 207

11. Broadband Medium Attachment Unit and Broadband Medium Specifications, Type 10BROAD36 209
11.1 Scope 209
11.1.1 Overview 209
11.1.2 Definitions 212
11.1.3 MAU and Medium Objectives 213
11.1.4 Compatibility Considerations 214
11.1.5 Relationship to PLS and AUI 214
11.1.6 Mode of Operation 214
11.2 MAU Functional Specifications 214
11.2.1 MAU Functional Requirements 214
11.2.2 DTE PLS to MAU and MAU to DTE PLS Messages 218
11.2.3 MAU State Diagrams 219
11.3 MAU Characteristics 224
11.3.1 MAU to Coaxial Cable Interface 224

Documents
Document Sharing Hub
Full document details: ISO_IEC 8802-3_1992

SECTION PAGE

11.3.2 MAU Frequency Allocations....231
11.3.3 AUI Electrical Characteristics....232
11.3.4 MAU Transfer Characteristics....233
11.3.5 Reliability....242
11.4 System Considerations....242
11.4.1 Delay Budget and Network Diameter....242
11.4.2 MAU Operation with Packets Shorter than 512 Bits....242
11.5 Characteristics of the Coaxial Cable System....244
11.5.1 Electrical Requirements....244
11.5.2 Mechanical Requirements....244
11.5.3 Delay Requirements....245
11.6 Frequency Translator Requirements for the Single-Cable Version....245
11.6.1 Electrical Requirements....245
11.6.2 Mechanical Requirements....246
11.7 Environmental Specifications....246
11.7.1 Safety Requirements....246
11.7.2 Electromagnetic Environment....246
11.7.3 Temperature and Humidity....247

12. Physical Signaling, Medium Attachment, and Baseband Medium Specifications, Type 1BASE5....249
12.1 Introduction....249
12.1.1 Overview....249
12.1.2 Scope....249
12.1.3 Definitions....249
12.1.4 General Characteristics....252
12.1.5 Compatibility....252
12.1.6 Objectives of Type 1BASE5 Specifications....252
12.2 Architecture....252
12.2.1 Major Concepts....252
12.2.2 Application Perspective....253
12.2.3 Packet Structure....254
12.3 DTE Physical Signaling (PLS) Specification....256
12.3.1 Overview....256
12.3.2 Functional Specification....256
12.4 Hub Specification....265
12.4.1 Overview....265
12.4.2 Hub Structure....267
12.4.3 Hub PLS Functional Specification....267
12.5 Physical Medium Attachment (PMA) Specification....274
12.5.1 Overview....274
12.5.2 PLS-PMA Interface....275
12.5.3 Signal Characteristics....275
12.6 Medium Dependent Interface (MDI) Specification....285

Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

SECTION PAGE

12.6.1 Line Interface Connector 285
12.6.2 Connector Contact Assignments 285
12.6.3 Labeling 285
12.7 Cable Medium Characteristics 285
12.7.1 Overview 285
12.7.2 Transmission Parameters 285
12.7.3 Coupling Parameters 287
12.7.4 Noise Environment 288
12.8 Special Link Specification 289
12.8.1 Overview 289
12.8.2 Transmission Characteristics 290
12.8.3 Permitted Configurations 290
12.9 Timing 290
12.9.1 Overview 290
12.9.2 DTE Timing 290
12.9.3 Medium Timing 291
12.9.4 Special Link Timing 291
12.9.5 Hub Timing 291
12.10 Safety 292
12.10.1 Isolation 292
12.10.2 Telephony Voltages 292

FIGURES

Fig 1-1 LAN Standard Relationship to the OSI Reference Model 32
Fig 1-2 State Diagram Notation Example 34
Fig 1-3 Service Primitive Notation 36
Fig 2-1 Service Specification Relation to the LAN Model 39
Fig 3-1 MAC Frame Format 43
Fig 3-2 Address Field Format 44
Fig 4-1 MAC Sublayer Partitioning, Relationship to OSI Reference Model 50
Fig 4-2 CSMA/CD Media Access Control Functions 53
Fig 4-3 Relationship Among CSMA/CD Procedures 56
Fig 4-4 Control Flow Summary 58
Fig 4-5 Control Flow: MAC Sublayer 59
Fig 6-1 Service Specification Relationship to the LAN Model 82
Fig 7-1 Physical Layer Partitioning, Relationship to OSI Reference Model 85
Fig 7-2 Generalized MAU Model 88
Fig 7-3 PLS Reset and Identify Function 90
Fig 7-4 PLS Mode Function 91
Fig 7-5 PLS Output Function 92
Fig 7-6 PLS Input Function 98
Fig 7-7 PLS Error Sense Function 99
Fig 7-8 PLS Carrier Sense Function 101

Documents
Document Sharing Hub
Full document details: ISO_IEC 8802-3_1992

FIGURES PAGE

Fig 7-9 Interface Function for MAU with Conditioning 102–103
Fig 7-10 Examples of Manchester Waveforms 104
Fig 7-11 Differential Output Voltage, Loaded 107
Fig 7-12 Generalized Driver Waveform 108
Fig 7-13 Common-Mode Output Voltage 109
Fig 7-14 Driver Fault Conditions 110
Fig 7-15 Common-Mode Input Test 111
Fig 7-16 Receiver Fault Conditions 112
Fig 7-17 Common-Mode Transfer Impedance 113
Fig 7-18 Connector Locking Posts 116
Fig 7-19 Connector Slide Latch 117
Fig 7-20 Connector Hardware and AUI Cable Configuration 118
Fig 8-1 Physical Layer Partitioning, Relationship to the ISO Open System Interconnection Reference Model 121
Fig 8-2 Interface Function: Simple MAU without Isolate Capability 130
Fig 8-3 Interface Function: Simple MAU with Isolate Capability 131
Fig 8-4 Jabber Function 132
Fig 8-5 Recommended Driver Current Signal Levels 134
Fig 8-6 Typical Coaxial Trunk Cable Signal Waveform 134
Fig 8-7 Maximum Coaxial Cable Transfer Impedance 137
Fig 8-8 Coaxial Tap Connector Configuration Concepts 142
Fig 8-9 Typical Coaxial Tap Connection Circuit 142
Fig 8-10 Maximum Transmission Path 143
Fig 8-11 Minimal System Configuration 144
Fig 8-12 Minimal System Configuration Requiring a Repeater Set 144
Fig 8-13 An Example of a Large System with Maximum Transmission Paths 145
Fig 8-14 An Example of a Large Point-to-Point Link System (5140 ns) 145
Fig 9-1 Repeater Set, Coax-to-Coax Configuration 151
Fig 9-2 Repeater Unit State Diagram 160
Fig 9-3 Transmit Timer State Diagram for Port X 161
Fig 9-4 Tw2 State Diagram 161
Fig 9-5 MAU Jabber Lockup Protection State Diagram 161
Fig 9-6 Partitioning State Diagram for Port X 164
Fig 9-7 Schematic of the Vendor-Independent FOIRL and Its Relationship to the Repeater Unit 167
Fig 9-8 FOMAU Transmit, Receive, and Collision Functions State Diagram 176
Fig 9-9 FOMAU Jabber Function State Diagram 177
Fig 9-10 Low Light Level Detection Function State Diagram 177
Fig 10-1 Physical Layer Partitioning; Relationship to the ISO Open System Interconnection (OSI) Reference Model 185
Fig 10-2 MAU Interface Function 190

Documents
Document Sharing Hub
Full document details: ISO_IEC 8802-3_1992

FIGURES PAGE

Fig 10-3 Jabber Function State Diagram....193
Fig 10-4 Driver Current Signal Levels....196
Fig 10-5 Coaxial Trunk Cable Waveform....197
Fig 10-6 Maximum Coaxial Cable Transfer Impedance....200
Fig 10-7 Examples of Insulated Connector Cover....202
Fig 10-8 Maximum Transfer Path....203
Fig 10-9 The Minimum System Configuration....205
Fig 10-10 The Minimum System Configuration Requiring a Repeater Set....205
Fig 10-11 An Example of a Large Hybrid System....206
Fig 11-1 Physical Layer Partitioning; Relationship to the ISO Open System Interconnection Reference Model....210
Fig 11-2 Broadband Cable Systems....211
Fig 11-3 Transmit Function Requirements....215
Fig 11-4 MAU State Diagram....220–221
Fig 11-5(a) MAU Jabber State Diagram....222
Fig 11-5(b) MAU Jabber State Diagram (continued)....223
Fig 11-6 Packet Format and Timing Diagram (AUI to Coaxial Cable Interface)....227
Fig 11-7 Spectrum Mask for RF Data Signal....228
Fig 11-8 Transmit Out-of-Band Power Attenuation....230
Fig 11-9 Packet Format at Modulator Input....233
Fig 11-10 Scrambler....235
Fig 11-11 Differential Encoder....236
Fig 11-12 Descrambler....236
Fig 11-13 No Collision Timing Diagram (Coax to AUI)....239
Fig 11-14 Collision Timing Diagram (RF Data to RF Collision Enforcement)....240
Fig 11-15 Collision Timing Diagram (Coaxial Cable Interface to AUI Circuit CI)....241
Fig 11-16 Timing at AUI for Zero-Length Coax....243
Fig 12-1 1BASE5 Relationship to the OSI Reference Model and the IEEE 802.3 CSMA/CD LAN Model....250
Fig 12-2 Single Hub Network....253
Fig 12-3 Network With Two Levels of Hubs....254
Fig 12-4 Network With Four Levels of Hubs....255
Fig 12-5 Station Physical Signaling Relationship to the OSI Reference Model and the IEEE 802.3 CSMA/CD LAN Model...257
Fig 12-6 DTE PLS Output Function....261
Fig 12-7 DTE PLS Input Function....262
Fig 12-8 DTE PLS Error Sense Function....263
Fig 12-9 DTE PLS Carrier Sense Function....263
Fig 12-10 Examples of Manchester Waveforms....264
Fig 12-11 Examples of Collision Presence Waveforms....265

Documents
Document Sharing Hub
Full document details: ISO_IEC 8802-3_1992

FIGURES PAGE

Fig 12-12 Hub Relationship to the OSI Reference Model and the IEEE 802.3 CSMA/CD LAN Model....266
Fig 12-13 Hub PLS Upward Transfer Function....270
Fig 12-14 Hub PLS Jabber Function for Port X....271
Fig 12-15 Hub PLS Downward Transfer Function....272
Fig 12-16 Physical Medium Attachment Relationship to the OSI Reference Model and the IEEE 802.3 CSMA/CD LAN Model....275
Fig 12-17 Simulated Light Load....276
Fig 12-18 Simulated Heavy Load....276
Fig 12-19 Differential Output Voltage, Nominal Duration BT/2....277
Fig 12-20 Differential Output Voltage, Duration BT....277
Fig 12-21 Transmitter Waveform for Idle....279
Fig 12-22 Start-of-Idle Test Load #1....279
Fig 12-23 Start-of-Idle Test Load #2....279
Fig 12-24 Transmitter Impedance Balance....280
Fig 12-25 Common-Mode Output Voltage....281
Fig 12-26 Transmitter Common-Mode Tolerance....281
Fig 12-27 Common-Mode Impulse Test....282
Fig 12-28 Receiver Signal Envelope....283
Fig 12-29 Receiver Common-Mode Rejection....284
Fig 12-30 DTE and Hub Connector....286
Fig 12-31 Cable Connector....286
Fig 12-32 Cable Balance Test....289

TABLES

Table 8-1 Generation of Collision Presence Signal....122
Table 9-1 Maximum Allowable Timing Budget Contributions to the FOIRL System Timing Budget....182
Table 10-1 Generation of Collision Presence Signal....191
Table 11.2-1 Single-Cable Frequency Allocations (Frequencies in MHz)....231
Table 11.2-2 Dual-Cable Frequency Allocations (Frequencies in MHz)....232
Table 11.4-1 Broadband Dual-Cable Systems—Physical Layer Delay Budget....244
Table 11.5-1 Cable System Electrical Requirements....245
Table 11.6-1 Frequency Translator Requirements....245

ANNEX

Additional Reference Material....295

Documents
Document Sharing Hub
Full document details: ISO_IEC 8802-3_1992

APPENDIXES PAGE

A System Guidelines....297
B State Diagram, MAC Sublayer....309
C Application Context, Selected Medium Specifications....315
D Receiver Wavelength Design Considerations....317

APPENDIX FIGURES

Fig A1 Maximal System Configuration Bit Budget Apportionments....299
Fig A2 Typical Signal Waveforms....302
Fig A3 Worst-Case Signal Waveform Variations....302
Fig A4 MDNEXT Cumulative Probability Distribution....308
Fig B1 Transmit Component State Diagram....310
Fig B2 Receive Component State Diagram....313

APPENDIX TABLES

Table B1 Transmit Component State Transition....311
Table B2 Receive Component State Transition....313

Documents
Document Sharing Hub
Full document details: ISO_IEC 8802-3_1992

Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

Information technology—
Local and metropolitan area networks—

Part 3:
Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications

1. Introduction

1.1 Overview

1.1.1 Basic Concepts. The Carrier Sense Multiple Access with Collision Detection (CSMA/CD) media access method is the means by which two or more stations share a common transmission medium. To transmit, a station waits (defers) for a quiet period on the medium (that is, no other station is transmitting) and then sends the intended message in bit-serial form. If, after initiating a transmission, the message collides with that of another station, then each transmitting station intentionally sends a few additional bytes to ensure propagation of the collision throughout the system. The station remains silent for a random amount of time (backoff) before attempting to transmit again. Each aspect of this access method process is specified in detail in subsequent sections of this standard.

This is a comprehensive standard for Local Area Networks employing CSMA/CD as the access method. This standard is intended to encompass several media types and techniques for signal rates of from 1 Mb/s to 20 Mb/s. This edition of the standard provides the necessary specifications for 10 Mb/s baseband and broadband systems, a 1 Mb/s baseband system, and a Repeater Unit.

1.1.2 Architectural Perspectives. There are two important ways to view local area network design corresponding to

(1) *Architecture.* Emphasizing the logical divisions of the system and how they fit together.

(2) *Implementation.* Emphasizing actual components, their packaging and interconnection.

This standard is organized along architectural lines, emphasizing the large-scale separation of the system into two parts: the Media Access Control (MAC) sublayer of the Data Link Layer, and the Physical Layer. These layers

Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

are intended to correspond closely to the lowest layers of the ISO Model for Open Systems Interconnection (see Fig 1-1). See ISO 7498:1984 [10].[1] The Logical Link Control (LLC) sublayer and MAC sublayer together encompass the functions intended for the Data Link Layer as defined in the OSI model.

1.1.2.1 An architectural organization of the standard has two main advantages:


(1) *Clarity*. A clean overall division of the design along architectural lines makes the standard clearer.

(2) *Flexibility*. Segregation of medium-dependent aspects in the Physical Layer allows the LLC and MAC sublayers to apply to a family of transmission media.

Partitioning the Data Link Layer allows various media access methods within the family of Local Area Network standards.

The architectural model is based on a set of interfaces that may be different from those emphasized in implementations. One critical aspect of the design,

Fig 1-1
LAN Standard Relationship to the OSI Reference Model



[1] The numbers in brackets correspond to those of the references listed in 1.3; when preceded by A, they correspond to those listed in the Annex.

Documents
Document Sharing Hub
Full document details: ISO_IEC 8802-3_1992

however, shall be addressed largely in terms of the implementation interfaces: compatibility.

1.1.2.2 Two important compatibility interfaces are defined within what is architecturally the Physical Layer.

(1) *Medium-Dependent Interface (MDI).* To communicate in a compatible manner, all stations shall adhere rigidly to the exact specification of physical media signals defined in Section 8 (and beyond) in this standard, and to the procedures that define correct behavior of a station. The medium-independent aspects of the LLC sublayer and the MAC sublayer should not be taken as detracting from this point; communication by way of the ISO 8802-3 [IEEE 802.3] Local Area Network requires complete compatibility at the Physical Medium interface (that is, the coaxial cable interface).

(2) *Attachment Unit Interface (AUI).* It is anticipated that most DTEs will be located some distance from their connection to the coaxial cable. A small amount of circuitry will exist in the Medium Attachment Unit (MAU) directly adjacent to the coaxial cable, while the majority of the hardware and all of the software will be placed within the DTE. The AUI is defined as a second compatibility interface. While conformance with this interface is not strictly necessary to ensure communication, it is highly recommended, since it allows maximum flexibility in intermixing MAUs and DTEs. The AUI may be optional or not specified for some implementations of this standard that are expected to be connected directly to the medium and so do not use a separate MAU or its interconnecting AUI cable. The PLS and PMA are then part of a single unit, and no explicit AUI specification is required.

1.1.3 Layer Interfaces. In the architectural model used here, the layers interact by way of well defined interfaces, providing services as specified in Sections 2 and 6. In general, the interface requirements are as follows:

(1) The interface between the MAC sublayer and the LLC sublayer includes facilities for transmitting and receiving frames, and provides per-operation status information for use by higher-layer error recovery procedures.

(2) The interface between the MAC sublayer and the Physical Layer includes signals for framing (carrier sense, transmit initiation) and contention resolution (collision detect), facilities for passing a pair of serial bit streams (transmit, receive) between the two layers, and a wait function for timing.

These interfaces are described more precisely in 4.3. Additional interfaces are necessary to allow higher level network management facilities to interact with these layers to perform operation, maintenance, and planning functions. Network management functions will be discussed in Section 5.

1.1.4 Application Areas. The applications environment for the Local Area Network is intended to be commercial and light industrial. Use of CSMA/CD LANs in home or heavy industrial environments, while not precluded, is not considered within the scope of this standard.

1.2 Notation

1.2.1 State Diagram Conventions. The operation of a protocol can be described by subdividing the protocol into a number of interrelated functions.

AVA Documents
Document Sharing Hub
Full document details: ISO_IEC 8802-3_1992

The operation of the functions can be described by state diagrams. Each diagram represents the domain of a function and consists of a group of connected, mutually exclusive states. Only one state of a function is active at any given time (see Fig 1-2).


Each state that the function can assume is represented by a rectangle. These are divided into two parts by a horizontal line. In the upper part the state is identified by a name in capital letters. The lower part contains the name of any ON signal that is generated by the function. Actions are described by short phrases and enclosed in brackets.

All permissible transitions between the states of a function are represented graphically by arrows between them. A transition that is global in nature (for example, an exit condition from all states to the IDLE or RESET state) is indicated by an open arrow. Labels on transitions are qualifiers that must be fulfilled before the transition will be taken. The label UCT designates an unconditional transition. Qualifiers described by short phrases are enclosed in parentheses.

State transitions and sending and receiving of messages occur instantaneously. When a state is entered and the condition to leave that state is not immediately fulfilled, the state executes continuously, sending the messages and executing the actions contained in the state in a continuous manner.

Some devices described in this standard (e.g., repeaters) are allowed to have two or more ports. State diagrams capable of describing the operation of devices with an unspecified number of ports, required qualifier notation that

Fig 1-2
State Diagram Notation Example



Key: ( ) = condition, for example, (if no_collision)
[ ] = action, for example, [reset PLS functions]
* = logical AND
\+ = logical OR
Tw = Wait Time, implementation dependent
Td = Delay Timeout
Tb = Backoff Timeout
UCT = unconditional transition

Documents
Document Sharing Hub
Full document details: ISO_IEC 8802-3_1992

allows testing for conditions at multiple ports. The notation used is a term that includes a description in parentheses of which ports must meet the term for the qualifier to be satisfied (e.g., ANY and ALL). It is also necessary to provide for term-assignment statements that assign a name to a port that satisfies a qualifier. The following convention is used to describe a term-assignment statement that is associated with a transition:

(1) The character ":" (colon) is a delimiter used to denote that a term assignment statement follows.

(2) The character "⇐" (left arrow) denotes assignment of the value following the arrow to the term preceding the arrow.

The state diagrams contain the authoritative statement of the functions they depict; when apparent conflicts between descriptive text and state diagrams arise, the state diagrams are to take precedence. This does not override, however, any explicit description in the text that has no parallel in the state diagrams.

The models presented by state diagrams are intended as the primary specifications of the functions to be provided. It is important to distinguish, however, between a model and a real implementation. The models are optimized for simplicity and clarity of presentation, while any realistic implementation may place heavier emphasis on efficiency and suitability to a particular implementation technology. It is the functional behavior of any unit that must match the standard, not its internal structure. The internal details of the model are useful only to the extent that they specify the external behavior clearly and precisely.

1.2.2 Service Specification Method and Notation. The service of a layer or sublayer is the set of capabilities that it offers to a user in the next higher (sub)layer. Abstract services are specified here by describing the service primitives and parameters that characterize each service. This definition of service is independent of any particular implementation (see Fig 1-3).

Specific implementations may also include provisions for interface interactions that have no direct end-to-end effects. Examples of such local interactions include interface flow control, status requests and indications, error notifications, and layer management. Specific implementation details are omitted from this service specification both because they will differ from implementation to implementation and because they do not impact the peer-to-peer protocols.

1.2.2.1 Classification of Service Primitives. Primitives are of two generic types:

(1) REQUEST. The request primitive is passed from layer N to layer N-1 to request that a service be initiated.

(2) INDICATION. The indication primitive is passed from layer N-1 to layer N to indicate an internal layer N-1 event that is significant to layer N. This event may be logically related to a remote service request, or may be caused by an event internal to layer N-1.

The service primitives are an abstraction of the functional specification and the user-layer interaction. The abstract definition does not contain local

Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992




Fig 1-3
Service Primitive Notation

detail of the user/provider interaction. For instance, it does not indicate the local mechanism that allows a user to indicate that it is awaiting an incoming call. Each primitive has a set of zero or more parameters, representing data elements that shall be passed to qualify the functions invoked by the primitive. Parameters indicate information available in a user/provider interaction; in any particular interface, some parameters may be explicitly stated (even though not explicitly defined in the primitive) or implicitly associated with the service access point. Similarly, in any particular protocol specification, functions corresponding to a service primitive may be explicitly defined or implicitly available.

1.2.3 Physical Layer and Media Notation. Users of this standard need to reference which particular implementation is being used or identified. Therefore, a means of identifying each implementation is given by a simple, three-field, type notation that is explicitly stated at the beginning of each relevant section. In general, the Physical Layer type is specified by these fields:

<data rate in Mb/s> <medium type> <maximum segment length (x 100 m)>

For example, the standard contains a 10 Mb/s baseband specification identified as "TYPE 10BASE5," meaning a 10 Mb/s baseband medium whose maximum segment length is 500 m. Each successive Physical Layer specification will state its own unique TYPE identifier along similar lines.

1.2.4 Physical Layer Message Notation. Messages generated within the Physical Layer, either within or between PLS and the MAU (that is, PMA circuitry), are designated by an italic type to designate either form of physical or logical message used to execute the physical layer signaling process (for example, *input_idle* or *mau_available*).

Documents
Document Sharing Hub
Full document details: ISO_IEC 8802-3_1992

1.3 References

[1] CISPR Publication 22 (1985), Limits and Methods of Measurement of Radio Interference Characteristics of Information Technology Equipment.[2]

[2] IEC Publication 96-1, Radio-frequency cables, Part 1: General requirements and measuring methods.

[3] IEC Publication 96-1A, 1st Supplement to Radio-frequency cables, Part 1: Appendix Section 5.4, Terminated triaxial test method for transfer impedance up to 100 MHz.

[4] IEC Publication 169-8 and -16, Radio-frequency connectors, Part 8: Radio-frequency coaxial connectors with inner diameter of outer conductor 6.5 mm (0.256 in) with bayonet lock—Characteristic impedance 50 ohms (Type BNC); Part 16: Radio-frequency coaxial connectors with inner diameter of outer conductor 7 mm (0.276 in) with screw coupling—Characteristic impedance 50 ohms (75 ohms) (Type N).

[5] IEC Publication 380, Safety of electrically energized office machines.

[6] IEC Publication 435, Safety of data processing equipment.

[7] IEC Publication 807-2, Rectangular connectors for frequencies below 3 MHz, Part 2: Detail specification for a range of connectors with round contacts—Fixed solder contact types.

[8] IEC Publication 950, Safety of Information Technology Equipment, Including Electrical Business Equipment.

[9] ISO 2382-9 : 1984, Data processing—Vocabulary—Part 09: Data communication.[3]

[10] ISO 7498 : 1984, Information processing systems–open systems interconnection–Basic reference model.

[11] IEC Publication 60, High-voltage test techniques.

[12] IEC Publication 68, Environmental testing.

[13] IEC Publication 793-1, Optical fibres, Part 1: Generic specification.

[14] IEC Publication 793-2, Optical fibres, Part 2: Product specifications.[4]

---

[2] CISPR and IEC documents are available in the US from the Sales Department, American National Standards Institute, 11 West 42nd St., New York, NY 10018, USA. These documents are also available from International Electrotechnical Commission, 3 rue de Varembé, Case Postale 131, CH-1211, Genève 20, Switzerland/Suisse.

[3] ISO documents are available in the US from the Sales Department, American National Standards Institute, 11 West 42nd St., New York, NY 10018, USA. ISO documents are also available from ISO member bodies and from ISO Central Secretariat, 1 rue de Varembé, Case Postale 56, CH-1211, Genève 20, Switzerland/Suisse.

[4] Subsection 9.9 is to be read with the understanding that the following changes to IEC Publication 793-2 [14] have been requested:

(1) Correction of the numerical aperture tolerance in Table III to ± 0.015.

(2) Addition of another bandwidth category, of ≥ 150 MHz referred to 1 km, for the type A1b fiber in Table III.

Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

[15] IEC Publication 794-1, Optical fibre cables, Part 1: Generic specification.

[16] IEC Publication 794-2, Optical fibres cables, Part 2: Product specifications.

[17] IEC Publication 825, Radiation safety of laser products, equipment classification, requirements, and user's guide.

[18] IEC Publication 874-1, Connectors for optical fibres and cables, Part 1: Generic specification.

[19] IEC Publication 874-2, Connectors for optical fibres and cables, Part 2: Sectional specification for fibre optic connector type F-SMA.

Local and national standards such as those supported by ANSI, EIA, IEEE, MIL, NFPA, and UL are not a formal part of the ISO/IEC 8802-3 standard. Reference to such local or national standards may be useful resource material and are identified by a bracketed number beginning with the letter A and located in Annex A.

1.4 Definitions. The definitions used in this standard are consistent with ISO 2382-9:1984 [9]. A more specific Part 25, pertaining to LAN systems, is in development.

Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992


2. MAC Service Specification

2.1 Scope and Field of Application. This section specifies the services provided by the Media Access Control (MAC) sublayer to the Logical Link Control (LLC) sublayer for the ISO [IEEE] Local Area Network standard (see Fig 2-1). The services are described in an abstract way and do not imply any particular implementation, or any exposed interface. There is not necessarily a one-to-one correspondence between the primitives and the formal procedures and interfaces described in 4.2 and 4.3.

2.2 Overview of the Service

2.2.1 General Description of Services Provided by the Layer. The services

Fig 2-1
Service Specification Relation to the LAN Model



Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

provided by the MAC sublayer allow the local LLC sublayer entity to exchange LLC data units with peer LLC sublayer entities. Optional support may be provided for resetting the MAC sublayer entity to a known state.

2.2.2 Model Used for the Service Specification. The model used in this service specification is identical to that used in 1.2.

2.2.3 Overview of Interactions

MA_DATA.request
MA_DATA.indication

2.2.4 Basic Services and Options. The MA_DATA.request and MA_DATA.indication service primitives described in this section are considered mandatory.

2.3 Detailed Service Specification

2.3.1 MA_DATA.request

2.3.1.1 Function. This primitive defines the transfer of data from a local LLC sublayer entity to a single peer LLC entity or multiple peer LLC entities in the case of group addresses.

2.3.1.2 Semantics of the Service Primitive. The semantics of the primitive are as follows:

```
MA_DATA.request (
                 destination_address,
                 m_sdu,
                 service_class
                 )
```

The destination_address parameter may specify either an individual or a group MAC entity address. It must contain sufficient information to create the DA field that is appended to the frame by the local MAC sublayer entity and any physical information. The m_sdu parameter specifies the MAC service data unit to be transmitted by the MAC sublayer entity. There is sufficient information associated with m_sdu for the MAC sublayer entity to determine the length of the data unit. The service_class parameter indicates a quality of service requested by LLC or higher layer (see 2.3.1.5).

2.3.1.3 When Generated. This primitive is generated by the LLC sublayer entity whenever data shall be transferred to a peer LLC entity or entities. This can be in response to a request from higher protocol layers or from data generated internally to the LLC sublayer, such as required by Type 2 service.

2.3.1.4 Effect of Receipt. The receipt of this primitive will cause the MAC entity to append all MAC specific fields, including DA, SA, and any fields that are unique to the particular media access method, and pass the properly formed frame to the lower protocol layers for transfer to the peer MAC sublayer entity or entities.

AVA Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

2.3.1.5 Additional Comments. The CSMA/CD MAC protocol provides a single quality of service regardless of the service_class requested.

2.3.2 MA_DATA.indication

2.3.2.1 Function. This primitive defines the transfer of data from the MAC sublayer entity to the LLC sublayer entity or entities in the case of group addresses.

2.3.2.2 Semantics of the Service Primitive. The semantics of the primitive are as follows:

```
MA_DATA.indication  (
                    destination_address,
                    source_address,
                    m_sdu,
                    reception_status
                    )
```

The destination_address parameter may be either an individual or a group address as specified by the DA field of the incoming frame. The source_address parameter is an individual address as specified by the SA field of the incoming frame. The m_sdu parameter specifies the MAC service data unit as received by the local MAC entity. The reception_status parameter is used to pass status information to the peer LLC sublayer entity.

2.3.2.3 When Generated. The MA_DATA.indication is passed from the MAC sublayer entity to the LLC sublayer entity or entities to indicate the arrival of a frame to the local MAC sublayer entity. Such frames are reported only if they are validly formed, received without error, and their destination address designates the local MAC entity.

2.3.2.4 Effect of Receipt. The effect of receipt of this primitive by the LLC sublayer is unspecified.

2.3.2.5 Additional Comments. If the local MAC sublayer entity is designated by the destination_address parameter of an MA_DATA.request, the indication primitive will also be invoked by the MAC entity to the local LLC entity. This full duplex characteristic of the MAC sublayer may be due to unique functionality within the MAC sublayer or full duplex characteristics of the lower layers (for example, all frames transmitted to the broadcast address will invoke MA_DATA.indication at all stations in the network including the station that generated the request).

AVA Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

Documents
Document Sharing Hub


Full document details: ISO_IEC 8802-3_1992

3. Media Access Control Frame Structure

3.1 Overview. This section defines in detail the frame structure for data communication systems using local area network MAC procedures. It defines the relative positions of the various components of the MAC frame. It defines the method for representing station addresses. It defines a partition of the address space into individual (single station) and group (multicast or multistation) addresses, and into user administered and globally administered addresses.

3.1.1 MAC Frame Format. Figure 3-1 shows the eight fields of a frame: the preamble, Start Frame Delimiter (SFD), the addresses of the frame's source and destination, a length field to indicate the length of the following field

Fig 3-1
MAC Frame Format



Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

containing the LLC data to be transmitted, a field that contains padding if required, and the frame check sequence field containing a cyclic redundancy check value to detect errors in received frames. Of these eight fields, all are of fixed size except the LLC data and PAD fields, which may contain any integer number of octets between the minimum and maximum values determined by the specific implementation of the CSMA/CD Media Access mechanism. See 4.4 for particular implementations.

The minimum and maximum frame size limits in 4.4 refer to that portion of the frame from the destination address field through the frame check sequence field, inclusive.

Relative to Fig 3-1, the octets of a frame are transmitted from top to bottom, and the bits of each octet are transmitted from left to right.

3.2 Elements of the MAC Frame


3.2.1 Preamble Field. The preamble field is a 7-octet field that is used to allow the PLS circuitry to reach its steady-state synchronization with the received frame timing (see 4.2.5).

3.2.2 Start Frame Delimiter (SFD) Field. The SFD field is the sequence 10101011. It immediately follows the preamble pattern and indicates the start of a frame.

3.2.3 Address Fields. Each MAC frame shall contain two address fields: the Destination Address field and the Source Address field, in that order. The Destination Address field shall specify the destination addressee(s) for which the frame is intended. The Source Address field shall identify the station from which the frame was initiated. The representation of each address field shall be as follows (see Fig 3-2):

(1) Each address field shall contain either 16 bits or 48 bits. However, at any

Fig 3-2
Address Field Format



Documents
Document Sharing Hub
Full document details: ISO_IEC 8802-3_1992

given time, the Source and Destination Address size shall be the same for all stations on a particular local area network.

(2) The support of 16 or 48 bit address length for Source and Destination Address shall be left to the manufacturer as an implementation decision. There is no requirement that manufacturers support both sizes.

(3) The first bit (LSB) shall be used in the Destination Address field as an address type designation bit to identify the Destination Address either as an individual or as a group address. In the Source Address field, the first bit is reserved and set to 0. If this bit is 0, it shall indicate that the address field contains an individual address. If this bit is 1, it shall indicate that the address field contains a group address that identifies none, one or more, or all of the stations connected to the local area network.

(4) For 48 bit addresses, the second bit shall be used to distinguish between locally or globally administered addresses. For globally administered (or U, universal) addresses, the bit is set to 0. If an address is to be assigned locally, this bit shall be set to 1. Note that for the broadcast address, this bit is also a 1.

(5) Each octet of each address field shall be transmitted least significant bit first.

3.2.3.1 Address Designation. A MAC sublayer address is of one of two types:

(1) *Individual Address.* The address associated with a particular station on the network.

(2) *Group Address.* A multidestination address, associated with one or more stations on a given network. There are two kinds of multicast address:

(a) *Multicast-Group Address.* An address associated by higher-level convention with a group of logically related stations.

(b) *Broadcast Address.* A distinguished, predefined multicast address that always denotes the set of all stations on a given local area network.

All 1's in the Destination Address field (for 16 or 48 bit address size LANs) shall be predefined to be the Broadcast address. This group shall be predefined for each communication medium to consist of all stations actively connected to that medium; it shall be used to broadcast to all the active stations on that medium. All stations shall be able to recognize the Broadcast address. It is not necessary that a station be capable of generating the Broadcast address.

The address space shall also be partitioned into locally administered and globally administered addresses. The nature of a body and the procedures by which it administers these global (U) addresses is beyond the scope of this standard.[5]

3.2.4 Destination Address Field. The Destination Address field specifies the station(s) for which the frame is intended. It may be an individual or multicast (including broadcast) address.

---

[5] Information concerning the Registration Authority and its procedures may be obtained on request to the Secretary General, ISO Central Secretariat, Case Postale 56, CH-1211 Genève, Switzerland, quoting the number of this International Standard. The ISO Global (U) address administration has been delegated to the Secretary, IEEE Standards Board, 345 East 47 Street, New York, NY 10017.

AVA Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

3.2.5 Source Address Field. The Source Address field specifies the station sending the frame. The Source Address field is not interpreted by the CSMA/CD MAC sublayer.

3.2.6 Length Field. The length field is a 2-octet field whose value[6] indicates the number of LLC data octets in the data field. If the value is less than the minimum required for proper operation of the protocol, a PAD field (a sequence of octets) will be added at the end of the data field but prior to the FCS field, specified below. The procedure that determines the size of the pad field is specified in 4.2.8. The length field is transmitted and received with the high order octet first.

3.2.7 Data and PAD Fields. The data field contains a sequence of n octets. Full data transparency is provided in the sense that any arbitrary sequence of octet values may appear in the data field up to a maximum number specified by the implementation of this standard that is used. A minimum frame size is required for correct CSMA/CD protocol operation and is specified by the particular implementation of the standard. If necessary, the data field is extended by appending extra bits (that is, a pad) in units of octets after the LLC data field but prior to calculating and appending the FCS. The size of the pad, if any, is determined by the size of the data field supplied by LLC and the minimum frame size and address size parameters of the particular implementation. The maximum size of the data field is determined by the maximum frame size and address size parameters of the particular implementation.

The length of PAD field required for LLC data that is n octets long is max (0, minFrameSize – (8 x n + 2 x addressSize + 48)) bits. The maximum possible size of the LLC data field is maxFrameSize – (2 x addressSize + 48)/8 octets. See 4.4 for a discussion of implementation parameters; see 4.2.3.3 for a discussion of the minFrameSize.

3.2.8 Frame Check Sequence Field. A cyclic redundancy check (CRC) is used by the transmit and receive algorithms to generate a CRC value for the FCS field. The frame check sequence (FCS) field contains a 4-octet (32-bit) cyclic redundancy check (CRC) value. This value is computed as a function of the contents of the source address, destination address, length, LLC data and pad (that is, all fields except the preamble, SFD, and FCS). The encoding is defined by the following generating polynomial.

$$G(x) = x^{32} + x^{26} + x^{23} + x^{22} + x^{16} + x^{12} + x^{11} + x^{10} + x^8 + x^7 + x^5 + x^4 + x^2 + x + 1$$

Mathematically, the CRC value corresponding to a given frame is defined by the following procedure:

(1) The first 32 bits of the frame are complemented.

(2) The n bits of the frame are then considered to be the coefficients of a polynomial M(x) of degree n-1. (The first bit of the Destination Address field cor-

[6] Packets with a length field value greater than those specified in 4.4.2 may be ignored, discarded, or used in a private manner. The use of such packets is beyond the scope of this standard.

Documents
Document Sharing Hub
Full document details: ISO_IEC 8802-3_1992

responds to the $x^{(n-1)}$ term and the last bit of the data field corresponds to the x^0 term.)

(3) M(x) is multiplied by x^{32} and divided by G(x), producing a remainder R(x) of degree <31.

(4) The coefficients of R(x) are considered to be a 32-bit sequence.

(5) The bit sequence is complemented and the result is the CRC.

The 32 bits of the CRC value are placed in the frame check sequence field so that the x^{31} term is the left-most bit of the first octet, and the x^0 term is the right-most bit of the last octet. (The bits of the CRC are thus transmitted in the order $x^{31}, x^{30}, \ldots, x^1, x^0$.) See reference [A18].

3.3 Order of Bit Transmission. Each octet of the MAC frame, with the exception of the FCS, is transmitted low-order bit first.


3.4 Invalid MAC Frame. An invalid MAC frame shall be defined as one that meets at least one of the following conditions:

(1) The frame length is inconsistent with the length field.

(2) It is not an integral number of octets in length.

(3) The bits of the incoming frame (exclusive of the FCS field itself) do not generate a CRC value identical to the one received.

The contents of invalid MAC frames shall not be passed to LLC. The occurrence of invalid MAC frames may be communicated to network management.



Key:
( ) = condition, for example, (if no_collision)
[ ] = *action, for example, [reset PLS functions]*
* = logical AND
\+ = logical OR
Tw = Wait Time, implementation dependent
Td = Delay Timeout
Tb = *Backoff Timeout*
UCT = unconditional transition

Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992

Documents
Document Sharing Hub

Full document details: ISO_IEC 8802-3_1992