INTERNATIONAL STANDARD

ISO/IEC 8825-2

Sixth edition
2021-06

Information technology — ASN.1 encoding rules —

Part 2: Specification of Packed Encoding Rules (PER)

Technologies de l'information — Règles de codage ASN.1 — Partie 2: Spécification des règles de codage compact (PER)

Reference number
ISO/IEC 8825-2:2021(E)

Documents
Document Sharing Hub

© ISO/IEC 2021

Full document details: ISO_IEC 8825-2_2021

COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

© ISO/IEC 2021 – All rights reserved

Documents
Document Sharing Hub

Full document details: ISO_IEC 8825-2_2021

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives or www.iec.ch/members_experts/refdocs)

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see patents.iec.ch).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems,* in collaboration with ITU-T. The identical text is published as ITU-T X.691 (02/2021).

This sixth edition cancels and replaces the fifth edition (ISO/IEC 8825-2:2015), which has been technically revised. It also incorporates ISO/IEC 8825-2:2015/Cor 1:2017.

A list of all parts in the ISO/IEC 8825 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

© ISO/IEC 2021 – All rights reserved

Documents
Document Sharing Hub
Full document details: ISO_IEC 8825-2_2021

Documents
Document Sharing Hub

Full document details: ISO_IEC 8825-2_2021

CONTENTS

		Page
Introduction		vi
1	Scope	1
2	Normative references	1
	2.1 Identical Recommendations | International Standards	1
	2.2 Additional references	1
3	Definitions	2
	3.1 Specification of Basic Notation	2
	3.2 Information Object Specification	2
	3.3 Constraint Specification	2
	3.4 Parameterization of ASN.1 Specification	2
	3.5 Basic Encoding Rules	2
	3.6 PER Encoding Instructions	2
	3.7 Additional definitions	2
4	Abbreviations	5
5	Notation	5
6	Convention	5
7	Encoding rules defined in this Recommendation | International Standard	5
8	Conformance	6
9	PER encoding instructions	6
10	The approach to encoding used for PER	7
	10.1 Use of the type notation	7
	10.2 Use of tags to provide a canonical order	7
	10.3 PER-visible constraints	7
	10.4 Type and value model used for encoding	9
	10.5 Structure of an encoding	9
	10.6 Types to be encoded	10
11	Encoding procedures	10
	11.1 Production of the complete encoding	10
	11.2 Open type fields	11
	11.3 Encoding as a non-negative-binary-integer	11
	11.4 Encoding as a 2's-complement-binary-integer	12
	11.5 Encoding of a constrained whole number	12
	11.6 Encoding of a normally small non-negative whole number	13
	11.7 Encoding of a semi-constrained whole number	13
	11.8 Encoding of an unconstrained whole number	13
	11.9 General rules for encoding a length determinant	14
12	Encoding the boolean type	16
13	Encoding the integer type	16
14	Encoding the enumerated type	17
15	Encoding the real type	18
16	Encoding the bitstring type	18
17	Encoding the octetstring type	19
18	Encoding the null type	19
19	Encoding the sequence type	19
20	Encoding the sequence-of type	20
21	Encoding the set type	21
22	Encoding the set-of type	21
23	Encoding the choice type	21

© ISO/IEC 2021 – All rights reserved

Documents
Document Sharing Hub
Full document details: ISO_IEC 8825-2_2021

24 Encoding the object identifier type 22
25 Encoding the relative object identifier type 22
26 Encoding the internationalized resource reference type 22
27 Encoding the relative internationalized resource reference type 23
28 Encoding the embedded-pdv type 23
29 Encoding of a value of the external type 23
30 Encoding the restricted character string types 24
31 Encoding the unrestricted character string type 26
32 Encoding the time type, the useful time types, the defined time types and the additional time types 26
32.1 General 26
32.2 Encoding subtypes with the "`Basic=Date`" property setting 30
32.3 Encoding subtypes with the "`Basic=Time`" property setting 32
32.4 Encoding subtypes with the "`Basic=Date-Time`" property setting 35
32.5 Encoding subtypes with the "`Basic=Interval Interval-type=SE`" property setting 35
32.6 Encoding subtypes with the "`Basic=Interval Interval-type=D`" property setting 36
32.7 Encoding subtypes with the "`Basic=Interval Interval-type=SD`" or "`Basic=Interval Interval-type=DE`" property setting 37
32.8 Encoding subtypes with the "`Basic=Rec-Interval Interval-type=SE`" property setting 38
32.9 Encoding subtypes with the "`Basic=Rec-Interval Interval-type=D`" property setting 38
32.10 Encoding subtypes with the "`Basic=Rec-Interval Interval-type=SD`" or "`Basic=Rec-Interval Interval-type=DE`" property setting 39
32.11 Encoding subtypes with mixed settings of the `Basic` property 40
33 Object identifiers for transfer syntaxes 42
Annex A – Example of encodings 43
A.1 Record that does not use subtype constraints 43
A.1.1 ASN.1 description of the record structure 43
A.1.2 ASN.1 description of a record value 43
A.1.3 ALIGNED PER representation of this record value 43
A.1.4 UNALIGNED PER representation of this record value 44
A.2 Record that uses subtype constraints 46
A.2.1 ASN.1 description of the record structure 46
A.2.2 ASN.1 description of a record value 46
A.2.3 ALIGNED PER representation of this record value 46
A.2.4 UNALIGNED PER representation of this record value 47
A.3 Record that uses extension markers 48
A.3.1 ASN.1 description of the record structure 48
A.3.2 ASN.1 description of a record value 49
A.3.3 ALIGNED PER representation of this record value 49
A.3.4 UNALIGNED PER representation of this record value 50
A.4 Record that uses extension addition groups 52
A.4.1 ASN.1 description of the record structure 52
A.4.2 ASN.1 description of a record value 52
A.4.3 ALIGNED PER representation of this record value 52
A.4.4 UNALIGNED PER representation of this record value 53
Annex B – Combining PER-visible and non-PER-visible constraints 54
B.1 General 54
B.2 Extensibility and visibility of constraints in PER 54
B.2.1 General 54
B.2.2 PER-visibility of constraints 55
B.2.3 Effective constraints 56
B.3 Examples 57

© ISO/IEC 2021 – All rights reserved
Documents
Document Sharing Hub
Full document details: ISO_IEC 8825-2_2021

Annex C – Support for the PER algorithms 59
Annex D – Support for the ASN.1 rules of extensibility 60
Annex E – Tutorial annex on concatenation of PER encodings 61
Annex F – Identification of Encoding Rules 62

© ISO/IEC 2021 – All rights reserved

Documents
Document Sharing Hub
Full document details: ISO_IEC 8825-2_2021

Introduction

Specifications Rec. ITU-T X.680 | ISO/IEC 8824-1, Rec. ITU-T X.681 | ISO/IEC 8824-2, Rec. ITU-T X.682 | ISO/IEC 8824-3, Rec. ITU-T X.683 | ISO/IEC 8824-4 together describe Abstract Syntax Notation One (ASN.1), a notation for the definition of messages to be exchanged between peer applications.

This Recommendation | International Standard defines encoding rules that may be applied to values of types defined using the notation specified in Rec. ITU-T X.680 | ISO/IEC 8824-1. Application of these encoding rules produces a transfer syntax for such values. It is implicit in the specification of these encoding rules that they are also to be used for decoding.

There are more than one set of encoding rules that can be applied to values of ASN.1 types. This Recommendation | International Standard defines a set of Packed Encoding Rules (PER), so called because they achieve a much more compact representation than that achieved by the Basic Encoding Rules (BER) and its derivatives described in Rec. ITU-T X.690 | ISO/IEC 8825-1 which is referenced for some parts of the specification of these Packed Encoding Rules.

© ISO/IEC 2021 – All rights reserved
Documents
Document Sharing Hub
Full document details: ISO_IEC 8825-2_2021

INTERNATIONAL STANDARD
ITU-T RECOMMENDATION

Information technology – ASN.1 encoding rules: Specification of Packed Encoding Rules (PER)

1 Scope

This Recommendation | International Standard specifies a set of Packed Encoding Rules that may be used to derive a transfer syntax for values of types defined in Rec. ITU-T X.680 | ISO/IEC 8824-1. These Packed Encoding Rules are also to be applied for decoding such a transfer syntax in order to identify the data values being transferred.

The encoding rules specified in this Recommendation | International Standard:

- are used at the time of communication;
- are intended for use in circumstances where minimizing the size of the representation of values is the major concern in the choice of encoding rules;
- allow the extension of an abstract syntax by addition of extra values, preserving the encodings of the existing values, for all forms of extension described in Rec. ITU-T X.680 | ISO/IEC 8824-1;
- can be modified in accordance with the provisions of Rec. ITU-T X.695 | ISO/IEC 8825-6.

2 Normative references

The following Recommendations and International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | International Standard. At the time of publication, the editions indicated were valid. All Recommendations and Standards are subject to revision, and parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent edition of the Recommendations and Standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards. The Telecommunication Standardization Bureau of the ITU maintains a list of currently valid ITU-T Recommendations.

NOTE – This Recommendation | International Standard is based on ISO/IEC 10646:2003. It cannot be applied using later versions of this standard.

2.1 Identical Recommendations | International Standards

- Recommendation ITU-T X.680 (2021) | ISO/IEC 8824-1:2021, *Information technology – Abstract Syntax Notation One (ASN.1): Specification of basic notation*.
- Recommendation ITU-T X.681 (2021) | ISO/IEC 8824-2:2021, *Information technology – Abstract Syntax Notation One (ASN.1): Information object specification*.
- Recommendation ITU-T X.682 (2021) | ISO/IEC 8824-3:2021, *Information technology – Abstract Syntax Notation One (ASN.1): Constraint specification.*
- Recommendation ITU-T X.683 (2021) | ISO/IEC 8824-4:2021, *Information technology – Abstract Syntax Notation One (ASN.1): Parameterization of ASN.1 specifications*.
- Recommendation ITU-T X.690 (2021) | ISO/IEC 8825-1:2021, *Information technology – ASN.1 encoding rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER).*
- Recommendation ITU-T X.695 (2021) | ISO/IEC 8825-6:2021, *Information technology – ASN.1 encoding rules: Registration and application of PER encoding instructions.*

NOTE – The references above shall be interpreted as references to the identified Recommendations | International Standards together with all their published amendments and technical corrigenda.

2.2 Additional references

- ISO/IEC 646:1991, *Information technology – ISO 7-bit coded character set for information interchange*.
- ISO/IEC 2022:1994, *Information technology – Character code structure and extension techniques*.
- ISO/IEC 2375:2003, *Information technology – Procedure for registration of escape sequences and coded character sets.*

© ISO/IEC 2021 – All rights reserved

Documents
Document Sharing Hub
Full document details: ISO_IEC 8825-2_2021

– ISO 6093:1985, *Information processing – Representation of numerical values in character strings for information interchange.*

– *ISO International Register of Coded Character Sets to be Used with Escape Sequences.*

– ISO/IEC 10646:2003, *Information technology – Universal Multiple-Octet Coded Character Set (UCS).*

3 Definitions

For the purposes of this Recommendation | International Standard, the following definitions apply.

3.1 Specification of Basic Notation

For the purposes of this Recommendation | International Standard, all the definitions in Rec. ITU-T X.680 | ISO/IEC 8824-1 apply.

3.2 Information Object Specification

For the purposes of this Recommendation | International Standard, all the definitions in Rec. ITU-T X.681 | ISO/IEC 8824-2 apply.

3.3 Constraint Specification

This Recommendation | International Standard makes use of the following terms defined in Rec. ITU-T X.682 | ISO/IEC 8824-3:

a) component relation constraint;

b) table constraint.

3.4 Parameterization of ASN.1 Specification

This Recommendation | International Standard makes use of the following term defined in Rec. ITU-T X.683 | ISO/IEC 8824-4:

– variable constraint.

3.5 Basic Encoding Rules

This Recommendation | International Standard makes use of the following terms defined in Rec. ITU-T X.690 | ISO/IEC 8825-1:

a) data value;

b) dynamic conformance;

c) encoding (of a data value);

d) receiver;

e) sender;

f) static conformance.

3.6 PER Encoding Instructions

This Recommendation | International Standard makes use of the following term defined in Rec. ITU-T X.695 | ISO/IEC 8825-6:

– identifying keyword.

3.7 Additional definitions

For the purposes of this Recommendation | International Standard, the following definitions apply.

3.7.1 2's-complement-binary-integer encoding: The encoding of a whole number into a bit-field (octet-aligned in the ALIGNED variant) of a specified length, or into the minimum number of octets that will accommodate that whole number encoded as a 2's-complement-integer, which provides representations for whole numbers that are equal to, greater than, or less than zero, as specified in 11.4.

© ISO/IEC 2021 – All rights reserved
Documents
Document Sharing Hub
Full document details: ISO_IEC 8825-2_2021

NOTE 1 – The value of a two's complement binary number is derived by numbering the bits in the contents octets, starting with bit 1 of the last octet as bit zero and ending the numbering with bit 8 of the first octet. Each bit is assigned a numerical value of 2^N, where N is its position in the above numbering sequence. The value of the two's complement binary number is obtained by summing the numerical values assigned to each bit for those bits which are set to one, excluding bit 8 of the first octet, and then reducing this value by the numerical value assigned to bit 8 of the first octet if that bit is set to one.

NOTE 2 – *Whole number* is a synonym for the mathematical term *integer*. It is used here to avoid confusion with the ASN.1 type *integer*.

3.7.2 abstract syntax value: A value of an abstract syntax (defined as the set of values of a single ASN.1 type), which is to be encoded by PER, or which is to be generated by PER decoding.

NOTE – The single ASN.1 type associated with an abstract syntax is formally identified by an object of class **ABSTRACT-SYNTAX**.

3.7.3 bit-field: The product of some part of the encoding mechanism that consists of an ordered set of bits that are not necessarily a multiple of eight.

NOTE – If the use of this term is followed by "octet-aligned in the ALIGNED variant", this means that the bit-field is required to begin on an octet boundary in the complete encoding for the aligned variant of PER.

3.7.4 canonical encoding: A complete encoding of an abstract syntax value obtained by the application of encoding rules that have no implementation-dependent options; such rules result in the definition of a 1-1 mapping between unambiguous and unique bitstrings in the transfer syntax and values in the abstract syntax.

3.7.5 composite type: A set, sequence, set-of, sequence-of, choice, embedded-pdv, external or unrestricted character string type.

3.7.6 composite value: The value of a composite type.

3.7.7 constrained whole number: A whole number which is constrained by PER-visible constraints to lie within a range from "lb" to "ub" with the value "lb" less than or equal to "ub", and the values of "lb" and "ub" as permitted values.

NOTE – Constrained whole numbers occur in the encoding which identifies the chosen alternative of a choice type, the length of character, octet and bit string types whose length has been restricted by PER-visible constraints to a maximum length, the count of the number of components in a sequence-of or set-of type that has been restricted by PER-visible constraints to a maximum number of components, the value of an integer type that has been constrained by PER-visible constraints to lie within finite minimum and maximum values, and the value that denotes an enumeration in an enumerated type.

3.7.8 effective size constraint (for a constrained string type): A single finite size constraint that could be applied to a built-in string type and whose effect would be to permit all and only those lengths that can be present in the constrained string type.

NOTE 1 – For example, the following has an effective size constraint:

```
A ::= IA5String (SIZE(1..4) | SIZE(10..15))
```

since it can be rewritten with a single size constraint that applies to all values:

```
A ::= IA5String (SIZE(1..4 | 10..15))
```

whereas the following has no effective size constraint since the string can be arbitrarily long if it does not contain any characters other than 'a', 'b' and 'c':

```
B ::= IA5String (SIZE(1..4) | FROM("abc"))
```

NOTE 2 – The effective size constraint is used only to determine the encoding of lengths.

3.7.9 effective permitted-alphabet constraint (for a constrained restricted character string type): A single permitted-alphabet constraint that could be applied to a built-in known-multiplier character string type and whose effect would be to permit all and only those characters that can be present in at least one character position of any one of the values in the constrained restricted character string type.

NOTE 1 – For example, in:

```
Ax ::= IA5String (FROM("AB") | FROM("CD"))
Bx ::= IA5String (SIZE(1..4) | FROM("abc"))
```

Ax has an effective permitted-alphabet constraint of **"ABCD"**. **Bx** has an effective permitted-alphabet constraint that consists of the entire **IA5String** alphabet since there is no smaller permitted-alphabet constraint that applies to all values of **Bx**.

NOTE 2 – The effective permitted-alphabet constraint is used only to determine the encoding of characters.

3.7.10 enumeration index: The non-negative whole number associated with an "EnumerationItem" in an enumerated type. The enumeration indices are determined by sorting the "EnumerationItem"s into ascending order by their enumeration value, then by assigning an enumeration index starting with zero for the first "EnumerationItem", one for the second, and so on up to the last "EnumerationItem" in the sorted list.

NOTE – "EnumerationItem"s in the "RootEnumeration" are sorted separately from those in the "AdditionalEnumeration".

3.7.11 extensible for PER encoding: A property of a type which requires that PER identifies an encoding of a value as that of a root value or as that of an extension addition.

NOTE – Root values are normally encoded more efficiently than extension additions.

© ISO/IEC 2021 – All rights reserved

Documents
Document Sharing Hub
Full document details: ISO_IEC 8825-2_2021

3.7.12 field-list: An ordered set of bit-fields that is produced as a result of applying these encoding rules to components of an abstract value.

3.7.13 indefinite-length: An encoding whose length is greater than 64K-1 or whose maximum length cannot be determined from the ASN.1 notation.

3.7.14 fixed-length type: A type such that the value of the outermost length determinant in an encoding of this type can be determined (using the mechanisms specified in this Recommendation | International Standard) from the type notation (after the application of PER-visible constraints only) and is the same for all possible values of the type.

3.7.15 fixed value: A value such that it can be determined (using the mechanisms specified in this Recommendation | International Standard) that this is the only permitted value (after the application of PER-visible constraints only) of the type governing it.

3.7.16 known-multiplier character string type: A restricted character string type where the number of octets in the encoding is a known fixed multiple of the number of characters in the character string for all permitted character string values. The known-multiplier character string types are **`IA5String`**, **`PrintableString`**, **`VisibleString`**, **`NumericString`**, **`UniversalString`** and **`BMPString`**.

3.7.17 length determinant: A count (of bits, octets, characters, or components) determining the length of part or all of a PER encoding.

3.7.18 normally small non-negative whole number: A part of an encoding which represents values of an unbounded non-negative integer, but where small values are more likely to occur than large ones.

3.7.19 normally small length: A length encoding which represents values of an unbounded length, but where small lengths are more likely to occur than large ones.

3.7.20 non-negative-binary-integer encoding: The encoding of a constrained or semi-constrained whole number into either a bit-field of a specified length, or into a bit-field (octet-aligned in the ALIGNED variant) of a specified length, or into the minimum number of octets that will accommodate that whole number encoded as a non-negative-binary-integer which provides representations for whole numbers greater than or equal to zero, as specified in 11.3.

NOTE – The value of a non-negative-binary-number is derived by numbering the bits in the contents octets, starting with bit 1 of the last octet as bit zero and ending the numbering with bit 8 of the first octet. Each bit is assigned a numerical value of 2^N, where N is its position in the above numbering sequence. The value of the non-negative-binary-number is obtained by summing the numerical values assigned to each bit for those bits which are set to one.

3.7.21 outermost type: An ASN.1 type whose encoding is included in a non-ASN.1 carrier or as the value of other ASN.1 constructs (see 11.1.1).

NOTE – PER encodings of an outermost type are always an integral multiple of eight bits.

3.7.22 PER-visible constraint: An instance of use of the ASN.1 constraint notation which affects the PER encoding of a value.

3.7.23 relay-safe encoding: A complete encoding of an abstract syntax value which can be decoded (including any embedded encodings) without knowledge of the environment in which the encoding was performed.

3.7.24 semi-constrained whole number: A whole number which is constrained by PER-visible constraints to exceed or equal some value "lb" with the value "lb" as a permitted value, and which is not a constrained whole number.

NOTE – Semi-constrained whole numbers occur in the encoding of the length of unconstrained (and in some cases constrained) character, octet and bit string types, the count of the number of components in unconstrained (and in some cases constrained) sequence-of and set-of types, and the value of an integer type that has been constrained to exceed some minimum value.

3.7.25 simple type: A type that is not a composite type.

3.7.26 textually dependent: A term used to identify the case where if some reference name is used in evaluating an element set, the value of the element set is considered to be dependent on that reference name, regardless of whether the actual set arithmetic being performed is such that the final value of the element set is independent of the actual element set value assigned to the reference name.

NOTE – For example, the following definition of **`Foo`** is textually dependent on **`Bar`** even though **`Bar`** has no effect on **`Foo`**s set of values (thus, according to 10.3.6 the constraint on **`Foo`** is not PER-visible since **`Bar`** is constrained by a table constraint and **`Foo`** is textually dependent on **`Bar`**).

```
MY-CLASS ::= CLASS { &name PrintableString, &age INTEGER } WITH SYNTAX{&name , &age}
MyObjectSet MY-CLASS ::= { {"Jack", 7} | {"Jill", 5} }
Bar ::= MY-CLASS.&age ({MyObjectSet})
Foo ::= INTEGER (Bar | 1..100)
```

3.7.27 unconstrained whole number: A whole number which is not constrained by PER-visible constraints.

NOTE – Unconstrained whole numbers occur only in the encoding of a value of the integer type.

© ISO/IEC 2021 – All rights reserved
Documents Document Sharing Hub
Full document details: ISO_IEC 8825-2_2021

4 Abbreviations

For the purposes of this Recommendation | International Standard, the following abbreviations apply:

ASN.1	Abstract Syntax Notation One
BER	Basic Encoding Rules of ASN.1
CER	Canonical Encoding Rules of ASN.1
DER	Distinguished Encoding Rules of ASN.1
PER	Packed Encoding Rules of ASN.1
16K	16384
32K	32768
48K	49152
64K	65536

5 Notation

This Recommendation | International Standard references the notation defined by Rec. ITU-T X.680 | ISO/IEC 8824-1.

6 Convention

6.1 This Recommendation | International Standard defines the value of each octet in an encoding by use of the terms "most significant bit" and "least significant bit".

NOTE – Lower layer specifications use the same notation to define the order of bit transmission on a serial line, or the assignment of bits to parallel channels.

6.2 For the purposes of this Recommendation | International Standard, the bits of an octet are numbered from 8 to 1, where bit 8 is the "most significant bit" and bit 1 the "least significant bit".

6.3 The term "octet" is frequently used in this Recommendation | International Standard to stand for "eight bits". The use of this term in place of "eight bits" does not carry any implications of alignment. Where alignment is intended, it is explicitly stated in this Recommendation | International Standard.

7 Encoding rules defined in this Recommendation | International Standard

7.1 This Recommendation | International Standard specifies four encoding rules (together with their associated object identifiers) which can be used to encode and decode the values of an abstract syntax defined as the values of a single (known) ASN.1 type. This clause describes their applicability and properties.

7.2 Without knowledge of the type of the value encoded, it is not possible to determine the structure of the encoding (under any of the PER encoding rule algorithms). In particular, the end of the encoding cannot be determined from the encoding itself without knowledge of the type being encoded.

7.3 PER encodings are always relay-safe provided the abstract values of the types **EXTERNAL**, **EMBEDDED PDV** and **CHARACTER STRING** are constrained to prevent the carriage of OSI presentation context identifiers.

7.4 The most general encoding rule algorithm specified in this Recommendation | International Standard is BASIC-PER, which does not in general produce a canonical encoding.

7.5 A second encoding rule algorithm specified in this Recommendation | International Standard is CANONICAL-PER, which produces encodings that are canonical. This is defined as a restriction of implementation-dependent choices in the BASIC-PER encoding.

NOTE 1 – CANONICAL-PER produces canonical encodings that have applications when authenticators need to be applied to abstract values.

NOTE 2 – Any implementation conforming to CANONICAL-PER for encoding is conformant to BASIC-PER for encoding. Any implementation conforming to BASIC-PER for decoding is conformant to CANONICAL-PER for decoding. Thus, encodings made according to CANONICAL-PER are encodings that are permitted by BASIC-PER.

7.6 If a type encoded with BASIC-PER or CANONICAL-PER contains **EMBEDDED PDV**, **CHARACTER STRING** or **EXTERNAL** types, then the outer encoding ceases to be relay-safe unless the transfer syntax used for all the **EMBEDDED PDV**, **CHARACTER STRING** and **EXTERNAL** types is relay safe. If a type encoded with CANONICAL-PER contains

© ISO/IEC 2021 – All rights reserved

Documents
Document Sharing Hub
Full document details: ISO_IEC 8825-2_2021

EMBEDDED PDV, **EXTERNAL** or **CHARACTER STRING** types, then the outer encoding ceases to be canonical unless the transfer syntax used for all the **EMBEDDED PDV**, **EXTERNAL** and **CHARACTER STRING** types is canonical.

NOTE – The character transfer syntaxes supporting all character abstract syntaxes of the form **{iso standard 10646 level-1(1) ....}** are canonical. Those supporting **{iso standard 10646 level-2(2) ....}** and **{iso standard 10646 level-3(3) ....}** are not always canonical. All the above character transfer syntaxes are relay-safe.

7.7 Both BASIC-PER and CANONICAL-PER come in two variants, the ALIGNED variant, and the UNALIGNED variant. In the ALIGNED variant, padding bits are inserted from time to time to restore octet alignment. In the UNALIGNED variant, no padding bits are ever inserted.

7.8 There are no interworking possibilities between the ALIGNED variant and the UNALIGNED variant.

7.9 PER encodings are self-delimiting only with knowledge of the type of the encoded value. Encodings are always a multiple of eight bits. When carried in an **EXTERNAL** type they shall be carried in the **OCTET STRING** choice alternative, unless the **EXTERNAL** type itself is encoded in PER, in which case the value may be encoded as a single ASN.1 type (i.e., an open type). When carried in OSI presentation protocol, the "full encoding" (as defined in Rec. ITU-T X.226 | ISO/IEC 8823-1) with the **OCTET STRING** choice alternative shall be used.

7.10 The rules of this Recommendation | International Standard apply to both algorithms and to both variants unless otherwise stated (but see 9.2 and 9.3).

7.11 Annex C is informative, and gives recommendations on which combinations of PER to implement in order to maximize the chances of interworking.

8 Conformance

8.1 Dynamic conformance is specified by clause 9 onwards.

8.2 Static conformance is specified by those standards which specify the application of these Packed Encoding Rules.

NOTE – Annex C provides guidance on static conformance in relation to support for the two variants of the two encoding rule algorithms. This guidance is designed to ensure interworking, while recognizing the benefits to some applications of encodings that are neither relay-safe nor canonical.

8.3 The rules in this Recommendation | International Standard are specified in terms of an encoding procedure. Implementations are not required to mirror the procedure specified, provided the bit string produced as the complete encoding of an abstract syntax value is identical to one of those specified in this Recommendation | International Standard for the applicable transfer syntax.

8.4 Implementations performing decoding are required to produce the abstract syntax value corresponding to any received bit string which could be produced by a sender conforming to the encoding rules identified in the transfer syntax associated with the material being decoded.

NOTE 1 – In general there are no alternative encodings defined for the BASIC-PER explicitly stated in this Recommendation | International Standard. The BASIC-PER becomes canonical by specifying relay-safe operation and by restricting some of the encoding options of other ISO/IEC Standards that are referenced. CANONICAL-PER provides an alternative to both the Distinguished Encoding Rules and Canonical Encoding Rules (see Rec. ITU-T X.690 | ISO/IEC 8825-1) where a canonical and relay-safe encoding is required.

NOTE 2 – When CANONICAL-PER is used to provide a canonical encoding, it is recommended that any resulting encrypted hash value that is derived from it should have associated with it an algorithm identifier that identifies CANONICAL-PER as the transformation from the abstract syntax value to an initial bitstring (which is then hashed).

9 PER encoding instructions

9.1 PER encoding instructions can be associated with a type in accordance with the provisions of Rec. ITU-T X.680 | ISO/IEC 8824-1 and Rec. ITU-T X.695 | ISO/IEC 8825-6.

NOTE 1 – The application of some PER encoding instructions can make it impossible to encode all the abstract values of the type. Where this can arise, the specific PER encoding instruction identifies the problem. It is a designers decision, based on the possible need to use multiple encoding rules, whether to add an explicit constraint on the type in order to restrict the range of abstract values to those that can be handled by the encoding using the PER encoding instruction. This can make the specification less readable, but ensures that all encoding rules can encode all allowed abstract values, making relaying possible without errors.

NOTE 2 – Each PER encoding instruction starts with an identifying keyword that unambiguously identifies that encoding instruction.

9.2 If the ALIGNED version of either BASIC-PER or CANONICAL-PER is in use, then all PER encoding instructions shall be silently ignored and have no affect on the encoding.

© ISO/IEC 2021 – All rights reserved
Documents Document Sharing Hub
Full document details: ISO_IEC 8825-2_2021

9.3 If the UNALIGNED version of either BASIC-PER or CANONICAL-PER is in use, then if a type has an associated encoding instruction, the following subclauses shall apply.

9.3.1 If the identifying keyword is not known, then a "not supported" error message shall be issued.

9.3.2 If the identifying keyword is known, the procedures of this Recommendation | International Standard shall be modified by the amendments to those procedures that are specified by the PER encoding instruction (see Rec. ITU-T X.695 | ISO/IEC 8825-6).

NOTE 1 – If multiple PER encoding instructions are associated with a type, then the amendments specified for all of them shall be applied.

NOTE 2 – It is an error in the register of PER encoding instructions if amendments produced by two or more separate encoding instructions conflict and it is not stated that they are mutually exclusive.

10 The approach to encoding used for PER

10.1 Use of the type notation

10.1.1 These encoding rules make specific use of the ASN.1 type notation as specified in Rec. ITU-T X.680 | ISO/IEC 8824-1, and can only be applied to encode the values of a single ASN.1 type specified using that notation.

10.1.2 In particular, but not exclusively, they are dependent on the following information being retained in the ASN.1 type and value model underlying the use of the notation:

a) the nesting of choice types within choice types;

b) the tags placed on the components in a set type, and on the alternatives in a choice type, and the values given to an enumeration;

c) whether a set or sequence type component is optional or not;

d) whether a set or sequence type component has a **DEFAULT** value or not;

e) the restricted range of values of a type which arise through the application of PER-visible constraints (only);

f) whether a component is an open type;

g) whether a type is extensible for PER encoding.

10.2 Use of tags to provide a canonical order

This Recommendation | International Standard requires components of a set type and a choice type to be canonically ordered independent of the textual ordering of the components. The canonical order is determined by sorting the outermost tag of each component, as specified in Rec. ITU-T X.680 | ISO/IEC 8824-1, 8.6.

10.3 PER-visible constraints

NOTE – The fact that some ASN.1 constraints may not be PER-visible for the purposes of encoding and decoding does not in any way affect the use of such constraints in the handling of errors detected during decoding, nor does it imply that values violating such constraints are allowed to be transmitted by a conforming sender. However, this Recommendation | International Standard makes no use of such constraints in the specification of encodings.

10.3.1 Constraints that are expressed in human-readable text or in ASN.1 comment are not PER-visible.

10.3.2 Variable constraints are not PER-visible (see Rec. ITU-T X.683 | ISO/IEC 8824-4, 10.3 and 10.4).

10.3.3 User-defined constraints (see Rec. ITU-T X.682 | ISO/IEC 8824-3, 9.1) are not PER visible.

10.3.4 Table constraints are not PER-visible (see Rec. ITU-T X.682 | ISO/IEC 8824-3).

10.3.5 Component relation constraints (see Rec. ITU-T X.682 | ISO/IEC 8824-3, 10.7) are not PER-visible.

10.3.6 Constraints whose evaluation is textually dependent on a table constraint or a component relation constraint are not PER-visible (see Rec. ITU-T X.682 | ISO/IEC 8824-3).

10.3.7 Constraints on restricted character string types which are not (see Rec. ITU-T X.680 | ISO/IEC 8824-1, clause 41) known-multiplier character string types are not PER-visible (see 3.7.16).

10.3.8 Pattern constraints are not PER-visible.

10.3.9 Subject to the above, all size constraints are PER-visible.

© ISO/IEC 2021 – All rights reserved

Documents
Document Sharing Hub
Full document details: ISO_IEC 8825-2_2021

10.3.10 The effective size constraint for a constrained type is a single size constraint such that a size is permitted if and only if there is some value of the constrained type that has that (permitted) size.

10.3.11 Permitted-alphabet constraints on known-multiplier character string types which are not extensible after application of Rec. ITU-T X.680 | ISO/IEC 8824-1, 52.3 to 52.5, are PER-visible. Permitted-alphabet constraints which are extensible are not PER-visible.

10.3.12 The effective permitted-alphabet constraint for a constrained type is a single permitted-alphabet constraint which allows a character if and only if there is some value of the constrained type that contains that character. If all characters of the type being constrained can be present in some value of the constrained type, then the effective permitted-alphabet constraint is the set of characters defined for the unconstrained type.

10.3.13 Property setting constraints on the time type (or on the useful and defined time types) which are not extensible after the application of Rec. ITU-T X.680 | ISO/IEC 8824-1, 52.3 to 52.5, are PER-visible. Property setting constraints which are extensible are not PER-visible.

10.3.14 Constraints applied to real types are not PER-visible.

10.3.15 An inner type constraint applied to an unrestricted character string or embbeded-pdv type is PER-visible only when it is used to restrict the value of the **`syntaxes`** component to a single value, or when it is used to restrict **`identification`** to the **`fixed`** alternative (see clauses 28 and 31).

10.3.16 Constraints on the useful types are not PER-visible.

10.3.17 Single value subtype constraints applied to a character string type are not PER-visible.

10.3.18 Subject to the above, all other constraints are PER-visible if and only if they are applied to an integer type or to a known-multiplier character string type.

10.3.19 In general the constraint on a type will consist of individual constraints combined using some or all of set arithmetic, contained subtype constraints, and serial application of constraints. The following clauses specify the effect if some of the component parts of the total constraint are PER-visible and some are not.

NOTE – See Annex B for further discussion on the effect of combining constraints that individually are PER-visible or not PER-visible.

10.3.20 If a constraint consists of a serial application of constraints, the constraints which are not PER-visible, if any, do not affect PER encodings, but cause the extensibility (and extension additions) present in any earlier constraints to be removed as specified in Rec. ITU-T X.680 | ISO/IEC 8824-1, 50.11.

NOTE 1 – If the final constraint in a serial application is not PER-visible, then the type is not extensible for PER-encodings, and is encoded without an extension bit.

NOTE 2 – For example:

```
A ::= IA5String(SIZE(1..4))(FROM("ABCD",...))
```

has an effective permitted-alphabet constraint that consists of the entire **`IA5String`** alphabet since the extensible permitted-alphabet constraint is not PER-visible. It has nevertheless an effective size constraint which is "**`SIZE(1..4)`**".

Similarly,

```
B ::= IA5String(A)
```

has the same effective size constraint and the same effective permitted-alphabet constraint.

10.3.21 If a constraint that is PER-visible is part of an **`INTERSECTION`** construction, then the resulting constraint is PER-visible, and consists of the **`INTERSECTION`** of all PER-visible parts (with the non-PER-visible parts ignored). If a constraint which is not PER-visible is part of a **`UNION`** construction, then the resulting constraint is not PER-visible. If a constraint has an **`EXCEPT`** clause, the **`EXCEPT`** and the following value set is completely ignored, whether the value set following the **`EXCEPT`** is PER-visible or not.

NOTE – For example:

```
A ::= IA5String (SIZE(1..4) INTERSECTION FROM("ABCD",...))
```

has an effective size constraint of 1..4 but the alphabet constraint is not visible because it is extensible.

10.3.22 A type is also extensible for PER encodings (whether subsequently constrained or not) if any of the following occurs:

a) it is derived from an **`ENUMERATED`** type (by subtyping, type referencing, or tagging) and there is an extension marker in the "Enumerations" production; or

b) it is derived from a **`SEQUENCE`** type (by subtyping, type referencing, or tagging) and there is an extension marker in the "ComponentTypeLists" or in the "SequenceType" productions; or

c) it is derived from a **`SET`** type (by subtyping, type referencing, or tagging) and there is an extension marker in the "ComponentTypeLists" or in the "SetType" productions; or

© ISO/IEC 2021 – All rights reserved
Documents Document Sharing Hub
Full document details: ISO_IEC 8825-2_2021

d) it is derived from a **CHOICE** type (by subtyping, type referencing, or tagging) and there is an extension marker in the "AlternativeTypeLists" production.

10.4 Type and value model used for encoding

10.4.1 An ASN.1 type is either a simple type or is a type built using other types. The notation permits the use of type references and tagging of types. For the purpose of these encoding rules, the use of type references and tagging have no effect on the encoding and are invisible in the model, except as stated in 10.2. The notation also permits the application of constraints and of error specifications. PER-visible constraints are present in the model as a restriction of the values of a type. Other constraints and error specifications do not affect encoding and are invisible in the PER type and value model.

10.4.2 A value to be encoded can be considered as either a simple value or as a composite value built using the structuring mechanisms from components which are either simple or composite values, paralleling the structure of the ASN.1 type definition.

10.4.3 When a constraint includes a value as an extension addition that is present in the root, that value is always encoded as a value in the root, not as a value which is an extension addition.

EXAMPLE

INTEGER (0..10, ..., 5)
-- *The value 5 encodes as a root value, not as an extension addition.*

10.5 Structure of an encoding

10.5.1 These encoding rules specify:

a) the encoding of a simple value into a field-list; and

b) the encoding of a composite value into a field-list, using the field-lists generated by application of these encoding rules to the components of the composite value; and

c) the transformation of the field-list of the outermost value into the complete encoding of the abstract syntax value (see 11.1).

10.5.2 The encoding of a component of a data value either:

a) consists of three parts, as shown in Figure 1, which appear in the following order:

1) a preamble (see clauses 19, 21 and 23);

2) a length determinant (see 11.9);

3) contents; or



NOTE – The preamble, length, and contents are all "fields" which, concatenated together, form a "field-list". The field-list of a composite type other than the choice type may consist of the fields of several values concatenated together. Either the preamble, length and/or contents of any value may be missing.

Figure 1 – Encoding of a composite value into a field-list

b) (where the contents are large) consists of an arbitrary number of parts, as shown in Figure 2, of which the first is a preamble (see clauses 19, 21 and 23) and the following parts are pairs of bit-fields (octet-aligned in the ALIGNED variant), the first being a length determinant for a fragment of the contents, and the second that fragment of the contents; the last pair of fields is identified by the length determinant part, as specified in 11.9.



Figure 2 – Encoding of a long data value

© ISO/IEC 2021 – All rights reserved

Documents
Document Sharing Hub
Full document details: ISO_IEC 8825-2_2021

10.5.3 Each of the parts mentioned in 10.5.2 generates either:

a) a null field (nothing); or

b) a bit-field (unaligned); or

c) a bit-field (octet-aligned in the ALIGNED variant); or

d) a field-list which may contain either bit-fields (unaligned), bit-fields (octet-aligned in the ALIGNED variant), or both.

10.6 Types to be encoded

10.6.1 The following clauses specify the encoding of the following types into a field-list: boolean, integer, enumerated, real, bitstring, octetstring, null, sequence, sequence-of, set, set-of, choice, open, object identifier, relative object identifier, embedded-pdv, external, restricted character string and unrestricted character string types.

10.6.2 The selection type shall be encoded as an encoding of the selected type.

10.6.3 Encoding of tagged types is not included in this Recommendation | International Standard as, except as stated in 10.2, tagging is not visible in the type and value model used for these encoding rules. Tagged types are thus encoded according to the encoding of the type which has been tagged.

10.6.4 An encoding prefixed type is encoded according to the type which has been prefixed.

10.6.5 The following "useful types" shall be encoded as if they had been replaced by their definitions given in Rec. ITU-T X.680 | ISO/IEC 8824-1, clause 45:

– generalized time;

– universal time;

– object descriptor.

Constraints on the useful types are not PER-visible. The restrictions imposed on the encoding of the generalized time and universal time types by Rec. ITU-T X.690 | ISO/IEC 8825-1, 11.7 and 11.8, shall apply here.

10.6.6 A type defined using a value set assignment shall be encoded as if the type had been defined using the production specified in Rec. ITU-T X.680 | ISO/IEC 8824-1, 16.8.

11 Encoding procedures

11.1 Production of the complete encoding

11.1.1 If an ASN.1 type is encoded using any of the encoding rules identified by the object identifiers listed in subclause 33.2 (or by direct textual reference to this Recommendation | International Standard), and the encoding is included in:

a) an ASN.1 octetstring; or

b) an ASN.1 bitstring, or

c) an ASN.1 open type; or

d) any part of an ASN.1 external or embedded pdv type; or

e) any carrier protocol that is not defined using ASN.1

then that ASN.1 type is defined as an outermost type for this application, and subclause 11.1.2 shall apply to all encodings of its values.

NOTE 1 – This means that all complete PER encodings (for all variants) that are used in this way are always an integral multiple of eight bits except when the UNALIGNED variant is used and the encoding is included in an ASN.1 bitstring (case b)) above).

NOTE 2 – It is possible using the Encoding Control Notation (see Recommendation ITU-T X.692 | ISO/IEC 8825-3) to specify a variant of PER encodings in which the encoding is not padded to an octet boundary as specified in 11.1.2. Many tools support this option.

NOTE 3 – It is recognized that a carrier protocol not defined using ASN.1 need not explicitly carry the additional zero bits for padding (specified in 11.1.2), but can imply their presence.

11.1.2 The field-list produced as a result of applying this Recommendation | International Standard to an abstract value of an outermost type shall be used to produce the complete encoding of that abstract syntax value as follows: each field in the field-list shall be taken in turn and concatenated to the end of the bit string which is to form the complete encoding of the abstract syntax value preceded by additional zero bits for padding as specified below.

© ISO/IEC 2021 – All rights reserved
Documents
Document Sharing Hub
Full document details: ISO_IEC 8825-2_2021

11.1.3 In the UNALIGNED variant of these encoding rules, all fields shall be concatenated without padding. In all the cases of 11.1.1 except case b), subclause 11.1.3.1 applies. In case b) of 11.1.1, subclause 11.1.3.2 applies.

11.1.3.1 (The result of the encoding is not contained in an ASN.1 bitstring) If the result of encoding the outermost value is an empty bit string, the bit string shall be replaced with a single octet with all bits set to 0. If it is a non-empty bit string and it is not a multiple of eight bits, (one to seven) zero bits shall be appended to it to produce a multiple of eight bits.

11.1.3.2 (The result of the encoding is contained in an ASN.1 bitstring) If the result of encoding the outermost value is an empty bit string, the bit string shall be replaced with a single bit set to 0. No padding bits shall be appended.

11.1.4 In the ALIGNED variant of these encoding rules, any bit-fields in the field-list shall be concatenated without padding, and any octet-aligned bit-fields shall be concatenated after (zero to seven) zero bits have been concatenated to make the length of the encoding produced so far a multiple of eight bits. If the result of encoding the outermost value is an empty bit string, the bit string shall be replaced with a single octet with all bits set to 0. If it is a non-empty bit string and it is not a multiple of eight bits, (zero to seven) zero bits shall be appended to it to produce a multiple of eight bits.

NOTE 1 – The encoding of the outermost value is the empty bit string if, for example, the abstract syntax value is of the null type or of an integer type constrained to a single value.

NOTE 2 – Zero-length octet-aligned bit-fields can never be present in the field-list (see 11.9.3.3).

11.1.5 The resulting bit string is the complete encoding of the abstract syntax value of an outermost type.

11.2 Open type fields

11.2.1 In order to encode an open type field, the value of the actual type occupying the field shall be encoded to a field-list which shall then be converted to a complete encoding of an abstract syntax value as specified in 11.1 to produce an octet string of length "n" (say).

11.2.2 The field-list for the value in which the open type is to be embedded shall then have added to it (as specified in 11.9) an unconstrained length of "n" (in units of octets) and an associated bit-field (octet-aligned in the ALIGNED variant) containing the bits produced in 11.2.1.

NOTE – Where the number of octets in the open type encoding is large, the fragmentation procedures of 11.9 will be used, and the encoding of the open type will be broken without regard to the position of the fragment boundary in the encoding of the type occupying the open type field.

11.3 Encoding as a non-negative-binary-integer

NOTE – (Tutorial) This subclause gives precision to the term "non-negative-binary-integer encoding", putting the integer into a field which is a fixed number of bits, a field which is a fixed number of octets, or a field that is the minimum number of octets needed to hold it.

11.3.1 Subsequent subclauses refer to the generation of a non-negative-binary-integer encoding of a non-negative whole number into a field which is either a bit-field of specified length, a single octet, a double octet, or the minimum number of octets for the value. This subclause (11.3) specifies the precise encoding to be applied when such references are made.

11.3.2 The leading bit of the field is defined as the leading bit of the bit-field, or as the most significant bit of the first octet in the field, and the trailing bit of the field is defined as the trailing bit of the bit-field or as the least significant bit of the last octet in the field.

11.3.3 For the following definition only, the bits shall be numbered zero for the trailing bit of the field, one for the next bit, and so on up to the leading bit of the field.

11.3.4 In a non-negative-binary-integer encoding, the value of the whole number represented by the encoding shall be the sum of the values specified by each bit. A bit which is set to "0" has zero value. A bit with number "n" which is set to "1" has the value 2^n.

11.3.5 The encoding which sums (as defined above) to the value being encoded is an encoding of that value.

NOTE – Where the size of the encoded field is fixed (a bit-field of specified length, a single octet, or a double octet), then there is a unique encoding which sums to the value being encoded.

11.3.6 A minimum octet non-negative-binary-integer encoding of the whole number (which does not predetermine the number of octets to be used for the encoding) has a field which is a multiple of eight bits and also satisfies the condition that the leading eight bits of the field shall not all be zero unless the field is precisely eight bits long.

NOTE – This is a necessary and sufficient condition to produce a unique encoding.

© ISO/IEC 2021 – All rights reserved

Documents
Document Sharing Hub
Full document details: ISO_IEC 8825-2_2021

11.4 Encoding as a 2's-complement-binary-integer

NOTE – (Tutorial) This subclause gives precision to the term "2's-complement-binary-integer encoding", putting a signed integer into a field that is the minimum number of octets needed to hold it. These procedures are referenced in later encoding specifications.

11.4.1 Subsequent subclauses refer to the generation of a 2's-complement-binary-integer encoding of a whole number (which may be negative, zero, or positive) into the minimum number of octets for the value. This subclause (11.4) specifies the precise encoding to be applied when such references are made.

11.4.2 The leading bit of the field is defined as the most significant bit of the first octet, and the trailing bit of the field is defined as the least significant bit of the last octet.

11.4.3 For the following definition only, the bits shall be numbered zero for the trailing bit of the field, one for the next bit, and so on up to the leading bit of the field.

11.4.4 In a 2's-complement-binary-integer encoding, the value of the whole number represented by the encoding shall be the sum of the values specified by each bit. A bit which is set to "0" has zero value. A bit with number "n" which is set to "1" has the value 2^n unless it is the leading bit, in which case it has the (negative) value -2^n.

11.4.5 Any encoding which sums (as defined above) to the value being encoded is an encoding of that value.

11.4.6 A minimum octet 2's-complement-binary-integer encoding of the whole number has a field-width that is a multiple of eight bits and also satisfies the condition that the leading nine bits of the field shall not all be zero and shall not all be ones.

NOTE – This is a necessary and sufficient condition to produce a unique encoding.

11.5 Encoding of a constrained whole number

NOTE – (Tutorial) This subclause is referenced by other clauses, and itself references earlier clauses for the production of a non-negative-binary-integer or a 2's-complement-binary-integer encoding. For the UNALIGNED variant the value is always encoded in the minimum number of bits necessary to represent the range (defined in 11.5.3). The rest of this Note addresses the ALIGNED variant. Where the range is less than or equal to 255, the value encodes into a bit-field of the minimum size for the range. Where the range is exactly 256, the value encodes into a single octet octet-aligned bit-field. Where the range is 257 to 64K, the value encodes into a two octet octet-aligned bit-field. Where the range is greater than 64K, the range is ignored and the value encodes into an octet-aligned bit-field which is the minimum number of octets for the value. In this latter case, later procedures (see 11.9) also encode a length field (usually a single octet) to indicate the length of the encoding. For the other cases, the length of the encoding is independent of the value being encoded, and is not explicitly encoded.

11.5.1 This subclause (11.5) specifies a mapping from a constrained whole number into either a bit-field (unaligned) or a bit-field (octet-aligned in the ALIGNED variant), and is invoked by later clauses in this Recommendation | International Standard.

11.5.2 The procedures of this subclause are invoked only if a constrained whole number to be encoded is available, and the values of the lower bound, "lb", and the upper bound, "ub", have been determined from the type notation (after the application of PER-visible constraints).

NOTE – A lower bound cannot be determined if **`MIN`** evaluates to an infinite number, nor can an upper bound be determined if **`MAX`** evaluates to an infinite number. For example, no upper or lower bound can be determined for **`INTEGER(MIN..MAX)`**.

11.5.3 Let "range" be defined as the integer value ("ub" – "lb" + 1), and let the value to be encoded be "n".

11.5.4 If "range" has the value 1, then the result of the encoding shall be an empty bit-field (no bits).

11.5.5 There are five other cases (leading to different encodings) to consider, where one applies to the UNALIGNED variant and four to the ALIGNED variant.

11.5.6 In the case of the UNALIGNED variant the value ("n" – "lb") shall be encoded as a non-negative- binary-integer in a bit-field as specified in 11.3 with the minimum number of bits necessary to represent the range.

NOTE – If "range" satisfies the inequality 2^m < "range" ≤ 2^{m+1}, then the number of bits = m + 1.

11.5.7 In the case of the ALIGNED variant the encoding depends on whether:

a) "range" is less than or equal to 255 (the bit-field case);

b) "range" is exactly 256 (the one-octet case);

c) "range" is greater than 256 and less than or equal to 64K (the two-octet case);

d) "range" is greater than 64K (the indefinite length case).

11.5.7.1 (The bit-field case.) If "range" is less than or equal to 255, then invocation of this subclause requires the generation of a bit-field with a number of bits as specified in the table below, and containing the value ("n" – "lb") as a non-negative-binary-integer encoding in a bit-field as specified in 11.3.

© ISO/IEC 2021 – All rights reserved
Documents Document Sharing Hub
Full document details: ISO_IEC 8825-2_2021

"range"	Bit-field size (in bits)
2	1
3, 4	2
5, 6, 7, 8	3
9 to 16	4
17 to 32	5
33 to 64	6
65 to 128	7
129 to 255	8

11.5.7.2 (The one-octet case.) If the range has a value of 256, then the value ("n" – "lb") shall be encoded in a one-octet bit-field (octet-aligned in the ALIGNED variant) as a non-negative-binary-integer as specified in 11.3.

11.5.7.3 (The two-octet case.) If the "range" has a value greater than or equal to 257 and less than or equal to 64K, then the value ("n" – "lb") shall be encoded in a two-octet bit-field (octet-aligned in the ALIGNED variant) as a non-negative-binary-integer encoding as specified in 11.3.

11.5.7.4 (The indefinite length case.) Otherwise, the value ("n" – "lb") shall be encoded as a non-negative-binary-integer in a bit-field (octet-aligned in the ALIGNED variant) with the minimum number of octets as specified in 11.3, and the number of octets "len" used in the encoding is used by other clauses that reference this subclause to specify an encoding of the length.

11.6 Encoding of a normally small non-negative whole number

NOTE – (Tutorial) This procedure is used when encoding a non-negative whole number that is expected to be small, but whose size is potentially unlimited due to the presence of an extension marker. An example is a choice index.

11.6.1 If the non-negative whole number, "n", is less than or equal to 63, then a single-bit bit-field shall be appended to the field-list with the bit set to 0, and "n" shall be encoded as a non-negative-binary-integer into a 6-bit bit-field.

11.6.2 If "n" is greater than or equal to 64, a single-bit bit-field with the bit set to 1 shall be appended to the field-list. The value "n" shall then be encoded as a semi-constrained whole number with "lb" equal to 0 and the procedures of 11.9 shall be invoked to add it to the field-list preceded by a length determinant.

11.7 Encoding of a semi-constrained whole number

NOTE – (Tutorial) This procedure is used when a lower bound can be identified but not an upper bound. The encoding procedure places the offset from the lower bound into the minimum number of octets as a non-negative-binary-integer, and requires an explicit length encoding (typically a single octet) as specified in later procedures.

11.7.1 This subclause specifies a mapping from a semi-constrained whole number into a bit-field (octet-aligned in the ALIGNED variant), and is invoked by later clauses in this Recommendation | International Standard.

11.7.2 The procedures of this subclause (11.7) are invoked only if a semi-constrained whole number ("n" say) to be encoded is available, and the value of "lb" has been determined from the type notation (after the application of PER-visible constraints).

NOTE – A lower bound cannot be determined if **`MIN`** evaluates to an infinite number. For example, no lower bound can be determined for **`INTEGER(MIN..MAX)`**.

11.7.3 The procedures of this subclause always produce the indefinite length case.

11.7.4 (The indefinite length case.) The value ("n" – "lb") shall be encoded as a non-negative-binary-integer in a bit-field (octet-aligned in the ALIGNED variant) with the minimum number of octets as specified in 11.3, and the number of octets "len" used in the encoding is used by other clauses that reference this subclause to specify an encoding of the length.

11.8 Encoding of an unconstrained whole number

NOTE – (Tutorial) This case only arises in the encoding of the value of an integer type with no lower bound. The procedure encodes the value as a 2's-complement-binary-integer into the minimum number of octets required to accommodate the encoding, and requires an explicit length encoding (typically a single octet) as specified in later procedures.

11.8.1 This subclause (11.8) specifies a mapping from an unconstrained whole number ("n" say) into a bit-field (octet-aligned in the ALIGNED variant), and is invoked by later clauses in this Recommendation | International Standard.

© ISO/IEC 2021 – All rights reserved

Documents
Document Sharing Hub
Full document details: ISO_IEC 8825-2_2021

11.8.2 The procedures of this subclause always produce the indefinite length case.

11.8.3 (The indefinite length case.) The value "n" shall be encoded as a 2's-complement-binary-integer in a bit-field (octet-aligned in the ALIGNED variant) with the minimum number of octets as specified in 11.4, and the number of octets "len" used in the encoding is used by other clauses that reference this subclause to specify an encoding of the length.

11.9 General rules for encoding a length determinant

NOTE 1 – (Tutorial) The procedures of this subclause are invoked when an explicit length field is needed for some part of the encoding regardless of whether the length count is bounded above (by PER-visible constraints) or not. The part of the encoding to which the length applies may be a bit string (with the length count in bits), an octet string (with the length count in octets), a known-multiplier character string (with the length count in characters), or a list of fields (with the length count in components of a sequence-of or set-of).

NOTE 2 – (Tutorial) In the case of the ALIGNED variant if the length count is bounded above by an upper bound that is less than 64K, then the constrained whole number encoding is used for the length. For sufficiently small ranges the result is a bit-field, otherwise the unconstrained length ("n" say) is encoded into an octet-aligned bit-field in one of three ways (in order of increasing size):

a) ("n" less than 128) a single octet containing "n" with bit 8 set to zero;

b) ("n" less than 16K) two octets containing "n" with bit 8 of the first octet set to 1 and bit 7 set to zero;

c) (large "n") a single octet containing a count "m" with bit 8 set to 1 and bit 7 set to 1. The count "m" is one to four, and the length indicates that a fragment of the material follows (a multiple "m" of 16K items). For all values of "m", the fragment is then followed by another length encoding for the remainder of the material.

NOTE 3 – (Tutorial) In the UNALIGNED variant, if the length count is bounded above by an upper bound that is less than 64K, then the constrained whole number encoding is used to encode the length in the minimum number of bits necessary to represent the range. Otherwise, the unconstrained length ("n" say) is encoded into a bit-field in the manner described above in Note 2.

11.9.1 This subclause is not invoked if, in accordance with the specification of later clauses, the value of the length determinant, "n", is fixed by the type definition (constrained by PER-visible constraints) to a value less than 64K.

11.9.2 This subclause is invoked for addition to the field-list of a field, or list of fields, preceded by a length determinant "n" which determines either:

a) the length in octets of an associated field (units are octets); or

b) the length in bits of an associated field (units are bits); or

c) the number of component encodings in an associated list of fields (units are components of a set-of or sequence-of); or

d) the number of characters in the value of an associated known-multiplier character string type (units are characters).

11.9.3 (ALIGNED variant) The procedures for the ALIGNED variant are specified in 11.9.3.1 to 11.9.3.8.4. (The procedures for the UNALIGNED variant are specified in 11.9.4.)

11.9.3.1 As a result of the analysis of the type definition (specified in later clauses) the length determinant (a whole number "n") will have been determined to be either:

a) a normally small length with a lower bound "lb" equal to one; or

b) a constrained whole number with a lower bound "lb" (greater than or equal to zero), and an upper bound "ub" less than 64K; or

c) a semi-constrained whole number with a lower bound "lb" (greater than or equal to zero), or a constrained whole number with a lower bound "lb" (greater than or equal to zero) and an upper bound "ub" greater than or equal to 64K.

11.9.3.2 The subclauses invoking the procedures of this subclause will have determined a value for "lb", the lower bound of the length (this is zero if the length is unconstrained), and for "ub", the upper bound of the length. "ub" is unset if there is no upper bound determinable from PER-visible constraints.

11.9.3.3 Where the length determinant is a constrained whole number with "ub" less than 64K, then the field-list shall have appended to it the encoding of the constrained whole number for the length determinant as specified in 11.5. If "n" is non-zero, this shall be followed by the associated field or list of fields, completing these procedures. If "n" is zero there shall be no further addition to the field-list, completing these procedures.

NOTE 1 – For example:

```
A ::= IA5String (SIZE (3..6))            -- Length is encoded in a 2-bit bit-field.
B ::= IA5String (SIZE (40000..40254))    -- Length is encoded in an 8-bit bit-field.
C ::= IA5String (SIZE (0..32000))        -- Length is encoded in a 2-octet
                                         -- bit-field (octet-aligned in the
ALIGNED variant).
```


© ISO/IEC 2021 – All rights reserved
Documents Document Sharing Hub
Full document details: ISO_IEC 8825-2_2021