

INTERNATIONAL
STANDARD

ISO/IEC
9594-7

Second edition
1995-09-15

**Information technology — Open Systems
Interconnection — The Directory: Selected
object classes**

*Technologies de l'information — Interconnexion de systèmes ouverts
(OSI) — L'Annuaire: Classe d'objets sélectionnés*



Reference number
ISO/IEC 9594-7:1995(E)
AVA Documents
Document Sharing Hub

Contents

	<i>Page</i>
SECTION 1 – GENERAL.....	1
1 Scope.....	1
2 Normative references	1
3 Definitions.....	2
4 Conventions.....	3
SECTION 2 – SELECTED OBJECT CLASSES.....	3
5 Definition of useful attribute sets	3
6 Definition of selected object classes	4
SECTION 3 – SELECTED NAME FORMS	7
7 Definition of selected name forms	7
Annex A – Selected object classes and name forms in ASN.1	10
Annex B – Suggested name forms and DIT structures	15
Annex C – Amendments and corrigenda.....	21

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 9594-7 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 21, *Open systems interconnection, data management and open distributed processing*, in collaboration with ITU-T. The identical text is published as ITU-T Recommendation X.521.

Implementors should note that a defect resolution process exists and that corrections may be applied to this part of ISO/IEC 9594 in the form of technical corrigenda. A list of approved technical corrigenda for this part of ISO/IEC 9594 can be obtained from the subcommittee secretariat. Published technical corrigenda are available from your national standards organization.

This second edition technically revises and enhances ISO/IEC 9594-7:1990. It also incorporates technical corrigendum 1:1991 and technical corrigendum 2:1992. Implementations may still claim conformance to the first edition of this part of ISO/IEC 9594. However, at some point, the first edition will no longer be supported (i.e. reported defects will no longer be resolved). It is recommended that implementations conform to this second edition as soon as possible.

ISO/IEC 9594 consists of the following parts, under the general title *Information technology — Open Systems Interconnection — The Directory*:

- *Part 1: Overview of concepts, models and services*
- *Part 2: Models*
- *Part 3: Abstract service definition*
- *Part 4: Procedures for distributed operation*
- *Part 5: Protocol specifications*
- *Part 6: Selected attribute types*
- *Part 7: Selected object classes*
- *Part 8: Authentication framework*
- *Part 9: Replication*

Annex A forms an integral part of this part of ISO/IEC 9594. Annexes B and C are for information only.

Introduction

This Recommendation | International Standard, together with other Recommendations | International Standards, has been produced to facilitate the interconnection of information processing systems to provide directory services. A set of such systems, together with the directory information which they hold, can be viewed as an integrated whole, called the *Directory*. The information held by the Directory, collectively known as the Directory Information Base (DIB), is typically used to facilitate communication between, with or about objects such as application entities, people, terminals, and distribution lists.

The Directory plays a significant role in Open Systems Interconnection, whose aim is to allow, with a minimum of technical agreement outside of the interconnection standards themselves, the interconnection of information processing systems:

- from different manufacturers;
- under different managements;
- of different levels of complexity; and
- of different ages.

This Recommendation | International Standard defines a number of attribute sets and object classes which may be found useful across a range of applications of the Directory.

This second edition technically revises and enhances, but does not replace, the first edition of this Recommendation | International Standard. Implementations may still claim conformance to the first edition.

This second edition specifies version 1 of the Directory service and protocols. The first edition also specifies version 1. Differences between the services and between the protocols defined in the two editions are accommodated using the rules of extensibility defined in this edition of X.519 | ISO/IEC 9594-5.

Annex A, which is an integral part of this Recommendation | International Standard, provides an ASN.1 module containing all of the type and value definitions which appear in this document.

Annex B, which is not an integral part of this Recommendation | International Standard, provides some common naming and structure rules which may or may not be used by administrative authorities.

Annex C, which is not an integral part of this Recommendation | International Standard, lists the amendments and defect reports that have been incorporated to form this edition of this Recommendation | International Standard.

INTERNATIONAL STANDARD

ITU-T RECOMMENDATION

INFORMATION TECHNOLOGY – OPEN SYSTEMS INTERCONNECTION – THE DIRECTORY: SELECTED OBJECT CLASSES

SECTION 1 – GENERAL

1 Scope

This Recommendation | International Standard defines a number of object classes and name forms which may be found useful across a range of applications of the Directory. The definition of an object class involves listing a number of attribute types which are relevant to objects of that class. The definition of a name form involves naming the object class to which it applies and listing the attributes to be used in forming names for objects of that class. These definitions are used by the administrative authority which is responsible for the management of the directory information.

Any administrative authority can define its own object classes or subclasses and name forms for any purpose.

NOTES

- 1 Those definitions may or may not use the notation specified in ITU-T Rec. X.501 | ISO/IEC 9594-2.
- 2 It is recommended that an object class defined in this Recommendation | International Standard, or a subclass derived from one, or a name form defined in this Recommendation | International Standard, be used in preference to the generation of a new one, whenever the semantics is appropriate for the application.

Administrative authorities may support some or all the selected object classes and name forms, and may also add additional ones.

All administrative authorities shall support the object classes which the directory uses for its own purpose (the top, alias and DSA object classes).

2 Normative references

The following Recommendations and International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | International Standard part. At the time of publication, the editions indicated were valid. All Recommendations and Standards are subject to revision, and parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent editions of the Recommendations and Standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards. The Telecommunication Standardization Bureau of the ITU maintains a list of currently valid ITU-T Recommendations.

2.1 Identical Recommendations | International Standards

- ITU-T Recommendation X.500 (1993) | ISO/IEC 9594-1:1995, *Information technology – Open Systems Interconnection – The Directory: Overview of concepts, models and services.*
- ITU-T Recommendation X.501 (1993) | ISO/IEC 9594-2:1995, *Information technology – Open Systems Interconnection – The Directory: Models.*
- ITU-T Recommendation X.511 (1993) | ISO/IEC 9594-3:1995, *Information technology – Open Systems Interconnection – The Directory: Abstract service definition.*
- ITU-T Recommendation X.518 (1993) | ISO/IEC 9594-4:1995, *Information technology – Open Systems Interconnection – The Directory: Procedures for distributed operation.*
- ITU-T Recommendation X.519 (1993) | ISO/IEC 9594-5:1995, *Information technology – Open Systems Interconnection – The Directory: Protocol specifications.*

- ITU-T Recommendation X.520 (1993) | ISO/IEC 9594-6:1995, *Information technology – Open Systems Interconnection – The Directory: Selected attribute types.*
- ITU-T Recommendation X.509 (1993) | ISO/IEC 9594-8:1995, *Information technology – Open Systems Interconnection – The Directory: Authentication framework.*
- ITU-T Recommendation X.525 (1993) | ISO/IEC 9594-9:1995, *Information technology – Open Systems Interconnection – The Directory: Replication*
- ITU-T Recommendation X.680 (1994) | ISO/IEC 8824-1:1995, *Information technology – Abstract Syntax Notation One (ASN.1): Specification of basic notation.*
- ITU-T Recommendation X.681 (1994) | ISO/IEC 8824-2:1995, *Information technology – Abstract Syntax Notation One (ASN.1): Information object specification.*
- ITU-T Recommendation X.682 (1994) | ISO/IEC 8824-3:1995, *Information technology – Abstract Syntax Notation One (ASN.1): Constraint specification.*
- ITU-T Recommendation X.683 (1994) | ISO/IEC 8824-4:1995, *Information technology – Abstract Syntax Notation One (ASN.1): Parametrization of ASN.1 specifications.*

2.2 Paired Recommendations | International Standards equivalent in technical content

- CCITT Recommendation X.200 (1988), *Reference Model of Open Systems Interconnection for CCITT Applications.*
ISO 7498:1984, *Information processing systems — Open Systems Interconnection — Basic Reference Model.*

3 Definitions

For the purposes of this Recommendation | International Standard, the following definitions apply.

3.1 OSI Reference Model definitions

The following terms are defined in CCITT Rec. X.200 | ISO 7498:

- a) *application-entity*;
- b) *application-process*.

3.2 Directory Model definitions

The following terms are defined in ITU-T Rec. X.501 | ISO/IEC 9594-2:

- a) *attribute*;
- b) *attribute type*;
- c) *Directory Information Tree (DIT)*;
- d) *Directory System Agent (DSA)*;
- e) *attribute set*;
- f) *entry*;
- g) *name*;
- h) *object class*;
- i) *subclass*;
- j) *name form*;
- k) *structure rule*.

4 Conventions

With minor exceptions this Directory Specification has been prepared according to the “Presentation of ITU-T | ISO/IEC common text” guidelines in the Guide for ITU-T and ISO/IEC JTC 1 Cooperation, March 1993.

The term “Directory Specification” (as in “this Directory Specification”) shall be taken to mean CCITT Rec. X.521 | ISO/IEC 9594-7. The term “Directory Specifications” shall be taken to mean the X.500-Series Recommendations and all parts of ISO/IEC 9594.

This Directory Specification uses the term “1988 edition systems” to refer to systems conforming to the previous (1988) edition of the Directory Specifications, i.e. the 1988 edition of the series of CCITT X.500 Recommendations and the ISO/IEC 9594:1990 edition. Systems conforming to the current Directory Specifications are referred to as “1993 edition systems”.

Object classes and name forms are defined in this Directory Specification as values of the OBJECT-CLASS and NAME-FORM information object classes defined in ITU-T Rec. X.501 | ISO/IEC 9594-2.

SECTION 2 – SELECTED OBJECT CLASSES

5 Definition of useful attribute sets

5.1 Telecommunication attribute set

This set of attributes is used to define those which are commonly used for business communications.

```
TelecommunicationAttributeSet  ATTRIBUTE ::= {
    facsimileTelephoneNumber |
    internationalISDNNumber |
    telephoneNumber |
    teletexTerminalIdentifier |
    telexNumber |
    preferredDeliveryMethod |
    destinationIndicator |
    registeredAddress |
    x121Address }
```

5.2 Postal attribute set

This set of attributes is used to define those which are directly associated with postal delivery.

```
PostalAttributeSet  ATTRIBUTE ::= {
    physicalDeliveryOfficeName |
    postalAddress |
    postalCode |
    postOfficeBox |
    streetAddress }
```

5.3 Locale attribute set

This set of attributes is used to define those which are commonly used for search purposes to indicate the locale of an object.

```
LocaleAttributeSet  ATTRIBUTE ::= {
    localityName |
    stateOrProvinceName |
    streetAddress }
```

5.4 Organizational attribute set

This set of attributes is used to define the attributes that an organization or organizational unit may typically possess.

OrganizationalAttributeSet ATTRIBUTE ::= {
 description |
 LocaleAttributeSet |
 PostalAttributeSet |
 TelecommunicationAttributeSet |
 businessCategory |
 seeAlso |
 searchGuide |
 userPassword }

6 Definition of selected object classes

6.1 Country

A *Country* object class is used to define country entries in the DIT.

country OBJECT-CLASS ::= {
 SUBCLASS OF { top }
 MUST CONTAIN { countryName }
 MAY CONTAIN { description | searchGuide }
 ID id-oc-country }

6.2 Locality

The *Locality* object class is used to define locality in the DIT.

locality OBJECT-CLASS ::= {
 SUBCLASS OF { top }
 MAY CONTAIN { description |
 searchGuide |
 LocaleAttributeSet |
 seeAlso }
 ID id-oc-locality }

At least one of Locality Name or State or Province Name must be present.

6.3 Organization

The *Organization* object class is used to define organization entries in the DIT.

organization OBJECT-CLASS ::= {
 SUBCLASS OF { top }
 MUST CONTAIN { organizationName }
 MAY CONTAIN { OrganizationalAttributeSet }
 ID id-oc-organization }

6.4 Organizational Unit

The *Organizational Unit* object class is used to define entries representing subdivisions of organizations.

organizationalUnit OBJECT-CLASS::= {
 SUBCLASS OF { top }
 MUST CONTAIN { organizationalUnitName }
 MAY CONTAIN { OrganizationalAttributeSet }
 ID id-oc-organizationalUnit }

6.5 Person

The *Person* object class is used to define entries representing people generically.

```

person          OBJECT-CLASS ::= {
  SUBCLASS OF    { top }
  MUST CONTAIN   { commonName | surname }
  MAY CONTAIN    { description |
                  telephoneNumber |
                  userPassword |
                  seeAlso }
  ID             id-oc-person }

```

6.6 Organizational Person

The *Organizational Person* object class is used to define entries representing people employed by, or in some other important way associated with, an organization.

```

organizationalPerson OBJECT-CLASS ::= {
  SUBCLASS OF    { person }
  MAY CONTAIN    { LocaleAttributeSet |
                  PostalAttributeSet |
                  TelecommunicationAttributeSet |
                  organizationalUnitName |
                  title }
  ID             id-oc-organizationalPerson }

```

6.7 Organizational Role

The *Organizational Role* object class is used to define entries representing an organizational role, i.e. a position or role within an organization. An organizational role is normally considered to be filled by a particular organizational person. Over its lifetime, however, an organizational role may be filled by a number of different organizational people in succession. In general, an organizational role may be filled by a person or a non-human entity.

```

organizationalRole   OBJECT-CLASS ::= {
  SUBCLASS OF    { top }
  MUST CONTAIN   { commonName }
  MAY CONTAIN    { description |
                  LocaleAttributeSet |
                  organizationalUnitName |
                  PostalAttributeSet |
                  preferredDeliveryMethod |
                  roleOccupant |
                  seeAlso |
                  TelecommunicationAttributeSet }
  ID             id-oc-organizationalRole }

```

6.8 Group of Names

The *Group Of Names* object class is used to define entries representing an unordered set of names which represent individual objects or other groups of names. The membership of a group is static, i.e. it is explicitly modified by administrative action, rather than dynamically determined each time the group is referred to.

The membership of a group can be reduced to a set of individual object's names by replacing each group with its membership. This process could be carried out recursively until all constituent group names have been eliminated, and only the names of individual objects remain.

```

groupOfNames        OBJECT-CLASS ::= {
  SUBCLASS OF    { top }
  MUST CONTAIN   { commonName | member }
  MAY CONTAIN    { description |
                  organizationName |
                  organizationalUnitName |
                  owner |
                  seeAlso |
                  businessCategory }
  ID             id-oc-groupOfNames }

```