

INTERNATIONAL
STANDARD

ISO/IEC/
IEEE
8802-3-1

First edition
2015-08-01

**Information technology — Management
Information Base (MIB) — Definitions for
Ethernet —**

Part 3-1:

*Technologies de l'information — Base d'information de gestion —
Définitions pour l'Ethernet —*

Partie 3-1:



Reference number
ISO/IEC/IEEE 8802-3-1:2015(E)

AVA Documents
Document Sharing Hub
© IEEE 2015



COPYRIGHT PROTECTED DOCUMENT

© IEEE 2015

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from ISO, IEC or IEEE at the respective address below.

ISO copyright office
Case postale 56
CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland
E-mail inmail@iec.ch
Web www.iec.ch

Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York
NY 10016-5997, USA
E-mail stds.ipr@ieee.org
Web www.ieee.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards.

The main task of ISO/IEC JTC 1 is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is called to the possibility that implementation of this standard may require the use of subject matter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. ISO/IEEE is not responsible for identifying essential patents or patent claims for which a license may be required, for conducting inquiries into the legal validity or scope of patents or patent claims or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance or a Patent Statement and Licensing Declaration Form, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from ISO or the IEEE Standards Association.

ISO/IEC/IEEE 8802-3-1 was prepared by the LAN/MAN Standards Committee of the IEEE Computer Society (as IEEE 802.3.1:2013). It was adopted by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunication and information exchange between systems*, in parallel with its approval by the ISO/IEC national bodies, under the “fast-track procedure” defined in the Partner Standards Development Organization cooperation agreement between ISO and IEEE. IEEE is responsible for the maintenance of this document with participation and input from ISO/IEC national bodies.

IEEE Standard for Management Information Base (MIB) Definitions for Ethernet

IEEE Computer Society

Sponsored by the
LAN/MAN Standards Committee

IEEE
3 Park Avenue
New York, NY 10016-5997
USA

IEEE Std 802.3.1™-2013
(Revision of
IEEE Std 802.3.1-2011)

IEEE Std 802.3.1™-2013

(Revision of
IEEE Std 802.3.1-2011)

IEEE Standard for Management Information Base (MIB) Definitions for Ethernet

Sponsor
LAN/MAN Standards Committee
of the
IEEE Computer Society

Approved 14 June 2013
IEEE-SA Standards Board

Permissions have been granted as follows^a:

Portions of this standard reprinted with permission from Avaya, IETF RFC 2108 Definitions of Managed Objects for IEEE 802.3 Repeater Devices using SMIPv2, © 1997.

Portions of this standard reprinted with permission from Microsemi Corporation, IETF RFC 3621 Definitions Power Ethernet MIB, © 2003.

Portions of this standard reprinted with permission from Avaya, IETF RFC 3621 Definitions Power Ethernet MIB, © 2003.

Portions of this standard reprinted with permission from the Hewlett-Packard Company, IETF RFC 3635 Definitions of Managed Objects for the Ethernet-like Interface Types, © 2003.

Material from IETF RFC 4836 Definitions of Managed Objects for IEEE 802.3 Medium Attachment Units (MAUs) reprinted with permission from the IETF Trust and the persons identified as the document authors, © 2007.

Portions of this standard reprinted with permission from Edward Beili, IETF RFC 4836 Definitions of Managed Objects for IEEE 802.3 Medium Attachment Units (MAUs), © 2007.

Material from IETF RFC 4837 Managed Objects of Ethernet Passive Optical Networks (EPON) reprinted with permission from the IETF Trust and the persons identified as the document authors, © 2007.

Portions of this standard reprinted with permission from PMC-Sierra, IETF RFC 4837 Managed Objects of Ethernet Passive Optical Networks (EPON), © 2007.

Material from IETF RFC 4878 Definitions and Managed Objects for Operations, Administration, and Maintenance (OAM) Functions on Ethernet-Like Interfaces reprinted with permission from the IETF Trust and the persons identified as the document authors, © 2007.

Material from IETF RFC 5066 Ethernet in the First Mile Copper (EFMCu) Interfaces MIB reprinted with permission from the IETF Trust and the persons identified as the document authors.

Portions of this standard reprinted with permission from Edward Beili, IETF RFC 5066 Ethernet in the First Mile Copper (EFMCu) Interfaces MIB, © 2007.

^aEvery effort has been made to secure permission to reprint borrowed material contained in this document. If omissions have been made, please bring them to the attention of the IEEE P802.3.1 working group.

Abstract: The Management Information Base (MIB) module specifications for IEEE Std 802.3™, also known as Ethernet, are contained in this standard. It includes the Structure of Management Information Version 2 (SMIPv2) MIB module specifications formerly produced and published by the Internet Engineering Task Force (IETF), as well as extensions resulting from amendments to IEEE Std 802.3. The SMIPv2 MIB modules are intended for use with the Simple Network Management Protocol (SNMP), commonly used to manage Ethernet.

Keywords: Ethernet, IEEE 802.3.1™, Management Information Base (MIB), network management, Simple Network Management Protocol (SNMP), Structure of Management Information Version 2 (SMIPv2)

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2013 by the Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 2 August 2013. Printed in the United States of America.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-0-7381-8432-6 STD98241
Print: ISBN 978-0-7381-8433-3 STDPD98241

IEEE prohibits discrimination, harassment, and bullying. For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Notice and Disclaimer of Liability Concerning the Use of IEEE Documents: IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

Use of an IEEE Standard is wholly voluntary. IEEE disclaims liability for any personal injury, property or other damage, of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, or reliance upon any IEEE Standard document.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims any express or implied warranty, including any implied warranty of merchantability or fitness for a specific purpose, or that the use of the material contained in its standards is free from patent infringement. IEEE Standards documents are supplied "AS IS."

The existence of an IEEE Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard. Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity. Nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

Translations: The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

Official Statements: A statement, written or oral, that is not processed in accordance with the IEEE-SA Standards Board Operations Manual shall not be considered the official position of IEEE or any of its committees and shall not be considered to be, nor be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

Comments on Standards: Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important to ensure that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. Any person who would like to participate in evaluating comments or revisions to an IEEE standard is welcome to join the relevant IEEE working group at <http://standards.ieee.org/develop/wg/>.

Comments on standards should be submitted to the following address:

Secretary, IEEE-SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854-4141
USA

Photocopies: Authorization to photocopy portions of any individual standard for internal or personal use is granted by The Institute of Electrical and Electronics Engineers, Inc., provided that the appropriate fee is paid to Copyright Clearance Center. To arrange for payment of licensing fee, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Notice to users

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

This document is copyrighted by the IEEE. It is made available for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making this document available for use and adoption by public authorities and private users, the IEEE does not waive any rights in copyright to this document.

Updating of IEEE documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect. In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the [IEEE-SA Website](http://standards.ieee.org) or contact the IEEE at the address listed previously. For more information about the IEEE Standards Association or the IEEE standards development process, visit the [IEEE-SA Website](http://standards.ieee.org).

Errata

Errata, if any, for this and all other standards can be accessed at the following URL: <http://standards.ieee.org/findstds/errata/index.html>. Users are encouraged to check this URL for errata periodically.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE-SA Website at <http://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

Participants

The following individuals were officers and members of the IEEE 802.3 working group at the beginning of the IEEE P802.3.1 working group ballot. Individuals may have not voted, voted for approval, disapproval, or abstained on this standard.

David J. Law, *IEEE 802.3 Working Group Chair*
Wael William Diab, *IEEE 802.3 Working Group Vice Chair*
Steven B. Carlson, *IEEE 802.3 Working Group Executive Secretary*
Adam Healey, *IEEE 802.3 Working Group Secretary*
Valerie Maguire, *IEEE 802.3 Working Group Treasurer*

Howard M. Frazier, *IEEE P802.3.1 MIB Task Force Chair and Editor*

Ghani Abbas	Alan Flatman	John McDonough
John Abbott	Harry Forbes	Martin McNarney
Jon Anderson	Hongyan Fu	Mounir Meghelli
Peter Anslow	Ilango S. Ganga	Brian Misek
Koussalya Balasubramanian	Ali Ghiasi	Merrick Moeller
Vittal Balasubramanian	Dimitrios Giannakopoulos	Charles Moore
Thananya Baldwin	Michael Grimwood	Shimon Muller
Barry Barnett	Robert M. Grow	Paul Nikolic
Hugh Barrass	Mark Gustlin	Ronald Nordin
Denis Beaudoin	Marek Hajduczenia	Philip Northcott
Yakov Belopolsky	Hiroshi Hamano	Mark Nowell
Michael Bennett	Bernie Hammond	David Ofelt
Vipul Bhatt	Yasuo Hidaka	Valy Ossman
Sudeep Bhoja	Rita Horner	George Oulundsen
Will Bliss	Xi Huang	Tom Palkert
Brad Booth	James Innis	Sesha Panguluri
Ralf-Peter Braun	Osamu Ishida	Vasu Parthasarathy
Dirk Breuer	Hirotake Iwadata	Pravin Patel
Matthew Brown	Hongtao Jiang	Petar Pepeljugoski
Mark Bugg	Sanjay Kasturia	Gerald Pepper
Robert Busse	Myles Kimmitt	John Petrilla
J. Martin Carroll	Jonathan King	Rick Pimpinella
Mandeep Chadha	Scott Kipp	Rick Rabinovich
David Chalupsky	Satoshi Kodama	Adee Ran
Frank Chang	Paul Kolesar	Duane Remein
Chung-Jue Chen	Masashi Kono	Iain Robertson
Joseph Chou	Glen Kramer	Sam Sambasivan
Golam Choudhury	Bengt Kvist	Shawn Searles
Christopher R. Cole	Hans Lackner	Oren Sela
Charles Cook	Lowell Lamb	Megha Shanbhag
Kai Cui	Wayne Larsen	Stephen Shellhammer
John Dambrosia	Mark Laubach	Siddharth Sheth
Piers Dawe	David Lewis	Hyungsoo Shin
Patrick Diamond	Mike Peng Li	Kapil Shrikhande
Chris Diminico	Robert Lingle	Jeff Slavick
Dan Dove	Kent Lusted	Scott Sommers
Mike Dudek	Sharon Lutz	Bryan Sparrowhawk
David Dwelley	Jeffery J. Maki	Peter Stassar
Gareth Edwards	Edwin Mallette	Ken-Ichi Suzuki
Hesham Elbakoury	Arthur Marris	Steve Swanson
David Estes	Phil McClay	Andre Szczepanek
John Ewen	Michael S. McCormack	

Antonio Teixeira
Geoffrey Thompson
Nathan Tracy
Francois Tremblay
Stephen Trowbridge

Alexander Umnov
Sterling A. Vaden
Paul Vanderlaan
Zhong Feng Wang

Tim Warland
David Warren
Wendy Wu
Li Zeng
Pavel Zivny

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Thomas Alexander
Peter Anslow
Hugh Barrass
Ralf-Peter Braun
Nancy Bravin
Matthew Brown
William Byrd
Steven B. Carlson
Xin Chang
Keith Chow
Charles Cook
Wael William Diab
Patrick Diamond
Andrew Fieldsend
Yukihiro Fujimoto
Ilango Ganga
Gregory Gillooly
Randall Groves
Robert M. Grow
Michael Gundlach
Chris Guy
Marek Hajduczenia
Hiroshi Hamano
Adam Healey
Werner Hoelzl
Noriyuki Ikeuchi
Akio Iso

Atsushi Ito
Shinkyō Kaku
Piotr Karocki
Stuart Kerry
Yongbum Kim
Scott Kipp
Bruce Kraemer
Thomas Kurihara
Geoff Ladwig
Richard Lancaster
David J. Law
Ru Lin
William Lumpkins
Greg Luri
Elvis Maculuba
Ahmad Mahinfallah
Jeffery Maki
Wayne Manges
Jeffery Masters
Brett McClellan
Thomas McDermott
Michael McInnis
Jonathon McLendon
Jose Morales
Michael S. Newman
Nick S. A. Nikjoo
Satoshi Obara
Satoshi Oyama

Maximilian Riegel
Robert Robinson
Jeff Rockower
Dan Romascanu
Randall Safier
Bartien Sayogo
Oren Sela
Shusaku Shimada
Thomas Starai
Walter Struppler
Chandrasekaran
Subramaniam
William Szeto
William Taylor
Patricia Thaler
Michael Thompson
Dmitri Varsanofiev
Prabodh Varshney
John Vergis
George Vlantis
Hung-Yu Wei
Charles Wong
Chun Yu
Oren Yuen
Janusz Zalewski
Daidi Zhong

Acknowledgments

This document was derived in part from several Request for Comments (RFCs) originally published by the Internet Engineering Task Force (IETF). The following individuals contributed to the development of those RFCs, and to earlier works on the subject matter.

Brian Arnold
Udi Ashkenazi
Ran Atkinson
Mike Ayers
Hugh Barrass
Edward Beili
Avi Berger
Chuck Black
Brad Booth
Al Braga
Ben Brown
John Cook
Kevin Daines
James Davin
Kathryn de Graaf
Wael Willaim Diab
John Flick
Howard M. Frazier
Floyd Gerhardt

Robert M. Grow
Mike Heard
Alfred Hoenes
Jeff Johnson
Frank Kastenholz
Lior Khernmash
Lynn Kubinec
Kam Lam
David J. Law
Leon Long
Mike Lui
Eric Lynskey
David Martin
Keith McCloghrie
Kerry McDonald
Donna McMaster
Steve McRobert
John Messenger

K. C. Norseth
Dave Perkins
Marina Popilov
Randy Presuhn
Mathias Riess
Anil Rijasinghani
Sam Roberts
Dan Romascanu
Marshall Rose
Scott Simon
Andrew Smith
Matt Squire
Louis Steinberg
Kaj Tesink
Jonathan Thatcher
Geoffrey Thompson
Maurice Turcotte
Bert Wijnen
Paul Woodruff

When the IEEE-SA Standards Board approved this standard on 14 June 2013, it had the following membership:

John Kulick, *Chair*
David J. Law, *Vice Chair*
Richard H. Hulett, *Past Chair*
Konstantinos Karachalios, *Secretary*

Masayuki Ariyoshi
Peter Balma
Farooq Bari
Ted Burse
Wael William Diab
Stephen Dukes
Jean-Philippe Faure
Alexander Gelman

Mark Halpin
Gary Hoffman
Paul Houzé
Jim Hughes
Michael Janezic
Joseph L. Koepfinger*
Oleg Logvinov

Ron Petersen
Gary Robinson
Jon Walter Rosdahl
Adrian Stephens
Peter Sutherland
Yatin Trivedi
Phil Winston
Yu Yuan

*Member Emeritus

Also included are the following nonvoting IEEE-SA Standards Board liaisons:

Richard DeBlasio, *DOE Representative*
Michael Janezic, *NIST Representative*

Catherine Berger
IEEE Standards Senior Program Manager, Document Development

Lisa Perry
IEEE Standards Program Manager, Technical Program Development

Introduction

This introduction is not part of IEEE Std 802.3.1-2013, IEEE Standard for Management Information Base (MIB) Definitions for Ethernet.

The initial version of this standard was based on the managed object definitions provided in IEEE Std 802.3TM-2008, which subsumed and superseded IEEE Std 802.3anTM-2006, IEEE Std 802.3apTM-2007, IEEE Std 802.3aqTM-2006, and IEEE Std 802.3asTM-2006. It also includes the Logical Link Discovery Protocol Ethernet extensions provided in Annex F of IEEE Std 802.1ABTM-2009.^b In addition, the initial version of this standard incorporated and updated the MIB module definitions formerly defined in IETF RFC 2108 [B20],^c IETF RFC 3621 [B27], IETF RFC 3635 [B29], IETF RFC 3637 [B30], IETF RFC 4836 [B35], IETF RFC 4837 [B36], IETF RFC 4878 [B37], and IETF RFC 5066 [B38].

The first revision of this standard updated the MIB module definitions to reflect the managed object definitions provided in IEEE Std 802.3-2012, which subsumed and superseded IEEE Std 802.3-2008, IEEE Std 802.3atTM, IEEE Std 802.3avTM, IEEE Std 802.3azTM, IEEE Std 802.3baTM, IEEE Std 802.3bcTM, IEEE Std 802.3bdTM, IEEE Std 802.3bfTM, and IEEE Std 802.3bgTM.

^bInformation on references can be found in Clause 2.

^cThe numbers in brackets correspond to those of the bibliography in Annex A.

Contents

1.	Overview.....	1
1.1	Scope.....	2
1.2	Purpose.....	2
1.3	Internet-Standard Management Framework.....	2
1.4	Security considerations.....	2
1.5	Conformance.....	3
2.	Normative references.....	5
3.	Definitions.....	7
4.	Abbreviations.....	9
5.	Ethernet logical link discovery protocol (LLDP) extension MIB module.....	11
5.1	Structure of the IEEE 802.3 LLDP extension MIB.....	11
5.2	Relationship to other MIBs.....	11
5.3	Security considerations for IEEE 802.3 LLDP extension MIB module.....	14
5.4	MIB module definition.....	15
6.	Ethernet operations, administration, and maintenance (OAM) MIB module.....	41
6.1	Introduction.....	41
6.2	Overview.....	41
6.2.1	Remote fault indication.....	41
6.2.2	Link monitoring.....	41
6.2.3	Remote loopback.....	42
6.2.4	Ethernet OAM protocol data units.....	42
6.3	Relation to other MIB modules.....	42
6.3.1	Relation to other EFM MIB modules.....	42
6.3.2	Mapping of IEEE 802.3 managed objects.....	42
6.4	MIB structure.....	45
6.5	Security considerations for Ethernet operations, administration, and maintenance (OAM) MIB module.....	45
6.6	MIB module definition.....	46
7.	Ethernet repeater device MIB module.....	83
7.1	Overview.....	83
7.1.1	Repeater management.....	83
7.1.2	Structure of the MIB.....	83
7.1.3	Relationship to MIB-II.....	83
7.2	Topology mapping.....	84
7.3	MIB module definition.....	84
8.	Ethernet data terminal equipment (DTE) power via medium dependent interface (MDI) MIB module.....	129
8.1	Introduction.....	129
8.2	Overview.....	129
8.3	MIB structure.....	129

8.4	Security considerations for Ethernet data terminal equipment (DTE) power via medium dependent interface (MDI) MIB module	129
8.5	MIB module definition	130
9.	Ethernet passive optical networks (EPON) MIB module	143
9.1	Overview	143
9.1.1	EPON architecture highlights	143
9.1.2	Management architecture	149
9.2	MIB structure	150
9.3	Relationship to other MIB modules	154
9.3.1	Relation to the Interfaces Group MIB and Ethernet-like interface MIB	154
9.3.2	Relation to the IEEE 802.3 MAU MIBs	160
9.3.3	Relation to the Ethernet OAM MIB	160
9.3.4	Relation to the bridge MIB	160
9.4	Mapping of IEEE 802.3 managed objects	160
9.5	Security considerations for Ethernet passive optical network (EPON) MIB module	163
9.5.1	dot3MpcpAdminState	163
9.5.2	dot3EponFecMode	163
9.5.3	dot3ExtPkgObjectReset	163
9.5.4	dot3ExtPkgObjectPowerDown	163
9.5.5	dot3ExtPkgObjectFecEnabled	163
9.5.6	dot3ExtPkgObjectRegisterAction	163
9.5.7	dot3ExtPkgObjectReportNumThreshold	163
9.5.8	dot3ExtPkgObjectReportThreshold	163
9.5.9	dot3ExtPkgOptIfLowerInputPowerThreshold	164
9.5.10	dot3ExtPkgOptIfUpperInputPowerThreshold	164
9.5.11	dot3ExtPkgOptIfLowerOutputPowerThreshold	164
9.5.12	dot3ExtPkgOptIfUpperOutputPowerThreshold	164
9.5.13	dot3ExtPkgOptIfTransmitEnable	164
9.6	MIB module definition	164
10.	Ethernet-like interface MIB module	209
10.1	Introduction	209
10.2	Overview	209
10.2.1	Relation to MIB-2	209
10.2.2	Relation to the Interfaces Group MIB	209
10.2.3	Relation to the IEEE 802.3 MAU-MIB module	215
10.2.4	Mapping of IEEE 802.3 managed objects	216
10.3	Security considerations for Ethernet-like interface MIB module	218
10.4	MIB module definition	219
11.	Ethernet in the First Mile copper (EFMCu) interfaces MIB module	253
11.1	Introduction	253
11.2	Relation to other MIB modules	253
11.2.1	Relation to Interfaces Group MIB module	253
11.2.2	Relation to SHDSL MIB module	259
11.2.3	Relation to VDSL MIB module	259
11.2.4	Relation to Ethernet-Like and MAU MIB modules	259
11.3	MIB structure	260
11.3.1	EFM copper MIB overview	260
11.3.2	PME profiles	260

11.3.3 Mapping of IEEE 802.3 managed objects	261
11.4 Security considerations for Ethernet in the First Mile copper interfaces MIB module	262
11.5 MIB module definition	262
12. Ethernet wide area network (WAN) interface sublayer (WIS) MIB module	313
12.1 Overview	313
12.1.1 Relationship to the SONET/SDH interface MIB	313
12.1.2 Relationship to the Ethernet-like interface MIB	313
12.1.3 Relationship to the IEEE 802.3 MAU MIB	314
12.1.4 Use of the ifTable	314
12.1.5 SONET/SDH terminology	315
12.1.6 Mapping of IEEE 802.3 managed objects	315
12.1.7 Mapping of SNMP objects to WIS station management registers	319
12.1.8 Structure of the MIB module	322
12.2 Security considerations for Ethernet wide area network (WAN) interface sublayer (WIS) MIB module	323
12.3 MIB module definition	324
Annex 12A (informative) Collection of performance data using WIS MDIO registers	337
13. Ethernet medium attachment units (MAUs) MIB module	339
13.1 Introduction	339
13.2 Overview	339
13.2.1 Relationship to IETF RFC 3636 and IETF RFC 4836	339
13.2.2 Relationship to other MIBs	339
13.2.3 Management of internal MAUs	340
13.2.4 Mapping of IEEE 802.3 managed objects	340
13.2.5 Addition of new MAU types	343
13.3 Security considerations for Ethernet medium attachment units (MAUs) MIB module	344
13.4 IANA considerations	344
13.5 MIB module definition	344
Annex A (informative) Bibliography	375
Annex B (normative) Branch and leaf assignments for IEEE 802.3 and IEEE 802.3.1 managed objects	379
B.1 Branch and leaf table	379

IEEE Standard for Management Information Base (MIB) Definitions for Ethernet

IMPORTANT NOTICE: IEEE Standards documents are not intended to ensure safety, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

This IEEE document is made available for use subject to important notices and legal disclaimers. These notices and disclaimers appear in all publications containing this document and may be found under the heading "Important Notice" or "Important Notices and Disclaimers Concerning IEEE Documents." They can also be obtained on request from IEEE or viewed at <http://standards.ieee.org/IPR/disclaimers.html>.

1. Overview

This document supersedes and makes obsolete Annex 30A and Annex 30B of IEEE Std 802.3™-2008, Annex F of IEEE Std 802.1AB™-2009,¹ IETF RFC 2108 [B20],² IETF RFC 3621 [B27], IETF RFC 3635 [B29], IETF RFC 3637 [B30], IETF RFC 4836 [B35], IETF RFC 4837 [B36], IETF RFC 4878 [B37], and IETF RFC 5066 [B38].

Ethernet technology, as defined by the IEEE 802.3 Working Group, continues to evolve, with scalable increases in speed, new types of cabling and interfaces, and new features. This evolution may require changes in the managed objects in order to reflect this new functionality. This document, as with other documents issued by this working group, reflects a certain stage in the evolution of Ethernet technology. In the future, this document might be revised, or new documents might be issued, in order to reflect the evolution of Ethernet technology.

The term "Ethernet-like interfaces" was historically used because the interfaces defined by the IEEE 802.3 Working Group were not considered "Ethernet" per se, but "Ethernet-like," because "Ethernet" was taken to

¹Information on references can be found in Clause 2.

²The numbers in brackets correspond to those of the bibliography in Annex A.

mean “Ethernet version 2” according to the (DEC, Intel, Xerox) DIX “blue book.” Today and in the context of SNMP management and SMIPv2 MIB modules, “Ethernet,” “Ethernet-like,” and “IEEE 802.3” are synonymous and interchangeable in the marketplace. The term “Ethernet-like” is retained in this document because of its common usage in the SNMP-based network management community.

1.1 Scope

This standard contains the Management Information Base (MIB) module specifications for IEEE Std 802.3, also known as Ethernet. It includes the Structure of Management Information Version 2 (SMIPv2) MIB module specifications formerly produced and published by the Internet Engineering Task Force (IETF), and the managed object branch and leaf assignments provided in the Guidelines for the Definition of Managed Objects (GDMO) MIB modules formerly specified within IEEE Std 802.3, as well as extensions resulting from recent amendments to IEEE Std 802.3. The SMIPv2 MIB modules are intended for use with the Simple Network Management Protocol (SNMP), commonly used to manage Ethernet.

1.2 Purpose

The purpose of the standard is to publish the SMIPv2 MIB module specifications in a single document that is separate from IEEE Std 802.3, and that can be published in a machine-readable format. Future amendments and revisions to IEEE Std 802.3.1 will be performed to update the MIB specifications as required to track future amendments and revisions to IEEE Std 802.3.

1.3 Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of IETF RFC 3410.

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the SNMP.

Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This standard specifies MIB modules that are compliant to the SMIPv2, which is described in IETF STD 58 (RFC 2578), IETF STD 58 (RFC 2579), and IETF STD 58 (RFC 2580).

1.4 Security considerations

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPSec), there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in a MIB module.

Implementers should consider the security features as provided by the SNMPv3 framework (see section 8 of IETF RFC 3410), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

SNMPv3 should be deployed, rather than previous versions of SNMP, and cryptographic security should be enabled. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

Throughout this standard, there are a number of accessible management objects that may be considered sensitive or vulnerable in some network environments. The support for some operations in a non-secure

environment without proper protection can have a negative effect on network operations. Such management objects are detailed in the clauses that define them.

The user of these MIB modules should therefore be aware that support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations.

The readable objects in these MIB modules (i.e., those with MAX-ACCESS other than not-accessible) may be considered sensitive in some environments since, collectively, they provide information about the performance of network interfaces and can reveal some aspects of their configuration. In such environments, it is important to control GET and NOTIFY access to these objects and possibly encrypt their values when sending them over the network via SNMP.

1.5 Conformance

Specific conformance statements and compliance statements, written in accordance with IETF STD 58, RFC 2580, are included in each MIB module. They can be found by searching for the text strings “Conformance statements” and “Compliance statements.”

2. Normative references

The following referenced documents are indispensable for the application of this document (i.e., they must be understood and used, so each referenced document is cited in text and its relationship to this document is explained). For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments or corrigenda) applies.

ANSI T1.231-1997, Layer 1 In-Service Digital Transmission Performance Monitoring.³

ANSI T1.424-2004, Interface Between Networks and Customer Installation—Very-high-bit-rate Digital Subscriber Lines (VDSL) Metallic Interface (DMT Based).

ETSI TS1 101 270-1 (1999), Transmission and Multiplexing (TM); Access transmission systems on metallic access cables; Very high speed Digital Subscriber Line (VDSL); Part 1: Functional requirements.⁴

IEEE Std 802[®], IEEE Standard for Local and Metropolitan Area Networks—Architecture and Overview.^{5, 6}

IEEE Std 802.1D[™], IEEE Standard for Local and Metropolitan Area Networks—Media Access Control (MAC) Bridges.

IEEE Std 802.1AB[™]-2009, IEEE Standard for Local and Metropolitan Area Networks—Station and Media Access Control Discovery.

IEEE Std 802.3[™], IEEE Standard for Ethernet.

IEEE Std 802.9a[™]-1995, IEEE Standards for Local and Metropolitan Area Networks—Supplement to Integrated Services (IS) LAN Interface at the Medium Access Control (MAC) and Physical (PHY) Layers—Specification of IsLAN16-T.

IETF RFC 1213, Management Information Base for Network Management of TCP/IP-based internets: MIB-II, McCloghrie, K., and Rose, M., Mar. 1991.⁷

IETF RFC 1516, Definitions of Managed Objects for IEEE 802.3 Repeater Devices, McMaster, D., and McCloghrie, K., Sept. 1993.

IETF RFC 2119, Keywords for use in RFCs to Indicate Requirement Levels, Bradner, S., Mar. 1997.

IETF RFC 2434, Guidelines for Writing an IANA Considerations Section in RFCs, Narten, T. and Alvestrand, H., Oct. 1998.

IETF STD 58 (RFC 2578), Structure of Management Information Version 2 (SMIv2), McCloghrie, K., Perkins, D., and Schoenwaelder, J., Apr. 1999.

IETF STD 58 (RFC 2579), Textual Conventions for SMIv2, McCloghrie, K., Perkins, D., and Schoenwaelder, J., Apr. 1999.

IETF STD 58 (RFC 2580), Conformance Statements for SMIv2, McCloghrie, K., Perkins, D., and Schoenwaelder, J., Apr. 1999.

³ANSI publications are available from the American National Standards Institute (<http://www.ansi.org/>).

⁴ETSI publications are available from the European Telecommunications Standards Institute (<http://www.etsi.org/>).

⁵IEEE publications are available from The Institute of Electrical and Electronics Engineers (<http://standards.ieee.org/>).

⁶The IEEE standards or products referred to in this clause are trademarks of The Institute of Electrical and Electronics Engineers, Inc.

⁷IETF documents (i.e., RFCs) are available for download at <http://www.rfc-archive.org/>.

IETF RFC 2856, Textual Conventions for Additional High Capacity Data Types, Bierman, A., McCloghrie, K., and Presuhn, R., June 2000.

IETF RFC 2863, The Interfaces Group MIB, McCloghrie, K., and Kastenholz, F., June 2000.

IETF RFC 2864, The Inverted Stack Table Extension to the Interfaces Group MIB, McCloghrie, K., and Hanson, G., June 2000.

IETF RFC 3410, Introduction and Applicability Statements for Internet Standard Management Framework, Case, J., Mundy R., Partain, D., and Stewart, B., Dec. 2002.

IETF RFC 3411, An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks, Harrington, D., Presuhn, R., and Wijnen, B., Dec. 2002.

IETF RFC 3592, Definitions of Managed Objects for the Synchronous Optical Network/Synchronous Digital Hierarchy (SONET/SDH) Interface Type, Tesink, K., Sept. 2003.

ITU-T Recommendation G.983.1, 1998—Optical line systems for local and access networks—Broadband optical access systems based on Passive Optical Networks (PON).⁸

ITU-T Recommendation G.991.2, 2003—Single-pair High-speed Digital Subscriber Line (SHDSL) transceivers.

ITU-T Recommendation G.993.1, 2004—Very high speed digital subscriber line transceivers.

⁸ITU-T publications are available from the International Telecommunications Union (<http://www.itu.int/>).

3. Definitions

For the purposes of this document, the following terms and definitions apply. *The IEEE Standards Dictionary Online* should be consulted for terms not defined in this clause.⁹

agent: An entity, typically implemented in software, which provides remote access to management instrumentation, via the Simple Network Management Protocol (SNMP).

group: Within the context of the repeater management Management Information Base (MIB) module defined in Clause 7 of IEEE Std 802.3.1-2013: A recommended, but optional, entity defined in Clause 30 of IEEE Std 802.3, in order to support a modular numbering scheme. The classic example allows an implementor to represent field-replaceable units as groups of ports, with the port numbering matching the modular hardware implementation.

jack type: The jack connector type, as it appears on the outside of the system. The type of mechanical interface to the transmission medium.

Loss of Codegroup Delineation: See 50.3.5.3 of IEEE Std 802.3.

managed object: An abstract representation of network resources that are managed. A managed object is defined according to the *Structure of Management Information version 2* (SMIv2) defined in IETF STD 58, RFC 2578.

managed repeater: A repeater as defined by IEEE Std 802.3 incorporating a management entity that complies with the Management Information Base (MIB) module definition contained in Clause 7 of IEEE Std 802.3.1-2013.

module: A building block in a modular system. In the context of the MIB definitions, a specification of management capabilities related to the system. In the context of a chassis, it typically maps into one “slot”; however, the range of configurations may be very large, with several modules entering one slot, or one module covering several slots.

non-trivial repeater: A repeater as defined by IEEE Std 802.3 having multiple ports.

Path Coding violations: In IEEE Std 802.3, the path layer coding violations count is based on block errors and not on BIP-8 errors; i.e., it is incremented only once for each B3 byte that indicates incorrect parity, regardless of the number of bits in error. Note that Section 8.4.5.1 of ANSI T1.231-1997 allows either path BIP-8 errors or path block errors to be used for the path layer error count.

repeater system: A managed entity compliant with this standard and incorporating at least one managed IEEE 802.3 repeater.

repeater-unit: The portion of a repeater that is inboard of its Physical Medium Attachment (PMA)/Physical Signaling Sublayer (PLS) or PMA/Physical Coding Sublayer (PCS).

Signal Label Mismatch: This defect is called Payload Label Mismatch (PLM) in IEEE Std 802.3. It is reported by setting both the `sonetPathSignalLabelMismatch` bit in the appropriate instance of `sonetPathCurrentStatus` (defined in IETF RFC 3592) and the `etherWisPathPLM` bit in the corresponding instance of `etherWisPathCurrentStatus`.

stack: A scalable system in which modularity is achieved by interconnecting a number of different systems.

⁹The *IEEE Standards Dictionary Online* subscription is available at http://www.ieee.org/portal/innovate/products/standard/standards_dictionary.html.

STS-Path Remote Defect Indication: IEEE Std 802.3 mandates the use of ERDI-P (Enhanced Remote Defect Indication-Path) defined in ANSI T1.231-1997 to signal remote server defects (triggered by path AIS or path LOP) and remote payload defects (triggered by Payload Label Mismatch or Loss of Codegroup Delineation). IETF RFC 3592 defines the one-bit RDI-P (Remote Defect Indication-Path), which signals remote server detects (i.e., path AIS and path LOP) only. An implementation of the MIB module defined in Clause 12 of IEEE Std 802.3.1-2013 sets the sonetPathSTSRDI bit in the appropriate instance of sonetPathCurrentStatus when it receives an ERDI-P server defect indication from the remote end. Both ERDI-P payload defects and ERDI-P server defects are reported in the object etherWisFarEndPathCurrentStatus.

system: An entity compliant with one or more Management Information Base (MIB) modules of this standard.

system interconnect segment: An internal segment allowing interconnection of ports belonging to different physical entities into the same logical managed repeater, bridge, or other system. Examples of implementation might be backplane busses in modular hubs, or chaining cables in stacks of bridges/switches. It is not uncommon for such segments to be a proprietary implementation.

trivial repeater-unit: An isolated port that can gather statistics.

4. Abbreviations

ACK	acknowledge
AIS	Alarm Indication Signal
ARP	address resolution protocol
ASCII	American Standard Code for Information Interchange
Atn	attenuation
BER	bit error ratio
BIP	bit interleaved parity
BW	bandwidth
CO	central office
CPE	customer premises equipment
CRC	cyclic redundancy check
DTE	data terminal equipment
EFM	Ethernet in the First Mile
EFMCu	EFM copper
ELTE	Ethernet line termination equipment
EPON	Ethernet passive optical network
ERDI-P	enhanced remote defect indication—path
FCS	frame check sequence
FEC	forward error correction
GDMO	Guidelines for Definition of Managed Objects
GMII	gigabit media independent interface
IANA	Internet Assigned Numbers Authority
IETF	Internet Engineering Task Force
IFG	inter-frame gap
ITU	International Telecommunication Union
LAN	local area network
LCD	Loss of Codegroup Deliniation
LLC	logical link control
LLDP	logical link discovery protocol
LLDPDU	logical link discovery protocol data unit
LLID	logical link identifier
LOP	Loss of Pointer
LTE	line termination equipment
MAC	media access control
MAU	medium attachment unit
Mb/s	megabit per second
MDI	medium dependent interface
MDIO	management data input/output
MII	media independent interface
MP2PE	multipoint-to-point emulation
MPCP	multipoint control protocol
MPCPDU	multipoint control protocol data unit
MTU	maximum transmission unit
NMS	network management system

OAM	operations, administration, and maintenance
OAMPDU	operations, administration, and maintenance protocol data unit
OID	object identifier
OLT	optical line terminal
OMP	optical multipoint
ONU	optical network unit
OSI	Open Systems Interconnection
P2MP	point-to-multipoint
P2PE	point-to-point emulation
PAF	PME aggregation function
PBO	power back-off
PCS	physical coding sublayer
PD	powered device
PDU	protocol data unit
PHY	Physical Layer entity
PLM	Payload Label Mismatch
PMA	physical medium attachment
PMD	physical medium dependent
PME	physical medium entity
PON	passive optical network
PSD	power spectral density
PSE	power sourcing equipment
RFC	Request for Comments
ROM	read-only-memory
RS	reconciliation sublayer
RTT	round-trip time
SDH	Synchronous Digital Hierarchy
SLA	service level agreement
SLD	start of LLID delimiter
SMIv2	structure of management information version 2
SNMP	simple network management protocol
SNR	signal-to-noise ratio
SONET	Synchronous Optical Network
TCPAM	trellis coded pulse amplitude modulation
TDM	time division multiplexing
TDMA	time division multiple access
TLV	type/length/value
TQ	time quanta
WAN	wide area network
WDM	wavelength division multiplexing
WIS	WAN interface sublayer

5. Ethernet logical link discovery protocol (LLDP) extension MIB module

The logical link discovery protocol (LLDP) is defined in IEEE Std 802.1AB-2009, Station and Media Access Control Discovery. Extensions to this protocol for Ethernet are defined in Clause 79 of IEEE Std 802.3.

5.1 Structure of the IEEE 802.3 LLDP extension MIB

Table 5-1 summarizes the particular object groups that are required for each operating mode. The implemented MIB shall comply with the MIB conformance section for the particular operating mode being supported.

Table 5-1—IEEE 802.3 LLDP extension MIB object group conformance requirements

MIB group	Rx mode	Tx mode	Tx/Rx mode
lldpV2Xdot3ConfigGroup	M ^a	M	M
lldpV2Xdot1LocSysGroup	M	—	M
lldpV2Xdot1RemSysGroup	—	M	M
ifGeneralInformationGroup	M	M	M

^aM = Mandatory.

Table 5-2 shows the structure of the MIB and the relationship of the MIB objects to the LLDP operational status/control variables, LLDP statistics variables, and TLV variables.

5.2 Relationship to other MIBs

Version 1 of the IEEE 802.3 LLDP extension MIB module is deprecated.

Table 5-2—IEEE 802.3/LLDP extension MIB cross reference

MIB table	MIB object	LLDP reference
<i>Configuration group</i>		
lldpV2Xdot3PortConfigTable		Augments lldpV2PortConfigEntry
	lldpV2Xdot3PortConfigTLVsTxEnable	Normal LLDPDUs
<i>Local devices information group</i>		
lldpV2Xdot3LocPortTable		
	lldpV2LocPortIfIndex	(Table index)
	lldpV2Xdot3LocPortAutoNegSupported	Auto-Negotiation support/status
	lldpV2Xdot3LocPortAutoNegEnabled	Auto-Negotiation support/status
	lldpV2Xdot3LocPortAutoNegAdvertisedCap	Auto-Negotiation advertised
	lldpV2Xdot3LocPortOperMauType	Operational MAU type
lldpV2Xdot3LocPowerTable		
	lldpV2LocPortIfIndex	(Table index)
	lldpV2Xdot3LocPowerPortClass	MDI power support
	lldpV2Xdot3LocPowerMDISupported	MDI power support
	lldpV2Xdot3LocPowerMDIEnabled	MDI power support
	lldpV2Xdot3LocPowerPairControlable	MDI power support
	lldpV2Xdot3LocPowerPairs	PSE power pair
	lldpV2Xdot3LocPowerClass	Power class
lldpV2Xdot3LocMaxFrameSizeTable		
	lldpV2LocPortIfIndex	(Table index)
	lldpV2Xdot3LocMaxFrameSize	Maximum frame size
<i>Remote devices information group</i>		
lldpV2Xdot3RemPortTable		
	lldpV2RemTimeMark	(Table index)
	lldpV2RemLocalIfIndex	(Table index)
	lldpV2RemLocalDestMACAddress	(Table index)
	lldpV2RemIndex	(Table index)
	lldpV2Xdot3RemPortAutoNegSupported	Auto-Negotiation support/status
	lldpV2Xdot3RemPortAutoNegEnabled	Auto-Negotiation support/status
	lldpV2Xdot3RemPortAutoNegAdvertisedCap	Auto-Negotiation advertised
	lldpV2Xdot3RemPortOperMauType	Operational MAU type

Table 5-2—IEEE 802.3/LLDP extension MIB cross reference (continued)

MIB table	MIB object	LLDP reference
lldpV2Xdot3RemPowerTable		
	lldpV2RemTimeMark	(Table index)
	lldpV2RemLocalIfIndex	(Table index)
	lldpV2RemLocalDestMACAddress	(Table index)
	lldpV2RemIndex	(Table index)
	lldpV2Xdot3RemPowerPortClass	MDI power support
	lldpV2Xdot3RemPowerMDISupported	MDI power support
	lldpV2Xdot3RemPowerMDIEnabled	MDI power support
	lldpV2Xdot3RemPowerPairControlable	MDI power support
	lldpV2Xdot3RemPowerPairs	PSE power pair
	lldpV2Xdot3RemPowerClass	Power class
lldpV2Xdot3RemMaxFrameSizeTable		
	lldpV2RemTimeMark	(Table index)
	lldpV2RemLocalIfIndex	(Table index)
	lldpV2RemLocalDestMACAddress	(Table index)
	lldpV2RemIndex	(Table index)
	lldpV2Xdot3RemMaxFrameSize	Maximum frame size

5.3 Security considerations for IEEE 802.3 LLDP extension MIB module

There are a number of management objects defined in this MIB module with a MAX-ACCESS clause of read-write.¹⁰ Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations.

Setting the object, `lldpV2Xdot3PortConfigTLVsTxEnable`, to incorrect values can result in improper operation of LLDP.

The following readable objects in this MIB module may be considered to be sensitive or vulnerable in some network environments:

a) Objects that are associated with the transmit mode are as follows:

- 1) `lldpV2Xdot3LocPortAutoNegSupported`
- 2) `lldpV2Xdot3LocPortAutoNegEnabled`
- 3) `lldpV2Xdot3LocPortAutoNegAdvertisedCap`
- 4) `lldpV2Xdot3LocPortOperMauType`
- 5) `lldpV2Xdot3LocPowerPortClass`
- 6) `lldpV2Xdot3LocPowerMDISupported`
- 7) `lldpV2Xdot3LocPowerMDIEnabled`
- 8) `lldpV2Xdot3LocPowerPairControlable`
- 9) `lldpV2Xdot3LocPowerPairs`
- 10) `lldpV2Xdot3LocPowerClass`
- 11) `lldpV2Xdot3LocMaxFrameSize`

b) Objects that are associated with the receive mode are as follows:

- 1) `lldpV2Xdot3RemPortAutoNegSupported`
- 2) `lldpV2Xdot3RemPortAutoNegEnabled`
- 3) `lldpV2Xdot3RemPortAutoNegAdvertisedCap`
- 4) `lldpV2Xdot3RemPortOperMauType`
- 5) `lldpV2Xdot3RemPowerPortClass`
- 6) `lldpV2Xdot3RemPowerMDISupported`
- 7) `lldpV2Xdot3RemPowerMDIEnabled`
- 8) `lldpV2Xdot3RemPowerPairControlable`
- 9) `lldpV2Xdot3RemPowerPairs`
- 10) `lldpV2Xdot3RemPowerClass`
- 11) `lldpV2Xdot3RemMaxFrameSize`

This concern applies both objects that describe the configuration of the local host, as well as objects that describe information from the remote hosts, acquired via LLDP and displayed by the objects in this MIB module. It is thus also important to control GET and/or NOTIFY access to these objects and possibly to encrypt the values of these objects when sending them over the network via SNMP.

¹⁰In IETF MIB definitions, the MAX-ACCESS clause defines the type of access that is allowed for particular data elements in the MIB. An explanation of the MAX-ACCESS mapping is given in section 7.3 of IETF STD 58, RFC 2578.

5.4 MIB module definition

In the following MIB definition, should any discrepancy between the DESCRIPTION text and the corresponding definition in 5.2 through 5.3 of this clause occur, the definitions in 5.2 through 5.3 shall take precedence.

An ASCII text version of the MIB definition can be found at the following URL¹¹:

http://www.ieee802.org/3/1/public/mib_modules/20130411/802dot3dot1C5mib.txt

Two additional modules must be imported when compiling the IEEE 802.3 LLDP extension MIB module, and they can be found at the following URLs:

<http://www.ieee802.org/1/files/public/MIBs/LLDP-V2-MIB-200906080000Z.txt>

<http://www.ieee802.org/1/files/public/MIBs/LLDP-V2-TC-MIB-200906080000Z.txt>

¹¹Copyright release for MIB modules: Users of this standard may freely reproduce the MIB module contained in this subclause so that it can be used for its intended purpose.


```

IEEE8023-DOT3-LLDP-EXT-V2-MIB DEFINITIONS ::= BEGIN

IMPORTS
    MODULE-IDENTITY,
    OBJECT-TYPE,
    Unsigned32,
    Integer32,
    org
        FROM SNMPv2-SMI
    TruthValue
        FROM SNMPv2-TC
    MODULE-COMPLIANCE,
    OBJECT-GROUP
        FROM SNMPv2-CONF
    ifGeneralInformationGroup
        FROM IF-MIB
    lldpV2LocPortIfIndex,
    lldpV2RemLocalIfIndex,
    lldpV2RemTimeMark,
    lldpV2RemLocalDestMACAddress,
    lldpV2RemIndex,
    lldpV2PortConfigEntry
        FROM LLDP-V2-MIB
-- http://www.ieee802.org/1/files/public/MIBs/LLDP-V2-MIB-200906080000Z.txt
    LldpV2PowerPortClass
        FROM LLDP-V2-TC-MIB
-- http://www.ieee802.org/1/files/public/MIBs/LLDP-V2-TC-MIB-200906080000Z.txt
;

ieee8023lldpV2Xdot3MIB MODULE-IDENTITY
    LAST-UPDATED "201304110000Z" -- April 11, 2013
    ORGANIZATION "IEEE 802.3 Working Group"
    CONTACT-INFO
        "WG-URL: http://www.ieee802.org/3/index.html
        WG-EMail: STDS-802-3-MIB@LISTSERV.IEEE.ORG

        Contact: Howard Frazier
        Postal: 3151 Zanker Road
               San Jose, CA 95134
               USA
        Tel: +1.408.922.8164
        E-mail: hfrazier@broadcom.com"
    DESCRIPTION
        "The LLDP Management Information Base extension module for
        IEEE 802.3 organizationally defined discovery information."

    REVISION "201304110000Z" -- April 11, 2013
    DESCRIPTION
        "Revision, based on an earlier version in IEEE Std 802.3.1-2011."

    REVISION "201102020000Z" -- February 2, 2011
    DESCRIPTION
        "This revision incorporated changes to the MIB module to
        add objects to support management of Energy Efficient
        Ethernet (EEE) and Enhanced DTE Power via the MDI (PoE+)."
```

```

 ::= { org ieee(111)
       standards-association-numbers-series-standards(2)
       lan-man-stds(802)ieee802dot3(3) ieee802dot3dot1mibs(1) 5 }

-----
--
-- Organizationaly Defined Information Extension - IEEE 802.3
--
-----

lldpV2Xdot3Objects      OBJECT IDENTIFIER ::= { ieee8023lldpV2Xdot3MIB 1 }

-- LLDP IEEE 802.3 extension MIB groups
lldpV2Xdot3Config      OBJECT IDENTIFIER ::= { lldpV2Xdot3Objects 1 }
lldpV2Xdot3LocalData   OBJECT IDENTIFIER ::= { lldpV2Xdot3Objects 2 }
lldpV2Xdot3RemoteData  OBJECT IDENTIFIER ::= { lldpV2Xdot3Objects 3 }

-----

-- IEEE 802.3 - Configuration
-----

--
-- Version 2 of lldpV2Xdot3PortConfigTable
-- supports use of multiple destination MAC addresses
--

lldpV2Xdot3PortConfigTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF LldpV2Xdot3PortConfigEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "A table that controls selection of LLDP TLVs to be transmitted
         on individual ports."
    ::= { lldpV2Xdot3Config 1 }

lldpV2Xdot3PortConfigEntry OBJECT-TYPE
    SYNTAX      LldpV2Xdot3PortConfigEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "LLDP configuration information that controls the
         transmission of IEEE 802.3 organizationally defined TLVs on
         LLDP transmission capable ports.

        This configuration object augments the lldpV2PortConfigEntry of
        the LLDP-MIB, therefore it is only present along with the port
        configuration defined by the associated lldpV2PortConfigEntry
        entry.

        Each active lldpV2Xdot3PortConfigEntry is restored from non-volatile
        storage (along with the corresponding lldpV2PortConfigEntry)
        after a re-initialization of the management system."
    AUGMENTS { lldpV2PortConfigEntry }

```

```

 ::= { lldpV2Xdot3PortConfigTable 1 }

LldpV2Xdot3PortConfigEntry ::= SEQUENCE {
    lldpV2Xdot3PortConfigTLVsTxEnable BITS
}

lldpV2Xdot3PortConfigTLVsTxEnable OBJECT-TYPE
    SYNTAX      BITS {
        macPhyConfigStatus(0),
        powerViaMDI(1),
        unused(2), --avoids re-use of the old link agg bit number
        maxFrameSize(3)
    }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The lldpV2Xdot3PortConfigTLVsTxEnable, defined as a bitmap,
        includes the IEEE 802.3 organizationally defined set of LLDP
        TLVs whose transmission is allowed by the local LLDP agent by
        the network management. Each bit in the bitmap corresponds
        to an IEEE 802.3 subtype associated with a specific IEEE
        802.3 optional TLV.

        The bit 'macPhyConfigStatus(0)' indicates that the LLDP agent
        should transmit 'MAC/PHY configuration/status TLV'.

        The bit 'powerViaMDI(1)' indicates that the LLDP agent should
        transmit 'Power via MDI TLV'.

        The bit 'unused(2)' is no longer used; this was used for
        the 'Link Aggregation TLV' in the previous version.

        The bit 'maxFrameSize(3)' indicates that the LLDP agent should
        transmit 'Maximum-frame-size TLV'.

        The default value for lldpV2Xdot3PortConfigTLVsTxEnable object
        is an empty set, which means no enumerated values are set.

        The value of this object is restored from non-volatile
        storage after a re-initialization of the management system."
    REFERENCE
        "IEEE Std 802.3 30.12.1.1.1"
    DEFVAL { { } }
    ::= { lldpV2Xdot3PortConfigEntry 1 }

```

```

-----
-- IEEE 802.3 - Local Device Information
-----

```

```

---
--- lldpV2Xdot3LocPortTable: Ethernet Port AutoNeg/Speed/Duplex
---                               Information Table
--- V2 modified to be indexed by ifIndex.
---

```

```

lldpV2Xdot3LocPortTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF LldpV2Xdot3LocPortEntry

```

```

MAX-ACCESS    not-accessible
STATUS        current
DESCRIPTION
    "This table contains one row per port of Ethernet port
    information (as a part of the LLDP 802.3 organizational
    extension) on the local system known to this agent."
 ::= { lldpV2Xdot3LocalData 1 }

```

```

lldpV2Xdot3LocPortEntry OBJECT-TYPE
SYNTAX        LldpV2Xdot3LocPortEntry
MAX-ACCESS    not-accessible
STATUS        current
DESCRIPTION
    "Information about a particular port component."
INDEX         { lldpV2LocPortIfIndex }
 ::= { lldpV2Xdot3LocPortTable 1 }

```

```

LldpV2Xdot3LocPortEntry ::= SEQUENCE {
    lldpV2Xdot3LocPortAutoNegSupported    TruthValue,
    lldpV2Xdot3LocPortAutoNegEnabled      TruthValue,
    lldpV2Xdot3LocPortAutoNegAdvertisedCap OCTET STRING,
    lldpV2Xdot3LocPortOperMauType         Unsigned32
}

```

```

lldpV2Xdot3LocPortAutoNegSupported OBJECT-TYPE
SYNTAX        TruthValue
MAX-ACCESS    read-only
STATUS        current
DESCRIPTION
    "The truth value used to indicate whether the given port
    (associated with the local system) supports Auto-negotiation."
REFERENCE
    "IEEE Std 802.3 30.12.2.1.1"
 ::= { lldpV2Xdot3LocPortEntry 1 }

```

```

lldpV2Xdot3LocPortAutoNegEnabled OBJECT-TYPE
SYNTAX        TruthValue
MAX-ACCESS    read-only
STATUS        current
DESCRIPTION
    "The truth value used to indicate whether port
    Auto-negotiation is enabled on the given port associated
    with the local system."
REFERENCE
    "IEEE Std 802.3 30.12.2.1.2"
 ::= { lldpV2Xdot3LocPortEntry 2 }

```

```

lldpV2Xdot3LocPortAutoNegAdvertisedCap OBJECT-TYPE
SYNTAX        OCTET STRING(SIZE(2))
MAX-ACCESS    read-only
STATUS        current
DESCRIPTION
    "This object contains the value (bitmap) of the
    ifMauAutoNegCapAdvertisedBits object (defined in IETF RFC
    3636) which is associated with the given port on the
    local system."
REFERENCE
    "IEEE Std 802.3 30.12.2.1.3"
 ::= { lldpV2Xdot3LocPortEntry 3 }

```

lldpV2Xdot3LocPortOperMauType OBJECT-TYPE

SYNTAX Unsigned32(0..2147483647)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"An integer value that indicates the operational MAU type of the given port on the local system.

This object contains the integer value derived from the list position of the corresponding dot3MauType as listed in Clause 13 and is equal to the last number in the respective dot3MauType OID.

For example, if the ifMauType object is dot3MauType1000BaseTHD which corresponds to {dot3MauType 29}, the numerical value of this field is 29. For MAU types not listed in Clause 13, the value of this field shall be set to zero."

REFERENCE

"IEEE Std 802.3 30.12.2.1.4"

::= { lldpV2Xdot3LocPortEntry 4 }

--- lldpV2Xdot3LocPowerTable: Power Ethernet Information Table

--- V2 modified to be indexed by ifIndex.

lldpV2Xdot3LocPowerTable OBJECT-TYPE

SYNTAX SEQUENCE OF LldpV2Xdot3LocPowerEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table contains one row per port of power Ethernet information (as a part of the LLDP IEEE 802.3 organizational extension) on the local system known to this agent."

::= { lldpV2Xdot3LocalData 2 }

lldpV2Xdot3LocPowerEntry OBJECT-TYPE

SYNTAX LldpV2Xdot3LocPowerEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Information about a particular port component."

INDEX { lldpV2LocPortIfIndex }

::= { lldpV2Xdot3LocPowerTable 1 }

LldpV2Xdot3LocPowerEntry ::= SEQUENCE {

lldpV2Xdot3LocPowerPortClass	LldpV2PowerPortClass,
lldpV2Xdot3LocPowerMDISupported	TruthValue,
lldpV2Xdot3LocPowerMDIEnabled	TruthValue,
lldpV2Xdot3LocPowerPairControlable	TruthValue,
lldpV2Xdot3LocPowerPairs	Unsigned32,
lldpV2Xdot3LocPowerClass	Unsigned32,
lldpV2Xdot3LocPowerType	INTEGER,
lldpV2Xdot3LocPowerSource	INTEGER,

```

        lldpV2Xdot3LocPowerPriority          INTEGER,
        lldpV2Xdot3LocPDRequestedPowerValue Integer32,
        lldpV2Xdot3LocPSEAllocatedPowerValue Integer32,
        lldpV2Xdot3LocResponseTime          Integer32,
        lldpV2Xdot3LocReady                  TruthValue,
        lldpV2Xdot3LocReducedOperationPowerValue Integer32
    }

```

lldpV2Xdot3LocPowerPortClass OBJECT-TYPE

SYNTAX LldpV2PowerPortClass

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value that identifies the port Class of the given port associated with the local system."

REFERENCE

"IEEE Std 802.3 30.12.2.1.5"

::= { lldpV2Xdot3LocPowerEntry 1 }

lldpV2Xdot3LocPowerMDISupported OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The truth value used to indicate whether the MDI power is supported on the given port associated with the local system."

REFERENCE

"IEEE Std 802.3 30.12.2.1.6"

::= { lldpV2Xdot3LocPowerEntry 2 }

lldpV2Xdot3LocPowerMDIEnabled OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The truth value used to identify whether MDI power is enabled on the given port associated with the local system."

REFERENCE

"IEEE Std 802.3 30.12.2.1.7"

::= { lldpV2Xdot3LocPowerEntry 3 }

lldpV2Xdot3LocPowerPairControlable OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The truth value is derived from the value of pethPsePortPowerPairsControlAbility object (defined in Clause 8) and is used to indicate whether the pair selection can be controlled on the given port associated with the local system."

REFERENCE

"IEEE Std 802.3 30.12.2.1.8"

::= { lldpV2Xdot3LocPowerEntry 4 }

lldpV2Xdot3LocPowerPairs OBJECT-TYPE

SYNTAX Unsigned32(1|2)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This object contains the value of the pethPsePortPowerPairs object (defined in Clause 8) which is associated with the given port on the local system."

REFERENCE

"IEEE Std 802.3 30.12.2.1.9"

::= { lldpV2Xdot3LocPowerEntry 5 }

lldpV2Xdot3LocPowerClass OBJECT-TYPE

SYNTAX Unsigned32(1|2|3|4|5)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This object contains the value of the pethPsePortPowerClassifications object (defined in Clause 8) which is associated with the given port on the local system."

REFERENCE

"IEEE Std 802.3 30.12.2.1.10"

::= { lldpV2Xdot3LocPowerEntry 6 }

lldpV2Xdot3LocPowerType OBJECT-TYPE

SYNTAX INTEGER {
 psetype1(0),
 psetype2(1),
 pdtype(2),
 pdtype2(3)
}

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A GET returns an integer indicating whether the local system is a PSE or a PD and whether it is Type 1 or Type 2."

REFERENCE

"IEEE Std 802.3 30.12.2.1.14"

::= { lldpV2Xdot3LocPowerEntry 7 }

lldpV2Xdot3LocPowerSource OBJECT-TYPE

SYNTAX INTEGER {
 pseprimary(0),
 psebackup(1),
 pseunknown(2),
 pdpseandlocal(3),
 pdpseonly(4),
 pdunknown(5)
}

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A GET returns an integer indicating the power sources of the local system. A PSE indicates whether it is being powered by a primary power source; a backup power source; or unknown. A PD indicates whether it is being powered by a PSE and locally; by a PSE only; or unknown."

REFERENCE

"IEEE Std 802.3 30.12.2.1.15"

::= { lldpV2Xdot3LocPowerEntry 8 }

```

lldpV2Xdot3LocPowerPriority OBJECT-TYPE
    SYNTAX      INTEGER {
                    low(0),
                    high(1),
                    critical(2),
                    unknown(3)
                }
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
        "A GET returns the priority of a PD system. For a PSE, this
        is the priority that the PSE assigns to the PD. For a PD, this
        is the priority that the PD requests from the PSE. A SET
        operation changes the priority of the PD system to the indicated
        value."
    REFERENCE
        "IEEE Std 802.3 30.12.2.1.16"
    ::= { lldpV2Xdot3LocPowerEntry 9 }

lldpV2Xdot3LocPDRequestedPowerValue OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "A GET returns the PD requested power value.
        For a PD, it is the power value that the PD has currently
        requested from the remote system. PD requested power value
        is the maximum input average power the PD ever draws under
        this power allocation if accepted. For a PSE, it is the power
        value that the PSE mirrors back to the remote system. This is
        the PD requested power value that was used by the PSE to compute
        the power it has currently allocated to the remote system.
        The PD requested power value is encoded according to
        IEEE Std 802.3 Equation (79-1), where X is the decimal value of
        aLldpXdot3LocPDRequestedPowerValue."
    REFERENCE
        "IEEE Std 802.3 30.12.2.1.17"
    ::= { lldpV2Xdot3LocPowerEntry 10 }

lldpV2Xdot3LocPSEAllocatedPowerValue OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "A GET returns the PSE allocated power value.
        For a PSE, it is the power value that the PSE has currently
        allocated to the remote system. The PSE allocated power value
        is the maximum input average power that the PSE wants the PD
        to ever draw under this allocation if it is accepted. For a PD,
        it is the power value that the PD mirrors back to the remote
        system. This is the PSE allocated power value that was used by
        the PD to compute the power that it has currently requested from
        the remote system. The PSE allocated power value is encoded
        according to IEEE Std 802.3 Equation (79-2), where X is the
        decimal value of aLldpXdot3LocPSEAllocatedPowerValue."
    REFERENCE
        "IEEE Std 802.3 30.12.2.1.18"
    ::= { lldpV2Xdot3LocPowerEntry 11 }

```

lldpV2Xdot3LocResponseTime OBJECT-TYPE

SYNTAX Integer32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A GET returns the response time in seconds of the local system. For a PD, it is the maximum time required to update the value of lldpV2Xdot3LocPDRequestedPowerValue when the remote system requests the PD to change its max power draw. For a PSE, it is the maximum time required to update the value of lldpV2Xdot3LocPDRequestedPowerValue when the remote system requests of the PSE a new power value."

REFERENCE

"IEEE Std 802.3 30.12.2.1.19"

::= { lldpV2Xdot3LocPowerEntry 12 }

lldpV2Xdot3LocReady OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The truth value used to identify whether the local Data Link Layer classification engine has completed initialization and is ready to receive and transmit LLDPDUs."

REFERENCE

"IEEE Std 802.3 30.12.2.1.20"

::= { lldpV2Xdot3LocPowerEntry 13 }

lldpV2Xdot3LocReducedOperationPowerValue OBJECT-TYPE

SYNTAX Integer32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A GET returns the reduced operation power value. For a PD, it is a power value that is lower than the currently requested power value. This reduced operation power value represents a power state in which the PD could continue to operate, but with less functionality than at the current PD requested power value. The PSE could optionally use this information in the event that the PSE subsequently requests a lower PD power value than the PD requested power value. For a PSE, it is a power value that the PSE could ask the PD to move to if the PSE wants the PD to move to a lower power state. The definition and encoding of PD requested power value is the same as described in lldpV2Xdot3LocPDRequestedPowerValue. The default value for this field is the hexadecimal value FFFF"

REFERENCE

"IEEE Std 802.3 30.12.2.1.21"

::= { lldpV2Xdot3LocPowerEntry 14 }

--- lldpV2Xdot3LocMaxFrameSizeTable: Maximum Frame Size information

--- V2 modified to be indexed by ifIndex.

lldpV2Xdot3LocMaxFrameSizeTable OBJECT-TYPE

SYNTAX SEQUENCE OF LldpV2Xdot3LocMaxFrameSizeEntry

MAX-ACCESS not-accessible

```

STATUS      current
DESCRIPTION
    "This table contains one row per port of maximum frame
    size information (as a part of the LLDP IEEE 802.3 organizational
    extension) on the local system known to this agent."
 ::= { lldpV2Xdot3LocalData 3 }

```

```

lldpV2Xdot3LocMaxFrameSizeEntry OBJECT-TYPE
SYNTAX      LldpV2Xdot3LocMaxFrameSizeEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "Maximum Frame Size information about a particular port
    component."
INDEX       { lldpV2LocPortIfIndex }
 ::= { lldpV2Xdot3LocMaxFrameSizeTable 1 }

```

```

LldpV2Xdot3LocMaxFrameSizeEntry ::= SEQUENCE {
    lldpV2Xdot3LocMaxFrameSize      Unsigned32
}

```

```

lldpV2Xdot3LocMaxFrameSize OBJECT-TYPE
SYNTAX      Unsigned32(0..65535)
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "An integer value indicating the maximum supported frame
    size in octets on the given port of the local system."
REFERENCE
    "IEEE Std 802.3 30.12.2.1.13"
 ::= { lldpV2Xdot3LocMaxFrameSizeEntry 1 }

```

```

---
```

```

---
```

```

--- lldpV2Xdot3LocEEETable: Energy Efficient Ethernet Information Table
--- V2 modified to be indexed by ifIndex.
---
```

```

---
```

```

---
```

```

lldpV2Xdot3LocEEETable OBJECT-TYPE
SYNTAX      SEQUENCE OF LldpV2Xdot3LocEEEEEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "This table contains one row per port of Energy Efficient Ethernet
    information (as a part of the LLDP IEEE 802.3 organizational
    extension) on the local system known to this agent."
 ::= { lldpV2Xdot3LocalData 4 }

```

```

lldpV2Xdot3LocEEEEEntry OBJECT-TYPE
SYNTAX      LldpV2Xdot3LocEEEEEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "Information about a particular port component."
INDEX       { lldpV2LocPortIfIndex }
 ::= { lldpV2Xdot3LocEEETable 1 }

```

```

LldpV2Xdot3LocEEEEEntry ::= SEQUENCE {

```

```

        lldpV2Xdot3LocTxTwSys          Integer32,
        lldpV2Xdot3LocTxTwSysEcho      Integer32,
        lldpV2Xdot3LocRxTwSys          Integer32,
        lldpV2Xdot3LocRxTwSysEcho      Integer32,
        lldpV2Xdot3LocFbTwSys          Integer32,
        lldpV2Xdot3TxDllReady          TruthValue,
        lldpV2Xdot3RxDllReady          TruthValue,
        lldpV2Xdot3LocDllEnabled       TruthValue
    }

lldpV2Xdot3LocTxTwSys      OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A GET returns the value of Tw_sys_tx that the local system
        can support in the transmit direction.
        This object maps to the variable LocTxSystemValue as defined
        in IEEE Std 802.3 78.4.2.3."
    REFERENCE
        "IEEE Std 802.3 30.12.2.1.22"
    ::= {lldpV2Xdot3LocEEEEEntry 1 }

lldpV2Xdot3LocTxTwSysEcho  OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A GET returns the value of Tw_sys_tx that the remote system is
        advertising that it can support in the transmit direction and is
        echoed by the local system under the control of the EEE DLL receiver
        state diagram. This object maps to the variable
        LocTxSystemValueEcho as defined in IEEE Std 802.3 78.4.2.3"
    REFERENCE
        "IEEE Std 802.3 30.12.2.1.23"
    ::= {lldpV2Xdot3LocEEEEEntry 2 }

lldpV2Xdot3LocRxTwSys      OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A GET returns the value of Tw_sys_tx that
        the local system is requesting in the receive direction.
        This object maps to the variable LocRxSystemValue as
        defined in IEEE Std 802.3 78.4.2.3."
    REFERENCE
        "IEEE Std 802.3 30.12.2.1.24"
    ::= {lldpV2Xdot3LocEEEEEntry 3 }

lldpV2Xdot3LocRxTwSysEcho  OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A GET returns the value of Tw_sys_tx that
        the remote system is advertising that it is requesting in the
        receive direction and is echoed by the local system under the
        control of the EEE DLL transmitter state diagram. This object

```

```

        maps to the variable LocRxSystemValueEcho as defined in
        IEEE Std 802.3 78.4.2.3."
REFERENCE
    "IEEE Std 802.3 30.12.2.1.25"
 ::= {lldpV2Xdot3LocEEEEEntry 4 }

lldpV2Xdot3LocFbTwSys      OBJECT-TYPE
SYNTAX      Integer32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "A GET returns the value of the fallback Tw_sys_tx
    that the local system is advertising to the remote system.
    This object maps to the variable LocFbSystemValue as defined
    in IEEE Std 802.3 78.4.2.3."
REFERENCE
    "IEEE Std 802.3 30.12.2.1.26"
 ::= {lldpV2Xdot3LocEEEEEntry 5 }

lldpV2Xdot3TxDllReady      OBJECT-TYPE
SYNTAX      TruthValue
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The truth value used to identify whether the local Data Link Layer
    EEE layer management function has completed initialization and
    is ready to receive and transmit LLDPDUs."
REFERENCE
    "IEEE Std 802.3 30.12.2.1.27"
 ::= {lldpV2Xdot3LocEEEEEntry 6 }

lldpV2Xdot3RxDllReady      OBJECT-TYPE
SYNTAX      TruthValue
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The truth value used to identify whether the local Data Link Layer
    EEE layer management function has completed initialization and
    is ready to receive and transmit LLDPDUs."
REFERENCE
    "IEEE Std 802.3 30.12.2.1.28"
 ::= {lldpV2Xdot3LocEEEEEntry 7 }

lldpV2Xdot3LocDllEnabled   OBJECT-TYPE
SYNTAX      TruthValue
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The truth value used to identify whether the local system has
    completed auto-negotiation with a link partner that has
    indicated at least one EEE capability."
REFERENCE
    "IEEE Std 802.3 30.12.2.1.29"
 ::= {lldpV2Xdot3LocEEEEEntry 8 }

```

 -- IEEE 802.3 - Remote Devices Information

```

-----

---
---
--- lldpV2Xdot3RemPortTable: Ethernet Information Table
--- V2 modified to be indexed by ifIndex and destination MAC address.
---
---

lldpV2Xdot3RemPortTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF LldpV2Xdot3RemPortEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table contains Ethernet port information (as a part
        of the LLDP IEEE 802.3 organizational extension) of the remote
        system."
    ::= { lldpV2Xdot3RemoteData 1 }

lldpV2Xdot3RemPortEntry OBJECT-TYPE
    SYNTAX      LldpV2Xdot3RemPortEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Information about a particular physical network connection."
    INDEX       { lldpV2RemTimeMark,
                  lldpV2RemLocalIfIndex,
                  lldpV2RemLocalDestMACAddress,
                  lldpV2RemIndex }
    ::= { lldpV2Xdot3RemPortTable 1 }

LldpV2Xdot3RemPortEntry ::= SEQUENCE {
    lldpV2Xdot3RemPortAutoNegSupported      TruthValue,
    lldpV2Xdot3RemPortAutoNegEnabled        TruthValue,
    lldpV2Xdot3RemPortAutoNegAdvertisedCap OCTET STRING,
    lldpV2Xdot3RemPortOperMauType           Unsigned32
}

lldpV2Xdot3RemPortAutoNegSupported OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The truth value used to indicate whether the given port
        (associated with remote system) supports Auto-negotiation."
    REFERENCE
        "IEEE Std 802.3 30.12.3.1.1"
    ::= { lldpV2Xdot3RemPortEntry 1 }

lldpV2Xdot3RemPortAutoNegEnabled OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The truth value used to indicate whether port
        Auto-negotiation is enabled on the given port associated
        with the remote system."
    REFERENCE

```

```

        "IEEE Std 802.3 30.12.3.1.2"
 ::= { lldpV2Xdot3RemPortEntry 2 }

lldpV2Xdot3RemPortAutoNegAdvertisedCap OBJECT-TYPE
    SYNTAX      OCTET STRING(SIZE(2))
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This object contains the value (bitmap) of the
         ifMauAutoNegCapAdvertisedBits object (defined in IETF RFC
         3636) which is associated with the given port on the
         remote system."
    REFERENCE
        "IEEE Std 802.3 30.12.3.1.3"
 ::= { lldpV2Xdot3RemPortEntry 3 }

lldpV2Xdot3RemPortOperMauType OBJECT-TYPE
    SYNTAX      Unsigned32(0..2147483647)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "An integer value that indicates the operational MAU type
         of the sending device.

        This object contains the integer value derived from the
        list position of the corresponding dot3MauType as listed in
        in Clause 13 and is equal to the last number in
        the respective dot3MauType OID.

        For example, if the ifMauType object is dot3MauType1000BaseTHD
        which corresponds to {dot3MauType 29}, the numerical value of
        this field is 29. For MAU types not listed in Clause 13,
        the value of this field shall be set to zero."
    REFERENCE
        "IEEE Std 802.3 30.12.3.1.4"
 ::= { lldpV2Xdot3RemPortEntry 4 }

---
---
--- lldpV2Xdot3RemPowerTable: Power Ethernet Information Table
--- V2 modified to be indexed by ifIndex and destination MAC address.
---
---

lldpV2Xdot3RemPowerTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF LldpV2Xdot3RemPowerEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table contains Ethernet power information (as a part
         of the LLDP IEEE 802.3 organizational extension) of the remote
         system."
 ::= { lldpV2Xdot3RemoteData 2 }

lldpV2Xdot3RemPowerEntry OBJECT-TYPE
    SYNTAX      LldpV2Xdot3RemPowerEntry
    MAX-ACCESS  not-accessible
    STATUS      current

```