

INTERNATIONAL
STANDARD

ISO/IEC/
IEEE
8802-3-2

First edition
2021-11

**Telecommunications and exchange
between information technology
systems — Requirements for local and
metropolitan area networks —**

**Part 3-2:
Standard for Ethernet YANG data
model definitions**

*Télécommunications et échange entre systèmes de technologies
de l'information — Exigences relatives aux réseaux locaux et
métropolitains —*

*Partie 3-2: Norme pour les définitions des modèles de données YANG
Ethernet*



Reference number
ISO/IEC/IEEE 8802-3-2:2021(E)
Documents
Document Sharing Hub
© IEEE 2019



COPYRIGHT PROTECTED DOCUMENT

© IEEE 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from IEEE at the address below.

Institute of Electrical and Electronics Engineers, Inc
3 Park Avenue, New York
NY 10016-5997, USA

Email: stds.ipr@ieee.org
Website: www.ieee.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO/IEC documents should be noted (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see patents.iec.ch).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

ISO/IEC/IEEE 8802-3-2 was prepared by the LAN/MAN of the IEEE Computer Society (as IEEE Std 802.3.2-2019) and drafted in accordance with its editorial rules. It was adopted, under the “fast-track procedure” defined in the Partner Standards Development Organization cooperation agreement between ISO and IEEE, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*.

A list of all parts in the ISO/IEC/IEEE 8802 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

Abstract: YANG models for IEEE Std 802.3 are defined in this standard. This standard also publishes these models in a machine-readable format.

Keywords: 802.3, 802.3.2, Ethernet, YANG

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2019 by the Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 21 June 2019. Printed in the United States of America.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by the Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-1-5044-5671-5 STD23620
Print: ISBN 978-1-5044-5672-2 STDPD23620

IEEE prohibits discrimination, harassment and bullying. For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading “Important Notice” or “Important Notices and Disclaimers Concerning IEEE Standards Documents.”

Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents (standards, recommended practices, and guides), both full-use and trial-use, are developed within IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (“IEEE-SA”) Standards Board. IEEE (“the Institute”) develops its standards through a consensus development process, approved by the American National Standards Institute (“ANSI”), which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims all warranties (express, implied and statutory) not included in this or any other document relating to the standard, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, IEEE disclaims any and all conditions relating to: results; and workmanlike effort. IEEE standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

Official statements

A statement, written or oral, that is not processed in accordance with the IEEE-SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, or be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in revisions to an IEEE standard is welcome to join the relevant IEEE working group.

Comments on standards should be submitted to the following address:

Secretary, IEEE-SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854 USA

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

IEEE draft and approved standards are copyrighted by IEEE under U.S. and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

Photocopies

Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to

photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE-SA Website at <http://ieeexplore.ieee.org/xpl/standards.jsp> or contact IEEE at the address listed previously. For more information about the IEEE SA or IEEE's standards development process, visit the IEEE-SA Website at <http://standards.ieee.org>.

Errata

Errata, if any, for all IEEE standards can be accessed on the IEEE-SA Website at the following URL: <http://standards.ieee.org/findstds/errata/index.html>. Users are encouraged to check this URL for errata periodically.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE-SA Website at <http://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

Participants

The following individuals were officers and members of the IEEE 802.3 working group at the beginning of the IEEE P802.3.2 (IEEE 802.3cf) working group ballot. Individuals may have not voted, voted for approval, disapproval or abstained on this standard.

David J. Law, *IEEE 802.3 Working Group Chair*

Adam Healey, *IEEE 802.3 Working Group Vice-Chair*

Pete Anslow, *IEEE 802.3 Working Group Secretary*

Steven B. Carlson, *IEEE 802.3 Working Group Executive Secretary*

Valerie Maguire, *IEEE 802.3 Working Group Treasurer*

Yan Zhuang, *IEEE P802.3.2 (IEEE 802.3cf) YANG Data Model Definitions
Task Force Chair*

Marek Hajduczenia, *IEEE P802.3.2 (IEEE 802.3cf) YANG Data Model Definitions
Task Force Editor-in-Chief*

David Abramson	Estes David	Kimber Mark
Dale Amason	John Ewen	Klaus Andrew
Ali Angha	Ramin Farjad	Michael Klempa
Eric Baden	Shahar Feldman	Curtis Knittle
Amrik Bains	Alan Flatman	Elizabeth Kochuparambil
Thananya Baldwin	Brian Franchuk	Paul Kolesar
Denis Beaudoin	Matthias Fritsche	Hans Lackner
Piergiorgio Beruto	Richard Frosch	Jeffrey Lapak
Mark Bohm	Mike Gardner	Mark Laubach
Brad Booth	Ali Ghiasi	Greg Le Cheminant
Martin Bouda	Joel Goergen	Han Hyub Lee
David Brandt	Steven Gorshe	Hanan Leizerovich
Ralf-Peter Braun	Jens Gotttron	David Lewis
Theodore Brillhart	Steffen Graber	Jon Lewis
Paul Brooks	Olaf Grau	Mike Peng Li
Matthew Brown	Robert M. Grow	Jane Lim
Phillip Brownlee	Yong Guo	Alex Lin
Chris Bullock	Mark Gustlin	Robert Lingle
Jairo Bustos Heredia	Tomohiro Hashimoto	Dekun Liu
Adrian Butter	Akinori Hayakawa	Hai-Feng Liu
Clark Carty	Rajmohan Hegde	Zhenyu Liu
Craig Chabot	David Hess	Miklos Lukacs
Mandeep Chadha	Yasuo Hidaka	Kent Lusted
David Chalupsky	David Høglund	Zahy Madgar
Frank Chang	Rita Horner	Jeffery Maki
Xin Chang	Bernd Hormmeyer	David Malicoat
Chan Chen	Xi Huang	Arthur Marris
Weiying Cheng	Yasuhiro Hyakutake	Takeo Masuda
Golam Choudhury	Jonathan Ingham	Kirsten Matheus
Keng Hua Chuang	Kazuhiko Ishibe	Erdem Matoglu
Keith Conroy	Hideki Isono	Mick McCarthy
John D'Ambrosia	Tom Issenhuth	Brett McClellan
Yair Darshan	Kenneth Jackson	Thomas Mcdermott
Piers Dawe	Andrew Jimenez	Larry McMillan
Fred Dawson	John Johnson	Greg McSorley
Eric DiBiaso	Chad Jones	Marcel Medina
Chris Diminico	Peter Jones	Richard Mei
Mike Dudek	Upen Kareti	Richard Mellitz
Frank Effenberger	Yasuaki Kawatsu	Phil Miguelez
Eitel Cornelia	Yong Kim	Harald Mueller
		Ron Muir

Henry Muyschondt	Laura Schweitz	Alexander Umnov
Edward Nakamoto	Masood Shariff	Sterling A. Vaden
Gary Nicholl	Ramin Shirani	Paul Vanderlaan
Kevin Noll	Mizuki Shirao	Dylan Walker
Ronald Nordin	Kapil Shrikhande	Edward Walter
Mark Nowell	Jeff Slavick	Haifei Wang
David Ofelt	Daniel Smith	Roy Wang
Tom Palkert	Scott Sommers	Tongtong Wang
Sujan Pandey	Bryan Sparrowhawk	Xinyuan Wang
Earl Parsons	Edward Sprague	Christoph Wechsler
Harsh Patel	Atul Srivastava	Brian Welch
Arkadiy Peker	Peter Stassar	Matthias Wendt
Wanquan Peng	Heath Stewart	Oded Wertheim
Gerald Pepper	David Stover	Natalie Wienckowski
Michael Peters	Junqing Sun	Ludwig Winkel
Phong Pham	Steve Swanson	Peter Wu
Jean Picard	Andre Szczepanek	Markus Wucher
David Piehler	Bharat Tailor	Dayin Xu
Rick Pimpinella	Tomoo Takahara	Yu Xu
William Powell	Kohichi Tamura	Adrian Young
Rick Rabinovich	Ronald Tellas	Lennart Yseboodt
Adee Ran	Geoffrey O. Thompson	Andrew Zambell
Alon Regev	Pirooz Tooyserkani	Conrad Zerna
Duane Remein	Nathan Tracy	Huanlin Zhang
Michael Ressler	Matthew Traverso	Qiwen Zhong
Salvatore Rotolo	David Tremblay	Martin Zielinski
Sam Sambasivan	Stephen Trowbridge	George Zimmerman
Edward Sayre	Ed Ulrichs	Helge Zinner
Fred Schindler	Daisuke Umeda	Pavel Zivny

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Andrea Agnes	Atsushi Ito	Maximilian Riegel
Richard Alfvén	Raj Jain	Robert Robinson
Niranth Amogh	SangKwon Jeong	Benjamin Rolfe
Peter Anslow	Stuart Kerry	Daniel Smith
Butch Anton	Yongbum Kim	Thomas Starai
Ralf-Peter Braun	Patrick Kinney	Peter Stassar
Nancy Bravin	Mark Laubach	Walter Struppler
Theodore Brillhart	David J. Law	Ganesh Subramanian
Matthew Brown	Hyeong Ho Lee	Mitsutoshi Sugawara
Demetrio Bucaneg	Jon Lewis	Kohichi Tamura
Jairo Bustos Heredia	Elvis Maculuba	David Tremblay
William Byrd	Valerie Maguire	Stephen Trowbridge
Steven Carlson	Jeffery Maki	Mark-Rene Uchida
Keith Chow	Vinayagam Mariappan	Alexander Umnov
Rodney Cummings	Roger Marks	Dmitri Varsanofiev
Andrew Fieldsend	Arthur Marris	George Vlantis
Avraham Freedman	Michael Maytum	Khurram Waheed
Matthias Fritsche	Brett McClellan	Karl Weber
Yukihiro Fujimoto	Thomas McDermott	Hung-Yu Wei
Eric W. Gray	Richard Mellitz	Scott Willy
Randall Groves	Nick S.A. Nikjoo	Adrian Young
Robert M. Grow	Satoshi Obara	James Young
Marek Hajduczenia	Bansi Patel	Oren Yuen
Adam Healey	Rick Pimpinella	Zhen Zhou
Marco Hernandez	William Powell	Yan Zhuang
Werner Hoelzl	R. K. Rannow	Pavel Zivny
Noriyuki Ikeuchi	Alon Regev	
Sergiu Iordanescu	Duane Remein	

When the IEEE-SA Standards Board approved this standard on 21 March 2019, it had the following membership:

Gary Hoffman, *Chair*
Ted Burse, *Vice Chair*
Jean-Philippe Faure, *Past Chair*
Konstantinos Karachalios, *Secretary*

Masayuki Ariyoshi
Stephen D. Dukes
J. Travis Griffith
Guido Hiertz
Christel Hunter
Thomas Koshy
Joseph L. Koepfinger*
Thomas Koshy

John D. Kulick
David J. Law
Joseph Levy
Howard Li
Xiaohui Liu
Kevin Lu
Daleep Mohla
Andrew Myles
Annette D. Reilly

Dorothy Stanley
Sha Wei
Phil Wennblom
Philip Winston
Howard Wolfman
Feng Wu
Jingyi Zhou

*Member Emeritus

Introduction

This introduction is not part of IEEE Std 802.3.2-2019, IEEE Standard for Ethernet YANG Data Model Definitions.

The YANG modules included in this standard provide YANG versions of attributes defined in IEEE Std 802.3TM-2018, Clause 30, as well as derivative attributes defined in other management information bases (e.g., SNMP attributes included in IEEE Std 802.3.1, YANG versions of IETF Etherlike MIB attributes, etc.). The YANG modules defined in this standard accommodate IEEE Std 802.3-2018, excluding any currently published or future amendments. As IEEE Std 802.3 continues to evolve, new revisions of this standard may be published in the future to address new technologies and features.

Contents

1. Overview.....	12
1.1 Scope.....	12
1.2 Purpose.....	12
1.3 Machine-readable YANG modules	12
1.4 Summary of YANG-based management framework.....	12
1.5 Security considerations	13
1.6 YANG module syntax validation	13
2. Normative references	14
3. Definitions	16
4. Abbreviations	17
5. Ethernet YANG Module	18
5.1 YANG module structure	18
5.2 Mapping of IEEE Std 802.3, Clause 30 managed objects	18
5.3 YANG module definition	23
5.3.1 Tree hierarchy	23
5.3.2 YANG module.....	26
5.3.2.1 Ethernet interface module.....	26
5.3.2.2 Ethernet interface module (half-duplex).....	43
6. YANG module for Ethernet data terminal equipment (DTE) power via medium dependent interface (MDI) and Power over Data Lines (PoDL)	50
6.1 Introduction.....	50
6.2 YANG module structure	50
6.3 Security considerations for Ethernet data terminal equipment (DTE) power via medium dependent interface (MDI) and Power over Data Line Module	50
6.4 Mapping of IEEE Std 802.3, Clause 30 managed objects	50
6.5 YANG module definition	53
6.5.1 Tree hierarchy	53
6.5.2 YANG module.....	54
7. YANG module for Ethernet Passive Optical Network (EPON).....	65
7.1 Introduction.....	65
7.2 YANG module structure	65
7.2.1 Introduction.....	65
7.2.2 Principles of operation	66
7.2.3 Physical media	67
7.2.4 PMD specifications.....	67
7.2.5 Principles of the MPCP.....	67
7.2.6 Forward error correction (FEC).....	69
7.2.7 Management architecture.....	70
7.3 Mapping of IEEE Std 802.3, Clause 30 managed objects	71
7.4 YANG module definition	77
7.4.1 Tree hierarchy	77

7.4.2	YANG module.....	80
8.	YANG module for Ethernet Link OAM (ELO)	123
8.1	Introduction.....	123
8.2	Overview.....	123
8.2.1	Remote fault indication.....	123
8.2.2	Link monitoring	123
8.2.3	Remote loopback	123
8.2.4	Ethernet OAM protocol data units.....	124
8.3	Security considerations for Ethernet operations, administration, and maintenance (OAM) module	124
8.4	Mapping of IEEE 802.3 managed objects	125
8.5	YANG module definition	129
8.5.1	Tree hierarchy	129
8.5.2	YANG module.....	133

IEEE Standard for Ethernet YANG Data Model Definitions

1. Overview

This standard defines YANG modules for various Ethernet devices specified in IEEE Std 802.3. This includes half-duplex and full-duplex data terminal equipment (DTE) using either Carrier Sense Multiple Access/Collision Detection (CSMA/CD) or Multipoint Control Protocol (MPCP), and Power Sourcing Equipment (PSE).

1.1 Scope

This standard defines YANG data models for IEEE Std 802.3 Ethernet.

1.2 Purpose

The purpose of the standard is to define YANG modules for IEEE Std 802.3 and publish these modules in a machine-readable format.

1.3 Machine-readable YANG modules

The machine-readable files are available for download at the following URL: <https://github.com/YangModels/yang/tree/master/standard/ieee/published/802.3> as text files with a *.yang* extension, e.g., *ieee802-ether-net-interface.yang*. The use of specialized tools to view YANG modules may be useful to create tree, UML image, and HTML outputs from the YANG modules.

Like other languages, YANG (see IETF RFC 7950) has an accepted style for machine-readable files, which was followed during the development of this standard. This formatting may not be preserved when importing the machine-readable YANG modules into the PDF. In case of any formatting discrepancies, the published machine-readable files should be consulted.

1.4 Summary of YANG-based management framework

The structure of YANG-based management framework closely resembles the structure of the Internet-Standard Management Framework, described in detail in section 7 of IETF RFC 3410.

Managed objects defined using YANG modeling language are hosted on the managed device and accessed through NETCONF (see IETF RFC 7803) or RESTCONF (see IETF RFC 8040). This standard specifies YANG modules that are compliant to YANG 1.1 (see IETF RFC 7950).

1.5 Security considerations

The YANG modules defined in this standard are designed to be accessed via network management protocols, including NETCONF (see IETF RFC 7803) or RESTCONF (see IETF RFC 8040). The lowest NETCONF layer is the secure transport layer, and the mandatory-to-implement secure transport is Secure Shell (SSH) (see IETF RFC 6242) or TLS (see IETF RFC 8446). The lowest RESTCONF layer is HTTPS, and the mandatory-to-implement secure transport is TLS (see IETF RFC 8446).

The NETCONF access control model (see IETF RFC 8341) provides the means to restrict access for particular NETCONF or RESTCONF users to a pre-configured subset of all available NETCONF or RESTCONF protocol operations and content.

There are a number of data nodes defined in these YANG modules that are writable/creatable/deletable, i.e., have the config property set to true, which is the default setting. These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations.

Some of the readable data nodes in these YANG modules may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes.

Some of the RPC operations in these YANG modules may be considered sensitive or vulnerable in some network environments. Therefore, it is important to control access to these operations.

1.6 YANG module syntax validation

All YANG modules included in this standard are YANG 1.1 (see IETF RFC 7950) compliant and pass automated checks using tools available at the time of publication.

The following open source and/or free versions of YANG validation tools may be used: Pyang (see <https://github.com/mbj4668/pyang>), ConfD (see <http://www.tail-f.com/confd-basic>), as well as other YANG model validation tools listed at <http://www.yangvalidator.com>.

2. Normative references

The following referenced documents are indispensable for the application of this document (i.e., they must be understood and used, so each referenced document is cited in text and its relationship to this document is explained). For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments or corrigenda) applies.

IEEE Std 802®-2014, IEEE Standard for Local and Metropolitan Area Networks: Overview and Architecture.^{1, 2}

IEEE Std 802d™-2017, IEEE Standard for Local and Metropolitan Area Networks: Overview and Architecture Amendment 1: Allocation of Uniform Resource Name (URN) Values in IEEE 802 Standards.

IEEE Std 802.1Q™-2014, IEEE Standard for Local and metropolitan area networks—Bridges and Bridged Networks.

IEEE Std 802.3™-2018, IEEE Standard for Ethernet.

IEEE Std 802.3.1™-2013, IEEE Standard for Management Information Base (MIB) Definitions for Ethernet.

IETF RFC 2819, Remote Network Monitoring Management Information Base, S. Waldbusser, May 2000.³

IETF RFC 3410, *Introduction and Applicability Statements for Internet Standard Management Framework*, J. Case, R. Mundy, D. Partain, B. Stewart, December 2002.

IETF RFC 3621, *Power Ethernet MIB*, A. Berger, December 2003

IETF RFC 3635, *Definitions of Managed Objects for the Ethernet-like Interface Types*, J. Flick, September 2003.

IETF RFC 6242, *Using the NETCONF Protocol over Secure Shell (SSH)*, Wasserman M., June 2011.

IETF RFC 6991, *Common YANG Data Types*, Schoenwaelder J., July 2013.

IETF RFC 7803, *Changing the Registration Policy for the NETCONF Capability URNs Registry*, B. Leiba February 2016.

IETF RFC 7950, *The YANG 1.1 Data Modeling Language*, Bjorklund M., August 2016.

IETF RFC 8040, *RESTCONF Protocol*, Bierman A., Bjorklund M., and Watsen K., January 2017.

IETF RFC 8342, *Network Management Datastore Architecture (NMDA)*, M. Bjorklund, J. Schoenwaelder, P. Shafer, K. Watsen, and R. Wilton, March 2018.

IETF RFC 8341, *Network Configuration Access Control Model*, A. Bierman and M. Bjorklund, March 2018.

¹The IEEE standards or products referred to in this clause are trademarks owned by the Institute of Electrical and Electronics Engineers, Incorporated.

²IEEE publications are available from the Institute of Electrical and Electronics Engineers (<http://standards.ieee.org/>).

³Internet Requests for Comments (RFCs) are available on the World Wide Web at the following ftp site: venera.isi.edu; login: anonymous; password: user's e-mail address; directory: in-inotes.

IEEE Std 802.3.2-2019
IEEE Standard for Ethernet YANG Data Model Definitions

IETF RFC 8343, *A YANG Data Model for Interface Management*, Bjorklund, M., March 2018.

IETF RFC 8407, *Guidelines for Authors and Reviewers of YANG Data Model Documents*, Bierman A., October 2018.

IETF RFC 8446, *The Transport Layer Security (TLS) Protocol Version 1.3*, E. Rescorla, August 2018.

3. Definitions

For the purposes of this document, the following terms and definitions apply. Some terms used in this document are defined in IEEE Std 802.3, and where alternative definitions occur in the IEEE Standards Dictionary, the IEEE Std 802.3 definition should be used. The *IEEE Standards Dictionary Online* should be consulted for terms not defined in this clause.⁴

3.1 data model: A data model describes how data is represented and accessed.

3.2 YANG module: A YANG module defines a hierarchy of nodes that can be used for NETCONF-based (see IETF RFC 7803) and RESTCONF-based (see IETF RFC 8040) operations. With its definitions and the definitions it imports or includes from elsewhere, a module is self-contained and can be compiled.

⁴*IEEE Standards Dictionary Online* is available at: <http://dictionary.ieee.org/>.

4. Abbreviations

This standard contains the following abbreviations:

CO	Central Office
CPE	Customer Premise Equipment
CSMA/CD	carrier sense multiple access with collision detection
DTE	data terminal equipment
EFM	Ethernet in the First Mile
ELO	Ethernet Link OAM
EPON	Ethernet passive optical networks
IEEE	Institute of Electrical and Electronics Engineers
IETF	Internet Engineering Task Force
NETCONF	Network Configuration Protocol
OAM	Operations, Administration, and Maintenance
PoE	Power over Ethernet
RESTCONF	RESTful Configuration Protocol
YANG	Yet Another Next Generation

5. Ethernet YANG Module

5.1 YANG module structure

Two modules defined in this clause are focused on the configuration and monitoring of IEEE Std 802.3 Ethernet interfaces. The *ieee802-ethernet-interface* YANG module contains definitions of current attributes used widely in the industry in current products, while the *ieee802-ethernet-interface-half-duplex* YANG module contains definitions of half-duplex attributes.

This standard does not have a normative requirement for data nodes of the base ietf-interfaces YANG module, but the following data nodes are supported: name, description, type, enabled, admin-status, oper-status, if-index, and phys-address.

5.2 Mapping of IEEE Std 802.3, Clause 30 managed objects

This subclause contains the mapping between YANG data nodes included in *ieee802-ethernet-interface* (see Table 5–1) and *ieee802-ethernet-interface-half-duplex* (see Table 5–4) YANG modules, managed objects, and attributes defined in IEEE Std 802.3, Clause 30.

Table 5–1—Mapping between IEEE Std 802.3, Clause 30 managed objects and *ieee802-ethernet-interface* YANG data nodes

IEEE Std 802.3, Clause 30		Corresponding <i>ieee802-ethernet-interface</i> YANG data nodes		
Managed object(s)	Attribute(s)	Reference	Container(s)	Data node(s) R/W
oAutoNegotiation	acAutoNegAdminControl	30.6.1.2.2	interfaces/interface/ethernet/	auto-negotiation/enable R/W
	aAutoNegAutoConfig	30.6.1.1.4		negotiation-status R
	N/A			flow-control/pause/direction R/W
oMACControl-FunctionEntity	aPAUSEMACCtrlFramesReceived	30.3.4.3		flow-control/pause/statistics/in-frames-pause R
	aPAUSEMACCtrlFramesTransmitted	30.3.4.2		flow-control/pause/statistics/out-frames-pause R
N/A	dot3HCOutPFCFrames			
N/A	N/A			flow-control/force-flow-control R/W
N/A	N/A			speed R/W
oMACEntity	aDuplexStatus	30.3.1.1.32		duplex R/W
	aMaxFrameLength	30.3.1.1.37		max-frame-length R
	aSlowProtocolFrameLimit	30.3.1.1.38		frame-limit-slow-protocol R
oEXTENSION	aEXTENSIONMACCtrlStatus	30.3.8.3		mac-control-extension-control R
	N/A			capabilities/auto-negotiation R

Table 5–1—Mapping between IEEE Std 802.3, Clause 30 managed objects and *ieee802-ethernet-interface* YANG data nodes (continued)

IEEE Std 802.3, Clause 30		Corresponding <i>ieee802-ethernet-interface</i> YANG data nodes		
Managed object(s)	Attribute(s)	Reference	Container(s)	Data node(s)
oMACEntity	aFramesReceivedOK	30.3.1.1.5	interfaces/interface/ethernet/statistics/frame	in-frames
	aMulticastFramesReceivedOK	30.3.1.1.21		in-multicast-frames
	aBroadcastFramesReceivedOK	30.3.1.1.22		in-broadcast-frames
	aFrameCheckSequenceErrors + aAlignmentErrors	30.4.3.1.6, 30.4.3.1.7		in-error-fcs-frames
	aFrameTooLongErrors	30.3.1.1.25		in-error-oversize-frames
oMACEntity	aFramesLostDueToIntMACRcvError	30.3.1.1.15		in-error-mac-internal-frames
	aFramesTransmittedOK	30.3.1.1.2		out-frames
	aMulticastFramesXmittedOK	30.3.1.1.18		out-multicast-frames
	aBroadcastFramesXmittedOK	30.3.1.1.19		out-broadcast-frames
	aFramesLostDueToIntMACXmitError	30.3.1.1.12		out-error-mac-internal-frames
oPHYEntity	aSymbolErrorDuringCarrier	30.3.2.1.5	interfaces/interface/ethernet/statistics/phy	in-error-symbol
	aReceiveLPITransitions	30.3.2.1.11	interfaces/interface/ethernet/statistics/phy/lpi	in-lpi-transitions
	aReceiveLPIMicroseconds	30.3.2.1.9		in-lpi-time
	aTransmitLPITransitions	30.3.2.1.10		out-lpi-transitions
	aTransmitLPIMicroseconds	30.3.2.1.8		out-lpi-time

Table 5-1—Mapping between IEEE Std 802.3, Clause 30 managed objects and *ieee802-ethernet-interface* YANG data nodes (continued)

IEEE Std 802.3, Clause 30		Corresponding <i>ieee802-ethernet-interface</i> YANG data nodes		
Managed object(s)	Attribute(s)	Reference	Container(s)	Data node(s) R/W
oMACControlEntity oEXTENSION	aUnsupportedOpCodesReceived	30.3.3.5	interfaces/interface/ethernet/statistics/mac-control	in-frames-mac-control-unknown R
	aEXTENSIONMACCtrlFramesReceived	30.3.8.2		in-frames-mac-control-extension R
	aEXTENSIONMACCtrlFramesTransmitted	30.3.8.1		out-frames-mac-control-extension R

Table 5-2—Mapping between IETF RFC 2819 managed objects and *ieee802-ethernet-interface* YANG data nodes

IETF RFC 2819 Attribute(s)		Corresponding <i>ieee802-ethernet-interface</i> YANG data nodes		
		Container(s)	Data node(s)	R/W
no direct object ^a etherStatsOctets etherStatsUndersizePkts + etherStatsFragments		interfaces/interface/ethernet/statistics/frame	in-total-frames	R
			in-total-octets	R
			in-error-undersize-frames	R

^a Can be calculated as: aFramesReceivedOK + aFrameCheckSequenceErrors + aAlignmentErrors + aFrameTooLongErrors + aFramesLostDuplicateToIntMACRevError.

Table 5-3—Mapping between IETF RFC 3635 managed objects and *ieee802-ethernet-interface* YANG data nodes

ETHERLIKE MIB Attribute(s)	Corresponding <i>ieee802-ethernet-interface</i> YANG data nodes		
	Container(s)	Data node(s)	R/W
dot3HCInPFCFrames	interfaces/interface/ethernet/	flow-control/pfc {ethernet-pfc} / statistics/in-frames-pfc	R
dot3HCOuPFCFrames		flow-control/pfc {ethernet-pfc} / statistics/out-frames-pfc	R

Table 5-4—Mapping between IEEE Std 802.3, Clause 30 managed objects and *ieee802-ethernet-interface-half-duplex* YANG data nodes

IEEE Std 802.3, Clause 30		Corresponding <i>ieee802-ethernet-interface-half-duplex</i> YANG data nodes		
Managed object(s)	Attribute(s)	Reference	Container(s)	Data node(s) R/W
oMACEntity	aRateControlAbility	30.3.1.1.33	interfaces/interface/ethernet	dynamic-rate-control R/W
	aSQETestErrors	30.3.2.1.4	interfaces/interface/ethernet/statistics/frame/ csmacd {csma-cd}	dynamic-rate-control-supported R
	aSingleCollisionFrames	30.3.1.1.3		in-errors-sqe-test R
	aMultipleCollisionFrames	30.3.1.1.4		out-frames-collision-single R
	aFramesWithDeferredXmissions	30.3.1.1.9		out-frames-collision-multiple R
	aFramesAbortedDueToXSColls	30.3.1.1.11		out-frames-deferred R
	aLateCollisions	30.3.1.1.10		out-frames-collisions-excessive R
	aCarrierSenseErrors	30.3.1.1.13		out-collisions-late R
	aCollisionFrames	30.3.1.1.30		out-errors-carrier-sense R
				collision-histogram/collision-count R
				collision-histogram/collision-count-frames R

5.3 YANG module definition⁵

The YANG module tree hierarchy uses terms defined in IETF RFC 8407.

5.3.1 Tree hierarchy

```

module: ieee802-ethernet-interface
  augment /if:interfaces/if:interface:
    +--rw ethernet
      +--rw auto-negotiation!
        | +--rw enable?          boolean
        | +--ro negotiation-status? enumeration
        +--rw duplex?          duplex-type
        +--rw speed?           eth-if-speed-type
      +--rw flow-control
        | +--rw pause {ethernet-pause}?
        | | +--rw direction?  pause-fc-direction-type
        | | +--ro statistics
        | | | +--ro in-frames-pause?  yang:counter64
        | | | +--ro out-frames-pause? yang:counter64
        | +--rw pfc {ethernet-pfc}?
        | | +--rw enable?    boolean
        | | +--ro statistics
        | | | +--ro in-frames-pfc?  yang:counter64
        | | | +--ro out-frames-pfc? yang:counter64
        | +--rw force-flow-control? boolean
        +--ro max-frame-length?    uint16
        +--ro mac-control-extension-control? boolean
        +--ro frame-limit-slow-protocol?  uint64
        +--ro capabilities
          | +--ro auto-negotiation?  boolean
          +--ro statistics
            +--ro frame
              | +--ro in-total-frames?          yang:counter64

```

⁵ Copyright release for YANG modules: Users of this standard may freely reproduce the YANG module contained in this subclause so that it can be used for its intended purpose.

```

| +--ro in-total-octets?          yang:counter64
| +--ro in-frames?               yang:counter64
| +--ro in-multicast-frames?     yang:counter64
| +--ro in-broadcast-frames?     yang:counter64
| +--ro in-error-fcs-frames?     yang:counter64
| +--ro in-error-undersize-frames? yang:counter64
| +--ro in-error-oversize-frames? yang:counter64
| +--ro in-error-mac-internal-frames? yang:counter64
| +--ro out-frames?              yang:counter64
| +--ro out-multicast-frames?    yang:counter64
| +--ro out-broadcast-frames?    yang:counter64
| +--ro out-error-mac-internal-frames? yang:counter64
+--ro phy
| +--ro in-error-symbol?        yang:counter64
| +--ro lpi
| | +--ro in-lpi-transitions?    yang:counter64
| | +--ro in-lpi-time?          decimal64
| | +--ro out-lpi-transitions?   yang:counter64
| | +--ro out-lpi-time?         decimal64
+--ro mac-control
| +--ro in-frames-mac-control-unknown? yang:counter64
| +--ro in-frames-mac-control-extension? yang:counter64
| +--ro out-frames-mac-control-extension? yang:counter64

module: ieee802-ethernet-interface-half-duplex
augment /if:interfaces/if:interface/ieee802-eth-if:ethernet:
+--rw dynamic-rate-control? dynamic-rate-control-type {dynamic-rate-control}?
augment /if:interfaces/if:interface/ieee802-eth-if:ethernet/ieee802-eth-if:capabilities:
+--ro dynamic-rate-control-supported? boolean {dynamic-rate-control}?
augment /if:interfaces/if:interface/ieee802-eth-if:ethernet/ieee802-eth-if:statistics/ieee802-eth-
if:frame:
+--ro csma-cd {csma-cd}?
| +--ro in-errors-sqe-test?          yang:counter64
| +--ro out-frames-collision-single? yang:counter64
| +--ro out-frames-collision-multiple? yang:counter64
| +--ro out-frames-deferred?        yang:counter64

```

```

+--ro out-frames-collisions-excessive?  yang:counter64
+--ro out-collisions-late?              yang:counter64
+--ro out-errors-carrier-sense?         yang:counter64
+--ro collision-histogram* [collision-count]
    +--ro collision-count                yang:counter64
    +--ro collision-count-frames?       yang:counter64

```

5.3.2 YANG module

In the following YANG module definitions, should any discrepancy between the text of the description for individual YANG nodes and the corresponding definition in 5.2 through 5.3 of this clause occur, the definitions and mappings in 5.3 shall take precedence.

An ASCII text version of the Ethernet YANG module can be found at the following URL:⁶
<https://github.com/YangModels/yang/tree/master/standard/ieee/published/802.3>.

5.3.2.1 Ethernet interface module

```

module ieee802-ethernet-interface {
  yang-version 1.1;

  namespace
    "urn:ieee:std:802.3:yang:ieee802-ethernet-interface";

  prefix ieee802-eth-if;

  revision 2019-06-21 {
    description "Initial revision.";
  }

  import ietf-yang-types {
    prefix yang;
    reference "IETF RFC 6991";
  }

  import ietf-interfaces {
    prefix if;
    reference "IETF RFC 8343";
  }

  import iana-if-type {
    prefix ianaift;
    reference "http://www.iana.org/assignments/yang-parameters/iana-if-type@2018-07-03.yang";
  }

  organization
    "IEEE Std 802.3 Ethernet Working Group
    Web URL: http://www.ieee802.org/3/";

  contact
    "Web URL: http://www.ieee802.org/3/";

  description
    "This module contains YANG definitions for configuring IEEE Std
    802.3 Ethernet Interfaces.
    In this YANG module, 'Ethernet interface' can be interpreted
    as referring to 'IEEE Std 802.3 compliant Ethernet

```

⁶Copyright release for YANG modules: Users of this standard may freely reproduce the YANG module contained in this subclause so that it can be used for its intended purpose.

```

    interfaces'.";

reference "IEEE Std 802.3-2018, unless dated explicitly";

typedef eth-if-speed-type {
    type decimal64 {
        fraction-digits 3;
    }
    units "Gb/s";
    description
        "Used to represent the configured, negotiated, or actual speed
        of an Ethernet interface in Gigabits per second (Gb/s),
        accurate to 3 decimal places (i.e., accurate to 1 Mb/s).";
}

typedef duplex-type {
    type enumeration {
        enum full {
            description
                "Full duplex.";
        }
        enum half {
            description
                "Half duplex.";
        }
        enum unknown {
            description
                "Link is currently disconnected or initializing.";
        }
    }
    default full;
    description
        "Used to represent the configured, negotiated, or actual
        duplex mode of an Ethernet interface.";
    reference "IEEE Std 802.3, 30.3.1.1.32, aDuplexStatus";
}

typedef pause-fc-direction-type {
    type enumeration {
        enum "disabled" {
            description
                "Flow-control disabled in both ingress and egress
                directions, i.e., PAUSE frames are not transmitted and
                PAUSE frames received in the ingress direction are
                discarded without processing.";
        }
        enum "ingress-only" {
            description
                "PAUSE frame based flow control is enabled in the ingress
                direction only, i.e., PAUSE frames may be transmitted to
                reduce the ingress traffic flow, but PAUSE frames received
                in the ingress direction are discarded without reducing
                the egress traffic rate.";
        }
    }
}

```

```

enum "egress-only" {
  description
    "PAUSE frame based flow control is enabled in the egress
    direction only, i.e., PAUSE frames are not transmitted,
    but PAUSE frames received in the ingress direction are
    processed to reduce the egress traffic rate.";
}
enum "bi-directional" {
  description
    "PAUSE frame based flow control is enabled in both ingress
    and egress directions, i.e., PAUSE frames may be
    transmitted to reduce the ingress traffic flow, and
    PAUSE frames received on ingress are processed to reduce
    the egress traffic rate.";
}
enum "undefined" {
  description
    "Link is currently disconnected or initializing.";
}
}
description
  "Used to represent the configured, negotiated, or actual
  PAUSE frame-based flow control setting.";

reference
  "IEEE Std 802.3.1, dot3PauseAdminMode and dot3PauseOperMode";
}

feature ethernet-pfc {
  description
    "This device supports Ethernet priority flow-control.";
}

feature ethernet-pause {
  description
    "This device supports Ethernet PAUSE.";
}

augment "/if:interfaces/if:interface" {
  when "derived-from-or-self(if:type, 'ianaift:ethernetCsmacd')" {
    description
      "Applies to all P2P Ethernet interfaces.";
  }
  description
    "Augment interface model with Ethernet interface
    specific configuration nodes.";

  container ethernet {
    description
      "Contains all Ethernet interface related configuration.";

    container auto-negotiation {
      presence
        "The presence of this container indicates that

```

IEEE Std 802.3.2-2019
IEEE Standard for Ethernet YANG Data Model Definitions

```

    auto-negotiation is supported on this Ethernet
    interface.";
description
    "Contains auto-negotiation transmission parameters

    This container contains a data node that allows the
    advertised duplex value in the negotiation to be
    restricted.

    If not specified then the default behavior for the duplex
    data node is to negotiate all available values for the
    particular type of Ethernet PHY associated with the
    interface.

    If auto-negotiation is enabled, and PAUSE frame based flow
    control has not been explicitly configured, then the
    default PAUSE frame based flow control capabilities that
    are negotiated allow for bi-directional or egress-only
    PAUSE frame based flow control.

    If auto-negotiation is enabled, and PAUSE frame based flow
    control has been explicitly configured, then the
    configuration settings restrict the values that may be
    negotiated. However, it should be noted that the protocol
    does not allow only egress PAUSE frame based flow control
    to be negotiated without also allowing bi-directional
    PAUSE frame based flow control.";
reference
    "IEEE Std 802.3, Clause 28 and Annexes 28A-D";

leaf enable {
    type boolean;
    default true;

    description
        "Controls whether auto-negotiation is enabled or
        disabled.
        For interface types that support auto-negotiation then
        it defaults to being enabled.

        For interface types that do not support auto-negotiation,
        the related configuration data is ignored.";
}
leaf negotiation-status {
    when "../enable = 'true'";
    type enumeration {
        enum in-progress {
            description
                "The auto-negotiation protocol is running and
                negotiation is currently in-progress.";
        }
        enum complete {
            description
                "The auto-negotiation protocol has completed

```

```

        successfully.";
    }
    enum failed {
        description
            "The auto-negotiation protocol has failed.";
    }
    enum unknown {
        description
            "The auto-negotiation status is not currently known,
            this could be because it is still negotiating or the
            protocol cannot run (e.g., if no medium is present).";
    }
    enum no-negotiation {
        description
            "No auto-negotiation is executed.
            The auto-negotiation function is either not supported
            on this interface or has not been enabled.";
    }
    }
    config false;
    description
        "The status of the auto-negotiation protocol.";
    reference
        "IEEE 802.3, 30.6.1.1.4, aAutoNegAutoConfig";
    }
}

leaf duplex {
    type duplex-type;
    description
        "Operational duplex mode of the Ethernet interface.";
    reference
        "IEEE Std 802.3, 30.3.1.1.32 aDuplexStatus";
}

leaf speed {
    type eth-if-speed-type;
    units "Gb/s";
    description
        "Operational speed (data rate) of the Ethernet interface.
        The default value is implementation-dependent.";
}

container flow-control {
    description
        "Holds the different types of Ethernet PAUSE frame based
        flow control that can be enabled.";
    container pause {
        if-feature "ethernet-pause";
        description
            "IEEE Std 802.3 PAUSE frame based PAUSE frame based flow
            control.";
        reference

```

IEEE Std 802.3.2-2019
IEEE Standard for Ethernet YANG Data Model Definitions

```

    "IEEE Std 802.3, Annex 31B";
leaf direction {
    type pause-fc-direction-type;
    description
        "Indicates which direction PAUSE frame based flow
        control is enabled in, or whether it is disabled.
        The default flow-control settings are vendor specific.
        If auto-negotiation is enabled, then PAUSE based
        flow-control is negotiated by default.
        The default value is implementation-dependent.";
}

container statistics {
    config false;
    description
        "Contains the number of PAUSE frames received or
        transmitted.";
    leaf in-frames-pause {
        type yang:counter64;
        units frames;
        description
            "A count of PAUSE MAC Control frames transmitted on
            this Ethernet interface.

            Discontinuities in the values of counters in
            this container can occur at re-initialization of the
            management system, and at other times as indicated
            by the value of the 'discontinuity-time' leaf
            defined in the ietf-interfaces YANG module
            (IETF RFC 8343).";
        reference
            "IEEE Std 802.3, 30.3.4.3 aPAUSEMACCtrlFramesReceived";
    }
    leaf out-frames-pause {
        type yang:counter64;
        units frames;
        description
            "A count of PAUSE MAC Control frames transmitted on
            this Ethernet interface.

            Discontinuities in the values of counters in
            this container can occur at re-initialization of the
            management system, and at other times as indicated
            by the value of the 'discontinuity-time' leaf
            defined in the ietf-interfaces YANG module
            (IETF RFC 8343).";
        reference
            "IEEE Std 802.3, 30.3.4.2
            aPAUSEMACCtrlFramesTransmitted";
    }
}
}

container pfc {

```

```
if-feature "ethernet-pfc";
description
  "IEEE Std 802.3 Priority-based flow control.";
reference
  "IEEE Std 802.3, Annex 31D";

leaf enable {
  type boolean;

  description
    "True indicates that IEEE Std 802.3 priority-based
    flow control is enabled, false indicates that
    IEEE Std 802.3 priority-based flow control is disabled.
    For interfaces that have auto-negotiation,
    the priority-based flow control is enabled by default.";
}

container statistics {
  config false;
  description
    "This container collects all statistics for
    Ethernet interfaces.";

  leaf in-frames-pfc {
    type yang:counter64;
    units frames;
    description
      "A count of PFC MAC Control frames received on this
      Ethernet interface.

      Discontinuities in the values of counters in
      this container can occur at re-initialization of the
      management system, and at other times as indicated
      by the value of the 'discontinuity-time' leaf
      defined in the ietf-interfaces YANG module
      (IETF RFC 8343).";
    reference
      "IEEE Std 802.3.1, dot3HCInPFCFrames";
  }

  leaf out-frames-pfc {
    type yang:counter64;
    units frames;
    description
      "A count of PFC MAC Control frames transmitted on
      this interface.

      Discontinuities in the values of counters in
      this container can occur at re-initialization of the
      management system, and at other times as indicated
      by the value of the 'discontinuity-time' leaf
      defined in the ietf-interfaces YANG module
      (IETF RFC 8343).";
    reference
```

IEEE Std 802.3.2-2019
IEEE Standard for Ethernet YANG Data Model Definitions

```

        "IEEE Std 802.3.1, dot3HCInPFCFrames";
    }
}

leaf force-flow-control {
    type boolean;
    default false;
    description
        "Explicitly forces the local PAUSE frame based flow control
        settings regardless of what has been negotiated.

        Since the auto-negotiation of flow-control settings
        does not allow all sane combinations to be negotiated
        (e.g., consider a device that is only capable of sending
        PAUSE frames connected to a peer device that is only
        capable of receiving and acting on PAUSE frames) and
        failing to agree on the flow-control settings does not
        cause the auto-negotiation to fail completely, then it is
        sometimes useful to be able to explicitly enable
        particular PAUSE frame based flow control settings on
        the local device regardless of what is being advertised
        or negotiated.";
    reference
        "IEEE Std 802.3, Table 28B-3";
}

leaf max-frame-length {
    type uint16;
    units octets;
    config false;
    description
        "This indicates the MAC frame length (including FCS bytes)
        at which frames are dropped for being too long.";
    reference
        "IEEE Std 802.3, 30.3.1.1.37 aMaxFrameLength";
}

leaf mac-control-extension-control {
    type boolean;
    config false;
    description
        "A value that identifies the current EXTENSION MAC Control
        function, as specified in IEEE Std 802.3, Annex 31C.";
    reference
        "IEEE Std 802.3, 30.3.8.3 aEXTENSIONMACCtrlStatus
        IEEE Std 802.3.1, dot3ExtensionMacCtrlStatus ";
}

leaf frame-limit-slow-protocol {
    type uint64;
    units f/s;
    default 10;

```

```

    config false;
    description
        "The maximum number of Slow Protocol frames of a given
        subtype that can be transmitted in a one second interval.
        The default value is 10.";
    reference
        "IEEE Std 802.3, 30.3.1.1.38 aSlowProtocolFrameLimit";
}

container capabilities {
    config false;
    description
        "Container all Ethernet interface specific capabilities.";

    leaf auto-negotiation {
        type boolean;
        description
            "Indicates whether auto-negotiation may be configured on
            this interface.";
    }
}

container statistics {
    config false;
    description
        "Contains statistics specific to Ethernet interfaces.

        Discontinuities in the values of counters in the
        container can occur at re-initialization of the management
        system, and at other times as indicated by the value of
        the 'discontinuity-time' leaf defined in the
        ietf-interfaces YANG module (IETF RFC 8343).";

    container frame {
        description
            "Contains frame statistics specific to Ethernet
            interfaces.

            All octet frame lengths include the 4 byte FCS.

            Error counters are only reported once ... The count
            represented by an instance of this object is incremented
            when the frameCheckError status is returned by the MAC
            service to the LLC (or other MAC user). Received frames
            for which multiple error conditions pertain are,
            according to the conventions of IEEE Std 802.3 Layer
            Management, counted exclusively according to the error
            status presented to the LLC.

            A frame that is counted by an instance of this object is
            also counted by the corresponding instance of 'in-errors'
            leaf defined in the ietf-interfaces YANG module
            (IETF RFC 8343).";
    }
}

```

IEEE Std 802.3.2-2019
IEEE Standard for Ethernet YANG Data Model Definitions

Discontinuities in the values of counters in the container can occur at re-initialization of the management system, and at other times as indicated by the value of the 'discontinuity-time' leaf defined in the ietf-interfaces YANG module (IETF RFC 8343).";

```
leaf in-total-frames {
  type yang:counter64;
  units frames;
  description
    "The total number of frames (including bad frames)
    received on the Ethernet interface.

    This counter is calculated by summing the following
    IEEE Std 802.3, Clause 30 counters:
    aFramesReceivedOK +
    aFrameCheckSequenceErrors +
    aAlignmentErrors +
    aFrameTooLongErrors +
    aFramesLostDueToIntMACRcvError

    Also see the 'description' statement associated with
    the parent 'statistics' container for additional
    common semantics related to this counter.";

  reference
    "IEEE Std 802.3, Clause 30 counters, as specified
    in the description above.";
}

leaf in-total-octets {
  type yang:counter64;
  units octets;
  description
    "The total number of octets of data (including those in
    bad frames) received on the Ethernet interface.

    Includes the 4-octet FCS.

    Also see the 'description' statement associated with
    the parent 'statistics' container for additional
    common semantics related to this counter.";

  reference
    "IETF RFC 2819, etherStatsOctets";
}

leaf in-frames {
  type yang:counter64;
  units frames;
  description
    "A count of frames (including unicast, multicast and
    broadcast) that have been successfully received on the
```

Ethernet interface.

This count does not include frames received with frame-too-long, FCS, length or alignment errors, or frames lost due to internal MAC sublayer error.

Also see the 'description' statement associated with the parent 'statistics' container for additional common semantics related to this counter.";

```
reference
  "IEEE Std 802.3, 30.3.1.1.5 aFramesReceivedOK";
}

leaf in-multicast-frames {
  type yang:counter64;
  units frames;
  description
    "A count of multicast frames that have been
    successfully received on the Ethernet interface.

    This counter represents a subset of the frames counted
    by in-frames.

    This count does not include frames received with
    frame-too-long, FCS, length or alignment errors, or
    frames lost due to internal MAC sublayer error.

    Also see the 'description' statement associated with
    the parent 'statistics' container for additional
    common semantics related to this counter.";

  reference
    "IEEE Std 802.3, 30.3.1.1.21 aMulticastFramesReceivedOK";
}

leaf in-broadcast-frames {
  type yang:counter64;
  units frames;
  description
    "A count of broadcast frames that have been
    successfully received on the Ethernet interface.

    This counter represents a subset of the frames counted
    by in-frames.

    This count does not include frames received with
    frame-too-long, FCS, length or alignment errors, or
    frames lost due to internal MAC sublayer error.

    Also see the 'description' statement associated with
    the parent 'statistics' container for additional
    common semantics related to this counter.";
```

IEEE Std 802.3.2-2019
IEEE Standard for Ethernet YANG Data Model Definitions

```

reference
  "IEEE Std 802.3, 30.3.1.1.22 aBroadcastFramesReceivedOK";
}

leaf in-error-fcs-frames {
  type yang:counter64;
  units frames;
  description
    "A count of receive frames that are of valid length,
    but do not pass the FCS check, regardless of whether
    or not the frames are an integral number of octets in
    length.

    This count effectively comprises
    aFrameCheckSequenceErrors and aAlignmentErrors added
    together.

    Also see the 'description' statement associated with
    the parent 'statistics' container for additional
    common semantics related to this counter.";

  reference
    "IEEE Std 802.3, 30.3.1.1.6 aFrameCheckSequenceErrors;
    IEEE Std 802.3, 30.3.1.1.7 aAlignmentErrors";
}

leaf in-error-undersize-frames {
  type yang:counter64;
  units frames;
  description
    "A count of frames received on a particular Ethernet
    interface that are less than 64 bytes in length, and
    are discarded.

    This counter is incremented regardless of whether the
    frame passes the FCS check.

    Also see the 'description' statement associated with
    the parent 'statistics' container for additional
    common semantics related to this counter.";

  reference
    "IETF RFC 2819, etherStatsUndersizePkts and
    etherStatsFragments";
}

leaf in-error-oversize-frames {
  type yang:counter64;
  units frames;
  description
    "A count of frames received on a particular Ethernet
    interface that exceed the maximum permitted frame
    size, that is specified in max-frame-length, and are
    discarded."

```

This counter is incremented regardless of whether the frame passes the FCS check.

Also see the 'description' statement associated with the parent 'statistics' container for additional common semantics related to this counter.";

```
reference "IEEE Std 802.3, 30.3.1.1.25 aFrameTooLongErrors";
}
```

```
leaf in-error-mac-internal-frames {
  type yang:counter64;
  units frames;
  description
    "A count of frames for which reception on a particular
    Ethernet interface fails due to an internal MAC
    sublayer receive error.

    A frame is only counted by an instance of this object
    if it is not counted by the corresponding instance of
    either the in-error-fcs-frames, in-error-undersize-frames,
    or in-error-oversize-frames. The precise meaning of the
    count represented by an instance of this object is
    implementation-specific.
```

In particular, an instance of this object may represent a count of receive errors on a particular Ethernet interface that are not otherwise counted.

Also see the 'description' statement associated with the parent 'statistics' container for additional common semantics related to this counter.";

```
reference
  "IEEE Std 802.3, 30.3.1.1.15
  aFramesLostDueToIntMACRcvError";
}
```

```
leaf out-frames {
  type yang:counter64;
  units frames;
  description
    "A count of frames (including unicast, multicast and
    broadcast) that have been successfully transmitted on
    the Ethernet interface.
```

Also see the 'description' statement associated with the parent 'statistics' container for additional common semantics related to this counter.";

```
reference
  "IEEE Std 802.3, 30.3.1.1.2 aFramesTransmittedOK";
}
```

IEEE Std 802.3.2-2019
IEEE Standard for Ethernet YANG Data Model Definitions

```

leaf out-multicast-frames {
  type yang:counter64;
  units frames;
  description
    "A count of multicast frames that have been
    successfully transmitted on the Ethernet interface.

    This counter represents a subset of the frames counted
    by out-frames.

    Also see the 'description' statement associated with
    the parent 'statistics' container for additional
    common semantics related to this counter.";

  reference
    "IEEE Std 802.3, 30.3.1.1.18 aMulticastFramesXmittedOK";
}

leaf out-broadcast-frames {
  type yang:counter64;
  units frames;
  description
    "A count of broadcast frames that have been
    successfully transmitted on the Ethernet interface.

    This counter represents a subset of the frames counted
    by out-frames.

    Also see the 'description' statement associated with
    the parent 'statistics' container for additional
    common semantics related to this counter.";

  reference
    "IEEE Std 802.3, 30.3.1.1.19 aBroadcastFramesXmittedOK";
}

leaf out-error-mac-internal-frames {
  type yang:counter64;
  units frames;
  description
    "A count of frames for which transmission on a
    particular Ethernet interface fails due to an internal
    MAC sublayer transmit error.

    The precise meaning of the count represented by an
    instance of this object is implementation-specific. In
    particular, an instance of this object may represent a
    count of transmission errors on a particular Ethernet
    interface that are not otherwise counted.

    Also see the 'description' statement associated with
    the parent 'statistics' container for additional
    common semantics related to this counter.";
```

```

        reference
        "IEEE Std 802.3, 30.3.1.1.12
        aFramesLostDueToIntMACXmitError";
    }
}

container phy {
    description
        "Ethernet statistics related to the PHY layer.

        Discontinuities in the values of counters in the
        container can occur at re-initialization of the
        management system, and at other times as indicated by
        the value of the 'discontinuity-time' leaf defined in
        the ietf-interfaces YANG module (IETF RFC 8343).";

    leaf in-error-symbol {
        type yang:counter64;
        units errors;
        description
            "A count of the number of symbol errors that have
            occurred.

            For the precise definition of when the symbol error
            counter is incremented, please see the 'description'
            text associated with aSymbolErrorDuringCarrier,
            specified in IEEE Std 802.3, 30.3.2.1.5.

            Also see the 'description' statement associated with
            the parent 'phy-statistics' container for additional
            common semantics related to this counter.";
        reference
            "IEEE Std 802.3, 30.3.2.1.5 aSymbolErrorDuringCarrier";
    }

    container lpi {
        description
            "Physical Ethernet statistics for the energy efficiency
            related low power idle indications.";

        leaf in-lpi-transitions {
            type yang:counter64;
            units transitions;
            description
                "A count of occurrences of the transition from
                DEASSERT to ASSERT of the LPI_INDICATE
                parameter. The indication reflects the state of the
                PHY according to the requirements of the RS (see
                IEEE Std 802.3, 22.7, 35.4, and 46.4).

                Also see the 'description' statement associated with
                the parent 'phy-statistics' container for additional
                common semantics related to this counter.";
        }
    }
}

```

IEEE Std 802.3.2-2019
IEEE Standard for Ethernet YANG Data Model Definitions

```

reference
  "IEEE Std 802.3, 30.3.2.1.11 aReceiveLPITransitions";
}

leaf in-lpi-time {
  type decimal64 {
    fraction-digits 6;
  }
  units seconds;
  description
    "A count reflecting the total amount of time (in
    seconds) that the LPI_REQUEST parameter has the
    value ASSERT. The request is indicated to the PHY
    according to the requirements of the RS (see IEEE Std
    802.3, 22.7, 35.4, and 46.4).

    Also see the 'description' statement associated with
    the parent 'phy-statistics' container for additional
    common semantics related to this counter.";

  reference
    "IEEE Std 802.3, 30.3.2.1.9 aReceiveLPIMicroseconds";
}

leaf out-lpi-transitions {
  type yang:counter64;
  units transitions;
  description
    "A count of occurrences of the transition from state
    LPI_DEASSERTED to state LPI_ASSERTED in the LPI
    transmit state diagram of the RS. The state
    transition corresponds to the assertion of the
    LPI_REQUEST parameter. The request is indicated to
    the PHY according to the requirements of the RS (see
    IEEE Std 802.3, 22.7, 35.4, 46.4.)

    Also see the 'description' statement associated with
    the parent 'phy-statistics' container for additional
    common semantics related to this counter.";

  reference
    "IEEE Std 802.3, 30.3.2.1.10 aTransmitLPITransitions";
}

leaf out-lpi-time {
  type decimal64 {
    fraction-digits 6;
  }
  units seconds;
  description
    "A count reflecting the total amount of time (in
    seconds) that the LPI_INDICATION parameter has the
    value ASSERT. The request is indicated to the PHY

```

IEEE Std 802.3.2-2019
IEEE Standard for Ethernet YANG Data Model Definitions

according to the requirements of the RS (see IEEE 802.3, 22.7, 35.4, and 46.4).

Also see the 'description' statement associated with the parent 'phy-statistics' container for additional common semantics related to this counter.";

```
reference
  "IEEE Std 802.3, 30.3.2.1.8 aTransmitLPIMicroseconds";
}
}
```

```
container mac-control {
  description
    "A group of statistics specific to MAC Control operation
    of selected Ethernet interfaces.
```

Discontinuities in the values of counters in the container can occur at re-initialization of the management system, and at other times as indicated by the value of the 'discontinuity-time' leaf defined in the ietf-interfaces YANG module (IETF RFC 8343).";

```
reference
  "IEEE Std 802.3.1, dot3ExtensionTable";
```

```
leaf in-frames-mac-control-unknown {
  type yang:counter64;
  units frames;
  description
    "A count of MAC Control frames with an unsupported
    opcode received on this Ethernet interface.

    Frames counted against this counter are also counted
    against in-discards defined in the ietf-interfaces
    YANG module (IETF RFC 8343).

    Also see the 'description' statement associated with
    the parent 'mac-control-statistics' container for
    additional semantics.";
  reference
    "IEEE Std 802.3, 30.3.3.5 aUnsupportedOpCodesReceived";
}
```

```
leaf in-frames-mac-control-extension {
  type yang:counter64;
  units frames;
  description
    "The count of Extension MAC Control frames received on
    this Ethernet interface.

    Also see the 'description' statement associated with
    the parent 'mac-control-statistics' container for
```

5.3.2.2 Ethernet interface module (half-duplex)

43
Copyright © 2019 IEEE. All rights reserved.

```

import ieee802-ethernet-interface {
  prefix ieee802-eth-if;
}

organization
  "IEEE Std 802.3 Ethernet Working Group
  Web URL: http://www.ieee802.org/3/";

contact
  "Web URL: http://www.ieee802.org/3/";

description
  "This module contains YANG definitions for configuring Ethernet
  interfaces that are deprecated, and are no longer
  widely used in the industry. The definitions are maintained for
  backwards compatibility purposes, but the general expectation is
  that this module is not anticipated to be widely implemented.";
reference
  "IEEE Std 802.3-2018, unless dated explicitly";

feature dynamic-rate-control {
  description
    "This feature indicates that the device supports Ethernet
    interfaces lowering the average data rate of the MAC sublayer,
    with frame granularity, by using Rate Control to dynamically
    increase the inter-packet gap for some types of Ethernet
    interface.
    Only valid for Ethernet interfaces operating at speeds (data rates)
    above 1000 Mb/s.";
  reference "IEEE Std 802.3, 30.3.1.1.33 aRateControlAbility";
}

feature csma-cd {
  description
    "This feature indicates that the device supports Ethernet
    interfaces running at half-duplex using CSMA/CD.";
}

typedef dynamic-rate-control-type {
  type enumeration {
    enum disabled {
      description
        "Dynamic rate control is disabled";
    }

    enum "sonet-oc192" {
      value 2;
      description
        "Dynamic rate control is enabled for a 10 Gb/s Ethernet
        interface to SONET/SDH OC192/STM64.";
    }
  }
}
default disabled;
description
  "Allowed values for dynamic-rate-control.";
reference
  "IEEE Std 802.3, 4.4.2 ipgStretchRatio and 30.3.1.1.34
  aRateControlStatus";

```

IEEE Std 802.3.2-2019
IEEE Standard for Ethernet YANG Data Model Definitions

```

}

augment "/if:interfaces/if:interface/ieee802-eth-if:ethernet" {
  when "derived-from-or-self(..if:type, 'ianaift:ethernetCsmacd')
    and ieee802-eth-if:duplex = 'half'" {
    description
      "Applies to half-duplex Ethernet interfaces.";
  }

  description
    "Augment with Ethernet interface configuration parameters
    for half-duplex operation.";

  leaf dynamic-rate-control {
    if-feature "dynamic-rate-control";
    type dynamic-rate-control-type;
    description
      "Enables dynamic rate control and specifies what speed (data rate)
      the dynamic rate control is operating at. The value of this attribute
      is constrained by the MAC data rate and hardware support.
      The default value is implementation-dependent.";
    reference
      "IEEE Std 802.3, 30.3.1.1.34 aRateControlStatus";
  }
}

augment "/if:interfaces/if:interface/ieee802-eth-if:ethernet/" +
  "ieee802-eth-if:capabilities"{
  when "derived-from-or-self(..if:type,
    'ianaift:ethernetCsmacd') and ../ieee802-eth-if:duplex = 'half'" {
    description "Applies to half-duplex Ethernet interfaces";
  }

  description
    "Augment with configuration capabilities for half-duplex
    Ethernet interface.";

  leaf dynamic-rate-control-supported {
    if-feature "dynamic-rate-control";
    type boolean;
    default false;
    description
      "Indicates whether the Ethernet interface supports lowering
      the average data rate of the MAC sublayer, with frame
      granularity, by using Rate Control to dynamically increase
      the inter-packet gap.
      Only valid for Ethernet interfaces operating at speeds (data rates)
      above 1000 Mb/s.";
    reference
      "IEEE Std 802.3, 30.3.1.1.33 aRateControlAbility";
  }
}

augment "/if:interfaces/if:interface/ieee802-eth-if:ethernet/" +
  "ieee802-eth-if:statistics/ieee802-eth-if:frame" {
  when "derived-from-or-self(..if:type,
    'ianaift:ethernetCsmacd') and ../ieee802-eth-if:duplex = 'half'" {
    description
      "Applies to half-duplex Ethernet interfaces.";
  }
}

```