
**Information technology —
Telecommunications and information
exchange between systems — Local and
metropolitan area networks — Specific
requirements —**

**Part 11:
Wireless LAN medium access control
(MAC) and physical layer (PHY)
specifications**

**AMENDMENT 2: MAC enhancements for
robust audio video streaming (adoption of
IEEE Std 802.11aa-2012)**

*Technologies de l'information — Télécommunications et échange
d'information entre systèmes — Réseaux locaux et métropolitains —
Exigences spécifiques —*

*Partie 11: Spécifications du contrôle d'accès du milieu sans fil (MAC) et
de la couche physique (PHY)*

*AMENDEMENT 2: Améliorations du MAC pour une lecture en transit
robuste de fichier sonore ou visuel (adoption de la norme IEEE Std
802.11aa-2012)*



Reference number
ISO/IEC/IEEE 8802-11:2012/Amd.2:2014(E)



Documents
Document Sharing Hub

© IEEE 2012



COPYRIGHT PROTECTED DOCUMENT

© IEEE 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from ISO, IEC or IEEE at the respective address below.

ISO copyright office
Case postale 56
CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
E-mail inmail@iec.ch
Web www.iec.ch

Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York
NY 10016-5997, USA
E-mail stds.ipr@ieee.org
Web www.ieee.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards.

The main task of ISO/IEC JTC 1 is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is called to the possibility that implementation of this standard may require the use of subject matter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. ISO/IEEE is not responsible for identifying essential patents or patent claims for which a license may be required, for conducting inquiries into the legal validity or scope of patents or patent claims or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance or a Patent Statement and Licensing Declaration Form, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from ISO or the IEEE Standards Association.

Amendment 2 to ISO/IEC/IEEE 8802-11 was prepared by the LAN/MAN Standards Committee of the IEEE Computer Society (as IEEE Std 802.11aa-2012). It was adopted by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*, in parallel with its approval by the ISO/IEC national bodies, under the “fast-track procedure” defined in the Partner Standards Development Organization cooperation agreement between ISO and IEEE. IEEE is responsible for the maintenance of this document with participation and input from ISO/IEC national bodies.

(blank page)

IEEE Standard for Information technology—
Telecommunications and information exchange between systems
Local and metropolitan area networks—
Specific requirements

Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications

Amendment 2: MAC Enhancements for Robust Audio Video Streaming

IEEE Computer Society

Sponsored by the
LAN/MAN Standards Committee

IEEE
3 Park Avenue
New York, NY 10016-5997
USA

29 May 2012

IEEE Std 802.11aa™-2012
(Amendment to
IEEE Std 802.11™-2012,
as amended by IEEE Std 802.11ae™-2012)

IEEE Std 802.11aa™-2012

(Amendment to
IEEE Std 802.11™-2012,
as amended by IEEE Std 802.11ae™-2012)

**IEEE Standard for Information technology—
Telecommunications and information exchange between systems
Local and metropolitan area networks—
Specific requirements**

**Part 11: Wireless LAN Medium Access Control
(MAC) and Physical Layer (PHY) Specifications**

**Amendment 2: MAC Enhancements for
Robust Audio Video Streaming**

Sponsor

**LAN/MAN Standards Committee
of the
IEEE Computer Society**

Approved 29 March 2012

IEEE-SA Standards Board

Abstract: This amendment specifies enhancements to the IEEE 802.11 medium access control (MAC) for robust audio video (AV) streaming, while maintaining coexistence with other types of traffic.

Keywords: audio, IEEE 802.11aa, medium access control, video, wireless LAN

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2012 by The Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 29 May 2012. Printed in the United States of America.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

Print: ISBN 978-0-7381-7260-6 STD97235
PDF: ISBN 978-0-7381-7366-5 STDPD97235

IEEE prohibits discrimination, harassment and bullying. For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>. No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Notice and Disclaimer of Liability Concerning the Use of IEEE Documents: IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

Use of an IEEE Standard is wholly voluntary. IEEE disclaims liability for any personal injury, property or other damage, of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, or reliance upon any IEEE Standard document.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims any express or implied warranty, including any implied warranty of merchantability or fitness for a specific purpose, or that the use of the material contained in its standards is free from patent infringement. IEEE Standards documents are supplied "AS IS."

The existence of an IEEE Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard. Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity. Nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

Translations: The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

Official Statements: A statement, written or oral, that is not processed in accordance with the IEEE-SA Standards Board Operations Manual shall not be considered the official position of IEEE or any of its committees and shall not be considered to be, nor be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

Comments on Standards: Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important to ensure that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. Any person who would like to participate in evaluating comments or revisions to an IEEE standard is welcome to join the relevant IEEE working group at <http://standards.ieee.org/develop/wg/>.

Comments on standards should be submitted to the following address:

Secretary, IEEE-SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854
USA

Photocopies: Authorization to photocopy portions of any individual standard for internal or personal use is granted by The Institute of Electrical and Electronics Engineers, Inc., provided that the appropriate fee is paid to Copyright Clearance Center. To arrange for payment of licensing fee, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Notice to users

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

This document is copyrighted by the IEEE. It is made available for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making this document available for use and adoption by public authorities and private users, the IEEE does not waive any rights in copyright to this document.

Updating of IEEE documents

Users of IEEE standards should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect. In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the [IEEE-SA website](http://standards.ieee.org/about/sasb/patcom/patents.html) or contact the IEEE at the address listed previously. For more information about the IEEE Standards Association or the IEEE standards development process, visit the [IEEE-SA website](http://standards.ieee.org).

Errata

Errata, if any, for this and all other standards can be accessed at the following URL: <http://standards.ieee.org/findstds/errata/index.html>. Users are encouraged to check this URL for errata periodically.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. A patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE-SA website <http://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or nondiscriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

Participants

At the time this amendment was sent to sponsor ballot, the IEEE 802.11 Working Group had the following officers:

Bruce P. Kraemer, *Chair*
Adrian P. Stephens and **Jon Walter Rosdahl**, *Vice-Chairs*
Stephen McCann, *Secretary*
Peter Ecclesine, *Technical Editor*

The following were officers of Task Group aa:

Graham K. Smith, *Chair*
Alex Ashley, *Vice-Chair*
Ganesh Venkatesan, *Secretary*
Alex Ashley, *Technical Editor*

When the IEEE 802.11 Working Group first approved this amendment, Task Group aa had the following membership:

Ganesh Venkatesan, *Chair*
Alex Ashley, *Vice Chair*
Hang Lui, *Technical Editor*

Osama S. Aboul-Magd
Santosh P. Abraham
Carlos H. Aldana
David C. Andrus
Lee R. Armstrong
Yusuke Asai
Geert A. Awater
David Bagby
Michael Bahr
Gabor Bajko
Raja Banerjee
Kaberi Banerjee
John R. Barr
Gal Basson
Tuncer Baykas
John L. Benko
Ted Booth
Daniel Borges
Andre Bourdoux
Gregory Breit
Walter Buga
G. Bumiller
Nancy Cam-Winget
Necati Canpolat
Laurent Cariou
Philippe Chambelin
Kapseok Chang
Clint F. Chaplin
Lidong Chen
Minho Cheong
Woong Cho
Chang-Soon Choi
Inhwan Choi
In-Kyeong Choi
Jee-Yon Choi
Liwen Chu

John Coffey
Charles I. Cook
Carlos Cordeiro
Xavier P. Costa
Subir Das
Rolf J. de Vegt
Theodorus Denteneer
Susan Dickey
John Dorsey
Offie Drennan
Roger P. Durand
Donald E. Eastlake
Marc Emmelmann
Vinko Erceg
Leonardo Estevez
Matthew J. Fischer
Wayne K. Fisher
Atsushi Fujimoto
Wen Gao
Matthew Gast
James P. Gilb
Jeffrey Gilbert
Claude Giraud
Ronald Glibbery
Reinhard Gloger
Michelle Gong
David Goodall
Sudheer A. Grandhi
Michael Grigat
Mark Grodzinsky
David Halasz
Mark Hamilton
Christopher J. Hansen
Hiroshi Harada
Dan N. Harkins
Brian D. Hart

Chris Hartman
Amer A. Hassan
Robert F. Heile
Guido R. Hiertz
Garth D. Hillman
Seungeun Hong
Ju-Lan Hsu
Wendong Hu
Tian-Wei Huang
David Hunter
Brima Ibrahim
Akio Iso
Wynona Jacobs
Avinash Jain
Lusheng Ji
Sunggeun Jin
Junho Jo
Vince Jones
Padam Kafle
Carl W. Kain
Naveen K. Kakani
Jeyhan Karaoguz
Assaf Y. Kasher
Shuzo Kato
Tatsuya Kato
Richard H. Kennedy
John Kenney
Stuart J. Kerry
Eung S. Kim
Joonsuk Kim
Kyeongpyo Kim
Yongsun Kim
Youhan Kim
Youngsoo Kim
Yunjoo Kim
Shoichi Kitazawa

Jarkko Knecht	Paul Nikolich	David S. Stephenson
Marm M. Kobayashi	Yujin Noh	John Stine
Fumihide Kojima	Jong-Ee Oh	Guenael T. Strutt
Tom Kolze	Youko Omori	Chin-Sean Sum
Thomas M. Kurihara	Satoshi Oyama	Mohammad H. Taghavi
Joseph Kwak	Richard H. Paine	Mineo Takai
Hyoungjin Kwon	Jaewoo Park	Yasushi Takatori
Ui K. Kwon	Minyoung Park	Teik-Kheong Tan
Ismail Lakkis	Bemini H. Peiris	Alireza Tarighat
Paul Lambert	Eldad Perahia	Geoffrey Thompson
Zhou Lan	James E. Petranovich	Allan Thomson
Leonardo Lanante	Albert Petrick	Jerry Thrasher
Jeremy A. Landt	John Petro	Eric Tokubo
Joseph P. Lauer	Vishakan Ponnampalam	Ichihiko Toyoda
Jae S. Lee	James D. Portaro	Jason Trachewsky
Wooyong Lee	Henry S. Ptasinski	Solomon B. Trainin
Yuro Lee	Rene Purnadi	Jean Tsao
Pei Liu	Ivan Pustogarov	Yung-Szu Tu
Peter Loc	Emily H. Qi	Masahiro Umehira
Artyom Lomayev	Huyu Qu	Richard D. Van Nee
Hui-Ling Lou	Jim E. Raab	Allert Van Zelst
Bradley Lynch	Mohammad Rahman	Prabodh Varshney
Michael Lynch	Harish Ramamurthy	Sameer Vermani
Alastair Malarky	Stephen G. Rayment	George A. Vlantis
Jouni K. Malinen	Ivan Reede	Jesse R. Walker
Alexander Maltsev	Alex Reznik	Chao-Chun Wang
Hiroshi Mano	Sandrine Roblot	Haiguang Wang
Bill Marshall	Randal Roebuck	Junyi Wang
Roman M. Maslennikov	Richard Roy	Qi Wang
Justin P. McNew	Ali Sadri	Craig D. Warren
Murat Mese	Kazuyuki Sakoda	Fujio Watanabe
Sven Mesecke	Hemant Sampath	Menzo M. Wentink
Robert R. Miller	Hirokazu Sawada	Pyo C. Woo
Jochen Miroll	Jean Schwoerer	James Worsham
Apurva Mody	Yongho Seok	Harry R. Worstell
Michael Montemurro	Huairong Shao	Fonchi Wu
Rajendra T. Moorti	Stephen J. Shellhammer	Liuyang Yang
Hitoshi Morioka	Bazhong Shen	James Yee
Yuichi Morioka	Ian Sherlock	Peter Yee
Daniel C. Mur	Nobuhiko Shibagaki	Su K. Yong
Anthony Murabito	Ashish Shukla	Christopher Young
Peter Murray	Francois Simon	Artur Zaks
Andrew Myles	Shubhanshu Singh	Hongyuan Zhang
Yuhei Nagao	Sudhir Srinivasa	Ning Zhang
Hiroki Nakano	Robert Stacey	Meiyuan Zhao
Sai S. Nandagopalan	Dorothy Stanley	Shiwei Zhao
Chiu Ngo		Chunhui Zhu

Major contributions were received from the following individuals:

Osama Aboul-Magd	Jun Li	Ed Reuss
Alex Ashley	Hang Liu	Kevin Rhee
Yonghwan Bang	Xiaojun Ma	Alexander Safonov
Matilda Benveniste	Ishan Mandrekar	John Simons
Douglas Chan	Bill Marshall	Graham K. Smith
Liwen Chu	Saurabh Mathur	Robert Stacey
Todor Cooklev	Jochen Miroll	Rohit Suri
Yacine Ghamri Doudane	Andrew Myles	Allan Thomson
Mark Hamilton	Sanjiv Nanda	Ganesh Venkatesan
Dan N. Harkins	Ivan Pustogarov	George A. Vlantis
Brian D. Hart	Satish Putta	Qi Wang
David Hunter	Luke Qian	Mingquan Wu
Naveen K. Kakani	Raghuram Rangarajan	Jing Zhu

The following members of the individual balloting committee voted on this amendment. Balloters may have voted for approval, disapproval, or abstention.

Tomoko Adachi	David Hunter	Brian Phelps
Iwan Adhicandra	Tetsushi Ikegami	Clinton Powell
Thomas Alexander	Noriyuki Ikeuchi	Venkatesha Prasad
Richard Alfvén	Yasuhiko Inoue	Michael Probasco
Mark Anderson	Sergiu Iordanescu	Henry S. Ptasinski
Butch Anton	Akio Iso	Jayaram Ramasastry
Lee R. Armstrong	Atsushi Ito	Ivan Reede
Alex Ashley	Mitsuru Iwaoka	Maximilian Riegel
Arthur Astrin	Raj Jain	Robert Robinson
Kwok Shum Au	Junghoon Jee	Jon Rosdahl
Michael Bahr	Tal Kaitz	Randall Safier
Nancy Bravin	Naveen K. Kakani	Shigenobu Sasaki
John Buffington	Shinkyō Kaku	Bartien Sayogo
William Byrd	Ruediger Kays	Shusaku Shimada
William Carney	Stuart J. Kerry	John Short
Clint F. Chaplin	Brian Kiernan	Gil Shultz
Keith Chow	Yongbum Kim	Graham K. Smith
Charles I. Cook	Youhan Kim	Kapil Sood
Ray Davis	Bruce P. Kraemer	Robert Stacey
Wael Diab	Thomas M. Kurihara	Dorothy Stanley
Patrick Diamond	Geoff Ladwig	Kevin B. Stanton
Thomas Dineen	Richard Lancaster	Thomas Starai
Sourav Dutta	Jeremy A. Landt	Adrian P. Stephens
Peter Ecclesine	Jan-Ray Liao	Walter Struppler
Richard Eckard	Arthur Light	Guenael T. Strutt
Richard Edgar	William Lumpkins	Mark Sturza
Dennis Edwards	Greg Luri	Bo Sun
Matthew J. Fischer	Elvis Maculuba	Joseph Tardo
Andre Fournier	Jouni K. Malinen	Michael Johas Teener
Avraham Freedman	Stephen McCann	Ichihiko Toyoda
Geoffrey Garner	Michael McInnis	Solomon B. Trainin
Matthew Gast	Gary Michel	Mark-Rene Uchida
Pieter-Paul Giesberts	Apurva Mody	Dmitri Varsanofiev
Gregory Gillooly	Michael Montemurro	Prabodh Varshney
Reinhard Gloger	Rick Murphy	Ganesh Venkatesan
David Goodall	Peter Murray	John Vergis
Sudheer A. Grandhi	Nabil Nasser	Bhupender Virk
Randall Groves	Michael S. Newman	George A. Vlantis
Michael Gundlach	Paul Nikolich	Khurram Waheed
C. Guy	Kevin Noll	Lei Wang
Rainer Hach	John Notor	Stanley Wang
Mark Hamilton	Satoshi Obara	Stephen Webb
Rodney Hemminger	Robert O'Hara	Karl Weber
Jerome Henry	Satoshi Oyama	Hung-Yu Wei
Marco Hernandez	Stephen Palm	Oren Yuen

When the IEEE-SA Standards Board approved this amendment on 29 March 2012, it had the following membership:

Richard H. Hulett, *Chair*
John Kulick, *Vice Chair*
Robert M. Grow, *Past Chair*
Judith Gorman, *Secretary*

Satish Aggarwal
Masayuki Ariyoshi
Peter Balma
William Bartley
Ted Burse
Clint Chaplin
Wael Diab
Jean-Philippe Faure

Alexander Gelman
Paul Houzé
Jim Hughes
Young Kuyn Kim
Joseph L. Koepfinger*
David J. Law
Thomas Lee
Hung Ling

Oleg Logvinov
Ted Olsen
Gary Robinson
Jon Walter Rosdahl
Mike Seavey
Yatin Trivedi
Phil Winston
Yu Yuan

*Member Emeritus

Also included are the following nonvoting IEEE-SA Standards Board liaisons:

Richard DeBlasio, *DOE Representative*
Michael Janezic, *NIST Representative*

Don Messina
IEEE Standards Program Manager, Document Development

Lisa Perry
IEEE Standards Program Manager, Technical Program Development

Introduction

This introduction is not part of IEEE Std 802.11aa-2012, IEEE Standard for Information technology—Telecommunications and information exchange between systems—Local and metropolitan area networks—Specific requirements—Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications—Amendment 2: MAC Enhancements for Robust Audio Video Streaming.

This amendment defines enhancements to the IEEE 802.11 medium access control (MAC) to support robust audio video (AV) streaming.

The amendment specifies enhancements to the following standard and amendment to support robust AV streaming:

- IEEE Std 802.11-2012
- IEEE Std 802.11ae-2012

Contents

1.	Overview	2
1.3	Supplementary information on purpose	2
2.	Normative references	2
3.	Definitions, acronyms, and abbreviations	2
3.1	Definitions	2
3.2	Definitions specific to IEEE 802.11	2
3.3	Abbreviations and acronyms	3
4.	General description	4
4.3	Components of the IEEE 802.11 architecture	4
4.3.15	Mesh BSS: IEEE 802.11 wireless mesh network	4
4.3.16	Robust audio video (AV) streaming	4
5.	MAC service definition	6
5.1	Overview of MAC services	6
5.1.1	Data service	6
6.	Layer management	7
6.3	MLME SAP interface	7
6.3.3	Scan	7
6.3.26	TS management interface	7
6.3.29	Block Ack	13
6.3.67	DMS or GCR request and response procedure	16
6.3.72	QoS Map Set element management	21
6.3.84	SCS request and response procedure	22
6.3.85	QLoad report management	27
6.3.86	HCCA TXOP advertisement management	31
6.3.87	Group membership management	35
6.3.88	AP PeerKey management	39
8.	Frame formats	41
8.2	MAC frame formats	41
8.2.4	Frame fields	41
8.3	Format of individual frame types	42
8.3.1	Control frames	42
8.3.2	Data frames	45
8.3.3	Management frames	46
8.4	Management frame body components	46
8.4.1	Fields that are not information elements	46
8.4.2	Information elements	48
8.5	Action frame format details	62
8.5.3	QoS Action frame details	62
8.5.5	Block Ack Action frame details	65
8.5.8	Public Action details	66

8.5.11	Protected Dual of Public Action frames	70
8.5.14	WNM Action details	70
8.5.16	Self-protected Action frame details	71
8.5.19	Robust AV Streaming Action frame details	72
9.	MAC sublayer functional description	75
9.2	MAC architecture	75
9.2.4	Hybrid coordination function (HCF)	75
9.3	DCF	76
9.3.2	Procedures common to the DCF and EDCAF	76
9.3.6	Group addressed MPDU transfer procedure	77
9.4	PCF	78
9.4.3	PCF access procedure	78
9.4.4	PCF transfer procedure	78
9.7	Multirate support	79
9.7.5	Rate selection for data and management frames	79
9.9	HT Control field operation	79
9.11	A-MSDU operation	79
9.19	HCF	79
9.19.2	HCF contention-based channel access (EDCA)	79
9.19.3	HCCA	83
9.21	Block Acknowledgment (Block Ack)	84
9.21.2	Setup and modification of the Block Ack parameters	84
9.21.3	Data and acknowledgment transfer using immediate Block Ack policy and delayed Block Ack policy	84
9.21.5	Teardown of the Block Ack mechanism	85
9.21.6	Selection of BlockAck and BlockAckReq variants	85
9.21.10	GCR Block Ack	85
9.26	PSMP Operation	88
9.26.1	Frame transmission mechanism during PSMP	88
10.	MLME	88
10.2	Power management	88
10.2.1	Power management in an infrastructure network	88
10.4	TS operation	93
10.4.1	Introduction	93
10.4.4	TS setup	93
10.4.8	Data transfer	95
10.5	Block Ack operation	95
10.5.2	Setup and modification of the Block Ack parameters	95
10.5.4	Error recovery upon a peer failure	96
10.18	RSNA A-MSDU procedures	96
10.23	Wireless network management procedures	96
10.23.15	Group addressed transmission service DMS procedures	96
10.25	Quality-of-service management frame (QMF)	107
10.25.2	QMF policy advertisement and configuration procedures	107
10.26	Robust AV streaming	108
10.26.1	Robust AV streaming dependencies	108
10.26.2	SCS procedures	108
10.27	Procedures to manage OBSS	109
10.27.1	General	109
10.27.2	QLoad Report element	110

10.27.3	HCCA TXOP negotiation	112
10.27.4	HCCA AP timing synchronization for HCCA TXOP advertisement	116
11.	Security	117
11.8	Per-frame pseudo-code	117
11.8.2	RSNA frame pseudo-code	117
11.10	AP PeerKey support	118
11.10.1	AP PeerKey overview	118
11.10.2	AP PeerKey protocol	119
	Annex B (normative) Protocol Implementation Conformance Statement (PICS) proforma.....	121
B.2	Abbreviations and special symbols	121
B.2.2	General abbreviations for Item and Support columns	121
B.4	PICS proforma—IEEE Std 802.11-2012.....	121
B.4.3	IUT configuration	121
B.4.25	RobustAVT extensions	121
	Annex C (normative) ASN.1 encoding of the MAC and PHY MIB	123
	Annex X (informative) Overlapping BSS (OBSS) management	135
X.1	Introduction	135
X.2	QLoad Report element.....	135
X.2.1	General.....	135
X.2.2	Calculating medium time.....	136
X.2.3	Calculation of potential traffic self.....	136
X.2.4	Calculation of allocated traffic self	138
X.2.5	Calculation of allocated traffic shared.....	139
X.2.6	Calculation of EDCA Access Factor	139
X.2.7	EDCA Overhead Factor.....	140
X.2.8	Calculation of HCCA Access Factor.....	141
X.3	Channel selection using QLoad report	141
X.3.1	General.....	141
X.3.2	AP with admission control mandatory	141
X.3.3	AP with an HC.....	142
X.3.4	Channel selection procedures	142
X.4	Sharing in an OBSS situation	143
X.4.1	General.....	143
X.4.2	Sharing schemes	144
X.5	Mitigating consequences of OBSS sharing in presence of noncollaborating devices.....	146

Tables

Table 6-1—Supported TS management primitives	7
Table 8-16—BlockAckReq frame variant encoding	43
Table 8-18—BlockAck frame variant encoding	44
Table 8-20—Beacon frame body	46
Table 8-27—Probe Response frame body	46
Table 8-37—Status codes	46
Table 8-38—Category values	47
Table 8-54—Element IDs	48
Table 8-101—AKM suite selectors	48
Table 8-103—Capabilities field	49
Table 8-110—Setting of Schedule subfield	50
Table 8-170—Optional Subelement IDs for DMS Descriptor	52
Table 8-170a—GATS Retransmission Policy field values	52
Table 8-170b—GCR Delivery Method field values	53
Table 8-171—Response Type field values	53
Table 8-172—Optional Subelement IDs for DMS Status	54
Table 8-183a—Request Type definitions	57
Table 8-183b—Optional Subelement IDs for SCS Descriptor element	57
Table 8-183c—Sharing Policy definitions	59
Table 8-183d—Optional Subelement IDs for QLoad Report element	59
Table 8-183e—Protocol ID definitions	61
Table 8-192—QoS Action field values	62
Table 8-193—ADDTS Request frame Action field format	62
Table 8-194—ADDTS Response frame Action field format	63
Table 8-197—QoS Map configure frame body	63
Table 8-197a—ADDTS Reserve Request frame Action field format	64
Table 8-197b—ADDTS Reserve Response frame Action field format	64
Table 8-203—ADDBA Request frame Action field format	65
Table 8-204—ADDBA Response frame Action field format	65
Table 8-205—DELBA frame Action field values	66
Table 8-210—Public Action field values	66
Table 8-221b—QLoad Report frame Action field format	67
Table 8-221a—QLoad Request frame Action field format	67
Table 8-228—Public Action field values defined for Protected Dual of Public Action frames	70
Table 8-221c—Request Type definitions	70
Table 8-262—Mesh Peering Open frame Action field format	71
Table 8-263—Mesh Peering Confirm frame Action field format	71
Table 8-264—Mesh Peering Close frame Action field format	72
Table 8-281a—Robust AV streaming Robust Action field values	72
Table 8-502d—Group Membership Request frame Action field format	74
Table 9-1—UP-to-AC mappings	75
Table 10-1—Power Management modes	89
Table 10-2—Types of Block Ack agreement based on capabilities and ADDBA conditions	96
Table 10-9a—STA recovery procedures for a changed retransmission policy	104
Table 10-9b—Non-AP STA recovery procedures for a changed delivery method	105
Table 10-14—Contents of HCCA TXOP Response frame	115

Figures

Figure 6-25—DMS or GCR setup protocol exchange.....	16
Figure 6-25a—Example SCS setup and termination protocol exchange	22
Figure 8-20—BAR Control field.....	42
Figure 8-5—HT Control field.....	42
Figure 8-23a—BAR Information field format (GCR BlockAckReq)	43
Figure 8-24—BA Control field.....	44
Figure 8-28a—BA Information field format (GCR BlockAck)	45
Figure 8-80a—TXOP Reservation field format	47
Figure 8-346a—GCR Request subelement field format.....	52
Figure 8-348a—GCR Response subelement field format	55
Figure 8-401d—Intra-Access Category Priority element format	55
Figure 8-401e—Intra-Access Priority field format	56
Figure 8-401f—SCS Descriptor element format	56
Figure 8-401g—QLoad Report element format	58
Figure 8-401h—QLoad field format.....	59
Figure 8-401i—HCCA TXOP Update Count element format	60
Figure 8-104j—Higher Layer Stream ID element format	60
Figure 8-401k—GCR Group Address element format.....	61
Figure 8-460c—HCCA TXOP Advertisement frame Action field format.....	68
Figure 8-460d—HCCA TXOP Response frame Action field format.....	68
Figure 8-460e—Public Key frame body format.....	69
Figure 8-502a—SCS Request frame Action field format.....	73
Figure 8-502b—SCS Response frame Action field format.....	73
Figure 8-502c—SCS Status dupe format	73
Figure 8-502e—Group Membership Response frame Action field format.....	74
Figure 9-19—Reference implementation model when dot11AlternateEDCAActivated is false or not present.....	79
Figure 9-19a—Reference implementation model when dot11AlternateEDCAActivated is true.....	80
Figure 9-28a—Example of a frame exchange with GCR Block Ack retransmission policy	87
Figure 10-8a—TS setup when initiated by the AP	94

IEEE Standard for Information technology—
Telecommunications and information exchange between systems
Local and metropolitan area networks—
Specific requirements

Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications

Amendment 2: MAC Enhancements for Robust Audio Video Streaming

IMPORTANT NOTICE: This standard is not intended to assure safety, security, health, or environmental protection. Implementers of the standard are responsible for determining appropriate safety, security, environmental, and health practices or regulatory requirements.

This IEEE document is made available for use subject to important notices and legal disclaimers. These notices and disclaimers appear in all publications containing this document and may be found under the heading “Important Notice” or “Important Notices and Disclaimers Concerning IEEE Documents.” They can also be obtained on request from IEEE or viewed at <http://standards.ieee.org/IPR/disclaimers.html>.

(This amendment is based on IEEE Std 802.11™-2012, as amended by IEEE Std 802.11ae-2012.)

NOTE—The editing instructions contained in this amendment define how to merge the material contained therein into the existing base standard and its amendments to form the comprehensive standard. The editing instructions are shown in **bold italic**. Four editing instructions are used: change, delete, insert, and replace. **Change** is used to make corrections in existing text or tables. The editing instruction specifies the location of the change and describes what is being changed by using ~~strike through~~ (to remove old material) and underscore (to add new material). **Delete** removes existing material. **Insert** adds new material without disturbing the existing material. Deletions and insertions may require renumbering. If so, renumbering instructions are given in the editing instruction. **Replace** is used to make changes in figures or equations by removing the existing figure or equation and replacing it with a new one. Editing instructions, change markings, and this NOTE will not be carried over into future editions because the changes will be incorporated into the base standard.¹

¹Notes in text, tables, and figures are given for information only and do not contain requirements needed to implement the standard

1. Overview

1.3 Supplementary information on purpose

Insert the following list item at the end of the dashed list in 1.3:

- Defines mechanisms to improve audio video (AV) streaming quality of service (QoS) while maintaining data and voice performance.

2. Normative references

Insert the following reference into Clause 2 in alphanumeric order:

IEEE Std 802.1Q™-2011, IEEE Standard for Local and Metropolitan Area Networks: Media Access Control (MAC) Bridges and Virtual Bridged Local Area Networks.^{2,3}

3. Definitions, acronyms, and abbreviations

3.1 Definitions

Change the definition of service period in 3.1 as follows:

service period (SP): A contiguous time during which one or more downlink unicast frames are transmitted to a quality of service (QoS) station (STA) and/or one or more transmission opportunities (TXOPs) are granted to the same STA. SPs can be scheduled or unscheduled. For a non-access point (non-AP) STA, there can be at most one nongroupcast with retries SP (non-GCR-SP) active at any time.

3.2 Definitions specific to IEEE 802.11

Insert the following definitions into 3.2 in alphabetic order:

advanced groupcast with retries (GCR): A set of features comprising the GCR block acknowledgment retransmission policy and the GCR service period (GCR-SP) delivery method.

concealed groupcast with retries (GCR) frame: A group addressed frame that is transmitted using the aggregate medium access control (MAC) service data unit (A-MSDU) frame format with the destination address (DA) field set to the GCR concealment address.

group addressed transmission service (GATS): A mechanism comprising directed multicast service (DMS) and groupcast with retries (GCR), for delivery of group addressed frames.

groupcast with retries (GCR) active (GCR-A) delivery: A delivery method for a group addressed stream subject to a GCR agreement wherein the frames may be transmitted without regard to the power state of non-access point (non-AP) stations (STAs).

²The IEEE standards or products referred to in this clause are trademarks owned by The Institute of Electrical and Electronics Engineers, Inc.

³IEEE publications are available from The Institute of Electrical and Electronics Engineers (<http://standards.ieee.org/>).

groupcast with retries (GCR) concealment address: A medium access control (MAC) address that is used to prevent group addressed frames transmitted via the GCR unsolicited retry or GCR Block Ack retransmission policies from being passed up the medium access control service access point (MAC_SAP) of GCR-incapable stations (STAs).

groupcast with retries (GCR) frame: A group addressed frame subject to a GCR agreement between the access point (AP) and at least one station (STA) within the infrastructure basic service set (BSS) or between peer mesh STAs in a mesh BSS.

groupcast with retries (GCR) group address: A group address subject to a GCR agreement between the access point (AP) and at least one station (STA) within the basic service set (BSS) or between peer mesh STAs in a mesh BSS.

groupcast with retries (GCR) service: A means for transmission and retransmission of medium access control (MAC) service data units (MSDUs) to a destination that is a group address. The GCR service provides greater reliability by using group addressed retransmissions, concealed from GCR-incapable stations (STAs).

groupcast with retries (GCR) service period (GCR-SP) aggregate medium access control (MAC) service data unit (A-MSDU): An A-MSDU subject to the GCR service with delivery method equal to GCR-SP.

groupcast with retries (GCR) service period (GCR-SP) frame: A frame subject to the GCR service when delivery method is GCR-SP.

groupcast with retries (GCR) service period (GCR-SP) medium access control (MAC) service data unit (MSDU): An MSDU subject to the GCR service with delivery method equal to GCR-SP.

groupcast with retries (GCR) transmission opportunity (TXOP): An interval of time when an access point (AP) or a mesh station (STA) has the right to initiate frame exchange sequences onto the wireless medium (WM) for the purpose of transmitting multiple frames that are subject to the GCR service.

no acknowledgment/no retry (No-Ack/No-Retry): A retransmission policy for group addressed frames in which each frame is transmitted once and without acknowledgment.

nonconcealed groupcast with retries (GCR) frame: A group addressed frame that is not transmitted to the GCR concealment address.

nongroupcast with retries (non-GCR): A method for delivering group addressed frames without using the GCR unsolicited retry retransmission policy, the GCR block acknowledgment retransmission policy, or the GCR service period (GCR-SP) delivery method.

nongroupcast with retries service period (non-GCR-SP): A method for the delivery of group addressed frames without the use of a GCR service period (GCR-SP).

3.3 Abbreviations and acronyms

Insert the following abbreviations into 3.3 in alphabetic order:

AV	audio visual
GATS	group addressed transmission service
GCR	groupcast with retries
GCR-SP	groupcast with retries service period

DEI	drop eligibility indicator
QLDRC	QoS long drop-eligible retry counter
QSDRC	QoS short drop-eligible retry counter
SCS	stream classification service
SCSID	stream classification service identifier

4. General description

4.3 Components of the IEEE 802.11 architecture

4.3.15 Mesh BSS: IEEE 802.11 wireless mesh network

4.3.15.3 Mesh STA

Change 4.3.15.3 as follows:

A STA that belongs to a mesh BSS is termed a “mesh station” (mesh STA). Mesh STAs are QoS STAs that support mesh services, i.e., they participate in formation and operation of a mesh basic service set (MBSS). A mesh STA implements a subset of the QoS functionality. This subset is as follows:

- Use of QoS frame format
- EDCA (as a part of MCF)
- Block acknowledgment (optional)
- No acknowledgment (optional)
- Use of TSPEC, TCLAS, and TCLAS Processing elements to establish DMS or GCR agreements (optional)

A mesh BSS does not incorporate the full hybrid coordinator (HC) and BSS QoS functionality. MBSSs do not incorporate the following:

- HCCA
- ~~Traffic specification (TSPEC)~~
- Traffic stream (TS) management
- Admission control
- Automatic power save delivery (APSD)
- Direct-link setup (DLS)
- Tunneled direct-link setup (TDLS)

Insert the following subclauses, 4.3.16 to 4.3.16.5, after 4.3.15.3.13:

4.3.16 Robust audio video (AV) streaming

Robust AV streaming improves AV streaming performance when using IEEE 802.11 for consumer and enterprise applications.

4.3.16.1 Groupcast with retries (GCR)

The GCR service allows a STA to request greater reliability for one or more group addressed streams that the STA receives. Greater reliability is provided via unsolicited retries or the Block Ack mechanism. A non-AP STA may request delivery so that the AP transmits the frames via EDCA within GCR service periods when all associated non-AP STAs are in active mode or the Awake state of the PS mode.

4.3.16.2 Stream classification service (SCS)

SCS enables the establishment of a classification using layer 2 and/or layer 3 signaling to match incoming unicast MSDUs. Once classified, unicast MSDUs matching the classification are assigned to an access category and are tagged with their drop eligibility. When intra-access category prioritization is enabled (see 4.3.16.5), SCS allows MSDUs matching the classification to be assigned to the primary or alternate transmit queues so that finer grained prioritization can be applied.

4.3.16.3 Overlapping BSS (OBSS) management

The objective of OBSS management is to facilitate cooperative sharing of the medium between APs that operate in the same channel and that are able to receive or obtain frames from each other, including Beacon frames. These frames might be received directly or via associated STAs that support the Beacon request capability (see 10.11.10).

OBSS management provides the means to

- Provide additional information for channel selection
- Extend the admission control mechanism to a distributed environment
- Enable the coordination of scheduled TXOPs between OBSSs

OBSS management enables stationary and portable APs to provide to neighboring APs information for the selection of a channel and for the cooperative sharing of that channel. The main component of OBSS management is the QLoad report that provides information on

- The reporting AP's overlap situation
- The reporting AP's QoS traffic load
- The total QoS traffic load of BSSs directly overlapping the reporting AP's BSS

This information might be used to aid an AP when searching for a channel and also when sharing a channel in an overlap situation.

To coordinate the TXOPs of overlapping HCCA APs, OBSS management provides a means for an AP to advertise its TXOP allocations so another AP might schedule its own TXOPs to avoid those already scheduled.

4.3.16.4 Interworking with IEEE 802.1Q Stream Reservation Protocol (SRP)

Support for SRP from IEEE Std 802.1Q-2011 enables integration of the TSPEC ADDTS request/response protocol with IEEE 802.1Q SRP to enable end-to-end SRP reservations when one or more IEEE 802.11 links are part of a path from IEEE 802.1Q Talker to IEEE 802.1Q Listener.

4.3.16.5 Intra-access category prioritization

Intra-access category prioritization provides six transmit queues that map to four enhanced distributed channel access functions (EDCAFs) to enable differentiation between traffic streams that are in the same access category in order for finer grained prioritization to be applied between individual AV streams or voice streams.

5. MAC service definition

5.1 Overview of MAC services

5.1.1 Data service

5.1.1.2 Determination of UP

Change 5.1.1.2 as follows:

The QoS facility supports eight priority values, referred to as UPs. The values a UP may take are the integer values from 0 to 7 and are identical to the IEEE 802.1D priority tags. An MSDU with a particular UP is said to belong to a traffic category (TC) with that UP. The UP is provided with each MSDU at the medium access control service access point (MAC_SAP) either directly, in the UP parameter, or indirectly, in a TSPEC or SCS Descriptor element designated by the UP parameter.

5.1.1.5 Interpretation of service class parameter in MAC service primitives in a STA

Change 5.1.1.5 as follows:

In QoS STAs, the value of the service class parameter in the MAC service primitive (see 5.2) may be a noninteger value of QoSack or QoSNoAck.

When an MSDU is received from the MAC_SAP and the recipient STA is a QoS STA with the service class set to

- QoSack, the MSDU is transmitted using a QoS data frame with the Ack Policy subfield in the QoS Control field set to either Normal Ack (normal acknowledgment) or Block Ack.
- QoSNoAck, the MSDU is transmitted using a QoS data frame with the Ack Policy subfield in the QoS Control field set to No Ack (no acknowledgment). ~~If the sender STA is contained within an AP and the frame has a group DA, then the MSDU is buffered for transmission and is also sent to the DS.~~

If the sender STA is an AP and the frame has a group DA that is not the GCR concealment address, then the MSDU is buffered for transmission and is also sent to the DS.

When an MSDU is received from the MAC_SAP and the recipient STA is not a QoS STA, the MSDU is transmitted using a non-QoS data frame.

When a QoS data frame is received from another STA, the service class parameter in the MA-UNITDATA.indication primitive is set to

- QoSack, if the frame is a QoS data frame with the Ack Policy subfield in the QoS Control field equal to either Normal Ack or Block Ack.
- QoSack, if the frame was delivered via the DMS or the GCR Block Ack retransmission policy.
- QoSNoAck, if the frame is a QoS data frame with the Ack Policy subfield in the QoS Control field equal to No Ack. This service class is also used ~~where when~~ the DA parameter is a group address unless the frame was delivered via DMS or the GCR Block Ack retransmission policy.

When a non-QoS data frame is received from a STA, the service class parameter in the MA-UNITDATA.indication primitive is set to

- QoSack, if the frame is an individually addressed frame and is acknowledged by the STA.
- QoSNoAck, if the frame is a group addressed frame and is not acknowledged by the STA.

Note that the group addressed frames sent by a non-QoS STA are not acknowledged regardless of the value of the service class parameter in the MA-UNITDATA.indication primitive.

NOTE—GCR frames are transmitted only by an AP for which dot11GCRActivated is true or by a mesh STA for which dot11MeshGCRActivated is true.

6. Layer management

6.3 MLME SAP interface

6.3.3 Scan

6.3.3.3 MLME-SCAN.confirm

6.3.3.3.2 Semantics of the service primitive

Insert the following row at the end of the untitled table describing BSSDescriptions in 6.3.3.3.2 (note that the entire table is not shown here):

Name	Type	Valid range	Description	IBSS adoption
QLoad Report	As defined in frame format	As defined in 8.4.2.125	The values from the QLoad Report element if such an element was present in the probe response frame, else null.	Do not adopt.

6.3.26 TS management interface

6.3.26.1 General

Change Table 6-1 as follows:

Table 6-1—Supported TS management primitives

Primitive	Request	Confirm	Indication	Response
ADDTS	non-AP QoS STA	non-AP QoS STA	HC	HC
DELTS	non-AP QoS STA and HC	non-AP QoS STA and HC	non-AP QoS STA and HC	—
<u>ADDTSRESERVE</u>	<u>HC</u>	<u>HC</u>	<u>non-AP QoS STA</u>	<u>non-AP QoS STA</u>

6.3.26.2 MLME-ADDTS.request**6.3.26.2.2 Semantics of the service primitive**

Change the primitive parameter list in 6.3.26.2.2 as follows:

The primitive parameters are as follows:

```
MLME-ADDTS.request(
    DialogToken,
    TSPEC,
    TCLAS,
    TCLASProcessing,
    ADDTSFailureTimeout,
    U-APSD Coexistence,
    EBR,
    IntraAccessCategoryPriority,
    HigherLayerStreamID,
    VendorSpecificInfo
)
```

Insert the following rows before the VendorSpecificInfo row of the untitled table in 6.3.26.2.2 (note that the entire table is not shown here):

Name	Type	Valid range	Description
IntraAccessCategoryPriority	Intra-Access Category Priority element	As defined in 8.4.2.123	Specifies the intra-AC priorities the STA should use.
HigherLayerStreamID	Higher Layer Stream ID element	As defined in 8.4.2.127	Identifies the higher layer stream.

6.3.26.3 MLME-ADDTS.confirm**6.3.26.3.2 Semantics of the service primitive**

Change the primitive parameter list in 6.3.26.3.2 as follows:

The primitive parameters are as follows:

```
MLME-ADDTS.confirm(
    ResultCode,
    DialogToken,
    TSDelay,
    TSPEC,
    Schedule,
    TCLAS,
    TCLASProcessing,
    EBR,
    HigherLayerStreamID,
    VendorSpecificInfo
)
```

Insert the following row before the VendorSpecificInfo row of the untitled table in 6.3.26.3.2 (note that the entire table is not shown here):

Name	Type	Valid range	Description
HigherLayerStreamID	Higher Layer Stream ID element	As defined in 8.4.2.127	Identifies the higher layer stream.

6.3.26.4 MLME-ADDTS.indication

6.3.26.4.2 Semantics of the service primitive

Change the primitive parameter list in 6.3.26.4.2 as follows:

The primitive parameters are as follows:

MLME-ADDTS.indication (

DialogToken,
STAAddress,
TSPEC,
TCLAS,
TCLASProcessing,
U-APSD Coexistence,
EBR,
IntraAccessCategoryPriority,
HigherLayerStreamID,
VendorSpecificInfo
)

Insert the following rows before the VendorSpecificInfo row of the untitled table in 6.3.26.4.2 (note that the entire table is not shown here):

Name	Type	Valid range	Description
IntraAccessCategoryPriority	Intra-Access Category Priority element	As defined in 8.4.2.123	Specifies the intra-AC priorities the STA should use.
HigherLayerStreamID	Higher Layer Stream ID element	As defined in 8.4.2.127	Identifies the higher layer stream.

6.3.26.5 MLME-ADDTS.response

6.3.26.5.2 Semantics of the service primitive

Change the primitive parameter list in 6.3.26.5.2 as follows:

The primitive parameters are as follows:

MLME-ADDTS.response (

ResultCode,
DialogToken,
STAAddress,
TSDelay,

TSPEC,
Schedule,
TCLAS,
TCLASProcessing,
EBR,
HigherLayerStreamID,
VendorSpecificInfo
)

Insert the following row before the VendorSpecificInfo row in the untitled table in 6.3.26.5.2 (note that the entire table is not shown here):

Name	Type	Valid range	Description
HigherLayerStreamID	Higher Layer Stream ID element	As defined in 8.4.2.127	Identifies the higher layer stream.

Insert the following subclauses, 6.3.26.8 to 6.3.26.11.4, after 6.3.26.7.4:

6.3.26.8 MLME-ADDTSRESERVE.request

6.3.26.8.1 Function

This primitive request is used by the SME at the AP to start the AP-initiated TS setup procedure.

6.3.26.8.2 Semantics of the service primitive

The primitive parameters are as follows:

MLME-ADDTSRESERVE.request (

TSPEC,
HigherLayerStreamID,
Schedule,
VendorSpecificInfo
)

Name	Type	Valid range	Description
TSPEC	TSPEC element	As defined in 8.4.2.32	Specifies the QoS parameters of the TS.
HigherLayerStreamID	Higher Layer Stream ID element	As defined in 8.4.2.127	Stream identifier assigned by a higher layer protocol.
Schedule	Schedule element	As defined in 8.4.2.36	Specifies the schedule information, service start time, SI, and the specification interval.
VendorSpecificInfo	A set of elements	As defined in 8.4.2.28	Zero or more elements.

6.3.26.8.3 When generated

This primitive is generated by the SME at the AP to start the AP-initiated TS setup procedure. If the parameter validation on the parameters used in this primitive succeeds, an ADDTS Reserve Request action frame is transmitted from the AP to a non-AP STA.

6.3.26.8.4 Effect of receipt

The STA operates according to the procedures defined in 10.4.4.3.

6.3.26.9 MLME-ADDTSRESERVE.confirm**6.3.26.9.1 Function**

This primitive is an indication to the SME that is generated by the MLME as a result of receiving an ADDTS Reserve Response action frame from the non-AP STA to which the AP sent a corresponding ADDTS Reserve Request action frame.

6.3.26.9.2 Semantics of the service primitive

The primitive parameters are as follows:

```
MLME-ADDTSRESERVE.confirm (
    ResultCode,
    StreamID
)
```

Name	Type	Valid range	Description
ResultCode	Enumeration	SUCCESS, FAILURE	Indicates the results of the corresponding MLME-ADDTSReserve.request primitive.
StreamID	Higher Layer Stream ID element	As defined in 8.4.2.127	Stream identifier specified in the corresponding MLME-ADDTSReserve.request primitive.

6.3.26.9.3 When generated

This primitive is generated by the MLME as a result of receiving an ADDTS Reserve Response action frame from the non-AP STA to which the AP sent a corresponding ADDTS Reserve Request action.

6.3.26.9.4 Effect of receipt

The SME is notified of the results of the AP-initiated TS setup procedure.

6.3.26.10 MLME-ADDTSRESERVE.indication**6.3.26.10.1 Function**

This primitive reports to the non-AP STA's SME the initiation of AP-initiated TS setup procedure.

6.3.26.10.2 Semantics of the service primitive

The primitive parameters are as follows:

MLME-ADDTSRESERVE.indication (
 APAddress,
 TSPEC,
 Schedule,
 HigherLayerStreamID,
 VendorSpecificInfo
)

Name	Type	Valid range	Description
APAddress	MAC Address	—	Contains the MAC address of the AP initiating the TS setup procedure.
TSPEC	TSPEC element	As defined in 8.4.2.32	Specifies the QoS parameters of the TS.
Schedule	Schedule element	As defined in 8.4.2.36	Specifies the schedule information, service start time, SI, and the specification interval.
HigherLayerStreamID	Higher Layer Stream ID element	As defined in 8.4.2.127	Stream identifier in the received ADDTS Reserve Request action frame.
VendorSpecificInfo	A set of elements	As defined in 8.4.2.28	Zero or more elements.

6.3.26.10.3 When generated

This primitive is generated by the MLME at the non-AP STA as a result of the receipt of an ADDTS Reserve Request action frame from the AP to which the non-AP STA is associated.

6.3.26.10.4 Effect of receipt

The SME is notified of the receipt of the ADDTS Reserve Request action frame from the AP. This primitive solicits the SME to participate in the AP-initiated TS setup procedure.

The SME should operate according to the procedures defined in 10.4.4.3.

6.3.26.11 MLME-ADDTSRESERVE.response**6.3.26.11.1 Function**

This primitive is used by a non-AP STA to indicate to the HC the completion of an AP-initiated TS setup procedure.

6.3.26.11.2 Semantics of the service primitive

The primitive parameters are as follows:

```
MLME-ADDTRESERVE.response (
    HigherLayerStreamID,
    ResultCode,
    VendorSpecificInfo
)
```

Name	Type	Valid range	Description
HigherLayerStreamID	Higher Layer Stream ID element	As defined in 8.4.2.127	Stream identifier specified in the corresponding MLME-ADDTRESERVE.indication primitive.
ResultCode	Enumeration	0 or 1 (as defined in Table 8-37)	Indicates the result of the AP-initiated TS setup procedure.
VendorSpecificInfo	A set of elements	As defined in 8.4.2.28	Zero or more elements.

6.3.26.11.3 When generated

This primitive is generated by the SME at the non-AP STA to indicate to a HC that the non-AP STA has setup a TS in response to a higher layer protocol.

6.3.26.11.4 Effect of receipt

The STA operates according to the procedures defined in 10.4.4.3.

6.3.29 Block Ack

6.3.29.2 MLME-ADDBA.request

6.3.29.2.2 Semantics of the service primitive

Change the primitive parameter list in 6.3.29.2.2 as follows:

The primitive parameters are as follows:

```
MLME-ADDBA.request(
    PeerSTAAddress,
    DialogToken,
    TID,
    BlockAckPolicy,
    BufferSize,
    BlockAckTimeout,
    ADDBAFailureTimeout,
    BlockAckStartingSequenceControl,
    GCRGroupAddress,
    VendorSpecificInfo
)
```

Insert the following row before the VendorSpecificInfo row in the untitled table in 6.3.29.2.2 (note that the entire table is not shown here):

Name	Type	Valid range	Description
GCRGroupAddress	GCR Group Address element	As defined in 8.4.2.128	Specifies the group address for which a Block Ack agreement is requested. If the element is present, a GCR Group Address element is included in the transmitted ADDBA Request frame.

6.3.29.3 MLME-ADDDBA.confirm

6.3.29.3.2 Semantics of the service primitive

Change the primitive parameter list in 6.3.29.3.2 as follows:

The primitive parameters are as follows:

```
MLME-ADDDBA.confirm(
    PeerSTAAddress,
    DialogToken,
    TID,
    ResultCode,
    BlockAckPolicy,
    BufferSize,
    BlockAckTimeout,
    GCRGroupAddress,
    VendorSpecificInfo
)
```

Insert the following row before the VendorSpecificInfo row in the untitled table in 6.3.29.3.2 (note that the entire table is not shown here):

Name	Type	Valid range	Description
GCRGroupAddress	GCR Group Address element	As defined in 8.4.2.128	Specifies the group address for which a Block Ack agreement was requested.

6.3.29.4 MLME-ADDDBA.indication

6.3.29.4.2 Semantics of the service primitive

Change the primitive parameter list in 6.3.29.4.2 as follows:

The primitive parameters are as follows:

```
MLME-ADDDBA.indication(
    PeerSTAAddress,
    DialogToken,
    TID,
```

```

BlockAckPolicy,
BufferSize,
BlockAckTimeout,
GCRGroupAddress,
VendorSpecificInfo
)

```

Insert the following row before the VendorSpecificInfo row in the untitled table in 6.3.29.4.2 (note that the entire table is not shown here):

Name	Type	Valid range	Description
GCRGroupAddress	GCR Group Address element	As defined in 8.4.2.128	Specifies the group address for which a Block Ack agreement is requested. This element is present if a GCR Group Address element was included in the transmitted ADDBA Request frame.

6.3.29.5 MLME-ADDDBA.response

6.3.29.5.2 Semantics of the service primitive

Change the primitive parameter list in 6.3.29.5.2 as follows:

The primitive parameters are as follows:

```

MLME-ADDDBA.response(
    PeerSTAAddress,
    DialogToken,
    TID,
    ResultCode,
    BlockAckPolicy,
    BufferSize,
    BlockAckTimeout,
    GCRGroupAddress,
    VendorSpecificInfo
)

```

Insert the following row before the VendorSpecificInfo row in the untitled table in 6.3.29.5.2 (note that the entire table is not shown here):

Name	Type	Valid range	Description
GCRGroupAddress	GCR Group Address element	As defined in 8.4.2.128	Specifies the group address for which a Block Ack agreement was requested.

Change the title of 6.3.67 as follows:

6.3.67 DMS or GCR request and response procedure

6.3.67.1 General

Change the first paragraph of 6.3.67.1 as follows:

The following MLME primitives support the signaling of DMS or GCR request and response procedure. The informative diagram shown in Figure 6-25 depicts the DMS or GCR request and response process and is not meant to be exhaustive of all possible protocol uses.

Change Figure 6-25 as follows:




Figure 6-25—DMS or GCR setup protocol exchange

Change the title of 6.3.67.2 as follows:

6.3.67.2 MLME-DMSGATS.request

6.3.67.2.2 Semantics of the service primitive

Change 6.3.67.2.2 as follows:

The primitive parameters are as follows:

MLME-DMSGATS.request(
 PeerSTAAddress,
 Dialog Token,
 DMSRequest
)

Name	Type	Valid range	Description
PeerSTAAddress	MAC Address	Any valid individual MAC address	Specifies the address of the peer MAC entity with which to perform the DMS <u>or</u> GCR process.
Dialog Token	Integer	1–255	The Dialog Token to identify the DMS <u>or</u> GCR request and response transaction.
DMSRequest	DMS Request element	As defined in 8.4.2.90	Specifies group addressed frames <u>and</u> parameters for the requested DMS <u>or</u> GCR stream.

Change the title of 6.3.67.3 as follows:

6.3.67.3 MLME-~~DMSGATS~~.confirm

6.3.67.3.1 Function

Change 6.3.67.3.1 as follows:

This primitive reports the result of a DMS or GCR procedure.

6.3.67.3.2 Semantics of the service primitive

Change 6.3.67.3.2 as follows:

The primitive parameters are as follows:

```
MLME-DMSGATS.confirm(
    PeerSTAAddress,
    Dialog Token,
    DMSResponse
)
```

Name	Type	Valid range	Description
PeerSTAAddress	MAC Address	Any valid individual MAC address	Specifies the address of the peer MAC entity with which to perform the DMS <u>or</u> GCR process.
Dialog Token	Integer	1–255	The Dialog Token to identify the DMS <u>or</u> GCR request and response transaction.
DMSResponse	DMS Response element	As defined in 8.4.2.91	Specifies the status returned by the AP responding to the STA's requested DMS <u>or</u> GCR stream.

6.3.67.3.3 When generated*Change 6.3.67.3.3 as follows:*

This primitive is generated by the MLME as a result of an MLME-~~DMSGATS~~.request and indicates the results of the request.

This primitive is generated when the MLME-~~DMSGATS~~.request contains invalid parameters, when a timeout or failure occurs, or when the STA receives a DMS Response frame from the AP.

*Change the title of 6.3.67.4 as follows:***6.3.67.4 MLME-~~DMSGATS~~.indication****6.3.67.4.2 Semantics of the service primitive***Change 6.3.67.4.2 as follows:*

The primitive parameters are as follows:

MLME-~~DMSGATS~~.indication(
 PeerSTAAddress,
 DialogToken,
 DMSRequest
)

Name	Type	Valid range	Description
PeerSTAAddress	MACAddress	Any valid individual MAC address	The address of the non-AP STA MAC entity from which a DMS Request frame was received.
DialogToken	Integer	1–255	The Dialog Token to identify the DMS <u>or GCR</u> request and response transaction.
DMSRequest	DMS Request element	As defined in 8.4.2.90	Specifies group addressed frames for the requested DMS <u>or GCR</u> stream.

*Change the title of 6.3.67.5 as follows:***6.3.67.5 MLME-~~DMSGATS~~.response****6.3.67.5.1 Function***Change 6.3.67.5.1 as follows:*

This primitive is generated in response to an MLME-~~DMSGATS~~.indication requesting a DMS Response frame be sent to a non-AP STA.

6.3.67.5.2 Semantics of the service primitive*Change 6.3.67.5.2 as follows:*

The primitive parameters are as follows:

```

MLME-DMSGATS.response(
    PeerSTAAddress,
    DialogToken,
    DMSResponse
)

```

Name	Type	Valid range	Description
PeerSTAAddress	MACAddress	Any valid individual MAC address	The address of the non-AP STA MAC entity from which a DMS Request frame was received.
DialogToken	Integer	1–255	The Dialog Token to identify the DMS <u>or GCR</u> request and response transaction.
DMSResponse	DMS Response element	As defined in 8.4.2.91	Specifies the status returned by the AP responding to the STA's requested DMS <u>or GCR</u> stream.

6.3.67.5.3 When generated*Change 6.3.67.5.3 as follows:*

This primitive is generated by the SME in response to an MLME-~~DMSGATS~~.indication requesting a DMS Response be sent to a non-AP STA.

*Change the title of 6.3.67.6 as follows:***6.3.67.6 MLME-~~DMSGATS~~-TERM.request****6.3.67.6.1 Function***Change 6.3.67.6.1 as follows:*

This primitive requests the transmission of a DMS Response frame to ~~non-AP~~ STAs to terminate a granted DMS or GCR service.

6.3.67.6.2 Semantics of the service primitive*Change 6.3.67.6.2 as follows:*

The primitive parameters are as follows:

```

MLME-DMSGATS-TERM.request(
    PeerSTAAddress,
    DialogToken,
    DMSResponse
)

```

Name	Type	Valid range	Description
PeerSTAAddress	MACAddress	Any valid individual MAC address	The address of the non-AP STA MAC entity from which a DMS Request frame was received.
DialogToken	Integer	0	Set to 0 for an autonomous DMS Response frame.
DMSResponse	DMS Response element	As defined in 8.4.2.91	Specifies the requested DMS <u>or GCR</u> stream that is cancelled by the AP.

6.3.67.6.3 When generated*Change 6.3.67.6.3 as follows:*

This primitive is generated by the SME to terminate DMS or GCR service.

*Change the title of 6.3.67.7 as follows:***6.3.67.7 MLME-~~DMSGATS~~-TERM.indication****6.3.67.7.2 Semantics of the service primitive***Change 6.3.67.7.2 as follows:*

The primitive parameters are as follows:

MLME-~~DMSGATS~~-TERM.indication(
 PeerSTAAddress,
 DialogToken,
 DMSResponse
)

Name	Type	Valid range	Description
PeerSTAAddress	MAC Address	Any valid individual MAC address	Specifies the address of the peer MAC entity with which to perform the DMS <u>or GCR</u> process.
DialogToken	Integer	0	Set to 0 for an autonomous DMS Response frame.
DMSResponse	DMS Response element	As defined in 8.4.2.91	Specifies the requested DMS <u>or GCR</u> stream that is cancelled by the AP.

6.3.72 QoS Map Set element management**6.3.72.2 MLME-QoSMap.request****6.3.72.2.2 Semantics of the service primitive**

Change the primitive parameter list in 6.3.72.2.2 as follows:

MLME-QoSMap.request (

Non-APSTAAddress,
QoSMapSet,
IntraAccessCategoryPriority

)

Insert the following row after the QoSMapSet row of the untitled table in 6.3.72.2.2 (note that entire table is not shown here):

Name	Type	Valid range	Description
IntraAccessCategoryPriority	Intra-Access Category Priority element	As defined in 8.4.2.123	Specifies the intra-AC priorities the STA should use. The parameter is present only if dot11SCSActivated is true.

6.3.72.3 MLME-QoSMap.indication**6.3.72.3.2 Semantics of the service primitive**

Change the primitive parameter list in 6.3.72.3.2 as follows:

MLME-QoSMap.indication (

QoSMapSet,
IntraAccessCategoryPriority

)

Insert the following row after the QoSMapSet row of the untitled table in 6.3.72.3.2 (note that the entire table is not shown here):

Name	Type	Valid range	Description
IntraAccessCategoryPriority	Intra-Access Category Priority element	As defined in 8.4.2.123	Specifies the intra-AC priorities the STA should use.

Insert the following subclauses, 6.3.84 to 6.3.88.3.4 (including Figure 6-25a), after 6.3.83.8.4:

6.3.84 SCS request and response procedure

6.3.84.1 General

The following MLME primitives support the signaling of the SCS request and response procedure. The informative diagram shown in Figure 6-25a depicts the SCS request and response process and is not meant to be exhaustive of all possible protocol uses.




Figure 6-25a—Example SCS setup and termination protocol exchange

6.3.84.2 MLME-SCS.request

6.3.84.2.1 Function

This primitive requests transmission of an SCS Request frame to an AP.

6.3.84.2.2 Semantics of the service primitive

The primitive parameters are as follows:

```

MLME-SCS.request(
    PeerSTAAddress,
    DialogToken,
    SCSRequest
)

```

Name	Type	Valid range	Description
PeerSTAAddress	MAC Address	Any valid individual MAC address	Specifies the address of the peer MAC entity with which to perform the SCS process.
DialogToken	Integer	1–255	The dialog token to identify the SCS request and response transaction.
SCSRequest	SCS Descriptor element	SCS Descriptor element, as defined in 8.4.2.124	Specifies frame classifiers and priority for the requested SCS stream.

6.3.84.2.3 When generated

This primitive is generated by the SME to request that a SCS Request frame be sent to the AP with which the STA is associated.

6.3.84.2.4 Effect of receipt

On receipt of this primitive, the MLME constructs a SCS Request action management frame. The STA then attempts to transmit this frame to the AP with which the STA is associated.

6.3.84.3 MLME-SCS.confirm

6.3.84.3.1 Function

This primitive reports the result of a SCS procedure.

6.3.84.3.2 Semantics of the service primitive

The primitive parameters are as follows:

```
MLME-SCS.confirm(
    ResultCode,
    PeerSTAAddress,
    DialogToken,
    SCSResponse
)
```

Name	Type	Valid range	Description
ResultCode	Enumeration	SUCCESS, DECLINED, TCLAS_PROCESSING_NOT_SUPPORTED, INSUFFICIENT_TCLAS_PROCESSING, TIMEOUT	Reports the outcome of a request to send a SCS Request frame.
PeerSTAAddress	MAC Address	Any valid individual MAC address	Specifies the address of the peer MAC entity with which to perform the SCS process.

Name	Type	Valid range	Description
DialogToken	Integer	1–255	The dialog token to identify the SCS request and response transaction.
SCSResponse	SCS Status duple	SCS Status duple, as defined in 8.5.19.3	Specifies the status returned by the AP responding to the STA's requested SCSID.

6.3.84.3.3 When generated

This primitive is generated by the MLME as a result of an MLME-SCS.request primitive and indicates the results of the request.

This primitive is generated when the MLME-SCS.request primitive contains invalid parameters, when a timeout or failure occurs, or when the STA receives a SCS Response frame from the AP.

6.3.84.3.4 Effect of receipt

On receipt of this primitive, the SME should operate according to the procedure in 10.26.2.

6.3.84.4 MLME-SCS.indication

6.3.84.4.1 Function

This primitive indicates that an SCS Request frame was received from a non-AP STA.

6.3.84.4.2 Semantics of the service primitive

The primitive parameters are as follows:

```
MLME-SCS.indication(
    PeerSTAAddress,
    DialogToken,
    SCSRequest
)
```

Name	Type	Valid range	Description
PeerSTAAddress	MACAddress	Any valid individual MAC address	The address of the non-AP STA MAC entity from which an SCS Request frame was received.
DialogToken	Integer	1–255	The dialog token to identify the SCS request and response transaction.
SCSRequest	SCS Descriptor element	SCS Descriptor element, as defined in 8.4.2.124	Specifies frame classifiers and priority for the requested SCS stream.

6.3.84.4.3 When generated

This primitive is generated by the MLME when a valid SCS Request frame is received.

6.3.84.4.4 Effect of receipt

On receipt of this primitive, the SME should operate according to the procedure in 10.26.2.

6.3.84.5 MLME-SCS.response**6.3.84.5.1 Function**

This primitive is generated in response to an MLME-SCS.indication primitive requesting an SCS Response frame be sent to a non-AP STA.

6.3.84.5.2 Semantics of the service primitive

The primitive parameters are as follows:

```
MLME-SCS.response(
    PeerSTAAddress,
    DialogToken,
    SCSResponse
)
```

Name	Type	Valid range	Description
PeerSTAAddress	MACAddress	Any valid individual MAC address	The address of the non-AP STA MAC entity from which a SCS Request frame was received.
DialogToken	Integer	1–255	The dialog token to identify the SCS request and response transaction.
SCSResponse	SCS Status duple	SCS Status duple, as defined in 8.5.19.3	Specifies the status returned by the AP responding to the STA's requested SCSID.

6.3.84.5.3 When generated

This primitive is generated by the SME in response to an MLME-SCS.indication primitive requesting an SCS Response frame be sent to a non-AP STA.

6.3.84.5.4 Effect of receipt

On receipt of this primitive, the MLME constructs a SCS Response frame. The STA then attempts to transmit this frame to the non-AP STA indicated by the PeerSTAAddress parameter.

6.3.84.6 MLME-SCS-TERM.request**6.3.84.6.1 Function**

This primitive requests the transmission of a SCS Response frame to a non-AP STA to terminate an established SCS stream.

6.3.84.6.2 Semantics of the service primitive

The primitive parameters are as follows:

```
MLME-SCS-TERM.request(
    PeerSTAAddress,
    DialogToken,
    SCSResponse
)
```

Name	Type	Valid range	Description
PeerSTAAddress	MACAddress	Any valid individual MAC address	The address of the non-AP STA MAC entity to which the SCS Response frame is to be sent.
DialogToken	Integer	0	Set to 0 for an autonomous SCS Response frame.
SCSResponse	SCS Status duple	SCS Status duple, as defined in 8.5.19.3	Specifies the requested SCSID that is cancelled by the AP.

6.3.84.6.3 When generated

This primitive is generated by the SME to terminate an SCS stream.

6.3.84.6.4 Effect of receipt

On receipt of this primitive, the MLME constructs an SCS Response frame. The STA then attempts to transmit this frame to the non-AP STA indicated by the PeerSTAAddress parameter.

6.3.84.7 MLME-SCS-TERM.indication**6.3.84.7.1 Function**

This primitive is generated by the MLME when a valid unsolicited SCS Response frame is received.

6.3.84.7.2 Semantics of the service primitive

The primitive parameters are as follows:

```
MLME-SCS-TERM.indication(
    ResultCode,
    DialogToken,
    SCSResponse
)
```

Name	Type	Valid range	Description
ResultCode	Enumeration	SUCCESS, FAILURE	Indicates the result of the MLME-SCS-TERM.request primitive.
DialogToken	Integer	0	Set to 0 for an autonomous SCS Response frame.
SCSResponse	SCS Status duple	SCS Status duple, as defined in 8.5.19.3	Specifies the requested SCSID that is cancelled by the AP.

6.3.84.7.3 When generated

This primitive is generated when the STA receives an unsolicited SCS Response frame from the AP.

6.3.84.7.4 Effect of receipt

On receipt of this primitive, the SME should operate according to the procedure in 10.26.2.

6.3.85 QLoad report management

6.3.85.1 General

The QLoad report management primitives support the process of QLoad reporting between APs as described in 10.27.2.

6.3.85.2 MLME-QLOAD.request

6.3.85.2.1 Function

This primitive is used by an AP to transmit a QLoad Request frame to a specified AP.

6.3.85.2.2 Semantics of the service primitive

The primitive parameters are as follows:

```
MLME-QLOAD.request(
    PeerMACAddress,
    DialogToken,
    Protected
)
```

Name	Type	Valid range	Description
PeerMACAddress	MACAddress	Any valid individual MAC address	The address of the peer MAC entity to which the QLoad Request frame is sent.
DialogToken	Integer	1–255	Specifies a number unique to the MLME-QLOAD.request primitive.
Protected	Boolean	true, false	If true, the request is sent using the Protected QLoad Request frame. If false, the request is sent using the QLoad Request frame.

6.3.85.2.3 When generated

This primitive is generated by the SME at an AP to request the transmission of a QLoad Request frame to the AP indicated by the PeerMACAddress parameter.

6.3.85.2.4 Effect of receipt

On receipt of this primitive, the MLME constructs a QLoad Request action management frame if the Protected parameter is false or a Protected QLoad Request frame if the Protected parameter is true. The AP then attempts to transmit this frame to the AP indicated by the PeerMACAddress parameter.

6.3.85.3 MLME-QLOAD.confirm

6.3.85.3.1 Function

This primitive reports the result of a request to send a QLoad Request frame.

6.3.85.3.2 Semantics of the service primitive

The primitive parameters are as follows:

```
MLME-QLOAD.confirm(
    ResultCode,
    PeerMACAddress,
    DialogToken,
    Protected,
    QLoadReport
)
```

Name	Type	Valid range	Description
ResultCode	Enumeration	SUCCESS, UNSPECIFIED_FAILURE	Reports the outcome of a QLoad request.
PeerMACAddress	MACAddress	Any valid individual MAC address	The address of the peer MAC entity to which the QLoad Request frame was sent.

Name	Type	Valid range	Description
DialogToken	Integer	0–255	Specifies a number unique to the QLoad Report request and response transaction or 0 when an unsolicited report was sent.
Protected	Boolean	true, false	If true, the response was sent using the Protected QLoad Report frame. If false, the response was sent using the QLoad Report frame.
QLoadReport	Set of reports, each as defined in the QLoad Report element	Set of reports, each as defined in the QLoad Report element	Set of reports, each as defined in the QLoad Report element.

6.3.85.3.3 When generated

This primitive is generated by the MLME as a result of an MLME-QLOAD.request primitive indicating the results of that request. This primitive is generated when an MLME-QLOAD.request primitive contains invalid parameters or when the STA receives a response in the form of a QLoad Report frame in the corresponding Robust AV Streaming Action frame.

6.3.85.3.4 Effect of receipt

The SME is notified of the results of the QLoad request procedure.

The SME should operate according to the procedures defined in 10.27.2.

6.3.85.4 MLME-QLOAD.indication

6.3.85.4.1 Function

This primitive indicates that a QLoad Request frame has been received.

6.3.85.4.2 Semantics of the service primitive

The primitive parameters are as follows:

```
MLME-QLOAD.indication(
    PeerMACAddress,
    DialogToken,
    Protected
)
```

Name	Type	Valid range	Description
PeerMACAddress	MACAddress	Any valid individual MAC address	The address of the peer MAC entity from which the QLoad Request frame was received.
DialogToken	Integer	1–255	Specifies a number unique to the MLME-QLOAD.request primitive.
Protected	Boolean	true, false	If true, the request was sent using the Protected QLoad Request frame. If false, the request was sent using the QLoad Request frame.

6.3.85.4.3 When generated

This primitive is generated by the MLME when a valid (Protected) QLoad Request frame is received.

6.3.85.4.4 Effect of receipt

On receipt of this primitive, the SME either rejects the request or commences the transaction as described in 10.27.2.

6.3.85.5 MLME-QLOAD.response

6.3.85.5.1 Function

This primitive is used by an AP to transmit a QLoad Report frame to a specified AP in response to a QLoad Request frame.

6.3.85.5.2 Semantics of the service primitive

The primitive parameters are as follows:

```
MLME-QLOAD.response(  
    PeerMACAddress,  
    DialogToken,  
    Protected,  
    QLoadReport  
)
```

Name	Type	Valid range	Description
PeerMACAddress	MACAddress	Any valid individual MAC address	The address of the peer MAC entity to which the QLoad Report frame is sent.
DialogToken	Integer	0–255	The dialog token of the matching MLME-QLOAD.indication primitive or 0 when sending an unsolicited report.