

INTERNATIONAL
STANDARD

ISO/
IEC/IEEE
8802-1CB

First edition
2019-02

AMENDMENT 1
2023-02

**Information technology —
Telecommunications and information
exchange between systems — Local
and metropolitan area networks —
Specific requirements —**

**Part 1CB:
Frame replication and elimination for
reliability**

**AMENDMENT 1: Information model,
YANG data model, and management
information base module**

*Technologies de l'information — Télécommunications et échange
d'information entre systèmes — Réseaux locaux et métropolitains —
Exigences spécifiques —*

Partie 1CB: Duplication de trame et son élimination pour la fiabilité

*AMENDEMENT 1: Modèle d'information, modèle de données YANG et
module de base d'informations de gestion*



Reference number
ISO/IEC/IEEE 8802-1CB:2019/Amd.1:2023(E)



Documents

Document Sharing Hub
© IEEE 2022

Authorized licensed use limited to: Tsinghua University. Downloaded on February 26, 2026 at 08:08:52 UTC from IEEE Xplore. Restrictions apply.



COPYRIGHT PROTECTED DOCUMENT

© IEEE 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from IEEE at the address below.

Institute of Electrical and Electronics Engineers, Inc
3 Park Avenue, New York
NY 10016-5997, USA

Email: stds.ipr@ieee.org
Website: www.ieee.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO/IEC documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see <https://patents.iec.ch>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

ISO/IEC/IEEE 8802-1CB:2019/Amd1 was prepared by the LAN/MAN of the IEEE Computer Society (as IEEE 802-1CBv™-2021) and drafted in accordance with its editorial rules. It was adopted, under the “fast-track procedure” defined in the Partner Standards Development Organization cooperation agreement between ISO and IEEE, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*.

A list of all parts in the ISO/IEC/IEEE 8802 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

**IEEE Standard for
Local and metropolitan area networks—**

Frame Replication and Elimination for Reliability

**Amendment 1: Information Model, YANG Data
Model, and Management Information Base Module**

Developed by the
LAN/MAN Standards Committee
of the
IEEE Computer Society

Approved 8 December 2021
IEEE SA Standards Board

Abstract: This amendment specifies YANG data models and MIB modules that allow configuration and status reporting for bridges and end systems with the capabilities for Frame Replication and Elimination for Reliability (FRER) and Stream identification.

Keywords: Bridged Local Area Networks, Bridges, Bridging, Frame Elimination, Frame Replication, IEEE 802[®], IEEE 802.1CB[™], IEEE 802.1Q[™], local area networks (LANs), MAC Bridges, Redundancy, Time-Sensitive Networking, TSN, Virtual Bridged Local Area Networks (virtual LANs)

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2022 by The Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 18 February 2022. Printed in the United States of America.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-1-5044-8245-5 STD25138
Print: ISBN 978-1-5044-8246-2 STDPD25138

IEEE prohibits discrimination, harassment and bullying.

For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE Standards documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page (<https://standards.ieee.org/ipr/disclaimers.html>), appear in all standards and may be found under the heading “Important Notices and Disclaimers Concerning IEEE Standards Documents.”

Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE SA) Standards Board. IEEE develops its standards through an accredited consensus development process, which brings together volunteers representing varied viewpoints and interests to achieve the final product. IEEE Standards are documents developed by volunteers with scientific, academic, and industry-based expertise in technical working groups. Volunteers are not necessarily members of IEEE or IEEE SA, and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE makes no warranties or representations concerning its standards, and expressly disclaims all warranties, express or implied, concerning this standard, including but not limited to the warranties of merchantability, fitness for a particular purpose and non-infringement. In addition, IEEE does not warrant or represent that the use of the material contained in its standards is free from patent infringement. IEEE standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity, nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: THE NEED TO PROCURE SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE is the approved IEEE standard.

Official statements

A statement, written or oral, that is not processed in accordance with the IEEE SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, nor be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that the presenter's views should be considered the personal views of that individual rather than the formal position of IEEE, IEEE SA, the Standards Committee, or the Working Group.

Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE or IEEE SA. However, **IEEE does not provide interpretations, consulting information, or advice pertaining to IEEE Standards documents.**

Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its Societies and Standards Coordinating Committees are not able to provide an instant response to comments, or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in evaluating comments or in revisions to an IEEE standard is welcome to join the relevant IEEE working group. You can indicate interest in a working group using the Interests tab in the Manage Profile & Interests area of the [IEEE SA myProject system](#).¹ An IEEE Account is needed to access the application.

Comments on standards should be submitted using the [Contact Us](#) form.²

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not constitute compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Data privacy

Users of IEEE Standards documents should evaluate the standards for considerations of data privacy and data ownership in the context of assessing and using the standards in compliance with applicable laws and regulations.

1. Available at: <https://development.standards.ieee.org/myproject-web/public/view.html#landing>.

2. Available at: <https://standards.ieee.org/content/ieee-standards/en/about/contact/index.html>.

Copyrights

IEEE draft and approved standards are copyrighted by IEEE under US and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

Photocopies

Subject to payment of the appropriate licensing fees, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400; <https://www.copyright.com/>. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every 10 years. When a document is more than 10 years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit [IEEE Xplore](#) or [contact IEEE](#).³ For more information about the IEEE SA or IEEE's standards development process, visit the IEEE SA Website.

Errata

Errata, if any, for all IEEE standards can be accessed on the [IEEE SA Website](#).⁴ Search for standard number and year of approval to access the web page of the published standard. Errata links are located under the Additional Resources Details section. Errata are also available in [IEEE Xplore](#). Users are encouraged to periodically check for errata.

Patents

IEEE Standards are developed in compliance with the [IEEE SA Patent Policy](#).⁵

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has

3. Available at: <https://ieeexplore.ieee.org/browse/standards/collection/ieee>.

4. Available at: <https://standards.ieee.org/standard/index.html>.

5. Available at: <https://standards.ieee.org/about/sasb/patcom/materials.html>.

filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE SA Website at <https://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

IMPORTANT NOTICE

IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. IEEE Standards development activities consider research and information presented to the standards development group in developing any safety recommendations. Other information about safety practices, changes in technology or technology implementation, or impact by peripheral systems also may be pertinent to safety considerations during implementation of the standard. Implementers and users of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

Participants

At the time this amendment was submitted to the IEEE SA Standards Board for approval, the IEEE 802.1 Working Group had the following membership:

Glenn Parsons, *Chair*
Jessy Rouyer, *Vice-Chair*
János Farkas, *Chair, Time-Sensitive Networking Task Group*
Stephan Kehrner, *Editor*

Astrit Ademaj	Woojung Huh	Maximilian Riegel
Ralf Assmann	Satoko Itaya	Silvana Rodrigues
Rudy Belliardi	Yoshihiro Ito	Atsushi Sato
Christian Boiger	Michael Karl	Frank Schewe
Paul Bottorff	Randy Kelsey	Michael Seaman
Radhakrishna Canchi	Marcel Kiessling	Maik Seewald
David Chen	Gavin Lai	Ramesh Sivakolundu
Feng Chen	James Lawlis	Johannes Specht
Paul Congdon	Joao Lopes	Marius Stanica
Rodney Cummings	Lily Lv	Gunter Steindl
Josef Dorr	Christophe Mangin	Liyang Sun
Hesham Elbakoury	Scott Mansfield	Karim Traore
Anna Engelmann	Kenichi Maruhashi	Max Turner
Thomas Enzinger	Olaf Mater	Balazs Varga
Donald Fedyk	David McCall	Ganesh Venkatesan
Norman Finn	Larry McMillan	Tongtong Wang
Geoffrey Garner	John Messenger	Xinyuan Wang
Amrit Gopal	Hiroki Nakano	Karl Weber
Craig Gunther	Bob Noseworthy	Ludwig Winkel
Marina Gutierrez	Hiroshi Ohue	Jordon Woods
Stephen Haddock	Donald R. Pannell	Takahiro Yamaura
Mark Hantel	Michael Potts	Yue Yin
Jerome Henry	Dieter Proell	Nader Zein
Marc Holness	Wei Qiu	William Zhao
Daniel Hopf	Karen Randall	Helge Zinner

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Thomas Alexander	Stephan Kehrner	Alon Regev
Christian Boiger	Randy Kelsey	Maximilian Riegel
Vern Brethour	Stuart Kerry	Jessy Rouyer
William Byrd	Evgeny Khorov	Frank Schewe
Paul Cardinal	Yongbum Kim	Michael Seaman
Pin Chang	Hyeong Ho Lee	Maik Seewald
Diego Chiozzi	Ting Li	Eugene Stoudenmire
Janos Farkas	Christophe Mangin	Walter Struppler
Avraham Freedman	Scott Mansfield	Mitsutoshi Sugawara
Stephen Haddock	Jonathon McLendon	Bo Sun
Marco Hernandez	Satoshi Obara	David Tremblay
Werner Hoelzl	Glenn Parsons	Max Turner
Oliver Holland	Bansi Patel	John Vergis
Marc Holness	Arumugam Paventhan	Stephen Webb
Pranav Jha	Clinton Powell	Karl Weber
Lokesh Kabra	Dieter Proell	Scott Willy
Piotr Karocki	R. K. Rannow	Yu Yuan
		Oren Yuen

When the IEEE SA Standards Board approved this standard on 8 December 2021, it had the following membership:

Gary Hoffman, *Chair*
Jon Walter Rosdahl, *Vice Chair*
John D. Kulick, *Past Chair*
Konstantinos Karachalios, *Secretary*

Edward A. Addy
Doug Edwards
Ramy Ahmed Fathy
J. Travis Griffith
Thomas Koshy
Joseph L. Koepfinger*
David J. Law

Howard Li
Daozhuang Lin
Kevin Lu
Daleep C. Mohla
Chenhui Niu
Damir Novosel
Annette Reilly
Dorothy Stanley

Mehmet Ulema
Lei Wang
F. Keith Waters
Karl Weber
Sha Wei
Howard Wolfman
Daidi Zhong

*Member Emeritus

Introduction

This introduction is not part of IEEE Std 802.1CBcv-2021, IEEE Standard for Local and metropolitan area networks—Frame Replication and Elimination for Reliability—Amendment 1: Information Model, YANG Data Model, and Management Information Base Module.

This Standard defines an Information Model, a YANG Data Model, and a Management Information Base Module.

This standard contains state-of-the-art material. The area covered by this standard is undergoing evolution. Revisions are anticipated within the next few years to clarify existing material, to correct possible errors, and to incorporate new related material. Information on the current revision state of this and other IEEE 802 standards can be obtained from

Secretary, IEEE SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854
USA

Contents

1.	Overview.....	13
1.6	Introduction.....	13
2.	Normative references	14
4.	Acronyms and abbreviations	15
5.	Conformance.....	16
5.8	Talker end system optional behaviors	16
5.11	Listener end system optional behaviors.....	16
5.14	Relay system optional behaviors	16
7.	Frame Replication and Elimination for Reliability.....	17
7.4	Sequencing function	17
7.4.1	Sequence generation function.....	17
7.4.1.3	SequenceGenerationReset.....	17
10.	Frame Replication and Elimination for Reliability management	18
10.3	Sequence generation table	18
10.3.1	frerSeqGenEntry	18
10.3.1.3	frerSeqGenReset	18
11.	Management Information Base (MIB)	19
11.1	Internet Standard Management Framework	19
11.2	Structure of the MIB	19
11.2.1	Structure of the IEEE8021-STREAM-IDENTIFICATION-MIB	21
11.2.2	Structure of the IEEE8021-FRER-MIB.....	23
11.3	Relationship to other MIBs.....	27
11.3.1	Relationship of the IEEE8021-STREAM-IDENTIFICATION-MIB to other MIBs ..	27
11.3.2	Relationship of the IEEE8021-FRER-MIB to other MIBs.....	28
11.4	Security considerations	28
11.4.1	Security considerations of the IEEE8021-STREAM-IDENTIFICATION-MIB	28
11.4.2	Security considerations of the IEEE8021-FRER-MIB	28
11.5	MIB modules	29
11.5.1	Definitions for the IEEE8021-STREAM-IDENTIFICATION-MIB	29
11.5.2	Definitions for the IEEE8021-FRER-MIB	50
12.	YANG Data Model.....	87
12.1	YANG Framework	87
12.2	IEEE Std 802.1CB YANG model.....	88
12.2.1	Stream Identification model.....	88
12.2.2	Frame Replication and Elimination for Reliability model.....	90
12.3	Structure of the YANG model.....	93
12.3.1	Structure of the ieee802-dot1cb-stream-identification YANG module.....	94
12.3.2	Structure of the ieee802-dot1cb-frer YANG module	95
12.4	Relationship to other YANG modules.....	96
12.4.1	IEEE 802 Types Module.....	96
12.4.2	IEEE 802.1Q Types Module.....	96
12.4.3	IETF Inet Types Module.....	96
12.4.4	IETF Interfaces YANG Module	96

12.4.5	IEEE 802.1CB Stream Identification Types YANG module	96
12.4.6	IEEE 802.1CB Stream Identification YANG module	96
12.4.7	IEEE 802.1CB FRER Types YANG module	96
12.5	Security Considerations	97
12.5.1	Security Considerations of the ieee802-dot1cb-stream-identification YANG module	97
12.5.2	Security Considerations of the ieee802-dot1cb-frer YANG module.....	97
12.6	Definition of 802.1CB YANG modules	97
12.6.1	YANG data scheme tree definitions	97
12.6.1.1	YANG data scheme definition for ieee802-dot1cb-stream-identification YANG module	98
12.6.1.2	YANG data scheme definition for ieee802-dot1cb-frer YANG module	99
12.6.2	YANG data module definitions.....	103
12.6.2.1	Definition for the ieee802-dot1cb-stream-identification-types YANG module	103
12.6.2.2	Definition for the ieee802-dot1cb-stream-identification YANG module.....	105
12.6.2.3	Definition for the ieee802-dot1cb-frer-types YANG module.....	123
12.6.2.4	Definition for the ieee802-dot1cb-frer YANG module	125
Annex A (normative)	Protocol Implementation Conformance Statement (PICS) proforma.....	153
A.2	PICS proforma for Frame Replication and Elimination for Reliability.....	153
A.2.1	Major capabilities/options.....	153
A.2.8	Management Information Base (MIB)	153
A.2.9	YANG.....	154
Annex D (informative)	Bibliography	155

IEEE Standard for
Local and metropolitan area networks—
Frame Replication and Elimination for Reliability
Amendment 1: Information Model, YANG Data
Model, and Management Information Base Module

(This amendment is based on IEEE Std 802.1CB™-2017.)

NOTE—The editing instructions contained in this amendment define how to merge the material contained therein into the existing base standard and its amendments to form the comprehensive standard.

The editing instructions are shown in ***bold italic***. Four editing instructions are used: change, delete, insert, and replace. ***Change*** is used to make corrections in existing text or tables. The editing instruction specifies the location of the change and describes what is being changed by using ~~striketrough~~ (to remove old material) and underscore (to add new material). ***Delete*** removes existing material. ***Insert*** adds new material without disturbing the existing material. Deletions and insertions may require renumbering. If so, renumbering instructions are given in the editing instruction. ***Replace*** is used to make changes in figures or equations by removing the existing figure or equation and replacing it with a new one. Editing instructions, change markings, and this NOTE will not be carried over into future editions because the changes will be incorporated into the base standard.⁶

⁶ Notes in text, tables, and figures are given for information only and do not contain requirements needed to implement the standard.

1. Overview

1.6 Introduction

Insert new text at the end of 1.6 as follows:

This standard also specifies a Unified Modeling Language (UML) based information model for the capabilities currently specified in Clause 9 and Clause 10 of this standard. A YANG data model and a Management Information Base (MIB) module, both based on that UML model, are provided in order to support configuration and status reporting.

2. Normative references

Insert the following references in alphanumeric order in Clause 2:

IETF RFC 2578 (STD 58), Structure of Management Information Version 2 (SMIv2), McCloghrie, K., D. Perkins, and J. Schoenwaelder, Apr. 1999.⁷

IETF RFC 2579 (STD 58), Textual Conventions for SMIv2, McCloghrie, K., D. Perkins, and J. Schoenwaelder, Apr. 1999.

IETF RFC 2580 (STD 58), Conformance Statements for SMIv2, McCloghrie, K., D. Perkins, and J. Schoenwaelder, Apr. 1999.

IETF RFC 3410, Introduction and Applicability Statements for Internet-Standard Management Framework, Case, J., R. Mundy, D. Partain, and B. Stewart, Dec. 2002.

IETF RFC 8343 (proposed standard), A YANG Data Model for Interface Management, Bjorklund, M., Mar. 2018.

⁷ IETF RFCs are available from the Internet Engineering Task Force (<https://www.rfc-archive.org/>).

4. Acronyms and abbreviations

Insert the following abbreviations in alphanumeric order in Clause 4:

MIB	Management Information Base
NETCONF	Network Configuration Protocol
SMI	Structure of Management Information
SNMP	Simple Network Management Protocol
YANG	Yet Another Next Generation ⁸
UML	Unified Modeling Language

⁸ YANG is best viewed as a name, not an acronym

5. Conformance

5.8 Talker end system optional behaviors

Change list items f) and g) in 5.8 as follows:

- f) The PRP sequence trailer (7.10); ~~and/or~~
- g) Additional types of Sequence encode/decode functions; ~~;~~
- h) [Support SMIPv2 MIB modules for the management of talker end system functions \(Clause 11\) as required by item e in 5.6; and/or](#)
- i) [Support YANG modules for the management of talker end system functions \(Clause 12\) as required by item e in 5.6.](#)

5.11 Listener end system optional behaviors

Change list items g) and h) in 5.11 as follows:

- g) Additional types of Sequence encode/decode functions; ~~and/or~~
- h) At least two instances of Individual recovery functions (7.5), each using the VectorRecoveryAlgorithm (7.4.3.4); ~~;~~
- i) [Support SMIPv2 MIB modules for the management of listener end system functions \(Clause 11\) as required by item f in 5.9; and/or](#)
- j) [Support YANG modules for the management of listener end system functions \(Clause 12\) as required by item f in 5.9.](#)

5.14 Relay system optional behaviors

Change list items g) to j) in 5.14 as follows:

- g) Additional types of Sequence encode/decode functions; ~~and/or~~
- h) Some or all of the functions in 5.12 or 5.13 as both in- and out-facing functions; ~~;~~
- i) At least two instances of Individual recovery functions (7.5), each using the VectorRecoveryAlgorithm (7.4.3.4); ~~;~~
- j) Autoconfiguration (7.11) and the associated managed objects (10.7); ~~;~~
- k) [Support SMIPv2 MIB modules for the management of relay systems functions \(Clause 11\) as required by item g in 5.12; and/or](#)
- l) [Support YANG modules for the management of relay systems functions \(Clause 12\) as required by item g in 5.12.](#)

7. Frame Replication and Elimination for Reliability

7.4 Sequencing function

7.4.1 Sequence generation function

7.4.1.3 SequenceGenerationReset

Change 7.4.1.3 as follows:

The SequenceGenerationReset function is called whenever the BEGIN event occurs (item a in 7.4.1.1) or the value True is written to the ~~frerSeqRevReset~~[frerSeqGenReset](#) managed object (~~10.4.1.4~~[10.3.1.3](#)). It resets GenSeqNum (7.4.1.2.2) and increments frerCpsSeqGenResets (10.8.2).

```
void SequenceGenerationReset () {
    GenSeqNum = 0;
    frerCpsSeqGenResets = frerCpsSeqGenResets + 1;
}
```

10. Frame Replication and Elimination for Reliability management

10.3 Sequence generation table

10.3.1 frerSeqGenEntry

Insert subclause 10.3.1.3 after 10.3.1.2, as follows:

10.3.1.3 frerSeqGenReset

A Boolean object indicating that the Sequence generation function (7.4.1) is to be reset by calling its corresponding SequenceGenerationReset function (7.4.1.3). Writing the value True to frerSeqGenReset triggers a reset; writing the value False has no effect. When read, frerSeqGenReset always returns the value False.

Insert Clause 11 and Clause 12 after Clause 10 as follows:

11. Management Information Base (MIB)

This clause contains a complete SMIV2 MIB set for all features of this standard.

11.1 Internet Standard Management Framework

The MIBs in this standard are designed to operate in a manner consistent with the principles of the Internet Standard Management Framework, which describes the separation of a data modeling language (for example, SMIV2) from content-specific data models (for example, the LLDP remote systems MIB), and from messages and protocol operations used to manipulate the data (for example, SNMPv3).

For a detailed overview of the documents that describe the current Internet Standard Management Framework, please refer to section 7 of IETF RFC 3410 (2002).

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This clause specifies a MIB module that is compliant to the SMIV2, which is described in IETF RFC 2578 (STD 58), IETF RFC 2579 (STD 58), and IETF RFC 2580 (STD 58).

11.2 Structure of the MIB

The IEEE Std 802.1CB MIB is divided into a number of MIB modules. A summary of the modules contained in this clause is represented in Table 11-1. The general MIB table structures for the MIB modules contained in this clause are illustrated in Figure 11-1.

Table 11-1—Structure of the MIB modules

Module	Subclause	References	Notes
IEEE8021-STREAM-IDENTIFICATION-MIB	11.5.1	Clause 9	MIB model for Stream identification.
IEEE8021-FRER-MIB	11.5.2	Clause 10	MIB model for FRER.




Figure 11-1—MIB modules structure

11.2.1 Structure of the IEEE8021-STREAM-IDENTIFICATION-MIB

The IEEE8021-STREAM-IDENTIFICATION-MIB module is divided into a number of branches (e.g., subtrees). Each subtree is organized as a set of related objects. Where appropriate, the corresponding Clause 9 management reference is also included.

Table 11-2 indicates the structure of the IEEE8021-STREAM-IDENTIFICATION-MIB module.

Table 11-2—IEEE8021-STREAM-IDENTIFICATION-MIB structure and relationship to this standard

Clause 11 MIB table/object	Reference
ieee8021StreamIdStreamIdentificationTable	9.1, 9.1.1
ieee8021StreamIdStreamIdentificationIndex	—
ieee8021StreamIdStreamIdIdentificationType	—
ieee8021StreamIdStreamIdIdentificationTypeOUI	—
ieee8021StreamIdStreamIdIdentificationCustomType	—
ieee8021StreamIdStreamIdIdentificationCustomTypeOUI	—
ieee8021StreamIdStreamIdIdentificationTypeSelect	—
ieee8021StreamIdStreamIdIdentificationTypeSelect	—
ieee8021StreamIdStreamIdInFacOutputPortList	—
ieee8021StreamIdStreamIdOutFacOutputPortList	—
ieee8021StreamIdStreamIdInFacInputPortList	—
ieee8021StreamIdStreamIdOutFacInputPortList	—
ieee8021StreamIdAutoConfigured	—
ieee8021StreamIdLanPathId	—
ieee8021StreamIdStatus	—
ieee8021StreamIdNullStreamIdentificationTable	9.1.2
ieee8021StreamIdCpeNullDownDestMac	—
ieee8021StreamIdCPENullDownTagged	—
ieee8021StreamIdCpeNullDownVlan	—
ieee8021StreamIdSrcMacVlanIdentificationTable	9.1.3
ieee8021StreamIdCpeSmacVlanDownSrcMac	—
ieee8021StreamIdCpeSmacVlanDownTagged	—
ieee8021StreamIdCpeSmacVlanDownVlan	—
ieee8021StreamIdActiveDestMacVlanIdentificationTable	9.1.4
ieee8021StreamIdCpeDmacVlanDownDestMac	—
ieee8021StreamIdCpeDmacVlanDownTagged	—

Table 11-2—IEEE8021-STREAM-IDENTIFICATION-MIB structure and relationship to this standard (*continued*)

Clause 11 MIB table/object	Reference
ieee8021StreamIdCpeDmacVlanDownVlan	—
ieee8021StreamIdCpeDmacVlanDownPriority	—
ieee8021StreamIdCpeDmacVlanUpDestMac	—
ieee8021StreamIdCpeDmacVlanUpTagged	—
ieee8021StreamIdCpeDmacVlanUpVlan	—
ieee8021StreamIdCpeDmacVlanUpPriority	—
ieee8021StreamIdIpStreamIdentificationTable	9.1.5
ieee8021StreamIdCpeIpIdDestMac	—
ieee8021StreamIdCpeIpIdTagged	—
ieee8021StreamIdCpeIpIdVlan	—
ieee8021StreamIdCpeIpIdIpSourceType	—
ieee8021StreamIdCpeIpIdIpSource	—
ieee8021StreamIdCpeIpIdIpDestinationType	—
ieee8021StreamIdCpeIpIdIpDestination	—
ieee8021StreamIdCpeIpIdDscp	—
ieee8021StreamIdCpeIpIdNextProtocol	—
ieee8021StreamIdCpeIpIdSourcePort	—
ieee8021StreamIdCpeIpIdDestinationPort	—
ieee8021StreamIdStreamIdInFacOutputPortHandleListTable	9.1.1.2
ieee8021StreamIdStreamIdInFacOutputPortHandleListIndex	—
ieee8021StreamIdStreamIdInFacOutputPortHandle	—
ieee8021StreamIdStreamIdInFacOutputPortHandleListStatus	—
ieee8021StreamIdStreamIdOutFacOutputPortHandleListTable	9.1.1.3
ieee8021StreamIdStreamIdOutFacOutputPortHandleListIndex	—
ieee8021StreamIdStreamIdOutFacOutputPortHandle	—
ieee8021StreamIdStreamIdOutFacOutputPortHandleListStatus	—
ieee8021StreamIdStreamIdInFacInputPortHandleListTable	9.1.1.2
ieee8021StreamIdStreamIdInFacInputPortHandleListIndex	—
ieee8021StreamIdStreamIdInFacInputPortHandle	—
ieee8021StreamIdStreamIdInFacInputPortHandleListStatus	—
ieee8021StreamIdStreamIdOutFacInputPortHandleListTable	9.1.1.5

Table 11-2—IEEE8021-STREAM-IDENTIFICATION-MIB structure and relationship to this standard (continued)

Clause 11 MIB table/object	Reference
ieee8021StreamIdStreamIdOutFacInputPortHandleListIndex	—
ieee8021StreamIdStreamIdOutFacInputPortHandle	—
ieee8021StreamIdStreamIdOutFacInputPortHandleListStatus	—
ieee8021StreamIdPerPortPerStreamCountersTable	9.2
ieee8021StreamIdPerPortPerStreamDirection	—
ieee8021StreamIdPerPortPerStreamInputPackets	—
ieee8021StreamIdPerPortPerStreamOutputPackets	—
ieee8021StreamIdPerPortCountersTable	9.3
ieee8021StreamIdPerPortInputPackets	—
ieee8021StreamIdPerPortOutputPackets	—

11.2.2 Structure of the IEEE8021-FRER-MIB

The IEEE8021-FRER-MIB module is divided into a number of branches (e.g., subtrees). Each subtree is organized as a set of related objects. Where appropriate, the corresponding Clause 9 management reference is also included.

Table 11-3 indicates the structure of the IEEE8021-FRER-MIB module.

Table 11-3—IEEE8021-FRER-MIB structure and relationship to this standard

Clause 11 MIB table/object	Reference
ieee8021FrerSequenceGenerationTable	10.3
ieee8021FrerSequenceGenerationIndex	—
ieee8021FrerSequenceGenerationStreamList	—
ieee8021FrerSequenceGenerationDirection	—
ieee8021FrerSequenceGenerationReset	—
ieee8021FrerSequenceGenerationHandleListTable	10.3.1.1
ieee8021FrerSequenceGenerationHandleListIndex	—
ieee8021FrerSequenceGenerationStreamHandle	—
ieee8021FrerSequenceGenerationHandleListStatus	—
ieee8021FrerSequenceRecoveryTable	10.4
ieee8021FrerSequenceRecoveryIndex	—
ieee8021FrerSequenceRecoveryStreamList	—
ieee8021FrerSequenceRecoveryPortList	—

Table 11-3—IEEE8021-FRER-MIB structure and relationship to this standard (continued)

Clause 11 MIB table/object	Reference
ieee8021FrerSequenceRecoveryDirection	—
ieee8021FrerSequenceRecoveryReset	—
ieee8021FrerSequenceRecoveryAlgorithm	—
ieee8021FrerSequenceRecoveryAlgorithmOUI	—
ieee8021FrerSequenceCustomRecoveryAlgorithm	—
ieee8021FrerSequenceCustomRecoveryAlgorithmOUI	—
ieee8021FrerSequenceRecoveryHistoryLength	—
ieee8021FrerSequenceRecoveryResetMSec	—
ieee8021FrerSequenceRecoveryInvalidSequenceValue	—
ieee8021FrerSequenceRecoveryTakeNoSequence	—
ieee8021FrerSequenceRecoveryIndividualRecovery	—
ieee8021FrerSequenceRecoveryLatentErrorDetection	—
ieee8021FrerSequenceRecoveryLatentErrorDifference	—
ieee8021FrerSequenceRecoveryLatentErrorPeriod	—
ieee8021FrerSequenceRecoveryLatentErrorPaths	—
ieee8021FrerSequenceRecoveryLatentResetPeriod	—
ieee8021FrerSequenceRecoveryStatus	—
ieee8021FrerSequenceRecoveryHandleListTable	10.4.1.1
ieee8021FrerSequenceRecoveryHandleListIndex	—
ieee8021FrerSequenceRecoveryStreamHandle	—
ieee8021FrerSequenceRecoveryHandleListStatus	—
ieee8021FrerSequenceRecoveryPortHandleListTable	10.4.1.2
ieee8021FrerSequenceRecoveryPortHandleListIndex	—
ieee8021FrerSequenceRecoveryPortHandle	—
ieee8021FrerSequenceRecoveryPortHandleListStatus	—
ieee8021FrerSequenceIdentificationTable	10.5
ieee8021FrerSequenceIdentificationEncodePort	—
ieee8021FrerSequenceIdentificationEncodeDirection	—
ieee8021FrerSequenceIdentificationStreamList	—
ieee8021FrerSequenceIdentificationEncodeActive	—
ieee8021FrerSequenceIdentificationEncodeEncapsulationType	—
ieee8021FrerSequenceIdentificationEncodeEncapsulationOUI	—
ieee8021FrerSequenceIdentificationCustomEncodeEncapsulationType	—

Table 11-3—IEEE8021-FRER-MIB structure and relationship to this standard (*continued*)

Clause 11 MIB table/object	Reference
ieee8021FrerSequenceIdentificationCustomEncodeEncapsulationOUI	—
ieee8021FrerSequenceIdentificationEncodePathIdLanId	—
ieee8021FrerSequenceIdentificationStatus	—
ieee8021FrerSequenceIdentificationHandleListTable	10.5.1.1
ieee8021FrerSequenceIdentificationHandleListIndex	—
ieee8021FrerSequenceIdentificationStreamHandle	—
ieee8021FrerSequenceIdentificationHandleListStatus	—
ieee8021FrerStreamSplitTable	10.6
ieee8021FrerStreamSplitIndex	—
ieee8021FrerStreamSplitPort	—
ieee8021FrerStreamSplitDirection	—
ieee8021FrerStreamSplitInputIdList	—
ieee8021FrerStreamSplitOutputIdList	—
ieee8021FrerStreamSplitInputHandleListTable	10.6.1.3
ieee8021FrerStreamSplitInputHandleListIndex	—
ieee8021FrerStreamSplitInputIdHandle	—
ieee8021FrerStreamSplitInputHandleListStatus	—
ieee8021FrerStreamSplitOutputHandleListTable	10.6.1.4
ieee8021FrerStreamSplitOutputHandleListIndex	—
ieee8021FrerStreamSplitOutputIdHandle	—
ieee8021FrerStreamSplitOutputHandleListStatus	—
ieee8021FrerSequenceAutoconfigTable	10.7, 10.7.1
ieee8021FrerSequenceAutoconfigIndex	—
ieee8021FrerSequenceAutoconfigSequenceEncapsulation	—
ieee8021FrerSequenceAutoconfigSequenceEncapsulationOUI	—
ieee8021FrerSequenceAutoconfigCustomSequenceEncapsulation	—
ieee8021FrerSequenceAutoconfigCustomSequenceEncOUI	—
ieee8021FrerSequenceAutoconfigReceivePortList	—
ieee8021FrerSequenceAutoconfigTagged	—
ieee8021FrerSequenceAutoconfigVlanList	—
ieee8021FrerSequenceAutoconfigRecoveryPortList	—
ieee8021FrerSequenceAutoconfigDestructMSec	—

Table 11-3—IEEE8021-FRER-MIB structure and relationship to this standard (continued)

Clause 11 MIB table/object	Reference
ieee8021FrerSequenceAutoconfigResetMSec	—
ieee8021FrerSequenceAutoconfigAlgorithm	—
ieee8021FrerSequenceAutoconfigAlgorithmOUI	—
ieee8021FrerSequenceAutoconfigCustomAlgorithm	—
ieee8021FrerSequenceAutoconfigCustomAlgorithmOUI	—
ieee8021FrerSequenceAutoconfigHistoryLength	—
ieee8021FrerSequenceAutoconfigCreateIndividual	—
ieee8021FrerSequenceAutoconfigCreateRecovery	—
ieee8021FrerSequenceAutoconfigLatentErrorDetection	—
ieee8021FrerSequenceAutoconfigLatentErrorDifference	—
ieee8021FrerSequenceAutoconfigLatentErrorPeriod	—
ieee8021FrerSequenceAutoconfigLatentErrorResetPeriod	—
ieee8021FrerSequenceAutoconfigStatus	—
ieee8021FrerSequenceAutoconfigReceivePortHandleListTable	10.7.1.1.2
ieee8021FrerSequenceAutoconfigReceivePortHandleListIndex	—
ieee8021FrerSequenceAutoconfigReceivePortHandle	—
ieee8021FrerSequenceAutoconfigReceivePortHandleListStatus	—
ieee8021FrerSequenceAutoconfigVlanListTable	10.7.1.1.4
ieee8021FrerSequenceAutoconfigVlanListIndex	—
ieee8021FrerSequenceAutoconfigVlan	—
ieee8021FrerSequenceAutoconfigVlanListStatus	—
ieee8021FrerSequenceAutoconfigRecoveryPortHandleListTable	10.7.1.1.5
ieee8021FrerSequenceAutoconfigRecoveryPortHandleListIndex	—
ieee8021FrerSequenceAutoconfigRecoveryPortHandle	—
ieee8021FrerSequenceAutoconfigRecoveryPortHandleListStatus	—
ieee8021FrerOutputAutoconfigTable	10.7, 10.7.2
ieee8021FrerOutputAutoconfigIndex	—
ieee8021FrerOutputAutoconfigPortList	—
ieee8021FrerOutputAutoconfigEncapsulation	—
ieee8021FrerOutputAutoconfigEncapsulationOUI	—
ieee8021FrerOutputAutoconfigCustomEncapsulation	—
ieee8021FrerOutputAutoconfigCustomEncapsulationOUI	—

Table 11-3—IEEE8021-FRER-MIB structure and relationship to this standard (continued)

Clause 11 MIB table/object	Reference
ieee8021FrerOutputAutoconfigLanPathId	—
ieee8021FrerOutputAutoconfigStatus	—
ieee8021FrerOutputAutoconfigPortHandleListTable	10.7.2.1.1
ieee8021FrerOutputAutoconfigPortHandleListIndex	—
ieee8021FrerOutputAutoconfigPortHandle	—
ieee8021FrerOutputAutoconfigPortHandleListStatus	—
ieee8021FrerPerPortPerStreamCountersTable	10.8
ieee8021FrerPerPortPerStreamDirection	—
ieee8021FrerPerPortPerStreamSeqGenResets	—
ieee8021FrerPerPortPerStreamSeqRecoveryOutOfOrderPackets	—
ieee8021FrerPerPortPerStreamSeqRecoveryRoguePackets	—
ieee8021FrerPerPortPerStreamSeqRecoveryPassedPackets	—
ieee8021FrerPerPortPerStreamSeqRecoveryDiscardedPackets	—
ieee8021FrerPerPortPerStreamSeqRecoveryLostPackets	—
ieee8021FrerPerPortPerStreamSeqRecoveryTaglessPackets	—
ieee8021FrerPerPortPerStreamSeqRecoveryResets	—
ieee8021FrerPerPortPerStreamSeqRecoveryLatentErrorResets	—
ieee8021FrerPerPortPerStreamSeqEncErroredPackets	—
ieee8021FrerPerPortCountersTable	10.9
ieee8021FrerPerPortSeqRecoveryPassedPackets	—
ieee8021FrerPerPortfrerCpSeqRecoveryDiscardPackets	—
ieee8021FrerPerPortfrerCpSeqEncErroredPackets	—

11.3 Relationship to other MIBs

In order to facilitate interoperable management of the features defined in this standard by remote means, 11.5 contains a complete set of SMIV2 MIB modules. This subclause describes how the MIB modules defined in this standard are related to the MIB modules that are imported.

11.3.1 Relationship of the IEEE8021-STREAM-IDENTIFICATION-MIB to other MIBs

The IEEE8021-STREAM-IDENTIFICATION-MIB identifies the interfaces for the counters provided by this standard by an ifIndex and therefore imports from the IF-MIB.

It also imports items from the SNMPv2-SMI, SNMPv2-TC, INET-ADDRESS-MIB, and IEEE8021-TC-MIB and requires SNMPv2-CONF for conformance.

11.3.2 Relationship of the IEEE8021-FRER-MIB to other MIBs

The IEEE8021-FRER-MIB identifies the interfaces for the counters provided by this standard by an ifIndex and therefore imports from the IF-MIB.

It also imports items from the IEEE8021-STREAM-IDENTIFICATION-MIB, SNMPv2-SMI, SNMPv2-TC, and IEEE8021-TC-MIB and requires SNMPv2-CONF for conformance.

11.4 Security considerations

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example, by using IPsec), there is no control about who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in these MIB modules.

It is recommended that implementers consider the security features as provided by the SNMPv3 framework (see IETF RFC 3410 (2002), section 8), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is not recommended. Instead, it is recommended to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of these MIB modules is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

11.4.1 Security considerations of the IEEE8021-STREAM-IDENTIFICATION-MIB

There are a number of management objects defined in the IEEE8021-STREAM-IDENTIFICATION-MIB module that have a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a nonsecure environment without proper protection can have a negative effect on network operations.

Some of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. It is thus important to control all types of access (including GET and/or NOTIFY) to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP.

11.4.2 Security considerations of the IEEE8021-FRER-MIB

There are a number of management objects defined in the IEEE8021-STREAM-IDENTIFICATION-MIB module that have a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a nonsecure environment without proper protection can have a negative effect on network operations.

Some of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. It is thus important to control all types of access (including GET and/or NOTIFY) to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP.

11.5 MIB modules^{9, 10}

In this subclause, certain terms (e.g., “SHOULD” and “MUST”) denote requirements terminology according to the usage specified in IETF RFC 2119, as is customary for IETF MIB module definitions. In the MIB modules definitions below, if any discrepancy between the DESCRIPTION text and the corresponding definition in any other part of this standard occur, the definitions outside this subclause take precedence.

11.5.1 Definitions for the IEEE8021-STREAM-IDENTIFICATION-MIB

```
IEEE8021-STREAM-IDENTIFICATION-MIB DEFINITIONS ::= BEGIN

-- =====
-- MIB for support of Stream identification of IEEE 802.1CB
-- Frame Replication and Elimination for Reliability
-- =====

IMPORTS
    OBJECT-GROUP,
    MODULE-COMPLIANCE
        FROM SNMPv2-CONF
    MODULE-IDENTITY,
    OBJECT-TYPE,
    OBJECT-IDENTITY,
    Counter64,
    Unsigned32,
    Integer32
        FROM SNMPv2-SMI
    TEXTUAL-CONVENTION,
    TruthValue,
    RowStatus,
    MacAddress,
    AutonomousType,
    VariablePointer
        FROM SNMPv2-TC
    ifIndex
        FROM IF-MIB
    InetAddressType,
    InetAddress,
    InetPortNumber
        FROM INET-ADDRESS-MIB
    IEEE8021PriorityValue,
    ieee802dot1mibs
        FROM IEEE8021-TC-MIB
    ;

ieee8021StreamIdMib MODULE-IDENTITY
    LAST-UPDATED "202112080000Z" -- December 8, 2021
    ORGANIZATION "IEEE 802.1 Working Group"
    CONTACT-INFO
        "WG-URL: http://ieee802.org/1/
        WG-EMail: stds-802-1-l@ieee.org

        Contact: IEEE 802.1 Working Group Chair
        Postal: C/O IEEE 802.1 Working Group
                IEEE Standards Association
                445 Hoes Lane
                Piscataway, NJ 08854
                USA

        E-mail: stds-802-1-chairs@ieee.org"

    DESCRIPTION
```

⁹ Copyright release for MIBs: Users of this standard may freely reproduce the MIBs contained in this subclause so that they can be used for their intended purpose.

¹⁰ An ASCII version of the MIB modules are attached to the PDF version of this standard, and can be obtained by Web browser from the IEEE 802.1 Website at <https://1.ieee802.org/mib-modules/>.

"The Management Information Base module for IEEE 802.1CB Stream identification. Unless otherwise indicated, the references in this MIB module are to IEEE Std 802.1CB-2017 as amended by IEEE Std 802.1CBv-2021. Copyright (C) IEEE (2021). This version of this MIB module is part of IEEE Std 802.1CB-2021; see the standard itself for full legal notices."

REVISION "202112080000Z" -- December 8, 2021

DESCRIPTION

"Initial revision published as part of IEEE Std 802.1CBv-2021."

::= { ieee802dot1mibs 34 }

```
-- =====
-- Textual Conventions
-- =====

Ieee8021CBStreamIdentificationType ::= TEXTUAL-CONVENTION
    STATUS      current
    DESCRIPTION
        "An enumerated value indicating the method used to identify
         packets belonging to the Stream. The values 0-255 are reserved
         for use by IEEE 802."
    REFERENCE   "9.1.1.6 and Table 9-1"
    SYNTAX      INTEGER {
        reserved(0),
        nullStreamIdentification(1),
        srcMacVlanStreamIdentification(2),
        activeDstMacVlanStreamIdentification(3),
        ipStreamStreamIdentification(4),
        nonIEEESpecified(256)
    }

Ieee8021CBTaggedType ::= TEXTUAL-CONVENTION
    STATUS      current
    DESCRIPTION
        "An enumerated value indicating whether a packet in an EISS
         indication primitive to a Stream identification function is
         permitted to have a VLAN tag."
    REFERENCE   "9.1.2.2, 9.1.3.2, 9.1.4.2, 9.1.4.6, 9.1.5.2, and
         10.7.1.1.3"
    SYNTAX      INTEGER {
        tagged(1),
        priority(2),
        all(3)
    }

Ieee8021CBVlanIdentifier ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "d"
    STATUS      current
    DESCRIPTION
        "Specifies the vlan identifier. A value of 0 indicates a special
         treatment, depending on the use of Ieee8021CBVlanIdentifier."
    SYNTAX      Integer32 (0|1..4094)

Ieee8021CBIpDscpType ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "d"
    STATUS      current
    DESCRIPTION
        "The code point used for discriminating a traffic
         Stream."
    SYNTAX      Integer32 (-1 | 0..63)

Ieee8021CBIdNextProtocolType ::= TEXTUAL-CONVENTION
    STATUS      current
    DESCRIPTION
        "An enumerated value indicating an IP next protocol."
    SYNTAX      INTEGER {
        none(1),
        udp(2),
        tcp(3),
        sctp(4)
    }
```

```

    }

Ieee8021CBLanPathIdType ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "d"
    STATUS current
    DESCRIPTION
        "An integer specifying a path or LAN. If and only if a packet
        matches an entry in the Sequence identification table that
        specifies HSR or PRP in its frerSeqEncEncapsType object,
        tsnStreamIdLanPathId specifies the LanId or PathId value that
        must be matched for this tsnStreamIdEntry to apply. A value
        of -1 indicates that the LanId or PathId are to be ignored."
    REFERENCE "10.22"
    SYNTAX Integer32 (-1 | 0..15)

-- =====
-- subtrees in the Stream identification MIB
-- =====

ieee8021StreamIdNotifications
    OBJECT IDENTIFIER ::= { ieee8021StreamIdMib 0 }

ieee8021StreamIdObjects
    OBJECT IDENTIFIER ::= { ieee8021StreamIdMib 1 }

ieee8021StreamIdConformance
    OBJECT IDENTIFIER ::= { ieee8021StreamIdMib 2 }

ieee8021StreamIdStreamIdentification
    OBJECT IDENTIFIER ::= { ieee8021StreamIdObjects 1 }

ieee8021StreamIdStreamIdInFacOutputPortHandleList
    OBJECT IDENTIFIER ::= { ieee8021StreamIdObjects 2 }

ieee8021StreamIdStreamIdOutFacOutputPortHandleList
    OBJECT IDENTIFIER ::= { ieee8021StreamIdObjects 3 }

ieee8021StreamIdStreamIdInFacInputPortHandleList
    OBJECT IDENTIFIER ::= { ieee8021StreamIdObjects 4 }

ieee8021StreamIdStreamIdOutFacInputPortHandleList
    OBJECT IDENTIFIER ::= { ieee8021StreamIdObjects 5 }

ieee8021StreamIdPerPortPerStreamCounters
    OBJECT IDENTIFIER ::= { ieee8021StreamIdObjects 6 }

ieee8021StreamIdPerPortCounters
    OBJECT IDENTIFIER ::= { ieee8021StreamIdObjects 7 }

-- =====
-- the ieee8021StreamIdStreamIdentification table
-- =====

-- =====
-- the ieee8021StreamIdStreamIdentificationTypes
-- =====
ieee8021StreamIdStreamIdentificationTypes
    OBJECT IDENTIFIER ::= { ieee8021StreamIdStreamIdentification 1 }

ieee8021StreamIdNullStream OBJECT-IDENTITY
    STATUS current
    DESCRIPTION
        "The Stream identification type for the Null Stream
        identification."
    ::= { ieee8021StreamIdStreamIdentificationTypes 1 }

ieee8021StreamIdSrcMacVlan OBJECT-IDENTITY
    STATUS current
    DESCRIPTION
        "The Stream identification type for the Source MAC and VLAN
        Stream identification."
    ::= { ieee8021StreamIdStreamIdentificationTypes 2 }

```

```

ieee8021StreamIdActiveDestMacVlan OBJECT-IDENTITY
    STATUS current
    DESCRIPTION
        "The Stream identification type for the Active Destination
        and VLAN Stream identification."
    ::= { ieee8021StreamIdStreamIdentificationTypes 3 }

ieee8021StreamIdIpStream OBJECT-IDENTITY
    STATUS current
    DESCRIPTION
        "The Stream identification type for the IP Stream
        identification."
    ::= { ieee8021StreamIdStreamIdentificationTypes 4 }

-- =====
-- the ieee8021StreamIdStreamIdentification
-- =====

ieee8021StreamIdStreamIdentificationTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Ieee8021StreamIdStreamIdentificationEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A table containing a set of tsnStreamIdEntry objects each
        relating to a single Stream, specifying the points in the
        system where Stream identification functions are to be
        instantiated."
    REFERENCE   "9.1"
    ::= { ieee8021StreamIdStreamIdentification 2 }

ieee8021StreamIdStreamIdentificationEntry OBJECT-TYPE
    SYNTAX      Ieee8021StreamIdStreamIdentificationEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A set of managed objects, all applying to the Stream specified
        by tsnStreamIdHandle, and all using the same Stream
        identification types and parameters."
    REFERENCE   "9.1.1"
    INDEX       { ieee8021StreamIdStreamIdentificationIndex }
    ::= { ieee8021StreamIdStreamIdentificationTable 1 }

Ieee8021StreamIdStreamIdentificationEntry ::=
    SEQUENCE {
        ieee8021StreamIdStreamIdentificationIndex
            Unsigned32,
        ieee8021StreamIdStreamIdIdentificationType
            Ieee8021CBStreamIdIdentificationType,
        ieee8021StreamIdStreamIdIdentificationTypeOUI
            OCTET STRING,
        ieee8021StreamIdStreamIdIdentificationCustomType
            Integer32,
        ieee8021StreamIdStreamIdIdentificationCustomTypeOUI
            OCTET STRING,
        ieee8021StreamIdStreamIdIdentificationTypeSelect
            AutonomousType,
        ieee8021StreamIdStreamIdHandle
            Unsigned32,
        ieee8021StreamIdStreamIdInFacOutputPortList
            AutonomousType,
        ieee8021StreamIdStreamIdOutFacOutputPortList
            AutonomousType,
        ieee8021StreamIdStreamIdInFacInputPortList
            AutonomousType,
        ieee8021StreamIdStreamIdOutFacInputPortList
            AutonomousType,
        ieee8021StreamIdAutoConfigured
            TruthValue,
        ieee8021StreamIdLanPathId
            Ieee8021CBLanPathIdType,
        ieee8021StreamIdStatus
    }

```

```

        RowStatus
    }

ieee8021StreamIdStreamIdentificationIndex OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "Index for the Stream Identity table."
    ::= { ieee8021StreamIdStreamIdentificationEntry 1 }

ieee8021StreamIdStreamIdIdentificationType OBJECT-TYPE
    SYNTAX      Ieee8021CBStreamIdIdentificationType
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "This managed object is an enumerated value indicating the
        method used to identify packets belonging to the Stream.
        If the value used is nonIEEESpecified(256), the managed objects
        ieee8021StreamIdStreamIdIdentificationCustomType and
        ieee8021StreamIdStreamIdIdentificationCustomTypeOUI are used to
        specify OUI/CID and the Stream identification method defined by
        the entity owning the OUI/CID."
    REFERENCE   "9.1.1.6"
    DEFVAL      { nullStreamIdentification }
    ::= { ieee8021StreamIdStreamIdIdentificationEntry 2 }

ieee8021StreamIdStreamIdIdentificationTypeOUI OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE (3))
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "This managed object specifies the OUI/CID used together with
        the Stream identification method specified in
        ieee8021StreamIdStreamIdIdentificationType.
        It is used if and only if the value for
        ieee8021StreamIdStreamIdIdentificationType is in the range of
        0-255. In this case it always takes the value 00-80-C2."
    REFERENCE   "9.1.1.6"
    ::= { ieee8021StreamIdStreamIdIdentificationEntry 3 }

ieee8021StreamIdStreamIdIdentificationCustomType OBJECT-TYPE
    SYNTAX      Integer32 (256..2147483647)
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "This managed object is an enumerated value indicating the
        method used to identify packets belonging to the Stream. It is
        used if and only if the value for
        ieee8021StreamIdStreamIdIdentificationType is 256."
    REFERENCE   "9.1.1.6"
    ::= { ieee8021StreamIdStreamIdIdentificationEntry 4 }

ieee8021StreamIdStreamIdIdentificationCustomTypeOUI OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE (3))
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "This managed object specifies the OUI/CID used together with
        the Stream identification method specified in
        ieee8021StreamIdStreamIdIdentificationType. It is used if and
        only if the value for
        ieee8021StreamIdStreamIdIdentificationType is 256."
    REFERENCE   "9.1.1.6"
    ::= { ieee8021StreamIdStreamIdIdentificationEntry 5 }

ieee8021StreamIdStreamIdIdentificationTypeSelect OBJECT-TYPE
    SYNTAX      AutonomousType
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "An indication of the type of Stream identification method that

```

is used.

If this value is
'ieee8021StreamIdNullStream ieee8021StreamIdObjects 1' then
an entry exists in the
ieee8021StreamIdStreamIdentificationTable
which corresponds to the Null Stream identification.

If this value is
'ieee8021StreamIdSrcMacVlan ieee8021StreamIdObjects 2' then
an entry exists in the
ieee8021StreamIdStreamIdentificationTable
which corresponds to the Source MAC and VLAN Stream
identification.

If this value is
'ieee8021StreamIdActiveDestMacVlan ieee8021StreamIdObjects 3'
then an entry exists in the
ieee8021StreamIdStreamIdentificationTable
which corresponds to the Active Destination MAC and VLAN Stream
identification.

If this value is
'ieee8021StreamIdIpStream ieee8021StreamIdObjects 4' then
an entry exists in the
ieee8021StreamIdStreamIdentificationTable
which corresponds to the IP Stream identification."

::= { ieee8021StreamIdStreamIdentificationEntry 6 }

ieee8021StreamIdStreamIdHandle OBJECT-TYPE

SYNTAX Unsigned32
MAX-ACCESS read-create
STATUS current

DESCRIPTION

"The objects in a given entry of the Stream identity table are
used to control packets whose stream_handle subparameter is
equal to the entry's tsNStreamIdHandle object."

REFERENCE "9.1.1.1"

::= { ieee8021StreamIdStreamIdentificationEntry 7 }

ieee8021StreamIdStreamIdInFacOutputPortList OBJECT-TYPE

SYNTAX AutonomousType
MAX-ACCESS read-only
STATUS current

DESCRIPTION

"The list of ports on which an in-facing Stream identification
function using this identification method is to be placed for
this Stream in the output (towards the system forwarding
function) direction.

For each port in this list, there exists an entry in the
ieee8021StreamIdStreamIdInFacOutputPortHandleListTable."

REFERENCE "9.1.1.2"

::= { ieee8021StreamIdStreamIdentificationEntry 8 }

ieee8021StreamIdStreamIdOutFacOutputPortList OBJECT-TYPE

SYNTAX AutonomousType
MAX-ACCESS read-only
STATUS current

DESCRIPTION

"The list of ports on which an out-facing Stream identification
function using this identification method is to be placed for
this Stream in the output (towards the physical interface)
direction.

For each port in this list, there exists an entry in the
ieee8021StreamIdStreamIdOutFacOutputPortHandleListTable."

REFERENCE "9.1.1.3"

::= { ieee8021StreamIdStreamIdentificationEntry 9 }

ieee8021StreamIdStreamIdInFacInputPortList OBJECT-TYPE

SYNTAX AutonomousType
MAX-ACCESS read-only
STATUS current

```

DESCRIPTION
    "The list of ports on which an in-facing Stream identification
    function using this identification method is to be placed for
    this Stream in the input (coming from the system forwarding
    function) direction.
    For each port in this list, there exists an entry in the
    ieee8021StreamIdStreamIdInFacInputPortHandleListTable."
REFERENCE    "9.1.1.4"
::= { ieee8021StreamIdStreamIdentificationEntry 10 }

ieee8021StreamIdStreamIdOutFacInputPortList OBJECT-TYPE
SYNTAX      AutonomousType
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The list of ports on which an out-facing Stream identification
    function using this identification method is to be placed for
    this Stream in the input (coming from the physical interface)
    direction.
    For each port in this list, there exists an entry in the
    ieee8021StreamIdStreamIdOutFacInputPortHandleListTable."
REFERENCE    "9.1.1.5"
::= { ieee8021StreamIdStreamIdentificationEntry 11 }

ieee8021StreamIdAutoConfigured OBJECT-TYPE
SYNTAX      TruthValue
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "A read-only Boolean value, supplied by the system, specifying
    whether this entry was created explicitly (False) or via the
    Sequence autoconfiguration table (True)."
REFERENCE    "10.2.1"
::= { ieee8021StreamIdStreamIdentificationEntry 12 }

ieee8021StreamIdLanPathId OBJECT-TYPE
SYNTAX      Ieee8021CBLanPathIdType
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "An integer specifying a path or LAN. If and only if a packet
    matches an entry in the Sequence identification table that
    specifies HSR or PRP in its frerSeqEncEncapsType object,
    tsnStreamIdLanPathId specifies the LanId or PathId value that
    must be matched for this tsnStreamIdEntry to apply. A value
    of -1 indicates that the LanId or PathId are to be ignored."
REFERENCE    "10.2.2"
::= { ieee8021StreamIdStreamIdentificationEntry 13 }

ieee8021StreamIdStatus OBJECT-TYPE
SYNTAX      RowStatus
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "Row-Status for the Stream Identity table."
::= { ieee8021StreamIdStreamIdentificationEntry 14 }

-- =====
-- the ieee8021StreamIdNullStreamIdentificationTable
-- =====

ieee8021StreamIdNullStreamIdentificationTable OBJECT-TYPE
SYNTAX      SEQUENCE OF Ieee8021StreamIdNullStreamIdentificationEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "A table containing a set of controlling parameters for the
    Null Stream identification method."
REFERENCE    "9.1.2"
::= { ieee8021StreamIdStreamIdentification 3 }

ieee8021StreamIdNullStreamIdentificationEntry OBJECT-TYPE

```

```

SYNTAX      Ieee8021StreamIdNullStreamIdentificationEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "A set of managed objects that serve as the Stream
    identification parameters when using the Null Stream
    identification method."
REFERENCE   "9.1.2"
INDEX      { ieee8021StreamIdStreamIdentificationIndex }
::= { ieee8021StreamIdNullStreamIdentificationTable 1 }

Ieee8021StreamIdNullStreamIdentificationEntry ::=
SEQUENCE {
    ieee8021StreamIdCpeNullDownDestMac
        MacAddress,
    ieee8021StreamIdCPENullDownTagged
        Ieee8021CBTaggedType,
    ieee8021StreamIdCpeNullDownVlan
        Ieee8021CBVlanIdentifier
}

ieee8021StreamIdCpeNullDownDestMac OBJECT-TYPE
SYNTAX      MacAddress
MAX-ACCESS  read-write
STATUS      current
DESCRIPTION
    "Specifies the destination address that identifies a packet in
    an EISS indication primitive, to the Null Stream identification
    function."
REFERENCE   "9.1.2.1"
::= { ieee8021StreamIdNullStreamIdentificationEntry 1 }

ieee8021StreamIdCPENullDownTagged OBJECT-TYPE
SYNTAX      Ieee8021CBTaggedType
MAX-ACCESS  read-write
STATUS      current
DESCRIPTION
    "An enumerated value indicating whether a packet in an EISS
    indication primitive to the Null Stream identification function
    is permitted to have a VLAN tag."
REFERENCE   "9.1.2.2"
::= { ieee8021StreamIdNullStreamIdentificationEntry 2 }

ieee8021StreamIdCpeNullDownVlan OBJECT-TYPE
SYNTAX      Ieee8021CBVlanIdentifier
MAX-ACCESS  read-write
STATUS      current
DESCRIPTION
    "Specifies the vlan_identifier parameter that identifies a
    packet in an EISS indication primitive to the Null Stream
    identification function. A value of 0 indicates that the
    vlan_identifier parameter is ignored on EISS indication
    primitives."
REFERENCE   "9.1.2.3"
::= { ieee8021StreamIdNullStreamIdentificationEntry 3 }

-- =====
-- the ieee8021StreamIdSrcMacVlanIdentificationTable
-- =====

ieee8021StreamIdSrcMacVlanIdentificationTable OBJECT-TYPE
SYNTAX      SEQUENCE OF Ieee8021StreamIdSrcMacVlanIdentificationEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "A table containing a set of controlling parameters for the
    Source MAC and VLAN Stream identification method."
REFERENCE   "9.1.3"
::= { ieee8021StreamIdStreamIdentification 4 }

ieee8021StreamIdSrcMacVlanIdentificationEntry OBJECT-TYPE
SYNTAX      Ieee8021StreamIdSrcMacVlanIdentificationEntry

```

```

MAX-ACCESS    not-accessible
STATUS        current
DESCRIPTION
    "A set of managed objects that serve as the Stream
    identification parameters when using the Source MAC and VLAN
    Stream identification method."
REFERENCE     "9.1.3"
INDEX { ieee8021StreamIdStreamIdentificationIndex }
::= { ieee8021StreamIdSrcMacVlanIdentificationTable 1 }

Ieee8021StreamIdSrcMacVlanIdentificationEntry ::=
SEQUENCE {
    ieee8021StreamIdCpeSmacVlanDownSrcMac
        MacAddress,
    ieee8021StreamIdCpeSmacVlanDownTagged
        Ieee8021CBTaggedType,
    ieee8021StreamIdCpeSmacVlanDownVlan
        Ieee8021CBVlanIdentifier
}

ieee8021StreamIdCpeSmacVlanDownSrcMac OBJECT-TYPE
SYNTAX        MacAddress
MAX-ACCESS    read-write
STATUS        current
DESCRIPTION
    "Specifies the source address that identifies a packet in an
    EISS indication primitive, to the Source MAC and VLAN Stream
    identification function."
REFERENCE     "9.1.3.1"
::= { ieee8021StreamIdSrcMacVlanIdentificationEntry 1 }

ieee8021StreamIdCpeSmacVlanDownTagged OBJECT-TYPE
SYNTAX        Ieee8021CBTaggedType
MAX-ACCESS    read-write
STATUS        current
DESCRIPTION
    "An enumerated value indicating whether a packet in an EISS
    indication primitive to the Source MAC and VLAN Stream
    identification function is permitted to have a VLAN tag."
REFERENCE     "9.1.3.2"
::= { ieee8021StreamIdSrcMacVlanIdentificationEntry 2 }

ieee8021StreamIdCpeSmacVlanDownVlan OBJECT-TYPE
SYNTAX        Ieee8021CBVlanIdentifier
MAX-ACCESS    read-write
STATUS        current
DESCRIPTION
    "Specifies the vlan identifier parameter that identifies a
    packet in an EISS indication primitive to the Source MAC and
    VLAN Stream identification function. A value of 0 indicates
    that the vlan identifier parameter is ignored on EISS
    indication primitives."
REFERENCE     "9.1.3.3"
::= { ieee8021StreamIdSrcMacVlanIdentificationEntry 3 }

-- =====
-- the ieee8021StreamIdActiveDestMacVlanIdentificationTable
-- =====

ieee8021StreamIdActiveDestMacVlanIdentificationTable OBJECT-TYPE
SYNTAX        SEQUENCE OF Ieee8021StreamIdActiveDestMacVlanIdentificationEntry
MAX-ACCESS    not-accessible
STATUS        current
DESCRIPTION
    "A table containing a set of controlling parameters for the
    Active Destination MAC and VLAN Stream identification method."
REFERENCE     "9.1.4"
::= { ieee8021StreamIdStreamIdentification 5 }

ieee8021StreamIdActiveDestMacVlanIdentificationEntry OBJECT-TYPE
SYNTAX        Ieee8021StreamIdActiveDestMacVlanIdentificationEntry
MAX-ACCESS    not-accessible

```

```

STATUS      current
DESCRIPTION
    "A set of managed objects that serve as the Stream
    identification parameters when using the Active Destination
    MAC and VLAN Stream identification method."
REFERENCE    "9.1.4"
INDEX { ieee8021StreamIdStreamIdentificationIndex }
::= { ieee8021StreamIdActiveDestMacVlanIdentificationTable 1 }

Ieee8021StreamIdActiveDestMacVlanIdentificationEntry ::=
SEQUENCE {
    ieee8021StreamIdCpeDmacVlanDownDestMac
        MacAddress,
    ieee8021StreamIdCpeDmacVlanDownTagged
        Ieee8021CBTaggedType,
    ieee8021StreamIdCpeDmacVlanDownVlan
        Ieee8021CBVlanIdentifier,
    ieee8021StreamIdCpeDmacVlanDownPriority
        IEEE8021PriorityValue,
    ieee8021StreamIdCpeDmacVlanUpDestMac
        MacAddress,
    ieee8021StreamIdCpeDmacVlanUpTagged
        Ieee8021CBTaggedType,
    ieee8021StreamIdCpeDmacVlanUpVlan
        Ieee8021CBVlanIdentifier,
    ieee8021StreamIdCpeDmacVlanUpPriority
        IEEE8021PriorityValue
}

ieee8021StreamIdCpeDmacVlanDownDestMac OBJECT-TYPE
SYNTAX      MacAddress
MAX-ACCESS  read-write
STATUS      current
DESCRIPTION
    "Specifies the destination address parameter to use in the
    EISS request primitive for output packets sent to lower layers
    by the Active Destination MAC and VLAN Stream identification
    function, and the destination address that identifies an input
    packet in an EISS indication primitive to the Active
    Destination MAC and VLAN Stream identification function."
REFERENCE    "9.1.4.1"
::= { ieee8021StreamIdActiveDestMacVlanIdentificationEntry 1 }

ieee8021StreamIdCpeDmacVlanDownTagged OBJECT-TYPE
SYNTAX      Ieee8021CBTaggedType
MAX-ACCESS  read-write
STATUS      current
DESCRIPTION
    "An enumerated value indicating whether a packet in an EISS
    indication or request primitive between the Active Destination
    MAC and VLAN Stream identification function and the lower
    layers is to have a VLAN tag.
    This variable is not used in an FRER C-component."
REFERENCE    "9.1.4.2"
::= { ieee8021StreamIdActiveDestMacVlanIdentificationEntry 2 }

ieee8021StreamIdCpeDmacVlanDownVlan OBJECT-TYPE
SYNTAX      Ieee8021CBVlanIdentifier
MAX-ACCESS  read-write
STATUS      current
DESCRIPTION
    "Specifies the vlan identifier parameter to use in the EISS
    request primitive for output packets sent to lower layers by
    the Active Destination MAC and VLAN Stream identification
    function, and the vlan identifier that identifies an input
    packet in an EISS indication primitive to the Active
    Destination MAC and VLAN Stream identification function.
    A value of 0 indicates that the vlan identifier parameter is
    ignored on EISS indication primitives."
REFERENCE    "9.1.4.3"
::= { ieee8021StreamIdActiveDestMacVlanIdentificationEntry 3 }

```

```

ieee8021StreamIdCpeDmacVlanDownPriority OBJECT-TYPE
    SYNTAX      IEEE8021PriorityValue
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "Specifies the priority parameter to use in the EISS request
        primitive for output packets sent to lower layers by the Active
        Destination MAC and VLAN Stream identification function for all
        packets in a particular Stream."
    REFERENCE   "9.1.4.4"
    ::= { ieee8021StreamIdActiveDestMacVlanIdentificationEntry 4 }

ieee8021StreamIdCpeDmacVlanUpDestMac OBJECT-TYPE
    SYNTAX      MacAddress
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "Specifies the destination address parameter to use in the EISS
        indication primitive for input packets offered to upper layers
        by the Active Destination MAC and VLAN Stream identification
        layer. This address replaces the address that was used to
        identify the packet (tsnCpeDmacVlanDownDestMac)."
    REFERENCE   "9.1.4.5"
    ::= { ieee8021StreamIdActiveDestMacVlanIdentificationEntry 5 }

ieee8021StreamIdCpeDmacVlanUpTagged OBJECT-TYPE
    SYNTAX      Ieee8021CBTaggedType
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "An enumerated value indicating whether a packet in an EISS
        indication or request primitive between the Active Destination
        MAC and VLAN Stream identification function and the upper
        layers is to have a VLAN tag.
        This variable is used only by an end system and not by a
        relay system."
    REFERENCE   "9.1.4.6"
    ::= { ieee8021StreamIdActiveDestMacVlanIdentificationEntry 6 }

ieee8021StreamIdCpeDmacVlanUpVlan OBJECT-TYPE
    SYNTAX      Ieee8021CBVlanIdentifier
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "Specifies the vlan identifier parameter to use in the EISS
        indication primitive for packets offered to upper layers, or
        the VLAN ID field for an IEEE 802.1Q tag in an
        ISS mac_service_data_unit. This address replaces the VLAN ID
        that was used to identify the packet (tsnCpeDmacVlanDownVlan)."
    REFERENCE   "9.1.4.7"
    ::= { ieee8021StreamIdActiveDestMacVlanIdentificationEntry 7 }

ieee8021StreamIdCpeDmacVlanUpPriority OBJECT-TYPE
    SYNTAX      IEEE8021PriorityValue
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "Specifies the priority parameter to use in the EISS indication
        primitive for packets offered to upper layers."
    REFERENCE   "9.1.4.8"
    ::= { ieee8021StreamIdActiveDestMacVlanIdentificationEntry 8 }

-- =====
-- the ieee8021StreamIdIpStreamIdentificationTable
-- =====

ieee8021StreamIdIpStreamIdentificationTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Ieee8021StreamIdIpStreamIdentificationEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A table containing a set of controlling parameters for the

```

```

        IP Stream identification method."
REFERENCE    "9.1.5"
::= { ieee8021StreamIdStreamIdentification 6 }

ieee8021StreamIdIpStreamIdentificationEntry OBJECT-TYPE
SYNTAX      Ieee8021StreamIdIpStreamIdentificationEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "A set of managed objects that serve as the Stream
     identification parameters when using the IP Stream
     identification method."
REFERENCE    "9.1.5"
INDEX       { ieee8021StreamIdStreamIdentificationIndex }
::= { ieee8021StreamIdIpStreamIdentificationTable 1 }

Ieee8021StreamIdIpStreamIdentificationEntry ::=
SEQUENCE {
    ieee8021StreamIdCpeIpIdDestMac
        MacAddress,
    ieee8021StreamIdCpeIpIdTagged
        Ieee8021CBTaggedType,
    ieee8021StreamIdCpeIpIdVlan
        Ieee8021CBVlanIdentifier,
    ieee8021StreamIdCpeIpIdIpSourceType
        InetAddressType,
    ieee8021StreamIdCpeIpIdIpSource
        InetAddress,
    ieee8021StreamIdCpeIpIdIpDestinationType
        InetAddressType,
    ieee8021StreamIdCpeIpIdIpDestination
        InetAddress,
    ieee8021StreamIdCpeIpIdDscp
        Ieee8021CBIpDscpType,
    ieee8021StreamIdCpeIpIdNextProtocol
        Ieee8021CBIdNextProtocolType,
    ieee8021StreamIdCpeIpIdSourcePort
        InetPortNumber,
    ieee8021StreamIdCpeIpIdDestinationPort
        InetPortNumber
}

ieee8021StreamIdCpeIpIdDestMac OBJECT-TYPE
SYNTAX      MacAddress
MAX-ACCESS  read-write
STATUS      current
DESCRIPTION
    "Specifies the destination address parameter that identifies a
     packet in an EISS indication primitive."
REFERENCE    "9.1.5.1"
::= { ieee8021StreamIdIpStreamIdentificationEntry 1 }

ieee8021StreamIdCpeIpIdTagged OBJECT-TYPE
SYNTAX      Ieee8021CBTaggedType
MAX-ACCESS  read-write
STATUS      current
DESCRIPTION
    "An enumerated value indicating whether a packet in an EISS
     indication or request primitive to the IP Stream identification
     function is to have a VLAN tag."
REFERENCE    "9.1.5.2"
::= { ieee8021StreamIdIpStreamIdentificationEntry 2 }

ieee8021StreamIdCpeIpIdVlan OBJECT-TYPE
SYNTAX      Ieee8021CBVlanIdentifier
MAX-ACCESS  read-write
STATUS      current
DESCRIPTION
    "Specifies the vlan identifier parameter that identifies a
     packet in an EISS indication primitive. A value of 0 indicates
     that the frame is not to have a VLAN tag."
REFERENCE    "9.1.5.3"

```

```

::= { ieee8021StreamIdIpStreamIdentificationEntry 3 }

ieee8021StreamIdCpeIpIdIpSourceType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
        "Specifies the type of the source address parameter supplied
        in ieee8021StreamIdCpeIpIdIpSource."
    REFERENCE    "9.1.5.4"
    ::= { ieee8021StreamIdIpStreamIdentificationEntry 4 }

ieee8021StreamIdCpeIpIdIpSource OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
        "Specifies the IPv4 (RFC 791) or IPv6 (RFC 2460) source address
        parameter that must be matched to identify packets coming up
        from lower layers. An address of all 0 indicates that the
        IP source address is to be ignored on packets received from
        lower layers."
    REFERENCE    "9.1.5.4"
    ::= { ieee8021StreamIdIpStreamIdentificationEntry 5 }

ieee8021StreamIdCpeIpIdIpDestinationType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
        "Specifies the type of the destination address parameter
        supplied in ieee8021StreamIdCpeIpIdIpDestination."
    REFERENCE    "9.1.5.4"
    ::= { ieee8021StreamIdIpStreamIdentificationEntry 6 }

ieee8021StreamIdCpeIpIdIpDestination OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
        "Specifies the IPv4 (RFC 791) or IPv6 (RFC 2460) destination
        address parameter that must be matched to identify packets
        coming up from lower layers."
    REFERENCE    "9.1.5.5"
    ::= { ieee8021StreamIdIpStreamIdentificationEntry 7 }

ieee8021StreamIdCpeIpIdDscp OBJECT-TYPE
    SYNTAX      Ieee8021CBIpDscpType
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
        "Specifies the IPv4 (RFC 791) or IPv6 (RFC 2460) differentiated
        services codepoint (DSCP, RFC 2474) that must be matched to
        identify packets coming up from the lower layers. A value of
        64 decimal indicates that the DSCP is to be ignored on packets
        received from lower layers."
    REFERENCE    "9.1.5.6"
    ::= { ieee8021StreamIdIpStreamIdentificationEntry 8 }

ieee8021StreamIdCpeIpIdNextProtocol OBJECT-TYPE
    SYNTAX      Ieee8021CBIdNextProtocolType
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
        "Specifies the IP next protocol parameter that must be matched
        to identify packets coming up from lower layers. The value of
        this parameter must specify either none, UDP (RFC 768),
        TCP (RFC 793), or SCTP (RFC 4960). If 'none', then the
        tsnCpeIpIdSourcePort and tsnCpeIpIdDestinationPort managed
        objects are not used."
    REFERENCE    "9.1.5.7"
    ::= { ieee8021StreamIdIpStreamIdentificationEntry 9 }

```

```

ieee8021StreamIdCpeIpIdSourcePort OBJECT-TYPE
    SYNTAX      InetPortNumber
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "Specifies the TCP or UDP Source Port parameter that must be
        matched to identify packets coming up from lower layers.
        A value of 0 indicates that the Source Port number of the
        packet is to be ignored on packets received from lower layers."
    REFERENCE   "9.1.5.8"
    ::= { ieee8021StreamIdIpStreamIdentificationEntry 10 }

ieee8021StreamIdCpeIpIdDestinationPort OBJECT-TYPE
    SYNTAX      InetPortNumber
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "Specifies the TCP or UDP Destination Port parameter that must
        be matched to identify packets coming up from lower layers.
        A value of 0 indicates that the Destination Port number of the
        packet is to be ignored on packets received from lower layers."
    REFERENCE   "9.1.5.9"
    ::= { ieee8021StreamIdIpStreamIdentificationEntry 11 }

-- =====
-- the ieee8021StreamIdStreamIdInFacOutputPortHandleList
-- table
-- =====
ieee8021StreamIdStreamIdInFacOutputPortHandleListTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Ieee8021StreamIdStreamIdInFacOutputPortHandleListEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A table containing a list of ports on which an in-facing Stream
        identification function using this identification method is to
        be placed for this Stream in the output (towards the system
        forwarding function) direction, referenced in
        ieee8021StreamIdStreamIdentificationIndex."
    REFERENCE   "9.1.1.2"
    ::= { ieee8021StreamIdStreamIdInFacOutputPortHandleList 2 }

ieee8021StreamIdStreamIdInFacOutputPortHandleListEntry OBJECT-TYPE
    SYNTAX      Ieee8021StreamIdStreamIdInFacOutputPortHandleListEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A set of managed objects providing the ports on which an
        in-facing Stream identification function using this
        identification method is to be placed for this Stream in the
        output (towards the system forwarding function) direction,
        referenced in ieee8021StreamIdStreamIdentificationIndex."
    REFERENCE   "9.1.1.2"
    INDEX       { ieee8021StreamIdStreamIdentificationIndex,
                  ieee8021StreamIdStreamIdInFacOutputPortHandleListIndex
                }
    ::= { ieee8021StreamIdStreamIdInFacOutputPortHandleListTable 1 }

Ieee8021StreamIdStreamIdInFacOutputPortHandleListEntry ::=
    SEQUENCE {
        ieee8021StreamIdStreamIdInFacOutputPortHandleListIndex
            Unsigned32,
        ieee8021StreamIdStreamIdInFacOutputPortHandle
            VariablePointer,
        ieee8021StreamIdStreamIdInFacOutputPortHandleListStatus
            RowStatus
    }

ieee8021StreamIdStreamIdInFacOutputPortHandleListIndex OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  not-accessible
    STATUS      current

```

```

DESCRIPTION
    "Index for the In-Facing Output Port handle list table."
    ::= { ieee8021StreamIdStreamIdInFacOutputPortHandleListEntry 1 }

ieee8021StreamIdStreamIdInFacOutputPortHandle OBJECT-TYPE
    SYNTAX      VariablePointer
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "A pointer to an interface that is an element of the
         ieee8021StreamIdStreamIdInFacOutputPortList instance in the
         ieee8021StreamIdStreamIdentificationTable."
    REFERENCE    "9.1.1.2"
    ::= { ieee8021StreamIdStreamIdInFacOutputPortHandleListEntry 2 }

ieee8021StreamIdStreamIdInFacOutputPortHandleListStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "Row-Status for the In-Facing Output Port handle list table."
    ::= { ieee8021StreamIdStreamIdInFacOutputPortHandleListEntry 3 }

-- =====
-- the ieee8021StreamIdStreamIdOutFacOutputPortList
-- table
-- =====
ieee8021StreamIdStreamIdOutFacOutputPortHandleListTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Ieee8021StreamIdStreamIdOutFacOutputPortHandleListEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "A table containing a list of ports on which an out-facing
         Stream identification function using this identification method
         is to be placed for this Stream in the output (towards the
         system forwarding function) direction, referenced in
         ieee8021StreamIdStreamIdentificationIndex."
    REFERENCE    "9.1.1.3"
    ::= { ieee8021StreamIdStreamIdOutFacOutputPortHandleList 3 }

ieee8021StreamIdStreamIdOutFacOutputPortHandleListEntry OBJECT-TYPE
    SYNTAX      Ieee8021StreamIdStreamIdOutFacOutputPortHandleListEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "A set of managed objects providing the ports on which an
         out-facing Stream identification function using this
         identification method is to be placed for this Stream in the
         output (towards the system forwarding function) direction,
         referenced in ieee8021StreamIdStreamIdentificationIndex."
    REFERENCE    "9.1.1.3"
    INDEX       { ieee8021StreamIdStreamIdentificationIndex,
                  ieee8021StreamIdStreamIdOutFacOutputPortHandleListIndex
                }
    ::= { ieee8021StreamIdStreamIdOutFacOutputPortHandleListTable 1 }

Ieee8021StreamIdStreamIdOutFacOutputPortHandleListEntry ::=
    SEQUENCE {
        ieee8021StreamIdStreamIdOutFacOutputPortHandleListIndex
            Unsigned32,
        ieee8021StreamIdStreamIdOutFacOutputPortHandle
            VariablePointer,
        ieee8021StreamIdStreamIdOutFacOutputPortHandleListStatus
            RowStatus
    }

ieee8021StreamIdStreamIdOutFacOutputPortHandleListIndex OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "Index for the Out-Facing Output Port handle list table."

```

```

 ::= { ieee8021StreamIdStreamIdOutFacOutputPortHandleListEntry 1 }

ieee8021StreamIdStreamIdOutFacOutputPortHandle OBJECT-TYPE
    SYNTAX      VariablePointer
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "A pointer to an interface that is an element of the
         ieee8021StreamIdStreamIdOutFacOutputPortList instance in the
         ieee8021StreamIdStreamIdentificationTable."
    REFERENCE   "9.1.1.3"
    ::= { ieee8021StreamIdStreamIdOutFacOutputPortHandleListEntry 2 }

ieee8021StreamIdStreamIdOutFacOutputPortHandleListStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Row-Status for the Out-Facing Output Port handle list table."
    ::= { ieee8021StreamIdStreamIdOutFacOutputPortHandleListEntry 3 }

-- =====
-- the ieee8021StreamIdStreamIdInFacInputPortList
-- table
-- =====
ieee8021StreamIdStreamIdInFacInputPortHandleListTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Ieee8021StreamIdStreamIdInFacInputPortHandleListEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A table containing a list of ports on which an in-facing Stream
         identification function using this identification method is to
         be placed for this Stream in the input (coming from the system
         forwarding function) direction, referenced in
         ieee8021StreamIdStreamIdentificationIndex."
    REFERENCE   "9.1.1.4"
    ::= { ieee8021StreamIdStreamIdInFacInputPortHandleList 4 }

ieee8021StreamIdStreamIdInFacInputPortHandleListEntry OBJECT-TYPE
    SYNTAX      Ieee8021StreamIdStreamIdInFacInputPortHandleListEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A set of managed objects providing the ports on which an
         in-facing Stream identification function using this
         identification method is to be placed for this Stream in the
         input (coming from the system forwarding function) direction,
         referenced in ieee8021StreamIdStreamIdentificationIndex."
    REFERENCE   "9.1.1.4"
    INDEX       { ieee8021StreamIdStreamIdentificationIndex,
                  ieee8021StreamIdStreamIdInFacInputPortHandleListIndex
                }
    ::= { ieee8021StreamIdStreamIdInFacInputPortHandleListTable 1 }

Ieee8021StreamIdStreamIdInFacInputPortHandleListEntry ::=
    SEQUENCE {
        ieee8021StreamIdStreamIdInFacInputPortHandleListIndex
            Unsigned32,
        ieee8021StreamIdStreamIdInFacInputPortHandle
            VariablePointer,
        ieee8021StreamIdStreamIdInFacInputPortHandleListStatus
            RowStatus
    }

ieee8021StreamIdStreamIdInFacInputPortHandleListIndex OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Index for the In-Facing Input Port handle list table."
    ::= { ieee8021StreamIdStreamIdInFacInputPortHandleListEntry 1 }

```