

INTERNATIONAL
STANDARD

ISO/IEC/
IEEE
8802-1Q

First edition
2016-03-15

Corrigendum 1
2017-10

**Information technology —
Telecommunications and information
exchange between systems — Local
and metropolitan area networks —
Specific requirements —**

**Part 1Q:
Bridges and bridged networks**

**TECHNICAL CORRIGENDUM 1:
Technical and editorial corrections**

*Technologies de l'information — Télécommunications et échange
d'information entre systèmes — Réseaux locaux et métropolitains
— Exigences spécifiques —*

*Partie 1Q: Ponts et réseaux pontés
RECTIFICATIF TECHNIQUE 2: Corrections techniques et
rédactionnelles*



Reference number
ISO/IEC/IEEE 8802-1Q:2016/Cor.1:2017(E)

Documents
© IEEE 2016
Document Sharing Hub



COPYRIGHT PROTECTED DOCUMENT

© IEEE 2016

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO or IEEE at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Institute of Electrical and Electronics Engineers, Inc
3 Park Avenue, New York
NY 10016-5997, USA

stds.ipr@ieee.org
www.ieee.org

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards.

The main task of ISO/IEC JTC 1 is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is called to the possibility that implementation of this standard may require the use of subject matter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. ISO/IEEE is not responsible for identifying essential patents or patent claims for which a license may be required, for conducting inquiries into the legal validity or scope of patents or patent claims or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance or a Patent Statement and Licensing Declaration Form, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from ISO or the IEEE Standards Association.

ISO/IEC/IEEE 8802-1Q:2016/Cor.1:2017 was prepared by the LAN/MAN of the IEEE Computer Society (as IEEE 802.1Q-2014/Cor 1-2015). It was adopted by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*, in parallel with its approval by the ISO/IEC national bodies, under the “fast-track procedure” defined in the Partner Standards Development Organization cooperation agreement between ISO and IEEE. IEEE is responsible for the maintenance of this document with participation and input from ISO/IEC national bodies.

IEEE Std 802.1Q™-2014/Cor 1-2015

(Corrigendum to
IEEE Std 802.1Q-2014)

**IEEE Standard for
Local and metropolitan area networks—**

Bridges and Bridged Networks—

**Corrigendum 1: Technical and editorial
corrections**

Sponsor

**LAN/MAN Standards Committee
of the
IEEE Computer Society**

Approved 5 December 2015

IEEE-SA Standards Board

Abstract: Correction of technical and editorial errors identified by the IEEE 802.1 maintenance activity are presented in this document.

Keywords: corrigendum, Bridged Local Area Networks, ECMP, Equal Cost Multiple Paths, IEEE 802.1Q™, LANs, local area networks, MAC Bridges, MANs, metropolitan area networks, Shortest Path Bridging, Virtual Bridged Local Area Networks

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2016 by The Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 12 January 2016. Printed in the United States of America.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-1-5044-0112-8 STD20519

IEEE prohibits discrimination, harassment and bullying. For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>. No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading “Important Notice” or “Important Notices and Disclaimers Concerning IEEE Standards Documents.”

Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents (standards, recommended practices, and guides), both full-use and trial-use, are developed within IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (“IEEE-SA”) Standards Board. IEEE (“the Institute”) develops its standards through a consensus development process, approved by the American National Standards Institute (“ANSI”), which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims all warranties (express, implied and statutory) not included in this or any other document relating to the standard, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, IEEE disclaims any and all conditions relating to: results; and workmanlike effort. IEEE standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

Official statements

A statement, written or oral, that is not processed in accordance with the IEEE-SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, or be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in revisions to an IEEE standard is welcome to join the relevant IEEE working group.

Comments on standards should be submitted to the following address:

Secretary, IEEE-SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854 USA

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

IEEE draft and approved standards are copyrighted by IEEE under U.S. and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

Photocopies

Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE-SA Website at <http://ieeexplore.ieee.org/xpl/standards.jsp> or contact IEEE at the address listed previously. For more information about the IEEE SA or IEEE's standards development process, visit the IEEE-SA Website at <http://standards.ieee.org>.

Errata

Errata, if any, for all IEEE standards can be accessed on the IEEE-SA Website at the following URL: <http://standards.ieee.org/findstds/errata/index.html>. Users are encouraged to check this URL for errata periodically.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE-SA Website at <http://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patent Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

Participants

At the time this corrigendum was submitted to the IEEE-SA Standards Board for approval, the IEEE 802.1 Working Group had the following membership:

Glenn Parsons, *Chair*
John Messenger, *Vice Chair and Chair, Maintenance Task Group*
Tony Jeffree, *Editor*

Christian Boiger
 Paul Bottorff
 David Chen
 Feng Chen
 Weiying Cheng
 Rodney Cummings
 Janos Farkas
 Norman Finn
 Geoffrey Garner
 Eric Gray
 Craig Gunther
 Stephen Haddock
 Mark Hantel
 Marc Holness
 Michael Johas Teener

Hal Keen
 Stephan Kehrer
 Marcel Kiessling
 Philippe Klein
 Jouni Korhonen
 Yizhou Li
 Christophe Mangin
 Tom McBeath
 James McIntosh
 Hiroki Nakano
 Bob Noseworthy
 Donald R. Pannell
 Walter Pieniac
 Karen Randall
 Maximilian Riegel
 Dan Romascanu

Jessy Rouyer
 Panagiotis Saltsidis
 Michael Seaman
 Daniel Sexton
 Johannes Specht
 Wilfried Steiner
 Patricia Thaler
 David Thornburg
 Jeremy Touve
 Paul Unbehagen
 Karl Weber
 Brian Weis
 Jordon Woods
 Helge Zinner
 Juan Carlos Zuniga

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Iwan Adhicandra
 Thomas Alexander
 Butch Anton
 Lee Armstrong
 Stefan Aust
 Christian Boiger
 Nancy Bravin
 William Byrd
 Juan Carreon
 Rodney Cummings
 Janos Farkas
 Avraham Freedman
 Yukihiro Fujimoto
 David Gregson
 Randall Groves
 Craig Gunther
 Stephen Haddock
 Jerome Henry
 Marco Hernandez
 Guido Hiertz
 Werner Hoelzl
 Victor Hou
 C. Huntley

Noriyuki Ikeuchi
 Sergiu Iordanescu
 Atsushi Ito
 Tony Jeffree
 Michael Johas Teener
 Adri Jovin
 Shinkyo Kaku
 Piotr Karocki
 Stuart Kerry
 Yongbum Kim
 Mark Laubach
 David Lewis
 Arthur H. Light
 William Lumpkins
 Michael Lynch
 Elvis Maculuba
 Jonathon McLendon
 Richard Mellitz
 Charles Moorwood
 Michael Newman
 Nick S.A. Nikjoo
 Satoshi Obara
 Alon Regev

Maximilian Riegel
 Robert Robinson
 Benjamin Rolfe
 Dan Romascanu
 Jessy Rouyer
 Bartien Sayogo
 Michael Seaman
 Thomas Starai
 Eugene Stoudenmire
 Walter Struppler
 Michael Swearingen
 Patricia Thaler
 Mark-Rene Uchida
 Lorenzo Vangelista
 Dmitri Varsanofiev
 George Vlantis
 Khurram Waheed
 Stephen Webb
 Hung-Yu Wei
 Natalie Wienckowski
 Oren Yuen
 Zhen Zhou

When the IEEE-SA Standards Board approved this corrigendum on 5 December 2015, it had the following membership:

John D. Kulick, *Chair*
Jon Walter Rosdahl, *Vice Chair*
Richard H. Hulett, *Past Chair*
Konstantinos Karachalios, *Secretary*

Masayuki Ariyoshi
Ted Burse
Stephen Dukes
Jean-Philippe Faure
J. Travis Griffith
Gary Hoffman
Michael Janezic

Joseph L. Koepfinger*
David J. Law
Hung Ling
Andrew Myles
T. W. Olsen
Glenn Parsons
Ronald C. Petersen
Annette D. Reilly

Stephen J. Shellhammer
Adrian P. Stephens
Yatin Trivedi
Phillip Winston
Don Wright
Yu Yuan
Daidi Zhong

*Member Emeritus

Introduction

This introduction is not part of IEEE Std 802.1Q-2014/Cor 1-2015, IEEE Standard for Local and metropolitan area networks—Bridges and Bridged Networks—Corrigendum 1: Technical and editorial corrections.

This corrigendum to IEEE Std 802.1Q-2014 corrects the small number of errors to the base text identified by the IEEE 802.1 maintenance activity. These changes are needed in order to correct technical and/or editorial errors in the existing text.

Contents

12. Bridge management	2
12.22 Stream Reservation Protocol (SRP) entities	2
17. Management Information Base (MIB)	3
17.2 Structure of the MIB	3
17.7 MIB modules	3
25. Support of the MAC Service by PBBNs	31
25.2 Customer service interface	31
32. Congestion notification protocol	32
32.14 RP procedures	32
33. Encoding of congestion notification PDUs	33
33.4 Congestion Notification Message PDU format	33
35. Stream Reservation Protocol (SRP)	34
35.1 Multiple Stream Registration Protocol (MSRP)	34
35.2 Definition of the MSRP application	35
Annex A (normative) PICS proforma—Bridge implementations	37
A.37 Shortest Path Bridging (SPB)	37
Annex B (normative) PICS proforma—End station implementations	38
B.10 Stream Reservation Protocol (SRP)	38
Annex D (normative) IEEE 802.1 Organizationally Specific TLVs	39
D.1 Requirements of the IEEE 802.1 Organizationally Specific TLV sets	39
D.2 Organizationally Specific TLV definitions	39
D.3 IEEE 802.1 Organizationally Specific TLV management	39
D.4 PICS proforma for IEEE 802.1 Organizationally Specific TLV extensions	40
D.5 IEEE 802.1/LLDP extension MIB	41
Annex Q (informative) Bibliography	109

Figures

Figure 35-2	Format of the components of the reservation FirstValue fields.....	35
-------------	--	----

Tables

Table 12-17 SRP Reservations Table row elements 2

Table 17-20 SRP MIB structure and object cross reference 3

Table 35-6 Reservation Failure Codes 36

Table D-1 IEEE 802.1 Organizationally Specific TLVs specified in this standard ~~39~~

Table D-12 IEEE 802.1/LLDP extension MIB object cross reference 41

IEEE Standard for Local and metropolitan area networks—

Bridges and Bridged Networks—

Corrigendum 1: Technical and editorial corrections

(This corrigendum is based on IEEE Std 802.1Q™-2014.)

NOTE—The editing instructions contained in this amendment define how to merge the material contained here into the base document and its other amendments to form the new comprehensive standard.

Editing instructions are shown in ***bold italic***. Four editing instructions are used: change, delete, insert, and replace. ***Change*** is used to make corrections in existing text or tables. The editing instruction specifies the location of the change and describes what is being changed either by using ~~strike through~~ (to remove old material) and underline (to add new material). ***Delete*** removes existing material. ***Insert*** adds new material without disturbing the existing material. Insertions may require renumbering. If so, renumbering instructions are given in the editing instruction. ***Replace*** is used to make changes in figures or equations by removing the existing figure or equation and replacing it with a new one. Editing instructions, change markings, and this NOTE will not be carried over into future editions because the changes will be incorporated into the base standard.¹

IMPORTANT NOTICE: IEEE Standards documents are not intended to ensure safety, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

This IEEE document is made available for use subject to important notices and legal disclaimers. These notices and disclaimers appear in all publications containing this document and may be found under the heading “Important Notice” or “Important Notices and Disclaimers Concerning IEEE Documents.” They can also be obtained on request from IEEE or viewed at <http://standards.ieee.org/IPR/disclaimers.html>.

¹Notes in text, tables, and figures are given for information only, and do not contain requirements needed to implement the standard.

12. Bridge management

12.22 Stream Reservation Protocol (SRP) entities

12.22.5 SRP Reservations Table

Change row 5 of Table 12-17 as follows:

Table 12-17—SRP Reservations Table row elements

Name	Data type	Operations supported	Conformance	References
Failed Bridge ID <u>system ID</u>	BridgeId	R	BE	35.2.2.8.7(a)

17. Management Information Base (MIB)

17.2 Structure of the MIB

17.2.14 Structure of the IEEE8021-SRP-MIB

Change row 31 and row 32 of Table 17-20 as follows:

Table 17-20—SRP MIB structure and object cross reference

MIB table	MIB object	References
	ieee8021SrpReservationFailure BridgeId <u>SystemId</u>	Bridge-system ID of Bridge-system that changed Talker Advertise to Talker Failed, 12.22.5, 35.2.2.8.7a.
	ieee8021SrpReservationFailureCode	Failure Code associated with Bridge-system that changed Talker Advertise to Talker Failed, 12.22.5, 35.2.2.8.7b.

17.7 MIB modules

17.7.12 Definitions for the IEEE8021-FQTSS-MIB module

Replace the text of 17.7.12 with the following:

```
IEEE8021-FQTSS-MIB DEFINITIONS ::= BEGIN

-- =====
-- MIB for support of the Forwarding & Queuing Enhancements
-- for Time Sensitive Streams (FQTSS) in 802.1Q Bridges.
-- =====

IMPORTS
    MODULE-IDENTITY,
    OBJECT-TYPE,
    Unsigned32
        FROM SNMPv2-SMI
    TEXTUAL-CONVENTION,
    TruthValue,
    RowStatus
        FROM SNMPv2-TC
    MODULE-COMPLIANCE,
    OBJECT-GROUP
        FROM SNMPv2-CONF
    ieee802dot1mibs,
    IEEE8021PriorityValue
        FROM IEEE8021-TC-MIB
    ieee8021BridgeBaseComponentId,
    ieee8021BridgeBasePort
        FROM IEEE8021-BRIDGE-MIB
    ;

ieee8021FqtssMib MODULE-IDENTITY
    LAST-UPDATED "201512020000Z" -- December 2, 2015
    ORGANIZATION "IEEE 802.1 Working Group"
    CONTACT-INFO
        " WG-URL: http://ieee802.org/1/
          WG-Email: STDS-802-1-L@LISTSERV.IEEE.ORG

          Contact: IEEE 802.1 Working Group Chair
          Postal: C/O IEEE 802.1 Working Group
                  IEEE Standards Association
                  445 Hoes Lane
                  Piscataway
                  NJ 08854
                  USA
          E-mail: STDS-802-1-L@LISTSERV.IEEE.ORG"
    DESCRIPTION
        "The Bridge MIB module for managing devices that support
        the Forwarding and Queuing Enhancements
        for Time Sensitive Streams.

        Unless otherwise indicated, the references in this MIB
        module are to IEEE Std 802.1Q-2014.

        Copyright (C) IEEE (2015).
        This version of this MIB module is part of IEEE802.1Q;
        see the draft itself for full legal notices."
```

IEEE Std 802.1Q™-2014/Cor 1-2015
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks—
Corrigendum 1: Technical and editorial corrections

REVISION "201512020000Z" -- December 2, 2015

DESCRIPTION

"Published as part of IEEE Std 802.1Q 2014 Cor-1.
ETS code point added to the textual convention
IEEE8021FqtssTxSelectionAlgorithmIDValue "

REVISION "201412150000Z" -- December 15, 2014

DESCRIPTION

"Published as part of IEEE Std 802.1Q 2014 revision.
Cross references updated and corrected."

REVISION "201102270000Z" -- February 27, 2011

DESCRIPTION

"Minor edits to contact information etc. as part of
2011 revision of IEEE Std 802.1Q."

REVISION "200910010000Z" -- October 1, 2009

DESCRIPTION

"Initial revision, included in IEEE 802.1Qav."
::= { ieee802dot1mibs 16 }

-- =====
-- Textual Conventions
-- =====

IEEE8021FqtssTrafficClassValue ::= TEXTUAL-CONVENTION

DISPLAY-HINT "d"

STATUS current

DESCRIPTION

"An 802.1 FQTSS traffic class value.
This is the numerical value associated with a traffic
class in a Bridge. Larger values are associated with
higher priority traffic classes."

REFERENCE "12.20.1"

SYNTAX Unsigned32 (0..7)

IEEE8021FqtssDeltaBandwidthValue ::= TEXTUAL-CONVENTION

DISPLAY-HINT "d"

STATUS current

DESCRIPTION

"An 802.1 FQTSS delta bandwidth percentage,
represented as a fixed point number scaled by
1,000,000."

REFERENCE "12.20.1, 34.4"

SYNTAX Unsigned32 (0..100000000)

IEEE8021FqtssTxSelectionAlgorithmIDValue ::= TEXTUAL-CONVENTION

DISPLAY-HINT "d"

STATUS current

DESCRIPTION

"An 802.1 transmission selection algorithm identifier
value. This is an integer, with the following
interpretation placed on the value:

0: Strict priority algorithm,
1: Credit-based shaper algorithm,
2: Enhanced Transmission Selection algorithm,
3-255: Reserved for future standardization,
256-4294967295: Vendor-specific transmission selection

IEEE Std 802.1Q™-2014/Cor 1-2015
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks—
Corrigendum 1: Technical and editorial corrections

```

algorithm identifiers, consisting of a
four-octet integer, where the most
significant 3 octets hold an OUI or CID value,
and the least significant octet holds
an integer value in the range 0-255
assigned by the owner of the OUI or CID."
REFERENCE    "8.6.8, 12.20.2"
SYNTAX      Unsigned32

-- =====
-- subtrees in the FQTSS MIB
-- =====

ieee8021FqtssNotifications
    OBJECT IDENTIFIER ::= { ieee8021FqtssMib 0 }

ieee8021FqtssObjects
    OBJECT IDENTIFIER ::= { ieee8021FqtssMib 1 }

ieee8021FqtssConformance
    OBJECT IDENTIFIER ::= { ieee8021FqtssMib 2 }

ieee8021FqtssBap
    OBJECT IDENTIFIER ::= { ieee8021FqtssObjects 1 }

ieee8021FqtssMappings
    OBJECT IDENTIFIER ::= { ieee8021FqtssObjects 2 }

-- =====
-- The ieee8021FqtssBap subtree
-- This subtree defines the objects necessary for the management
-- of bandwidth allocation for queues that support FQTSS.
-- =====

-- =====
-- the ieee8021FqtssBapTable
-- =====

ieee8021FqtssBapTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Ieee8021FqtssBapEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A table containing a set of bandwidth availability
        parameters for each traffic class that supports the
        credit-based shaper algorithm.
        All writable objects in this table must be
        persistent over power up restart/reboot."
    REFERENCE   "12.20.1"
    ::= { ieee8021FqtssBap 1 }

ieee8021FqtssBapEntry OBJECT-TYPE
    SYNTAX      Ieee8021FqtssBapEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A list of objects containing bandwidth allocation
        information for each traffic class that supports the
        credit-based shaper algorithm. Rows in the table are

```

IEEE Std 802.1Q™-2014/Cor 1-2015
 IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks—
 Corrigendum 1: Technical and editorial corrections

automatically created and deleted as a result of the operation of the algorithm described in 34.5. "

```

INDEX { ieee8021BridgeBaseComponentId,
        ieee8021BridgeBasePort,
        ieee8021FqtssBAPTrafficClass }
 ::= { ieee8021FqtssBapTable 1 }

```

```

Ieee8021FqtssBapEntry ::=
SEQUENCE {
    ieee8021FqtssBAPTrafficClass
        IEEE8021FqtssTrafficClassValue,
    ieee8021FqtssDeltaBandwidth
        IEEE8021FqtssDeltaBandwidthValue,
    ieee8021FqtssOperIdleSlopeMs
        Unsigned32,
    ieee8021FqtssOperIdleSlopeLs
        Unsigned32,
    ieee8021FqtssAdminIdleSlopeMs
        Unsigned32,
    ieee8021FqtssAdminIdleSlopeLs
        Unsigned32,
    ieee8021FqtssBapRowStatus
        RowStatus
}

```

```

ieee8021FqtssBAPTrafficClass OBJECT-TYPE
SYNTAX      IEEE8021FqtssTrafficClassValue
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The traffic class number associated with the row of
    the table.

    A row in this table is created for each traffic class
    that supports the credit-based shaper algorithm. The
    recommended mappings of priorities to traffic classes
    for support of the credit-based shaper algorithm are
    described in 34.5."
REFERENCE   "12.20.2, 34.3, 34.5"
 ::= { ieee8021FqtssBapTable 1 }

```

```

ieee8021FqtssDeltaBandwidth OBJECT-TYPE
SYNTAX      IEEE8021FqtssDeltaBandwidthValue
UNITS       "percent"
MAX-ACCESS  read-write
STATUS      current
DESCRIPTION
    "The value of the deltaBandwidth parameter
    for the traffic class.
    This value is represented as a fixed point number
    scaled by a factor of 1,000,000; i.e., 100,000,000
    (the maximum value) represents 100%.

    The default value of the deltaBandwidth parameter
    for the highest numbered traffic class that supports
    the credit-based shaper algorithm is 75%; for all
    lower numbered traffic classes that support the
    credit-based shaper algorithm the default value is 0%."

```

The value of this object MUST be retained across reinitializations of the management system."

REFERENCE "12.20.1, 34.3"
::= { ieee8021FqtssBapEntry 2 }

ieee8021FqtssOperIdleSlopeMs OBJECT-TYPE

SYNTAX Unsigned32

UNITS "bits per second"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The most significant 32 bits of the bandwidth, in bits per second, that is currently allocated to the traffic class (idleSlope(N)). This object MUST be read at the same time as ieee8021FqtssOperIdleSlopeLs, which represents the LS 32 bits of the value, in order for the read operation to succeed.

If SRP is supported and in operation, then the reserved bandwidth is determined by the operation of SRP; otherwise, the value of ieee8021FqtssOperIdleSlopeMs is equal to the value of ieee8021FqtssAdminIdleSlopeMs.

The value of this object MUST be retained across reinitializations of the management system."

REFERENCE "12.20.1, 34.3"
::= { ieee8021FqtssBapEntry 3 }

ieee8021FqtssOperIdleSlopeLs OBJECT-TYPE

SYNTAX Unsigned32

UNITS "bits per second"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The least significant 32 bits of the bandwidth, in bits per second, that is currently allocated to the traffic class (idleSlope(N)). This object MUST be read at the same time as ieee8021FqtssOperIdleSlopeMs, which represents the LS 32 bits of the value, in order for the read operation to succeed.

If SRP is supported and in operation, then the reserved bandwidth is determined by the operation of SRP; otherwise, the value of ieee8021FqtssOperIdleSlopeLs is equal to the value of ieee8021FqtssAdminIdleSlopeMs.

The value of this object MUST be retained across reinitializations of the management system."

REFERENCE "12.20.1, 34.3"
::= { ieee8021FqtssBapEntry 4 }

ieee8021FqtssAdminIdleSlopeMs OBJECT-TYPE

SYNTAX Unsigned32

UNITS "bits per second"

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The most significant 32 bits of the bandwidth,

IEEE Std 802.1Q™-2014/Cor 1-2015
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks—
Corrigendum 1: Technical and editorial corrections

in bits per second, that the manager desires to allocate to the traffic class as `idleSlope(N)`. This object MUST be read or written at the same time as `ieee8021FqtssAdminIdleSlopeLs`, which represents the LS 32 bits of the value, in order for the read or write operation to succeed.

If SRP is supported and in operation, then the reserved bandwidth is determined by the operation of SRP, and any changes to the value of this object have no effect on the operational value of `idleSlope(N)`.

The value of this object MUST be retained across reinitializations of the management system."

REFERENCE "12.20.1, 34.3"

DEFVAL { 0 }

::= { ieee8021FqtssBapEntry 5 }

`ieee8021FqtssAdminIdleSlopeLs` OBJECT-TYPE

SYNTAX Unsigned32

UNITS "bits per second"

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The least significant 32 bits of the bandwidth, in bits per second, that the manager desires to allocate to the traffic class as `idleSlope(N)`. This object MUST be read or written at the same time as `ieee8021FqtssAdminIdleSlopeMs`, which represents the LS 32 bits of the value, in order for the read or write operation to succeed.

If SRP is supported and in operation, then the reserved bandwidth is determined by the operation of SRP, and any changes to the value of this object have no effect on the operational value of `idleSlope(N)`.

The value of this object MUST be retained across reinitializations of the management system."

REFERENCE "12.20.1, 34.3"

DEFVAL { 0 }

::= { ieee8021FqtssBapEntry 6 }

`ieee8021FqtssBapRowStatus` OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"Indicates the status of an entry (row) in this table, and is used to create/delete entries.

The corresponding instances of the following objects must be set before this object can be made active(1):

`ieee8021FqtssBAPTrafficClass`

`ieee8021FqtssDeltaBandwidth`

`ieee8021FqtssOperIdleSlopeMs`

`ieee8021FqtssOperIdleSlopeLs`

`ieee8021FqtssAdminIdleSlopeMs`

`ieee8021FqtssAdminIdleSlopeLs`

The corresponding instances of the following objects may not be changed while this object is active(1):

```

ieee8021FqtssBAPTrafficClass"
::= { ieee8021FqtssBapEntry 7 }

-- =====
-- The ieee8021FqtssMappings subtree
-- This subtree defines the objects necessary for the assignment
-- of transmission selection algorithms to traffic classes,
-- and definition of regeneration table override values.
-- =====

-- =====
-- the ieee8021FqtssTxSelectionAlgorithmTable
-- =====

ieee8021FqtssTxSelectionAlgorithmTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Ieee8021FqtssTxSelectionAlgorithmEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A table containing the assignment of transmission
        selection algorithms to traffic classes for the Port.
        This table provides management of the Transmission
        Selection Algorithm Table defined in 8.6.8.

        For a given Port, a row in the table exists for each
        traffic class that is supported by the Port.

        The default assignments of transmission selection
        algorithms to traffic classes in the table are made
        on instantiation of the table, in accordance
        with the defaults defined in 8.6.8 and 34.5.

        All writable objects in this table must be
        persistent over power up restart/reboot."
    REFERENCE   "8.6.8, 12.20.2, 34.5"
    ::= { ieee8021FqtssMappings 1 }

ieee8021FqtssTxSelectionAlgorithmEntry OBJECT-TYPE
    SYNTAX      Ieee8021FqtssTxSelectionAlgorithmEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A list of objects that contain the mapping of a
        traffic class value to a transmission selection algorithm
        value."
    INDEX { ieee8021BridgeBaseComponentId,
            ieee8021BridgeBasePort,
            ieee8021FqtssTrafficClass }
    ::= { ieee8021FqtssTxSelectionAlgorithmTable 1 }

Ieee8021FqtssTxSelectionAlgorithmEntry ::=
    SEQUENCE {
        ieee8021FqtssTrafficClass
            IEEE8021FqtssTrafficClassValue,
        ieee8021FqtssTxSelectionAlgorithmID
            IEEE8021FqtssTxSelectionAlgorithmIDValue
    }

```

IEEE Std 802.1Q™-2014/Cor 1-2015
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks—
Corrigendum 1: Technical and editorial corrections

}

ieee8021FqtssTrafficClass OBJECT-TYPE

SYNTAX IEEE8021FqtssTrafficClassValue

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The traffic class to which the transmission selection algorithm is assigned.

The value of this object MUST be retained across reinitializations of the management system."

REFERENCE "8.6.8, 12.20.2, 34.5"

::= { ieee8021FqtssTxSelectionAlgorithmEntry 1 }

ieee8021FqtssTxSelectionAlgorithmID OBJECT-TYPE

SYNTAX IEEE8021FqtssTxSelectionAlgorithmIDValue

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The identifier of the transmission selection algorithm assigned to the traffic class.

The value of this object MUST be retained across reinitializations of the management system."

REFERENCE "8.6.8, 12.20.2, 34.5"

::= { ieee8021FqtssTxSelectionAlgorithmEntry 2 }

```
-- =====
-- the ieee8021FqtssSrpRegenOverrideTable
-- =====
```

ieee8021FqtssSrpRegenOverrideTable OBJECT-TYPE

SYNTAX SEQUENCE OF Ieee8021FqtssSrpRegenOverrideEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A table containing the set of priority regeneration table override values for the Port.

The recommended default values of priorities associated with SR classes, and the corresponding override values, are defined in 6.9.4.

All writable objects in this table must be persistent over power up restart/reboot."

REFERENCE "35.1.4, 6.9.4, 12.20.3"

::= { ieee8021FqtssMappings 2 }

ieee8021FqtssSrpRegenOverrideEntry OBJECT-TYPE

SYNTAX Ieee8021FqtssSrpRegenOverrideEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A list of objects that contain the mapping of a priority value to a priority regeneration override value, and a boundary port indication.

Rows in the table exist for all priorities that are

```

    associated with SR classes."
INDEX { ieee8021BridgeBaseComponentId,
        ieee8021BridgeBasePort,
        ieee8021FqtssSrClassPriority }
 ::= { ieee8021FqtssSrpRegenOverrideTable 1 }

Ieee8021FqtssSrpRegenOverrideEntry ::=
SEQUENCE {
    ieee8021FqtssSrClassPriority
        IEEE8021PriorityValue,
    ieee8021FqtssPriorityRegenOverride
        IEEE8021PriorityValue,
    ieee8021FqtssSrpBoundaryPort
        TruthValue
}

ieee8021FqtssSrClassPriority OBJECT-TYPE
SYNTAX      IEEE8021PriorityValue
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The priority value that is overridden at the
    SRP domain boundary. "
REFERENCE   "35.1.4, 6.9.4, 12.20.3"
 ::= { ieee8021FqtssSrpRegenOverrideEntry 1 }

ieee8021FqtssPriorityRegenOverride OBJECT-TYPE
SYNTAX      IEEE8021PriorityValue
MAX-ACCESS  read-write
STATUS      current
DESCRIPTION
    "The priority value that is used to override the
    priority regeneration table entry at the SRP
    domain boundary.

    The value of this object MUST be retained across
    reinitializations of the management system."
REFERENCE   "35.1.4, 6.9.4, 12.20.3"
 ::= { ieee8021FqtssSrpRegenOverrideEntry 2 }

ieee8021FqtssSrpBoundaryPort OBJECT-TYPE
SYNTAX      TruthValue
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The value of the SRPdomainBoundaryPort parameter
    (35.1.4) for the priority. "
REFERENCE   "35.1.4, 6.9.4, 12.20.3"
 ::= { ieee8021FqtssSrpRegenOverrideEntry 3 }

-- =====
-- IEEE8021 FQTSS MIB - Conformance Information
-- =====

ieee8021FqtssCompliances
    OBJECT IDENTIFIER ::= { ieee8021FqtssConformance 1 }
ieee8021FqtssGroups
    OBJECT IDENTIFIER ::= { ieee8021FqtssConformance 2 }

```

IEEE Std 802.1Q™-2014/Cor 1-2015
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks—
Corrigendum 1: Technical and editorial corrections

```
-- =====
-- units of conformance
-- =====

-- =====
-- the ieee8021FqtssBap group
-- =====

ieee8021FqtssBapGroup OBJECT-GROUP
    OBJECTS {
        ieee8021FqtssDeltaBandwidth,
        ieee8021FqtssOperIdleSlopeMs,
        ieee8021FqtssOperIdleSlopeLs,
        ieee8021FqtssAdminIdleSlopeMs,
        ieee8021FqtssAdminIdleSlopeLs,
        ieee8021FqtssBapRowStatus
    }
    STATUS      current
    DESCRIPTION
        "Objects that define bandwidth allocation for FQTSS."
    ::= { ieee8021FqtssGroups 1 }

-- =====
-- the ieee8021FqtssTxSelectionAlgorithm group
-- =====

ieee8021FqtssTxSelectionAlgorithmGroup OBJECT-GROUP
    OBJECTS {
        ieee8021FqtssTxSelectionAlgorithmID
    }
    STATUS      current
    DESCRIPTION
        "Objects that define transmission selection
        mappings for FQTSS."
    ::= { ieee8021FqtssGroups 2 }

-- =====
-- the ieee8021FqtssBoundaryPort group
-- =====

ieee8021FqtssBoundaryPortGroup OBJECT-GROUP
    OBJECTS {
        ieee8021FqtssPriorityRegenOverride,
        ieee8021FqtssSrpBoundaryPort
    }
    STATUS      current
    DESCRIPTION
        "Objects that define boundary port priority override
        mappings for FQTSS."
    ::= { ieee8021FqtssGroups 3 }

-- =====
-- compliance statements
-- =====

ieee8021FqtssCompliance MODULE-COMPLIANCE
    STATUS      current
    DESCRIPTION
```

IEEE Std 802.1Q™-2014/Cor 1-2015
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks—
Corrigendum 1: Technical and editorial corrections

"The compliance statement for devices supporting forwarding and queuing for time sensitive streams.

Support of the objects defined in the IEEE8021-FQTSS MIB also requires support of the IEEE8021-BRIDGE-MIB; the provisions of 17.3.2 apply to implementations claiming support of the IEEE8021-FQTSS MIB. "

```
MODULE -- this module
  MANDATORY-GROUPS {
    ieee8021FqtssBapGroup,
    ieee8021FqtssTxSelectionAlgorithmGroup,
    ieee8021FqtssBoundaryPortGroup
  }

  ::= { ieee8021FqtssCompliances 1 }
```

END

IEEE Std 802.1Q™-2014/Cor 1-2015
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks—
Corrigendum 1: Technical and editorial corrections

17.7.14 Definitions for the IEEE8021-SRP-MIB module

Replace the text of 17.7.14 with the following:

```
IEEE8021-SRP-MIB DEFINITIONS ::= BEGIN

-- =====
-- MIB for support of 802.1Qat Stream Reservation Protocol
-- (SRP) in 802.1Q Bridges.
-- =====

IMPORTS
    MODULE-IDENTITY,
    OBJECT-TYPE,
    Counter64,
    Unsigned32
        FROM SNMPv2-SMI
    MacAddress,
    TEXTUAL-CONVENTION,
    TruthValue
        FROM SNMPv2-TC
    MODULE-COMPLIANCE,
    OBJECT-GROUP
        FROM SNMPv2-CONF
    ieee802dot1mibs,
    IEEE8021PriorityCodePoint,
    IEEE8021VlanIndex
        FROM IEEE8021-TC-MIB
    IEEE8021FqtssTrafficClassValue
        FROM IEEE8021-FQTSS-MIB
    ieee8021BridgeBaseComponentId,
    ieee8021BridgeBaseEntry,
    ieee8021BridgeBasePort,
    ieee8021BridgeBasePortEntry
        FROM IEEE8021-BRIDGE-MIB
;

ieee8021SrpMib MODULE-IDENTITY
    LAST-UPDATED "201512020000Z" -- December 2, 2015
    ORGANIZATION "IEEE 802.1 Working Group"
    CONTACT-INFO
        "WG-URL: http://ieee802.org/1/
        WG-Email: STDS-802-1-L@LISTSERV.IEEE.ORG

        Contact: IEEE 802.1 Working Group Chair
        Postal: C/O IEEE 802.1 Working Group
                IEEE Standards Association
                445 Hoes Lane
                Piscataway
                NJ 08854
                USA
        E-mail: STDS-802-1-L@LISTSERV.IEEE.ORG"
    DESCRIPTION
        "The Bridge MIB module for managing devices that support
        the IEEE Std 802.1Q Stream Reservation Protocol.

        Unless otherwise indicated, the references in this MIB
```

IEEE Std 802.1Q™-2014/Cor 1-2015
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks—
Corrigendum 1: Technical and editorial corrections

module are to IEEE Std 802.1Q-2014.

Copyright (C) IEEE (2015).

This version of this MIB module is part of IEEE802.1Q;
see the draft itself for full legal notices."

REVISION "201512020000Z" -- December 2, 2015

DESCRIPTION

"Published as part of IEEE Std 802.1Q-2014 Cor-1.
ieee8021SrpReservationFailureBridgeId changed to
ieee8021SrpReservationFailureSystemId."

REVISION "201412150000Z" -- December 15, 2014

DESCRIPTION

"Published as part of IEEE Std 802.1Q 2014 revision.
Cross references updated and corrected."

REVISION "201102270000Z" -- February 27, 2011

DESCRIPTION

"Minor edits to contact information etc. as part of
2011 revision of Std 802.1Q."

REVISION "201004190000Z" -- April 19, 2010

DESCRIPTION

"Initial revision, included in IEEE 802.1Qat"
::= { ieee802dot1mibs 19 }

-- =====
-- Textual Conventions
-- =====

IEEE8021SrpStreamRankValue ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"An 802.1 SRP Stream Rank value. This is an integer,
with the following interpretation placed on the value:

0: Emergency, high-rank stream,
1: Non-emergency stream."

REFERENCE "35.2.2.8.5b"

SYNTAX INTEGER {
 emergency(0),
 nonEmergency(1)
}

IEEE8021SrpStreamIdValue ::= TEXTUAL-CONVENTION

DISPLAY-HINT "1x:1x:1x:1x:1x:1x:1x:1x"

STATUS current

DESCRIPTION

"Represents an SRP Stream ID, which is often defined
as a MAC Address followed by a unique 16-bit ID."

SYNTAX OCTET STRING (SIZE (8))

IEEE8021SrpReservationDirectionValue ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"An 802.1 SRP Stream Reservation Direction value. This is
an integer, with the following interpretation placed on

IEEE Std 802.1Q™-2014/Cor 1-2015
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks—
Corrigendum 1: Technical and editorial corrections

the value:

```

0: Talker registrations,
1: Listener registrations."
REFERENCE      "35.2.1.2"
SYNTAX         INTEGER {
                    talkerRegistrations(0),
                    listenerRegistrations(1)
                }

```

IEEE8021SrpReservationDeclarationTypeValue ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"An 802.1 SRP Stream Reservation Declaration Type value.
This is an integer, with the following interpretation
placed on the value:

```

0: Talker Advertise,
1: Talker Failed,
2: Listener Asking Failed,
3: Listener Ready,
4: Listener Ready Failed."
REFERENCE      "35.2.1.3"
SYNTAX         INTEGER {
                    talkerAdvertise(0),
                    talkerFailed(1),
                    listenerAskingFailed(2),
                    listenerReady(3),
                    listenerReadyFailed(4)
                }

```

IEEE8021SrpReservationFailureCodeValue ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"An 802.1 SRP Stream Reservation Failure Code value.
This is an integer, with the following interpretation
placed on the value:

```

0: No failure,
1: Insufficient bandwidth,
2: Insufficient Bridge resources,
3: Insufficient bandwidth for Traffic Class,
4: StreamID in use by another Talker,
5: Stream destination address already in use,
6: Stream pre-empted by higher rank,
7: Reported latency has changed,
8: Egress port is not AVBCapable,
9: Use a different destination_address,
10: Out of MSRP resources,
11: Out of MMRP resources,
12: Cannot store destination_address,
13: Requested priority is not an SR Class priority,
14: MaxFrameSize is too large for media,
15: maxFanInPorts limit has been reached,
16: Changes in FirstValue for a registered StreamID,
17: VLAN is blocked on this egress port (Registration Forbidden),

```

IEEE Std 802.1Q™-2014/Cor 1-2015 IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks— Corrigendum 1: Technical and editorial corrections

```

18: VLAN tagging is disabled on this egress port (untagged set),
19: SR class priority mismatch."
REFERENCE      "35.2.2.8.7"
SYNTAX         INTEGER {
                    noFailure(0),
                    insufficientBandwidth(1),
                    insufficientResources(2),
                    insufficientTrafficClassBandwidth(3),
                    streamIDInUse(4),
                    streamDestinationAddressInUse(5),
                    streamPreemptedByHigherRank(6),
                    latencyHasChanged(7),
                    egressPortNotAVBCapable(8),
                    useDifferentDestinationAddress(9),
                    outOfMSRPResources(10),
                    outOfMMRPResources(11),
                    cannotStoreDestinationAddress(12),
                    priorityIsNoAnSRClass(13),
                    maxFrameSizeTooLarge(14),
                    maxFanInPortsLimitReached(15),
                    firstValueChangedForStreamID(16),
                    vlanBlockedOnEgress(17),
                    vlanTaggingDisabledOnEgress(18),
                    srClassPriorityMismatch(19)
                }

```

```

-- =====
-- subtrees in the SRP MIB
-- =====

ieee8021SrpNotifications
    OBJECT IDENTIFIER ::= { ieee8021SrpMib 0 }

ieee8021SrpObjects
    OBJECT IDENTIFIER ::= { ieee8021SrpMib 1 }

ieee8021SrpConformance
    OBJECT IDENTIFIER ::= { ieee8021SrpMib 2 }

ieee8021SrpConfiguration
    OBJECT IDENTIFIER ::= { ieee8021SrpObjects 1 }

ieee8021SrpLatency
    OBJECT IDENTIFIER ::= { ieee8021SrpObjects 2 }

ieee8021SrpStreams
    OBJECT IDENTIFIER ::= { ieee8021SrpObjects 3 }

ieee8021SrpReservations
    OBJECT IDENTIFIER ::= { ieee8021SrpObjects 4 }

-- =====
-- The ieee8021SrpConfiguration subtree
-- This subtree defines the objects necessary for the
-- operational management of SRP.
-- =====

```

IEEE Std 802.1Q™-2014/Cor 1-2015
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks—
Corrigendum 1: Technical and editorial corrections

```

ieee8021SrpBridgeBaseTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Ieee8021SrpBridgeBaseEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A table for SRP main control and status information.
        All writeable objects in this table must be persistent
        over power up restart/reboot. These objects augment
        the ieee8021BridgeBasePortTable."
    ::= { ieee8021SrpConfiguration 1 }

ieee8021SrpBridgeBaseEntry OBJECT-TYPE
    SYNTAX      Ieee8021SrpBridgeBaseEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "SRP control and status information for a Bridge."
    AUGMENTS { ieee8021BridgeBaseEntry }
    ::= { ieee8021SrpBridgeBaseTable 1 }

Ieee8021SrpBridgeBaseEntry ::=
    SEQUENCE {
        ieee8021SrpBridgeBaseMsrpEnabledStatus
            TruthValue,
        ieee8021SrpBridgeBaseMsrpTalkerPruning
            TruthValue,
        ieee8021SrpBridgeBaseMsrpMaxFanInPorts
            Unsigned32,
        ieee8021SrpBridgeBaseMsrpLatencyMaxFrameSize
            Unsigned32
    }

ieee8021SrpBridgeBaseMsrpEnabledStatus OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The administrative status requested by management for
        MSRP. The value true(1) indicates that MSRP should
        be enabled on this device, in all VLANs, on all ports
        for which it has not been specifically disabled. When
        false(2), MSRP is disabled, in all VLANs and on all
        ports, and all MSRP frames will be forwarded
        transparently. This objects affects both Applicant and
        Registrar state machines. A transition from false(2)
        to true(1) will cause a reset of all MSRP state
        machines on all ports.

        This object may be modified while the corresponding
        instance of ieee8021BridgeBaseRowStatus is active(1).

        The value of this object MUST be retained across
        reinitializations of the management system."
    REFERENCE   "35.2.1.4d"
    DEFVAL      { true }
    ::= { ieee8021SrpBridgeBaseEntry 1 }

ieee8021SrpBridgeBaseMsrpTalkerPruning OBJECT-TYPE

```

IEEE Std 802.1Q™-2014/Cor 1-2015
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks—
Corrigendum 1: Technical and editorial corrections

SYNTAX TruthValue
MAX-ACCESS read-create
STATUS current

DESCRIPTION

"The value of the talkerPruning parameter which controls the propagation of Talker declarations. The value true(1) indicates that Talker attributes are only declared on ports that have the Stream destination_address registered in the MMRP MAC Address Registration Entries. When false(2), Talker attribute are declared on all egress ports in the active topology.

The value of this object MUST be retained across reinitializations of the management system."

REFERENCE "12.22.1, 35.2.1.4b, 35.2.4.3.1"

DEFVAL { false }

::= { ieee8021SrpBridgeBaseEntry 2 }

ieee8021SrpBridgeBaseMsrpMaxFanInPorts OBJECT-TYPE

SYNTAX Unsigned32
MAX-ACCESS read-create
STATUS current

DESCRIPTION

"The value of the msrpMaxFanInPorts parameter which limits the total number of ports on a Bridge that are allowed to establish reservations for inbound Streams. A value of zero (0) indicates no fan-in limit is being specified and calculations involving fan-in will only be limited by the number of MSRP enabled ports.

The value of this object MUST be retained across reinitializations of the management system."

REFERENCE "12.22.1, 35.2.1.4f"

DEFVAL { 0 }

::= { ieee8021SrpBridgeBaseEntry 3 }

ieee8021SrpBridgeBaseMsrpLatencyMaxFrameSize OBJECT-TYPE

SYNTAX Unsigned32
MAX-ACCESS read-create
STATUS current

DESCRIPTION

"The value of msrpLatencyMaxFrameSize parameter which is used in the calculation of the maximum latency through a Bridge. The maximum size is defined to be 2000 octets by default, but may be set to a smaller or larger value dependent on the particular Bridge configuration. This parameter does not imply any type of policing of frame size, it is only used in the latency calculations.

The value of this object MUST be retained across reinitializations of the management system."

REFERENCE "12.22.1, 35.2.1.4g"

DEFVAL { 2000 }

::= { ieee8021SrpBridgeBaseEntry 4 }

IEEE Std 802.1Q™-2014/Cor 1-2015
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks—
Corrigendum 1: Technical and editorial corrections

```

ieee8021SrpBridgePortTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Ieee8021SrpBridgePortEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A table for SRP control and status information about
        every Bridge Port. Augments the ieee8021BridgeBasePortTable."
    ::= { ieee8021SrpConfiguration 2 }

ieee8021SrpBridgePortEntry OBJECT-TYPE
    SYNTAX      Ieee8021SrpBridgePortEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "SRP control and status information for a Bridge Port."
    AUGMENTS { ieee8021BridgeBasePortEntry }
    ::= { ieee8021SrpBridgePortTable 1 }

Ieee8021SrpBridgePortEntry ::=
    SEQUENCE {
        ieee8021SrpBridgePortMsrpEnabledStatus
            TruthValue,
        ieee8021SrpBridgePortMsrpFailedRegistrations
            Counter64,
        ieee8021SrpBridgePortMsrpLastPduOrigin
            MacAddress,
        ieee8021SrpBridgePortSrPvid
            IEEE8021VlanIndex
    }

ieee8021SrpBridgePortMsrpEnabledStatus OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The administrative state of MSRP operation on this port. The
        value true(1) indicates that MSRP is enabled on this port
        in all VLANs as long as ieee8021BridgeMsrpEnabledStatus is
        also true(1). A value of false(2) indicates that MSRP is
        disabled on this port in all VLANs: any MSRP frames received
        will be silently discarded, and no MSRP registrations will be
        propagated from other ports. Setting this to a value of
        true(1) will be stored by the agent but will only take
        effect on the MSRP protocol operation if
        ieee8021BridgeMsrpEnabledStatus
        also indicates the value true(1). This object affects
        all MSRP Applicant and Registrar state machines on this
        port. A transition from false(2) to true(1) will
        cause a reset of all MSRP state machines on this port.

        The value of this object MUST be retained across
        reinitializations of the management system."
    REFERENCE   "35.2.1.4e"
    DEFVAL      { true }
    ::= { ieee8021SrpBridgePortEntry 1 }

ieee8021SrpBridgePortMsrpFailedRegistrations OBJECT-TYPE
    SYNTAX      Counter64

```

IEEE Std 802.1Q™-2014/Cor 1-2015 IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks— Corrigendum 1: Technical and editorial corrections

UNITS "failed MSRP registrations"

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The total number of failed MSRP registrations, for any reason, in all VLANs, on this port.

Discontinuities in the value of the counter can occur at re-initialization of the management system, and at other times as indicated by the value of ifCounterDiscontinuityTime object of the associated interface (if any)."

REFERENCE "10.7.12.1"

::= { ieee8021SrpBridgePortEntry 2 }

ieee8021SrpBridgePortMsrpLastPduOrigin OBJECT-TYPE

SYNTAX MacAddress

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The Source MAC Address of the last MSRP message received on this port."

REFERENCE "10.7.12.2"

::= { ieee8021SrpBridgePortEntry 3 }

ieee8021SrpBridgePortSrPvid OBJECT-TYPE

SYNTAX IEEE8021VlanIndex

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The default VLAN ID that Streams are assigned to. Talkers learn this VID from the SRP Domain attribute and tag Streams accordingly.

The value of this object MUST be retained across reinitializations of the management system."

REFERENCE "35.2.2.8.3b"

DEFVAL { 2 }

::= { ieee8021SrpBridgePortEntry 4 }

```
-- =====
-- The ieee8021SrpLatency subtree
-- This subtree defines the objects necessary for retrieving
-- the latency of the various traffic classes on a port.
-- =====
```

```
-- =====
-- the ieee8021SrpLatencyTable
-- =====
```

ieee8021SrpLatencyTable OBJECT-TYPE

SYNTAX SEQUENCE OF Ieee8021SrpLatencyEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A table containing a set of latency measurement parameters for each traffic class."

REFERENCE "35.2.2.8.6"

::= { ieee8021SrpLatency 1 }