

INTERNATIONAL
STANDARD

ISO/IEC/
IEEE
8802-1Q

Second edition
2020-08

AMENDMENT 2
2021-09

**Telecommunications and exchange
between information technology
systems — Requirements for local and
metropolitan area networks —**

**Part 1Q:
Bridges and bridged networks**

AMENDMENT 2: YANG data model

*Télécommunications et échange entre systèmes informatiques —
Exigences pour les réseaux locaux et métropolitains —*

Partie 1Q: Ponts et réseaux pontés

AMENDEMENT 2



Reference number
ISO/IEC/IEEE 8802-1Q:2020/Amd.2:2021(E)

AVA Documents
Document Sharing Hub
© IEEE 2018



COPYRIGHT PROTECTED DOCUMENT

© IEEE 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from IEEE at the address below.

Institute of Electrical and Electronics Engineers, Inc
3 Park Avenue, New York
NY 10016-5997, USA

Email: stds.ipr@ieee.org
Website: www.ieee.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO/IEC documents should be noted.

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see patents.iec.ch).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

ISO/IEC/IEEE 8802-1Q:2020/Amd 2 was prepared by the LAN/MAN of the IEEE Computer Society (as IEEE Std 802.1Qcp-2018) and drafted in accordance with its editorial rules. It was adopted, under the “fast-track procedure” defined in the Partner Standards Development Organization cooperation agreement between ISO and IEEE, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*.

A list of all parts in the ISO/IEC/IEEE 8802 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

IEEE Std 802.1Qcp™-2018
(Amendment to
IEEE Std 802.1Q™-2018)

**IEEE Standard for
Local and metropolitan area networks—
Bridges and Bridged Networks—
Amendment 30: YANG Data Model**

Sponsor

**LAN/MAN Standards Committee
of the
IEEE Computer Society**

Approved 14 June 2018

IEEE-SA Standards Board

Abstract: A YANG data model in support of configuration and operational status information for a subset of Bridging capabilities is provided in this amendment to IEEE Std 802.1Q™-2018.

Keywords: Bridged Local Area Networks, IEEE 802®, IEEE 802.1Q™, IEEE 802.1Qcp™, local area networks (LANs), MAC Bridges, metropolitan area networks, Virtual Bridged Local Area Networks (virtual LANs), YANG

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2018 by The Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 14 September 2018. Printed in the United States of America.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-1-5044-4927-4 STD23138
Print: ISBN 978-1-5044-4928-1 STDPD23138

IEEE prohibits discrimination, harassment, and bullying.

For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading “Important Notices and Disclaimers Concerning IEEE Standards Documents.” They can also be obtained on request from IEEE or viewed at <http://standards.ieee.org/IPR/disclaimers.html>.

Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents (standards, recommended practices, and guides), both full-use and trial-use, are developed within IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (“IEEE-SA”) Standards Board. IEEE (“the Institute”) develops its standards through a consensus development process, approved by the American National Standards Institute (“ANSI”), which brings together volunteers representing varied viewpoints and interests to achieve the final product. IEEE Standards are documents developed through scientific, academic, and industry-based technical working groups. Volunteers in IEEE working groups are not necessarily members of the Institute and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers and users of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims all warranties (express, implied and statutory) not included in this or any other document relating to the standard, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, IEEE disclaims any and all conditions relating to: results; and workmanlike effort. IEEE standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

Official statements

A statement, written or oral, that is not processed in accordance with the IEEE-SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, or be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in revisions to an IEEE standard is welcome to join the relevant IEEE working group.

Comments on standards should be submitted to the following address:

Secretary, IEEE-SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854 USA

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

IEEE draft and approved standards are copyrighted by IEEE under U.S. and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

Photocopies

Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. A current IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE-SA Website at <http://ieeexplore.ieee.org/> or contact IEEE at the address listed previously. For more information about the IEEE-SA or IEEE's standards development process, visit the IEEE-SA Website at <http://standards.ieee.org>.

Errata

Errata, if any, for all IEEE standards can be accessed on the IEEE-SA Website at the following URL: <http://standards.ieee.org/findstds/errata/index.html>. Users are encouraged to check this URL for errata periodically.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE-SA Website at <http://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

Participants

At the time of approval of this standard, the IEEE 802.1 Working Group had the following membership:

Glenn Parsons, *Chair*
John Messenger, *Vice Chair*
János Farkas, *Chair, Time-Sensitive Networking Task Group*
Marc Holness, *Editor*

Ralf Assmann	Marina Gutierrez	Maximilian Riegel
Shenghua Bao	Stephen Haddock	Jessy V. Rouyer
Jens Bierschenk	Mark Hantel	Atsushi Sato
Steinar Bjornstad	Lokesh Kabra	Frank Schewe
Christian Boiger	Michael Karl	Michael Seaman
Paul Bottorff	Stephan Kehrer	Johannes Specht
Radhakrishna Canchi	Hajime Koto	Patricia Thaler
David Chen	Christophe Mangin	Paul Unbehagen
Feng Chen	Scott Mansfield	Xinyuan Wang
Weiyang Cheng	James McIntosh	Tongtong Wang
Paul Congdon	Tero Mustala	Hao Wang
Rodney Cummings	Tomoki Ohsawa	Karl Weber
Hesham Elbakoury	Donald R. Pannell	Brian Weis
Norman Finn	Walter Pienciak	Jordon Woods
Geoffrey Garner	Michael Potts	Takahiro Yamaura
Eric W. Gray	Wei Qiu	Xiang Yu
Craig Gunther	Karen Randall	Nader Zein

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Thomas Alexander	Randall Groves	Charles Moorwood
Richard Alfvén	Stephen Haddock	Nick S. A. Nikjoo
Butch Anton	Mark Hantel	Paul Nikolich
Stefan Aust	Marco Hernandez	Satoshi Obara
Gordon Bechtel	Werner Hoelzl	Bansi Patel
David Black	Noriyuki Ikeuchi	Alon Regev
Christian Boiger	Atsushi Ito	Maximilian Riegel
Nancy Bravin	Raj Jain	Robert Robinson
Dietmar Bruckner	SangKwon Jeong	Benjamin Rolfe
Demetrio Bucaneg, Jr.	Peter Jones	Jessy V. Rouyer
Stephen Bush	Piotr Karocki	Michael Seaman
William Byrd	Stephan Kehrer	Daniel Smith
Juan Carreon	Stuart Kerry	Thomas Starai
Keith Chow	Yongbum Kim	Walter Struppler
Charles Cook	Hyeong Ho Lee	Mark-Rene Uchida
Rodney Cummings	James Lepp	Dmitri Varsanofiev
Sourav Dutta	Jon Lewis	George Vlantis
János Farkas	Michael Lynch	Khurram Waheed
Norman Finn	Elvis Maculuba	Andreas Wolf
Avraham Freedman	Arthur Marris	Chun Yu Charles Wong
Eric W. Gray	Richard Mellitz	Oren Yuen
		Zhen Zhou

When the IEEE-SA Standards Board approved this standard on 14 June 2018, it had the following membership:

Jean-Philippe Faure, *Chair*
Gary Hoffman, *Vice Chair*
John D. Kulick, *Past Chair*
Konstantinos Karachalios, *Secretary*

Chuck Adams
Masayuki Ariyoshi
Ted Burse
Stephen Dukes
Doug Edwards
J. Travis Griffith
Michael Janezic

Thomas Koshy
Joseph L. Koepfinger*
Kevin Lu
Daleep Mohla
Damir Novosel
Ronald C. Petersen
Annette D. Reilly

Robby Robson
Dorothy Stanley
Adrian Stephens
Mehmet Ulema
Phil Wennblom
Howard Wolfman
Yu Yuan

*Member Emeritus

Introduction

This introduction is not part of IEEE Std 802.1Qcp-2018, IEEE Standard for Local and metropolitan area networks—Bridges and Bridged Networks—Amendment 30: YANG Data Model.

This amendment to IEEE Std 802.1Q-2018 specifies a YANG data model that provides configuration and operational status reporting for IEEE 802.1Q Two-Port MAC Relay, Customer VLAN Bridges, and Provider Bridges.

This standard contains state-of-the-art material. The area covered by this standard is undergoing evolution. Revisions are anticipated within the next few years to clarify existing material, to correct possible errors, and to incorporate new related material. Information on the current revision state of this and other IEEE 802[®] standards may be obtained from

Secretary, IEEE-SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854
USA

Contents

1.	Overview	12
1.3	Introduction.....	12
2.	Normative references	13
4.	Abbreviations	14
5.	Conformance	15
5.4	VLAN Bridge component requirements.....	15
5.13	MAC Bridge component requirements	15
5.16	TPMR conformance.....	15
8.	Principles of Bridge operation	16
8.12	Bridge Management Entity	16
8.13	Addressing	16
12.	Bridge management	17
12.10	Bridge VLAN managed objects.....	17
48.	YANG Data Model	18
48.1	YANG Framework.....	18
48.2	Security considerations	19
48.3	IEEE 802.1Q YANG model	21
48.4	Structure of the YANG model.....	31
48.5	Relationship to IEEE 802.1Q managed objects.....	33
48.6	Definition of IEEE 802.1Q YANG modules	39
Annex A (normative)	PICS proforma—Bridge implementations	90
A.5	Major capabilities.....	90
A.48	YANG	90
Annex U (informative)	Bibliography	91

List of figures

Figure 48-1—General YANG hierarchy	18
Figure 48-2—YANG root hierarchy with IEEE 802.1Q YANG modules	19
Figure 48-3—UML YANG interface management model	22
Figure 48-4—Generic IEEE 802.1Q bridge mode	23
Figure 48-5—Bridge port model	24
Figure 48-6—TPMR model	25
Figure 48-7—TPMR port model	26
Figure 48-8—Provider Bridge model	28
Figure 48-9—Provider Edge Bridge C-VLAN Interface mode	29
Figure 48-10—Provider Edge Bridge S-VLAN interface model	30

List of tables

Table 48-1—Structure of the YANG modules	31
Table 48-2—Structure of the ieee802-dot1q-bridge module.....	31
Table 48-3—Structure of the ieee802-dot1q-tpmr module	32
Table 48-4—Structure of the ieee802-dot1q-vlan-bridge module.....	32
Table 48-5—Structure of the ieee802-dot1q-pb module	32
Table 48-6—Bridge cross-reference table	33
Table 48-7—Bridge component cross-reference table	34
Table 48-8—Bridge component filtering database cross-reference table.....	35
Table 48-9—Bridge component permanent database cross-reference table.....	36
Table 48-10—Bridge component Bridge VLAN cross-reference table	36
Table 48-11—Bridge component Bridge MST cross-reference table	37
Table 48-12—Bridge port cross-reference table.....	38

IEEE Standard for Local and metropolitan area networks—

Bridges and Bridged Networks—

Amendment 30: YANG Data Model

(This amendment is based on IEEE Std 802.1Q™-2018)

NOTE—The editing instructions contained in this amendment define how to merge the material contained here into the base document and its other amendments to form the new comprehensive standard.

Editing instructions are shown in ***bold italic***. Four editing instructions are used: change, delete, insert, and replace. ***Change*** is used to make corrections in existing text or tables. The editing instruction specifies the location of the change and describes what is being changed by using ***strikethrough*** (to remove old material) and ***underscore*** (to add new material). ***Delete*** removes existing material. ***Insert*** adds new material without disturbing the existing material. Insertions may require renumbering. If so, renumbering instructions are given in the editing instruction. ***Replace*** is used to make changes in figures or equations by removing the existing figure or equation and replacing it with a new one. Editing instructions, change markings, and this NOTE will not be carried over into future editions because the changes will be incorporated into the base standard.¹

1. Overview

1.3 Introduction

Insert the following item after j) Defines SMIPv2 (IETF STD 58) Management Information Based (MIB) modules for the management of VLAN Bridge capabilities including spanning tree protocols and Provider Bridges, renumbering as necessary:

- k) Define YANG configuration and operational state models (Clause 48) in support of Two-Port MAC Relays, Customer VLAN Bridges, and Provider Bridges.

¹Notes in text, tables, and figures are given for information only, and do not contain requirements needed to implement the standard.

2. Normative references

Insert the following references in alphanumeric order:

IEEE Std 802d™-2017, IEEE Standard for Local and Metropolitan Area Networks: Overview and Architecture—Amendment 1: Allocation of Uniform Resource Name (URN) Values in IEEE 802® Standards.

IETF RFC 8343 (proposed standard), A YANG Data Model for Interface Management, March 2018.

4. Abbreviations

Insert the following abbreviations in alphanumeric order in Clause 4:

NETCONF Network Configuration Protocol

YANG Yet Another Next Generation²

²YANG is best viewed as a name, not an acronym.

5. Conformance

5.4 VLAN Bridge component requirements

5.4.1 VLAN Bridge component options

Insert the following item w) after v) Support SMIPv2 MIB modules for the management of VLAN Bridge capabilities (Clause 17), renumbering as necessary:

- w) Support YANG modules for the management of VLAN Bridge capabilities (Clause 48);

5.13 MAC Bridge component requirements

5.13.1 MAC Bridge component options

Insert the following item h) after g) Support SMIPv2 MIB modules for the management of MAC Bridge capabilities (Clause 17), renumbering as necessary:

- h) Support YANG modules for the management of MAC Bridge capabilities (Clause 48);

5.16 TPMR conformance

5.16.1 TPMR options

Insert the following item d) after c) Support remote management using the TPMR MIB module defined in 17.7.11, renumbering as necessary:

- d) Support remote management using the TPMR YANG module defined in 48.4.2.

8. Principles of Bridge operation

Change the text of 8.12 as follows:

8.12 Bridge Management Entity

~~In order to facilitate interoperable management of Bridges by remote means (as opposed to management via some kind of management console attached directly to the Bridge), it is recommended that SNMP should be the protocol that is used, in conjunction with the SMIPv2 MIB modules specified in Clause 17.~~

Remote management capabilities (as opposed to management via a console or other device attached directly to a Bridge) are modeled as performed by a Bridge Management Entity supported by a protocol stack as described in 8.13.7. To facilitate interoperable remote management, the Bridge Management Entity should use either the SMIPv2 MIB modules specified in Clause 17 with SNMP or the YANG modules specified in Clause 48 with a network configuration protocol, e.g., NETCONF, RESTCONF.

8.13 Addressing

Change the text of 8.13.7 as follows:

8.13.7 Bridge Management Entities

~~The recommended protocol for remote Bridge management is SNMP, which typically uses IP as a network layer protocol; however,~~ Network configuration and management protocols typically use IP as a network layer protocol. SNMP can also be supported directly over an IEEE 802 LAN, as specified in IETF RFC 4789. ~~If implemented, the~~ The management protocol stack and address used shall be supported by a single LLC Entity attached to a Bridge Port. The Port should be a Management Port for the Bridge, as described in 8.3 and Figure 8-8, but may be a Port attached to a LAN, as described in 8.13.9, Figure 8-21, and Figure 8-22.

12. Bridge management

12.10 Bridge VLAN managed objects

Change the first paragraph of 12.10.1 as follows:

12.10.1 Bridge VLAN Configuration managed object

The Bridge VLAN Configuration managed object models operations that modify, or inquire about, the overall configuration of the Bridge's VLAN resources. There is a single Bridge VLAN Configuration managed object per Bridge [Component](#).

Insert a new Clause 48 after Clause 47 as follows:

48. YANG Data Model

This clause specifies YANG data models that provide control and status monitoring of IEEE 802.1Q Bridges. Specifically,

- a) Two-Port MAC Relays,
- b) Customer VLAN bridges, and
- c) Provider bridges.

The YANG bridge data management models are derived from UML models specified in 48.3. The UML models are based on Clause 12.

NOTE 1—OMG UML 2.5 [B78] conventions together with C++ language constructs are used in this clause as a representation to convey model structure and relationships.

NOTE 2—The MIB modules specified in Clause 17 were also derived from Clause 12. Consequently, the capabilities and structure of the YANG data models should closely aligned with that represented by the MIBs. However the YANG data model has not been derived from the MIB, and there has been no attempt to include data or modeling constructs that might appear in the MIB but not in the information model.

48.1 YANG Framework

This clause has been developed according to the YANG guidelines published in IETF RFC 6087 [B68] as applicable to IEEE standards.

The YANG framework applies hierarchy in the following areas:

- 1) The uniform resource name (URN), as specified in IEEE Std 802d. The structure of the URN is such that *ieee* is the root (i.e., name-space identifier), followed by the standard, then the working group developing the standard.
- 2) The YANG objects form a hierarchy of configuration and operational data structures that define the YANG model. These hierarchical relationships are described in 48.3.

The general YANG framework hierarchy is illustrated in Figure 48-1.




Figure 48-1—General YANG hierarchy

IEEE Std 802.1Qcp-2018
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks—
Amendment 30: YANG Data Model

Network interfaces are central to the management of protocols supported over said interface. Thus, it is important to establish a common data model for how interfaces are identified, configured, and monitored. The IETF Interface Management model (IETF RFC 8343) defines a generic YANG data model for the management of network interfaces. Consequently, IEEE 802.1Q Bridge Ports augment the generic interfaces data model defined by the IETF Interface Management model (IETF RFC 8343).

In addition, a high level YANG object is defined to support IEEE 802.1Q Bridge YANG models. An “IEEE 802.1Q Bridge” YANG model is introduced, which can be augmented by the various IEEE 802.1Q Bridge models.

The YANG hierarchical structure that incorporates the IEEE 802.1Q YANG models supported by this standard is represented in Figure 48-2.




Figure 48-2—YANG root hierarchy with IEEE 802.1Q YANG modules

48.2 Security considerations

The YANG modules defined in this clause are designed to be accessed via a network configuration protocol, e.g., NETCONF protocol (IETF RFC 6536 [B71]). In the case of NETCONF, the lowest NETCONF layer is the secure transport layer and the mandatory to implement secure transport is SSH (IETF RFC 6242 [B70]). The NETCONF access control model provides the means to restrict access for particular NETCONF users to a preconfigured subset of all available NETCONF protocol operations and content.

It is the responsibility of a system’s implementor and administrator to ensure that the protocol entities in the system that support NETCONF, and any other remote configuration protocols that make use of these YANG modules, are properly configured to allow access only to those principals (users) that have legitimate rights to read or write data nodes. This standard does not specify how the credentials of those users are to be stored or validated.

48.2.1 Security considerations of the ieee802-dot1q-bridge and ieee802-dot1q-vlan-bridge YANG modules

There are a number of management objects defined in the ieee802-dot1q-bridge and ieee802-dot1q-vlan-bridge YANG modules that are configurable (i.e., read-write) and/or operational (i.e., read-only). Such objects may be considered sensitive or vulnerable in some network environments. A network configuration protocol, such as NETCONF (IETF RFC 6241 [B69]), can support protocol operations that can edit or delete YANG module configuration data (e.g., edit-config, delete-config, copy-config). If this is done in a non-secure environment without proper protection, then negative effects on the network operation is possible.

The following objects in the `ieee802-dot1q-bridge` and `ieee802-dot1q-vlan-bridge` YANG modules can be manipulated to interfere with the operation of VLANs and priority classes. This could, for example, be used to force a reinitialization of state machines, thus causing network instability, or to change the forwarding and filtering policies. Another possibility would be for an attacker to override established policy on Port priorities, thus giving a user (or an attacker) unauthorized preferential treatment.

`interfaces/interface/bridge-port`
`interfaces/interface/bridge-port/priority-regeneration`
`bridges/bridge/component/traffic-class-enabled`
`bridges/bridge/component/bridge-vlan/protocol-group-database`
`interfaces/interface/bridge-port/traffic-class`
`interfaces/interface/bridge-port/protocol-group-vid-set`

- a) The configurable object `bridges/bridge/component/filtering-database/aging-time` controls how fast dynamically learned forwarding information is aged out. Setting this object to a large value may simplify FDB overflow attacks. Setting this object to too small a value may compromise the throughput of the network by causing excessive flooding.
- b) The configurable object `bridges/bridge/component/filtering-database/filtering-entries/entry-type` provides a filtering mechanism controlling which Ports frames originating from a specific source may be forwarded to. Write access to this table can be used to turn provisioned filtering off or to add filters to prevent rightful use of the network.

Some of the readable data in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control all types of access (e.g., including NETCONF `get`, `get-config` operations) to these objects and possibly to even encrypt the values of these objects when sending them over the network. These tables and objects and their sensitivity/vulnerability are described as follows:

- The object `bridges/bridge/component/capabilities` could be used by an attacker to determine which attacks might be useful to attempt against a given device.
- The readable objects defined in the `ieee802-dot1q-bridge` and `ieee802-dot1q-vlan-bridge` modules provide information about the topology of a bridged network and the attached active stations. The addresses listed in the `bridges/bridge/component/filtering-database/filtering-entries` usually reveal information about the manufacturer of the MAC hardware, which can be useful information for mounting other specific attacks.
- The readable objects defined in the `ieee802-dot1q-bridge` and `ieee802-dot1q-vlan-bridge` modules provide information about the topology of a bridged network and the attached active stations. In some networks, information about attached active stations can be considered personal identifying information about the user of the station. Unauthorized use of this object can be considered a privacy threat.

48.2.2 Security considerations of the `ieee802-dot1q-tpmr` YANG module

There are a number of management objects defined in the `ieee802-dot1q-tpmr` YANG module that are configurable (i.e., read-write) and/or operational (i.e., read-only). Such objects may be considered sensitive or vulnerable in some network environments. A network configuration protocol, such as NETCONF (IETF RFC 6241 [B69]), can support protocol operations that can edit or delete YANG module configuration data (e.g., `edit-config`, `delete-config`, `copy-config`). If this is done in a non-secure environment without proper protection, then negative effects on the network operation is possible.

The following objects in the `ieee802-dot1q-tpmr` YANG module could be manipulated to interfere with the operation of MAC status propagation on a TPMR port and, for example, be used to cause network instability:

```

interfaces/interface/bridge-port/mac-status-propagation/link-notify
interfaces/interface/bridge-port/mac-status-propagation/link-notify-wait
interfaces/interface/bridge-port/mac-status-propagation/link-notify-retry
interfaces/interface/bridge-port/mac-status-propagation/mac-notify
interfaces/interface/bridge-port/mac-status-propagation/mac-notify-time
interfaces/interface/bridge-port/mac-status-propagation/mac-recover-time
  
```

48.2.3 Security considerations of the `ieee802-dot1q-pb` YANG module

There are a number of management objects defined in the `ieee802-dot1q-pb` YANG module that are configurable (i.e., read-write) and/or operational (i.e., read-only). Such objects may be considered sensitive or vulnerable in some network environments. A network configuration protocol, such as NETCONF (IETF RFC 6241 [B69]), can support protocol operations that can edit or delete YANG module configuration data (e.g., edit-config, delete-config, copy-config). If this is done in a non-secure environment without proper protection, then negative effects on the network operation is possible.

The following objects in the `ieee802-dot1q-pb` YANG module can be manipulated to interfere with the operation of VLANs. This could, for example, be used to force a reinitialization of state machines, thus causing network instability, or to change the forwarding and filtering policies.

```

interfaces/interface/bridge-port
interfaces/interface/bridge-port/cvid-registration
interfaces/interface/bridge-port/service-priority-regeneration
  
```

48.3 IEEE 802.1Q YANG model

The YANG data models are based on the management model outline in Clause 12. A UML representation of the management model is provided in the following subclauses.

48.3.1 Interface Management (IETF RFC 8343) Model

The Interface Management YANG model is augmented by the IEEE 802.1Q YANG models, and specifically the Bridge Port. As such, it is useful to have a UML representation. The UML representation of the Interface Management (IETF RFC 8343) model is illustrated in Figure 48-3.³

³ The representation of the Interface YANG model is completely derived from IETF RFC 8343.




Figure 48-3—UML YANG interface management model

48.3.2 Generic IEEE 802.1Q-2018 bridge model

Based upon the bridge management outlined in Clause 12, the generic IEEE 802.1Q bridge model represented in a UML form is illustrated in Figure 48-4.

A Bridge Port represents the service access points to the Bridge’s MAC Relay Entity and the interface stack that supports that service access point. Refer to 8.2.

The interface stack associated with the Bridge Port can be such that when it is initially created (a) the underlying MAC entity along with the bridge port data are associated with the same Interface, or (b) the underlying MAC entity is associated with a separate Interface from that of the bridge port Interface. In the later model, the bridge port Interface is the higher layer interface of the underlying MAC entity Interface.

The bridge port interfaces associated with this generic model, is shown in Figure 48-5.

IEEE Std 802.1Qcp-2018
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks—
Amendment 30: YANG Data Model





Figure 48-4—Generic IEEE 802.1Q bridge mode

IEEE Std 802.1Qcp-2018
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks—
Amendment 30: YANG Data Model



NOTE—Items shaded in gray indicate extension provided by the IEEE 802.1Q YANG models.

Figure 48-5—Bridge port model

IEEE Std 802.1Qcp-2018
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks—
Amendment 30: YANG Data Model

Each Bridge Port (3.25) is associated with one Interface. The *higher-layer-if* and *lower-layer-if* attributes provide the interface stacking relationships of the Bridge Port. For example, an Aggregator (as defined by IEEE Std 802.1AX) Interface could be a Bridge Port. The *lower-layer-if* attributes associated with the Aggregator would point to the Aggregation Ports, thus forming the interface staking relationship of the Bridge Port.

Each Bridge Port is uniquely identified by a Port Number (*port-number*). A port number has no mandatory relationship to an Interface index (*if-index*).

48.3.2.1 Two-Port MAC Relay model

The Two-Port MAC Relay (TPMR) bridge UML data model is a subset of the generic IEEE 802.1Q bridge illustrated in Figure 48-4. A TPMR:

- Supports only 2 bridge ports.
- Supports a “VLAN-unaware” bridge component.
- Does not support any “bridged VLAN” object.
- Does not support a “filtering database” object.
- Provides extensions to the “bridge port.”

The TPMR model is illustrated in Figure 48-6.




Figure 48-6—TPMR model

NOTE—The bridge type would be *two-port-mac-relay-bridge* and the component type would be *d-bridge-component* (which denotes a VLAN unaware component). The number of ports associated with the component must be 2.