



International
Standard

**ISO/IEC/IEEE
8802-1Q**

**Telecommunications and exchange
between information technology
systems — Requirements for local
and metropolitan area networks —**

**Part 1Q:
Bridges and bridged networks**

**AMENDMENT 36: YANG Data
Models for Scheduled Traffic, Frame
Preemption, and Per-Stream Filtering
and Policing**

*Télécommunications et échange entre systèmes informatiques —
Exigences pour les réseaux locaux et métropolitains —*

Partie 1Q: Ponts et réseaux pontés

AMENDEMENT 36

**Third edition
2024-08
AMENDMENT 36**

Reference number
ISO/IEC/IEEE 8802-1Q:2024/
Amd.36:2025(en)

Authorized licensed use limited to: Tsinghua University. Downloaded on February 26, 2026 at 08:18:52 UTC from IEEE Xplore. Restrictions apply.

Full document details: ISO/IEC/IEEE 8802-1Q-2024_Amd36-2025

 **Documents**
Document Sharing Hub
© IEEE 2025



COPYRIGHT PROTECTED DOCUMENT

© IEEE 2025

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from IEEE at the address below.

Institute of Electrical and Electronics Engineers, Inc
3 Park Avenue, New York
NY 10016-5997, USA

Email: stds.ipr@ieee.org
Website: www.ieee.org

Published in Switzerland

© IEEE 2025 – All rights reserved

Authorized licensed use limited to: Tsinghua University. Downloaded on February 26, 2026 at 08:18:52 UTC from IEEE Xplore. Restrictions apply.

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards.

ISO and IEC draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO and IEC take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO and IEC had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents and <https://patents.iec.ch>. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

ISO/IEC/IEEE 8802-1Q:2024/Amd 36 was prepared by the LAN/MAN of the IEEE Computer Society (as IEEE 802.1Qcw-2023) and drafted in accordance with its editorial rules. It was adopted, under the “fast-track procedure” defined in the Partner Standards Development Organization cooperation agreement between ISO and IEEE, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*.

A list of all parts in the ISO/IEC/IEEE 8802 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

Contents

1.	Overview.....	15
1.3	Introduction.....	15
12.	Bridge management.....	16
12.29	Managed objects for scheduled traffic.....	16
12.29.1	The Gate Parameter Table	16
12.31	Managed objects for per-stream classification and metering	17
12.31.1	The Stream Parameter Table	17
12.31.3	The Stream Gate Instance Table	17
17.	Management Information Base (MIB)	18
17.2	Structure of the MIB	18
17.2.22	Structure of the IEEE8021-ST-MIB	18
17.2.24	Structure of the IEEE8021-PSFP-MIB	18
17.7	MIB modules	19
17.7.14	Definitions for the IEEE8021-SRP-MIB module	19
17.7.22	Definitions for the IEEE8021-ST-MIB module	38
17.7.24	Definitions for the IEEE8021-PSFP-MIB module	49
35.	Stream Reservation Protocol (SRP).....	69
35.2	Definition of the MSRP application	69
35.2.2	Definition of MRP elements	69
46.	Time-Sensitive Networking (TSN) configuration	70
46.2	User/network configuration information	70
46.2.3	Talker	70
48.	YANG Data Models	71
48.2	IEEE 802.1Q YANG models.....	71
48.2.1	VLAN Bridge components model	71
48.2.2	Two-Port MAC Relay (TPMR) model	73
48.2.4	Provider Bridge model	74
48.2.5	CFM Model	77
48.2.7	Asynchronous Traffic Shaping (ATS) model	79
48.2.8	Congestion Isolation (CI) model	80
48.2.9	Scheduled Traffic model	80
48.2.10	Frame Preemption model	81
48.2.11	Per-Stream Filtering and Policing model	82
48.3	Structure of the YANG models	84
48.3.9	Scheduled Traffic model	84
48.3.10	Frame Preemption model	85
48.3.11	Per-Stream Filtering and Policing model	85
48.4	Security considerations	86
48.4.9	Security considerations of the Scheduled Traffic model	86
48.4.10	Security considerations of the Frame Preemption model	86
48.4.11	Security considerations of the Per-Stream Filtering and Policing model	86

48.5	YANG schema tree definitions	87
48.5.4	Schema for the ieee802-dot1q-bridge YANG module	87
48.5.17	Schema for the ieee802-dot1q-sched YANG module	91
48.5.18	Schema for the ieee802-dot1q-sched-bridge YANG module	91
48.5.19	Schema for the ieee802-dot1q-preemption YANG module	91
48.5.20	Schema for the ieee802-dot1q-preemption-bridge YANG module	92
48.5.21	Schema for the ieee802-dot1q-psfp YANG module	92
48.5.22	Schema for the ieee802-dot1q-psfp-bridge YANG module	92
48.6	YANG modules	94
48.6.1	The ieee802-types YANG module	94
48.6.2	The ieee802-dot1q-types YANG module	99
48.6.4	The ieee802-dot1q-bridge YANG module	115
48.6.6	The ieee802-dot1q-pb YANG module	141
48.6.17	The ieee802-dot1q-sched YANG module	145
48.6.18	The ieee802-dot1q-sched-bridge YANG module	151
48.6.19	The ieee802-dot1q-preemption YANG module	152
48.6.20	The ieee802-dot1q-preemption-bridge YANG module	156
48.6.21	The ieee802-dot1q-psfp YANG module	157
48.6.22	The ieee802-dot1q-psfp-bridge YANG module	167
Annex A (normative)	PICS proforma—Bridge implementations	168
A.47	YANG	168
Annex B (normative)	PICS proforma—End station implementations	169
B.15	Scheduled traffic	169
B.16	Frame Preemption.....	169
B.17	Per-Stream Filtering and Policing.....	169

Figures

Figure 48-5	Bridge Port model.....	72
Figure 48-7	TPMR port model	73
Figure 48-9	Provider Edge Bridge C-VLAN Interface model	75
Figure 48-10	Provider Edge Bridge S-VLAN interface model	76
Figure 48-12	CFM MEP model relationships	78
Figure 48-16	Asynchronous Traffic Shaping model	79
Figure 48-17	Congestion Isolation model	80
Figure 48-18	Scheduled Traffic model.....	81
Figure 48-19	Frame Preemption model.....	82
Figure 48-20	PSFP model.....	83

Tables

Table 12-32	The Gate Parameter Table	16
Table 12-34	The Stream Parameter Table.....	17
Table 17-28	IEEE8021-ST-MIB structure.....	18
Table 17-30	IEEE8021-PSFP-MIB structure.....	18
Table 48-1	Summary of the YANG modules.....	84
Table 48-10	Scheduled Traffic model YANG modules.....	84
Table 48-11	Frame Preemption model YANG modules.....	85
Table 48-12	Per-Stream Filtering and Policing model YANG modules	85

IEEE Standard for
Local and Metropolitan Area Networks—

Bridges and Bridged Networks

Amendment 36: YANG Data Models for Scheduled Traffic, Frame Preemption, and Per-Stream Filtering and Policing

(This amendment is based on IEEE Std 802.1Q™-2022 as amended by IEEE Std 802.1Qcz-2023.)

NOTE—The editing instructions contained in this amendment define how to merge the material contained therein into the existing base standard and its amendments to form the comprehensive standard.

The editing instructions are shown in ***bold italics***. Four editing instructions are used: change, delete, insert, and replace. ***Change*** is used to make corrections in existing text or tables. The editing instruction specifies the location of the change and describes what is being changed by using ~~striketrough~~ (to remove old material) and underscore (to add new material). ***Delete*** removes existing material. ***Insert*** adds new material without disturbing the existing material. Deletions and insertions may require renumbering. If so, renumbering instructions are given in the editing instruction. ***Replace*** is used to make changes in figures or equations by removing the existing figure or equation and replacing it with a new one. Editing instructions, change markings, and this note will not be carried over into future editions because the changes will be incorporated into the base standard.⁶

⁶ Notes in text, tables, and figures are given for information only and do not contain requirements needed to implement the standard.

1. Overview

1.3 Introduction

Insert new list item cs) after item cr) in 1.3 and renumber the subsequent list items accordingly:

- cs) Define YANG configuration and operational state models (Clause 48) in support of scheduled traffic, frame preemption, and Per-Stream Filtering and Policing.

12. Bridge management

12.29 Managed objects for scheduled traffic

12.29.1 The Gate Parameter Table

Insert two new rows at the end of Table 12-32 as follows (unchanged rows not shown):

Table 12-32—The Gate Parameter Table

Name	Data type	Operations supported ^a	Conformance ^b	References
SupportedCycleMax	RationalNumber (seconds)	R	B, E	8.6.8.4, 12.29.1.3, 12.29.1.6
SupportedIntervalMax	Integer	R	B, E	8.6.8.4, 12.29.1.7

^a R = Read only access; RW = Read/Write access.

^b B = Required for Bridge or Bridge component support of enhancements for scheduled traffic; E = Required for end station support of enhancements for scheduled traffic.

12.29.1.2 The gate control list structure and data types

12.29.1.2.1 GateControlEntry

Change 12.29.1.2.1 as follows:

A GateControlEntry consists of an operation name, followed by ~~up to~~ 2 parameters associated with the operation, as detailed in Table 8-7. The first parameter, ~~if present~~, is a gateStatesValue (12.29.1.2.2); the second parameter, ~~if present~~, is a timeIntervalValue (12.29.1.2.3).

Insert 12.29.1.6 and 12.29.1.7 after 12.29.1.5 as follows:

12.29.1.6 SupportedCycleMax

The maximum value supported by this Port of the AdminCycleTime (8.6.9.4.3) and OperCycleTime (8.6.9.4.19) parameters.

12.29.1.7 SupportedIntervalMax

The maximum value supported by this Port of the timeIntervalValue (12.29.1.2.3) parameter.

12.31 Managed objects for per-stream classification and metering

12.31.1 The Stream Parameter Table

Insert two new rows at the end of Table 12-34 as follows (unchanged rows not shown):

Table 12-34—The Stream Parameter Table

Name	Data type	Operations supported ^a	Conformance ^b	References
SupportedCycleMax	RationalNumber (seconds)	R	PSFP, ATS	8.6.5.4, 12.29.1.3, 12.29.1.6
SupportedIntervalMax	Integer	R	PSFP, ATS	8.6.5.4, 12.29.1.7

^a R= Read only access; RW = Read/Write access.

^b PSFP = Required for Bridge, Bridge component, or end station support of PSFP.

psfp = Optional for Bridge, Bridge component, or end station support of PSFP.

ATS = Required for Bridge or Bridge component support of ATS.

ats = Optional for Bridge or Bridge component support of ATS.

CI = Required for Bridge or Bridge component support of CI.

Insert 12.31.1.7 and 12.31.1.8 after 12.31.1.6 as follows:

12.31.1.7 SupportedCycleMax

The maximum value supported by this Port of the AdminCycleTime (8.6.9.4.3) and OperCycleTime (8.6.9.4.19) parameters.

12.31.1.8 SupportedIntervalMax

The maximum value supported by this Bridge component of the timeIntervalValue (12.31.3.2.4) parameter.

12.31.3 The Stream Gate Instance Table

12.31.3.2 The gate control list structure and data types

12.31.3.2.2 StreamGateControlEntry

Change 12.31.3.2.2 as follows:

A StreamGateControlEntry consists of an operation name, followed by three mandatory parameters and one optional parameter associated with the operation, as detailed in Table 8-4. The first parameter is a StreamGateStatesValue (8.6.10.5, 12.31.3.2.1); the second parameter is an IPV value (8.6.10.7, 12.31.3.2.3); ~~and~~; the third parameter is a timeIntervalValue (8.6.9.4.23, 12.31.3.2.4); and the fourth parameter is an IntervalOctetMaxValue (8.6.10.1, 12.31.3.2.5). IntervalOctetMaxValue is optional.

Insert 12.31.3.2.5 after 12.31.3.2.4 as follows:

12.31.3.2.5 IntervalOctetMaxValue

An unsigned integer, denoting an IntervalOctetMax in MSDU octets (see IntervalOctetMax in Table 8-4).

17. Management Information Base (MIB)

17.2 Structure of the MIB

17.2.22 Structure of the IEEE8021-ST-MIB

Insert three new rows at the end of Table 17-28 as follows (unchanged rows not shown):

Table 17-28—IEEE8021-ST-MIB structure

IEEE8021-ST-MIB table/object	Reference
ieee8021STSupportedCycleMaxNumerator	SupportedCycleMax, 12.29.1.6
ieee8021STSupportedCycleMaxDenominator	SupportedCycleMax, 12.29.1.6
ieee8021STSupportedIntervalMax	SupportedIntervalMax, 12.29.1.7

17.2.24 Structure of the IEEE8021-PSFP-MIB

Insert three new rows at the end of Table 17-30 as follows (unchanged rows not shown):

Table 17-30—IEEE8021-PSFP-MIB structure

IEEE8021-PSFP-MIB table/object	Reference
ieee8021PSFPSupportedCycleMaxNumerator	SupportedCycleMax, 12.31.1.7
ieee8021PSFPSupportedCycleMaxDenominator	SupportedCycleMax, 12.31.1.7
ieee8021PSFPSupportedIntervalMax	SupportedIntervalMax, 12.31.1.8

17.7 MIB modules^{7 8}

17.7.14 Definitions for the IEEE8021-SRP-MIB module

Change 17.7.14 as follows:

```
IEEE8021-SRP-MIB DEFINITIONS ::= BEGIN

-- =====
-- MIB for support of IEEE 802.1Qat Stream Reservation Protocol
-- (SRP) in IEEE 802.1Q Bridges.
-- =====

IMPORTS
    MODULE-IDENTITY,
    OBJECT-TYPE,
    Counter64,
    Unsigned32
        FROM SNMPv2-SMI
    MacAddress,
    TEXTUAL-CONVENTION,
    TruthValue
        FROM SNMPv2-TC
    MODULE-COMPLIANCE,
    OBJECT-GROUP
        FROM SNMPv2-CONF
    ieee802dot1mibs,
IEEE8021PriorityCodePoint,
    IEEE8021VlanIndex
        FROM IEEE8021-TC-MIB
    IEEE8021FqtssTrafficClassValue
        FROM IEEE8021-FQTSS-MIB
    ieee8021BridgeBaseComponentId,
    ieee8021BridgeBaseEntry,
    ieee8021BridgeBasePort,
    ieee8021BridgeBasePortEntry
        FROM IEEE8021-BRIDGE-MIB

;

ieee8021SrpMib MODULE-IDENTITY
    LAST-UPDATED "202211080000Z" November 8, 2022 "202309260000Z" -- September 26, 2023
    ORGANIZATION "IEEE 802.1 Working Group"
    CONTACT-INFO
        " WG-URL: http://www.ieee802.org/1/
          WG-EMail: stds-802-1-1@ieee.org
          Contact: IEEE 802.1 Working Group Chair
          Postal: C/O IEEE 802.1 Working Group
                  IEEE Standards Association
                  445 Hoes Lane
                  Piscataway, NJ 08854
                  USA
          E-mail: stds-802-1-chairs@ieee.org"
    DESCRIPTION
        "The Bridge MIB module for managing devices that support
        the IEEE Std 802.1Q Stream Reservation Protocol.

        Unless otherwise indicated, the references in this MIB
        module are to IEEE Std 802.1Q-2022.

        Copyright (C) IEEE (20222023).
        This version of this MIB module is part of IEEE Std 802.1Q;
        see that standard for full legal notices."
```

⁷Copyright release for MIBs: Users of this standard may freely reproduce the MIB modules in this standard so that they can be used for their intended purpose.

⁸An ASCII version of this MIB module is attached to the PDF version of this standard, and can be obtained by Web browser from the IEEE 802.1 Website at <https://1.ieee802.org/mib-modules/>.

ISO/IEC/IEEE 8802-1Q:2024/Amd.36:2024(en)

IEEE Std 802.1Qcw™-2023
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks
Amendment 36: YANG Data Models for Scheduled Traffic, Frame Preemption, and Per-Stream Filtering and Policing

REVISION "202309260000Z" -- September 26, 2023
DESCRIPTION
"Published as part of IEEE 802.1Qcw.
Changed the applicable SYNTAX of object definitions
ieee8021SrpStreamDataFramePriority, and
ieee8021SrpStreamPreloadDataFramePriority
from IEEE8021PriorityCodePoint to INTEGER
to correct an error identifying PCP encoding SYNTAX
instead of PCP values as intended."

REVISION "202211080000Z" -- November 8, 2022
DESCRIPTION
"Published as part of IEEE Std 802.1Q-2022.
Cross references and contact information updated."

REVISION "201810040000Z" -- October 4, 2018
DESCRIPTION
"Published as part of IEEE 802.1Qcc-2018.
Added managed objects for Stream Reservation
Protocol (SRP) Enhancements and Performance
Improvements"

REVISION "201806280000Z" -- June 28, 2018
DESCRIPTION
"Published as part of IEEE Std 802.1Q 2018.
Cross references updated. "

REVISION "201512020000Z" -- December 2, 2015
DESCRIPTION
"Published as part of IEEE Std 802.1Q-2014 Cor-1.
ieee8021SrpReservationFailureBridgeId changed to
ieee8021SrpReservationFailureSystemId."

REVISION "201412150000Z" -- December 15, 2014
DESCRIPTION
"Published as part of IEEE Std 802.1Q 2014 revision.
Cross references updated and corrected."

REVISION "201102270000Z" -- February 27, 2011
DESCRIPTION
"Minor edits to contact information etc. as part of
2011 revision of Std 802.1Q."

REVISION "201004190000Z" -- April 19, 2010
DESCRIPTION
"Initial revision, included in IEEE 802.1Qat"
::= { ieee802dot1mibs 19 }

-- =====
-- Textual Conventions
-- =====

IEEE8021SrpStreamRankValue ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION
"An 802.1 SRP Stream Rank value. This is an integer,
with the following interpretation placed on the value:

0: Emergency, high-rank stream,
1: Non-emergency stream."
REFERENCE "35.2.2.8.5b"
SYNTAX INTEGER {
 emergency(0),
 nonEmergency(1)
}

IEEE8021SrpStreamIdValue ::= TEXTUAL-CONVENTION
DISPLAY-HINT "1x:1x:1x:1x:1x:1x:1x:1x"
STATUS current
DESCRIPTION

"Represents an SRP Stream ID, which is often defined as a MAC Address followed by a unique 16-bit ID."

SYNTAX OCTET STRING (SIZE (8))

IEEE8021SrpReservationDirectionValue ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"An 802.1 SRP Stream Reservation Direction value. This is an integer, with the following interpretation placed on the value:

0: Talker registrations,
1: Listener registrations."

REFERENCE "35.2.1.2"

SYNTAX INTEGER {
 talkerRegistrations(0),
 listenerRegistrations(1)
}

IEEE8021SrpReservationDeclarationTypeValue ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"An 802.1 SRP Stream Reservation Declaration Type value. This is an integer, with the following interpretation placed on the value:

0: Talker Advertise,
1: Talker Failed,
2: Listener Asking Failed,
3: Listener Ready,
4: Listener Ready Failed."

REFERENCE "35.2.1.3"

SYNTAX INTEGER {
 talkerAdvertise(0),
 talkerFailed(1),
 listenerAskingFailed(2),
 listenerReady(3),
 listenerReadyFailed(4)
}

IEEE8021SrpReservationFailureCodeValue ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"An 802.1 SRP Stream Reservation Failure Code value. This is an integer, with the following interpretation placed on the value:

0: No failure,
1: Insufficient bandwidth,
2: Insufficient Bridge resources,
3: Insufficient bandwidth for Traffic Class,
4: StreamID in use by another Talker,
5: Stream destination address already in use,
6: Stream pre-empted by higher rank,
7: Reported latency has changed,
8: Egress port is not AVBCapable,
9: Use a different destination_address,
10: Out of MSRP resources,
11: Out of MMRP resources,
12: Cannot store destination_address,
13: Requested priority is not an SR Class priority,
14: MaxFrameSize is too large for media,
15: maxFanInPorts limit has been reached,
16: Changes in FirstValue for a registered StreamID,
17: VLAN is blocked on this egress port (Registration Forbidden),
18: VLAN tagging is disabled on this egress port (untagged set),
19: SR class priority mismatch."

REFERENCE "35.2.2.8.7"

SYNTAX INTEGER {
 noFailure(0),

IEEE Std 802.1Qcw™-2023
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks
Amendment 36: YANG Data Models for Scheduled Traffic, Frame Preemption, and Per-Stream Filtering and Policing

```

        insufficientBandwidth(1),
        insufficientResources(2),
        insufficientTrafficClassBandwidth(3),
        streamIDInUse(4),
        streamDestinationAddressInUse(5),
        streamPreemptedByHigherRank(6),
        latencyHasChanged(7),
        egressPortNotAVBCapable(8),
        useDifferentDestinationAddress(9),
        outOfMSRPResources(10),
        outOfMMRPResources(11),
        cannotStoreDestinationAddress(12),
        priorityIsNoAnSRClass(13),
        maxFrameSizeTooLarge(14),
        maxFanInPortsLimitReached(15),
        firstValueChangedForStreamID(16),
        vlanBlockedOnEgress(17),
        vlanTaggingDisabledOnEgress(18),
        srClassPriorityMismatch(19)
    }

-- =====
-- subtrees in the SRP MIB
-- =====

ieee8021SrpNotifications
    OBJECT IDENTIFIER ::= { ieee8021SrpMib 0 }

ieee8021SrpObjects
    OBJECT IDENTIFIER ::= { ieee8021SrpMib 1 }

ieee8021SrpConformance
    OBJECT IDENTIFIER ::= { ieee8021SrpMib 2 }

ieee8021SrpConfiguration
    OBJECT IDENTIFIER ::= { ieee8021SrpObjects 1 }

ieee8021SrpLatency
    OBJECT IDENTIFIER ::= { ieee8021SrpObjects 2 }

ieee8021SrpStreams
    OBJECT IDENTIFIER ::= { ieee8021SrpObjects 3 }

ieee8021SrpReservations
    OBJECT IDENTIFIER ::= { ieee8021SrpObjects 4 }

-- =====
-- The ieee8021SrpConfiguration subtree
-- This subtree defines the objects necessary for the
-- operational management of SRP.
-- =====

ieee8021SrpBridgeBaseTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Ieee8021SrpBridgeBaseEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A table for SRP main control and status information.
        All writable objects in this table must be persistent
        over power up restart/reboot. These objects augment
        the ieee8021BridgeBasePortTable."
    ::= { ieee8021SrpConfiguration 1 }

ieee8021SrpBridgeBaseEntry OBJECT-TYPE
    SYNTAX      Ieee8021SrpBridgeBaseEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "SRP control and status information for a Bridge."
    AUGMENTS { ieee8021BridgeBaseEntry }
```

```

::= { ieee8021SrpBridgeBaseTable 1 }

Ieee8021SrpBridgeBaseEntry ::=
  SEQUENCE {
    ieee8021SrpBridgeBaseMsrpEnabledStatus
      TruthValue,
    ieee8021SrpBridgeBaseMsrpTalkerPruning
      TruthValue,
    ieee8021SrpBridgeBaseMsrpMaxFanInPorts
      Unsigned32,
    ieee8021SrpBridgeBaseMsrpLatencyMaxFrameSize
      Unsigned32,
    ieee8021SrpBridgeBaseMsrpTalkerVlanPruning
      TruthValue,
    ieee8021SrpBridgeBaseMsrpMaxSRClasses
      Unsigned32
  }

ieee8021SrpBridgeBaseMsrpEnabledStatus OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The administrative status requested by management for
    MSRP. The value true(1) indicates that MSRP should
    be enabled on this device, in all VLANs, on all ports
    for which it has not been specifically disabled. When
    false(2), MSRP is disabled, in all VLANs and on all
    ports, and all MSRP frames will be forwarded
    transparently. This objects affects both Applicant and
    Registrar state machines. A transition from false(2)
    to true(1) will cause a reset of all MSRP state
    machines on all ports.

    This object may be modified while the corresponding
    instance of ieee8021BridgeBaseRowStatus is active(1).

    The value of this object MUST be retained across
    reinitializations of the management system."
  REFERENCE   "35.2.1.4d"
  DEFVAL      { true }
  ::= { ieee8021SrpBridgeBaseEntry 1 }

ieee8021SrpBridgeBaseMsrpTalkerPruning OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The value of the talkerPruning parameter, which
    controls the propagation of Talker declarations.
    The value true(1) indicates that Talker attributes
    are only declared on ports that have the Stream
    destination address registered in the MMRP MAC
    Address Registration Entries. When false(2),
    Talker attribute are declared on all egress ports
    in the active topology.

    The value of this object MUST be retained across
    reinitializations of the management system."
  REFERENCE   "12.22.1, 35.2.1.4b, 35.2.4.3.1"
  DEFVAL      { false }
  ::= { ieee8021SrpBridgeBaseEntry 2 }

ieee8021SrpBridgeBaseMsrpMaxFanInPorts OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The value of the msrpMaxFanInPorts parameter, which
    limits the total number of ports on a Bridge that
    are allowed to establish reservations for inbound
    Streams. A value of zero (0) indicates no fan-in

```

limit is being specified and calculations involving fan-in will only be limited by the number of MSRP enabled ports.

The value of this object MUST be retained across reinitializations of the management system."

REFERENCE "12.22.1, 35.2.1.4f"

DEFVAL { 0 }

::= { ieee8021SrpBridgeBaseEntry 3 }

ieee8021SrpBridgeBaseMsrpLatencyMaxFrameSize OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The value of msrpLatencyMaxFrameSize parameter which is used in the calculation of the maximum latency through a Bridge. The maximum size is defined to be 2000 octets by default, but may be set to a smaller or larger value dependent on the particular Bridge configuration. This parameter does not imply any type of policing of frame size, it is only used in the latency calculations.

The value of this object MUST be retained across reinitializations of the management system."

REFERENCE "12.22.1, 35.2.1.4g"

DEFVAL { 2000 }

::= { ieee8021SrpBridgeBaseEntry 4 }

ieee8021SrpBridgeBaseMsrpTalkerVlanPruning OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This parameter allows to limit the Talker declaration to ports, that have the Stream's VLAN identifier registered as a member in the VLAN Registration Entries. The value true(1) indicates that Talker declarations are only sent out on ports, that have the Stream's VLAN identifier registered as a member in the VLAN Registration Entries. When false(2), Talker declarations are propagated according to the VLAN spanning tree."

REFERENCE "12.22.1, 35.2.1.4l"

DEFVAL { false }

::= { ieee8021SrpBridgeBaseEntry 5 }

ieee8021SrpBridgeBaseMsrpMaxSRClasses OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This attribute provides the maximum number of SR classes supported by the Bridge."

REFERENCE "12.22.1, 35.2.1.4m"

::= { ieee8021SrpBridgeBaseEntry 6 }

ieee8021SrpBridgePortTable OBJECT-TYPE

SYNTAX SEQUENCE OF Ieee8021SrpBridgePortEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A table for SRP control and status information about every Bridge Port. Augments the ieee8021BridgeBasePortTable."

::= { ieee8021SrpConfiguration 2 }

ieee8021SrpBridgePortEntry OBJECT-TYPE

SYNTAX Ieee8021SrpBridgePortEntry

MAX-ACCESS not-accessible

STATUS current

```

DESCRIPTION
    "SRP control and status information for a Bridge Port."
AUGMENTS { ieee8021BridgeBasePortEntry }
::= { ieee8021SrpBridgePortTable 1 }

Ieee8021SrpBridgePortEntry ::=
SEQUENCE {
    ieee8021SrpBridgePortMsrpEnabledStatus
        TruthValue,
    ieee8021SrpBridgePortMsrpFailedRegistrations
        Counter64,
    ieee8021SrpBridgePortMsrpLastPduOrigin
        MacAddress,
    ieee8021SrpBridgePortSrPvid
        IEEE8021VlanIndex,
    ieee8021SrpBridgePortMsrpTalkerPrunningPerPort
        TruthValue
}

ieee8021SrpBridgePortMsrpEnabledStatus OBJECT-TYPE
SYNTAX      TruthValue
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The administrative state of MSRP operation on this port. The
    value true(1) indicates that MSRP is enabled on this port
    in all VLANs as long as ieee8021BridgeMsrpEnabledStatus is
    also true(1). A value of false(2) indicates that MSRP is
    disabled on this port in all VLANs: any MSRP frames received
    will be silently discarded, and no MSRP registrations will be
    propagated from other ports. Setting this to a value of
    true(1) will be stored by the agent but will only take
    effect on the MSRP protocol operation if
    ieee8021BridgeMsrpEnabledStatus
    also indicates the value true(1). This object affects
    all MSRP Applicant and Registrar state machines on this
    port. A transition from false(2) to true(1) will
    cause a reset of all MSRP state machines on this port.

    The value of this object MUST be retained across
    reinitializations of the management system."
REFERENCE   "35.2.1.4e"
DEFVAL      { true }
::= { ieee8021SrpBridgePortEntry 1 }

ieee8021SrpBridgePortMsrpFailedRegistrations OBJECT-TYPE
SYNTAX      Counter64
UNITS       "failed MSRP registrations"
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The total number of failed MSRP registrations, for any
    reason, in all VLANs, on this port.

    Discontinuities in the value of the counter can occur at
    re-initialization of the management system, and at other
    times as indicated by the value of ifCounterDiscontinuityTime
    object of the associated interface (if any)."
```

```

REFERENCE   "10.7.12.1"
::= { ieee8021SrpBridgePortEntry 2 }

ieee8021SrpBridgePortMsrpLastPduOrigin OBJECT-TYPE
SYNTAX      MacAddress
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The Source MAC Address of the last MSRP message
    received on this port."
REFERENCE   "10.7.12.2"
::= { ieee8021SrpBridgePortEntry 3 }

ieee8021SrpBridgePortSrPvid OBJECT-TYPE
```

```

SYNTAX      IEEE8021VlanIndex
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The default VLAN ID that Streams are assigned to.
    Talkers learn this VID from the SRP Domain attribute
    and tag Streams accordingly.

    The value of this object MUST be retained across
    reinitializations of the management system."
REFERENCE   "35.2.2.8.3b"
DEFVAL      { 2 }
::= { ieee8021SrpBridgePortEntry 4 }

ieee8021SrpBridgePortMsrpTalkerPrunningPerPort OBJECT-TYPE
SYNTAX      TruthValue
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "This parameter controls the forwarding behavior for
    Talker declarations on the port when the TalkerPrunning
    parameter is disabled for the bridge. The value true(1)
    indicates, that Talker declarations are only forwarded
    on that port, if the destination_address of the Stream
    is found in the MAC Address Registration Entries for the
    port. When false(2), Talker declarations are forwarded
    on that port regardless of the destination address."
REFERENCE   "12.22.2, 35.2.1.4k"
DEFVAL      { false }
::= { ieee8021SrpBridgePortEntry 5 }

-- =====
-- The ieee8021SrpLatency subtree
-- This subtree defines the objects necessary for retrieving
-- the latency of the various traffic classes on a port.
-- =====

-- =====
-- the ieee8021SrpLatencyTable
-- =====
ieee8021SrpLatencyTable OBJECT-TYPE
SYNTAX      SEQUENCE OF Ieee8021SrpLatencyEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "A table containing a set of latency measurement
    parameters for each traffic class."
REFERENCE   "35.2.2.8.6"
::= { ieee8021SrpLatency 1 }

ieee8021SrpLatencyEntry OBJECT-TYPE
SYNTAX      Ieee8021SrpLatencyEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "A list of objects containing latency information
    for each traffic class. Rows in the table are
    automatically created for ports that are not an
    SRP domain boundary port (i.e., SRPdomainBoundaryPort
    is FALSE). See 35.1.4, 8.8.2, 12.22.3."
INDEX      { ieee8021BridgeBaseComponentId,
              ieee8021BridgeBasePort,
              ieee8021SrpTrafficClass }
::= { ieee8021SrpLatencyTable 1 }

Ieee8021SrpLatencyEntry ::=
SEQUENCE {
    ieee8021SrpTrafficClass
        IEEE8021FqtssTrafficClassValue,
    ieee8021SrpPortTcLatency
        Unsigned32
}

```

```

ieee8021SrpTrafficClass OBJECT-TYPE
    SYNTAX      IEEE8021FqtssTrafficClassValue
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The traffic class number associated with the
        row of the table.

        Rows in the table are automatically created for
        ports that are not an SRP domain boundary port
        (i.e., SRPdomainBoundaryPort is FALSE)."
```

REFERENCE "35.1.4, 8.8.2, 12.22.3"

```

    ::= { ieee8021SrpLatencyEntry 1 }
```

```

ieee8021SrpPortTcLatency OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "nano-seconds"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of the portTcMaxLatency parameter for the
        traffic class. This value is expressed in
        nano-seconds."
    REFERENCE   "35.2.1.4, 35.2.2.8.6"
    ::= { ieee8021SrpLatencyEntry 2 }
```

```

-- =====
-- The ieee8021SrpStreams subtree
-- This subtree defines the objects necessary for retrieving
-- the characteristics of the various Streams currently registered.
-- =====

-- =====
-- the ieee8021SrpStreamTable
-- =====
ieee8021SrpStreamTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Ieee8021SrpStreamEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A table containing a set of characteristics
        for each registered Stream."
    REFERENCE   "35.2.2.8"
    ::= { ieee8021SrpStreams 1 }
```

```

ieee8021SrpStreamEntry OBJECT-TYPE
    SYNTAX      Ieee8021SrpStreamEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A list of objects containing characteristics
        for each registered Stream. Rows in the table are
        automatically created for Streams registered on any
        port of a Bridge."
    INDEX       { ieee8021SrpStreamId }
    ::= { ieee8021SrpStreamTable 1 }
```

```

Ieee8021SrpStreamEntry ::=
    SEQUENCE {
        ieee8021SrpStreamId
            IEEE8021SrpStreamIdValue,
        ieee8021SrpStreamDestinationAddress
            MacAddress,
        ieee8021SrpStreamVlanId
            IEEE8021VlanIndex,
        ieee8021SrpStreamTspecMaxFrameSize
            Unsigned32,
        ieee8021SrpStreamTspecMaxIntervalFrames
            Unsigned32,
```

IEEE Std 802.1Qcw™-2023
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks
Amendment 36: YANG Data Models for Scheduled Traffic, Frame Preemption, and Per-Stream Filtering and Policing

```

ieee8021SrpStreamDataFramePriority
    INTEGER IEEE8021PriorityCodePoint,
ieee8021SrpStreamRank
    IEEE8021SrpStreamRankValue
}

ieee8021SrpStreamId OBJECT-TYPE
    SYNTAX      IEEE8021SrpStreamIdValue
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The Stream ID associated with the row of the table.

        Rows in the table are automatically created when
        Streams are registered via MSRP."
    REFERENCE   "35.2.2.8.2"
    ::= { ieee8021SrpStreamEntry 1 }

ieee8021SrpStreamDestinationAddress OBJECT-TYPE
    SYNTAX      MacAddress
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The MAC destination address for the Stream described
        by this reservation."
    REFERENCE   "35.2.2.8.3a"
    ::= { ieee8021SrpStreamEntry 2 }

ieee8021SrpStreamVlanId OBJECT-TYPE
    SYNTAX      IEEE8021VlanIndex
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The VLAN ID associated with the MSRP registration
        for this Stream."
    REFERENCE   "35.2.2.8.3b"
    ::= { ieee8021SrpStreamEntry 3 }

ieee8021SrpStreamTspecMaxFrameSize OBJECT-TYPE
    SYNTAX      Unsigned32 (0..65535)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The maximum size frame that will be sent by
        a Talker for this Stream. This value is part
        of the Traffic Specification for the Stream."
    REFERENCE   "35.2.2.8.4a"
    ::= { ieee8021SrpStreamEntry 4 }

ieee8021SrpStreamTspecMaxIntervalFrames OBJECT-TYPE
    SYNTAX      Unsigned32 (0..65535)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The maximum number of frame that will be sent
        during a class measurement interval (L.2). This
        value is part of the Traffic Specification for
        the Stream."
    REFERENCE   "35.2.2.8.4b, L.2"
    ::= { ieee8021SrpStreamEntry 5 }

ieee8021SrpStreamDataFramePriority OBJECT-TYPE
    SYNTAX      INTEGER (0..7) IEEE8021PriorityCodePoint
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The Priority Code Point (PCP) value that the
        referenced Stream will be tagged with. This value
        is used to distinguish Class A and Class B traffic."
    REFERENCE   "35.2.2.8.5a"
    ::= { ieee8021SrpStreamEntry 6 }

```

IEEE Std 802.1Qcw™-2023
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks
Amendment 36: YANG Data Models for Scheduled Traffic, Frame Preemption, and Per-Stream Filtering and Policing

```

ieee8021SrpStreamRank OBJECT-TYPE
    SYNTAX      IEEE8021SrpStreamRankValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "SRP supports emergency and non-emergency.
        Emergency traffic will interrupt non-emergency
        traffic if there is insufficient bandwidth or
        resources available for the emergency traffic."
    REFERENCE   "35.2.2.8.5b"
    ::= { ieee8021SrpStreamEntry 7 }

-- =====
-- the ieee8021SrpStreamPreloadTable
-- =====
ieee8021SrpStreamPreloadTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Ieee8021SrpStreamPreloadEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A table containing a set of parameters for each StreamID
        that is preloaded on the Bridge as it initializes."
    REFERENCE   "12.22.6"
    ::= { ieee8021SrpStreams 2 }

ieee8021SrpStreamPreloadEntry OBJECT-TYPE
    SYNTAX      Ieee8021SrpStreamPreloadEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A list of objects containing characteristics
        for each registered Stream. Rows in the table are
        automatically created for Streams registered on any
        port of a Bridge."
    INDEX       { ieee8021SrpStreamPreloadId }
    ::= { ieee8021SrpStreamPreloadTable 1 }

Ieee8021SrpStreamPreloadEntry ::=
    SEQUENCE {
        ieee8021SrpStreamPreloadId
            IEEE8021SrpStreamIdValue,
        ieee8021SrpStreamPreloadDestinationAddress
            MacAddress,
        ieee8021SrpStreamPreloadVlanId
            IEEE8021VlanIndex,
        ieee8021SrpStreamPreloadTspecMaxFrameSize
            Unsigned32,
        ieee8021SrpStreamPreloadTspecMaxIntervalFrames
            Unsigned32,
        ieee8021SrpStreamPreloadDataFramePriority
            INTEGER IEEE8021PriorityCodePoint,
        ieee8021SrpStreamPreloadRank
            IEEE8021SrpStreamRankValue
    }

ieee8021SrpStreamPreloadId OBJECT-TYPE
    SYNTAX      IEEE8021SrpStreamIdValue
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The 64-bit StreamID is used to match Talker
        registrations with their corresponding Listener
        registrations (35.2.4)."
    REFERENCE   "12.22.6, 35.2.2.8.2"
    ::= { ieee8021SrpStreamPreloadEntry 1 }

ieee8021SrpStreamPreloadDestinationAddress OBJECT-TYPE
    SYNTAX      MacAddress
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION

```

"The MAC destination address for the Stream described by this reservation."

REFERENCE "12.22.6, 35.2.2.8.3a"

::= { ieee8021SrpStreamPreloadEntry 2}

ieee8021SrpStreamPreloadVlanId OBJECT-TYPE

SYNTAX IEEE8021VlanIndex

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The VLAN ID associated with the MSRP registration for this Stream."

REFERENCE "12.22.6, 35.2.2.8.3b"

::= { ieee8021SrpStreamPreloadEntry 3}

ieee8021SrpStreamPreloadTspecMaxFrameSize OBJECT-TYPE

SYNTAX Unsigned32 (0..65535)

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The maximum size frame that will be sent by a Talker for this Stream. This value is part of the Traffic Specification for the Stream."

REFERENCE "12.22.6, 35.2.2.8.4a"

::= { ieee8021SrpStreamPreloadEntry 4}

ieee8021SrpStreamPreloadTspecMaxIntervalFrames OBJECT-TYPE

SYNTAX Unsigned32 (0..65535)

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The maximum number of frames that the Talker may transmit in one classMeasurementInterval (34.3). This value is part of the Traffic Specification for the Stream."

REFERENCE "12.22.6, 35.2.2.8.4b"

::= { ieee8021SrpStreamPreloadEntry 5}

ieee8021SrpStreamPreloadDataFramePriority OBJECT-TYPE

SYNTAX INTEGER (0..7) ~~IEEE8021PriorityCodePoint~~

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The Priority Code Point (PCP) value that the referenced Stream will be tagged with. This value is used to distinguish Class A and Class B traffic."

REFERENCE "12.22.6, 35.2.2.8.5a"

::= { ieee8021SrpStreamPreloadEntry 6}

ieee8021SrpStreamPreloadRank OBJECT-TYPE

SYNTAX IEEE8021SrpStreamRankValue

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"SRP supports emergency and non-emergency. Emergency traffic will interrupt non-emergency traffic if there is insufficient bandwidth or resources available for the emergency traffic."

REFERENCE "12.22.6, 35.2.2.8.5b"

::= { ieee8021SrpStreamPreloadEntry 7}

```
-- =====
-- The ieee8021SrpReservations subtree
-- This subtree defines the objects necessary for retrieving
-- the Stream attribute registrations on each port of a Bridge.
-- =====

-- =====
-- the ieee8021SrpReservationsTable
-- =====
ieee8021SrpReservationsTable OBJECT-TYPE
```

```

SYNTAX      SEQUENCE OF Ieee8021SrpReservationsEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "A table containing Stream attribute
    registrations per port."
REFERENCE   "35.2.4"
::= { ieee8021SrpReservations 1 }

ieee8021SrpReservationsEntry OBJECT-TYPE
SYNTAX      Ieee8021SrpReservationsEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "A list of objects containing Stream attribute
    registrations per port. Rows in the table are
    automatically created for Streams registered on any
    port of a Bridge."
INDEX { ieee8021SrpReservationStreamId,
        ieee8021SrpReservationDirection,
        ieee8021BridgeBaseComponentId,
        ieee8021BridgeBasePort }
::= { ieee8021SrpReservationsTable 1 }

Ieee8021SrpReservationsEntry ::=
SEQUENCE {
    ieee8021SrpReservationStreamId
        IEEE8021SrpStreamIdValue,
    ieee8021SrpReservationDirection
        IEEE8021SrpReservationDirectionValue,
    ieee8021SrpReservationDeclarationType
        IEEE8021SrpReservationDeclarationTypeValue,
    ieee8021SrpReservationAccumulatedLatency
        Unsigned32,
    ieee8021SrpReservationFailureSystemId
        OCTET STRING,
    ieee8021SrpReservationFailureCode
        IEEE8021SrpReservationFailureCodeValue,
    ieee8021SrpReservationDroppedStreamFrames
        Counter64,
    ieee8021SrpReservationStreamAge
        Unsigned32
}

ieee8021SrpReservationStreamId OBJECT-TYPE
SYNTAX      IEEE8021SrpStreamIdValue
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The Stream ID associated with the row of the table.

    Rows in the table are automatically created when
    Streams are registered via MSRP."
REFERENCE   "35.2.2.8.2"
::= { ieee8021SrpReservationsEntry 1 }

ieee8021SrpReservationDirection OBJECT-TYPE
SYNTAX      IEEE8021SrpReservationDirectionValue
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The source of this Stream registration, either
    Talker or Listener."
REFERENCE   "35.2.1.2"
::= { ieee8021SrpReservationsEntry 2 }

ieee8021SrpReservationDeclarationType OBJECT-TYPE
SYNTAX      IEEE8021SrpReservationDeclarationTypeValue
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The type of Talker or Listener registration."

```

REFERENCE "35.2.1.3"
::= { ieee8021SrpReservationsEntry 3 }

ieee8021SrpReservationAccumulatedLatency OBJECT-TYPE

SYNTAX Unsigned32
UNITS "nano-seconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The Accumulated Latency associated with the current registration.

For Talker registrations this represents the accumulated latency from the Talker to the ingress port of this Bridge.

For Listener registrations this represents the accumulated latency to the ingress port of the neighbor Bridge or end stations. This include the latency of the media attached to this egress port."

REFERENCE "35.2.2.8.6"
::= { ieee8021SrpReservationsEntry 4 }

ieee8021SrpReservationFailureSystemId OBJECT-TYPE

SYNTAX OCTET STRING(SIZE(8))
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The first system that changes a Talker Advertise to a Talker Failed registration will report its System Identification in this field. That single System Identification is then propagated from system to system."

REFERENCE "35.2.2.8.7a"
::= { ieee8021SrpReservationsEntry 5 }

ieee8021SrpReservationFailureCode OBJECT-TYPE

SYNTAX IEEE8021SrpReservationFailureCodeValue
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The first Bridge that changes a Talker Advertise to a Talker Failed registration will report the Failure Code in this field. That single Failure Code is then propagated from Bridge to Bridge."

REFERENCE "35.2.2.8.7b"
::= { ieee8021SrpReservationsEntry 6 }

ieee8021SrpReservationDroppedStreamFrames OBJECT-TYPE

SYNTAX Counter64
UNITS "frames"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"A count of the number of data stream frames that have been dropped for whatever reason. These are not MSRP frames, but the stream data frames that are carried by the MSRP Reservation.

Discontinuities in the value of the counter can occur at re-initialization of the management system, and at other times as indicated by the value of ifCounterDiscontinuityTime object of the associated interface (if any)."

REFERENCE "35.2.5.1"
::= { ieee8021SrpReservationsEntry 7 }

ieee8021SrpReservationStreamAge OBJECT-TYPE

SYNTAX Unsigned32
UNITS "seconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of seconds since the reservation was established

```

    on this port."
REFERENCE    "35.2.1.4c"
::= { ieee8021SrpReservationsEntry 8 }

-- =====
-- the ieee8021SrpReservationsPreloadTable
-- =====
ieee8021SrpReservationsPreloadTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Ieee8021SrpReservationsPreloadEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A table containing Stream attribute
        registrations per port."
    REFERENCE   "12.22.7"
    ::= { ieee8021SrpReservations 2 }

ieee8021SrpReservationsPreloadEntry OBJECT-TYPE
    SYNTAX      Ieee8021SrpReservationsPreloadEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A list of objects containing Stream attribute
        registrations per port. Rows in the table are
        automatically created for Streams registered on any
        port of a Bridge."
    INDEX { ieee8021SrpReservationsPreloadStreamId,
            ieee8021SrpReservationPreloadDirection,
            ieee8021BridgeBaseComponentId,
            ieee8021BridgeBasePort }
    ::= { ieee8021SrpReservationsPreloadTable 1 }

Ieee8021SrpReservationsPreloadEntry ::=
    SEQUENCE {
        ieee8021SrpReservationsPreloadStreamId
            IEEE8021SrpStreamIdValue,
        ieee8021SrpReservationPreloadDirection
            IEEE8021SrpReservationDirectionValue,
        ieee8021SrpReservationPreloadAccumulatedLatency
            Unsigned32
    }

ieee8021SrpReservationsPreloadStreamId OBJECT-TYPE
    SYNTAX      IEEE8021SrpStreamIdValue
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The 64-bit StreamID is used to match Talker
        registrations with their corresponding Listener
        registrations (35.2.4)."
    REFERENCE   "12.22.7, 35.2.2.8.2"
    ::= { ieee8021SrpReservationsPreloadEntry 1 }

ieee8021SrpReservationPreloadDirection OBJECT-TYPE
    SYNTAX      IEEE8021SrpReservationDirectionValue
    MAX-ACCESS  not-accessibleread-write
    STATUS      current
    DESCRIPTION
        "The source of this Stream registration, either
        Talker or Listener"
    REFERENCE   "12.22.7, 35.2.1.1"
    ::= { ieee8021SrpReservationsPreloadEntry 2 }

ieee8021SrpReservationPreloadAccumulatedLatency OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "nano-seconds"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The Accumulated Latency associated with the current
        registration."

```

IEEE Std 802.1Qcw™-2023
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks
Amendment 36: YANG Data Models for Scheduled Traffic, Frame Preemption, and Per-Stream Filtering and Policing

```

For Talker registrations this represents the accumulated
latency from the Talker to the ingress port of this
Bridge.

For Listener registrations this represents the accumulated
latency to the ingress port of the neighbor Bridge or
end stations. This include the latency of the media
attached to this egress port."
REFERENCE "12.22.7, 35.2.2.8.6"
::= { ieee8021SrpReservationsPreloadEntry 3 }

-- =====
-- IEEE8021 SRP MIB - Conformance Information
-- =====

ieee8021SrpCompliances
  OBJECT IDENTIFIER ::= { ieee8021SrpConformance 1 }
ieee8021SrpGroups
  OBJECT IDENTIFIER ::= { ieee8021SrpConformance 2 }

-- =====
-- units of conformance
-- =====

-- =====
-- the ieee8021SrpConfiguration group
-- =====

ieee8021SrpConfigurationGroup OBJECT-GROUP
  OBJECTS {
    ieee8021SrpBridgeBaseMsrpEnabledStatus,
    ieee8021SrpBridgeBaseMsrpTalkerPruning,
    ieee8021SrpBridgeBaseMsrpMaxFanInPorts,
    ieee8021SrpBridgeBaseMsrpLatencyMaxFrameSize,
    ieee8021SrpBridgeBaseMsrpTalkerVlanPruning,
    ieee8021SrpBridgeBaseMsrpMaxSRClasses,
    ieee8021SrpBridgePortMsrpEnabledStatus,
    ieee8021SrpBridgePortMsrpFailedRegistrations,
    ieee8021SrpBridgePortMsrpLastPduOrigin,
    ieee8021SrpBridgePortSrPvid,
    ieee8021SrpBridgePortMsrpTalkerPruningPerPort
  }
  STATUS      current
  DESCRIPTION
    "Objects that define configuration of SRP."
    ::= { ieee8021SrpGroups 1 }

-- =====
-- the ieee8021SrpLatency group
-- =====

ieee8021SrpLatencyGroup OBJECT-GROUP
  OBJECTS {
    ieee8021SrpPortTcLatency
  }
  STATUS      current
  DESCRIPTION
    "Objects that define latency for SRP."
    ::= { ieee8021SrpGroups 2 }

-- =====
-- the ieee8021SrpStreams group
-- =====

ieee8021SrpStreamsGroup OBJECT-GROUP
  OBJECTS {
    -- ieee8021SrpStreamId,
    ieee8021SrpStreamDestinationAddress,
    ieee8021SrpStreamVlanId,
    ieee8021SrpStreamTspecMaxFrameSize,
  }

```

```

        ieee8021SrpStreamTspecMaxIntervalFrames,
        ieee8021SrpStreamDataFramePriority,
        ieee8021SrpStreamRank
    }
    STATUS      current
    DESCRIPTION
        "Objects that define Streams for SRP."
    ::= { ieee8021SrpGroups 3 }

-- =====
-- the ieee8021SrpReservations group
-- =====

ieee8021SrpReservationsGroup OBJECT-GROUP
    OBJECTS {
        -- ieee8021SrpReservationStreamId,
        -- ieee8021SrpReservationDirection,
        ieee8021SrpReservationDeclarationType,
        ieee8021SrpReservationAccumulatedLatency,
        ieee8021SrpReservationFailureSystemId,
        ieee8021SrpReservationFailureCode,
        ieee8021SrpReservationDroppedStreamFrames,
        ieee8021SrpReservationStreamAge
    }
    STATUS      current
    DESCRIPTION
        "Objects that define Stream Reservations for SRP."
    ::= { ieee8021SrpGroups 4 }

-- =====
-- the ieee8021SrpConfigurationPruning group
-- =====

ieee8021SrpConfigurationPruningGroup OBJECT-GROUP
    OBJECTS {
        ieee8021SrpBridgeBaseMsrpTalkerVlanPruning,
        ieee8021SrpBridgePortMsrpTalkerPruningPerPort
    }
    STATUS      current
    DESCRIPTION
        "Objects that allow configuration of pruning behavior
        for SRP."
    ::= { ieee8021SrpGroups 5 }

-- =====
-- the ieee8021SrpMonitoringSRclasses group
-- =====

ieee8021SrpMonitoringSRclassesGroup OBJECT-GROUP
    OBJECTS {
        ieee8021SrpBridgeBaseMsrpMaxSRClasses
    }
    STATUS      current
    DESCRIPTION
        "Objects that provides information on the maximum number
        of SR classes supported on the Bridge."
    ::= { ieee8021SrpGroups 6 }

-- =====
-- the ieee8021SrpStreamsPreload group
-- =====

ieee8021SrpStreamsPreloadGroup OBJECT-GROUP
    OBJECTS {
        ieee8021SrpStreamPreloadId,
        ieee8021SrpStreamPreloadDestinationAddress,
        ieee8021SrpStreamPreloadVlanId,
        ieee8021SrpStreamPreloadTspecMaxFrameSize,
        ieee8021SrpStreamPreloadTspecMaxIntervalFrames,
        ieee8021SrpStreamPreloadDataFramePriority,
        ieee8021SrpStreamPreloadRank
    }

```

IEEE Std 802.1Qcw™-2023
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks
Amendment 36: YANG Data Models for Scheduled Traffic, Frame Preemption, and Per-Stream Filtering and Policing

```

STATUS      current
DESCRIPTION
    "Objects that allow to preload parameters for each
    StreamId on Bridge Ports as the Bridge initializes."
::= { ieee8021SrpGroups 7 }

-- =====
-- the ieee8021SrpReservationsPreload group
-- =====

ieee8021SrpReservationsPreloadGroup OBJECT-GROUP
OBJECTS {
ieee8021SrpReservationsPreloadStreamId,
ieee8021SrpReservationPreloadDirection,
    ieee8021SrpReservationPreloadAccumulatedLatency
}
STATUS      current
DESCRIPTION
    "Objects that allow to initialize Streams within each
    Bridge as it powers up, to preload the Stream
    registrations that will later be provided by operation
    of SRP."
::= { ieee8021SrpGroups 8 }

-- =====
-- compliance statements
-- =====

ieee8021SrpCompliance MODULE-COMPLIANCE
STATUS      current
DESCRIPTION
    "The compliance statement for devices supporting
    Stream Reservation Protocol.

    Support of the objects defined in the IEEE8021-SRP MIB
    also requires support of the IEEE8021-BRIDGE-MIB; the
    provisions of 17.3.2 apply to implementations claiming
    support of the IEEE8021-SRP MIB."

MODULE -- this module
MANDATORY-GROUPS {
    ieee8021SrpConfigurationGroup,
    ieee8021SrpLatencyGroup,
    ieee8021SrpStreamsGroup,
    ieee8021SrpReservationsGroup
}

GROUP      ieee8021SrpConfigurationPruningGroup
DESCRIPTION
    "Implementation of this group is optional. Implementation
    will allow configuration of pruning behavior for SRP."

GROUP      ieee8021SrpMonitoringSRclassesGroup
DESCRIPTION
    "Implementation of this group is optional. Implementation
    will allow configuration of pruning behavior for SRP."

GROUP      ieee8021SrpStreamsPreloadGroup
DESCRIPTION
    "Implementation of this group is optional. Implementation
    will allow to preload parameters for each StreamId on
    Bridge Ports as the Bridge initializes."

GROUP      ieee8021SrpReservationsPreloadGroup
DESCRIPTION
    "Implementation of this group is optional. Implementation
    will allow to initialize Streams within each Bridge as it
    powers up, to preload the Stream registrations that will
    later be provided by operation of SRP."

::= { ieee8021SrpCompliances 1 }

```

IEEE Std 802.1Qcw™-2023
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks
Amendment 36: YANG Data Models for Scheduled Traffic, Frame Preemption, and Per-Stream Filtering and Policing

END

17.7.22 Definitions for the IEEE8021-ST-MIB module

Change 17.7.22 as follows:

```
IEEE8021-ST-MIB DEFINITIONS ::= BEGIN

-- =====
-- MIB for support of the Scheduled Traffic Enhancements
-- for IEEE 802.1Q Bridges.
-- =====

IMPORTS
    MODULE-IDENTITY,
    OBJECT-TYPE,
    Unsigned32,
    Counter64
        FROM SNMPv2-SMI
    TEXTUAL-CONVENTION,
    TruthValue
        FROM SNMPv2-TC
    MODULE-COMPLIANCE,
    OBJECT-GROUP
        FROM SNMPv2-CONF
    ieee802dot1mibs
        FROM IEEE8021-TC-MIB
    ieee8021BridgeBaseComponentId,
    ieee8021BridgeBasePort
        FROM IEEE8021-BRIDGE-MIB
    ;

ieee8021STMib MODULE-IDENTITY
    LAST-UPDATED "202211080000Z" November 8, 2022 "202309260000Z" -- September 26, 2023
    ORGANIZATION "IEEE 802.1 Working Group"
    CONTACT-INFO
        " WG-URL: http://www.ieee802.org/1/
          WG-EMail: stds-802-1-l@ieee.org
          Contact: IEEE 802.1 Working Group Chair
          Postal: C/O IEEE 802.1 Working Group
                  IEEE Standards Association
                  445 Hoes Lane
                  Piscataway, NJ 08854
                  USA
          E-mail: stds-802-1-chairs@ieee.org"
    DESCRIPTION
        "The Bridge MIB module for managing devices that support
        the Scheduled Traffic Enhancements
        for IEEE 802.1Q Bridges.

        Unless otherwise indicated, the references in this MIB
        module are to IEEE Std 802.1Q-2022 as amended by
        IEEE Std 802.1Qcz and IEEE Std 802.1Qcw.

        Copyright (C) IEEE (20222023).
        This version of this MIB module is part of IEEE Std 802.1Q;
        see that standard for full legal notices."

        REVISION "202309260000Z" -- September 26, 2023
        DESCRIPTION
            "Update to include SupportedCycleMax and
            SupportedIntervalMax parameters.
            Published as part of IEEE Std 802.1Qcw-2023."

        REVISION "202211080000Z" -- November 8, 2022
        DESCRIPTION
            "Published as part of IEEE Std 802.1Q-2022.
            Cross references and contact information updated."

        REVISION "201807010000Z" -- July 1, 2018
        DESCRIPTION
```

"Published as part of IEEE Std 802.1Q 2018 revision.
Cross references updated and corrected."

REVISION "201608150000Z" -- August 15, 2016

DESCRIPTION

"Revised to include Set-And-Hold-MAC and
Set-And-Release-MAC in the description of
ieee8021STAdminControlList and
ieee8021STOperControlList.
Published as part of IEEE Std 802.1Qbu."

REVISION "201602190000Z" -- February 19, 2016

DESCRIPTION

"Initial version published as part of IEEE Std 802.1Qbv."

::= { ieee802dot1mibs 30 }

-- =====
-- Textual Conventions
-- =====

IEEE8021STTrafficClassValue ::= TEXTUAL-CONVENTION

DISPLAY-HINT "d"

STATUS current

DESCRIPTION

"A traffic class value.
This is the numerical value associated with a traffic
class in a Bridge. Larger values are associated with
higher priority traffic classes."

REFERENCE "12.29.1"

SYNTAX Unsigned32 (0..7)

IEEE8021STPTptimeValue ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"A PTptime value, represented as a 48-bit unsigned integer
number of seconds and a 32-bit unsigned integer number of
nanoseconds.

The first 6 octets represent the number of seconds: the
first octet is the most significant
octet of the 48-bit seconds value and the sixth octet
is the least significant octet of the seconds value.
The remaining octets, 7 through 10, represent the
number of nanoseconds: the seventh octet
is the most significant octet of the 32-bit nanoseconds
value and the tenth octet is the
least significant octet of the nanoseconds value."

REFERENCE "8.6.8.4, 8.6.9.4, 12.29.1"

SYNTAX OCTET STRING (SIZE(10))

-- =====
-- subtrees in the ST MIB
-- =====

ieee8021STNotifications

OBJECT IDENTIFIER ::= { ieee8021STMib 0 }

ieee8021STObjects

OBJECT IDENTIFIER ::= { ieee8021STMib 1 }

ieee8021STConformance

OBJECT IDENTIFIER ::= { ieee8021STMib 2 }

ieee8021STMaxSDUSubtree

OBJECT IDENTIFIER ::= { ieee8021STObjects 1 }

ieee8021STParameters

OBJECT IDENTIFIER ::= { ieee8021STObjects 2 }

-- =====
-- The ieee8021STMaxSDUSubtree subtree

```
-- This subtree defines the objects necessary for the management
-- of the max SDU size parameters for each traffic class on a Port.
-- =====
```

```
-- =====
-- the ieee8021STMaxSDUTable
-- =====
```

```
ieee8021STMaxSDUTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Ieee8021STMaxSDUEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A table containing a set of max SDU
        parameters, one for each traffic class.
        All writable objects in this table must be
        persistent over power up restart/reboot."
    REFERENCE   "8.6.8.4, 8.6.9.4, 12.29.1"
    ::= { ieee8021STMaxSDUSubtree 1 }
```

```
ieee8021STMaxSDUEntry OBJECT-TYPE
    SYNTAX      Ieee8021STMaxSDUEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A list of objects containing Max SDU size
        for each traffic class supported by the Port."
    INDEX { ieee8021BridgeBaseComponentId,
            ieee8021BridgeBasePort,
            ieee8021STTrafficClass }
    ::= { ieee8021STMaxSDUTable 1 }
```

```
Ieee8021STMaxSDUEntry ::=
    SEQUENCE {
        ieee8021STTrafficClass
            IEEE8021STTrafficClassValue,
        ieee8021STMaxSDU
            Unsigned32,
        ieee8021TransmissionOverrun
            Counter64
    }
```

```
ieee8021STTrafficClass OBJECT-TYPE
    SYNTAX      IEEE8021STTrafficClassValue
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The traffic class number associated with the row of
        the table.

        A row in this table is created for each traffic class
        that is supported by the Port"
    REFERENCE   "8.6.8.4, 8.6.9.4, 12.29.1"
    ::= { ieee8021STMaxSDUEntry 1 }
```

```
ieee8021STMaxSDU OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "octets"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The value of the MaxSDU parameter for the traffic class.
        This value is represented as an unsigned integer. A value
        of 0 is interpreted as the max SDU size supported by
        the underlying MAC.

        The default value of the MaxSDU parameter is 0.

        The value of this object MUST be retained across
        reinitializations of the management system."
    REFERENCE   "8.6.8.4, 8.6.9.4, 12.29.1"
```

```

DEFVAL { 0 }
::= { ieee8021STMaxSDUEntry 2}

ieee8021TransmissionOverrun OBJECT-TYPE
    SYNTAX      Counter64
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter of transmission overrun events, where
         a PDU is still being transmitted by a MAC at the
         time when the transmission gate for the queue closed."
    REFERENCE   "8.6.8.4, 8.6.9.4, 12.29.1, 12.29.1.1.2"
    DEFVAL { 0 }
    ::= { ieee8021STMaxSDUEntry 3}

-- =====
-- The ieee8021STParameters subtree
-- This subtree defines the objects necessary for the management
-- of the traffic scheduling mechanism for IEEE Std 802.1Q.
-- =====

-- =====
-- the ieee8021STParametersTable
-- =====

ieee8021STParametersTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Ieee8021STParametersEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A table that contains the per-port manageable parameters for
         traffic scheduling.

         For a given Port, a row in the table exists.

         All writable objects in this table must be
         persistent over power up restart/reboot."
    REFERENCE   "8.6.8.4, 8.6.9.4, 12.29.1"
    ::= { ieee8021STParameters 1 }

ieee8021STParametersEntry OBJECT-TYPE
    SYNTAX      Ieee8021STParametersEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A list of objects that contains the manageable parameters for
         traffic scheduling for a port."
    INDEX { ieee8021BridgeBaseComponentId,
            ieee8021BridgeBasePort
          }
    ::= { ieee8021STParametersTable 1 }

Ieee8021STParametersEntry ::=
    SEQUENCE {
        ieee8021STGateEnabled
            TruthValue,
        ieee8021STAdminGateStates
            OCTET STRING,
        ieee8021STOperGateStates
            OCTET STRING,
        ieee8021STAdminControlListLength
            Unsigned32,
        ieee8021STOperControlListLength
            Unsigned32,
        ieee8021STAdminControlList
            OCTET STRING,
        ieee8021STOperControlList
            OCTET STRING,
        ieee8021STAdminCycleTimeNumerator
            Unsigned32,
    }

```

```

ieee8021STAdminCycleTimeDenominator
    Unsigned32,
ieee8021STOperCycleTimeNumerator
    Unsigned32,
ieee8021STOperCycleTimeDenominator
    Unsigned32,
ieee8021STAdminCycleTimeExtension
    Unsigned32,
ieee8021STOperCycleTimeExtension
    Unsigned32,
ieee8021STAdminBaseTime
    IEEE8021STPTPtimeValue,
ieee8021STOperBaseTime
    IEEE8021STPTPtimeValue,
ieee8021STConfigChange
    TruthValue,
ieee8021STConfigChangeTime
    IEEE8021STPTPtimeValue,
ieee8021STTickGranularity
    Unsigned32,
ieee8021STCurrentTime
    IEEE8021STPTPtimeValue,
ieee8021STConfigPending
    TruthValue,
ieee8021STConfigChangeError
    Counter64,
ieee8021STSupportedListMax
    Unsigned32,
ieee8021STSupportedCycleMaxNumerator
    Unsigned32,
ieee8021STSupportedCycleMaxDenominator
    Unsigned32,
ieee8021STSupportedIntervalMax
    Unsigned32
}

ieee8021STGateEnabled OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The GateEnabled parameter determines whether traffic scheduling
        is active (true) or inactive (false).

        The value of this object MUST be retained across
        reinitializations of the management system."
    REFERENCE   "8.6.8.4, 8.6.9.4, 12.29.1"
    DEFVAL { false }
    ::= { ieee8021STParametersEntry 1 }

ieee8021STAdminGateStates OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE(1))
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The administrative value of the GateStates parameter for the Port.
        The bits of the octet represent the gate states for the
        corresponding traffic classes; the MS bit corresponds to traffic class 7,
        the LS bit to traffic class 0. A bit value of 0 indicates closed; a
        bit value of 1 indicates open.

        The value of this object MUST be retained across
        reinitializations of the management system."
    REFERENCE   "8.6.8.4, 8.6.9.4, 12.29.1"
    ::= { ieee8021STParametersEntry 2 }

ieee8021STOperGateStates OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE(1))
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The operational value of the GateStates parameter for the Port.

```

The bits of the octet represent the gate states for the corresponding traffic classes; the MS bit corresponds to traffic class 7, the LS bit to traffic class 0. A bit value of 0 indicates closed; a bit value of 1 indicates open."

REFERENCE "8.6.8.4, 8.6.9.4, 12.29.1"
 ::= { ieee8021STParametersEntry 3 }

ieee8021STAdminControlListLength OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The administrative value of the ListMax parameter for the Port. The integer value indicates the number of entries (TLVs) in the AdminControlList.

The value of this object MUST be retained across reinitializations of the management system."

REFERENCE "8.6.8.4, 8.6.9.4, 12.29.1"
 ::= { ieee8021STParametersEntry 4 }

ieee8021STOperControlListLength OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The operational value of the ListMax parameter for the Port. The integer value indicates the number of entries (TLVs) in the OperControlList."

REFERENCE "8.6.8.4, 8.6.9.4, 12.29.1"
 ::= { ieee8021STParametersEntry 5 }

ieee8021STAdminControlList OBJECT-TYPE

SYNTAX OCTET STRING

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The administrative value of the ControlList parameter for the Port. The octet string value represents the contents of the control list as an ordered list of entries, each encoded as a TLV, as follows.

The first octet of each TLV is interpreted as an unsigned integer representing a gate operation name:

- 0: SetGateStates
- 1: Set-And-Hold-MAC
- 2: Set-And-Release-MAC
- 3-255: Reserved for future gate operations

The second octet of the TLV is the length field, interpreted as an unsigned integer, indicating the number of octets of the value that follows the length. A length of zero indicates that there is no value (i.e., the gate operation has no parameters).

The third through (3 + length - 1)th octets encode the parameters of the gate operation, in the order that they appear in the definition of the operation in Table 8-6. Two parameter types are currently defined:

- GateState:

A GateState parameter is encoded in a single octet. The bits of the octet represent the gate states for the corresponding traffic classes; the MS bit corresponds to traffic class 7, the LS bit to traffic class 0. A bit value of 0 indicates closed; a bit value of 1 indicates open.

- TimeInterval:

A TimeInterval is encoded in 4 octets as a 32-bit unsigned integer, representing a number of nanoseconds. The first octet encodes the most significant 8 bits of the integer, and the fourth octet encodes the least significant 8 bits.

IEEE Std 802.1Qcw™-2023
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks
Amendment 36: YANG Data Models for Scheduled Traffic, Frame Preemption, and Per-Stream Filtering and Policing

The value of this object MUST be retained across reinitializations of the management system."
REFERENCE "8.6.8.4, 8.6.9.4, 12.29.1"
::= { ieee8021STParametersEntry 6 }

ieee8021STOperControlList OBJECT-TYPE

SYNTAX OCTET STRING

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The operational value of the ListMax parameter for the Port.
The octet string value represents the contents of the control list as an ordered list of TLVs, as follows.
The first octet of each TLV is interpreted as a gate operation name:
0: SetGateStates
1: Set-And-Hold-MAC
2: Set-And-Release-MAC
3-255: Reserved for future gate operations

The second octet of the TLV is the length field, interpreted as an unsigned integer, indicating the number of octets of the value that follows the length. A length of zero indicates that there is no value (i.e., the gate operation has no parameters).

The third through (3 + length -1)th octets encode the parameters of the gate operation, in the order that they appear in the definition of the operation in Table 8-6. Two parameter types are currently defined:

- GateState:
A GateState parameter is encoded in a single octet. The bits of the octet represent the gate states for the corresponding traffic classes; the MS bit corresponds to traffic class 7, the LS bit to traffic class 0. A bit value of 0 indicates closed; a bit value of 1 indicates open.
- TimeInterval:
A TimeInterval is encoded in 4 octets as a 32-bit unsigned integer, representing a number of nanoseconds. The first octet encodes the most significant 8 bits of the integer, and the fourth octet encodes the least significant 8 bits."

REFERENCE "8.6.8.4, 8.6.9.4, 12.29.1"
::= { ieee8021STParametersEntry 7 }

ieee8021STAdminCycleTimeNumerator OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The administrative value of the numerator of the CycleTime parameter for the Port.
The numerator and denominator together represent the cycle time as a rational number of seconds.

The value of this object MUST be retained across reinitializations of the management system."

REFERENCE "8.6.8.4, 8.6.9.4, 12.29.1"
::= { ieee8021STParametersEntry 8 }

ieee8021STAdminCycleTimeDenominator OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The administrative value of the denominator of the CycleTime parameter for the Port.
The numerator and denominator together represent the cycle time as a rational number of seconds.

IEEE Std 802.1Qcw™-2023
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks
Amendment 36: YANG Data Models for Scheduled Traffic, Frame Preemption, and Per-Stream Filtering and Policing

The value of this object MUST be retained across reinitializations of the management system."
REFERENCE "8.6.8.4, 8.6.9.4, 12.29.1"
::= { ieee8021STParametersEntry 9 }

ieee8021STOperCycleTimeNumerator OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The operational value of the numerator of the CycleTime parameter for the Port.
The numerator and denominator together represent the cycle time as a rational number of seconds."
REFERENCE "8.6.8.4, 8.6.9.4, 12.29.1"
::= { ieee8021STParametersEntry 10 }

ieee8021STOperCycleTimeDenominator OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The operational value of the denominator of the CycleTime parameter for the Port.
The numerator and denominator together represent the cycle time as a rational number of seconds."
REFERENCE "8.6.8.4, 8.6.9.4, 12.29.1"
::= { ieee8021STParametersEntry 11 }

ieee8021STAdminCycleTimeExtension OBJECT-TYPE
SYNTAX Unsigned32
UNITS "nanoseconds"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"The administrative value of the CycleTimeExtension parameter for the Port.
The value is an unsigned integer number of nanoseconds.

The value of this object MUST be retained across reinitializations of the management system."
REFERENCE "8.6.8.4, 8.6.9.4, 12.29.1"
::= { ieee8021STParametersEntry 12 }

ieee8021STOperCycleTimeExtension OBJECT-TYPE
SYNTAX Unsigned32
UNITS "nanoseconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The operational value of the CycleTimeExtension parameter for the Port.
The value is an unsigned integer number of nanoseconds."
REFERENCE "8.6.8.4, 8.6.9.4, 12.29.1"
::= { ieee8021STParametersEntry 13 }

ieee8021STAdminBaseTime OBJECT-TYPE
SYNTAX IEEE8021STPTPtimeValue
UNITS "PTP time"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"The administrative value of the BaseTime parameter for the Port.
The value is a representation of a PTPtime value, consisting of a 48-bit integer number of seconds and a 32-bit integer number of nanoseconds.

The value of this object MUST be retained across reinitializations of the management system."
REFERENCE "8.6.8.4, 8.6.9.4, 12.29.1"
::= { ieee8021STParametersEntry 14 }

```

ieee8021STOperBaseTime OBJECT-TYPE
    SYNTAX      IEEE8021STPTptimeValue
    UNITS       "PTP time"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The operational-operational value of the BaseTime parameter for the Port.
        The value is a representation of a PTptime value,
        consisting of a 48-bit integer
        number of seconds and a 32-bit integer number of nanoseconds."
    REFERENCE   "8.6.8.4, 8.6.9.4, 12.29.1"
    ::= { ieee8021STParametersEntry 15 }

ieee8021STConfigChange OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The ConfigChange parameter signals the start of a
        configuration change
        when it is set to TRUE. This should only be done
        when the various administrative parameters
        are all set to appropriate values."
    REFERENCE   "8.6.8.4, 8.6.9.4, 12.29.1"
    ::= { ieee8021STParametersEntry 16 }

ieee8021STConfigChangeTime OBJECT-TYPE
    SYNTAX      IEEE8021STPTptimeValue
    UNITS       "PTP time"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The PTptime at which the next config change is scheduled to occur.
        The value is a representation of a PTptime value,
        consisting of a 48-bit integer
        number of seconds and a 32-bit integer number of nanoseconds.

        The value of this object MUST be retained across
        reinitializations of the management system."
    REFERENCE   "8.6.8.4, 8.6.9.4, 12.29.1"
    ::= { ieee8021STParametersEntry 17 }

ieee8021STTickGranularity OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The granularity of the cycle time clock, represented as an
        unsigned number of tenths of nanoseconds.

        The value of this object MUST be retained across
        reinitializations of the management system."
    REFERENCE   "8.6.8.4, 8.6.9.4, 12.29.1"
    ::= { ieee8021STParametersEntry 18 }

ieee8021STCurrentTime OBJECT-TYPE
    SYNTAX      IEEE8021STPTptimeValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The current time, in PTptime, as maintained by the local system.
        The value is a representation of a PTptime value,
        consisting of a 48-bit integer
        number of seconds and a 32-bit integer number of nanoseconds."
    REFERENCE   "8.6.8.4, 8.6.9.4, 12.29.1"
    ::= { ieee8021STParametersEntry 19 }

ieee8021STConfigPending OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION

```

"The value of the ConfigPending state machine variable.
The value is TRUE if a configuration change is in progress
but has not yet completed."
REFERENCE "8.6.8.4, 8.6.9.4, 12.29.1"
::= { ieee8021STParametersEntry 20 }

ieee8021STConfigChangeError OBJECT-TYPE
SYNTAX Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"A counter of the number of times that a re-configuration
of the traffic schedule has been requested with the old
schedule still running and the requested base time was
in the past."
REFERENCE "8.6.8.4, 8.6.9.3, 12.29.1"
::= { ieee8021STParametersEntry 21 }

ieee8021STSupportedListMax OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The maximum value supported by this Port of the
AdminControlListLength and OperControlListLength
parameters."
REFERENCE "12.29.1.5"
::= { ieee8021STParametersEntry 22 }

ieee8021STSupportedCycleMaxNumerator OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The numerator of the SupportedCycleMax parameter for
the Port. The numerator and denominator together
represent the maximum value supported by this Port of
the AdminCycleTime and OperCycleTime parameters"
REFERENCE "12.29.1.6"
::= { ieee8021STParametersEntry 23 }

ieee8021STSupportedCycleMaxDenominator OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The denominator of the SupportedCycleMax parameter for
the Port. The numerator and denominator together
represent the maximum value supported by this Port of
the AdminCycleTime and OperCycleTime parameters"
REFERENCE "12.29.1.6"
::= { ieee8021STParametersEntry 24 }

ieee8021STSupportedIntervalMax OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The maximum value supported by this Port of the
TimeIntervalValue parameter."
REFERENCE "12.29.1.7"
::= { ieee8021STParametersEntry 25 }

-- =====
-- IEEE8021 ~~ST~~~~QTS~~ MIB - Conformance Information
-- =====

ieee8021STCompliances
OBJECT IDENTIFIER ::= { ieee8021STConformance 1 }

ieee8021STGroups
OBJECT IDENTIFIER ::= { ieee8021STConformance 2 }

```

-- =====
-- units of conformance
-- =====

-- =====
-- the ieee8021STObjectsGroup group
-- =====

ieee8021STObjectsGroup OBJECT-GROUP
  OBJECTS {
    ieee8021STMaxSDU,
    ieee8021STTransmissionOverrun,
    ieee8021STGateEnabled,
    ieee8021STAdminGateStates,
    ieee8021STOperGateStates,
    ieee8021STAdminControlListLength,
    ieee8021STOperControlListLength,
    ieee8021STAdminControlList,
    ieee8021STOperControlList,
    ieee8021STAdminCycleTimeNumerator,
    ieee8021STAdminCycleTimeDenominator,
    ieee8021STOperCycleTimeNumerator,
    ieee8021STOperCycleTimeDenominator,
    ieee8021STAdminCycleTimeExtension,
    ieee8021STOperCycleTimeExtension,
    ieee8021STAdminBaseTime,
    ieee8021STOperBaseTime,
    ieee8021STConfigChange,
    ieee8021STConfigChangeTime,
    ieee8021STTickGranularity,
    ieee8021STCurrentTime,
    ieee8021STConfigPending,
    ieee8021STConfigChangeError,
    ieee8021STSupportedListMax,
    ieee8021STSupportedCycleMaxNumerator,
    ieee8021STSupportedCycleMaxDenominator,
    ieee8021STSupportedIntervalMax
  }
  STATUS      current
  DESCRIPTION
    "Objects that allow management of scheduled traffic."
    ::= { ieee8021STGroups 1 }

-- =====
-- compliance statements
-- =====

ieee8021STCompliance MODULE-COMPLIANCE
  STATUS      current
  DESCRIPTION
    "The compliance statement for devices supporting
    scheduled traffic.

    Support of the objects defined in this MIB module
    also requires support of the IEEE8021-BRIDGE-MIB; the
    provisions of 17.3.2 apply to implementations claiming
    support of this MIB. "

  MODULE -- this module
    MANDATORY-GROUPS {
      ieee8021STObjectsGroup
    }

    ::= { ieee8021STCompliances 1 }

END

```

IEEE Std 802.1Qcw™-2023
 IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks
 Amendment 36: YANG Data Models for Scheduled Traffic, Frame Preemption, and Per-Stream Filtering and Policing

17.7.24 Definitions for the IEEE8021-PSFP-MIB module

Change 17.7.24 as follows:

```
IEEE8021-PSFP-MIB DEFINITIONS ::= BEGIN

-- =====
-- MIB for support of the Per-Stream Filtering and Policing
-- Enhancements for IEEE 802.1Q Bridges.
-- =====

IMPORTS
    MODULE-IDENTITY,
    OBJECT-TYPE,
    Unsigned32,
    Integer32,
    Counter64
        FROM SNMPv2-SMI
    TruthValue, RowStatus
        FROM SNMPv2-TC
    MODULE-COMPLIANCE,
    OBJECT-GROUP
        FROM SNMPv2-CONF
    ieee802dot1mibs
        FROM IEEE8021-TC-MIB
    ieee8021BridgeBaseComponentId
        FROM IEEE8021-BRIDGE-MIB
    IEEE8021STPTptimeValue
        FROM IEEE8021-ST-MIB
    ;

ieee8021PSFPMib MODULE-IDENTITY
    LAST-UPDATED "202201130000Z" January 13, 2022 "202309260000Z" -- September 26, 2023
    ORGANIZATION "IEEE 802.1 Working Group"
    CONTACT-INFO
        " WG-URL: http://www.ieee802.org/1/
        WG-EMail: stds-802-1-l@ieee.org
        Contact: IEEE 802.1 Working Group Chair
        Postal: C/O IEEE 802.1 Working Group
                IEEE Standards Association
                445 Hoes Lane
                Piscataway, NJ 08854
                USA
        E-mail: stds-802-1-chairs@ieee.org"
    DESCRIPTION
        "The Bridge MIB module for managing devices that support
        the Per-Stream Filtering and Policing enhancements
        for IEEE 802.1Q Bridges.

        Unless otherwise indicated, the references in this MIB
        module are to IEEE Std 802.1Q-2022.

        Copyright (C) IEEE (20222023).
        This version of this MIB module is part of IEEE Std 802.1Q;
        see that standard for full legal notices."

        REVISION "202309260000Z" -- September 26, 2023
        DESCRIPTION
        "Update to include SupportedCycleMax and
        SupportedIntervalMax parameters.
        Published as part of IEEE Std 802.1Qcw-2023."

        REVISION "202201130000Z" -- January 13, 2022
        DESCRIPTION
            "Published as part of IEEE Std 802.1Q-2022.
            Cross references and contact information updated."

        REVISION "202011060000Z" -- November 6, 2020
        DESCRIPTION
            "Published as part of IEEE Std 802.1Qcr-2020.
```

IEEE Std 802.1Qcw™-2023
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks
Amendment 36: YANG Data Models for Scheduled Traffic, Frame Preemption, and Per-Stream Filtering and Policing

Cross references and contact information updated."

REVISION "201807010000Z" -- July 1, 2018
DESCRIPTION
"Published as part of IEEE Std 802.1Q 2018 revision.
Cross references updated and corrected."

REVISION "201709080000Z" -- September 29, 2017
DESCRIPTION
"Initial version published as part of IEEE Std 802.1Qci."

::= { ieee802dot1mibs 31 }

-- =====
-- subtrees in the PSFP MIB
-- =====

ieee8021PSFPNotifications
OBJECT IDENTIFIER ::= { ieee8021PSFPMib 0 }

ieee8021PSFPObjects
OBJECT IDENTIFIER ::= { ieee8021PSFPMib 1 }

ieee8021PSFPConformance
OBJECT IDENTIFIER ::= { ieee8021PSFPMib 2 }

ieee8021PSFPStreamFilterParameters
OBJECT IDENTIFIER ::= { ieee8021PSFPObjects 1 }

ieee8021PSFPStreamGateParameters
OBJECT IDENTIFIER ::= { ieee8021PSFPObjects 2 }

ieee8021PSFPFlowMeterParameters
OBJECT IDENTIFIER ::= { ieee8021PSFPObjects 3 }

ieee8021PSFPStreamParameters
OBJECT IDENTIFIER ::= { ieee8021PSFPObjects 4 }

-- =====
-- The ieee8021PSFPStreamFilterParameters subtree
-- This subtree defines the objects necessary for the management
-- of the stream filters for IEEE Std 802.1Q.
-- =====

-- =====
-- the ieee8021PSFPStreamFilterTable
-- =====

ieee8021PSFPStreamFilterTable OBJECT-TYPE
SYNTAX SEQUENCE OF Ieee8021PSFPStreamFilterEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"A table that contains the per-filter instance
manageable parameters for stream filters.

A row in the table exists for each stream filter instance.
associated with a Bridge component.

All writable objects in this table must be
persistent over power up restart/reboot."
REFERENCE "8.6.5.2.1, 8.6.5.3, 12.31.2"
 ::= { ieee8021PSFPStreamFilterParameters 1 }

ieee8021PSFPStreamFilterEntry OBJECT-TYPE
SYNTAX Ieee8021PSFPStreamFilterEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"A list of objects that contains the manageable parameters for

```

    stream filters for a Bridge component."
INDEX { ieee8021BridgeBaseComponentId,
        ieee8021PSFPStreamFilterInstance
      }
::= { ieee8021PSFPStreamFilterTable 1 }

Ieee8021PSFPStreamFilterEntry ::=
SEQUENCE {
    ieee8021PSFPStreamFilterInstance
        Unsigned32,
    ieee8021PSFPStreamHandleSpec
        Integer32,
    ieee8021PSFPPrioritySpec
        Integer32,
    ieee8021PSFPStreamGateInstanceID
        Unsigned32,
    ieee8021PSFPFilterSpecificationList
        OCTET STRING,
    ieee8021PSFPMatchingFramesCount
        Counter64,
    ieee8021PSFPPassingFramesCount
        Counter64,
    ieee8021PSFPNotPassingFramesCount
        Counter64,
    ieee8021PSFPPassingSDUCount
        Counter64,
    ieee8021PSFPNotPassingSDUCount
        Counter64,
    ieee8021PSFPREDFramesCount
        Counter64,
    ieee8021PSFPStreamBlockedDueToOversizeFrameEnable
        TruthValue,
    ieee8021PSFPStreamBlockedDueToOversizeFrame
        TruthValue,
    ieee8021PSFPStreamFilterEntryRowStatus
        RowStatus
    }

ieee8021PSFPStreamFilterInstance OBJECT-TYPE
SYNTAX      Unsigned32
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
    "The StreamFilterInstance parameter is an index into the
    StreamFilterTable.

    The value of this object MUST be retained across
    reinitializations of the management system."
REFERENCE   "8.6.5.2.1, 8.6.5.3, 12.31.2"
::= { ieee8021PSFPStreamFilterEntry 1}

ieee8021PSFPStreamHandleSpec OBJECT-TYPE
SYNTAX      Integer32 (-1..2147483647)
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The StreamHandleSpec parameter contains a stream identifier
    specification value. A value of -1 denotes the wild card value;
    all positive values denote stream identifier values.

    The value of this object MUST be retained across
    reinitializations of the management system."
REFERENCE   "8.6.5.2.1, 8.6.5.3, 12.31.2"
::= { ieee8021PSFPStreamFilterEntry 2}

ieee8021PSFPPrioritySpec OBJECT-TYPE
SYNTAX      Integer32 (-1..2147483647)
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The PrioritySpec parameter contains a priority
    specification value. A value of -1 denotes the wild card value;

```

zero or positive values denote priority values.

The value of this object MUST be retained across reinitializations of the management system."

REFERENCE "8.6.5.2.1, 8.6.5.3, 12.31.2"
::= { ieee8021PSFPStreamFilterEntry 3}

ieee8021PSFPStreamGateInstanceID OBJECT-TYPE

SYNTAX Unsigned32
MAX-ACCESS read-create
STATUS current
DESCRIPTION

"The StreamGateInstance parameter contains the index of an entry in the Stream Gate Table.

The value of this object MUST be retained across reinitializations of the management system."

REFERENCE "8.6.5.2.1, 8.6.5.3, 12.31.2"
::= { ieee8021PSFPStreamFilterEntry 4}

ieee8021PSFPFilterSpecificationList OBJECT-TYPE

SYNTAX OCTET STRING
MAX-ACCESS read-create
STATUS current
DESCRIPTION

"The FilterSpecificationList parameter contains a list of filter specifications associated with this stream filter.

The octet string value represents the contents of the list as an ordered list of entries, each encoded as a TLV, as follows.

The first octet of each TLV is interpreted as an unsigned integer representing a filter specification type:

- 0: Maximum SDU Size.
- 1: Flow meter instance identifier.
- 2-255: Reserved for future filter specification types

The second and third octets of the TLV are the length field, interpreted as an unsigned integer, indicating the number of octets of the value that follows the length. A length of zero indicates that there is no value (i.e., the filter specification has no parameters).

The fourth through (4 + length -1)th octets encode the parameters of the filter specification, as defined for each filter specification type.

- Maximum SDU Size:
A single SDU size parameter is encoded in four octets, and is interpreted as an unsigned integer value.
- Flow meter instance identifier:
A single flow meter instance identifier is encoded in four octets, and is interpreted as an unsigned integer value.

The value of this object MUST be retained across reinitializations of the management system."

REFERENCE "8.6.5.2.1, 8.6.5.3, 12.31.2"
::= { ieee8021PSFPStreamFilterEntry 5}

ieee8021PSFPMatchingFramesCount OBJECT-TYPE

SYNTAX Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION

"The MatchingFramesCount counter counts received frames that match this stream filter.

REFERENCE "8.6.5.2.1, 8.6.5.3, 12.31.2"
::= { ieee8021PSFPStreamFilterEntry 6}

ieee8021PSFPPassingFramesCount OBJECT-TYPE

```

SYNTAX      Counter64
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The PassingFramesCount counter counts received frames that
    pass the gate associated with this stream filter.
    "
REFERENCE   "8.6.5.2.1, 8.6.5.3, 12.31.2"
::= { ieee8021PSFPStreamFilterEntry 7}

ieee8021PSFPNotPassingFramesCount OBJECT-TYPE
SYNTAX      Counter64
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The NotPassingFramesCount counter counts received frames that
    do not pass the gate associated
    with this stream filter.
    "
REFERENCE   "8.6.5.2.1, 8.6.5.3, 12.31.2"
::= { ieee8021PSFPStreamFilterEntry 8}

ieee8021PSFPPassingSDUCount OBJECT-TYPE
SYNTAX      Counter64
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The PassingSDUCount counter counts received frames that
    pass the maximum SDU size filter specification associated
    with this stream filter.
    "
REFERENCE   "8.6.5.2.1, 8.6.5.3, 12.31.2"
::= { ieee8021PSFPStreamFilterEntry 9}

ieee8021PSFPNotPassingSDUCount OBJECT-TYPE
SYNTAX      Counter64
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The NotPassingSDUCount counter counts received frames that
    do not pass the maximum SDU size filter specification associated
    with this stream filter.
    "
REFERENCE   "8.6.5.2.1, 8.6.5.3, 12.31.2"
::= { ieee8021PSFPStreamFilterEntry 10}

ieee8021PSFPPREDFramesCount OBJECT-TYPE
SYNTAX      Counter64
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The REDFramesCount counter counts received
    frames that were discarded as a result of the
    operation of the flow meter.
    "
REFERENCE   "8.6.5.2.1, 8.6.5.3, 12.31.2"
::= { ieee8021PSFPStreamFilterEntry 11}

ieee8021PSFPStreamBlockedDueToOversizeFrameEnable OBJECT-TYPE
SYNTAX      TruthValue
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The ieee8021PSFPStreamBlockedDueToOversizeFrameEnable object
    contains a Boolean value that indicates whether the
    StreamBlockedDueToOversizeFrame function is
    enabled (TRUE) or disabled (FALSE).

    The value of this object MUST be retained across
    reinitializations of the management system."
REFERENCE   "8.6.5.2.1, 8.6.5.3, 12.31.2"
DEFVAL { false }

```

```

::= { ieee8021PSFPStreamFilterEntry 12 }

ieee8021PSFPStreamBlockedDueToOversizeFrame OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "The ieee8021PSFPStreamBlockedDueToOversizeFrame object
        contains a Boolean value that indicates whether, if the
        StreamBlockedDueToOversizeFrame function is
        enabled, all frames are to be discarded (TRUE)
        or not (FALSE).

        The value of this object MUST be retained across
        reinitializations of the management system."
    REFERENCE    "8.6.5.2.1, 8.6.5.3, 12.31.2"
    DEFVAL { false }
    ::= { ieee8021PSFPStreamFilterEntry 13 }

ieee8021PSFPStreamFilterEntryRowStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "The status of the row.

        The writable columns in a row cannot be changed if the row
        is active. All columns MUST have a valid value before a row
        can be activated.
        "
    ::= { ieee8021PSFPStreamFilterEntry 14 }

-- =====
-- The ieee8021PSFPStreamGateParameters subtree
-- This subtree defines the objects necessary for the management
-- of the stream gate scheduling mechanism for IEEE Std 802.1Q.
-- =====

-- =====
-- the ieee8021PSFPStreamGateTable
-- =====

ieee8021PSFPStreamGateTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF Ieee8021PSFPStreamGateEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "A table that contains the per-gate instance
        manageable parameters for stream gate scheduling.

        For a given Bridge component, a row in the table exists for
        each stream gate instance.

        All writable objects in this table must be
        persistent over power up restart/reboot."
    REFERENCE    "8.6.8.4, 8.6.9.4, 12.31.3"
    ::= { ieee8021PSFPStreamGateParameters 1 }

ieee8021PSFPStreamGateEntry OBJECT-TYPE
    SYNTAX      Ieee8021PSFPStreamGateEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "A list of objects that contains the manageable parameters for
        stream gate scheduling for a Bridge component."
    INDEX { ieee8021BridgeBaseComponentId,
            ieee8021PSFPStreamGateInstance
          }
    ::= { ieee8021PSFPStreamGateTable 1 }

Ieee8021PSFPStreamGateEntry ::=

```

```

SEQUENCE {
    ieee8021PSFPStreamGateInstance
        Unsigned32,
    ieee8021PSFPGateEnabled
        TruthValue,
    ieee8021PSFPAdminGateStates
        INTEGER,
    ieee8021PSFPOperGateStates
        INTEGER,
    ieee8021PSFPAdminControlListLength
        Unsigned32,
    ieee8021PSFPOperControlListLength
        Unsigned32,
    ieee8021PSFPAdminControlList
        OCTET STRING,
    ieee8021PSFPOperControlList
        OCTET STRING,
    ieee8021PSFPAdminCycleTimeNumerator
        Unsigned32,
    ieee8021PSFPAdminCycleTimeDenominator
        Unsigned32,
    ieee8021PSFPOperCycleTimeNumerator
        Unsigned32,
    ieee8021PSFPOperCycleTimeDenominator
        Unsigned32,
    ieee8021PSFPAdminCycleTimeExtension
        Unsigned32,
    ieee8021PSFPOperCycleTimeExtension
        Unsigned32,
    ieee8021PSFPAdminBaseTime
        IEEE8021STPTPtimeValue,
    ieee8021PSFPOperBaseTime
        IEEE8021STPTPtimeValue,
    ieee8021PSFPConfigChange
        TruthValue,
    ieee8021PSFPConfigChangeTime
        IEEE8021STPTPtimeValue,
    ieee8021PSFPTickGranularity
        Unsigned32,
    ieee8021PSFPCurrentTime
        IEEE8021STPTPtimeValue,
    ieee8021PSFPConfigPending
        TruthValue,
    ieee8021PSFPConfigChangeError
        Counter64,
    ieee8021PSFPAdminIPV
        Integer32,
    ieee8021PSFPOperIPV
        Integer32,
    ieee8021PSFPGateClosedDueToInvalidRxEnable
        TruthValue,
    ieee8021PSFPGateClosedDueToInvalidRx
        TruthValue,
    ieee8021PSFPGateClosedDueToOctetsExceededEnable
        TruthValue,
    ieee8021PSFPGateClosedDueToOctetsExceeded
        TruthValue,
    ieee8021PSFPStreamGateEntryRowStatus
        RowStatus
}

ieee8021PSFPStreamGateInstance OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The StreamGateInstance parameter is an index into the
        StreamGateTable.

        The value of this object MUST be retained across
        reinitializations of the management system."
    REFERENCE   "8.6.5.2.1, 8.6.5.4, 12.31.3"

```

IEEE Std 802.1Qcw™-2023
IEEE Standard for Local and Metropolitan Area Networks—Bridges and Bridged Networks
Amendment 36: YANG Data Models for Scheduled Traffic, Frame Preemption, and Per-Stream Filtering and Policing

```

 ::= { ieee8021PSFPStreamGateEntry 1}

ieee8021PSFPGateEnabled OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The GateEnabled parameter determines whether the stream gate
        is active (true) or inactive (false).

        The value of this object MUST be retained across
        reinitializations of the management system."
    REFERENCE   "8.6.8.4, 8.6.9.4, 12.31.3"
    DEFVAL { false }
    ::= { ieee8021PSFPStreamGateEntry 2}

ieee8021PSFPAdminGateStates OBJECT-TYPE
    SYNTAX      INTEGER { open(1), closed(2) }
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The administrative value of the GateStates parameter for the
        stream gate.
        The open value indicates that the gate is open,
        the closed value indicates that the gate is closed.

        The value of this object MUST be retained across
        reinitializations of the management system."
    REFERENCE   "8.6.8.4, 8.6.9.4, 12.31.3"
    ::= { ieee8021PSFPStreamGateEntry 3 }

ieee8021PSFPOperGateStates OBJECT-TYPE
    SYNTAX      INTEGER { open(1), closed(2) }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The operational value of the GateStates parameter for the
        stream gate.
        The open value indicates that the gate is open,
        the closed value indicates that the gate is closed.
"
    REFERENCE   "8.6.8.4, 8.6.9.4, 12.31.3"
    ::= { ieee8021PSFPStreamGateEntry 4 }

ieee8021PSFPAdminControlListLength OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The administrative value of the ListMax parameter for the gate.
        The integer value indicates the number of entries (TLVs) in the
        AdminControlList.

        The value of this object MUST be retained across
        reinitializations of the management system."
    REFERENCE   "8.6.8.4, 8.6.9.4, 12.31.3"
    ::= { ieee8021PSFPStreamGateEntry 5 }

ieee8021PSFPOperControlListLength OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The operational value of the ListMax parameter for the gate.
        The integer value indicates the number of entries (TLVs) in the
        OperControlList."
    REFERENCE   "8.6.8.4, 8.6.9.4, 12.31.3"
    ::= { ieee8021PSFPStreamGateEntry 6 }

ieee8021PSFPAdminControlList OBJECT-TYPE
    SYNTAX      OCTET STRING
    MAX-ACCESS  read-create

```