
**Telecommunications and exchange
between information technology
systems — Requirements for local and
metropolitan area networks —**

**Part 3:
Standard for Ethernet**

**AMENDMENT 11: Physical layers and
management parameters for 100 Gb/s
and 400 Gb/s operation over single-
mode fiber at 100 Gb/s per wavelength**

*Télécommunications et échange entre systèmes informatiques —
Exigences pour les réseaux locaux et métropolitains —*

Partie 3: Norme pour Ethernet

*AMENDEMENT 11: Couches physiques et paramètres de gestion pour
le fonctionnement à 100 Gb/s et 400 Gb/s sur fibre unimodale à 100
Gb/s par longueur d'onde*



Reference number
ISO/IEC/IEEE 8802-3:2021/Amd.11:2022(E)



Documents

Document Sharing Hub
© IEEE 2021



COPYRIGHT PROTECTED DOCUMENT

© IEEE 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from IEEE at the address below.

Institute of Electrical and Electronics Engineers, Inc
3 Park Avenue, New York
NY 10016-5997, USA

Email: stds.ipr@ieee.org
Website: www.ieee.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO/IEC documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see <https://patents.iec.ch>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

ISO/IEC/IEEE 8802-3:2021/Amd 11 was prepared by the LAN/MAN of the IEEE Computer Society (as IEEE 802.3cu™-2021) and drafted in accordance with its editorial rules. It was adopted, under the “fast-track procedure” defined in the Partner Standards Development Organization cooperation agreement between ISO and IEEE, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*.

A list of all parts in the ISO/IEC/IEEE 8802 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

IEEE Std 802.3cu™-2021

(Amendment to IEEE Std 802.3™-2018
as amended by IEEE Std 802.3cb™-2018,
IEEE Std 802.3bt™-2018,
IEEE Std 802.3cd™-2018,
IEEE Std 802.3cn™-2019,
IEEE Std 802.3cg™-2019,
IEEE Std 802.3cq™-2020,
IEEE Std 802.3cm™-2020,
IEEE Std 802.3ch™-2020,
IEEE Std 802.3ca™-2020,
and IEEE Std 802.3cr™-2020)

IEEE Standard for Ethernet

Amendment 11: Physical Layers and Management Parameters for 100 Gb/s and 400 Gb/s Operation over Single-Mode Fiber at 100 Gb/s per Wavelength

Developed by the

LAN/MAN Standards Committee
of the
IEEE Computer Society

Approved 9 February 2021

IEEE SA Standards Board

Abstract: This amendment to IEEE Std 802.3-2018 adds Physical Layer specifications and management parameters for 100 Gb/s and 400 Gb/s Ethernet optical interfaces for reaches up to 10 km based on 100 Gb/s per wavelength optical signaling.

Keywords: 100 Gb/s Ethernet, 100GBASE-FR1, 100GBASE-LR1, 400 Gb/s Ethernet, 400GBASE-FR4, 400GBASE-LR4-6, Energy-Efficient Ethernet (EEE), Ethernet, forward error correction (FEC), IEEE 802.3™, IEEE 802.3cu™, PAM4, Physical Medium Dependent (PMD) sublayer, single-mode fiber (SMF)

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2021 by The Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 26 February 2021. Printed in the United States of America.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-1-5044-7383-5 STD24602
Print: ISBN 978-1-5044-7384-2 STDPD24602

IEEE prohibits discrimination, harassment and bullying.

For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE Standards documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page (<https://standards.ieee.org/ipr/disclaimers.html>), appear in all standards and may be found under the heading “Important Notices and Disclaimers Concerning IEEE Standards Documents.”

Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE SA) Standards Board. IEEE develops its standards through an accredited consensus development process, which brings together volunteers representing varied viewpoints and interests to achieve the final product. IEEE Standards are documents developed by volunteers with scientific, academic, and industry-based expertise in technical working groups. Volunteers are not necessarily members of IEEE or IEEE SA, and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE makes no warranties or representations concerning its standards, and expressly disclaims all warranties, express or implied, concerning this standard, including but not limited to the warranties of merchantability, fitness for a particular purpose and non-infringement. In addition, IEEE does not warrant or represent that the use of the material contained in its standards is free from patent infringement. IEEE Standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity, nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: THE NEED TO PROCURE SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE is the approved IEEE standard.

Official statements

A statement, written or oral, that is not processed in accordance with the IEEE SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, nor be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that the presenter's views should be considered the personal views of that individual rather than the formal position of IEEE, IEEE SA, the Standards Committee, or the Working Group.

Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE or IEEE SA. However, **IEEE does not provide interpretations, consulting information, or advice pertaining to IEEE Standards documents.**

Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its Societies and Standards Coordinating Committees are not able to provide an instant response to comments, or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in evaluating comments or in revisions to an IEEE standard is welcome to join the relevant IEEE working group. You can indicate interest in a working group using the Interests tab in the Manage Profile & Interests area of the [IEEE SA myProject system](#). An IEEE Account is needed to access the application.

Comments on standards should be submitted using the [Contact Us](#) form.

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not constitute compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Data privacy

Users of IEEE Standards documents should evaluate the standards for considerations of data privacy and data ownership in the context of assessing and using the standards in compliance with applicable laws and regulations.

Copyrights

IEEE draft and approved standards are copyrighted by IEEE under US and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

Photocopies

Subject to payment of the appropriate licensing fees, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400; <https://www.copyright.com/>. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every 10 years. When a document is more than 10 years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit [IEEE Xplore](#) or [contact IEEE](#). For more information about the IEEE SA or IEEE's standards development process, visit the IEEE SA Website.

Errata

Errata, if any, for all IEEE standards can be accessed on the [IEEE SA Website](#). Search for standard number and year of approval to access the web page of the published standard. Errata links are located under the Additional Resources Details section. Errata are also available in [IEEE Xplore](#). Users are encouraged to periodically check for errata.

Patents

IEEE Standards are developed in compliance with the [IEEE SA Patent Policy](#).

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE SA Website at <https://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

IMPORTANT NOTICE

IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. IEEE Standards development activities consider research and information presented to the standards development group in developing any safety recommendations. Other information about safety practices, changes in technology or technology implementation, or impact by peripheral systems also may be pertinent to safety considerations during implementation of the standard. Implementers and users of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

Participants

The following individuals were officers and members of the IEEE 802.3 Working Group at the beginning of the IEEE P802.3cu Working Group ballot.

David J. Law, *IEEE 802.3 Working Group Chair*
Adam Healey, *IEEE 802.3 Working Group Vice-Chair*
Jon Lewis, *IEEE 802.3 Working Group Secretary*
Steven B. Carlson, *IEEE 802.3 Working Group Executive Secretary*
Valerie Maguire, *IEEE 802.3 Working Group Treasurer*

Mark Nowell, *IEEE P802.3cu 100 Gb/s and 400 Gb/s over SMF at 100 Gb/s per Wavelength Task Force Chair*

Gary Nicholl, *IEEE P802.3cu 100 Gb/s and 400 Gb/s over SMF at 100 Gb/s per Wavelength Task Force Editor-in-Chief*

David Lewis, *IEEE P802.3cu 100 Gb/s and 400 Gb/s over SMF at 100 Gb/s per Wavelength Task Force Editor*

David Abramson
Pete Anslow
Michikazu Aono
Nobuyasu Araki
Tim Baggett
Thananya Baldwin
Steven Baumgartner
Denis Beaudoin
Gitesh Bhagwat
Rich Boyer
David Brandt
Ralf-Peter Braun
Theodore Brillhart
Paul Brooks
Matthew Brown
Jairo Bustos Heredia
Adrian Butter
Clark Carty
David Chalupsky
Jacky Chang
Xin Chang
Chan Chen
Golam Choudhury
Keng Hua Chuang
John D'Ambrosia
Piers Dawe
Fred Dawson
Gerrit den Besten
Claudio DeSanti
Curtis Donahue
Liang Du
Kathryn Dube
Frank Effenberger
David Estes
John Ewen
Vincent Ferretti
Brian Franchuk
Matthias Fritsche
Takashi Fukuoka
Ali Ghiasi
Joel Goergen
Steven Gorshe

Hideki Goto
Steffen Graber
Olaf Grau
Robert Grow
Martin Gubow
Mark Gustlin
Marek Hajduczenia
Howard Heck
Brian Holden
Bernd Horrmeyer
Yasuhiro Hyakutake
Jonathan Ingham
Kazuhiko Ishibe
Hideki Isono
Tom Issenhuth
Hiroaki Ito
Kenneth Jackson
Andrew Jimenez
John Johnson
Chad Jones
Peter Jones
Lokesh Kabra
Haysam Kadry
Manabu Kagami
Upen Kareti
Athanasios Kasapi
Yong Kim
Mark Kimber
Michael Klempa
Curtis Knittle
Elizabeth Kochuparambil
Sam Kocsis
Wojciech Koczwara
Paul Kolesar
Taiji Kondo
Daniel Koppermueller
Glen Kramer
Taketo Kumada
Hans Lackner
Frank Lambrecht
Mark Laubach
Greg Le Cheminant

Mike-Peng Li
Alex Lin
Hai-Feng Liu
William Lo
Kent Lusted
Jeffery Maki
David Malicoat
Eric Maniloff
Flavio Marques
Arthur Marris
Takeo Masuda
Mick McCarthy
Brett McClellan
Larry McMillan
Richard Mellitz
Shimon Muller
James Nadolny
Edward Nakamoto
Paul Neveux
Gary Nicholl
Shawn Nicholl
Kevin Noll
David Ofelt
Ryo Okabe
Tom Palkert
Carlos Pardo
Earl Parsons
Gerald Pepper
David Piehler
Fabio Pittala
Christopher Pohl
William Powell
Rick Rabinovich
Parthasarathy Raju
Adee Ran
Alon Regev
Duane Remein
Victor Renteria
Thomas Rettig
Hamid Salehi
Sam Sambasivan
Edward Sayre
Matthew Schmitt

Hossein Sedarat	Tadashi Takahashi	Xuehuan Wang
Masood Shariff	Kazuya Takayama	Dong Wei
Masato Shiino	Michael Takefman	Matthias Wendt
Ramin Shirani	Masaru Terada	Natalie Wienckowski
Kapil Shrikhande	Geoffrey Thompson	Dance Wu
Jeff Slavick	Piroom Tooyserkani	Peter Wu
Scott Sommers	Nathan Tracy	Dayin Xu
Edward Sprague	David Tremblay	Yu Xu
Peter Stassar	Stephen Trowbridge	Lennart Yseboodt
Heath Stewart	Mike Tu	Conrad Zerna
Junqing Sun	Ed Ulrichs	Xingxin Zhang
Steve Swanson	Alexander Umnov	Chunhui Zhu
Tomoo Takahara	Edward Walter	Yan Zhuang
Satoshi Takahashi	Roy Wang	Martin Zielinski
		George Zimmerman

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Robert Aiello	Peter Jones	David Piehler
Thomas Alexander	Lokesh Kabra	Rick Pimpinella
Ralf-Peter Braun	Piotr Karocki	R. K. Rannow
Theodore Brillhart	Stuart Kerry	Alon Regev
Matthew Brown	Yong Kim	Maximilian Riegel
Jairo Bustos Heredia	Mark Laubach	Robert Robinson
William Byrd	David J. Law	Roberto Rodes
Steven B. Carlson	Pi-Cheng Law	Toshiaki Sakai
Clark Carty	Hyeong Ho Lee	Olindo Savi
Pin Chang	David Lewis	Jason Shriver
Chan Chen	Jon Lewis	Scott Sommers
Charles Cook	Karen Liu	Peter Stassar
Piers Dawe	Kent Lusted	Walter Struppler
John Deandrea	Valerie Maguire	Mitsutoshi Sugawara
Michael Dudek	Jeffery Maki	Kohichi Tamura
Avraham Freedman	Michael Maytum	James Theodoras
Matthias Fritsche	Brett McClellan	Nathan Tracy
Robert Grow	Jonathon McLendon	David Tremblay
Joseph Gwinn	Richard Mellitz	Stephen Trowbridge
Xiang He	Guangcan Mi	Mark-Rene Uchida
Adam Healey	Tremont Miao	John Vergis
Marco Hernandez	Raymond Nering	Ruoxu Wang
David Hess	Gary Nicholl	Brian Welch
Werner Hoelzl	Nick S. A. Nikjoo	Andreas Wolf
Thomas Huber	Mark Nowell	Peter Wu
Yasuhiro Hyakutake	Satoshi Obara	James Young
Jonathan Ingham	Tom Palkert	Yu Yuan
Osamu Ishida	Carlos Pardo	Oren Yuen
Hideki Isono	Earl Parsons	Bo Zhang
Chad Jones	Bansi Patel	Pavel Zivny

When the IEEE SA Standards Board approved this standard on 9 February 2021, it had the following membership:

Gary Hoffman, *Chair*
Vacant Position, *Vice Chair*
John D. Kulick, *Past Chair*
Konstantinos Karachalios, *Secretary*

Edward A. Addy
Doug Edwards
Ramy Ahmed Fathy
J. Travis Griffith
Joseph L. Koepfinger*
Thomas Koshy
David J. Law
Howard Li

Daozhuang Lin
Kevin Lu
Daleep C. Mohla
Chenhui Niu
Damir Novosel
Annette Reilly
Jon Walter Rosdahl

Dorothy Stanley
Mehmet Ulema
Lei Wang
F. Keith Waters
Karl Weber
Sha Wei
Howard Wolfman
Daidi Zhong

*Member Emeritus

Introduction

This introduction is not part of IEEE Std 802.3cu-2021, IEEE Standard for Ethernet—Amendment 11: Physical Layers and Management Parameters for 100 Gb/s and 400 Gb/s Operation over Single-Mode Fiber at 100 Gb/s per Wavelength.

IEEE Std 802.3™ was first published in 1985. Since the initial publication, many projects have added functionality or provided maintenance updates to the specifications and text included in the standard. Each IEEE 802.3 project/amendment is identified with a suffix (e.g., IEEE Std 802.3ba™-2010).

The half duplex Media Access Control (MAC) protocol specified in IEEE Std 802.3-1985 is Carrier Sense Multiple Access with Collision Detection (CSMA/CD). This MAC protocol was key to the experimental Ethernet developed at Xerox Palo Alto Research Center, which had a 2.94 Mb/s data rate. Ethernet at 10 Mb/s was jointly released as a public specification by Digital Equipment Corporation (DEC), Intel and Xerox in 1980. Ethernet at 10 Mb/s was approved as an IEEE standard by the IEEE Standards Board in 1983 and subsequently published in 1985 as IEEE Std 802.3-1985. Since 1985, new media options, new speeds of operation, and new capabilities have been added to IEEE Std 802.3. A full duplex MAC protocol was added in 1997.

Some of the major additions to IEEE Std 802.3 are identified in the marketplace with their project number. This is most common for projects adding higher speeds of operation or new protocols. For example, IEEE Std 802.3u™ added 100 Mb/s operation (also called Fast Ethernet), IEEE Std 802.3z added 1000 Mb/s operation (also called Gigabit Ethernet), IEEE Std 802.3ae added 10 Gb/s operation (also called 10 Gigabit Ethernet), IEEE Std 802.3ah™ specified access network Ethernet (also called Ethernet in the First Mile) and IEEE Std 802.3ba added 40 Gb/s operation (also called 40 Gigabit Ethernet) and 100 Gb/s operation (also called 100 Gigabit Ethernet). These major additions are all now included in and are superseded by IEEE Std 802.3-2018 and are not maintained as separate documents.

At the date of IEEE Std 802.3cu-2021 publication, IEEE Std 802.3 was composed of the following documents:

IEEE Std 802.3-2018

Section One—Includes Clause 1 through Clause 20 and Annex A through Annex H and Annex 4A. Section One includes the specifications for 10 Mb/s operation and the MAC, frame formats and service interfaces used for all speeds of operation.

Section Two—Includes Clause 21 through Clause 33 and Annex 22A through Annex 33E. Section Two includes management attributes for multiple protocols and speed of operation as well as specifications for providing power over twisted pair cabling for multiple operational speeds. It also includes general information on 100 Mb/s operation as well as most of the 100 Mb/s Physical Layer specifications.

Section Three—Includes Clause 34 through Clause 43 and Annex 36A through Annex 43C. Section Three includes general information on 1000 Mb/s operation as well as most of the 1000 Mb/s Physical Layer specifications.

Section Four—Includes Clause 44 through Clause 55 and Annex 44A through Annex 55B. Section Four includes general information on 10 Gb/s operation as well as most of the 10 Gb/s Physical Layer specifications.

Section Five—Includes Clause 56 through Clause 77 and Annex 57A through Annex 76A. Clause 56 through Clause 67 and Clause 75 through Clause 77, as well as associated annexes, specify subscriber

access and other Physical Layers and sublayers for operation from 512 kb/s to 10 Gb/s, and defines services and protocol elements that enable the exchange of IEEE Std 802.3 format frames between stations in a subscriber access network. Clause 68 specifies a 10 Gb/s Physical Layer specification. Clause 69 through Clause 74 and associated annexes specify Ethernet operation over electrical backplanes at speeds of 1000 Mb/s and 10 Gb/s.

Section Six—Includes Clause 78 through Clause 95 and Annex 83A through Annex 93C. Clause 78 specifies Energy-Efficient Ethernet. Clause 79 specifies IEEE 802.3 Organizationally Specific Link Layer Discovery Protocol (LLDP) type, length, and value (TLV) information elements. Clause 80 through Clause 95 and associated annexes include general information on 40 Gb/s and 100 Gb/s operation as well the 40 Gb/s and 100 Gb/s Physical Layer specifications. Clause 90 specifies Ethernet support for time synchronization protocols.

Section Seven—Includes Clause 96 through Clause 115 and Annex 97A through Annex 115A. Clause 96 through Clause 98, Clause 104, and associated annexes, specify Physical Layers and optional features for 100 Mb/s and 1000 Mb/s operation over a single twisted pair. Clause 100 through Clause 103, as well as associated annexes, specify Physical Layers for the operation of the EPON protocol over coaxial distribution networks. Clause 105 through Clause 114 and associated annexes include general information on 25 Gb/s operation as well as 25 Gb/s Physical Layer specifications. Clause 99 specifies a MAC merge sublayer for the interspersing of express traffic. Clause 115 and its associated annex specify a Physical Layer for 1000 Mb/s operation over plastic optical fiber.

Section Eight—Includes Clause 116 through Clause 126 and Annex 119A through Annex 120E. Clause 116 through Clause 124 and associated annexes include general information on 200 Gb/s and 400 Gb/s operation as well the 200 Gb/s and 400 Gb/s Physical Layer specifications. Clause 125 and Clause 126 include general information on 2.5 Gb/s and 5 Gb/s operation as well as 2.5 Gb/s and 5 Gb/s Physical Layer specifications.

IEEE Std 802.3cb™-2018

Amendment 1—This amendment includes changes to IEEE Std 802.3-2018 and its amendments, and adds Clause 127 through Clause 130, Annex 127A, Annex 128A, Annex 128B, and Annex 130A. This amendment adds new Physical Layers for operation at 2.5 Gb/s and 5 Gb/s over electrical backplanes.

IEEE Std 802.3bt™-2018

Amendment 2—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 145, Annex 145A, Annex 145B, and Annex 145C. This amendment adds power delivery using all four pairs in the structured wiring plant, resulting in greater power being available to end devices. This amendment also allows for lower standby power consumption in end devices and adds a mechanism to better manage the available power budget.

IEEE Std 802.3cd™-2018

Amendment 3—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 131 through Clause 140 and Annex 135A through Annex 136D. This amendment adds MAC parameters, Physical Layers, and management parameters for the transfer of IEEE 802.3 format frames at 50 Gb/s, 100 Gb/s, and 200 Gb/s.

IEEE Std 802.3cn™-2019

Amendment 4—This amendment includes changes to IEEE Std 802.3-2018 and adds 50 Gb/s, 200 Gb/s, and 400 Gb/s Physical Layer specifications and management parameters for operation over single-mode fiber with reaches of at least 40 km.

IEEE Std 802.3cg™-2019

Amendment 5—This amendment includes changes to IEEE Std 802.3-2018 and its amendments and adds Clause 146 through Clause 148 and Annex 146A and Annex 146B. This amendment adds 10 Mb/s Physical Layer specifications and management parameters for operation on a single balanced pair of conductors.

IEEE Std 802.3cq™-2020

Amendment 6—This amendment includes editorial and technical corrections, refinements, and clarifications to Clause 33 and related portions of the standard.

IEEE Std 802.3cm™-2020

Amendment 7—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 150. This amendment adds Physical Layer (PHY) specifications and management parameters for 400 Gb/s operation on four pairs (400GBASE-SR4.2) and eight pairs (400GBASE-SR8) of multimode fiber, over reaches of at least 100 m.

IEEE Std 802.3ch™-2020

Amendment 8—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 149, Annex 149A, Annex 149B, and Annex 149C. This amendment adds physical layer specifications and management parameters for operation at 2.5 Gb/s, 5 Gb/s, and 10 Gb/s over a single balanced pair of conductors.

IEEE Std 802.3ca™-2020

Amendment 9—This amendment to IEEE Std 802.3-2018 extends the operation of Ethernet passive optical networks (EPONs) to multiple channels of 25 Gb/s providing both symmetric and asymmetric operation for the following data rates (downstream/upstream): 25/10 Gb/s, 25/25 Gb/s, 50/10 Gb/s, 50/25 Gb/s, and 50/50 Gb/s. This amendment specifies the 25 Gb/s EPON Multi-Channel Reconciliation Sublayer (MCRS), Nx25G-EPON Physical Coding Sublayers (PCSs), Physical Media Attachment (PMA) sublayers, and Physical Medium Dependent (PMD) sublayers that support both symmetric and asymmetric data rates while maintaining backward compatibility with already deployed 10 Gb/s EPON equipment. The EPON operation is defined for distances of at least 20 km, and for a split ratio of at least 1:32.

IEEE Std 802.3cr™-2021

Amendment 10—This amendment includes changes to IEEE Std 802.3-2018 and adds Annex J. This amendment replaces references to the IEC 60950 series of standards (including IEC 60950-1 “Information technology equipment—Safety—Part 1: General requirements”) with appropriate references to the IEC 62368 “Audio/video, information and communication technology equipment” series and makes appropriate changes to the standard corresponding to the new references.

IEEE Std 802.3cu™-2021

Amendment 11—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 151. This amendment adds Physical Layer (PHY) specifications and management parameters for 100 Gb/s and 400 Gb/s operation over single-mode fiber, based on 100 Gb/s per wavelength optical signaling.

Two companion documents exist, IEEE Std 802.3.1 and IEEE Std 802.3.2. IEEE Std 802.3.1 describes Ethernet management information base (MIB) modules for use with the Simple Network Management

Protocol (SNMP). IEEE Std 802.3.2 describes YANG data models for Ethernet. IEEE Std 802.3.1 and IEEE Std 802.3.2 are updated to add management capability for enhancements to IEEE Std 802.3 after approval of those enhancements.

IEEE Std 802.3 will continue to evolve. New Ethernet capabilities are anticipated to be added within the next few years as amendments to this standard.

Contents

1. Introduction.....	18
1.4 Definitions	18
30. Management.....	19
30.5 Layer management for medium attachment units (MAUs)	19
30.5.1 MAU managed object class.....	19
30.5.1.1 MAU attributes	19
30.5.1.1.2 aMAUType	19
45. Management Data Input/Output (MDIO) Interface.....	20
45.2 MDIO Interface Registers.....	20
45.2.1 PMA/PMD registers.....	20
45.2.1.6 PMA/PMD control 2 register (Register 1.7)	20
45.2.1.7 PMA/PMD status 2 register (Register 1.8).....	20
45.2.1.7.4 Transmit fault (1.8.11)	20
45.2.1.7.5 Receive fault (1.8.10).....	21
45.2.1.8 PMD transmit disable register (Register 1.9)	21
45.2.1.21 400G PMA/PMD extended ability register (Register 1.24)	22
45.2.1.21.1a1 400GBASE-LR4-6 ability (1.24.9).....	22
45.2.1.21.1a2 400GBASE-FR4 ability (1.24.8)	22
45.2.1.21b 40G/100G PMA/PMD extended ability 2 (Register 1.26)	23
45.2.1.21b.3a 100GBASE-LR1 ability (1.26.5)	23
45.2.1.21b.3b 100GBASE-FR1 ability (1.26.4)	23
78. Energy-Efficient Ethernet (EEE).....	24
78.1 Overview.....	24
78.1.4 PHY types optionally supporting EEE.....	24
80. Introduction to 40 Gb/s and 100 Gb/s networks	25
80.1 Overview.....	25
80.1.3 Relationship of 40 Gigabit and 100 Gigabit Ethernet to the ISO OSI reference model.....	25
80.1.4 Nomenclature	25
80.1.5 Physical Layer signaling systems.....	26
80.2 Summary of 40 Gigabit and 100 Gigabit Ethernet sublayers	26
80.2.3 Forward Error Correction (FEC) sublayers.....	26
80.4 Delay constraints.....	27
91. Reed-Solomon Forward Error Correction (RS-FEC) sublayer for 100GBASE-R PHYs	28
91.5 Functions within the RS-FEC sublayer	28
91.5.2.7 Reed-Solomon encoder.....	28
91.5.3 Receive function.....	28
91.5.3.3 Reed-Solomon decoder.....	28
91.5.3.3.1 FEC Degraded SER (optional).....	28
91.6 RS-FEC MDIO function mapping.....	29

91.6.2a	four_lane_pmd	29
91.7	Protocol implementation conformance statement (PICS) proforma for Clause 91, Reed-Solomon Forward Error Correction (RS-FEC) sublayer for 100GBASE-R PHYs.....	30
91.7.3	Major capabilities/options	30
91.7.4	PICS proforma tables for Reed-Solomon Forward Error Correction (RS-FEC) sublayer for 100GBASE-R PHYs	30
91.7.4.1	Transmit function	30
91.7.4.2	Receive function	31
116.	Introduction to 200 Gb/s and 400 Gb/s networks	32
116.1	Overview	32
116.1.2	Relationship of 200 Gigabit and 400 Gigabit Ethernet to the ISO OSI reference model	32
116.1.3	Nomenclature	32
116.1.4	Physical Layer signaling systems	33
116.4	Delay constraints	33
116.5	Skew constraints	34
140.	Physical Medium Dependent (PMD) sublayer and medium, type 100GBASE-DR, 100GBASE-FR1, and 100GBASE-LR1	36
140.1	Overview	36
140.2	Physical Medium Dependent (PMD) service interface	37
140.3	Delay and Skew	38
140.3.1	Delay constraints	38
140.5	PMD functional specifications	38
140.5.1	PMD block diagram	38
140.6	PMD to MDI optical specifications for 100GBASE-DR, 100GBASE-FR1, and 100GBASE-LR1	38
140.6.1	100GBASE-DR, 100GBASE-FR1, and 100GBASE-LR1 transmitter optical specifications	39
140.6.2	100GBASE-DR, 100GBASE-FR1, and 100GBASE-LR1 receive optical specifications	41
140.6.3	100GBASE-DR, 100GBASE-FR1, and 100GBASE-LR1 illustrative link power budgets	43
140.7	Definition of optical parameters and measurement methods	46
140.7.1	Test patterns for optical parameters	46
140.7.5	Transmitter and dispersion eye closure for PAM4 (TDECQ)	46
140.7.5.1	TDECQ reference equalizer	47
140.7.5.2	Channel requirements	47
140.7.5a	Transmitter eye closure for PAM4 (TECQ)	47
140.7.5b	Over/under-shoot	48
140.7.5c	Transmitter power excursion	48
140.7.8	Relative intensity noise (RIN _{15.5xOMA})	49
140.7.9	Receiver sensitivity	49
140.7.9.1	Receiver sensitivity for 100GBASE-DR	49
140.7.9.2	Receiver sensitivity for 100GBASE-FR1 and 100GBASE-LR1	49
140.7.10	Stressed receiver sensitivity	50
140.8	Safety, installation, environment, and labeling	50
140.8.2	Laser safety	50
140.8.4	Environment	50
140.8.5	Electromagnetic emission	50
140.9	Fiber optic cabling model	51

140.10	Characteristics of the fiber optic cabling (channel)	51
140.10.1	Optical fiber cable	52
140.10.2	Optical fiber connection	52
140.10.2.1	Connection insertion loss	52
140.10.2.2	Maximum discrete reflectance	52
140.10.3	Medium Dependent Interface (MDI)	53
140.10a	Interoperation between 100GBASE-DR, 100GBASE-FR1, and 100GBASE-LR1	53
140.10a.1	Interoperation between 100GBASE-FR1 and 100GBASE-DR	53
140.10a.2	Interoperation between 100GBASE-LR1 and 100GBASE-DR	54
140.10a.3	Interoperation between 100GBASE-LR1 and 100GBASE-FR1	54
140.11	Protocol implementation conformance statement (PICS) proforma for Clause 140, Physical Medium Dependent (PMD) sublayer and medium, types 100GBASE-DR, 100GBASE-FR1, and 100GBASE-LR1	55
140.11.1	Introduction	55
140.11.2	Identification	55
140.11.2.2	Protocol summary	55
140.11.3	Major capabilities/options	56
140.11.4	PICS proforma tables for Physical Medium Dependent (PMD) sublayer and medium, type 100GBASE-DR, 100GBASE-FR1, and 100GBASE-LR1	56
140.11.4.3	PMD to MDI optical specifications for 100GBASE-DR	56
140.11.4.3a	PMD to MDI optical specifications for 100GBASE-FR1	56
140.11.4.3b	PMD to MDI optical specifications for 100GBASE-LR1	57
140.11.4.4	Optical measurement methods	57
140.11.4.6	Characteristics of the fiber optic cabling and MDI	58
151.	Physical Medium Dependent (PMD) sublayer and medium, type 400GBASE-FR4 and 400GBASE-LR4-6	59
151.1	Overview	59
151.1.1	Bit error ratio	60
151.2	Physical Medium Dependent (PMD) service interface	60
151.3	Delay and Skew	61
151.3.1	Delay constraints	61
151.3.2	Skew constraints	61
151.4	PMD MDIO function mapping	62
151.5	PMD functional specifications	62
151.5.1	PMD block diagram	62
151.5.2	PMD transmit function	63
151.5.3	PMD receive function	63
151.5.4	PMD global signal detect function	64
151.5.5	PMD lane-by-lane signal detect function	64
151.5.6	PMD reset function	64
151.5.7	PMD global transmit disable function (optional)	64
151.5.8	PMD lane-by-lane transmit disable function	65
151.5.9	PMD fault function (optional)	65
151.5.10	PMD transmit fault function (optional)	65
151.5.11	PMD receive fault function (optional)	65
151.6	Wavelength-division-multiplexed lane assignments	66
151.7	PMD to MDI optical specifications for 400GBASE-FR4 and 400GBASE-LR4-6	66
151.7.1	400GBASE-FR4 and 400GBASE-LR4-6 transmitter optical specifications	66
151.7.2	400GBASE-FR4 and 400GBASE-LR4-6 receive optical specifications	68
151.7.3	400GBASE-FR4 and 400GBASE-LR4-6 illustrative link power budgets	70
151.8	Definition of optical parameters and measurement methods	72
151.8.1	Test patterns for optical parameters	72

151.8.2	Wavelength and side mode suppression ratio (SMSR)	73
151.8.3	Average optical power	73
151.8.4	Outer Optical Modulation Amplitude (OMA _{outer})	73
151.8.5	Transmitter and dispersion eye closure for PAM4 (TDECQ).....	73
151.8.5.1	Channel requirements	73
151.8.6	Transmitter eye closure for PAM4 (TECQ).....	74
151.8.7	Over/under-shoot.....	74
151.8.8	Transmitter power excursion.....	74
151.8.9	Extinction ratio	74
151.8.10	Transmitter transition time	74
151.8.11	Relative intensity noise (RIN _{17.1OMA} and RIN _{15.6OMA})	75
151.8.12	Receiver sensitivity	75
151.8.13	Stressed receiver sensitivity	76
151.9	Safety, installation, environment, and labeling.....	76
151.9.1	General safety.....	76
151.9.2	Laser safety	76
151.9.3	Installation.....	76
151.9.4	Environment.....	77
151.9.5	Electromagnetic emission	77
151.9.6	Temperature, humidity, and handling	77
151.9.7	PMD labeling requirements	77
151.10	Fiber optic cabling model	77
151.11	Characteristics of the fiber optic cabling (channel)	78
151.11.1	Optical fiber cable	78
151.11.2	Optical fiber connection	78
151.11.2.1	Connection insertion loss.....	79
151.11.2.2	Maximum discrete reflectance.....	79
151.11.3	Medium Dependent Interface (MDI) requirements	79
151.12	Interoperation between 400GBASE-LR4-6 and 400GBASE-FR4	79
151.13	Protocol implementation conformance statement (PICS) proforma for Clause 151, Physical Medium Dependent (PMD) sublayer and medium, type 400GBASE-FR4 and 400GBASE-LR4-6.....	81
151.13.1	Introduction	81
151.13.2	Identification	81
151.13.2.1	Implementation identification.....	81
151.13.2.2	Protocol summary	81
151.13.3	Major capabilities/options	82
151.13.4	PICS proforma tables for Physical Medium Dependent (PMD) sublayer and medium, type 400GBASE-FR4 and 400GBASE-LR4-6.....	82
151.13.4.1	PMD functional specifications	82
151.13.4.2	Management functions	83
151.13.4.3	PMD to MDI optical specifications for 400GBASE-FR4.....	84
151.13.4.4	PMD to MDI optical specifications for 400GBASE-LR4-6	84
151.13.4.5	Optical measurement methods.....	84
151.13.4.6	Environmental specifications	85
151.13.4.7	Characteristics of the fiber optic cabling and MDI	85

IEEE Standard for Ethernet

Amendment 11: Physical Layers and Management Parameters for 100 Gb/s and 400 Gb/s Operation over Single-Mode Fiber at 100 Gb/s per Wavelength

(This amendment is based on IEEE Std 802.3™-2018 as amended by IEEE Std 802.3cb™-2018, IEEE Std 802.3bt™-2018, IEEE Std 802.3cd™-2018, IEEE Std 802.3cn™-2019, IEEE Std 802.3cg™-2019, IEEE Std 802.3cq™-2020, IEEE Std 802.3cm™-2020, IEEE Std 802.3ch™-2020, IEEE Std 802.3ca™-2020, and IEEE Std 802.3cr™-2020.)

NOTE—The editing instructions contained in this amendment define how to merge the material contained therein into the existing base standard and its amendments to form the comprehensive standard.

The editing instructions are shown in ***bold italic***. Four editing instructions are used: change, delete, insert, and replace. ***Change*** is used to make corrections in existing text or tables. The editing instruction specifies the location of the change and describes what is being changed by using ~~strike through~~ (to remove old material) and underscore (to add new material). ***Delete*** removes existing material. ***Insert*** adds new material without disturbing the existing material. Deletions and insertions may require renumbering. If so, renumbering instructions are given in the editing instruction. ***Replace*** is used to make changes in figures or equations by removing the existing figure or equation and replacing it with a new one. Editing instructions, change markings, and this NOTE will not be carried over into future editions because the changes will be incorporated into the base standard.

Cross references that refer to clauses, tables, equations, or figures not covered by this amendment are highlighted in ***green***.¹

¹ Notes in text, tables, and figures are given for information only and do not contain requirements needed to implement the standard.

1. Introduction

1.4 Definitions

Insert the following new definition after 1.4.27 “100GBASE-ER4”:

1.4.27a 100GBASE-FR1: IEEE 802.3 Physical Layer specification for 100 Gb/s serial transmission using 100GBASE-R encoding and 4-level pulse amplitude modulation over one wavelength on single-mode fiber, with reach up to at least 2 km. (See IEEE Std 802.3, Clause 140.)

Insert the following new definition after 1.4.29 “100GBASE-KR4”:

1.4.29a 100GBASE-LR1: IEEE 802.3 Physical Layer specification for 100 Gb/s serial transmission using 100GBASE-R encoding and 4-level pulse amplitude modulation over one wavelength on single-mode fiber, with reach up to at least 10 km. (See IEEE Std 802.3, Clause 140.)

Insert the following new definition after 1.4.106a “400GBASE-ER8” as inserted by IEEE Std 802.3cn-2019:

1.4.106b 400GBASE-FR4: IEEE 802.3 Physical Layer specification for 400 Gb/s using 400GBASE-R encoding and 4-level pulse amplitude modulation over four WDM lanes on single-mode fiber, with reach up to at least 2 km. (See IEEE Std 802.3, Clause 151.)

Insert the following new definition after 1.4.107 “400GBASE-FR8”:

1.4.107a 400GBASE-LR4-6: IEEE 802.3 Physical Layer specification for 400 Gb/s using 400GBASE-R encoding and 4-level pulse amplitude modulation over four WDM lanes on single-mode fiber, with reach up to at least 6 km. (See IEEE Std 802.3, Clause 151.)

30. Management

30.5 Layer management for medium attachment units (MAUs)

30.5.1 MAU managed object class

30.5.1.1 MAU attributes

30.5.1.1.2 aMAUType

Insert 100GBASE-FR1 PHY type into the “APPROPRIATE SYNTAX” section of 30.5.1.1.2 after 100GBASE-SR10 as follows:

APPROPRIATE SYNTAX:

...	
100GBASE-FR1	100GBASE-R PCS/PMA over single-mode fiber PMD with reach up to at least 2 km as specified in Clause 140
...	

Insert 100GBASE-LR1 PHY type into the “APPROPRIATE SYNTAX” section of 30.5.1.1.2 after 100GBASE-LR4 as follows:

APPROPRIATE SYNTAX:

...	
100GBASE-LR1	100GBASE-R PCS/PMA over single-mode fiber PMD with reach up to at least 10 km as specified in Clause 140
...	

Insert 400GBASE-FR4 and 400GBASE-LR4-6 PHY types into the “APPROPRIATE SYNTAX” section of 30.5.1.1.2 after 400GBASE-FR8 as follows:

APPROPRIATE SYNTAX:

...	
400GBASE-FR4	400GBASE-R PCS/PMA over 4 WDM lane single-mode fiber PMD with reach up to at least 2 km as specified in Clause 151
400GBASE-LR4-6	400GBASE-R PCS/PMA over 4 WDM lane single-mode fiber PMD with reach up to at least 6 km as specified in Clause 151
...	

45. Management Data Input/Output (MDIO) Interface

45.2 MDIO Interface Registers

45.2.1 PMA/PMD registers

45.2.1.6 PMA/PMD control 2 register (Register 1.7)

Change the indicated reserved rows of Table 45–7 (as modified by IEEE Std 802.3cd-2018, IEEE Std 802.3cn-2019, and IEEE Std 802.3cm-2020) as follows (unchanged rows not shown):

Table 45–7—PMA/PMD control 2 register bit definitions

Bit(s)	Name	Description	R/W ^a
...			
1.7.6:0	PMA/PMD type selection	6 5 4 3 2 1 0 ... <u>1 1 0 0 0 1 0</u> = 400GBASE-LR4-6 PMA/PMD reserved <u>1 1 0 0 0 0 1</u> = 400GBASE-FR4 PMA/PMD reserved ... <u>1 0 0 1 1 x x</u> = reserved <u>1 0 0 1 1 1 x</u> = reserved <u>1 0 0 1 1 0 1</u> = 100GBASE-LR1 PMA/PMD <u>1 0 0 1 1 0 0</u> = 100GBASE-FR1 PMA/PMD ...	R/W

^aR/W = Read/Write, RO = Read only

45.2.1.7 PMA/PMD status 2 register (Register 1.8)

45.2.1.7.4 Transmit fault (1.8.11)

Change the row for 100GBASE-DR in Table 45–9 (as inserted by IEEE Std 802.3cd-2018) and insert a new row for 400GBASE-FR4 and 400GBASE-LR4-6 at the end of Table 45–9 as follows (unchanged rows not shown):

Table 45–9—Transmit fault description location

PMA/PMD	Description location
...	
<u>100GBASE-DR, 100GBASE-FR1,</u> <u>100GBASE-LR1</u>	140.5.8
...	
400GBASE-FR4, 400GBASE-LR4-6	151.5.10

45.2.1.7.5 Receive fault (1.8.10)

Change the row for 100GBASE-DR in Table 45–10 (as inserted by IEEE Std 802.3cd-2018) and insert a new row for 400GBASE-FR4 and 400GBASE-LR4-6 at the end of Table 45–10 as follows (unchanged rows not shown):

Table 45–10—Receive fault description location

PMA/PMD	Description location
...	
100GBASE-DR, 100GBASE-FR1, 100GBASE-LR1	140.5.9
...	
400GBASE-FR4, 400GBASE-LR4-6	151.5.11

45.2.1.8 PMD transmit disable register (Register 1.9)

Change the row for 100GBASE-DR in Table 45–12 (as inserted by IEEE Std 802.3cd-2018) and insert a new row for 400GBASE-FR4 and 400GBASE-LR4-6 at the end of Table 45–12 as follows (unchanged rows not shown):

Table 45–12—Transmit disable description location

PMA/PMD	Description location
...	
100GBASE-DR, 100GBASE-FR1, and 100GBASE-LR1	140.5.6
...	
400GBASE-FR4 and 400GBASE-LR4-6	151.5.7

45.2.1.21 400G PMA/PMD extended ability register (Register 1.24)

Change the row for bits 1.24.9:8 in Table 45–24 (as modified by IEEE Std 802.3cm-2020) as follows (unchanged rows not shown):

Table 45–24—400G PMA/PMD extended ability register bit definitions

Bit(s)	Name	Description	R/W ^a
...			
1.24.9:8	Reserved	Value always 0	RO
1.24.9	400GBASE-LR4-6 ability	1 = PMA/PMD is able to perform 400GBASE-LR4-6 0 = PMA/PMD is not able to perform 400GBASE-LR4-6	RO
1.24.8	400GBASE-FR4 ability	1 = PMA/PMD is able to perform 400GBASE-FR4 0 = PMA/PMD is not able to perform 400GBASE-FR4	RO
...			

^aRO = Read only

Insert 45.2.1.21.1a1 and 45.2.1.21.1a2 after 45.2.1.21.1a (as inserted by IEEE Std 802.3cn-2019) and before 45.2.1.21.1b (as inserted by IEEE Std 802.3cm-2020) as follows:

45.2.1.21.1a1 400GBASE-LR4-6 ability (1.24.9)

When read as a one, bit 1.24.9 indicates that the PMA/PMD is able to operate as a 400GBASE-LR4-6 PMA/PMD type. When read as a zero, bit 1.24.9 indicates that the PMA/PMD is not able to operate as a 400GBASE-LR4-6 PMA/PMD type.

45.2.1.21.1a2 400GBASE-FR4 ability (1.24.8)

When read as a one, bit 1.24.8 indicates that the PMA/PMD is able to operate as a 400GBASE-FR4 PMA/PMD type. When read as a zero, bit 1.24.8 indicates that the PMA/PMD is not able to operate as a 400GBASE-FR4 PMA/PMD type.

45.2.1.21b 40G/100G PMA/PMD extended ability 2 (Register 1.26)

Change the row for bits 1.26.6:4 in Table 45–24b (as inserted by IEEE Std 802.3cn-2019) as follows (unchanged rows not shown):

Table 45–24b—40G/100G PMA/PMD extended ability 2 register bit definitions

Bit(s)	Name	Description	R/W ^a
...			
1.26.6:4 1.26.6	Reserved	Value always 0	RO
1.26.5	100GBASE-LR1 ability	1 = PMA/PMD is able to perform 100GBASE-LR1 0 = PMA/PMD is not able to perform 100GBASE-LR1	RO
1.26.4	100GBASE-FR1 ability	1 = PMA/PMD is able to perform 100GBASE-FR1 0 = PMA/PMD is not able to perform 100GBASE-FR1	RO
...			

^aRO = Read only

Insert 45.2.1.21b.3a and 45.2.1.21b.3b after 45.2.1.21b.3 (as inserted by IEEE Std 802.3cn-2019) as follows:

45.2.1.21b.3a 100GBASE-LR1 ability (1.26.5)

When read as a one, bit 1.26.5 indicates that the PMA/PMD is able to operate as a 100GBASE-LR1 PMA/PMD type. When read as a zero, bit 1.26.5 indicates that the PMA/PMD is not able to operate as a 100GBASE-LR1 PMA/PMD type.

45.2.1.21b.3b 100GBASE-FR1 ability (1.26.4)

When read as a one, bit 1.26.4 indicates that the PMA/PMD is able to operate as a 100GBASE-FR1 PMA/PMD type. When read as a zero, bit 1.26.4 indicates that the PMA/PMD is not able to operate as a 100GBASE-FR1 PMA/PMD type.