

INTERNATIONAL
STANDARD

ISO/IEC/
IEEE
8802-3

Third edition
2021-02

AMENDMENT 4
2021-10

**Telecommunications and exchange
between information technology
systems — Requirements for local and
metropolitan area networks —**

**Part 3:
Standard for Ethernet**

**AMENDMENT 4: Physical layers and
management parameters for 50 Gb/s,
200 Gb/s, and 400 Gb/s operation over
single-mode fiber**

*Télécommunications et échange entre systèmes informatiques —
Exigences pour les réseaux locaux et métropolitains —*

Partie 3: Norme pour Ethernet

*AMENDEMENT 4: Couches physiques et paramètres de gestion pour
le fonctionnement à 50 Gb/s, 200 Gb/s et 400 Gb/s sur des fibres
unimodales*



Reference number
ISO/IEC/IEEE 8802-3:2021/Amd.4:2021(E)

Documents
Document Sharing Hub
© IEEE 2019



COPYRIGHT PROTECTED DOCUMENT

© IEEE 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from IEEE at the address below.

Institute of Electrical and Electronics Engineers, Inc
3 Park Avenue, New York
NY 10016-5997, USA

Email: stds.ipr@ieee.org
Website: www.ieee.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO/IEC documents should be noted (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see patents.iec.ch).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

ISO/IEC/IEEE 8802-3:2021/Amd 4 was prepared by the LAN/MAN of the IEEE Computer Society (as IEEE Std 802-3cn-2019) and drafted in accordance with its editorial rules. It was adopted, under the “fast-track procedure” defined in the Partner Standards Development Organization cooperation agreement between ISO and IEEE, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*.

A list of all parts in the ISO/IEC/IEEE 8802 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

IEEE Std 802.3cn™-2019
(Amendment to IEEE Std 802.3™-2018
as amended by IEEE Std 802.3cb™-2018,
IEEE Std 802.3bt™-2018, and
IEEE Std 802.3cd™-2018)

IEEE Standard for Ethernet

Amendment 4: Physical Layers and Management Parameters for 50 Gb/s, 200 Gb/s, and 400 Gb/s Operation over Single-Mode Fiber

Developed by the
LAN/MAN Standards Committee
of the
IEEE Computer Society

Approved 7 November 2019
IEEE SA Standards Board

Abstract: This amendment to IEEE Std 802.3-2018 adds Physical Layer (PHY) specifications and management parameters for 50 Gb/s, 200 Gb/s, and 400 Gb/s operation over single-mode fiber with reaches of at least 40 km.

Keywords: 50 Gb/s Ethernet, 50GBASE-ER, 200 Gb/s Ethernet, 200GBASE-ER4, 400 Gb/s Ethernet, 400GBASE-ER8, amendment, EEE, Energy-Efficient Ethernet, Ethernet, FEC, forward error correction, IEEE 802.3™, IEEE 802.3cn™, PAM4, physical medium dependent sublayer, PMD sublayer, single-mode fiber, SMF

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2019 by The Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 20 December 2019. Printed in the United States of America.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-1-5044-6384-3 STD24016
Print: ISBN 978-1-5044-6385-0 STDPD24016

IEEE prohibits discrimination, harassment and bullying.

For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading “Important Notices and Disclaimers Concerning IEEE Standards Documents.” They can also be obtained on request from IEEE or viewed at <http://standards.ieee.org/ipr/disclaimers.html>.

Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents (standards, recommended practices, and guides), both full-use and trial-use, are developed within IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (“IEEE SA”) Standards Board. IEEE (“the Institute”) develops its standards through a consensus development process, approved by the American National Standards Institute (“ANSI”), which brings together volunteers representing varied viewpoints and interests to achieve the final product. IEEE Standards are documents developed through scientific, academic, and industry-based technical working groups. Volunteers in IEEE working groups are not necessarily members of the Institute and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers and users of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims all warranties (express, implied and statutory) not included in this or any other document relating to the standard, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, IEEE disclaims any and all conditions relating to: results; and workmanlike effort. IEEE standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

Official statements

A statement, written or oral, that is not processed in accordance with the IEEE SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, or be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in revisions to an IEEE standard is welcome to join the relevant IEEE working group.

Comments on standards should be submitted to the following address:

Secretary, IEEE SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854 USA

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

IEEE draft and approved standards are copyrighted by IEEE under US and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

Photocopies

Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every 10 years. When a document is more than 10 years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit IEEE Xplore at <https://ieeexplore.ieee.org> or contact IEEE at the address listed previously. For more information about the IEEE SA or IEEE's standards development process, visit the IEEE SA Website at <http://standards.ieee.org>.

Errata

Errata, if any, for IEEE standards can be accessed via <https://standards.ieee.org/standard/index.html>. Search for standard number and year of approval to access the web page of the published standard. Errata links are located under the Additional Resources Details section. Errata are also available in IEEE Xplore: <https://ieeexplore.ieee.org/browse/standards/collection/ieee/>. Users are encouraged to periodically check for errata.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE SA Website at <https://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patent Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

Participants

The following individuals were officers and members of the IEEE 802.3 Working Group at the beginning of the IEEE P802.3cn Working Group ballot.

David J. Law, *IEEE 802.3 Working Group Chair*
Adam Healey, *IEEE 802.3 Working Group Vice-Chair*
Pete Anslow, *IEEE 802.3 Working Group Secretary*
Steven B. Carlson, *IEEE 802.3 Working Group Executive Secretary*
Valerie Maguire, *IEEE 802.3 Working Group Treasurer*

John D'Ambrosia, *IEEE P802.3cn 50 Gb/s, 200 Gb/s, and 400 Gb/s over Single-Mode Fiber Task Force Chair*

Pete Anslow, *IEEE P802.3cn 50 Gb/s, 200 Gb/s, and 400 Gb/s over Single-Mode Fiber Task Force Editor-in-Chief*

Peter Stassar, *IEEE P802.3cn 50 Gb/s, 200 Gb/s, and 400 Gb/s over Single-Mode Fiber Task Force Editor for Clauses 122 and 139*

John Abbott	Hormoz Djahanshahi	John Johnson
David Abramson	Curtis Donahue	Chad Jones
Andrea Agnes	Liang Du	Peter Jones
Dale Amason	Kathryn Dube	Lokesh Kabra
Hongming An	Mike Dudek	Manabu Kagami
Jes Asmussen	Marc Dupuis	Upen Kareti
Richard Baca	Frank Effenberger	Yasuaki Kawatsu
Tim Baggett	David Estes	Yong Kim
Amrik Bains	John Ewen	Mark Kimber
Thananya Baldwin	Borhan Fathi Moghadam	Jonathan King
Steven Baumgartner	Vincent Ferretti	Michael Klempa
Denis Beaudoin	Brian Franchuk	Curtis Knittle
Liav Ben-Artzi	Matthias Fritsche	Elizabeth Kochuparambil
Piergiorgio Beruto	Richard Frosch	Wojciech Koczwara
Vipul Bhatt	Shiyong Fu	Paul Kolesar
Gao Bo	Mike Gardner	Taiji Kondo
Brad Booth	Claude Gauthier	Glen Kramer
Martin Bouda	Ali Ghiasi	Olaf Krieger
David Brandt	Joel Goergen	Hans Lackner
Ralf-Peter Braun	Zhigang Gong	Jeffrey Lapak
Paul Brooks	Steven Gorshe	Mark Laubach
Alan Brown	Jens Gottron	Han Hyub Lee
Matthew Brown	Steffen Graber	June Hee Lee
Michal Brychta	Olaf Grau	Alex Levin
Gary Burrell	Robert Grow	David Lewis
Jairo Bustos Heredia	Mark Gustlin	Jon Lewis
Adrian Butter	Marek Hajduczenia	David Li
John Calvin	Hayden Haynes	Mike-Peng Li
Clark Carty	Xiang He	Jane Lim
Craig Chabot	Howard Heck	Alex Lin
David Chalupsky	Rajmohan Hegde	Robert Lingle
Frank Chang	Brian Holden	Dekun Liu
Xin Chang	Rita Horner	Hai-Feng Liu
Golam Choudhury	Bernd Horrmeyer	Karen Liu
Keng Hua Chuang	Gergely Huszak	Zhenyu Liu
Kamal Dalmia	Yasuhiro Hyakutake	William Lo
Piers Dawe	Jonathan Ingham	Yuchun Lu
Fred Dawson	Kazuhiko Ishibe	Miklos Lukacs
John Deandrea	Hideki Isono	Kent Lusted
Gerrit den Besten	Tom Issenhuth	
Claudio DeSanti	Kenneth Jackson	
Chris Diminico	Andrew Jimenez	

Ilya Lyubomirsky
Zahy Madgar
Jeffery Maki
David Malicoat
Flavio Marques
Arthur Marris
Chris Mash
Takeo Masuda
Kirsten Matheus
Erdem Matoglu
Marco Mazzini
Mick McCarthy
Brett McClellan
Larry McMillan
Greg McSorley
Richard Mellitz
Martin Miller
Toshiyuki Moritake
Harald Mueller
Thomas Mueller
Edward Nakamoto
Paul Neveux
Gary Nicholl
Shawn Nicholl
John Nolan
Kevin Noll
Mark Nowell
David Ofelt
Josef Ohni
Tom Palkert
Sujan Pandey
Carlos Pardo
Earl Parsons
Gerald Pepper
Phong Pham
David Piehler
Rick Pimpinella

Christopher Pohl
William Powell
Dino Pozzebon
Rick Rabinovich
Zvi Rechtman
Alon Regev
Duane Remein
Victor Renteria
Salvatore Rotolo
Alexander Rysin
Toshiaki Sakai
Hamid Salehi
Sam Sambasivan
Edward Sayre
James Schuessler
Steve Sekel
Masood Shariff
Mizuki Shirao
Jialong Shuai
Jeff Slavick
Daniel Smith
Scott Sommers
Tom Souvignier
Bryan Sparrowhawk
Edward Sprague
Heath Stewart
David Stover
Junqing Sun
Liyang Sun
Steve Swanson
Bharat Tailor
Tomoo Takahara
Kohichi Tamura
Mehmet Tazebay
Ronald Tellas
Geoffrey Thompson
Pirooz Tooyserkani

Nathan Tracy
David Tremblay
Stephen Trowbridge
Ta Chin Tseng
Ed Ulrichs
Alexander Umnov
Ricky Vernickel
Marco Vitali
Robert Voss
Dylan Walker
Haifei Wang
Roy Wang
Tongtong Wang
Xinyuan Wang
Xuehuan Wang
Christoph Wechsler
Brian Welch
Matthias Wendt
Natalie Wienckowski
James Withey
Mau-Lin Wu
Peter Wu
Markus Wucher
Dayin Xu
Yu Xu
Shuto Yamamoto
Adrian Young
James Young
Lennart Yseboodt
Andrew Zambell
Conrad Zerna
Richard (Yujia) Zhou
Yan Zhuang
Martin Zielinski
George Zimmerman
Pavel Zivny
Harald Zweck

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Rob Aekins	David Hess	Thomas Palkert
Thomas Alexander	Werner Hoelzl	Carlos Pardo
Pete Anslow	Rita Horner	Bansi Patel
Burrell Best	C. Huntley	David Piehler
Rich Boyer	Yasuhiro Hyakutake	Rick Pimpinella
Ralf-Peter Braun	Atsushi Ito	Adee Ran
Nancy Bravin	Raj Jain	R. K. Rannow
Matthew Brown	Peter Jones	Alon Regev
Demetrio Bucaneg	Lokesh Kabra	Robert Robinson
Gary Burrell	Piotr Karocki	Thomas Starai
Jairo Bustos Heredia	Stuart Kerry	Peter Stassar
William Byrd	Yongbum Kim	Walter Struppler
John Calvin	Mark Laubach	Mitsutoshi Sugawara
Steven B. Carlson	David J. Law	James Theodoras
Juan Carreon	Hyeong Ho Lee	David Thompson
Chan Chen	David Lewis	David Tremblay
John D'Ambrosia	Jon Lewis	Stephen Trowbridge
Piers J. G. Dawe	Michael Lynch	Mark-Rene Uchida
John Deandrea	Valerie Maguire	Alexander Umnov
Marc Dupuis	Jeffery Maki	Dmitri Varsanofiev
Avraham Freedman	David Malicoat	George Vlantis
Ali Ghiasi	Arthur Marris	Lisa Ward
James Gilb	Michael Maytum	Keith Waters
Zhigang Gong	Richard Mellitz	Chun Yu Charles Wong
Randall Groves	Paul Neveux	James Young
Marek Hajduczenia	Nick S. A. Nikjoo	Yu Yuan
Marco Hernandez	Satoshi Obara	Oren Yuen
		Zhen Zhou

When the IEEE SA Standards Board approved this standard on 7 November 2019, it had the following membership:

Gary Hoffman, *Chair*
Ted Burse, *Vice Chair*
Jean-Philippe Faure, *Past Chair*
Konstantinos Karachalios, *Secretary*

Masayuki Ariyoshi	David J. Law	Annette Reilly
Stephen D. Dukes	Joseph Levy	Dorothy Stanley
J. Travis Griffith	Howard Li	Sha Wei
Guido Hiertz	Xiaohui Liu	Phil Wennblom
Christel Hunter	Kevin Lu	Philip Winston
Joseph L. Koepfinger*	Daleep Mohla	Howard Wolfman
Thomas Koshy	Andrew Myles	Feng Wu
John D. Kulick		Jingyi Zhou

*Member Emeritus

Introduction

This introduction is not part of IEEE Std 802.3cn-2019, IEEE Standard for Ethernet. Amendment 4: Physical Layers and Management Parameters for 50 Gb/s, 200 Gb/s, and 400 Gb/s Operation over Single-Mode Fiber.

IEEE Std 802.3™ was first published in 1985. Since the initial publication, many projects have added functionality or provided maintenance updates to the specifications and text included in the standard. Each IEEE 802.3 project/amendment is identified with a suffix (e.g., IEEE Std 802.3ba™-2010).

The half duplex Media Access Control (MAC) protocol specified in IEEE Std 802.3-1985 is Carrier Sense Multiple Access with Collision Detection (CSMA/CD). This MAC protocol was key to the experimental Ethernet developed at Xerox Palo Alto Research Center, which had a 2.94 Mb/s data rate. Ethernet at 10 Mb/s was jointly released as a public specification by Digital Equipment Corporation (DEC), Intel and Xerox in 1980. Ethernet at 10 Mb/s was approved as an IEEE standard by the IEEE Standards Board in 1983 and subsequently published in 1985 as IEEE Std 802.3-1985. Since 1985, new media options, new speeds of operation, and new capabilities have been added to IEEE Std 802.3. A full duplex MAC protocol was added in 1997.

Some of the major additions to IEEE Std 802.3 are identified in the marketplace with their project number. This is most common for projects adding higher speeds of operation or new protocols. For example, IEEE Std 802.3u™ added 100 Mb/s operation (also called Fast Ethernet), IEEE Std 802.3z added 1000 Mb/s operation (also called Gigabit Ethernet), IEEE Std 802.3ae added 10 Gb/s operation (also called 10 Gigabit Ethernet), IEEE Std 802.3ah™ specified access network Ethernet (also called Ethernet in the First Mile) and IEEE Std 802.3ba added 40 Gb/s operation (also called 40 Gigabit Ethernet) and 100 Gb/s operation (also called 100 Gigabit Ethernet). These major additions are all now included in and are superseded by IEEE Std 802.3-2018 and are not maintained as separate documents.

At the date of publication for IEEE Std 802.3cn-2019, IEEE Std 802.3 was composed of the following documents:

IEEE Std 802.3-2018

Section One—Includes Clause 1 through Clause 20 and Annex A through Annex H and Annex 4A. Section One includes the specifications for 10 Mb/s operation and the MAC, frame formats and service interfaces used for all speeds of operation.

Section Two—Includes Clause 21 through Clause 33 and Annex 22A through Annex 33E. Section Two includes management attributes for multiple protocols and speed of operation as well as specifications for providing power over twisted pair cabling for multiple operational speeds. It also includes general information on 100 Mb/s operation as well as most of the 100 Mb/s Physical Layer specifications.

Section Three—Includes Clause 34 through Clause 43 and Annex 36A through Annex 43C. Section Three includes general information on 1000 Mb/s operation as well as most of the 1000 Mb/s Physical Layer specifications.

Section Four—Includes Clause 44 through Clause 55 and Annex 44A through Annex 55B. Section Four includes general information on 10 Gb/s operation as well as most of the 10 Gb/s Physical Layer specifications.

Section Five—Includes Clause 56 through Clause 77 and Annex 57A through Annex 76A. Clause 56 through Clause 67 and Clause 75 through Clause 77, as well as associated annexes, specify subscriber access and other Physical Layers and sublayers for operation from 512 kb/s to 10 Gb/s, and defines

services and protocol elements that enable the exchange of IEEE Std 802.3 format frames between stations in a subscriber access network. Clause 68 specifies a 10 Gb/s Physical Layer specification. Clause 69 through Clause 74 and associated annexes specify Ethernet operation over electrical backplanes at speeds of 1000 Mb/s and 10 Gb/s.

Section Six—Includes Clause 78 through Clause 95 and Annex 83A through Annex 93C. Clause 78 specifies Energy-Efficient Ethernet. Clause 79 specifies IEEE 802.3 Organizationally Specific Link Layer Discovery Protocol (LLDP) type, length, and value (TLV) information elements. Clause 80 through Clause 95 and associated annexes include general information on 40 Gb/s and 100 Gb/s operation as well the 40 Gb/s and 100 Gb/s Physical Layer specifications. Clause 90 specifies Ethernet support for time synchronization protocols.

Section Seven—Includes Clause 96 through Clause 115 and Annex 97A through Annex 115A. Clause 96 through Clause 98, Clause 104, and associated annexes, specify Physical Layers and optional features for 100 Mb/s and 1000 Mb/s operation over a single twisted pair. Clause 100 through Clause 103, as well as associated annexes, specify Physical Layers for the operation of the EPON protocol over coaxial distribution networks. Clause 105 through Clause 114 and associated annexes include general information on 25 Gb/s operation as well as 25 Gb/s Physical Layer specifications. Clause 99 specifies a MAC merge sublayer for the interspersing of express traffic. Clause 115 and its associated annex specify a Physical Layer for 1000 Mb/s operation over plastic optical fiber.

Section Eight—Includes Clause 116 through Clause 126 and Annex 119A through Annex 120E. Clause 116 through Clause 124 and associated annexes include general information on 200 Gb/s and 400 Gb/s operation as well the 200 Gb/s and 400 Gb/s Physical Layer specifications. Clause 125 and Clause 126 include general information on 2.5 Gb/s and 5 Gb/s operation as well as 2.5 Gb/s and 5 Gb/s Physical Layer specifications.

IEEE Std 802.3cb™-2018

Amendment 1—This amendment includes changes to IEEE Std 802.3-2018 and its amendments, and adds Clause 127 through Clause 130, Annex 127A, Annex 128A, Annex 128B, and Annex 130A. This amendment adds new Physical Layers for operation at 2.5 Gb/s and 5 Gb/s over electrical backplanes.

IEEE Std 802.3bt™-2018

Amendment 2—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 145, Annex 145A, Annex 145B, and Annex 145C. This amendment adds power delivery using all four pairs in the structured wiring plant, resulting in greater power being available to end devices. This amendment also allows for lower standby power consumption in end devices and adds a mechanism to better manage the available power budget.

IEEE Std 802.3cd™-2018

Amendment 3—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 131 through Clause 140 and Annex 135A through Annex 136D. This amendment adds MAC parameters, Physical Layers, and management parameters for the transfer of IEEE 802.3 format frames at 50 Gb/s, 100 Gb/s, and 200 Gb/s.

IEEE Std 802.3cn™-2019

Amendment 4—This amendment includes changes to IEEE Std 802.3-2018 and adds 50 Gb/s, 200 Gb/s, and 400 Gb/s Physical Layer specifications and management parameters for operation over single-mode fiber with reaches of at least 40 km.

Two companion documents exist, IEEE Std 802.3.1 and IEEE Std 802.3.2. IEEE Std 802.3.1 describes Ethernet management information base (MIB) modules for use with the Simple Network Management Protocol (SNMP). IEEE Std 802.3.2 describes YANG data models for Ethernet. IEEE Std 802.3.1 and IEEE Std 802.3.2 are updated to add management capability for enhancements to IEEE Std 802.3 after approval of those enhancements.

IEEE Std 802.3 will continue to evolve. New Ethernet capabilities are anticipated to be added within the next few years as amendments to this standard.

Contents

1. Introduction.....	18
1.4 Definitions	18
30. Management.....	19
30.5 Layer management for medium attachment units (MAUs)	19
30.5.1 MAU managed object class	19
30.5.1.1 MAU attributes	19
30.5.1.1.2 aMAUType	19
45. Management Data Input/Output (MDIO) Interface	20
45.2 MDIO Interface Registers.....	20
45.2.1 PMA/PMD registers	20
45.2.1.6 PMA/PMD control 2 register (Register 1.7).....	20
45.2.1.7 PMA/PMD status 2 register (Register 1.8)	21
45.2.1.7.4 Transmit fault (1.8.11)	21
45.2.1.7.5 Receive fault (1.8.10).....	21
45.2.1.8 PMD transmit disable register (Register 1.9)	22
45.2.1.17a 50G PMA/PMD extended ability register (Register 1.20)	22
45.2.1.17a.1a 50GBASE-ER ability (1.20.5)	22
45.2.1.20 200G PMA/PMD extended ability register (Register 1.23)	23
45.2.1.20.1a 200GBASE-ER4 ability (1.23.6)	23
45.2.1.20.5 200GBASE-SR4 ability (1.23.2)	23
45.2.1.20.6 200GBASE-CR4 ability (1.23.1)	23
45.2.1.20.7 200GBASE-KR4 ability (1.23.0).....	23
45.2.1.21 400G PMA/PMD extended ability register (Register 1.24)	24
45.2.1.21.1a 400GBASE-ER8 ability (1.24.10).....	24
45.2.1.21b 40G/100G PMA/PMD extended ability 2 (Register 1.26)	24
45.2.1.21b.1 100GBASE-SR2 ability (1.26.9)	25
45.2.1.21b.2 100GBASE-CR2 ability (1.26.8).....	25
45.2.1.21b.3 100GBASE-KR2 ability (1.26.7).....	25
45.2.1.21b.4 100GBASE-DR ability (1.26.3).....	25
78. Energy-Efficient Ethernet (EEE)	26
78.1 Overview.....	26
78.1.4 PHY types optionally supporting EEE	26
116. Introduction to 200 Gb/s and 400 Gb/s networks	27
116.1 Overview.....	27
116.1.2 Relationship of 200 Gigabit and 400 Gigabit Ethernet to the ISO OSI reference model	27
116.1.3 Nomenclature.....	27
116.1.4 Physical Layer signaling systems	28
116.4 Delay constraints.....	29

121. Physical Medium Dependent (PMD) sublayer and medium, type 200GBASE-DR4	30
121.7 PMD to MDI optical specifications for 200GBASE-DR4	30
121.7.1 200GBASE-DR4 transmitter optical specifications	30
121.7.2 200GBASE-DR4 receive optical specifications	31
121.7.3 200GBASE-DR4 illustrative link power budget	32
121.8 Definition of optical parameters and measurement methods.....	32
121.8.1 Test patterns for optical parameters.....	32
121.8.5 Transmitter and dispersion eye closure for PAM4 (TDECQ).....	33
121.8.5.1 TDECQ conformance test setup	33
121.8.5.3 TDECQ measurement method.....	33
121.8.5.4 TDECQ reference equalizer.....	33
121.8.6a Transmitter transition time.....	33
121.8.8 Receiver sensitivity.....	34
121.8.9 Stressed receiver sensitivity.....	34
121.8.9.1 Stressed receiver conformance test block diagram.....	34
121.8.9.2 Stressed receiver conformance test signal characteristics and calibration	35
121.12 Protocol implementation conformance statement (PICS) proforma for Clause 121, Physical Medium Dependent (PMD) sublayer and medium, type 200GBASE-DR4.....	35
121.12.4 PICS proforma tables for Physical Medium Dependent (PMD) sublayer and medium, type 200GBASE-DR4	35
121.12.4.4 Optical measurement methods.....	35
122. Physical Medium Dependent (PMD) sublayer and medium, type 200GBASE-FR4, 200GBASE- LR4, 200GBASE-ER4, 400GBASE-FR8, and 400GBASE-LR8, and 400GBASE-ER8.....	36
122.1 Overview.....	36
122.2 Physical Medium Dependent (PMD) service interface	38
122.3 Delay and Skew	38
122.3.1 Delay constraints.....	38
122.5 PMD functional specifications.....	38
122.5.1 PMD block diagram.....	39
122.5.4 PMD global signal detect function	39
122.5.7 PMD global transmit disable function (optional)	40
122.5.8 PMD lane-by-lane transmit disable function	40
122.6 Wavelength-division-multiplexed lane assignments	40
122.7 PMD to MDI optical specifications for 200GBASE-FR4, 200GBASE-LR4, 200GBASE- ER4, 400GBASE-FR8, and 400GBASE-LR8, and 400GBASE-ER8	41
122.7.1 200GBASE-FR4, 200GBASE-LR4, 200GBASE-ER4, 400GBASE-FR8, and 400GBASE-LR8, and 400GBASE-ER8 transmitter optical specifications	42
122.7.2 200GBASE-FR4, 200GBASE-LR4, 200GBASE-ER4, 400GBASE-FR8, and 400GBASE-LR8, and 400GBASE-ER8 receive optical specifications	45
122.7.3 200GBASE-FR4, 200GBASE-LR4, 200GBASE-ER4, 400GBASE-FR8, and 400GBASE-LR8, and 400GBASE-ER8 illustrative link power budgets.....	47
122.8 Definition of optical parameters and measurement methods.....	48
122.8.1 Test patterns for optical parameters.....	48
122.8.2 Wavelength and side mode suppression ratio (SMSR)	48
122.8.3 Average optical power	48
122.8.4 Outer Optical Modulation Amplitude (OMA _{outer}).....	49
122.8.5 Transmitter and dispersion eye closure for PAM4 (TDECQ).....	49
122.8.5.1 TDECQ conformance test setup	49
122.8.5.2 Channel requirements	50
122.8.5.3 TDECQ measurement method.....	50
122.8.5.4 TDECQ reference equalizer.....	50

122.8.6	Extinction ratio	51
122.8.6a	Transmitter transition time.....	51
122.8.7	Relative intensity noise (RIN17.1OMA, and RIN15.6OMA, and RIN15OMA).....	51
122.8.8	Receiver sensitivity.....	51
122.8.9	Stressed receiver sensitivity.....	53
122.8.9.1	Stressed receiver conformance test block diagram.....	54
122.8.9.2	Stressed receiver conformance test signal characteristics and calibration	54
122.9	Safety, installation, environment, and labeling.....	54
122.9.2	Laser safety.....	54
122.9.4	Environment.....	55
122.9.5	Electromagnetic emission	55
122.9.7	PMD labeling requirements.....	55
122.10	Fiber optic cabling model	55
122.11	Characteristics of the fiber optic cabling (channel).....	56
122.11.1	Optical fiber cable.....	56
122.11.2	Optical fiber connection.....	56
122.11.2.1	Connection insertion loss.....	56
122.11.2.2	Maximum discrete reflectance.....	57
122.11.3	Medium Dependent Interface (MDI) requirements	57
122.11a	Requirements for interoperation between 200GBASE-ER4 and 200GBASE-LR4	57
122.11b	Requirements for interoperation between 400GBASE-ER8 and 400GBASE-FR8	58
122.11c	Requirements for interoperation between 400GBASE-ER8 and 400GBASE-LR8	58
122.12	Protocol implementation conformance statement (PICS) proforma for Clause 122, Physical Medium Dependent (PMD) sublayer and medium, type 200GBASE-FR4, 200GBASE-LR4, 200GBASE-ER4, 400GBASE-FR8, and 400GBASE-LR8, and 400GBASE-ER8.....	59
122.12.1	Introduction.....	59
122.12.2	Identification.....	59
122.12.2.2	Protocol summary	59
122.12.3	Major capabilities/options.....	60
122.12.4	PICS proforma tables for Physical Medium Dependent (PMD) sublayer and medium, type 200GBASE-FR4, 200GBASE-LR4, 200GBASE-ER4, 400GBASE-FR8, and 400GBASE-LR8, and 400GBASE-ER8	60
122.12.4.4a	PMD to MDI optical specifications for 200GBASE-ER4.....	61
122.12.4.6a	PMD to MDI optical specifications for 400GBASE-ER8.....	61
122.12.4.7	Optical measurement methods.....	61
122.12.4.8	Environmental specifications.....	61
124.	Physical Medium Dependent (PMD) sublayer and medium, type 400GBASE-DR4	62
124.7	PMD to MDI optical specifications for 400GBASE-DR4	62
124.7.1	400GBASE-DR4 transmitter optical specifications	62
124.7.2	400GBASE-DR4 receiver optical specifications	63
124.8	Definition of optical parameters and measurement methods.....	63
124.8.1	Test patterns for optical parameters.....	63
124.8.5	Transmitter and dispersion eye closure for PAM4 (TDECQ)	64
124.8.6a	Transmitter transition time.....	64
124.8.9	Stressed receiver sensitivity.....	65
124.12	Protocol implementation conformance statement (PICS) proforma for Clause 124, Physical Medium Dependent (PMD) sublayer and medium, type 400GBASE-DR4.....	65
124.12.4	PICS proforma tables for Physical Medium Dependent (PMD) sublayer and medium, type 400GBASE-DR4	65
124.12.4.4	Optical measurement methods.....	65

131. Introduction to 50 Gb/s networks	66
131.1 Overview.....	66
131.1.2 Relationship of 50 Gigabit Ethernet to the ISO OSI reference model.....	66
131.1.3 Nomenclature.....	66
131.1.4 Physical Layer signaling systems	66
131.4 Delay constraints.....	67
138. Physical Medium Dependent (PMD) sublayer and medium, type 50GBASE-SR, 100GBASE-SR2, 200GBASE-SR4	68
138.8 Definition of optical parameters and measurement methods.....	68
138.8.5 Transmitter and dispersion eye closure for PAM4 (TDECQ)	68
138.8.10 Stressed receiver sensitivity.....	68
139. Physical Medium Dependent (PMD) sublayer and medium, type 50GBASE-FR, and 50GBASE-LR, and 50GBASE-ER.....	69
139.1 Overview.....	69
139.2 Physical Medium Dependent (PMD) service interface	70
139.3 Delay and Skew	71
139.3.1 Delay constraints.....	71
139.5 PMD functional specifications.....	71
139.5.1 PMD block diagram.....	71
139.6 PMD to MDI optical specifications for 50GBASE-FR, and 50GBASE-LR, and 50GBASE-ER.....	71
139.6.1 50GBASE-FR, and 50GBASE-LR, and 50GBASE-ER transmitter optical specifications	72
139.6.2 50GBASE-FR, and 50GBASE-LR, and 50GBASE-ER receive optical specifications ...	73
139.6.3 50GBASE-FR, and 50GBASE-LR, and 50GBASE-ER illustrative link power budgets	74
139.7 Definition of optical parameters and measurement methods.....	75
139.7.1 Test patterns for optical parameters.....	75
139.7.2 Wavelength and side-mode suppression ratio (SMSR)	75
139.7.3 Average optical power	75
139.7.4 Outer Optical Modulation Amplitude (OMA _{outer}).....	76
139.7.5 Transmitter and dispersion eye closure for PAM4 (TDECQ)	76
139.7.5.2 Channel requirements	76
139.7.5.3 TDECQ measurement method.....	76
139.7.5.4 TDECQ reference equalizer.....	77
139.7.6 Extinction ratio	77
139.7.8 Relative intensity noise (RIN _{17.1} OMA, and RIN _{15.6} OMA, and RIN ₁₅ OMA).....	77
139.7.9 Receiver sensitivity	77
139.7.10 Stressed receiver sensitivity.....	78
139.7.10.2 Stressed receiver conformance test signal characteristics and calibration	78
139.8 Safety, installation, environment, and labeling.....	79
139.8.2 Laser safety	79
139.8.4 Environment.....	79
139.8.5 Electromagnetic emission	79
139.9 Fiber optic cabling model	80
139.10 Characteristics of the fiber optic cabling (channel).....	80
139.10.1 Optical fiber cable.....	80
139.10.2 Optical fiber connection.....	81
139.10.2.1 Connection insertion loss.....	81

139.10.2.2 Maximum discrete reflectance	81
139.10.3 Medium Dependent Interface (MDI) requirements	81
139.10a Requirements for interoperation between 50GBASE-ER and 50GBASE-FR	82
139.10b Requirements for interoperation between 50GBASE-ER and 50GBASE-LR	82
139.11 Protocol implementation conformance statement (PICS) proforma for Clause 139, Physical Medium Dependent (PMD) sublayer and medium, type 50GBASE-FR, and 50GBASE-LR, and 50GBASE-ER	82
139.11.1 Introduction	83
139.11.2 Identification	83
139.11.2.2 Protocol summary	83
139.11.3 Major capabilities/options	83
139.11.4 PICS proforma tables for Physical Medium Dependent (PMD) sublayer and medium, type 50GBASE-FR, and 50GBASE-LR, and 50GBASE-ER	84
139.11.4.4a PMD to MDI optical specifications for 50GBASE-ER	84
140. Physical Medium Dependent (PMD) sublayer and medium, type 100GBASE-DR	85
140.7 Definition of optical parameters and measurement methods	85
140.7.5 Transmitter and dispersion eye closure for PAM4 (TDECQ)	85
140.7.10 Stressed receiver sensitivity	85

IEEE Standard for Ethernet

Amendment 4: Physical Layers and Management Parameters for 50 Gb/s, 200 Gb/s, and 400 Gb/s Operation over Single-Mode Fiber

(This amendment is based on IEEE Std 802.3™-2018 as amended by IEEE Std 802.3cb™-2018, IEEE Std 802.3bt™-2018, and IEEE Std 802.3cd™-2018.)

NOTE—The editing instructions contained in this amendment define how to merge the material contained therein into the existing base standard and its amendments to form the comprehensive standard.

The editing instructions are shown in ***bold italic***. Four editing instructions are used: change, delete, insert, and replace. ***Change*** is used to make corrections in existing text or tables. The editing instruction specifies the location of the change and describes what is being changed by using ~~strike through~~ (to remove old material) and underscore (to add new material). ***Delete*** removes existing material. ***Insert*** adds new material without disturbing the existing material. Deletions and insertions may require renumbering. If so, renumbering instructions are given in the editing instruction. ***Replace*** is used to make changes in figures or equations by removing the existing figure or equation and replacing it with a new one. Editing instructions, change markings, and this NOTE will not be carried over into future editions because the changes will be incorporated into the base standard.

Cross references that refer to clauses, tables, equations, or figures not covered by this amendment are highlighted in green.¹

¹ Notes in text, tables, and figures are given for information only and do not contain requirements needed to implement the standard.

1. Introduction

1.4 Definitions

Insert the following new definition after 1.4.83 “200GBASE-DR4”:

1.4.83a 200GBASE-ER4: IEEE 802.3 Physical Layer specification for 200 Gb/s using 200GBASE-R encoding and 4-level pulse amplitude modulation over four WDM lanes on single-mode fiber, with reach up to at least 40 km. (See IEEE Std 802.3, Clause 122.)

Insert the following new definition after 1.4.106 “400GBASE-DR4”:

1.4.106a 400GBASE-ER8: IEEE 802.3 Physical Layer specification for 400 Gb/s using 400GBASE-R encoding and 4-level pulse amplitude modulation over eight WDM lanes on single-mode fiber, with reach up to at least 40 km. (See IEEE Std 802.3, Clause 122.)

Insert the following new definition between 1.4.128aa “50GBASE-CR” and 1.4.128ab “50GBASE-FR” as inserted by IEEE Std 802.3cd-2018:

1.4.128aa1 50GBASE-ER: IEEE 802.3 Physical Layer specification for 50 Gb/s serial transmission using 50GBASE-R encoding and 4-level pulse amplitude modulation over one wavelength on single-mode fiber, with reach up to at least 40 km. (See IEEE Std 802.3, Clause 139.)

30. Management

30.5 Layer management for medium attachment units (MAUs)

30.5.1 MAU managed object class

30.5.1.1 MAU attributes

30.5.1.1.2 aMAUType

APPROPRIATE SYNTAX:

Insert the following new PHY type into the “APPROPRIATE SYNTAX” section of 30.5.1.1.2 after 50GBASE-LR (as inserted by IEEE Std 802.3cd-2018):

50GBASE-ER	50GBASE-R PCS/PMA over single-mode fiber PMD with reach up to at least 40 km as specified in Clause 139
------------	--

Insert the following new PHY type into the “APPROPRIATE SYNTAX” section of 30.5.1.1.2 after 200GBASE-LR4:

200GBASE-ER4	200GBASE-R PCS/PMA over 4 WDM lane single-mode fiber PMD with reach up to at least 40 km as specified in Clause 122
--------------	--

Insert the following new PHY type into the “APPROPRIATE SYNTAX” section of 30.5.1.1.2 after 400GBASE-LR8:

400GBASE-ER8	400GBASE-R PCS/PMA over 8 WDM lane single-mode fiber PMD with reach up to at least 40 km as specified in Clause 122
--------------	--

45. Management Data Input/Output (MDIO) Interface

45.2 MDIO Interface Registers

45.2.1 PMA/PMD registers

Change Table 45–3 (as modified by IEEE Std 802.3cd-2018) as follows (unchanged rows not shown):

Table 45–3—PMA/PMD registers

Register address	Register name	Subclause
...		
1.26	40G/100G PMA/PMD extended ability 2 Reserved	<u>45.2.1.21b</u>
...		

45.2.1.6 PMA/PMD control 2 register (Register 1.7)

Change Table 45–7 (as modified by IEEE Std 802.3cd-2018) as follows (unchanged rows and bit description lines not shown):

Table 45–7—PMA/PMD control 2 register bit definitions

Bit(s)	Name	Description	R/W ^a
...			
1.7.6:0	PMA/PMD type selection	6 5 4 3 2 1 0 1 1 x x x x = reserved 1 1 1 x x x = reserved 1 1 0 1 x x = reserved 1 1 0 0 1 x = reserved 1 1 0 0 0 1 = 400GBASE-ER8 PMA/PMD 1 1 0 0 0 1 0 = reserved 1 1 0 0 0 0 x = reserved ... 1 0 1 1 0 0 0 = 200GBASE-ER4 PMA/PMD reserved ... 1 0 0 0 1 0 1 = 50GBASE-ER PMA/PMD reserved ...	R/W

^a R/W = Read/Write, RO = Read only

45.2.1.7 PMA/PMD status 2 register (Register 1.8)**45.2.1.7.4 Transmit fault (1.8.11)**

Change Table 45–9 (as modified by IEEE Std 802.3cd-2018) as follows (unchanged rows not shown):

Table 45–9—Transmit fault description location

PMA/PMD	Description location
...	
50GBASE-FR, 50GBASE-LR, <u>50GBASE-ER</u>	139.5.8
...	
200GBASE-FR4, 200GBASE-LR4, <u>200GBASE-ER4</u> , 400GBASE-FR8, 400GBASE-LR8, <u>400GBASE-ER8</u>	122.5.10
...	

45.2.1.7.5 Receive fault (1.8.10)

Change Table 45–10 (as modified by IEEE Std 802.3cd-2018) as follows (unchanged rows not shown):

Table 45–10—Receive fault description location

PMA/PMD	Description location
...	
50GBASE-FR, 50GBASE-LR, <u>50GBASE-ER</u>	139.5.9
...	
200GBASE-FR4, 200GBASE-LR4, <u>200GBASE-ER4</u> , 400GBASE-FR8, 400GBASE-LR8, <u>400GBASE-ER8</u>	122.5.11
...	

45.2.1.8 PMD transmit disable register (Register 1.9)*Change Table 45–12 (as modified by IEEE Std 802.3cd-2018) as follows (unchanged rows not shown):***Table 45–12—Transmit disable description location**

PMA/PMD	Description location
...	
50GBASE-FR 4 and 50GBASE-LR 4 and 50GBASE-ER	139.5.6
...	
200GBASE-FR4, 200GBASE-LR4, 200GBASE-ER4, 400GBASE-FR8, and 400GBASE-LR8, and 400GBASE-ER8	122.5.7
...	

45.2.1.17a 50G PMA/PMD extended ability register (Register 1.20)*Change Table 45–20a (as inserted by IEEE Std 802.3cd-2018) as follows (unchanged rows not shown):***Table 45–20a—50G PMA/PMD extended ability register bit definitions**

Bit(s)	Name	Description	R/W ^a
...			
1.20.14:6 5	Reserved	Value always 0	RO
1.20.5	50GBASE-ER ability	1 = PMA/PMD is able to perform 50GBASE-ER 0 = PMA/PMD is not able to perform 50GBASE-ER	RO
...			

^a RO = Read only*Insert the following new subclause (45.2.1.17a.1a) after 45.2.1.17a.1 (as inserted by IEEE Std 802.3cd-2018):***45.2.1.17a.1a 50GBASE-ER ability (1.20.5)**

When read as a one, bit 1.20.5 indicates that the PMA/PMD is able to operate as a 50GBASE-ER PMA/PMD type. When read as a zero, bit 1.20.5 indicates that the PMA/PMD is not able to operate as a 50GBASE-ER PMA/PMD type.

45.2.1.20 200G PMA/PMD extended ability register (Register 1.23)*Change Table 45–23 as follows (unchanged rows not shown):***Table 45–23—200G PMA/PMD extended ability register bit definitions**

Bit(s)	Name	Description	R/W ^a
...			
1.23.14:7 1.23.6	Reserved <u>200GBASE-ER4 ability</u>	Value always 0 <u>1 = PMA/PMD is able to perform 200GBASE-ER4</u> <u>0 = PMA/PMD is not able to perform 200GBASE-ER4</u>	RO <u>RO</u>
...			
1.23.2:0 1.23.2	Reserved <u>200GBASE-SR4 ability</u>	Value always 0 <u>1 = PMA/PMD is able to perform 200GBASE-SR4</u> <u>0 = PMA/PMD is not able to perform 200GBASE-SR4</u>	RO <u>RO</u>
1.23.1 1.23.1	<u>200GBASE-CR4 ability</u>	<u>1 = PMA/PMD is able to perform 200GBASE-CR4</u> <u>0 = PMA/PMD is not able to perform 200GBASE-CR4</u>	<u>RO</u>
1.23.0 1.23.0	<u>200GBASE-KR4 ability</u>	<u>1 = PMA/PMD is able to perform 200GBASE-KR4</u> <u>0 = PMA/PMD is not able to perform 200GBASE-KR4</u>	<u>RO</u>

^a RO = Read only*Insert the following new subclause (45.2.1.20.1a) after 45.2.1.20.1:***45.2.1.20.1a 200GBASE-ER4 ability (1.23.6)**

When read as a one, bit 1.23.6 indicates that the PMA/PMD is able to operate as a 200GBASE-ER4 PMA/PMD type. When read as a zero, bit 1.23.6 indicates that the PMA/PMD is not able to operate as a 200GBASE-ER4 PMA/PMD type.

*Insert the following new subclauses (45.2.1.20.5, 45.2.1.20.6, and 45.2.1.20.7) after 45.2.1.20.4:***45.2.1.20.5 200GBASE-SR4 ability (1.23.2)**

When read as a one, bit 1.23.2 indicates that the PMA/PMD is able to operate as a 200GBASE-SR4 PMA/PMD type. When read as a zero, bit 1.23.2 indicates that the PMA/PMD is not able to operate as a 200GBASE-SR4 PMA/PMD type.

45.2.1.20.6 200GBASE-CR4 ability (1.23.1)

When read as a one, bit 1.23.1 indicates that the PMA/PMD is able to operate as a 200GBASE-CR4 PMA/PMD type. When read as a zero, bit 1.23.1 indicates that the PMA/PMD is not able to operate as a 200GBASE-CR4 PMA/PMD type.

45.2.1.20.7 200GBASE-KR4 ability (1.23.0)

When read as a one, bit 1.23.0 indicates that the PMA/PMD is able to operate as a 200GBASE-KR4 PMA/PMD type. When read as a zero, bit 1.23.0 indicates that the PMA/PMD is not able to operate as a 200GBASE-KR4 PMA/PMD type.