

---

---

**Telecommunications and exchange  
between information technology  
systems — Requirements for local and  
metropolitan area networks —**

**Part 3:  
Standard for Ethernet**

**AMENDMENT 9: Physical layer  
specifications and management  
parameters for 25 Gb/s and 50 Gb/s  
passive optical networks**

*Télécommunications et échange entre systèmes informatiques —  
Exigences pour les réseaux locaux et métropolitains —*

*Partie 3: Norme pour Ethernet*

*AMENDEMENT 9: Spécifications de couche physique et paramètres de  
gestion pour réseaux optiques passifs à 25 Gb/s et 50 Gb/s*



Reference number  
ISO/IEC/IEEE 8802-3:2021/Amd.9:2021(E)

**Documents**  
© IEEE 2020  
Document Sharing Hub



**COPYRIGHT PROTECTED DOCUMENT**

© IEEE 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from IEEE at the address below.

Institute of Electrical and Electronics Engineers, Inc  
3 Park Avenue, New York  
NY 10016-5997, USA

Email: [stds.ipr@ieee.org](mailto:stds.ipr@ieee.org)  
Website: [www.ieee.org](http://www.ieee.org)

Published in Switzerland

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO/IEC documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives) or [www.iec.ch/members\\_experts/refdocs](http://www.iec.ch/members_experts/refdocs)).

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)) or the IEC list of patent declarations received (see [patents.iec.ch](http://patents.iec.ch)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html). In the IEC, see [www.iec.ch/understanding-standards](http://www.iec.ch/understanding-standards).

ISO/IEC/IEEE 8802-3:2021/Amd 9 was prepared by the LAN/MAN of the IEEE Computer Society (as [IEEE Std 802.3 ca™-2020]) and drafted in accordance with its editorial rules. It was adopted, under the “fast-track procedure” defined in the Partner Standards Development Organization cooperation agreement between ISO and IEEE, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*.

A list of all parts in the ISO/IEC/IEEE 8802 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html) and [www.iec.ch/national-committees](http://www.iec.ch/national-committees).



**IEEE Std 802.3ca™-2020**

(Amendment to IEEE Std 802.3™-2018  
as amended by IEEE Std 802.3cb™-2018,  
IEEE Std 802.3bt™-2018,  
IEEE Std 802.3cd™-2018,  
IEEE Std 802.3cn™-2019,  
IEEE Std 802.3cg™-2019,  
IEEE Std 802.3cq™-2020,  
IEEE Std 802.3cm™-2020,  
and IEEE Std 802.3ch™-2020)

# IEEE Standard for Ethernet

## Amendment 9: Physical Layer Specifications and Management Parameters for 25 Gb/s and 50 Gb/s Passive Optical Networks

Developed by the

**LAN/MAN Standards Committee**  
of the  
**IEEE Computer Society**

Approved 4 June 2020

**IEEE SA Standards Board**

**Abstract:** This amendment to IEEE Std 802.3-2018 extends the operation of Ethernet passive optical networks (EPONs) to multiple channels of 25 Gb/s providing both symmetric and asymmetric operation for the following data rates (downstream/upstream): 25/10 Gb/s, 25/25 Gb/s, 50/10 Gb/s, 50/25 Gb/s, and 50/50 Gb/s. This standard specifies the 25 Gb/s EPON Multi-Channel Reconciliation Sublayer (MCRS), Nx25G-EPON Physical Coding Sublayers (PCSs), Physical Media Attachment (PMA) sublayers, and Physical Medium Dependent (PMD) sublayers that support both symmetric and asymmetric data rates while maintaining backward compatibility with already deployed 10 Gb/s EPON equipment. Backward compatibility with deployed 1G-EPON and ITU-T G.984 GPON is maintained with 25GBASE-PQ for the specific case of 1G-EPON and GPON ONUs using reduced-band (40 nm) lasers. The EPON operation is defined for distances of at least 20 km, and for a split ratio of at least 1:32.

**Keywords:** 25 Gb/s Ethernet passive optical networks (25G-EPON), 50 Gb/s Ethernet passive optical networks (50G-EPON), amendment, forward error correction (FEC), IEEE 802.3™, IEEE 802.3ca™, Multi-Channel Reconciliation Sublayer (MCRS), Multipoint MAC Control (MPMC), Physical Coding Sublayer (PCS), Physical Media Attachment (PMA), Physical Medium Dependent (PMD), PON, Point-to-Multipoint (P2MP)

---

The Institute of Electrical and Electronics Engineers, Inc.  
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2020 by The Institute of Electrical and Electronics Engineers, Inc.  
All rights reserved. Published 3 July 2020. Printed in the United States of America.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-1-5044-6768-1 STD24221  
Print: ISBN 978-1-5044-6769-8 STDPD24221

*IEEE prohibits discrimination, harassment and bullying.*

*For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.*

*No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.*

## Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading “Important Notices and Disclaimers Concerning IEEE Standards Documents.” They can also be obtained on request from IEEE or viewed at <https://standards.ieee.org/ipr/disclaimers.html>.

### Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents (standards, recommended practices, and guides), both full-use and trial-use, are developed within IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (“IEEE SA”) Standards Board. IEEE (“the Institute”) develops its standards through a consensus development process, approved by the American National Standards Institute (“ANSI”), which brings together volunteers representing varied viewpoints and interests to achieve the final product. IEEE Standards are documents developed through scientific, academic, and industry-based technical working groups. Volunteers in IEEE working groups are not necessarily members of the Institute and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers and users of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims all warranties (express, implied and statutory) not included in this or any other document relating to the standard, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, IEEE disclaims any and all conditions relating to: results; and workmanlike effort. IEEE standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

### Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

## Official statements

A statement, written or oral, that is not processed in accordance with the IEEE SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, or be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

## Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in revisions to an IEEE standard is welcome to join the relevant IEEE working group.

Comments on standards should be submitted to the following address:

Secretary, IEEE SA Standards Board  
445 Hoes Lane  
Piscataway, NJ 08854 USA

## Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

## Copyrights

IEEE draft and approved standards are copyrighted by IEEE under U.S. and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

## Photocopies

Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

## Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. A current IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE SA Website at <https://ieeexplore.ieee.org> or contact IEEE at the address listed previously. For more information about the IEEE SA or IEEE's standards development process, visit the IEEE SA Website at <https://standards.ieee.org>.

## Errata

Errata, if any, for all IEEE standards can be accessed on the IEEE SA Website at the following URL: <https://standards.ieee.org/findstds/errata/index.html>. Users are encouraged to check this URL for errata periodically.

## Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE SA Website at <https://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

## Participants

The following individuals were officers and members of the IEEE 802.3 Working Group at the beginning of the IEEE P802.3ca Working Group ballot.

**David J. Law**, *IEEE 802.3 Working Group Chair*  
**Adam Healey**, *IEEE 802.3 Working Group Vice-Chair*  
**Pete Anslow**, *IEEE 802.3 Working Group Secretary, Phase 1*  
**Jon Lewis**, *IEEE 802.3 Working Group Secretary, Phase 2*  
**Steven B. Carlson**, *IEEE 802.3 Working Group Executive Secretary*  
**Valerie Maguire**, *IEEE 802.3 Working Group Treasurer*

**Curtis Knittle**, *IEEE P802.3ca Nx25G-EPON Task Force Chair*  
**Glen Kramer**, *IEEE P802.3ca Nx25G-EPON Task Force Vice-Chair*  
**Marek Hajduczenia**, *IEEE P802.3ca Nx25G-EPON Task Force Editor-in-Chief*

|                      |                       |                         |
|----------------------|-----------------------|-------------------------|
| John Abbott          | Liang Du              | Yasuaki Kawatsu         |
| David Abramson       | Kathryn Dube          | Yong Kim                |
| Andrea Agnes         | Mike Dudek            | Mark Kimber             |
| Dale Amason          | Marc Dupuis           | Jonathan King           |
| Hongming An          | Frank Effenberger     | Michael Klempa          |
| Jes Asmussen         | David Estes           | Elizabeth Kochuparambil |
| Richard Baca         | John Ewen             | Wojciech Koczwar        |
| Tim Baggett          | Borhan Fathi Moghadam | Paul Kolesar            |
| Amrik Bains          | Vincent Ferretti      | Taiji Kondo             |
| Thananya Baldwin     | Brian Franchuk        | Olaf Krieger            |
| Steven Baumgartner   | Matthias Fritsche     | Hans Lackner            |
| Denis Beaudoin       | Richard Frosch        | Jeffrey Lapak           |
| Liav Ben-Artzi       | Shiyong Fu            | Mark Laubach            |
| Piergiorgio Beruto   | Mike Gardner          | Han Hyub Lee            |
| Vipul Bhatt          | Claude Gauthier       | June Hee Lee            |
| Gao Bo               | Ali Ghiasi            | Alex Levin              |
| Martin Bouda         | Joel Goergen          | Jon Lewis               |
| David Brandt         | Zhigang Gong          | David Li                |
| Ralf-Peter Braun     | Steven Gorshe         | Mike-Peng Li            |
| Paul Brooks          | Jens Gottron          | Jane Lim                |
| Alan Brown           | Steffen Graber        | Alex Lin                |
| Matthew Brown        | Olaf Grau             | Dekun Liu               |
| Michal Brychta       | Robert Grow           | Hai-Feng Liu            |
| Gary Burrell         | Mark Gustlin          | Karen Liu               |
| Jairo Bustos Heredia | Hayden Haynes         | Zhenyu Liu              |
| Adrian Butter        | Xiang He              | William Lo              |
| John Calvin          | Howard Heck           | Yuchun Lu               |
| Clark Carty          | Brian Holden          | Miklos Lukacs           |
| Craig Chabot         | Rita Horner           | Kent Lusted             |
| David Chalupsky      | Bernd Hormmeyer       | Ilya Lyubomirsky        |
| Frank Chang          | Gergely Huszak        | Jeffery Maki            |
| Xin Chang            | Yasuhiro Hyakutake    | David Malicoat          |
| Golam Choudhury      | Jonathan Ingham       | Flavio Marques          |
| Keng Hua Chuang      | Kazuhiko Ishibe       | Arthur Marris           |
| Kamal Dalmia         | Hideki Isono          | Chris Mash              |
| John D'Ambrosia      | Tom Issenhuth         | Takeo Masuda            |
| Piers Dawe           | Kenneth Jackson       | Kirsten Matheus         |
| Fred Dawson          | Andrew Jimenez        | Erdem Matoglu           |
| John Deandrea        | John Johnson          | Marco Mazzini           |
| Gerrit den Besten    | Chad Jones            | Mick McCarthy           |
| Claudio DeSanti      | Peter Jones           | Brett McClellan         |
| Chris Diminico       | Lokesh Kabra          | Larry McMillan          |
| Hormoz Djahanshahi   | Manabu Kagami         | Greg McSorley           |
| Curtis Donahue       | Upen Kareti           | Richard Mellitz         |

|                    |                    |                      |
|--------------------|--------------------|----------------------|
| Martin Miller      | Sam Sambasivan     | Ricky Vernickel      |
| Toshiyuki Moritake | Edward Sayre       | Marco Vitali         |
| Thomas Mueller     | James Schuessler   | Robert Voss          |
| Edward Nakamoto    | Steve Sekel        | Dylan Walker         |
| Paul Neveux        | Masood Shariff     | Haifei Wang          |
| Gary Nicholl       | Mizuki Shirao      | Roy Wang             |
| Shawn Nicholl      | Jialong Shuai      | Tongtong Wang        |
| John Nolan         | Jeff Slavick       | Xinyuan Wang         |
| Kevin Noll         | Daniel Smith       | Xuehuan Wang         |
| Mark Nowell        | Scott Sommers      | Christoph Wechsler   |
| David Ofelt        | Tom Souvignier     | Brian Welch          |
| Josef Ohni         | Bryan Sparrowhawk  | Matthias Wendt       |
| Tom Palkert        | Edward Sprague     | Natalie Wienckowski  |
| Sujan Pandey       | Peter Stassar      | James Withey         |
| Carlos Pardo       | Heath Stewart      | Mau-Lin Wu           |
| Earl Parsons       | David Stover       | Peter Wu             |
| Gerald Pepper      | Junqing Sun        | Markus Wucher        |
| Phong Pham         | Liyang Sun         | Dayin Xu             |
| David Piehler      | Steve Swanson      | Yu Xu                |
| Rick Pimpinella    | Bharat Tailor      | Shuto Yamamoto       |
| Christopher Pohl   | Tomoo Takahara     | Adrian Young         |
| William Powell     | Kohichi Tamura     | James Young          |
| Dino Pozzebon      | Mehmet Tazebay     | Lennart Yseboodt     |
| Rick Rabinovich    | Ronald Tellas      | Andrew Zambell       |
| Zvi Rechtman       | Geoffrey Thompson  | Conrad Zema          |
| Alon Regev         | Pirooz Tooyserkani | Richard (Yujia) Zhou |
| Duane Remein       | Nathan Tracy       | Yan Zhuang           |
| Victor Renteria    | David Tremblay     | Martin Zielinski     |
| Salvatore Rotolo   | Stephen Trowbridge | George Zimmerman     |
| Alexander Rysin    | Ta Chin Tseng      | Pavel Zivny          |
| Toshiaki Sakai     | Ed Ulrichs         | Harald Zweck         |
| Hamid Salehi       | Alexander Umnov    |                      |

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

|                       |                    |                     |
|-----------------------|--------------------|---------------------|
| Thomas Alexander      | Werner Hoelzl      | Satoshi Obara       |
| Nancy Bravin          | Yasuhiro Hyakutake | Thomas Palkert      |
| Matthew Brown         | Raj Jain           | Carlos Pardo        |
| Demetrio Bucaneg, Jr. | SangKwon Jeong     | Bansi Patel         |
| Jairo Bustos Heredia  | Lokesh Kabra       | Dev Paul            |
| William Byrd          | Stuart Kerry       | Arumugam Paventhan  |
| Steven B. Carlson     | Yongbum Kim        | David Piehler       |
| Juan Carreon          | Curtis Knittle     | William Powell      |
| Clark Carty           | Glen Kramer        | R. K. Rannow        |
| Pin Chang             | Mark Laubach       | Maximilian Riegel   |
| Xin Chang             | David J. Law       | Robert Robinson     |
| Chan Chen             | Pi-Cheng Law       | Benjamin Rolfe      |
| Joseph Coffey         | Han Hyub Lee       | Dieter Schicketanz  |
| Charles Cook          | Hyeong Ho Lee      | Thomas Starai       |
| John Deandrea         | David Lewis        | Mitsutoshi Sugawara |
| Claudio DeSanti       | Jon Lewis          | Ronald Tellas       |
| Vincent Ferretti      | Karen Liu          | Geoffrey Thompson   |
| Avraham Freedman      | Javier Luiso       | David Tremblay      |
| Matthias Fritsche     | Valerie Maguire    | Mark-Rene Uchida    |
| Joel Goergen          | Jeffery Maki       | Dmitri Varsanofiev  |
| Zhigang Gong          | David Malicoat     | George Vlantis      |
| Randall Groves        | Brett McClellan    | Lisa Ward           |
| Martin Gubow          | Richard Mellitz    | Karl Weber          |
| Marek Hajduczenia     | Tremont Miao       | Andreas Wolf        |
| Adam Healey           | Raymond Nering     | Yu Yuan             |
| Marco Hernandez       | Paul Neveux        | Oren Yuen           |
| David Hess            | Paul Nikolich      | Zhen Zhou           |
|                       |                    | Pavel Zivny         |

When the IEEE SA Standards Board approved this standard on 4 June 2020, it had the following membership:

**Gary Hoffman**, *Chair*  
**Jon Walter Rosdahl**, *Vice Chair*  
**Jean-Philippe Faure**, *Past Chair*  
**Konstantinos Karachalios**, *Secretary*

Ted Burse  
J. Travis Griffith  
Grace Gu  
Guido R. Hiertz  
Joseph L. Koepfinger\*  
John D. Kulick

David J. Law  
Howard Li  
Dong Liu  
Kevin Lu  
Paul Nikolich  
Damir Novosel  
Dorothy Stanley

Mehmet Ulema  
Lei Wang  
Sha Wei  
Philip B. Winston  
Daidi Zhong  
Jingyi Zhou

\*Member Emeritus

## Introduction

This introduction is not part of IEEE Std 802.3ca-2020, IEEE Standard for Ethernet. Amendment 9: Physical Layer Specifications and Management Parameters for 25 Gb/s and 50 Gb/s Passive Optical Networks.

IEEE Std 802.3™ was first published in 1985. Since the initial publication, many projects have added functionality or provided maintenance updates to the specifications and text included in the standard. Each IEEE 802.3 project/amendment is identified with a suffix (e.g., IEEE Std 802.3ba™-2010).

The half duplex Media Access Control (MAC) protocol specified in IEEE Std 802.3-1985 is Carrier Sense Multiple Access with Collision Detection (CSMA/CD). This MAC protocol was key to the experimental Ethernet developed at Xerox Palo Alto Research Center, which had a 2.94 Mb/s data rate. Ethernet at 10 Mb/s was jointly released as a public specification by Digital Equipment Corporation (DEC), Intel and Xerox in 1980. Ethernet at 10 Mb/s was approved as an IEEE standard by the IEEE Standards Board in 1983 and subsequently published in 1985 as IEEE Std 802.3-1985. Since 1985, new media options, new speeds of operation, and new capabilities have been added to IEEE Std 802.3. A full duplex MAC protocol was added in 1997.

Some of the major additions to IEEE Std 802.3 are identified in the marketplace with their project number. This is most common for projects adding higher speeds of operation or new protocols. For example, IEEE Std 802.3u™ added 100 Mb/s operation (also called Fast Ethernet), IEEE Std 802.3z added 1000 Mb/s operation (also called Gigabit Ethernet), IEEE Std 802.3ae added 10 Gb/s operation (also called 10 Gigabit Ethernet), IEEE Std 802.3ah™ specified access network Ethernet (also called Ethernet in the First Mile) and IEEE Std 802.3ba added 40 Gb/s operation (also called 40 Gigabit Ethernet) and 100 Gb/s operation (also called 100 Gigabit Ethernet). These major additions are all now included in and are superseded by IEEE Std 802.3-2018 and are not maintained as separate documents.

At the date of IEEE Std 802.3ca-2020 publication, IEEE Std 802.3 was composed of the following documents:

### IEEE Std 802.3-2018

Section One—Includes Clause 1 through Clause 20 and Annex A through Annex H and Annex 4A. Section One includes the specifications for 10 Mb/s operation and the MAC, frame formats and service interfaces used for all speeds of operation.

Section Two—Includes Clause 21 through Clause 33 and Annex 22A through Annex 33E. Section Two includes management attributes for multiple protocols and speed of operation as well as specifications for providing power over twisted pair cabling for multiple operational speeds. It also includes general information on 100 Mb/s operation as well as most of the 100 Mb/s Physical Layer specifications.

Section Three—Includes Clause 34 through Clause 43 and Annex 36A through Annex 43C. Section Three includes general information on 1000 Mb/s operation as well as most of the 1000 Mb/s Physical Layer specifications.

Section Four—Includes Clause 44 through Clause 55 and Annex 44A through Annex 55B. Section Four includes general information on 10 Gb/s operation as well as most of the 10 Gb/s Physical Layer specifications.

Section Five—Includes Clause 56 through Clause 77 and Annex 57A through Annex 76A. Clause 56 through Clause 67 and Clause 75 through Clause 77, as well as associated annexes, specify subscriber access and other Physical Layers and sublayers for operation from 512 kb/s to 10 Gb/s, and defines

services and protocol elements that enable the exchange of IEEE Std 802.3 format frames between stations in a subscriber access network. Clause 68 specifies a 10 Gb/s Physical Layer specification. Clause 69 through Clause 74 and associated annexes specify Ethernet operation over electrical backplanes at speeds of 1000 Mb/s and 10 Gb/s.

Section Six—Includes Clause 78 through Clause 95 and Annex 83A through Annex 93C. Clause 78 specifies Energy-Efficient Ethernet. Clause 79 specifies IEEE 802.3 Organizationally Specific Link Layer Discovery Protocol (LLDP) type, length, and value (TLV) information elements. Clause 80 through Clause 95 and associated annexes include general information on 40 Gb/s and 100 Gb/s operation as well the 40 Gb/s and 100 Gb/s Physical Layer specifications. Clause 90 specifies Ethernet support for time synchronization protocols.

Section Seven—Includes Clause 96 through Clause 115 and Annex 97A through Annex 115A. Clause 96 through Clause 98, Clause 104, and associated annexes, specify Physical Layers and optional features for 100 Mb/s and 1000 Mb/s operation over a single twisted pair. Clause 100 through Clause 103, as well as associated annexes, specify Physical Layers for the operation of the EPON protocol over coaxial distribution networks. Clause 105 through Clause 114 and associated annexes include general information on 25 Gb/s operation as well as 25 Gb/s Physical Layer specifications. Clause 99 specifies a MAC merge sublayer for the interspersing of express traffic. Clause 115 and its associated annex specify a Physical Layer for 1000 Mb/s operation over plastic optical fiber.

Section Eight—Includes Clause 116 through Clause 126 and Annex 119A through Annex 120E. Clause 116 through Clause 124 and associated annexes include general information on 200 Gb/s and 400 Gb/s operation as well the 200 Gb/s and 400 Gb/s Physical Layer specifications. Clause 125 and Clause 126 include general information on 2.5 Gb/s and 5 Gb/s operation as well as 2.5 Gb/s and 5 Gb/s Physical Layer specifications.

### IEEE Std 802.3cb™-2018

Amendment 1—This amendment includes changes to IEEE Std 802.3-2018 and its amendments, and adds Clause 127 through Clause 130, Annex 127A, Annex 128A, Annex 128B, and Annex 130A. This amendment adds new Physical Layers for operation at 2.5 Gb/s and 5 Gb/s over electrical backplanes.

### IEEE Std 802.3bt™-2018

Amendment 2—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 145, Annex 145A, Annex 145B, and Annex 145C. This amendment adds power delivery using all four pairs in the structured wiring plant, resulting in greater power being available to end devices. This amendment also allows for lower standby power consumption in end devices and adds a mechanism to better manage the available power budget.

### IEEE Std 802.3cd™-2018

Amendment 3—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 131 through Clause 140 and Annex 135A through Annex 136D. This amendment adds MAC parameters, Physical Layers, and management parameters for the transfer of IEEE 802.3 format frames at 50 Gb/s, 100 Gb/s, and 200 Gb/s.

### IEEE Std 802.3cn™-2019

Amendment 4—This amendment includes changes to IEEE Std 802.3-2018 and adds 50 Gb/s, 200 Gb/s, and 400 Gb/s Physical Layer specifications and management parameters for operation over single-mode fiber with reaches of at least 40 km.

## IEEE Std 802.3cg™-2019

Amendment 5—This amendment includes changes to IEEE Std 802.3-2018 and its amendments and adds Clause 146 through Clause 148 and Annex 146A and Annex 146B. This amendment adds 10 Mb/s Physical Layer specifications and management parameters for operation on a single balanced pair of conductors.

## IEEE Std 802.3cq™-2020

Amendment 6—This amendment includes editorial and technical corrections, refinements, and clarifications to Clause 33 and related portions of the standard.

## IEEE Std 802.3cm™-2020

Amendment 7—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 150. This amendment adds Physical Layer (PHY) specifications and management parameters for 400 Gb/s operation on four pairs (400GBASE-SR4.2) and eight pairs (400GBASE-SR8) of multimode fiber, over reaches of at least 100 m.

## IEEE Std 802.3ch™-2020

Amendment 8—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 149, Annex 149A, Annex 149B, and Annex 149C. This amendment adds physical layer specifications and management parameters for operation at 2.5 Gb/s, 5 Gb/s, and 10 Gb/s over a single balanced pair of conductors.

## IEEE Std 802.3ca™-2020

Amendment 9—This amendment to IEEE Std 802.3-2018 extends the operation of Ethernet passive optical networks (EPONs) to multiple channels of 25 Gb/s providing both symmetric and asymmetric operation for the following data rates (downstream/upstream): 25/10 Gb/s, 25/25 Gb/s, 50/10 Gb/s, 50/25 Gb/s, and 50/50 Gb/s. This amendment specifies the 25 Gb/s EPON Multi-Channel Reconciliation Sublayer (MCRS), Nx25G-EPON Physical Coding Sublayers (PCSs), Physical Media Attachment (PMA) sublayers, and Physical Medium Dependent (PMD) sublayers that support both symmetric and asymmetric data rates while maintaining backward compatibility with already deployed 10 Gb/s EPON equipment. The EPON operation is defined for distances of at least 20 km, and for a split ratio of at least 1:32.

Two companion documents exist, IEEE Std 802.3.1 and IEEE Std 802.3.2. IEEE Std 802.3.1 describes Ethernet management information base (MIB) modules for use with the Simple Network Management Protocol (SNMP). IEEE Std 802.3.2 describes YANG data models for Ethernet. IEEE Std 802.3.1 and IEEE Std 802.3.2 are updated to add management capability for enhancements to IEEE Std 802.3 after approval of those enhancements.

IEEE Std 802.3 will continue to evolve. New Ethernet capabilities are anticipated to be added within the next few years as amendments to this standard.

## Contents

|                                                                                                 |    |
|-------------------------------------------------------------------------------------------------|----|
| 1. Introduction.....                                                                            | 23 |
| 1.3 Normative references.....                                                                   | 23 |
| 1.4 Definitions .....                                                                           | 23 |
| 1.5 Abbreviations.....                                                                          | 25 |
| 30. Management.....                                                                             | 26 |
| 30.3 Layer management for DTEs.....                                                             | 26 |
| 30.3.2 PHY device managed object class .....                                                    | 26 |
| 30.3.2.1 PHY device attributes.....                                                             | 26 |
| 30.3.2.1.2 aPhyType .....                                                                       | 26 |
| 30.3.2.1.3 aPhyTypeList .....                                                                   | 26 |
| 30.3.5 MPCP managed object class .....                                                          | 27 |
| 30.3.5.1 MPCP Attributes.....                                                                   | 27 |
| 30.3.5.1.2 aMPCPAdminState .....                                                                | 27 |
| 30.3.5.1.3 aMPCPMode.....                                                                       | 27 |
| 30.3.5.1.4 aMPCPLinkID .....                                                                    | 27 |
| 30.5 Layer management for medium attachment units (MAUs).....                                   | 27 |
| 30.5.1 MAU managed object class.....                                                            | 27 |
| 30.5.1.1 MAU attributes .....                                                                   | 27 |
| 30.5.1.1.2 aMAUType .....                                                                       | 27 |
| 45. Management Data Input/Output (MDIO) Interface.....                                          | 31 |
| 45.2 MDIO Interface Registers.....                                                              | 31 |
| 45.2.1 PMA/PMD registers.....                                                                   | 31 |
| 45.2.1.23a PMA/PMD control 3 register (Register 1.29) .....                                     | 31 |
| 45.2.1.23a.1 Downstream differential encoding (1.29.15).....                                    | 31 |
| 45.2.1.23a.2 PMA/PMD type selection (1.29.5:0) .....                                            | 31 |
| 45.2.1.134a Nx25G-EPON PMA/PMD extended ability register (Registers 1.1000 through 1.1002)..... | 33 |
| 45.2.1.134a.1 25GBASE-PQX-U3 (1.1000.15) .....                                                  | 35 |
| 45.2.1.134a.2 25GBASE-PQX-U2 (1.1000.14) .....                                                  | 35 |
| 45.2.1.134a.3 25GBASE-PQX-D3 (1.1000.13) .....                                                  | 35 |
| 45.2.1.134a.4 25GBASE-PQX-D2 (1.1000.12) .....                                                  | 35 |
| 45.2.1.134a.5 25GBASE-PQG-U3 (1.1000.11) .....                                                  | 35 |
| 45.2.1.134a.6 25GBASE-PQG-U2 (1.1000.10) .....                                                  | 35 |
| 45.2.1.134a.7 25GBASE-PQG-D3 (1.1000.9) .....                                                   | 36 |
| 45.2.1.134a.8 25GBASE-PQG-D2 (1.1000.8) .....                                                   | 36 |
| 45.2.1.134a.9 25/10GBASE-PQX-U3 (1.1000.7) .....                                                | 36 |
| 45.2.1.134a.10 25/10GBASE-PQX-U2 (1.1000.6) .....                                               | 36 |
| 45.2.1.134a.11 25/10GBASE-PQX-D3 (1.1000.5) .....                                               | 36 |
| 45.2.1.134a.12 25/10GBASE-PQX-D2 (1.1000.4) .....                                               | 36 |
| 45.2.1.134a.13 25/10GBASE-PQG-U3 (1.1000.3) .....                                               | 36 |
| 45.2.1.134a.14 25/10GBASE-PQG-U2 (1.1000.2) .....                                               | 36 |
| 45.2.1.134a.15 25/10GBASE-PQG-D3 (1.1000.1) .....                                               | 36 |
| 45.2.1.134a.16 25/10GBASE-PQG-D2 (1.1000.0) .....                                               | 37 |
| 45.2.1.134a.17 50/25GBASE-PQX-U3 (1.1001.15) .....                                              | 37 |
| 45.2.1.134a.18 50/25GBASE-PQX-U2 (1.1001.14) .....                                              | 37 |
| 45.2.1.134a.19 50/25GBASE-PQX-D3 (1.1001.13) .....                                              | 37 |

|                |                                                                                                                      |    |
|----------------|----------------------------------------------------------------------------------------------------------------------|----|
| 45.2.1.134a.20 | 50/25GBASE-PQX-D2 (1.1001.12) .....                                                                                  | 37 |
| 45.2.1.134a.21 | 50/25GBASE-PQG-U3 (1.1001.11) .....                                                                                  | 37 |
| 45.2.1.134a.22 | 50/25GBASE-PQG-U2 (1.1001.10) .....                                                                                  | 37 |
| 45.2.1.134a.23 | 50/25GBASE-PQG-D3 (1.1001.9) .....                                                                                   | 37 |
| 45.2.1.134a.24 | 50/25GBASE-PQG-D2 (1.1001.8) .....                                                                                   | 37 |
| 45.2.1.134a.25 | 50/10GBASE-PQX-U3 (1.1001.7) .....                                                                                   | 38 |
| 45.2.1.134a.26 | 50/10GBASE-PQX-U2 (1.1001.6) .....                                                                                   | 38 |
| 45.2.1.134a.27 | 50/10GBASE-PQX-D3 (1.1001.5) .....                                                                                   | 38 |
| 45.2.1.134a.28 | 50/10GBASE-PQX-D2 (1.1001.4) .....                                                                                   | 38 |
| 45.2.1.134a.29 | 50/10GBASE-PQG-U3 (1.1001.3) .....                                                                                   | 38 |
| 45.2.1.134a.30 | 50/10GBASE-PQG-U2 (1.1001.2) .....                                                                                   | 38 |
| 45.2.1.134a.31 | 50/10GBASE-PQG-D3 (1.1001.1) .....                                                                                   | 38 |
| 45.2.1.134a.32 | 50/10GBASE-PQG-D2 (1.1001.0) .....                                                                                   | 38 |
| 45.2.1.134a.33 | 50GBASE-PQX-U3 (1.1002.7) .....                                                                                      | 38 |
| 45.2.1.134a.34 | 50GBASE-PQX-U2 (1.1002.6) .....                                                                                      | 39 |
| 45.2.1.134a.35 | 50GBASE-PQX-D3 (1.1002.5) .....                                                                                      | 39 |
| 45.2.1.134a.36 | 50GBASE-PQX-D2 (1.1002.4) .....                                                                                      | 39 |
| 45.2.1.134a.37 | 50GBASE-PQG-U3 (1.1002.3) .....                                                                                      | 39 |
| 45.2.1.134a.38 | 50GBASE-PQG-U2 (1.1002.2) .....                                                                                      | 39 |
| 45.2.1.134a.39 | 50GBASE-PQG-D3 (1.1002.1) .....                                                                                      | 39 |
| 45.2.1.134a.40 | 50GBASE-PQG-D2 (1.1002.0) .....                                                                                      | 39 |
| 45.2.3         | PCS registers .....                                                                                                  | 40 |
| 45.2.3.1       | PCS control 1 register (Register 3.0) .....                                                                          | 40 |
| 45.2.3.6       | PCS control 2 register (Register 3.7) .....                                                                          | 41 |
| 45.2.3.6.1     | PCS type selection (3.7.34:0) .....                                                                                  | 41 |
| 45.2.3.8       | PCS status 3 register (Register 3.9) .....                                                                           | 41 |
| 45.2.3.8.aa    | 25GBASE-PQ capable (3.9.7) .....                                                                                     | 42 |
| 45.2.3.8.ab    | 25/10GBASE-PQ capable (3.9.6) .....                                                                                  | 42 |
| 45.2.3.8.ac    | 25GBASE-PQ Rx only capable (3.9.5) .....                                                                             | 42 |
| 45.2.3.8.ad    | 25GBASE-PQ Tx only capable (3.9.4) .....                                                                             | 42 |
| 45.2.3.41      | 10/1GBASE-PRX and 10GBASE-PR10G-EPON and Nx25G-EPON corrected<br>FEC codewords counter (Register 3.76, 3.77) .....   | 42 |
| 45.2.3.42      | 10/1GBASE-PRX and 10GBASE-PR10G-EPON and Nx25G-EPON<br>uncorrected FEC codewords counter (Register 3.78, 3.79) ..... | 43 |
| 45.2.3.43      | 10GBASE-PR and, 10/1GBASE-PRX, and Nx25G-EPON BER monitor<br>interval timer control register (Register 3.80) .....   | 43 |
| 45.2.3.44      | 10GBASE-PR and, 10/1GBASE-PRX, and Nx25G-EPON BER monitor status<br>(Register 3.81) .....                            | 44 |
| 45.2.3.44.1    | 10GBASE-PR and, 10/1GBASE-PRX, and Nx25G-EPON PCS high<br>BER (3.81.0) .....                                         | 44 |
| 45.2.3.44.2    | 10GBASE-PR and, 10/1GBASE-PRX, and Nx25G-EPON PCS latched<br>high BER (3.81.1) .....                                 | 45 |
| 45.2.3.45      | 10GBASE-PR and, 10/1GBASE-PRX, and Nx25G-EPON BER monitor<br>threshold control (Register 3.82) .....                 | 45 |
| 45.2.3.45a     | Nx25G-EPON synchronization pattern registers (Registers 3.83 through<br>3.134) .....                                 | 45 |
| 45.2.3.45a.1   | SP3 bit 257 (3.83.5) .....                                                                                           | 46 |
| 45.2.3.45a.2   | SP3 balanced (3.83.4) .....                                                                                          | 46 |
| 45.2.3.45a.3   | SP2 bit 257 (3.83.3) .....                                                                                           | 46 |
| 45.2.3.45a.4   | SP2 balanced (3.83.2) .....                                                                                          | 46 |
| 45.2.3.45a.5   | SP1 bit 257 (3.83.1) .....                                                                                           | 47 |
| 45.2.3.45a.6   | SP1 balanced (3.83.0) .....                                                                                          | 47 |
| 45.2.3.45a.7   | SP1 pattern (3.84.0 through 3.99.15) .....                                                                           | 47 |
| 45.2.3.45a.8   | SP1 length (3.100.15:0) .....                                                                                        | 47 |

|               |                                                                                                                                     |    |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------|----|
| 45.2.3.45a.9  | SP2 pattern (3.101.0 through 3.116.15) .....                                                                                        | 47 |
| 45.2.3.45a.10 | SP2 length (3.117.15:0) .....                                                                                                       | 47 |
| 45.2.3.45a.11 | SP3 pattern (3.118.0 through 3.133.15) .....                                                                                        | 47 |
| 45.2.3.45a.12 | SP3 length (3.134.15:0) .....                                                                                                       | 47 |
| 45.5          | Protocol implementation conformance statement (PICS) proforma for Clause 45,<br>Management Data Input/Output (MDIO) interface ..... | 48 |
| 45.5.1        | Introduction .....                                                                                                                  | 48 |
| 45.5.2        | Identification .....                                                                                                                | 48 |
| 45.5.2.1      | Implementation identification .....                                                                                                 | 48 |
| 45.5.2.2      | Protocol summary .....                                                                                                              | 48 |
| 45.5.3        | PICS proforma tables for the Management Data Input Output (MDIO) interface .....                                                    | 49 |
| 45.5.3.3      | PMA/PMD management functions .....                                                                                                  | 49 |
| 45.5.3.7      | PCS management functions .....                                                                                                      | 49 |
| 56.           | Introduction to Ethernet for subscriber access networks .....                                                                       | 50 |
| 56.1          | Overview .....                                                                                                                      | 50 |
| 56.1.2        | Summary of P2MP sublayers .....                                                                                                     | 50 |
| 56.1.2.1      | Multipoint MAC Control Protocol (MPCP) .....                                                                                        | 52 |
| 56.1.2.2      | Reconciliation Sublayer (RS) and media independent interfaces .....                                                                 | 52 |
| 56.1.3        | Physical Layer signaling systems .....                                                                                              | 52 |
| 67.           | System considerations for Ethernet subscriber access networks .....                                                                 | 59 |
| 67.1          | Overview .....                                                                                                                      | 59 |
| 141.          | Physical Medium Dependent (PMD) sublayer and medium for Nx25G-EPON passive optical<br>networks .....                                | 61 |
| 141.1         | Overview .....                                                                                                                      | 61 |
| 141.1.1       | Terminology .....                                                                                                                   | 61 |
| 141.1.2       | Positioning of the PMD sublayer within the IEEE 802.3 architecture .....                                                            | 61 |
| 141.1.3       | PHY link types .....                                                                                                                | 61 |
| 141.2         | PMD nomenclature .....                                                                                                              | 64 |
| 141.2.1       | Introduction .....                                                                                                                  | 64 |
| 141.2.2       | PMD rate classes .....                                                                                                              | 64 |
| 141.2.3       | PMD coexistence classes .....                                                                                                       | 64 |
| 141.2.4       | PMD transmission direction classes .....                                                                                            | 64 |
| 141.2.5       | PMD power classes .....                                                                                                             | 64 |
| 141.2.6       | PMD naming .....                                                                                                                    | 65 |
| 141.2.7       | Supported combinations of OLT and ONU PMDs .....                                                                                    | 65 |
| 141.2.7.1     | PHY Links supporting medium power budget .....                                                                                      | 66 |
| 141.2.7.2     | PHY Links supporting high power budget .....                                                                                        | 67 |
| 141.3         | PMD functional specifications .....                                                                                                 | 67 |
| 141.3.1       | PMD service interface .....                                                                                                         | 67 |
| 141.3.1.1     | Channel-to-wavelength mapping .....                                                                                                 | 67 |
| 141.3.1.2     | Delay constraints .....                                                                                                             | 68 |
| 141.3.1.3     | PMD_UNITDATA[i].request .....                                                                                                       | 68 |
| 141.3.1.4     | PMD_UNITDATA[i].indication .....                                                                                                    | 68 |
| 141.3.1.5     | PMD_SIGNAL[i].request .....                                                                                                         | 69 |
| 141.3.1.6     | PMD_SIGNAL[i].indication .....                                                                                                      | 69 |
| 141.3.2       | PMD block diagram .....                                                                                                             | 69 |
| 141.3.3       | PMD transmit function .....                                                                                                         | 70 |
| 141.3.4       | PMD receive function .....                                                                                                          | 70 |

|            |                                                                                                                                                                                       |    |
|------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| 141.3.5    | PMD signal detect function.....                                                                                                                                                       | 70 |
| 141.3.5.1  | ONU PMD signal detect.....                                                                                                                                                            | 70 |
| 141.3.5.2  | OLT PMD signal detect.....                                                                                                                                                            | 71 |
| 141.3.5.3  | Nx25G-EPON signal detect functions.....                                                                                                                                               | 71 |
| 141.4      | Wavelength allocation .....                                                                                                                                                           | 71 |
| 141.5      | PMD to MDI optical specifications for OLT PMDs .....                                                                                                                                  | 72 |
| 141.5.1    | Transmitter optical specifications .....                                                                                                                                              | 72 |
| 141.5.2    | Receiver optical specifications.....                                                                                                                                                  | 72 |
| 141.6      | PMD to MDI optical specifications for ONU PMDs .....                                                                                                                                  | 77 |
| 141.6.1    | Transmitter optical specifications .....                                                                                                                                              | 77 |
| 141.6.2    | Receiver optical specifications.....                                                                                                                                                  | 80 |
| 141.7      | Definitions of optical parameters and measurement methods .....                                                                                                                       | 82 |
| 141.7.1    | Insertion loss .....                                                                                                                                                                  | 82 |
| 141.7.2    | Test patterns .....                                                                                                                                                                   | 82 |
| 141.7.3    | Wavelength and spectral width measurement.....                                                                                                                                        | 82 |
| 141.7.4    | Optical power measurements .....                                                                                                                                                      | 82 |
| 141.7.5    | Extinction ratio measurements .....                                                                                                                                                   | 82 |
| 141.7.6    | Optical Modulation Amplitude (OMA) test procedure.....                                                                                                                                | 82 |
| 141.7.7    | Relative intensity noise optical modulation amplitude (RINxOMA) measuring<br>procedure.....                                                                                           | 82 |
| 141.7.8    | Transmit optical waveform (transmit eye).....                                                                                                                                         | 83 |
| 141.7.9    | Transmitter and dispersion penalty (TDP) for 25G .....                                                                                                                                | 83 |
| 141.7.9.1  | Reference transmitter requirements.....                                                                                                                                               | 83 |
| 141.7.9.2  | Channel requirements.....                                                                                                                                                             | 83 |
| 141.7.9.3  | Reference receiver requirements .....                                                                                                                                                 | 83 |
| 141.7.9.4  | Test procedure .....                                                                                                                                                                  | 83 |
| 141.7.10   | Receive sensitivity.....                                                                                                                                                              | 84 |
| 141.7.11   | Stressed receiver conformance test .....                                                                                                                                              | 84 |
| 141.7.12   | Jitter measurements .....                                                                                                                                                             | 84 |
| 141.7.13   | Laser on/off timing measurement .....                                                                                                                                                 | 84 |
| 141.7.13.1 | Definitions .....                                                                                                                                                                     | 84 |
| 141.7.13.2 | Test specification .....                                                                                                                                                              | 84 |
| 141.7.14   | Receiver settling timing measurement .....                                                                                                                                            | 86 |
| 141.7.14.1 | Definitions .....                                                                                                                                                                     | 86 |
| 141.7.14.2 | Test specification .....                                                                                                                                                              | 86 |
| 141.8      | Environmental, safety, and labeling .....                                                                                                                                             | 87 |
| 141.8.1    | General safety.....                                                                                                                                                                   | 87 |
| 141.8.2    | Laser safety .....                                                                                                                                                                    | 87 |
| 141.8.3    | Installation.....                                                                                                                                                                     | 87 |
| 141.8.4    | Environment.....                                                                                                                                                                      | 87 |
| 141.8.5    | PMD labeling .....                                                                                                                                                                    | 87 |
| 141.9      | Characteristics of the fiber optic cabling .....                                                                                                                                      | 88 |
| 141.9.1    | Fiber optic cabling model.....                                                                                                                                                        | 88 |
| 141.9.2    | Optical fiber and cable .....                                                                                                                                                         | 88 |
| 141.9.3    | Optical fiber connection.....                                                                                                                                                         | 88 |
| 141.9.4    | Medium Dependent Interface (MDI) .....                                                                                                                                                | 89 |
| 141.10     | Protocol implementation conformance statement (PICS) proforma for Clause 141,<br>Physical Medium Dependent (PMD) sublayer and medium for Nx25G-EPON passive<br>optical networks ..... | 90 |
| 141.10.1   | Introduction .....                                                                                                                                                                    | 90 |
| 141.10.2   | Identification .....                                                                                                                                                                  | 90 |
| 141.10.2.1 | Implementation identification.....                                                                                                                                                    | 90 |
| 141.10.2.2 | Protocol summary .....                                                                                                                                                                | 90 |
| 141.10.3   | Major capabilities/options .....                                                                                                                                                      | 91 |

|             |                                                                                                                                                                                               |     |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| 141.10.4    | PICS proforma tables for Physical Medium Dependent (PMD) sublayer and medium for passive optical networks, type 25/10GBASE-PQ, 25GBASE-PQ, 50/10GBASE-PQ, 50/25GBASE-PQ, and 50GBASE-PQ ..... | 94  |
| 141.10.4.1  | PMD functional specifications .....                                                                                                                                                           | 94  |
| 141.10.4.2  | PMD to MDI optical specifications for 25/10GBASE-PQG-D2 .....                                                                                                                                 | 95  |
| 141.10.4.3  | PMD to MDI optical specifications for 25/10GBASE-PQG-D3 .....                                                                                                                                 | 95  |
| 141.10.4.4  | PMD to MDI optical specifications for 25/10GBASE-PQX-D2 .....                                                                                                                                 | 95  |
| 141.10.4.5  | PMD to MDI optical specifications for 25/10GBASE-PQX-D3 .....                                                                                                                                 | 96  |
| 141.10.4.6  | PMD to MDI optical specifications for 25GBASE-PQG-D2 .....                                                                                                                                    | 96  |
| 141.10.4.7  | PMD to MDI optical specifications for 25GBASE-PQG-D3 .....                                                                                                                                    | 96  |
| 141.10.4.8  | PMD to MDI optical specifications for 25GBASE-PQX-D2 .....                                                                                                                                    | 96  |
| 141.10.4.9  | PMD to MDI optical specifications for 25GBASE-PQX-D3 .....                                                                                                                                    | 97  |
| 141.10.4.10 | PMD to MDI optical specifications for 50/10GBASE-PQG-D2 .....                                                                                                                                 | 97  |
| 141.10.4.11 | PMD to MDI optical specifications for 50/10GBASE-PQG-D3 .....                                                                                                                                 | 97  |
| 141.10.4.12 | PMD to MDI optical specifications for 50/10GBASE-PQX-D2 .....                                                                                                                                 | 97  |
| 141.10.4.13 | PMD to MDI optical specifications for 50/10GBASE-PQX-D3 .....                                                                                                                                 | 98  |
| 141.10.4.14 | PMD to MDI optical specifications for 50/25GBASE-PQG-D2 .....                                                                                                                                 | 98  |
| 141.10.4.15 | PMD to MDI optical specifications for 50/25GBASE-PQG-D3 .....                                                                                                                                 | 98  |
| 141.10.4.16 | PMD to MDI optical specifications for 50/25GBASE-PQX-D2 .....                                                                                                                                 | 98  |
| 141.10.4.17 | PMD to MDI optical specifications for 50/25GBASE-PQX-D3 .....                                                                                                                                 | 99  |
| 141.10.4.18 | PMD to MDI optical specifications for 50GBASE-PQG-D2 .....                                                                                                                                    | 99  |
| 141.10.4.19 | PMD to MDI optical specifications for 50GBASE-PQG-D3 .....                                                                                                                                    | 99  |
| 141.10.4.20 | PMD to MDI optical specifications for 50GBASE-PQX-D2 .....                                                                                                                                    | 99  |
| 141.10.4.21 | PMD to MDI optical specifications for 50GBASE-PQX-D3 .....                                                                                                                                    | 100 |
| 141.10.4.22 | PMD to MDI optical specifications for 25/10GBASE-PQG-U2 .....                                                                                                                                 | 100 |
| 141.10.4.23 | PMD to MDI optical specifications for 25/10GBASE-PQG-U3 .....                                                                                                                                 | 100 |
| 141.10.4.24 | PMD to MDI optical specifications for 25/10GBASE-PQX-U2 .....                                                                                                                                 | 100 |
| 141.10.4.25 | PMD to MDI optical specifications for 25/10GBASE-PQX-U3 .....                                                                                                                                 | 101 |
| 141.10.4.26 | PMD to MDI optical specifications for 25GBASE-PQG-U2 .....                                                                                                                                    | 101 |
| 141.10.4.27 | PMD to MDI optical specifications for 25GBASE-PQG-U3 .....                                                                                                                                    | 101 |
| 141.10.4.28 | PMD to MDI optical specifications for 25GBASE-PQX-U2 .....                                                                                                                                    | 101 |
| 141.10.4.29 | PMD to MDI optical specifications for 25GBASE-PQX-U3 .....                                                                                                                                    | 102 |
| 141.10.4.30 | PMD to MDI optical specifications for 50/10GBASE-PQG-U2 .....                                                                                                                                 | 102 |
| 141.10.4.31 | PMD to MDI optical specifications for 50/10GBASE-PQG-U3 .....                                                                                                                                 | 102 |
| 141.10.4.32 | PMD to MDI optical specifications for 50/10GBASE-PQX-U2 .....                                                                                                                                 | 102 |
| 141.10.4.33 | PMD to MDI optical specifications for 50/10GBASE-PQX-U3 .....                                                                                                                                 | 103 |
| 141.10.4.34 | PMD to MDI optical specifications for 50/25GBASE-PQG-U2 .....                                                                                                                                 | 103 |
| 141.10.4.35 | PMD to MDI optical specifications for 50/25GBASE-PQG-U3 .....                                                                                                                                 | 103 |
| 141.10.4.36 | PMD to MDI optical specifications for 50/25GBASE-PQX-U2 .....                                                                                                                                 | 103 |
| 141.10.4.37 | PMD to MDI optical specifications for 50/25GBASE-PQX-U3 .....                                                                                                                                 | 104 |
| 141.10.4.38 | PMD to MDI optical specifications for 50GBASE-PQG-U2 .....                                                                                                                                    | 104 |
| 141.10.4.39 | PMD to MDI optical specifications for 50GBASE-PQG-U3 .....                                                                                                                                    | 104 |
| 141.10.4.40 | PMD to MDI optical specifications for 50GBASE-PQX-U2 .....                                                                                                                                    | 104 |
| 141.10.4.41 | PMD to MDI optical specifications for 50GBASE-PQX-U3 .....                                                                                                                                    | 105 |
| 141.10.4.42 | Definitions of optical parameters and measurement methods.....                                                                                                                                | 105 |
| 141.10.4.43 | Characteristics of the fiber optic cabling and MDI .....                                                                                                                                      | 106 |
| 141.10.4.44 | Environmental specifications .....                                                                                                                                                            | 106 |
| 142.        | Physical Coding Sublayer and Physical Media Attachment for Nx25G-EPON .....                                                                                                                   | 107 |
| 142.1       | Overview.....                                                                                                                                                                                 | 107 |
| 142.1.1     | Conventions.....                                                                                                                                                                              | 107 |
| 142.1.1.1   | State diagrams.....                                                                                                                                                                           | 107 |
| 142.1.1.2   | Hexadecimal notation .....                                                                                                                                                                    | 107 |

|             |                                                  |     |
|-------------|--------------------------------------------------|-----|
| 142.1.1.3   | Timers .....                                     | 110 |
| 142.1.1.4   | Operations on variables .....                    | 110 |
| 142.1.1.5   | Operations on wrap-around variables .....        | 111 |
| 142.1.1.6   | FIFO access operations .....                     | 111 |
| 142.1.2     | Delay constraints .....                          | 112 |
| 142.1.3     | Burst transmission .....                         | 112 |
| 142.1.3.1   | Default synchronization pattern parameters ..... | 113 |
| 142.2       | PCS transmit data path .....                     | 114 |
| 142.2.1     | 64B/66B line encoder .....                       | 114 |
| 142.2.2     | Scrambler .....                                  | 116 |
| 142.2.3     | 64B/66B to 256B/257B transcoder .....            | 116 |
| 142.2.4     | FEC encoder .....                                | 116 |
| 142.2.4.1   | Low-density parity-check coding .....            | 116 |
| 142.2.4.2   | FEC encoder processing .....                     | 119 |
| 142.2.4.3   | Interleaver .....                                | 121 |
| 142.2.5     | Transmit data path state diagrams .....          | 126 |
| 142.2.5.1   | Constants .....                                  | 126 |
| 142.2.5.2   | Variables .....                                  | 127 |
| 142.2.5.3   | Functions .....                                  | 129 |
| 142.2.5.4   | State diagrams .....                             | 130 |
| 142.2.5.4.1 | PCS Input process .....                          | 130 |
| 142.2.5.4.2 | PCS Framer process .....                         | 131 |
| 142.2.5.4.3 | PCS Transmit process .....                       | 132 |
| 142.3       | PCS receive data path .....                      | 133 |
| 142.3.1     | FEC decoder .....                                | 133 |
| 142.3.1.1   | Receive interleaving .....                       | 133 |
| 142.3.2     | 256B/257B to 64B/66B transcoder .....            | 134 |
| 142.3.3     | Descrambler .....                                | 134 |
| 142.3.4     | 64B/66B decoder .....                            | 135 |
| 142.3.5     | Receive data path state diagrams .....           | 136 |
| 142.3.5.1   | Constants .....                                  | 136 |
| 142.3.5.2   | Variables .....                                  | 137 |
| 142.3.5.3   | Functions .....                                  | 139 |
| 142.3.5.4   | OLT Synchronizer process state diagram .....     | 140 |
| 142.3.5.5   | ONU Synchronizer process state diagram .....     | 140 |
| 142.3.5.6   | PCS ONU BER Monitor process .....                | 141 |
| 142.3.5.7   | PCS Output process .....                         | 142 |
| 142.4       | Nx25G-EPON PMA .....                             | 142 |
| 142.4.1     | Service Interface .....                          | 142 |
| 142.4.1.1   | PMA_UNITDATA[i].request .....                    | 143 |
| 142.4.1.1.1 | Semantics of the service primitive .....         | 143 |
| 142.4.1.1.2 | When generated .....                             | 143 |
| 142.4.1.1.3 | Effect of receipt .....                          | 143 |
| 142.4.1.2   | PMA_UNITDATA[i].indication .....                 | 143 |
| 142.4.1.2.1 | Semantics of the service primitive .....         | 143 |
| 142.4.1.2.2 | When generated .....                             | 143 |
| 142.4.1.2.3 | Effect of receipt .....                          | 143 |
| 142.4.1.3   | PMA_SIGNAL[i].request .....                      | 144 |
| 142.4.1.4   | PMA_SIGNAL[i].indication .....                   | 144 |
| 142.4.1.4.1 | Semantics of the service primitive .....         | 144 |
| 142.4.1.4.2 | When generated .....                             | 144 |
| 142.4.1.4.3 | Effect of receipt .....                          | 144 |
| 142.4.2     | Differential encoder .....                       | 144 |
| 142.4.3     | Differential decoder .....                       | 145 |

|             |                                                                                                                                                              |     |
|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| 142.4.4     | PMA transmit clock .....                                                                                                                                     | 145 |
| 142.4.4.1   | Loop-timing specifications for ONUs .....                                                                                                                    | 145 |
| 142.4.5     | TCDR measurement .....                                                                                                                                       | 145 |
| 142.4.5.1   | Definitions .....                                                                                                                                            | 145 |
| 142.4.5.2   | Test specification .....                                                                                                                                     | 145 |
| 142.5       | Protocol implementation conformance statement (PICS) proforma for Clause 142,<br>Physical Coding Sublayer and Physical Media Attachment for Nx25G-EPON ..... | 147 |
| 142.5.1     | Introduction .....                                                                                                                                           | 147 |
| 142.5.2     | Identification .....                                                                                                                                         | 147 |
| 142.5.2.1   | Implementation identification .....                                                                                                                          | 147 |
| 142.5.2.2   | Protocol summary .....                                                                                                                                       | 147 |
| 142.5.3     | PCS capabilities/options .....                                                                                                                               | 148 |
| 142.5.4     | PCS processes .....                                                                                                                                          | 148 |
| 142.5.5     | PMA processes .....                                                                                                                                          | 149 |
| 143.        | Multi-Channel Reconciliation Sublayer .....                                                                                                                  | 150 |
| 143.1       | Overview .....                                                                                                                                               | 150 |
| 143.2       | Summary of major concepts .....                                                                                                                              | 150 |
| 143.2.1     | Concept of a logical link and LLID .....                                                                                                                     | 151 |
| 143.2.2     | Concept of an MCRS channel .....                                                                                                                             | 151 |
| 143.2.3     | Binding of multiple MACs to multiple xMII instances .....                                                                                                    | 151 |
| 143.2.4     | Transmission and reception over multiple MCRS channels .....                                                                                                 | 152 |
| 143.2.4.1   | Transmission unit .....                                                                                                                                      | 152 |
| 143.2.4.2   | Transmission envelopes .....                                                                                                                                 | 152 |
| 143.2.4.3   | Envelope headers .....                                                                                                                                       | 152 |
| 143.2.4.4   | Interpacket gap adjustment .....                                                                                                                             | 153 |
| 143.2.5     | Dynamic channel bonding .....                                                                                                                                | 154 |
| 143.2.5.1   | LLID transmission over multiple MCRS channels .....                                                                                                          | 155 |
| 143.2.5.2   | MCRS channel skew remediation mechanism .....                                                                                                                | 156 |
| 143.2.5.3   | <i>EnvTx</i> and <i>EnvRx</i> buffers .....                                                                                                                  | 156 |
| 143.2.5.4   | Envelope position alignment marker .....                                                                                                                     | 158 |
| 143.2.6     | MDIO addressing model for multi-channel architecture .....                                                                                                   | 158 |
| 143.3       | MCRS functional specifications .....                                                                                                                         | 160 |
| 143.3.1     | MCRS interfaces .....                                                                                                                                        | 160 |
| 143.3.1.1   | PLS service primitives .....                                                                                                                                 | 160 |
| 143.3.1.1.1 | Mapping of PLS_DATA[ch].request primitive .....                                                                                                              | 161 |
| 143.3.1.1.2 | Mapping of PLS_SIGNAL[ch].indication primitive .....                                                                                                         | 161 |
| 143.3.1.1.3 | Mapping of PLS_DATA[ch].indication primitive .....                                                                                                           | 161 |
| 143.3.1.1.4 | Mapping of PLS_DATA_VALID[ch].indication primitive .....                                                                                                     | 162 |
| 143.3.1.1.5 | Mapping of PLS_CARRIER[ch].indication primitive .....                                                                                                        | 162 |
| 143.3.1.2   | MCRS control primitives .....                                                                                                                                | 162 |
| 143.3.1.2.1 | MCRS_CTRL[ch].request(link_id, epam, env_length) primitive .....                                                                                             | 162 |
| 143.3.1.2.2 | MCRS_CTRL[ch].indication() primitive .....                                                                                                                   | 162 |
| 143.3.1.2.3 | MCRS_ECH[ch].indication(Llid) primitive .....                                                                                                                | 162 |
| 143.3.1.3   | XGMII interfaces .....                                                                                                                                       | 162 |
| 143.3.1.4   | 25GMII interfaces .....                                                                                                                                      | 162 |
| 143.3.2     | Envelope header format .....                                                                                                                                 | 163 |
| 143.3.2.1   | CRC8 calculation test sequences .....                                                                                                                        | 164 |
| 143.3.3     | Transmit functional specifications .....                                                                                                                     | 165 |
| 143.3.3.1   | Conventions .....                                                                                                                                            | 166 |
| 143.3.3.2   | Application-specific parameter definitions .....                                                                                                             | 166 |
| 143.3.3.3   | Constants .....                                                                                                                                              | 166 |
| 143.3.3.4   | Variables .....                                                                                                                                              | 167 |

|             |                                                                                                                          |     |
|-------------|--------------------------------------------------------------------------------------------------------------------------|-----|
| 143.3.3.5   | Functions .....                                                                                                          | 169 |
| 143.3.3.6   | State diagrams.....                                                                                                      | 171 |
| 143.3.3.6.1 | Input process .....                                                                                                      | 171 |
| 143.3.3.6.2 | Transmit process .....                                                                                                   | 171 |
| 143.3.4     | Receive functional specifications.....                                                                                   | 173 |
| 143.3.4.1   | Conventions .....                                                                                                        | 174 |
| 143.3.4.2   | Constants .....                                                                                                          | 174 |
| 143.3.4.3   | Variables .....                                                                                                          | 175 |
| 143.3.4.4   | Functions .....                                                                                                          | 176 |
| 143.3.4.5   | State diagrams.....                                                                                                      | 177 |
| 143.3.4.5.1 | Receive process .....                                                                                                    | 177 |
| 143.3.4.5.2 | Output process.....                                                                                                      | 178 |
| 143.4       | Nx25G-EPON MCRS requirements.....                                                                                        | 178 |
| 143.4.1     | Nx25G-EPON architecture .....                                                                                            | 178 |
| 143.4.1.1   | MCRS channels .....                                                                                                      | 180 |
| 143.4.1.2   | Symmetric and asymmetric data rates .....                                                                                | 180 |
| 143.4.1.3   | Nx25G-EPON application-specific parameters.....                                                                          | 181 |
| 143.4.1.3.1 | Constants .....                                                                                                          | 181 |
| 143.4.1.3.2 | Transmit variables.....                                                                                                  | 181 |
| 143.4.2     | MCRS time synchronization.....                                                                                           | 181 |
| 143.4.3     | Delay variability constraints.....                                                                                       | 182 |
| 143.4.4     | Asymmetric rate operation .....                                                                                          | 182 |
| 143.5       | Protocol implementation conformance statement (PICS) proforma for Clause 143, Multi-Channel Reconciliation Sublayer..... | 185 |
| 143.5.1     | Introduction .....                                                                                                       | 185 |
| 143.5.2     | Identification .....                                                                                                     | 185 |
| 143.5.2.1   | Implementation identification.....                                                                                       | 185 |
| 143.5.2.2   | Protocol summary.....                                                                                                    | 185 |
| 143.5.3     | Generic MCRS .....                                                                                                       | 186 |
| 143.5.4     | MCRS in Nx25G-EPON .....                                                                                                 | 186 |
| 143.5.4.1   | Major capabilities/option .....                                                                                          | 186 |
| 143.5.4.2   | MCRS implementation in Nx25G-EPON .....                                                                                  | 187 |
| 144.        | Multipoint MAC Control for Nx25G-EPON.....                                                                               | 188 |
| 144.1       | Overview.....                                                                                                            | 188 |
| 144.1.1     | Principles of point-to-multipoint operation.....                                                                         | 188 |
| 144.1.1.1   | Transmission arbitration .....                                                                                           | 188 |
| 144.1.1.2   | Concept of logical links.....                                                                                            | 189 |
| 144.1.1.3   | ONU discovery and registration .....                                                                                     | 191 |
| 144.1.2     | Position of Multipoint MAC Control (MPMC) within the IEEE 802.3 hierarchy .....                                          | 191 |
| 144.1.3     | Functional block diagram.....                                                                                            | 191 |
| 144.1.4     | Service interfaces .....                                                                                                 | 191 |
| 144.1.4.1   | MAC Control service (MCS) interface .....                                                                                | 191 |
| 144.1.4.2   | MAC Control interconnect (MCI) .....                                                                                     | 194 |
| 144.1.4.3   | MAC service Interface.....                                                                                               | 194 |
| 144.1.4.4   | MCRS Control interface .....                                                                                             | 194 |
| 144.1.5     | Conventions.....                                                                                                         | 194 |
| 144.2       | Protocol-independent operation.....                                                                                      | 194 |
| 144.2.1     | Control Parser and Control Multiplexer.....                                                                              | 195 |
| 144.2.1.1   | Constants .....                                                                                                          | 195 |
| 144.2.1.2   | Counters.....                                                                                                            | 195 |
| 144.2.1.3   | Variables .....                                                                                                          | 195 |
| 144.2.1.4   | Functions .....                                                                                                          | 196 |

|            |                                                        |     |
|------------|--------------------------------------------------------|-----|
| 144.2.1.5  | Control Parser state diagram.....                      | 197 |
| 144.2.1.6  | Control Multiplexer state diagram.....                 | 198 |
| 144.3      | Multipoint Control Protocol (MPCP) .....               | 198 |
| 144.3.1    | Principles of Multipoint Control Protocol (MPCP) ..... | 198 |
| 144.3.1.1  | Ranging measurement and time synchronization .....     | 198 |
| 144.3.1.2  | Granting access to the PON media by the OLT .....      | 201 |
| 144.3.2    | MPCP block diagram .....                               | 202 |
| 144.3.3    | Delay variability requirements .....                   | 204 |
| 144.3.4    | Logical link identifier (LLID) types.....              | 204 |
| 144.3.4.1  | Physical Layer ID (PLID).....                          | 204 |
| 144.3.4.2  | Management link ID (MLID) .....                        | 205 |
| 144.3.4.3  | User link ID (ULID) .....                              | 205 |
| 144.3.4.4  | Group link ID (GLID) .....                             | 205 |
| 144.3.5    | Allocation of LLID values .....                        | 205 |
| 144.3.6    | MPCPDU structure and encoding .....                    | 206 |
| 144.3.6.1  | GATE description.....                                  | 207 |
| 144.3.6.2  | REPORT description .....                               | 209 |
| 144.3.6.3  | REGISTER_REQ description .....                         | 211 |
| 144.3.6.4  | REGISTER description .....                             | 212 |
| 144.3.6.5  | REGISTER_ACK description.....                          | 214 |
| 144.3.6.6  | DISCOVERY description.....                             | 216 |
| 144.3.6.7  | SYNC_PATTERN description.....                          | 218 |
| 144.3.7    | Discovery process .....                                | 220 |
| 144.3.7.1  | Constants .....                                        | 222 |
| 144.3.7.2  | Counters.....                                          | 223 |
| 144.3.7.3  | Variables .....                                        | 223 |
| 144.3.7.4  | Functions .....                                        | 225 |
| 144.3.7.5  | Messages.....                                          | 226 |
| 144.3.7.6  | Discovery Initiation state diagram.....                | 226 |
| 144.3.7.7  | Registration Completion state diagram .....            | 227 |
| 144.3.7.8  | ONU Registration state diagram.....                    | 228 |
| 144.3.8    | Granting process.....                                  | 230 |
| 144.3.8.1  | Constants .....                                        | 230 |
| 144.3.8.2  | Counters.....                                          | 231 |
| 144.3.8.3  | Variables .....                                        | 231 |
| 144.3.8.4  | Functions .....                                        | 232 |
| 144.3.8.5  | Timers.....                                            | 232 |
| 144.3.8.6  | Messages.....                                          | 232 |
| 144.3.8.7  | GATE Generation state diagram .....                    | 232 |
| 144.3.8.8  | GATE Reception state diagram.....                      | 233 |
| 144.3.8.9  | OLT Envelope Commitment state diagram.....             | 233 |
| 144.3.8.10 | ONU Envelope Commitment state diagram.....             | 234 |
| 144.3.8.11 | Envelope Activation state diagram.....                 | 235 |
| 144.3.9    | Discovery process in dual-rate systems .....           | 235 |
| 144.3.9.1  | OLT rate-specific discovery .....                      | 235 |
| 144.3.9.2  | ONU rate-specific registration.....                    | 236 |
| 144.4      | Channel Control Protocol (CCP) .....                   | 237 |
| 144.4.1    | CCP block diagram .....                                | 237 |
| 144.4.2    | Principles of Channel Control Protocol .....           | 238 |
| 144.4.2.1  | Disabling a downstream channel at an ONU.....          | 239 |
| 144.4.2.2  | Enabling a downstream channel at an ONU .....          | 239 |
| 144.4.2.3  | Disabling an upstream channel at an ONU .....          | 239 |
| 144.4.2.4  | Enabling an upstream channel at an ONU.....            | 240 |
| 144.4.2.5  | Local channel state changes at an ONU .....            | 240 |

|                                                                                               |                                                                                                                              |     |
|-----------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|-----|
| 144.4.3                                                                                       | CCPDU structure and encoding .....                                                                                           | 240 |
| 144.4.3.1                                                                                     | CC_REQUEST description .....                                                                                                 | 241 |
| 144.4.3.2                                                                                     | CC_RESPONSE description .....                                                                                                | 243 |
| 144.4.4                                                                                       | Channel Control operation .....                                                                                              | 244 |
| 144.4.4.1                                                                                     | Constants .....                                                                                                              | 244 |
| 144.4.4.2                                                                                     | Variables .....                                                                                                              | 245 |
| 144.4.4.3                                                                                     | Functions .....                                                                                                              | 246 |
| 144.4.4.4                                                                                     | Messages .....                                                                                                               | 247 |
| 144.4.4.5                                                                                     | OLT CCPDU processing state diagram .....                                                                                     | 247 |
| 144.4.4.6                                                                                     | ONU CCPDU processing state diagram .....                                                                                     | 248 |
| 144.5                                                                                         | Protocol implementation conformance statement (PICS) proforma for Clause 144,<br>Multipoint MAC Control for Nx25G-EPON ..... | 249 |
| 144.5.1                                                                                       | Introduction .....                                                                                                           | 249 |
| 144.5.2                                                                                       | Identification .....                                                                                                         | 249 |
| 144.5.2.1                                                                                     | Implementation identification .....                                                                                          | 249 |
| 144.5.2.2                                                                                     | Protocol summary .....                                                                                                       | 249 |
| 144.5.3                                                                                       | Major capabilities/options .....                                                                                             | 250 |
| 144.5.4                                                                                       | PICS proforma tables for Multipoint MAC Control .....                                                                        | 250 |
| 144.5.4.1                                                                                     | Clock tracking .....                                                                                                         | 250 |
| 144.5.4.2                                                                                     | LLID .....                                                                                                                   | 250 |
| 144.5.4.3                                                                                     | Protocol-independent state diagrams .....                                                                                    | 251 |
| 144.5.4.4                                                                                     | MPCP .....                                                                                                                   | 251 |
| 144.5.4.5                                                                                     | CCP .....                                                                                                                    | 254 |
| Annex A (informative) Bibliography .....                                                      |                                                                                                                              | 255 |
| Annex 31A (normative) MAC Control opcode assignments .....                                    |                                                                                                                              | 256 |
| Annex 142A (informative) Encoding example for QC-LDPC(16952,14392) FEC and interleaving ..... |                                                                                                                              | 258 |
| 142A.1                                                                                        | Example of initial control seed sequence .....                                                                               | 258 |
| 142A.2                                                                                        | QC-LDPC FEC encoder test vectors .....                                                                                       | 258 |

# IEEE Standard for Ethernet

## Amendment 9: Physical Layer Specifications and Management Parameters for 25 Gb/s and 50 Gb/s Passive Optical Networks

(This amendment is based on IEEE Std 802.3™-2018 as amended by IEEE Std 802.3cb™-2018, IEEE Std 802.3bt™-2018, IEEE Std 802.3cd™-2018, IEEE Std 802.3cn™-2019, IEEE Std 802.3cg™-2019, IEEE Std 802.3cq™-2020, IEEE Std 802.3cm™-2020, and IEEE Std 802.3ch™-2020.)

NOTE—The editing instructions contained in this amendment define how to merge the material contained therein into the existing base standard and its amendments to form the comprehensive standard.

The editing instructions are shown in ***bold italic***. Four editing instructions are used: change, delete, insert, and replace. ***Change*** is used to make corrections in existing text or tables. The editing instruction specifies the location of the change and describes what is being changed by using ~~strike through~~ (to remove old material) and underscore (to add new material). ***Delete*** removes existing material. ***Insert*** adds new material without disturbing the existing material. Deletions and insertions may require renumbering. If so, renumbering instructions are given in the editing instruction. ***Replace*** is used to make changes in figures or equations by removing the existing figure or equation and replacing it with a new one. Editing instructions, change markings, and this NOTE will not be carried over into future editions because the changes will be incorporated into the base standard.

Cross references that refer to clauses, tables, equations, or figures not covered by this amendment are highlighted in green.<sup>1</sup>

<sup>1</sup> Notes in text, tables, and figures are given for information only and do not contain requirements needed to implement the standard.

## 1. Introduction

### 1.3 Normative references

*Change the references for ITU-T Recommendations G.652 and G.657 as follows:*

ITU-T Recommendation G.652, ~~2009~~2016—Characteristics of a single-mode optical fibre and cable.<sup>2</sup>

ITU-T Recommendation G.657, ~~2009~~2016—Characteristics of a bending-loss insensitive single-mode optical fibre and cable ~~for the access network~~.

### 1.4 Definitions

*Insert the following two new definitions after 1.4.90 “200GXS”:*

**1.4.90a 25/10G-EPON:** An EPON architecture supporting a maximum sustained throughput of 25 Gb/s in the downstream direction and 10 Gb/s in the upstream direction (asymmetric rate).

**1.4.90b 25/25G-EPON:** An EPON architecture supporting a maximum sustained throughput of 25 Gb/s in both downstream and upstream directions (symmetric rate).

*Insert the following new definition after 1.4.100 “25GBASE-T”:*

**1.4.100a 25G-EPON:** An EPON architecture supporting a maximum sustained throughput of 25 Gb/s in either downstream or both downstream and upstream directions. This term collectively refers to 25/10G-EPON and 25/25G-EPON architectures.

*Insert the following three new definitions before 1.4.128aa “50GBASE-CR” as inserted by IEEE Std 802.3cd-2018:*

**1.4.128aaa 50/10G-EPON:** An EPON architecture supporting a maximum sustained throughput of 50 Gb/s in the downstream direction and 10 Gb/s in the upstream direction (asymmetric rate).

**1.4.128aab 50/25G-EPON:** An EPON architecture supporting a maximum sustained throughput of 50 Gb/s in the downstream direction and 25 Gb/s in the upstream direction (asymmetric rate).

**1.4.128aac 50/50G-EPON:** An EPON architecture supporting a maximum sustained throughput of 50 Gb/s in both downstream and upstream directions (symmetric rate).

*Insert the following new definition after 1.4.128ah “50 Gb/s Media Independent Interface (50GMII)” as inserted by IEEE Std 802.3cd-2018:*

**1.4.128ai 50G-EPON:** An EPON architecture supporting a maximum sustained throughput of 50 Gb/s in either downstream or both downstream and upstream directions. This term collectively refers to 50/10G-EPON, 50/25G-EPON, and 50/50G-EPON architectures.

*Insert the following three new definitions after 1.4.244 “Energy-Efficient Ethernet (EEE)”:*

**1.4.244a envelope:** In the Multi-Channel Reconciliation Sublayer (MCRS, see IEEE Std 802.3, Clause 143), an envelope encapsulates data belonging to a specific LLID being transmitted on a specific

<sup>2</sup>ITU-T publications are available from the International Telecommunications Union (<https://www.itu.int/>).

MCRS channel, i.e., the data or idles sourced from a specific MAC instance and sent over a specific MCRS channel.

**1.4.244b envelope allocation:** In Nx25G-EPON, an envelope allocation represents a transmission window allocated to a single LLID (including GLID). A single GATE MPCPDU can carry up to seven envelope allocations.

**1.4.244c envelope descriptor:** A set of parameters consisting of LLID, StartTime, and EnvLength. An envelope descriptor defines a specific envelope pending transmission. Envelope descriptors are generated by the local MPCP sublayer and are passed to MCRS at the appropriate time to start the envelope transmission.

*Insert the following three new definitions after 1.4.245 “envelope frame”:*

**1.4.245a envelope header:** An MCRS-specific marker that is inserted at the beginning of every envelope (envelope start header) and in place of every frame preamble (envelope continuation header). The envelope header includes fields that identify the LLID that sourced the encapsulated data and the length of the data (in units of EQ). Envelope headers also include a CRC8 field used to detect bit errors.

**1.4.245b envelope quantum:** A unit of information volume. Each envelope quantum represents 64 bits of data plus the layer-specific encoding. Thus, at the MAC Control sublayer and above, an envelope quantum is equal to 64 bits. Within the MCRS, an envelope quantum contains 72 bits (i.e., 64 bits of data and 8 bits of control). Within the PCS, after the 64B/66B encoding, an envelope quantum contains 66 bits, and after 256B/257B encoding, four envelope quanta are packed into a single 257-bit block.

**1.4.245c EQT:** The unit of measurement of time for time-related parameters specified in IEEE Std 802.3, Clause 144 Multipoint MAC Control for Nx25G-EPON. Each EQT is equal to the time required to transmit one EQ between the MCRS and the PCS across 25GMII, and equal to 2.56 ns.

*Insert the following new definition after 1.4.277 “Gigabit Media Independent Interface (GMII)”:*

**1.4.277a GPON:** A Gigabit-capable Passive Optical Network, as specified in ITU-T G.984.2.

NOTE—ITU-T G.984.2 [B48a].

*Change definition 1.4.278 as shown below:*

**1.4.278 grant:** Within P2MP protocols, a permission to transmit at a specific time, for a specific duration. Grants are issued by the OLT (master) to ONUs (slaves) by means of GATE messages. In IEEE Std 802.3, Clause 64 and Clause 77, a GATE MPCPDU contains one or multiple grants issued to a single LLID, with each grant resulting in one or multiple upstream bursts transmitted by the ONU. In Clause 144, a grant includes envelope allocations for multiple LLIDs and there is a one-to-one correspondence between the grants issued to an ONU and upstream bursts transmitted by that ONU.

*Change 1.4.312 (renumbered from 1.4.313 due to the deletion of 1.4.294 by IEEE Std 802.3bt-2018) as follows:*

**1.4.312 Logical Link Identifier (LLID):** A numeric identifier assigned to a P2MP association between an OLT and ONU established through the Point-to-Point Emulation sublayer. Each P2MP association is assigned a unique LLID. The P2MP association is bound to an ONU DTE, where ~~a the ONU MAC would be~~ is to observe a private association. In Nx25G-EPON, an LLID is also a collective term that refers to a Physical Layer ID (PLID), management link ID (MLID), user link ID (ULID), and a group link ID (GLID).

*Insert the following new definition after 1.4.319 “maximum differential input” (renumbered from 1.4.320 due to the deletion of 1.4.294 by IEEE Std 802.3bt-2018):*

**1.4.319a MCRS channel:** In IEEE Std 802.3, Clause 143, an MCRS channel represents one of a number of defined paths along which data passes in an MCRS.

*Insert the following new definition after 1.4.332 “modulation error ratio (MER)” (renumbered from 1.4.333 due to the deletion of 1.4.294 by IEEE Std 802.3bt-2018):*

**1.4.332a Multi-Channel Reconciliation Sublayer (MCRS):** The MCRS provides a mapping function that reconciles the signals at a specific Media Independent Interface (xMII) to a specific Media Access Control (MAC) Physical Signaling Sublayer (PLS) service definitions.

*Insert the following new definition after 1.4.350 “NRZI” (renumbered from 1.4.351 due to the deletion of 1.4.294 by IEEE Std 802.3bt-2018):*

**1.4.350a Nx25G-EPON:** An EPON architecture operating at a number of different downstream and upstream speeds. This term collectively refers to 25/10G-EPON, 25/25G-EPON, 50/10G-EPON, 50/25G-EPON, and 50/50G-EPON architectures.

## 1.5 Abbreviations

*Insert the following new abbreviations into the list, in alphabetical order:*

|         |                                                                    |
|---------|--------------------------------------------------------------------|
| ECH     | envelope continuation header                                       |
| EQ      | envelope quantum                                                   |
| EQT     | envelope quantum time                                              |
| ESH     | envelope start header                                              |
| GLID    | group link ID                                                      |
| GPON    | Gigabit-capable Passive Optical Network (see ITU-T G.984.2 [B48a]) |
| MACI    | MA_CONTROL.indication                                              |
| MACR    | MA_CONTROL.request                                                 |
| MADI    | MA_DATA.indication                                                 |
| MADR    | MA_DATA.request                                                    |
| MCRS    | Multi-Channel Reconciliation Sublayer                              |
| MLID    | management link ID                                                 |
| PLID    | Physical Layer ID                                                  |
| QC-LDPC | quasi-cyclic low-density parity check                              |
| ULID    | user link ID                                                       |

## 30. Management

### 30.3 Layer management for DTEs

#### 30.3.2 PHY device managed object class

##### 30.3.2.1 PHY device attributes

##### 30.3.2.1.2 aPhyType

*Insert new entries in the APPROPRIATE SYNTAX section of 30.3.2.1.2 after the entry for 25GBASE-T as follows:*

|               |                                  |
|---------------|----------------------------------|
| ...           |                                  |
| 25GBASE-PQ    | Clause 142 25/25G-EPON 256B/257B |
| 25/10GBASE-PQ | Clause 142 25/10G-EPON 256B/257B |
| ...           |                                  |

*Insert new entries in the APPROPRIATE SYNTAX section of 30.3.2.1.2 after the entry for 50GBASE-R (inserted by IEEE Std 802.3cd-2018) as follows:*

|               |                                  |
|---------------|----------------------------------|
| ...           |                                  |
| 50GBASE-PQ    | Clause 142 50/50G-EPON 256B/257B |
| 50/25GBASE-PQ | Clause 142 50/25G-EPON 256B/257B |
| 50/10GBASE-PQ | Clause 142 50/10G-EPON 256B/257B |
| ...           |                                  |

##### 30.3.2.1.3 aPhyTypeList

*Insert new entries in the APPROPRIATE SYNTAX section of 30.3.2.1.3 after the entry for 25GBASE-T as follows:*

|               |                                  |
|---------------|----------------------------------|
| ...           |                                  |
| 25GBASE-PQ    | Clause 142 25/25G-EPON 256B/257B |
| 25/10GBASE-PQ | Clause 142 25/10G-EPON 256B/257B |
| ...           |                                  |

*Insert new entries in the APPROPRIATE SYNTAX section of 30.3.2.1.3 after the entry for 50GBASE-R (inserted by IEEE Std 802.3cd-2018) as follows:*

|               |                                  |
|---------------|----------------------------------|
| ...           |                                  |
| 50GBASE-PQ    | Clause 142 50/50G-EPON 256B/257B |
| 50/25GBASE-PQ | Clause 142 50/25G-EPON 256B/257B |
| 50/10GBASE-PQ | Clause 142 50/10G-EPON 256B/257B |
| ...           |                                  |

### 30.3.5 MPCP managed object class

#### 30.3.5.1 MPCP Attributes

##### 30.3.5.1.2 aMPCPAdminState

*Change the text of the BEHAVIOUR DEFINED AS section of 30.3.5.1.2 as follows:*

##### BEHAVIOUR DEFINED AS:

A read-only value that identifies the operational state of the Multipoint MAC Control sublayer. An interface that can provide the Multipoint MAC Control sublayer functions specified in [Clause 64](#), [Clause 77](#), ~~or Clause 103~~, or Clause 144 is enabled to do so when this attribute has the enumeration “enabled”. When this attribute has the enumeration “disabled”, the interface acts as it would if it had no Multipoint MAC Control sublayer. The operational state of the Multipoint MAC Control sublayer can be changed using the acMPCPAdminControl action.;

##### 30.3.5.1.3 aMPCPMode

*Change the text of the BEHAVIOUR DEFINED AS section of 30.3.5.1.3 as follows:*

##### BEHAVIOUR DEFINED AS:

A read-only value that identifies the operational mode of the Multipoint MAC Control sublayer. An interface that can provide the Multipoint MAC Control sublayer functions specified in [Clause 64](#), [Clause 77](#), ~~or Clause 103~~, or Clause 144. When this attribute has the enumeration “OLT”, the interface acts as an OLT. When this attribute has the enumeration “ONU”, the interface acts as an ONU. When this attribute has the enumeration “CLT”, the interface acts as a CLT. When this attribute has the enumeration “CNU”, the interface acts as a CNU.;

##### 30.3.5.1.4 aMPCPLinkID

*Change the text of the BEHAVIOUR DEFINED AS section of 30.3.5.1.3 as follows:*

##### BEHAVIOUR DEFINED AS:

A read-only value that identifies the Logical Link identity (LLID) associated with the MAC port as specified in [65.1.3.2.2](#), ~~or 76.2.6.1.3.2~~, or 144.3.4, as appropriate.;

## 30.5 Layer management for medium attachment units (MAUs)

### 30.5.1 MAU managed object class

#### 30.5.1.1 MAU attributes

##### 30.5.1.1.2 aMAUType

*Insert new entries in the APPROPRIATE SYNTAX section of 30.5.1.1.2 after the entry for 25GBASE-T as follows:*

...  
 25/10GBASE-PQG-D2 One single mode fiber, 1 × 25.78125 GBd continuous transmission /  
 1 × 10.3125 GBd burst mode reception, medium power class,  
 as specified in Clause 141

|                   |                                                                                                                                                               |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 25/10GBASE-PQG-D3 | One single mode fiber, 1 × 25.78125 GBd continuous transmission /<br>1 × 10.3125 GBd burst mode reception, high power class,<br>as specified in Clause 141    |
| 25/10GBASE-PQG-U2 | One single mode fiber, 1 × 25.78125 GBd continuous reception /<br>1 × 10.3125 GBd burst mode transmission, medium power class,<br>as specified in Clause 141  |
| 25/10GBASE-PQG-U3 | One single mode fiber, 1 × 25.78125 GBd continuous reception /<br>1 × 10.3125 GBd burst mode transmission, high power class,<br>as specified in Clause 141    |
| 25/10GBASE-PQX-D2 | One single mode fiber, 1 × 25.78125 GBd continuous transmission /<br>1 × 10.3125 GBd burst mode reception, medium power class,<br>as specified in Clause 141  |
| 25/10GBASE-PQX-D3 | One single mode fiber, 1 × 25.78125 GBd continuous transmission /<br>1 × 10.3125 GBd burst mode reception, high power class,<br>as specified in Clause 141    |
| 25/10GBASE-PQX-U2 | One single mode fiber, 1 × 25.78125 GBd continuous reception /<br>1 × 10.3125 GBd burst mode transmission, medium power class,<br>as specified in Clause 141  |
| 25/10GBASE-PQX-U3 | One single mode fiber, 1 × 25.78125 GBd continuous reception /<br>1 × 10.3125 GBd burst mode transmission, high power class,<br>as specified in Clause 141    |
| 25GBASE-PQG-D2    | One single mode fiber, 1 × 25.78125 GBd continuous transmission /<br>1 × 25.78125 GBd burst mode reception, medium power class,<br>as specified in Clause 141 |
| 25GBASE-PQG-D3    | One single mode fiber, 1 × 25.78125 GBd continuous transmission /<br>1 × 25.78125 GBd burst mode reception, high power class,<br>as specified in Clause 141   |
| 25GBASE-PQG-U2    | One single mode fiber, 1 × 25.78125 GBd continuous reception /<br>1 × 25.78125 GBd burst mode transmission, medium power class,<br>as specified in Clause 141 |
| 25GBASE-PQG-U3    | One single mode fiber, 1 × 25.78125 GBd continuous reception /<br>1 × 25.78125 GBd burst mode transmission, high power class,<br>as specified in Clause 141   |
| 25GBASE-PQX-D2    | One single mode fiber, 1 × 25.78125 GBd continuous transmission /<br>1 × 25.78125 GBd burst mode reception, medium power class,<br>as specified in Clause 141 |
| 25GBASE-PQX-D3    | One single mode fiber, 1 × 25.78125 GBd continuous transmission /<br>1 × 25.78125 GBd burst mode reception, high power class,<br>as specified in Clause 141   |
| 25GBASE-PQX-U2    | One single mode fiber, 1 × 25.78125 GBd continuous reception /<br>1 × 25.78125 GBd burst mode transmission, medium power class,<br>as specified in Clause 141 |
| 25GBASE-PQX-U3    | One single mode fiber, 1 × 25.78125 GBd continuous reception /<br>1 × 25.78125 GBd burst mode transmission, high power class,<br>as specified in Clause 141   |
| ...               |                                                                                                                                                               |

***Insert new entries in the APPROPRIATE SYNTAX section of 30.5.1.1.2 after the entry for 50GBASE-ER (inserted by IEEE Std 802.3cn-2019) as follows:***

|                   |                                                                                                                                                              |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ...               |                                                                                                                                                              |
| 50/10GBASE-PQG-D2 | One single mode fiber, 2 × 25.78125 GBd continuous transmission /<br>1 × 10.3125 GBd burst mode reception, medium power class,<br>as specified in Clause 141 |

|                   |                                                                                                                                                                       |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 50/10GBASE-PQG-D3 | One single mode fiber, $2 \times 25.78125$ GBd continuous transmission / $1 \times 10.3125$ GBd burst mode reception, high power class, as specified in Clause 141    |
| 50/10GBASE-PQG-U2 | One single mode fiber, $2 \times 25.78125$ GBd continuous reception / $1 \times 10.3125$ GBd burst mode transmission, medium power class, as specified in Clause 141  |
| 50/10GBASE-PQG-U3 | One single mode fiber, $2 \times 25.78125$ GBd continuous reception / $1 \times 10.3125$ GBd burst mode transmission, high power class, as specified in Clause 141    |
| 50/10GBASE-PQX-D2 | One single mode fiber, $2 \times 25.78125$ GBd continuous transmission / $1 \times 10.3125$ GBd burst mode reception, medium power class, as specified in Clause 141  |
| 50/10GBASE-PQX-D3 | One single mode fiber, $2 \times 25.78125$ GBd continuous transmission / $1 \times 10.3125$ GBd burst mode reception, high power class, as specified in Clause 141    |
| 50/10GBASE-PQX-U2 | One single mode fiber, $2 \times 25.78125$ GBd continuous reception / $1 \times 10.3125$ GBd burst mode transmission, medium power class, as specified in Clause 141  |
| 50/10GBASE-PQX-U3 | One single mode fiber, $2 \times 25.78125$ GBd continuous reception / $1 \times 10.3125$ GBd burst mode transmission, high power class, as specified in Clause 141    |
| 50/25GBASE-PQG-D2 | One single mode fiber, $2 \times 25.78125$ GBd continuous transmission / $1 \times 25.78125$ GBd burst mode reception, medium power class, as specified in Clause 141 |
| 50/25GBASE-PQG-D3 | One single mode fiber, $2 \times 25.78125$ GBd continuous transmission / $1 \times 25.78125$ GBd burst mode reception, high power class, as specified in Clause 141   |
| 50/25GBASE-PQG-U2 | One single mode fiber, $2 \times 25.78125$ GBd continuous reception / $1 \times 25.78125$ GBd burst mode transmission, medium power class, as specified in Clause 141 |
| 50/25GBASE-PQG-U3 | One single mode fiber, $2 \times 25.78125$ GBd continuous reception / $1 \times 25.78125$ GBd burst mode transmission, high power class, as specified in Clause 141   |
| 50/25GBASE-PQX-D2 | One single mode fiber, $2 \times 25.78125$ GBd continuous transmission / $1 \times 25.78125$ GBd burst mode reception, medium power class, as specified in Clause 141 |
| 50/25GBASE-PQX-D3 | One single mode fiber, $2 \times 25.78125$ GBd continuous transmission / $1 \times 25.78125$ GBd burst mode reception, high power class, as specified in Clause 141   |
| 50/25GBASE-PQX-U2 | One single mode fiber, $2 \times 25.78125$ GBd continuous reception / $1 \times 25.78125$ GBd burst mode transmission, medium power class, as specified in Clause 141 |
| 50/25GBASE-PQX-U3 | One single mode fiber, $2 \times 25.78125$ GBd continuous reception / $1 \times 25.78125$ GBd burst mode transmission, high power class, as specified in Clause 141   |
| 50GBASE-PQG-D2    | One single mode fiber, $2 \times 25.78125$ GBd continuous transmission / $2 \times 25.78125$ GBd burst mode reception, medium power class, as specified in Clause 141 |
| 50GBASE-PQG-D3    | One single mode fiber, $2 \times 25.78125$ GBd continuous transmission / $2 \times 25.78125$ GBd burst mode reception, high power class, as specified in Clause 141   |
| 50GBASE-PQG-U2    | One single mode fiber, $2 \times 25.78125$ GBd continuous reception / $2 \times 25.78125$ GBd burst mode transmission, medium power class, as specified in Clause 141 |

|                |                                                                                                                                                                             |
|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 50GBASE-PQG-U3 | One single mode fiber, $2 \times 25.78125$ GBd continuous reception /<br>$2 \times 25.78125$ GBd burst mode transmission, high power class,<br>as specified in Clause 141   |
| 50GBASE-PQX-D2 | One single mode fiber, $2 \times 25.78125$ GBd continuous transmission /<br>$2 \times 25.78125$ GBd burst mode reception, medium power class,<br>as specified in Clause 141 |
| 50GBASE-PQX-D3 | One single mode fiber, $2 \times 25.78125$ GBd continuous transmission /<br>$2 \times 25.78125$ GBd burst mode reception, high power class,<br>as specified in Clause 141   |
| 50GBASE-PQX-U2 | One single mode fiber, $2 \times 25.78125$ GBd continuous reception /<br>$2 \times 25.78125$ GBd burst mode transmission, medium power class,<br>as specified in Clause 141 |
| 50GBASE-PQX-U3 | One single mode fiber, $2 \times 25.78125$ GBd continuous reception /<br>$2 \times 25.78125$ GBd burst mode transmission, high power class,<br>as specified in Clause 141   |
| ...            |                                                                                                                                                                             |

## 45. Management Data Input/Output (MDIO) Interface

### 45.2 MDIO Interface Registers

#### 45.2.1 PMA/PMD registers

Change rows for 1.29 and 1.901 through 1.1099 in Table 45–3 as follows (unchanged rows not shown):

Table 45–3—PMA/PMD registers

| Register address             | Register name                              | Subclause          |
|------------------------------|--------------------------------------------|--------------------|
| ...                          |                                            |                    |
| 1.29                         | <del>Reserved</del> PMA/PMD control 3      | 45.2.1.23a         |
| ...                          |                                            |                    |
| 1.901 through 1.4099999      | Reserved                                   |                    |
| <u>1.1000 through 1.1002</u> | <u>Nx25G-EPON PMA/PMD extended ability</u> | <u>45.2.1.134a</u> |
| <u>1.1003 through 1.1099</u> | <u>Reserved</u>                            |                    |
| ...                          |                                            |                    |

Insert 45.2.1.23a after 45.2.1.23 as follows:

#### 45.2.1.23a PMA/PMD control 3 register (Register 1.29)

The assignment of bits in the PMA/PMD control 3 register is shown in Table 45–26a.

##### 45.2.1.23a.1 Downstream differential encoding (1.29.15)

Downstream differential encoding is selected using bit 1.29.15. This bit is read/write in the OLT and read only in the ONU with the default value of 0 (indicating that downstream differential encoding is not enabled).

In the OLT, this bit controls whether downstream differential encoding is selected for the transmit PMA output.

In the ONU, this bit indicates whether the downstream differential decoding is enabled in the ONU receive PMA.

##### 45.2.1.23a.2 PMA/PMD type selection (1.29.5:0)

The PMA/PMD type of the PMA/PMD is selected using bits 5 to 0. The PMA/PMD type abilities of the PMA/PMD are advertised in the Nx25G-EPON PMA/PMD extended ability registers (Registers 1.1000 through 1.1002, see 45.2.1.134a). A PMA/PMD shall ignore writes to the PMA/PMD type selection bits that select PMA/PMD types it has not advertised. It is the responsibility of the STA entity to ensure that mutually acceptable MMD types are applied consistently across all the MMDs on a particular PHY.

Table 45–26a—PMA/PMD control 3 register bit definitions

| Bit(s)    | Name                             | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | R/W <sup>a</sup>        |
|-----------|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| 1.29.15   | Downstream differential encoding | 1 = Downstream differential encoding enabled<br>0 = Downstream differential encoding disabled                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | R/W in OLT<br>RO in ONU |
| 1.29.14:6 | Reserved                         | Value always 0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | RO                      |
| 1.29.5:0  | PMA/PMD type selection           | 5 4 3 2 1 0<br>1 1 x x x x = Reserved<br>1 0 1 x x x = Reserved<br>1 0 0 1 1 1 = 50GBASE-PQX-U3<br>1 0 0 1 1 0 = 50GBASE-PQX-U2<br>1 0 0 1 0 1 = 50GBASE-PQX-D3<br>1 0 0 1 0 0 = 50GBASE-PQX-D2<br>1 0 0 0 1 1 = 50GBASE-PQG-U3<br>1 0 0 0 1 0 = 50GBASE-PQG-U2<br>1 0 0 0 0 1 = 50GBASE-PQG-D3<br>1 0 0 0 0 0 = 50GBASE-PQG-D2<br>0 1 1 1 1 1 = 50/25GBASE-PQX-U3<br>0 1 1 1 1 0 = 50/25GBASE-PQX-U2<br>0 1 1 1 0 1 = 50/25GBASE-PQX-D3<br>0 1 1 1 0 0 = 50/25GBASE-PQX-D2<br>0 1 1 0 1 1 = 50/25GBASE-PQG-U3<br>0 1 1 0 1 0 = 50/25GBASE-PQG-U2<br>0 1 1 0 0 1 = 50/25GBASE-PQG-D3<br>0 1 1 0 0 0 = 50/25GBASE-PQG-D2<br>0 1 0 1 1 1 = 50/10GBASE-PQX-U3<br>0 1 0 1 1 0 = 50/10GBASE-PQX-U2<br>0 1 0 1 0 1 = 50/10GBASE-PQX-D3<br>0 1 0 1 0 0 = 50/10GBASE-PQX-D2<br>0 1 0 0 1 1 = 50/10GBASE-PQG-U3<br>0 1 0 0 1 0 = 50/10GBASE-PQG-U2<br>0 1 0 0 0 1 = 50/10GBASE-PQG-D3<br>0 1 0 0 0 0 = 50/10GBASE-PQG-D2<br>0 0 1 1 1 1 = 25GBASE-PQX-U3<br>0 0 1 1 1 0 = 25GBASE-PQX-U2<br>0 0 1 1 0 1 = 25GBASE-PQX-D3<br>0 0 1 1 0 0 = 25GBASE-PQX-D2<br>0 0 1 0 1 1 = 25GBASE-PQG-U3<br>0 0 1 0 1 0 = 25GBASE-PQG-U2<br>0 0 1 0 0 1 = 25GBASE-PQG-D3<br>0 0 1 0 0 0 = 25GBASE-PQG-D2<br>0 0 0 1 1 1 = 25/10GBASE-PQX-U3<br>0 0 0 1 1 0 = 25/10GBASE-PQX-U2<br>0 0 0 1 0 1 = 25/10GBASE-PQX-D3<br>0 0 0 1 0 0 = 25/10GBASE-PQX-D2<br>0 0 0 0 1 1 = 25/10GBASE-PQG-U3<br>0 0 0 0 1 0 = 25/10GBASE-PQG-U2<br>0 0 0 0 0 1 = 25/10GBASE-PQG-D3<br>0 0 0 0 0 0 = 25/10GBASE-PQG-D2 | R/W                     |

<sup>a</sup>R/W = Read/Write, RO = Read only

*Insert 45.2.1.134a after 45.2.1.134 as follows:*

**45.2.1.134a Nx25G-EPON PMA/PMD extended ability register (Registers 1.1000 through 1.1002)**

The assignment of bits in the Nx25G-EPON PMA/PMD extended ability register is shown in Table 45–103a.

**Table 45–103a—Nx25G-EPON PMA/PMD extended ability register bit definitions**

| Bit(s)    | Name              | Description                                                                                              | R/W <sup>a</sup> |
|-----------|-------------------|----------------------------------------------------------------------------------------------------------|------------------|
| 1.1000.15 | 25GBASE-PQX-U3    | 1 = PMA/PMD is able to perform 25GBASE-PQX-U3<br>0 = PMA/PMD is not able to perform 25GBASE-PQX-U3       | RO               |
| 1.1000.14 | 25GBASE-PQX-U2    | 1 = PMA/PMD is able to perform 25GBASE-PQX-U2<br>0 = PMA/PMD is not able to perform 25GBASE-PQX-U2       | RO               |
| 1.1000.13 | 25GBASE-PQX-D3    | 1 = PMA/PMD is able to perform 25GBASE-PQX-D3<br>0 = PMA/PMD is not able to perform 25GBASE-PQX-D3       | RO               |
| 1.1000.12 | 25GBASE-PQX-D2    | 1 = PMA/PMD is able to perform 25GBASE-PQX-D2<br>0 = PMA/PMD is not able to perform 25GBASE-PQX-D2       | RO               |
| 1.1000.11 | 25GBASE-PQG-U3    | 1 = PMA/PMD is able to perform 25GBASE-PQG-U3<br>0 = PMA/PMD is not able to perform 25GBASE-PQG-U3       | RO               |
| 1.1000.10 | 25GBASE-PQG-U2    | 1 = PMA/PMD is able to perform 25GBASE-PQG-U2<br>0 = PMA/PMD is not able to perform 25GBASE-PQG-U2       | RO               |
| 1.1000.9  | 25GBASE-PQG-D3    | 1 = PMA/PMD is able to perform 25GBASE-PQG-D3<br>0 = PMA/PMD is not able to perform 25GBASE-PQG-D3       | RO               |
| 1.1000.8  | 25GBASE-PQG-D2    | 1 = PMA/PMD is able to perform 25GBASE-PQG-D2<br>0 = PMA/PMD is not able to perform 25GBASE-PQG-D2       | RO               |
| 1.1000.7  | 25/10GBASE-PQX-U3 | 1 = PMA/PMD is able to perform 25/10GBASE-PQX-U3<br>0 = PMA/PMD is not able to perform 25/10GBASE-PQX-U3 | RO               |
| 1.1000.6  | 25/10GBASE-PQX-U2 | 1 = PMA/PMD is able to perform 25/10GBASE-PQX-U2<br>0 = PMA/PMD is not able to perform 25/10GBASE-PQX-U2 | RO               |
| 1.1000.5  | 25/10GBASE-PQX-D3 | 1 = PMA/PMD is able to perform 25/10GBASE-PQX-D3<br>0 = PMA/PMD is not able to perform 25/10GBASE-PQX-D3 | RO               |
| 1.1000.4  | 25/10GBASE-PQX-D2 | 1 = PMA/PMD is able to perform 25/10GBASE-PQX-D2<br>0 = PMA/PMD is not able to perform 25/10GBASE-PQX-D2 | RO               |
| 1.1000.3  | 25/10GBASE-PQG-U3 | 1 = PMA/PMD is able to perform 25/10GBASE-PQG-U3<br>0 = PMA/PMD is not able to perform 25/10GBASE-PQG-U3 | RO               |
| 1.1000.2  | 25/10GBASE-PQG-U2 | 1 = PMA/PMD is able to perform 25/10GBASE-PQG-U2<br>0 = PMA/PMD is not able to perform 25/10GBASE-PQG-U2 | RO               |
| 1.1000.1  | 25/10GBASE-PQG-D3 | 1 = PMA/PMD is able to perform 25/10GBASE-PQG-D3<br>0 = PMA/PMD is not able to perform 25/10GBASE-PQG-D3 | RO               |
| 1.1000.0  | 25/10GBASE-PQG-D2 | 1 = PMA/PMD is able to perform 25/10GBASE-PQG-D2<br>0 = PMA/PMD is not able to perform 25/10GBASE-PQG-D2 | RO               |
| 1.1001.15 | 50/25GBASE-PQX-U3 | 1 = PMA/PMD is able to perform 50/25GBASE-PQX-U3<br>0 = PMA/PMD is not able to perform 50/25GBASE-PQX-U3 | RO               |

**Table 45–103a—Nx25G-EPON PMA/PMD extended ability register bit definitions (continued)**

| Bit(s)      | Name              | Description                                                                                              | R/W <sup>a</sup> |
|-------------|-------------------|----------------------------------------------------------------------------------------------------------|------------------|
| 1.1001.14   | 50/25GBASE-PQX-U2 | 1 = PMA/PMD is able to perform 50/25GBASE-PQX-U2<br>0 = PMA/PMD is not able to perform 50/25GBASE-PQX-U2 | RO               |
| 1.1001.13   | 50/25GBASE-PQX-D3 | 1 = PMA/PMD is able to perform 50/25GBASE-PQX-D3<br>0 = PMA/PMD is not able to perform 50/25GBASE-PQX-D3 | RO               |
| 1.1001.12   | 50/25GBASE-PQX-D2 | 1 = PMA/PMD is able to perform 50/25GBASE-PQX-D2<br>0 = PMA/PMD is not able to perform 50/25GBASE-PQX-D2 | RO               |
| 1.1001.11   | 50/25GBASE-PQG-U3 | 1 = PMA/PMD is able to perform 50/25GBASE-PQG-U3<br>0 = PMA/PMD is not able to perform 50/25GBASE-PQG-U3 | RO               |
| 1.1001.10   | 50/25GBASE-PQG-U2 | 1 = PMA/PMD is able to perform 50/25GBASE-PQG-U2<br>0 = PMA/PMD is not able to perform 50/25GBASE-PQG-U2 | RO               |
| 1.1001.9    | 50/25GBASE-PQG-D3 | 1 = PMA/PMD is able to perform 50/25GBASE-PQG-D3<br>0 = PMA/PMD is not able to perform 50/25GBASE-PQG-D3 | RO               |
| 1.1001.8    | 50/25GBASE-PQG-D2 | 1 = PMA/PMD is able to perform 50/25GBASE-PQG-D2<br>0 = PMA/PMD is not able to perform 50/25GBASE-PQG-D2 | RO               |
| 1.1001.7    | 50/10GBASE-PQX-U3 | 1 = PMA/PMD is able to perform 50/10GBASE-PQX-U3<br>0 = PMA/PMD is not able to perform 50/10GBASE-PQX-U3 | RO               |
| 1.1001.6    | 50/10GBASE-PQX-U2 | 1 = PMA/PMD is able to perform 50/10GBASE-PQX-U2<br>0 = PMA/PMD is not able to perform 50/10GBASE-PQX-U2 | RO               |
| 1.1001.5    | 50/10GBASE-PQX-D3 | 1 = PMA/PMD is able to perform 50/10GBASE-PQX-D3<br>0 = PMA/PMD is not able to perform 50/10GBASE-PQX-D3 | RO               |
| 1.1001.4    | 50/10GBASE-PQX-D2 | 1 = PMA/PMD is able to perform 50/10GBASE-PQX-D2<br>0 = PMA/PMD is not able to perform 50/10GBASE-PQX-D2 | RO               |
| 1.1001.3    | 50/10GBASE-PQG-U3 | 1 = PMA/PMD is able to perform 50/10GBASE-PQG-U3<br>0 = PMA/PMD is not able to perform 50/10GBASE-PQG-U3 | RO               |
| 1.1001.2    | 50/10GBASE-PQG-U2 | 1 = PMA/PMD is able to perform 50/10GBASE-PQG-U2<br>0 = PMA/PMD is not able to perform 50/10GBASE-PQG-U2 | RO               |
| 1.1001.1    | 50/10GBASE-PQG-D3 | 1 = PMA/PMD is able to perform 50/10GBASE-PQG-D3<br>0 = PMA/PMD is not able to perform 50/10GBASE-PQG-D3 | RO               |
| 1.1001.0    | 50/10GBASE-PQG-D2 | 1 = PMA/PMD is able to perform 50/10GBASE-PQG-D2<br>0 = PMA/PMD is not able to perform 50/10GBASE-PQG-D2 | RO               |
| 1.1002.15:8 | Reserved          | Value always 0                                                                                           | RO               |
| 1.1002.7    | 50GBASE-PQX-U3    | 1 = PMA/PMD is able to perform 50GBASE-PQX-U3<br>0 = PMA/PMD is not able to perform 50GBASE-PQX-U3       | RO               |
| 1.1002.6    | 50GBASE-PQX-U2    | 1 = PMA/PMD is able to perform 50GBASE-PQX-U2<br>0 = PMA/PMD is not able to perform 50GBASE-PQX-U2       | RO               |
| 1.1002.5    | 50GBASE-PQX-D3    | 1 = PMA/PMD is able to perform 50GBASE-PQX-D3<br>0 = PMA/PMD is not able to perform 50GBASE-PQX-D3       | RO               |
| 1.1002.4    | 50GBASE-PQX-D2    | 1 = PMA/PMD is able to perform 50GBASE-PQX-D2<br>0 = PMA/PMD is not able to perform 50GBASE-PQX-D2       | RO               |
| 1.1002.3    | 50GBASE-PQG-U3    | 1 = PMA/PMD is able to perform 50GBASE-PQG-U3<br>0 = PMA/PMD is not able to perform 50GBASE-PQG-U3       | RO               |

**Table 45–103a—Nx25G-EPON PMA/PMD extended ability register bit definitions (continued)**

| Bit(s)   | Name           | Description                                                                                        | R/W <sup>a</sup> |
|----------|----------------|----------------------------------------------------------------------------------------------------|------------------|
| 1.1002.2 | 50GBASE-PQG-U2 | 1 = PMA/PMD is able to perform 50GBASE-PQG-U2<br>0 = PMA/PMD is not able to perform 50GBASE-PQG-U2 | RO               |
| 1.1002.1 | 50GBASE-PQG-D3 | 1 = PMA/PMD is able to perform 50GBASE-PQG-D3<br>0 = PMA/PMD is not able to perform 50GBASE-PQG-D3 | RO               |
| 1.1002.0 | 50GBASE-PQG-D2 | 1 = PMA/PMD is able to perform 50GBASE-PQG-D2<br>0 = PMA/PMD is not able to perform 50GBASE-PQG-D2 | RO               |

<sup>a</sup>RO = Read only**45.2.1.134a.1 25GBASE-PQX-U3 (1.1000.15)**

When read as a one, bit 1.1000.15 indicates that the PMA/PMD is able to support a 25GBASE-PQX-U3 PMA/PMD type. When read as a zero, bit 1.1000.15 indicates that the PMA/PMD is not able to support a 25GBASE-PQX-U3 PMA/PMD type.

**45.2.1.134a.2 25GBASE-PQX-U2 (1.1000.14)**

When read as a one, bit 1.1000.14 indicates that the PMA/PMD is able to support a 25GBASE-PQX-U2 PMA/PMD type. When read as a zero, bit 1.1000.14 indicates that the PMA/PMD is not able to support a 25GBASE-PQX-U2 PMA/PMD type.

**45.2.1.134a.3 25GBASE-PQX-D3 (1.1000.13)**

When read as a one, bit 1.1000.13 indicates that the PMA/PMD is able to support a 25GBASE-PQX-D3 PMA/PMD type. When read as a zero, bit 1.1000.13 indicates that the PMA/PMD is not able to support a 25GBASE-PQX-D3 PMA/PMD type.

**45.2.1.134a.4 25GBASE-PQX-D2 (1.1000.12)**

When read as a one, bit 1.1000.12 indicates that the PMA/PMD is able to support a 25GBASE-PQX-D2 PMA/PMD type. When read as a zero, bit 1.1000.12 indicates that the PMA/PMD is not able to support a 25GBASE-PQX-D2 PMA/PMD type.

**45.2.1.134a.5 25GBASE-PQG-U3 (1.1000.11)**

When read as a one, bit 1.1000.11 indicates that the PMA/PMD is able to support a 25GBASE-PQG-U3 PMA/PMD type. When read as a zero, bit 1.1000.11 indicates that the PMA/PMD is not able to support a 25GBASE-PQG-U3 PMA/PMD type.

**45.2.1.134a.6 25GBASE-PQG-U2 (1.1000.10)**

When read as a one, bit 1.1000.10 indicates that the PMA/PMD is able to support a 25GBASE-PQG-U2 PMA/PMD type. When read as a zero, bit 1.1000.10 indicates that the PMA/PMD is not able to support a 25GBASE-PQG-U2 PMA/PMD type.

**45.2.1.134a.7 25GBASE-PQG-D3 (1.1000.9)**

When read as a one, bit 1.1000.9 indicates that the PMA/PMD is able to support a 25GBASE-PQG-D3 PMA/PMD type. When read as a zero, bit 1.1000.9 indicates that the PMA/PMD is not able to support a 25GBASE-PQG-D3 PMA/PMD type.

**45.2.1.134a.8 25GBASE-PQG-D2 (1.1000.8)**

When read as a one, bit 1.1000.8 indicates that the PMA/PMD is able to support a 25GBASE-PQG-D2 PMA/PMD type. When read as a zero, bit 1.1000.8 indicates that the PMA/PMD is not able to support a 25GBASE-PQG-D2 PMA/PMD type.

**45.2.1.134a.9 25/10GBASE-PQX-U3 (1.1000.7)**

When read as a one, bit 1.1000.7 indicates that the PMA/PMD is able to support a 25/10GBASE-PQX-U3 PMA/PMD type. When read as a zero, bit 1.1000.7 indicates that the PMA/PMD is not able to support a 25/10GBASE-PQX-U3 PMA/PMD type.

**45.2.1.134a.10 25/10GBASE-PQX-U2 (1.1000.6)**

When read as a one, bit 1.1000.6 indicates that the PMA/PMD is able to support a 25/10GBASE-PQX-U2 PMA/PMD type. When read as a zero, bit 1.1000.6 indicates that the PMA/PMD is not able to support a 25/10GBASE-PQX-U2 PMA/PMD type.

**45.2.1.134a.11 25/10GBASE-PQX-D3 (1.1000.5)**

When read as a one, bit 1.1000.5 indicates that the PMA/PMD is able to support a 25/10GBASE-PQX-D3 PMA/PMD type. When read as a zero, bit 1.1000.5 indicates that the PMA/PMD is not able to support a 25/10GBASE-PQX-D3 PMA/PMD type.

**45.2.1.134a.12 25/10GBASE-PQX-D2 (1.1000.4)**

When read as a one, bit 1.1000.4 indicates that the PMA/PMD is able to support a 25/10GBASE-PQX-D2 PMA/PMD type. When read as a zero, bit 1.1000.4 indicates that the PMA/PMD is not able to support a 25/10GBASE-PQX-D2 PMA/PMD type.

**45.2.1.134a.13 25/10GBASE-PQG-U3 (1.1000.3)**

When read as a one, bit 1.1000.3 indicates that the PMA/PMD is able to support a 25/10GBASE-PQG-U3 PMA/PMD type. When read as a zero, bit 1.1000.3 indicates that the PMA/PMD is not able to support a 25/10GBASE-PQG-U3 PMA/PMD type.

**45.2.1.134a.14 25/10GBASE-PQG-U2 (1.1000.2)**

When read as a one, bit 1.1000.2 indicates that the PMA/PMD is able to support a 25/10GBASE-PQG-U2 PMA/PMD type. When read as a zero, bit 1.1000.2 indicates that the PMA/PMD is not able to support a 25/10GBASE-PQG-U2 PMA/PMD type.

**45.2.1.134a.15 25/10GBASE-PQG-D3 (1.1000.1)**

When read as a one, bit 1.1000.1 indicates that the PMA/PMD is able to support a 25/10GBASE-PQG-D3 PMA/PMD type. When read as a zero, bit 1.1000.1 indicates that the PMA/PMD is not able to support a 25/10GBASE-PQG-D3 PMA/PMD type.

**45.2.1.134a.16 25/10GBASE-PQG-D2 (1.1000.0)**

When read as a one, bit 1.1000.0 indicates that the PMA/PMD is able to support a 25/10GBASE-PQG-D2 PMA/PMD type. When read as a zero, bit 1.1000.0 indicates that the PMA/PMD is not able to support a 25/10GBASE-PQG-D2 PMA/PMD type.

**45.2.1.134a.17 50/25GBASE-PQX-U3 (1.1001.15)**

When read as a one, bit 1.1001.15 indicates that the PMA/PMD is able to support a 50/25GBASE-PQX-U3 PMA/PMD type. When read as a zero, bit 1.1001.15 indicates that the PMA/PMD is not able to support a 50/25GBASE-PQX-U3 PMA/PMD type.

**45.2.1.134a.18 50/25GBASE-PQX-U2 (1.1001.14)**

When read as a one, bit 1.1001.14 indicates that the PMA/PMD is able to support a 50/25GBASE-PQX-U2 PMA/PMD type. When read as a zero, bit 1.1001.14 indicates that the PMA/PMD is not able to support a 50/25GBASE-PQX-U2 PMA/PMD type.

**45.2.1.134a.19 50/25GBASE-PQX-D3 (1.1001.13)**

When read as a one, bit 1.1001.13 indicates that the PMA/PMD is able to support a 50/25GBASE-PQX-D3 PMA/PMD type. When read as a zero, bit 1.1001.13 indicates that the PMA/PMD is not able to support a 50/25GBASE-PQX-D3 PMA/PMD type.

**45.2.1.134a.20 50/25GBASE-PQX-D2 (1.1001.12)**

When read as a one, bit 1.1001.12 indicates that the PMA/PMD is able to support a 50/25GBASE-PQX-D2 PMA/PMD type. When read as a zero, bit 1.1001.12 indicates that the PMA/PMD is not able to support a 50/25GBASE-PQX-D2 PMA/PMD type.

**45.2.1.134a.21 50/25GBASE-PQG-U3 (1.1001.11)**

When read as a one, bit 1.1001.11 indicates that the PMA/PMD is able to support a 50/25GBASE-PQG-U3 PMA/PMD type. When read as a zero, bit 1.1001.11 indicates that the PMA/PMD is not able to support a 50/25GBASE-PQG-U3 PMA/PMD type.

**45.2.1.134a.22 50/25GBASE-PQG-U2 (1.1001.10)**

When read as a one, bit 1.1001.10 indicates that the PMA/PMD is able to support a 50/25GBASE-PQG-U2 PMA/PMD type. When read as a zero, bit 1.1001.10 indicates that the PMA/PMD is not able to support a 50/25GBASE-PQG-U2 PMA/PMD type.

**45.2.1.134a.23 50/25GBASE-PQG-D3 (1.1001.9)**

When read as a one, bit 1.1001.9 indicates that the PMA/PMD is able to support a 50/25GBASE-PQG-D3 PMA/PMD type. When read as a zero, bit 1.1001.9 indicates that the PMA/PMD is not able to support a 50/25GBASE-PQG-D3 PMA/PMD type.

**45.2.1.134a.24 50/25GBASE-PQG-D2 (1.1001.8)**

When read as a one, bit 1.1001.8 indicates that the PMA/PMD is able to support a 50/25GBASE-PQG-D2 PMA/PMD type. When read as a zero, bit 1.1001.8 indicates that the PMA/PMD is not able to support a 50/25GBASE-PQG-D2 PMA/PMD type.

**45.2.1.134a.25 50/10GBASE-PQX-U3 (1.1001.7)**

When read as a one, bit 1.1001.7 indicates that the PMA/PMD is able to support a 50/10GBASE-PQX-U3 PMA/PMD type. When read as a zero, bit 1.1001.7 indicates that the PMA/PMD is not able to support a 50/10GBASE-PQX-U3 PMA/PMD type.

**45.2.1.134a.26 50/10GBASE-PQX-U2 (1.1001.6)**

When read as a one, bit 1.1001.6 indicates that the PMA/PMD is able to support a 50/10GBASE-PQX-U2 PMA/PMD type. When read as a zero, bit 1.1001.6 indicates that the PMA/PMD is not able to support a 50/10GBASE-PQX-U2 PMA/PMD type.

**45.2.1.134a.27 50/10GBASE-PQX-D3 (1.1001.5)**

When read as a one, bit 1.1001.5 indicates that the PMA/PMD is able to support a 50/10GBASE-PQX-D3 PMA/PMD type. When read as a zero, bit 1.1001.5 indicates that the PMA/PMD is not able to support a 50/10GBASE-PQX-D3 PMA/PMD type.

**45.2.1.134a.28 50/10GBASE-PQX-D2 (1.1001.4)**

When read as a one, bit 1.1001.4 indicates that the PMA/PMD is able to support a 50/10GBASE-PQX-D2 PMA/PMD type. When read as a zero, bit 1.1001.4 indicates that the PMA/PMD is not able to support a 50/10GBASE-PQX-D2 PMA/PMD type.

**45.2.1.134a.29 50/10GBASE-PQG-U3 (1.1001.3)**

When read as a one, bit 1.1001.3 indicates that the PMA/PMD is able to support a 50/10GBASE-PQG-U3 PMA/PMD type. When read as a zero, bit 1.1001.3 indicates that the PMA/PMD is not able to support a 50/10GBASE-PQG-U3 PMA/PMD type.

**45.2.1.134a.30 50/10GBASE-PQG-U2 (1.1001.2)**

When read as a one, bit 1.1001.2 indicates that the PMA/PMD is able to support a 50/10GBASE-PQG-U2 PMA/PMD type. When read as a zero, bit 1.1001.2 indicates that the PMA/PMD is not able to support a 50/10GBASE-PQG-U2 PMA/PMD type.

**45.2.1.134a.31 50/10GBASE-PQG-D3 (1.1001.1)**

When read as a one, bit 1.1001.1 indicates that the PMA/PMD is able to support a 50/10GBASE-PQG-D3 PMA/PMD type. When read as a zero, bit 1.1001.1 indicates that the PMA/PMD is not able to support a 50/10GBASE-PQG-D3 PMA/PMD type.

**45.2.1.134a.32 50/10GBASE-PQG-D2 (1.1001.0)**

When read as a one, bit 1.1001.0 indicates that the PMA/PMD is able to support a 50/10GBASE-PQG-D2 PMA/PMD type. When read as a zero, bit 1.1001.0 indicates that the PMA/PMD is not able to support a 50/10GBASE-PQG-D2 PMA/PMD type.

**45.2.1.134a.33 50GBASE-PQX-U3 (1.1002.7)**

When read as a one, bit 1.1002.7 indicates that the PMA/PMD is able to support a 50GBASE-PQX-U3 PMA/PMD type. When read as a zero, bit 1.1002.7 indicates that the PMA/PMD is not able to support a 50GBASE-PQX-U3 PMA/PMD type.

**45.2.1.134a.34 50GBASE-PQX-U2 (1.1002.6)**

When read as a one, bit 1.1002.6 indicates that the PMA/PMD is able to support a 50GBASE-PQX-U2 PMA/PMD type. When read as a zero, bit 1.1002.6 indicates that the PMA/PMD is not able to support a 50GBASE-PQX-U2 PMA/PMD type.

**45.2.1.134a.35 50GBASE-PQX-D3 (1.1002.5)**

When read as a one, bit 1.1002.5 indicates that the PMA/PMD is able to support a 50GBASE-PQX-D3 PMA/PMD type. When read as a zero, bit 1.1002.5 indicates that the PMA/PMD is not able to support a 50GBASE-PQX-D3 PMA/PMD type.

**45.2.1.134a.36 50GBASE-PQX-D2 (1.1002.4)**

When read as a one, bit 1.1002.4 indicates that the PMA/PMD is able to support a 50GBASE-PQX-D2 PMA/PMD type. When read as a zero, bit 1.1002.4 indicates that the PMA/PMD is not able to support a 50GBASE-PQX-D2 PMA/PMD type.

**45.2.1.134a.37 50GBASE-PQG-U3 (1.1002.3)**

When read as a one, bit 1.1002.3 indicates that the PMA/PMD is able to support a 50GBASE-PQG-U3 PMA/PMD type. When read as a zero, bit 1.1002.3 indicates that the PMA/PMD is not able to support a 50GBASE-PQG-U3 PMA/PMD type.

**45.2.1.134a.38 50GBASE-PQG-U2 (1.1002.2)**

When read as a one, bit 1.1002.2 indicates that the PMA/PMD is able to support a 50GBASE-PQG-U2 PMA/PMD type. When read as a zero, bit 1.1002.2 indicates that the PMA/PMD is not able to support a 50GBASE-PQG-U2 PMA/PMD type.

**45.2.1.134a.39 50GBASE-PQG-D3 (1.1002.1)**

When read as a one, bit 1.1002.1 indicates that the PMA/PMD is able to support a 50GBASE-PQG-D3 PMA/PMD type. When read as a zero, bit 1.1002.1 indicates that the PMA/PMD is not able to support a 50GBASE-PQG-D3 PMA/PMD type.

**45.2.1.134a.40 50GBASE-PQG-D2 (1.1002.0)**

When read as a one, bit 1.1002.0 indicates that the PMA/PMD is able to support a 50GBASE-PQG-D2 PMA/PMD type. When read as a zero, bit 1.1002.0 indicates that the PMA/PMD is not able to support a 50GBASE-PQG-D2 PMA/PMD type.

**45.2.3 PCS registers**

*Change the rows for registers 3.76 through 3.199 in Table 45–176 as follows (unchanged rows not shown):*

**Table 45–176—PCS registers**

| Register address                   | Register name                                                                                                    | Subclause             |
|------------------------------------|------------------------------------------------------------------------------------------------------------------|-----------------------|
| ...                                |                                                                                                                  |                       |
| 3.76, 3.77                         | <del>10/1GBASE-PRX and 10GBASE-PR</del> 10G-EPON and Nx25G-EPON corrected FEC codewords counter                  | 45.2.3.41             |
| 3.78, 3.79                         | <del>10/1GBASE-PRX and 10GBASE-PR</del> 10G-EPON and Nx25G-EPON uncorrected FEC codewords counter                | 45.2.3.42             |
| 3.80                               | 10GBASE-PR <del>and</del> 10/1GBASE-PRX <del> and</del> Nx25G-EPON BER monitor <del>interval</del> timer control | 45.2.3.43             |
| 3.81                               | 10GBASE-PR <del>and</del> 10/1GBASE-PRX <del> and</del> Nx25G-EPON BER monitor status                            | 45.2.3.44             |
| 3.82                               | 10GBASE-PR <del>and</del> 10/1GBASE-PRX <del> and</del> Nx25G-EPON BER monitor threshold control                 | 45.2.3.45             |
| <del>3.83 through 3.134</del>      | <del>Nx25G-EPON synchronization pattern</del>                                                                    | <del>45.2.3.45a</del> |
| <del>3.833.135 through 3.199</del> | Reserved                                                                                                         |                       |
| ...                                |                                                                                                                  |                       |

**45.2.3.1 PCS control 1 register (Register 3.0)**

*Change the row for bits 3.0.5:2 in Table 45–177 (as modified IEEE Std 802.cd-2018) as follows (unchanged rows not shown):*

**Table 45–177—PCS control 1 register bit definitions**

| Bit(s)  | Name            | Description                                                                                                                                                                                                                                                                                                                      | R/W <sup>a</sup> |
|---------|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| ...     |                 |                                                                                                                                                                                                                                                                                                                                  |                  |
| 3.0.5:2 | Speed selection | 5 4 3 2<br>1 1 x x = Reserved<br>1 0 1 1 = <del>Reserved</del> 25/10 Gb/s<br>1 0 1 0 = 400 Gb/s<br>1 0 0 1 = 200 Gb/s<br>1 0 0 0 = 5 Gb/s<br>0 1 1 1 = 2.5 Gb/s<br>0 1 1 0 = 50 Gb/s<br>0 1 0 1 = 25 Gb/s<br>0 1 0 0 = 100 Gb/s<br>0 0 1 1 = 40 Gb/s<br>0 0 1 0 = 10/1 Gb/s<br>0 0 0 1 = 10PASS-TS/2BASE-TL<br>0 0 0 0 = 10 Gb/s | R/W              |
| ...     |                 |                                                                                                                                                                                                                                                                                                                                  |                  |

<sup>a</sup>RO = Read only, R/W = Read/Write, SC = Self-clearing

**45.2.3.6 PCS control 2 register (Register 3.7)**

*Change Table 45–180 (as modified by IEEE Std 802.3cb-2018 and IEEE Std 802.cd-2018) as follows (unchanged rows not shown):*

**Table 45–180—PCS control 2 register bit definitions**

| Bit(s)                | Name               | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | R/W <sup>a</sup> |
|-----------------------|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| 3.7.15:4 <del>5</del> | Reserved           | Value always 0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | RO               |
| 3.7.3 <del>4</del> :0 | PCS type selection | <del>4 3 2 1 0</del><br><del>1 1 x x x = reserved</del><br><del>1 0 1 x x = reserved</del><br><del>1 0 0 1 1 = Select 25GBASE-PQ PCS type</del><br><del>1 0 0 1 0 = Select 25/10GBASE-PQ PCS type</del><br><del>1 0 0 0 1 = Select 25GBASE-PQ PCS type, Tx only</del><br><del>1 0 0 0 0 = Select 25GBASE-PQ PCS type, Rx only</del><br><del>0 1 1 1 1 = Select 5GBASE-R PCS type</del><br><del>0 1 1 1 0 = Select 2.5GBASE-X PCS type</del><br><del>0 1 1 0 1 = Select 400GBASE-R PCS type</del><br><del>0 1 1 0 0 = Select 200GBASE-R PCS type</del><br><del>0 1 0 1 1 = Select 5GBASE-T PCS type</del><br><del>0 1 0 1 0 = Select 2.5GBASE-T PCS type</del><br><del>0 1 0 0 1 = Select 25GBASE-T PCS type</del><br><del>0 1 0 0 0 = Select 50GBASE-R PCS type</del><br><del>0 0 1 1 1 = Select 25GBASE-R PCS type</del><br><del>0 0 1 1 0 = Select 40GBASE-T PCS type</del><br><del>0 0 1 0 1 = Select 100GBASE-R PCS type</del><br><del>0 0 1 0 0 = Select 40GBASE-R PCS type</del><br><del>0 0 0 1 1 = Select 10GBASE-T PCS type</del><br><del>0 0 0 1 0 = Select 10GBASE-W PCS type</del><br><del>0 0 0 0 1 = Select 10GBASE-X PCS type</del><br><del>0 0 0 0 0 = Select 10GBASE-R PCS type</del> | R/W              |

<sup>a</sup>RO = Read only, R/W = Read/Write

*Change the title and text of 45.2.3.6.1 as follows:*

**45.2.3.6.1 PCS type selection (3.7.3~~4~~:0)**

The PCS type shall be selected using bits ~~34~~ through 0. The PCS type abilities of the PCS are advertised in bits ~~3.8.9:0, 3.8.7:0, and 3.9.47:0~~. A PCS shall ignore writes to the PCS type selection bits that select PCS types it has not advertised in the PCS status 2 register ~~or the PCS status 3 register~~. It is the responsibility of the STA entity to ensure that mutually acceptable MMD types are applied consistently across all the MMDs on a particular PHY. The PCS type selection defaults to a supported ability.

**45.2.3.8 PCS status 3 register (Register 3.9)**

*Change the row for bits 3.9.15:4 in Table 45–182 (as modified by IEEE Std 802.3cb-2018) as follows (unchanged rows not shown):*

**Table 45–182—PCS status 3 register bit definitions**

| Bit(s)       | Name                              | Description                                                                                                                        | R/W <sup>a</sup> |
|--------------|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------|------------------|
| 3.9.15:48    | Reserved                          | Value always 0                                                                                                                     | RO               |
| <u>3.9.7</u> | <u>25GBASE-PQ capable</u>         | <u>1 = PCS is able to support 25GBASE-PQ PCS type</u><br><u>0 = PCS is not able to support 25GBASE-PQ PCS type</u>                 | <u>RO</u>        |
| <u>3.9.6</u> | <u>25/10GBASE-PQ capable</u>      | <u>1 = PCS is able to support 25/10GBASE-PQ PCS type</u><br><u>0 = PCS is not able to support 25/10GBASE-PQ PCS type</u>           | <u>RO</u>        |
| <u>3.9.5</u> | <u>25GBASE-PQ Rx only capable</u> | <u>1 = PCS is able to support 25GBASE-PQ Rx only PCS type</u><br><u>0 = PCS is not able to support 25GBASE-PQ Rx only PCS type</u> | <u>RO</u>        |
| <u>3.9.4</u> | <u>25GBASE-PQ Tx only capable</u> | <u>1 = PCS is able to support 25GBASE-PQ Tx only PCS type</u><br><u>0 = PCS is not able to support 25GBASE-PQ Tx only PCS type</u> | <u>RO</u>        |
| ...          |                                   |                                                                                                                                    |                  |

<sup>a</sup>RO = Read only

*Insert 45.2.3.8.aa through 45.2.3.8.ad (before 45.2.3.8.a as inserted by IEEE Std 802.3cb-2018) as follows:*

**45.2.3.8.aa 25GBASE-PQ capable (3.9.7)**

When read as a one, bit 3.9.7 indicates that the PCS is able to support the 25GBASE-PQ PCS type. When read as a zero, bit 3.9.7 indicates that the PCS is not able to support the 25GBASE-PQ PCS type.

**45.2.3.8.ab 25/10GBASE-PQ capable (3.9.6)**

When read as a one, bit 3.9.6 indicates that the PCS is able to support the 25/10GBASE-PQ PCS type. When read as a zero, bit 3.9.6 indicates that the PCS is not able to support the 25/10GBASE-PQ PCS type.

**45.2.3.8.ac 25GBASE-PQ Rx only capable (3.9.5)**

When read as a one, bit 3.9.5 indicates that the PCS is able to support the 25GBASE-PQ Rx only PCS type. When read as a zero, bit 3.9.5 indicates that the PCS is not able to support the 25GBASE-PQ Rx only PCS type.

**45.2.3.8.ad 25GBASE-PQ Tx only capable (3.9.4)**

When read as a one, bit 3.9.4 indicates that the PCS is able to support the 25GBASE-PQ Tx only PCS type. When read as a zero, bit 3.9.4 indicates that the PCS is not able to support the 25GBASE-PQ Tx only PCS type.

*Change the title, text and tables for 45.2.3.41 through 45.2.3.45 as follows:*

**45.2.3.41 ~~40/10GBASE-PRX and 40GBASE-PR10G-EPON and Nx25G-EPON~~ corrected FEC codewords counter (Register 3.76, 3.77)**

The assignment of bits in the ~~40/10GBASE-PRX and 40GBASE-PR10G-EPON and Nx25G-EPON~~ corrected FEC codewords counter register is shown in Table 45–213. See 76.3.3.3.2 for a definition of ~~this~~ the

~~10G-EPON counters and 142.3.5.2 for the definition of the Nx25-EPON counters.~~ These bits shall be reset to all zeros when the register is read by the management function or upon PCS reset. These bits shall be held at all ones in the case of overflow.

**Table 45–213—~~10GBASE-PR~~10G-EPON and Nx25G-EPON corrected FEC codewords counter register bit definitions**

| Bit(s)    | Name                          | Description                            | R/W <sup>a</sup> |
|-----------|-------------------------------|----------------------------------------|------------------|
| 3.76.15:0 | corrected FEC codewords lower | corrected_FEC_codewords_counter[15:0]  | RO, MW, NR       |
| 3.77.15:0 | corrected FEC codewords upper | corrected_FEC_codewords_counter[31:16] | RO, MW, NR       |

<sup>a</sup>RO = Read only, MW = Multi-word, NR = Non Roll-over

#### 45.2.3.42 ~~10/1GBASE-PRX and 10GBASE-PR~~10G-EPON and Nx25G-EPON uncorrected FEC codewords counter (Register 3.78, 3.79)

The assignment of bits in the ~~10/1GBASE-PRX and 10GBASE-PR~~10G-EPON and Nx25G-EPON uncorrected FEC codewords counter register is shown in Table 45–214. See 76.3.3.3.2 for a definition of ~~this the 10G-EPON counters and 142.3.5.2 for the definition of the Nx25-EPON counters.~~ These bits shall be reset to all zeros when the register is read by the management function or upon PCS reset. These bits shall be held at all ones in the case of overflow.

**Table 45–214—~~10GBASE-PR~~10G-EPON and Nx25G-EPON uncorrected FEC codewords counter register bit definitions**

| Bit(s)    | Name                            | Description                              | R/W <sup>a</sup> |
|-----------|---------------------------------|------------------------------------------|------------------|
| 3.78.15:0 | uncorrected FEC codewords lower | uncorrected_FEC_codewords_counter[15:0]  | RO, MW, NR       |
| 3.79.15:0 | uncorrected FEC codewords lower | uncorrected_FEC_codewords_counter[32:16] | RO, MW, NR       |

<sup>a</sup>RO = Read only, MW = Multi-word, NR = Non Roll-over

#### 45.2.3.43 ~~10GBASE-PR and 10/1GBASE-PRX, and Nx25G-EPON~~ BER monitor ~~interval timer~~ control register (Register 3.80)

The assignment of bits in the ~~10GBASE-PR and 10/1GBASE-PRX, and Nx25G-EPON~~ BER monitor ~~interval timer~~ control register is shown in Table 45–215. This register is defined only when ~~10GBASE-PR, or 10/1GBASE-PRX, or Nx25G-EPON~~ 10GBASE-PR, or 10/1GBASE-PRX, or Nx25G-EPON ONU capability is supported. The 10G-EPON BER monitor is described in 76.3.3.4. ~~The Nx25G-EPON QC-LDPC BER Monitor is described in 142.3.5.6.~~

**Table 45–215—10GBASE-PR and 10/1GBASE-PRX, and Nx25G-EPON BER monitor interval timer-control register bit definitions**

| Bit(s)    | Name                                                  | Description                                                                                                                                                                                                                                                                                                                                                                                                                                       | R/W <sup>a</sup> |
|-----------|-------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| 3.80.15:8 | Reserved                                              | Value always 0                                                                                                                                                                                                                                                                                                                                                                                                                                    | RO               |
| 3.80.7:0  | <del>10G-EPON</del><br>BER monitor-<br>timer interval | <del>For 10GBASE-PR and 10/1GBASE-PRX: Duration (in units of 5 microseconds) of the timer used by the 10G-EPON-BER monitor function. Default value is 25 (i.e., 125 microseconds). A value of zero indicates that the BER monitor function is disabled.</del><br><u>For Nx25G-EPON: QC-LDPC codeword count (in units of 16 codewords) of the monitoring interval used by the BER Monitor function. Default value is 12 (i.e., 192 codewords).</u> | R/W              |

<sup>a</sup>RO = Read only, R/W = Read/Write

#### 45.2.3.44 10GBASE-PR and 10/1GBASE-PRX, and Nx25G-EPON BER monitor status (Register 3.81)

The assignment of bits in the 10GBASE-PR and 10/1GBASE-PRX, and Nx25G-EPON BER monitor status register is shown in Table 45–216. This register is defined only when 10GBASE-PR or 10/1GBASE-PRX, or Nx25G-EPON ONU capability is supported.

**Table 45–216—10GBASE-PR and 10/1GBASE-PRX, and Nx25G-EPON BER monitor status register bit definitions**

| Bit(s)    | Name             | Description                                                                                                                                                                                                  | R/W <sup>a</sup> |
|-----------|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| 3.81.15:2 | Reserved         | Value always 0                                                                                                                                                                                               | RO               |
| 3.81.1    | Latched high BER | <del>10GBASE-PR, 10/1GBASE-PRX, or Nx25G-EPON PCS:</del><br>1 = <del>10GBASE-PR or 10/1GBASE-PRX PCS</del> reported a high BER.<br>0 = <del>10GBASE-PR or 10/1GBASE-PRX PCS</del> did not report a high BER. | RO,<br>LH        |
| 3.81.0    | high BER         | <del>10GBASE-PR, 10/1GBASE-PRX, or Nx25G-EPON PCS:</del><br>1 = <del>10GBASE-PR or 10/1GBASE-PRX PCS</del> reporting a high BER.<br>0 = <del>10GBASE-PR or 10/1GBASE-PRX PCS</del> not reporting a high BER. | RO               |

<sup>a</sup>RO Read only, LH = Latching high

##### 45.2.3.44.1 10GBASE-PR and 10/1GBASE-PRX, and Nx25G-EPON PCS high BER (3.81.0)

In the 10GBASE-PR and 10/1GBASE-PRX, and Nx25G-EPON PCS, when read as a one, bit 3.81.0 indicates that the receiver is detecting a BER greater than the configurable threshold (high BER state). When read as a zero, bit 3.81.0 indicates that the receiver is detecting a BER lower than the configurable threshold (low BER state). This bit mirrors the state of the hi\_ber variable, defined in 76.3.3.4 for 10GBASE-PR and 10/1GBASE-PRX, and the HiBer variable in 142.3.5.2 for Nx25G-EPON.

**45.2.3.44.2 10GBASE-PR~~and~~, 10/1GBASE-PRX~~, and~~ Nx25G-EPON PCS latched high BER (3.81.1)**

In the 10GBASE-PR~~and~~, 10/1GBASE-PRX~~, and~~ Nx25G-EPON PCS, when read as a one, bit 3.81.1 indicates that the receiver detected a BER greater than the configurable threshold (high BER state). When read as a zero, bit 3.81.1 indicates that the receiver detected BER lower than the configurable threshold (low BER state).

This bit is a latching high version of the 10GBASE-PR~~and~~, 10/1GBASE-PRX~~, and~~ Nx25G-EPON high BER status bit (3.81.0).

**45.2.3.45 10GBASE-PR~~and~~, 10/1GBASE-PRX~~, and~~ Nx25G-EPON BER monitor threshold control (Register 3.82)**

The assignment of bits in the 10GBASE-PR~~and~~, 10/1GBASE-PRX~~, and~~ Nx25G-EPON BER monitor threshold control register is shown in Table 45–217. This register is defined only when 10GBASE-PR~~or~~, 10/1GBASE-PRX~~, or~~ Nx25G-EPON ONU capability is supported. The 10G-EPON BER monitor is described in 76.3.3.4. The Nx25G-EPON QC-LDPC BER Monitor is described in 142.3.5.6.

**Table 45–217—10GBASE-PR~~and~~, 10/1GBASE-PRX~~, and~~ Nx25G-EPON BER monitor threshold control register bit definitions**

| Bit(s)    | Name                                      | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | R/W <sup>a</sup> |
|-----------|-------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| 3.82.15:0 | <del>10G-EPON BER monitor threshold</del> | <del>For 10G-EPON: n</del> Number of sync header errors within a timer interval that triggers a high BER condition for the <del>10G-EPON</del> BER monitor function. Default value is 1600. A value of zero indicates that the BER monitor function is disabled.<br><u>For Nx25G-EPON: number of invalid QC-LDPC codeword parity checks within a BER monitor interval that triggers a high BER condition for the BER Monitor function. Default value is 18. A value of zero indicates that the BER Monitor function is disabled.</u> | R/W              |

<sup>a</sup>R/W = Read/Write

*Insert 45.2.3.45a and subclauses after 45.2.3.45 as follows:*

**45.2.3.45a Nx25G-EPON synchronization pattern registers (Registers 3.83 through 3.134)**

The assignment of bits in registers 3.83 through 3.134 is shown in Table 45–217a. The Nx25G-EPON synchronization pattern (see 142.1.3 and 144.3.6.7) is used in the upstream data transmissions to facilitate the OLT in locking to the incoming data burst.

**Table 45–217a—Nx25G-EPON synchronization pattern registers bit definitions**

| Bit(s)    | Name         | Description                 | R/W <sup>a</sup> |
|-----------|--------------|-----------------------------|------------------|
| 3.83.15:6 | Reserved     | Value always 0              | RO               |
| 3.83.5    | SP3 bit 257  | The MSB of the 257-bit SP3. | R/W              |
| 3.83.4    | SP3 balanced | Balance setting for SP3.    | R/W              |
| 3.83.3    | SP2 bit 257  | The MSB of the 257-bit SP2. | R/W              |

**Table 45–217a—Nx25G-EPON synchronization pattern registers bit definitions (continued)**

| Bit(s)                   | Name         | Description                                                                               | R/W <sup>a</sup> |
|--------------------------|--------------|-------------------------------------------------------------------------------------------|------------------|
| 3.83.2                   | SP2 balanced | Balance setting for SP2.                                                                  | R/W              |
| 3.83.1                   | SP1 bit 257  | The MSB of the 257-bit SP1.                                                               | R/W              |
| 3.83.0                   | SP1 balanced | Balance setting for SP1.                                                                  | R/W              |
| 3.99.15 through 3.84.0   | SP1 pattern  | The lower 256 bits of SP1. Bit 0 is stored in 3.84.0, and bit 255 is stored in 3.99.15.   | R/W              |
| 3.100.15:0               | SP1 length   | The number of times SP1 is to be repeated.                                                | R/W              |
| 3.116.15 through 3.101.0 | SP2 pattern  | The lower 256 bits of SP2. Bit 0 is stored in 3.101.0, and bit 255 is stored in 3.116.15. | R/W              |
| 3.117.15:0               | SP2 length   | The number of times SP2 is to be repeated.                                                | R/W              |
| 3.133.15 through 3.118.0 | SP3 pattern  | The lower 256 bits of SP3. Bit 0 is stored in 3.118.0, and bit 255 is stored in 3.133.15. | R/W              |
| 3.134.15:0               | SP3 length   | The number of times SP3 is to be repeated.                                                | R/W              |

<sup>a</sup>RO = Read only, R/W = Read/Write**45.2.3.45a.1 SP3 bit 257 (3.83.5)**

In the Nx25G-EPON PCS, bit 3.83.5 indicates the value to be used for the 257th bit of SP3. See 142.1.3 and 144.3.6.7 for additional details.

**45.2.3.45a.2 SP3 balanced (3.83.4)**

In the Nx25G-EPON PCS, bit 3.83.4 indicates that repeating SP3 synchronization patterns are to have a balanced number of one and zero bits transmitted. When this bit is set to a zero then SP3 is to remain unbalanced, i.e., SP3 is always transmitted using the values from 3.83.5 and 3.118.0 through 3.133.15. When this bit is set to a one SP3 is to be balanced, i.e., each 257-bit block of SP3 (starting with the second block) is an inversion of the preceding block. See 142.1.3 and 144.3.6.7 for additional details.

**45.2.3.45a.3 SP2 bit 257 (3.83.3)**

In the Nx25G-EPON PCS, bit 3.83.3 indicates the value to be used for the 257th bit of SP2. See 142.1.3 and 144.3.6.7 for additional details.

**45.2.3.45a.4 SP2 balanced (3.83.2)**

In the Nx25G-EPON PCS, bit 3.83.2 indicates that repeating SP2 synchronization patterns are to have a balanced number of one and zero bits transmitted. When this bit is set to a zero then SP2 is to remain unbalanced, i.e., SP2 is always transmitted using the values from 3.83.3 and 3.101.0 through 3.116.15. When this bit is set to a one SP2 is to be balanced, i.e., each 257-bit block of SP2 (starting with the second block) is an inversion of the preceding block. See 142.1.3 and 144.3.6.7 for additional details.