

INTERNATIONAL
STANDARD

ISO/IEC/
IEEE
9945

First edition
2009-09-15

Corrigendum 2
2017-03

Information technology — Portable Operating System Interface (POSIX®) Base Specifications, Issue 7

TECHNICAL CORRIGENDUM 2

*Technologies de l'information — Spécifications de base de l'interface
pour la portabilité des systèmes (POSIX®), Issue 7*

RECTIFICATIF TECHNIQUE 2



Reference number
ISO/IEC/IEEE 9945:2009/Cor.2:2017(E)

Documents
Document Sharing Hub
© IEEE 2016



COPYRIGHT PROTECTED DOCUMENT

© IEEE 2016

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO or IEEE at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Institute of Electrical and Electronics Engineers, Inc
3 Park Avenue, New York
NY 10016-5997, USA

stds.ipr@ieee.org
www.ieee.org

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards.

The main task of ISO/IEC JTC 1 is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is called to the possibility that implementation of this standard may require the use of subject matter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. ISO/IEEE is not responsible for identifying essential patents or patent claims for which a license may be required, for conducting inquiries into the legal validity or scope of patents or patent claims or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance or a Patent Statement and Licensing Declaration Form, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from ISO or the IEEE Standards Association.

ISO/IEC/IEEE 9945 was prepared by The Open Group (as The Open Group Technical Standard Base Specifications, Issue 7) and the Portable Applications Standards Committee of the Computer Society of the IEEE (as IEEE Std 1003.1™-2008). It was adopted by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 22, *Programming languages, their environments and system software interfaces*, in parallel with its approval by the ISO/IEC national bodies, under the “fast-track procedure” defined in the Partner Standards Development Organization cooperation agreement between ISO and IEEE. IEEE is responsible for the maintenance of this document with participation and input from ISO/IEC national bodies.

IEEE Std 1003.1™-2008/Cor 2-2016

(Corrigendum to
IEEE Std 1003.1-2008)

The Open Group Technical Standard
Base Specifications, Issue 7

IEEE Standard for Information Technology—Portable Operating System Interface (POSIX®)

Base Specifications, Issue 7— Technical Corrigendum 2

Sponsor

Portable Applications Standards Committee
of the
IEEE Computer Society

and
The Open Group

Approved 30 June 2016

IEEE-SA Standards Board

Approved 20 June 2016

The Open Group

ISO/IEC/IEEE 9945:2009/Cor.2:2017(E)

IEEE Std 1003.1™-2008/Cor 2-2016
IEEE Standard for Information Technology—Portable Operating System Interface (POSIX®)
Base Specifications, Issue 7—Technical Corrigendum 2

Abstract: Problems discovered since the approval of IEEE Std 1003.1-2008 and IEEE Std 1003.1-2008/Cor 1-2013 are addressed.

Keywords: API, application program interface, argument, asynchronous, basic regular expression, batch job, batch system, BRE, built-in utility, byte, child, command language interpreter, CPU, ERE, extended regular expression, FIFO, file access control mechanism, IEEE 1003.1™, input/output, I/O, job control, network, portable operating system interface, POSIX®

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2016 by The Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 15 August 2016. Printed in the United States of America.

Published 15 August 2016 by The Open Group.

IEEE is a registered trademark in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

POSIX is a registered trademark of IEEE.

The Open Group
Apex Plaza, Forbury Road, Reading, Berkshire RG1 1AX, U.K.

PDF: ISBN 978-1-5044-2148-5 STD1005

IEEE prohibits discrimination, harassment, and bullying.

For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

IEEE Std 1003.1™-2008/Cor 2-2016
IEEE Standard for Information Technology—Portable Operating System Interface (POSIX®)
Base Specifications, Issue 7—Technical Corrigendum 2

The Open Group is a global consortium that enables the achievement of business objectives through IT standards. With more than 500 member organizations, The Open Group has a diverse membership that spans all sectors of the IT community—customers, systems and solutions suppliers, tool vendors, integrators, and consultants, as well as academics and researchers—to:

- Capture, understand, and address current and emerging requirements, establish policies, and share best practices
- Facilitate interoperability, develop consensus, and evolve and integrate specifications and open source technologies
- Offer a comprehensive set of services to enhance the operational efficiency of consortia
- Operate the industry's premier certification service

Further information on The Open Group is available at www.opengroup.org.

The Open Group publishes a wide range of technical documentation, most of which is focused on development of Open Group Standards and Guides, but which also includes white papers, technical studies, certification and testing documentation, and business titles. Full details and a catalog are available at www.opengroup.org/bookstore.

Readers should note that updates—in the form of Corrigenda—may apply to any publication. This information is published at www.opengroup.org/corrigenda.

Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading “Important Notice” or “Important Notices and Disclaimers Concerning IEEE Standards Documents.”

Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents (standards, recommended practices, and guides), both full-use and trial-use, are developed within IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (“IEEE-SA”) Standards Board. IEEE (“the Institute”) develops its standards through a consensus development process, approved by the American National Standards Institute (“ANSI”), which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims all warranties (express, implied and statutory) not included in this or any other document relating to the standard, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, IEEE disclaims any and all conditions relating to: results; and workmanlike effort. IEEE standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

Official statements

A statement, written or oral, that is not processed in accordance with the IEEE-SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, or be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in revisions to an IEEE standard is welcome to join the relevant IEEE working group.

Comments on standards should be submitted to the following address:

Secretary, IEEE-SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854 USA

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

IEEE draft and approved standards are copyrighted by IEEE under U.S. and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

Photocopies

Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE-SA Website at <http://standards.ieee.org> or contact IEEE at the address listed previously. For more information about the IEEE SA or IEEE's standards development process, visit the IEEE-SA Website at <http://standards.ieee.org/develop/index.html>.

Errata

Errata, if any, for all IEEE standards can be accessed on the IEEE-SA Website at the following URL: <http://standards.ieee.org/findstds/errata/index.html>. Users are encouraged to check this URL for errata periodically.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE-SA Website at <http://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

IEEE Std 1003.1™-2008/Cor 2-2016
 IEEE Standard for Information Technology—Portable Operating System Interface (POSIX®)
 Base Specifications, Issue 7—Technical Corrigendum 2

Participants

IEEE Std 1003.1™-2008/Cor 2-2016 was prepared by the Austin Group, sponsored by the Portable Applications Standards Committee of the IEEE Computer Society, The Open Group, and ISO/IEC JTC 1/SC22.

The Austin Group

At the time this draft standard was completed, the Austin Group had the following membership:

Andrew Josey, *Chair*

Donald W. Cragun, *Organizational Representative, IEEE PASC*
Nicholas M. Stoughton, *Organizational Representative, ISO/IEC JTC 1/SC22*
Roger Faulkner, *Organizational Representative, The Open Group*

Cathy Fox, *Technical Editor*

Austin Group Technical Reviewers

Bogdan Barbu	Felix Janda	Martin Řehák
Eric Blake	Aurelio Jargas	Torvald Riegel
Harvey Block	Andrew Josey	Xavier Roche
Mark S. Brown	John Kearney	Askar Safin
Milan Cermak	Michael Kerrisk	Anton Salikhmetov
Stephane Chazelas	Rob King	Jörg Schilling
Alexander Cherepanov	Andi Kleen	Ed Schouten
Mark Clancy	Bruce Korb	Konrad Schwarz
Geoff Clare	Kaz Kylheku	Jens Schweikhardt
David Clissold	Antoine Leca	Mike Scudder
Alan Coopersmith	Wojtek Lerch	Martin Sebor
Donald W. Cragun	Sven Mascheck	Nicholas M. Stoughton
Matthew Dempsky	Margot Hackett Miller	Keith Thompson
Dan Douglas	Joseph S. Myers	Jilles Tjoelker
Lawrence D.K.B. Dwyer	Szabolcs Nagy	William Toth
Paul Eggert	Alexander Nasonov	Daniel Trebbien
Steve Emmerson	Jonathan Nieder	Miloslav Trmac
David Egan Evans	Danny Niu	Fred J. Tydeman
Roger Faulkner	Gian Ntzik	Ted Unangst
Richard Felker	Steffen Nurmese	Brian Utterback
Thorsten Glaser	Carlos O'Donnell	Stijn van Drongelen
Glenn D. Golden	Vladimir Támara Patiño	Jonathan Wakely
Jim Grisanzio	Peter Petrov	Nathan Weeks
Philip Guenther	William Pitcock	Florian Weimer
Richard Hansen	Jim Pryor	David A. Wheeler
Mark Harris	James C. Pugsley	Michael Wilson
Cyril Hrubis	Yury Pukhalsky	André Zepezauer
Jarmo Jaakkola	Steve Rago	Mark Ziegast
	Chet Ramey	

Austin Group Working Group Members

Eitan Adler	Philip Guenther	Jim Pryor
Iwan Aucamp	Joseph M. Gwinn	James C. Pugsley
Bogdan Barbu	Bruno Haible	Yury Pukhalsky
David Bartley	Richard Hansen	Steve Rago
Steve Bartolomei	Mark Harris	Chet Ramey
Fabrice Bauzac	Barry E. Hedquist	Martin Řehák
Guido Berhoerster	David Holland	Tom Ridge
Eric Blake	Tom Honermann	Torvald Riegel
Harvey Block	Cyril Hrubis	Xavier Roche
Hans Boehm	Jarmo Jaakkola	Askar Safin
Bill Bogstad	Felix Janda	Anton Salikhmetov
Pádraig Brady	Aurelio Jargas	Jörg Schilling
Davide Brini	Ross Johnson	Ed Schouten
Andries E. Brouwer	Andrew Josey	Konrad Schwarz
Mark S. Brown	John Kearney	Ingo Schwarze
David Butenhof	Dan Kegel	Jens Schweikhardt
Milan Cermak	Michael Kerrisk	Mike Scudder
Stephane Chazelas	Rob King	Martin Sebor
Alexander Cherepanov	Tomas Klacko	Glen Seeds
Mark Clancy	Andi Kleen	Jeffrey Sheinberg
Geoff Clare	Bruce Korb	Thor Lancelot Simon
David Clissold	David Korn	Keld Simonsen
Alan Coopersmith	Kaz Kylheku	Ranjit Singh
Donald W. Cragun	Rob Landley	Paul Smith
Martijn Dekker	Antoine Leca	Steven Stewart-Gallus
Matthew Dempsky	Vincent Lefèvre	Nicholas M. Stoughton
Thomas E. Dickey	Sean Leonard	Alfred M. Szmidt
Casper Dik	Wojtek Lerch	Marcel Telka
Dan Douglas	Yonggang Luo	Donn Terry
Niall Douglas	Scott Lurndal	Keith Thompson
Ulrich Drepper	Roger Marquis	Jilles Tjoelker
Lawrence D.K.B. Dwyer	Sven Mascheck	William Toth
Paul Eggert	Per Mildner	Daniel Trebbien
Daniel Eischen	Margot Hackett Miller	Miloslav Trmac
Robert Elz	Joseph S. Myers	Fred J. Tydeman
Steve Emmerson	Szabolcs Nagy	Ted Unangst
Laszlo Ersek	Alexander Nasonov	Brian Utterback
Bruce Evans	Jonathan Nieder	Stijn van Drongelen
David Egan Evans	Danny Niu	Christopher Vance
Roger Faulkner	Gian Ntzik	Jonathan Wakely
Richard Felker	Steffen Nurpmeso	Nathan Weeks
Jeffrey K. Fellin	Carlos O'Donnell	Florian Weimer
Hal Finkel	Isabella Parakiss	David A. Wheeler
Glenn Fowler	Vladimir Támara Patiño	Mats D. Wichmann
Cathy Fox	Phil Pinnock	Michael Wilson
Mike Frysinger	Andres Perera	Garrett Wollman
Andrea Giugliano	Peter Petrov	Jörg Wunsch
Thorsten Glaser	William Pitcock	James Youngman
Glenn D. Golden	Wayne Pollock	André Zepezauer
Jim Grisanzio		Mark Ziegast

IEEE Std 1003.1™-2008/Cor 2-2016
IEEE Standard for Information Technology—Portable Operating System Interface (POSIX®)
Base Specifications, Issue 7—Technical Corrigendum 2

The Open Group

When The Open Group approved the Base Specifications, Issue 7, Technical Corrigendum 2 on 20 June 2016, the membership of The Open Group Base Working Group was as follows:

Andrew Josey, *Chair*
Roger Faulkner, *Austin Group Liaison*

Cathy Fox, *Technical Editor*

Base Working Group Members

Eric Blake
Geoff Clare
David Clissold

Donald W. Cragun
Roger Faulkner
Darrin Johnson

Andrew Josey
Martin Řehák
S. R. Srinivasan

IEEE

At the time this standard was submitted to the IEEE-SA Standards Board for approval, the Portable Applications Standards Committee had the following membership:

Joseph M. Gwinn, *Chair*
Andrew Josey, *Functional Chair (Interpretations)*
Donald W. Cragun, *Shell and Utilities Working Group Chair*
Barry Hedquist, *Test Methods Working Group Chair*
Craig Meyers, *Distributed Services Working Group Chair*
Stephen Walli, *US TAG Institutional Representative*
Roger Martin, *Ex-officio Emeritus*
Nicholas M. Stoughton, *Secretary*

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Johann Amsenga
Juan Carreon
Keith Chow
Donald W. Cragun
Sourav Dutta
Andrew Fieldsend
David Fuschi

Randall Groves
Joseph M. Gwinn
Barry E. Hedquist
Werner Hoelzl
Noriyuki Ikeuchi
Andrew Josey
Piotr Karocki

Kenneth Lang
Vincent Lefèvre
Peter Petrov
Stephen Schwarm
Walter Struppler
Mark-Rene Uchida
Oren Yuen

ISO/IEC/IEEE 9945:2009/Cor.2:2017(E)

IEEE Std 1003.1™-2008/Cor 2-2016
IEEE Standard for Information Technology—Portable Operating System Interface (POSIX®)
Base Specifications, Issue 7—Technical Corrigendum 2

When the IEEE-SA Standards Board approved this standard on 30 June 2016, it had the following membership:

Jean-Philippe Faure, *Chair*
Ted Burse, *Vice Chair*
John D. Kulick, *Past Chair*
Konstantinos Karachalios, *Secretary*

Chuck Adams
Masayuki Ariyoshi
Stephen Dukes
Jianbin Fan
J. Travis Griffith
Ronald W. Hotchkiss

Gary Hoffman
Michael Janezic
Joseph L. Koepfinger*
Hung Ling
Kevin Lu
Annette D. Reilly
Gary Robinson

Mehmet Ulema
Yingli Wen
Howard Wolfman
Don Wright
Yu Yuan
Daidi Zhong

*Member Emeritus

IEEE Std 1003.1™-2008/Cor 2-2016
IEEE Standard for Information Technology—Portable Operating System Interface (POSIX®)
Base Specifications, Issue 7—Technical Corrigendum 2

Introduction

This introduction is not part of IEEE Std 1003.1-2008/Cor 2, IEEE Standard for Information Technology—Portable Operating System Interface (POSIX®)/Base Specifications, Issue 7—Technical Corrigendum 2 .

This Technical Corrigendum addresses issues raised in defect reports and interpretation requests submitted up to 24 August 2015 that meet all of the following criteria:

- a) They are in the scope of the approved standard.
- b) They contain no new APIs (functions/utilities); however, they may add enumeration symbols, non-function #defines, and reserve additional namespaces.
- c) They address contradictions between different parts of the standard, or add consistency between the standard and overriding standards, or address security-related problems.

Contents

1. Changes to the Front Matter	2
2. Changes to Base Definitions.....	3
3. Changes to System Interfaces.....	46
4. Changes to Shell and Utilities	198
5. Changes to Rationale	283

IEEE Std 1003.1™-2008/Cor 2-2016
IEEE Standard for Information Technology—Portable Operating System Interface (POSIX®)
Base Specifications, Issue 7—Technical Corrigendum 2

IEEE Standard for Information Technology—Portable Operating System Interface (POSIX®)

Base Specifications, Issue 7— Technical Corrigendum 2

IMPORTANT NOTICE: *This standard is not intended to ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.*

This IEEE document is made available for use subject to important notices and legal disclaimers. These notices and disclaimers appear in all publications containing this document and may be found under the heading “Important Notice” or “Important Notices and Disclaimers Concerning IEEE Documents.” They can also be obtained on request from IEEE or viewed at <http://standards.ieee.org/IPR/disclaimers.html>.

NOTE—The editing instructions contained in this corrigendum define how to merge the material contained therein into the existing base standard to form the comprehensive standard.

1. Changes to the Front Matter

This section contains the set of changes to the text of the front matter.

[*Note to reviewers: References to defect reports are provided to aid reviewers.*]

Change Number: Front Matter/TC2/D4/0001 [885]

On Page: xlv Line: NA Section: Referenced Documents
(2013 edition Page: xlvii Line: NA)

In the line below the **Source Documents** header, change from:

base documents for POSIX.1-2008

to:

base documents for POSIX.1-2001

Rationale: Austin Group Defect Report(s) applied: 885. See <http://austingroupbugs.net/view.php?id=885>.

Change Number: Front Matter/TC2/D4/0002 [726]

On Page: xxxviii Line: NA Section: Acknowledgements

Remove the period from the first bullet list item.

Rationale: Austin Group Defect Report(s) applied: 726. See <http://austingroupbugs.net/view.php?id=726>.
Editorial change.

17

2. Changes to Base Definitions

This section contains the set of changes to the text of the Base Definitions.

[*Note to reviewers: References to defect reports are provided to aid reviewers.*]

Change Number: XBD/TC2/D4/0001 [591]

On Page: 9 Line: 266 Section: 1.7.1 Codes

Change from:

```
[OH]#include <sys/types.h>[/OH]
#include <grp.h>
struct group *getgrnam(const char *name);
```

The OH margin legend indicates that the marked header is not required on XSI-conformant systems.

to:

```
[OH]#include <sys/stat.h>[/OH]
#include <fcntl.h>
int open(const char *path, int oflag, ...);
```

The OH margin legend indicates that the optional header defines constants that will be needed if the function is called with certain flag arguments; thus it may be required for some of the functionality described, but is not needed otherwise.

Rationale: Austin Group Defect Report(s) applied: 591. See <http://austingroupbugs.net/view.php?id=591>.

Change Number: XBD/TC2/D4/0002 [810]

On Page: 16 Line: 493 Section: 2.1.1 Requirements

At the end of section 2.1.1, add a small-font note:

Note: If the documented method of setting up a conforming environment includes the need to set one or more environment variables, then the values of those environment variables cannot include any <space> characters, since the *confstr()* function must be able to return them in a <space>-separated list of variable=value pairs. See [xref to XSH confstr()].

Rationale: Austin Group Defect Report(s) applied: 810. See <http://austingroupbugs.net/view.php?id=810>.

Change Number: XBD/TC2/D4/0003 [637]

On Page: 17 Line: 561 Section: 2.1.3 POSIX Conformance

Change from:

```
_POSIX_TIMERS
-- Symbolic constants defined with a value greater than zero:
```

50 _POSIX_JOB_CONTROL
51 _POSIX_SAVED_IDS

52 to:

53 _POSIX_TIMERS
54 _POSIX2_C_BIND

55
56 -- Symbolic constants defined with a value greater than zero:

57 _POSIX_JOB_CONTROL
58 _POSIX_REGEX
59 _POSIX_SAVED_IDS
60 _POSIX_SHELL

61 *Rationale:* Austin Group Defect Report(s) applied: 637. See <http://austingroupbugs.net/view.php?id=637>.

62 **Change Number: XBD/TC2/D4/0004** [937]

63 On Page: 35 Line: 1195 Section: 3.17 Application
64 (2013 edition Page: 35 Line: 1199)

65 After:

66 A computer program that performs some desired function.

67 add a new paragraph:

68 When the User Portability Utilities option is supported, requirements placed on applications relating to the
69 use of standard utilities shall also apply to the actions of a user who is entering shell command language
70 statements into an interactive shell.

71 *Rationale:* Austin Group Defect Report(s) applied: 937. See <http://austingroupbugs.net/view.php?id=937>.

72 **Change Number: XBD/TC2/D4/0005** [516]

73 On Page: 37 Line: 1229 Section: 3.27 Async-Signal-Safe Function

74 Change the definition from:

75 A function that may be invoked, without restriction, from signal-catching functions. No function is async-
76 signal-safe unless explicitly described as such.

77 to:

78 A function that can be called, without restriction, from signal-catching functions. Note that, although there
79 is no restriction on the calls themselves, for certain functions there are restrictions on subsequent behavior
80 after the function is called from a signal-catching function. No function is async-signal-safe unless
81 explicitly described as such.

82 Note: Async-signal-safety is defined in detail in [xref to XSH 2.4.3].

83 *Rationale:* Austin Group Defect Report(s) applied: 516. See <http://austingroupbugs.net/view.php?id=516>.
84 The restrictions on using longjmp() and siglongjmp() are more restrictive than they need to be on POSIX

IEEE Std 1003.1™-2008/Cor 2-2016
IEEE Standard for Information Technology—Portable Operating System Interface (POSIX®)
Base Specifications, Issue 7—Technical Corrigendum 2

85 systems. The loosened restrictions presented here do not break existing implementations and make it easier
86 for application writers to create portable applications.

87 **Change Number: XBD/TC2/D4/0006** [653]

88 On Page: 39 Line: 1274 Section: 3.40 Basename

89 Change from:

90 The final, or only, filename in a pathname.

91 to:

92 For pathnames containing at least one filename: the final, or only, filename in the pathname. For pathnames
93 consisting only of <slash> characters: either "/" or "/" if the pathname consists of exactly two <slash>
94 characters, and "/" otherwise.

95 *Rationale:* Austin Group Defect Report(s) applied: 653. See <http://austingroupbugs.net/view.php?id=653>.

96 **Change Number: XBD/TC2/D4/0007** [834]

97 On Page: 60 Line: 1775 Section: 3.168 File Mode

98 Change from:

99 An object containing the file mode bits and file type of a file.

100 to:

101 An object containing the file mode bits and some information about the file type of a file.

102 *Rationale:* Austin Group Defect Report(s) applied: 834. See <http://austingroupbugs.net/view.php?id=834>.

103 **Change Number: XBD/TC2/D4/0008** [511]

104 On Page: 63 Line: 1855 Section: 3.188 Group ID

105 Add a sentence:

106 The value (**gid_t**)-1 shall not be a valid group ID, but does have a defined use in some interfaces defined in
107 this standard.

108 *Rationale:* Austin Group Defect Report(s) applied: 511. See <http://austingroupbugs.net/view.php?id=511>.

109 **Change Number: XBD/TC2/D4/0009** [584]

110 On Page: 63 Line: 1859 Section: 3.189 Group Name

111 Change from:

- 112 <hyphen>
- 113 to:
- 114 <hyphen-minus>
- 115 *Rationale:* Austin Group Defect Report(s) applied: 584. See <http://austingroupbugs.net/view.php?id=584>.
- 116 **Change Number: XBD/TC2/D4/0010** [690]
- 117 On Page: 66 Line: 1926 Section: 3 Definitions
- 118 (2013 edition Page: 66 Line: 1935)
- 119 After section 3.208 ("Link Count"), insert a new section **3.209 Live Process** whose contents are copied
- 120 from section 3.289 ("Process") page 80 lines 2243-2250 (2013 edition section 3.291 page 80 lines 2269-
- 121 2275):
- 122 An address space with one or more threads executing within that address space, and the required system
- 123 resources for those threads.
- 124 <small>**Note:** Many of the system resources defined by POSIX.1-2008 are shared among all of the threads
- 125 within a process. These include the process ID, the parent process ID, process group ID, session
- 126 membership, real, effective, and saved set-user-ID, real, effective, and saved set-group-ID, supplementary
- 127 group IDs, current working directory, root directory, file mode creation mask, and file descriptors.</small>
- 128 *Rationale:* Austin Group Defect Report(s) applied: 690. See <http://austingroupbugs.net/view.php?id=690>.
- 129 **Change Number: XBD/TC2/D4/0011** [625]
- 130 On Page: 69 Line: 2000 Section: 3 Definitions
- 131 Add the following definitions in alphabetical order:
- 132 **Multi-threaded library**
- 133 A library containing object files that were produced by compiling with c99 using the flags output by
- 134 getconf POSIX_V7_THREADS_CFLAGS, or by compiling using a non-standard utility with equivalent
- 135 flags, and which makes use of interfaces that are only made available by c99 when the **-l pthread** option is
- 136 used or makes use of SIGEV_THREAD notifications.
- 137 **Multi-threaded process**
- 138 A process that contains more than one thread.
- 139 **Multi-threaded program**
- 140 A program whose executable file was produced by compiling with c99 using the flags output by getconf
- 141 POSIX_V7_THREADS_CFLAGS, and linking with c99 using the flags output by getconf
- 142 POSIX_V7_THREADS_LDFLAGS and the **-l pthread** option, or by compiling and linking using a non-
- 143 standard utility with equivalent flags. Execution of a multi-threaded program initially creates a single-
- 144 threaded process; the process can create additional threads using *pthread_create()* or SIGEV_THREAD

145 notifications.

146 **Single-threaded process**

147 A process that contains a single thread.

148 **Single-threaded program**

149 A program whose executable file was produced by compiling with `c99` without using the flags output by
 150 `getconf POSIX_V7_THREADS_CFLAGS` and linking with `c99` using neither the flags output by `getconf`
 151 `POSIX_V7_THREADS_LDFLAGS` nor the `-l pthread` option, or by compiling and linking using a non-
 152 standard utility with equivalent flags. Execution of a single-threaded program creates a single-threaded
 153 process; if the process attempts to create additional threads using `pthread_create()` or `SIGEV_THREAD`
 154 notifications, the behavior is undefined. If the process uses `dlopen()` to load a multi-threaded library, the
 155 behavior is undefined.

156 *Rationale:* Austin Group Defect Report(s) applied: 625. See <http://austingroupbugs.net/view.php?id=625>.
 157 The standard does not adequately address the differences between single-threaded and multi-threaded
 158 processes and programs.

159 **Change Number: XBD/TC2/D4/0012** [584]

160 On Page: 77 Line: 2193 Section: 3. Definitions

161 After Section 3.275, add a new section:

162 **3.2xx Portable Filename**

163 A filename consisting only of characters from the portable filename character set.

164 <small>Note: Applications should avoid using filenames that have the <hyphen-minus> character as the
 165 first character since this may cause problems when filenames are passed as command line
 166 arguments.</small>

167 *Rationale:* Austin Group Defect Report(s) applied: 584. See <http://austingroupbugs.net/view.php?id=584>.
 168 This is a layered change on XBD/TC1/D5/0010 [291]. The change is to replace <hyphen> with <hyphen-
 169 minus>.

170 **Change Number: XBD/TC2/D4/0013** [584]

171 On Page: 77 Line: 2199 Section: 3.276 Portable Filename Character Set

172 Change from:

173 <hyphen>

174 to:

175 <hyphen-minus>

176 *Rationale:* Austin Group Defect Report(s) applied: 584. See <http://austingroupbugs.net/view.php?id=584>.

- 177 **Change Number: XBD/TC2/D4/0014** [690]
- 178 On Page: 80 Line: 2244-2250 Section: 3.289 Process
179 (2013 edition Page: 80 Line: 2269-2275 Section: 3.291)
- 180 Replace the definition with:
- 181 A live process (see Section 3.xxx) or a zombie process (see Section 3.xxx). The lifetime of a process is
182 described in Section 3.xxx.
- 183 On Page: 81 Line: 2270-2279 Section: 3.295 Process Lifetime
184 (2013 edition Page: 81 Line: 2295-2304 Section: 3.297)
- 185 Change from:
- 186 The period of time that begins when a process is created and ends when its process ID is returned to the
187 system. After a process is created by *fork()*, *posix_spawn()*, or *posix_spawnp()*, it is considered active. At
188 least one thread of control and address space exist until it terminates. It then enters an inactive state where
189 certain resources may be returned to the system, although some resources, such as the process ID, are still
190 in use. When another process executes a *wait()*, *waitid()*, or *waitpid()* function for an inactive process, the
191 remaining resources are returned to the system. The last resource to be returned to the system is the process
192 ID. At this time, the lifetime of the process ends.
- 193
194 <small>**Note:** The *fork()*, *posix_spawn()*, *posix_spawnp()*, *wait()*, *waitid()*, and *waitpid()* functions are
195 defined in detail in the System Interfaces volume of POSIX.1-2008.</small>
- 196 to:
- 197 The period of time that begins when a process is created and ends when its process ID is returned to the
198 system.
- 199
200 See also *Live Process* in Section 3.xxx, *Process Termination* in Section 3.xxx, and *Zombie Process* in
201 Section 3.xxx.
- 202
203 <small>**Note:** Process creation is defined in detail in the descriptions of the *fork()*, *posix_spawn()*, and
204 *posix_spawnp()* functions in the System Interfaces volume of POSIX.1-2008.</small>
- 205 On Page: 81 Line: 2293-2294 Section: 3.297 Process Termination
206 (2013 edition Page: 81 Line: 2318-2319 Section: 3.299)
- 207 Change from:
- 208 <small>**Note:** The *_exit()*, *_Exit()*, *abort()*, and *exit()* functions are defined in detail in the System
209 Interfaces volume of POSIX.1-2008.</small>
- 210 to:
- 211 <small>**Note:** The consequences of process termination can be found in the description of the *_Exit()*
212 function in the System Interfaces volume of POSIX.1-2008. The *_exit()*, *_Exit()*, *abort()*, and *exit()*
213 functions are defined in detail in the System Interfaces volume of POSIX.1-2008.</small>
- 214 *Rationale:* Austin Group Defect Report(s) applied: 690. See <http://austingroupbugs.net/view.php?id=690>.

IEEE Std 1003.1™-2008/Cor 2-2016
 IEEE Standard for Information Technology—Portable Operating System Interface (POSIX®)
 Base Specifications, Issue 7—Technical Corrigendum 2

215 **Change Number: XBD/TC2/D4/0015** [896]

216 On Page: 90 Line: 2485 Section: 3.351 Source Code
 217 (2013 edition Page: 90 Line: 2510 Section: 3.353 Source Code)

218 Change from:

219 ... *ed, lex*, ...

220 to:

221 ... *ed, ex, lex*, ...

222 On Page: 90 Line: 2487 Section: 3.351 Source Code
 223 (2013 edition Page: 90 Line: 2512 Section: 3.353 Source Code)

224 Change from:

225 ... *ed, lex*, ...

226 to:

227 ... *ed, ex, lex*, ...

228 *Rationale:* Austin Group Defect Report(s) applied: 896. See <http://austingroupbugs.net/view.php?id=896>.

229 **Change Number: XBD/TC2/D4/0016** [511]

230 On Page: 102 Line: 2782 Section: 3.428 User ID

231 Add a sentence:

232 The value (**uid_t**)-1 shall not be a valid user ID, but does have a defined use in some interfaces defined in
 233 this standard.

234 *Rationale:* Austin Group Defect Report(s) applied: 511. See <http://austingroupbugs.net/view.php?id=511>.

235 **Change Number: XBD/TC2/D4/0017** [584]

236 On Page: 102 Line: 2786 Section: 3.429 User Name

237 Change from:

238 <hyphen>

239 to:

240 <hyphen-minus>

241 *Rationale:* Austin Group Defect Report(s) applied: 584. See <http://austingroupbugs.net/view.php?id=584>.

242

- 243 **Change Number: XBD/TC2/D4/0018** [690]
- 244 On Page: 105 Line: 2845-2846 Section: 3.444 Zombie Process
245 (2013 edition Page: 105 Line: 2871-2872 Section: 3.446)
- 246 Change from:
- 247 A process that has terminated and that is deleted when its exit status has been reported to another process
248 which is waiting for that process to terminate.
- 249 to:
- 250 The remains of a live process (see Section 3.xxx) after it terminates (see Section 3.xxx) and before its status
251 information (see XSH Section 2.13) is consumed by its parent process.
- 252 *Rationale:* Austin Group Defect Report(s) applied: 690. See <http://austingroupbugs.net/view.php?id=690>.
- 253 **Change Number: XBD/TC2/D4/0019** [934]
- 254 On Page: 107 Line: 2858 Section: 4 General Concepts
255 (2013 edition Page: 107 Line: 2884)
- 256 Add a new section (and renumber subsequent sections as needed):
- 257 **4.2 Default Initialization**
- 258 Default initialization causes an object to be initialized according to these rules:
- 259 • If it has pointer type, it is initialized to a null pointer.
260 • If it has arithmetic type, it is initialized to (positive or unsigned) zero.
261 • If it is an aggregate, every member is initialized (recursively) according to these rules.
262 • If it is a union, the first named member is initialized (recursively) according to these rules.
- 263 For an object of aggregate type with an explicit initializer, the initialization shall occur in initializer list
264 order, each initializer provided for a particular subobject overriding any previously listed initializer for the
265 same subobject; all subobjects that are not initialized explicitly shall be initialized implicitly according to
266 the rules for default initialization.
- 267 Objects with static storage duration but no explicit initializer shall be initialized implicitly according to the
268 rules for default initialization.
- 269 An explicit initializer of { 0 } works to perform explicit default initialization for any object of scalar or
270 aggregate type, and for any storage duration.
- 271 <small>Note: The C standard does not require a compiler to set any field alignment padding bits in a
272 structure or array definition to a particular value. Because of this, a structure initialized using { 0 } might
273 not *memcmp()* as equal to the same structure initialized using *memset()* to zero. For consistent results,
274 portable applications comparing structures should test each field individually.
- 275 Note: If an implementation treats the all-zero bit pattern of a pointer object as a null pointer, and the all-
276 zero bit pattern of a floating point object as equivalent to positive 0, then *memset()* to zero and *calloc()*
277 have the same effects as default initialization for all named members of a structure. [MX]Implementations

IEEE Std 1003.1™-2008/Cor 2-2016
 IEEE Standard for Information Technology—Portable Operating System Interface (POSIX®)
 Base Specifications, Issue 7—Technical Corrigendum 2

278 that define `__STDC_IEC_559__` guarantee that the all-zero bit pattern of a floating point object represents
 279 `0.0.[MX]`</small>

280 *Rationale:* Austin Group Defect Report(s) applied: 934. See <http://austingroupbugs.net/view.php?id=934>.

281 **Change Number: XBD/TC2/D4/0020** [584]

282 On Page: 109 Line: 2914 Section: 4.7 Filename Portability

283 Change from:

284 <hyphen>

285 to:

286 <hyphen-minus>

287 *Rationale:* Austin Group Defect Report(s) applied: 584. See <http://austingroupbugs.net/view.php?id=584>.

288 **Change Number: XBD/TC2/D4/0021** [626]

289 On Page: 109 Line: 2917 Section: 4.8 File Times Update

290 Insert a new paragraph at the start of the section:

291 Many operations have requirements to update file timestamps. These requirements do not apply to streams
 292 that have no underlying file description (for example, memory streams created by `open_memstream()` have
 293 no underlying file description).

294 *Rationale:* Austin Group Defect Report(s) applied: 626. See <http://austingroupbugs.net/view.php?id=626>.

295 **Change Number: XBD/TC2/D4/0022** [863]

296 On Page: 110 Line: 2980 Section: 4.11 Memory Synchronization
 297 (2013 edition Page: 110 Line: 3004)

298 Change from:

299 The `pthread_once()` function shall synchronize memory for the first call in each thread for a given
 300 **pthread_once_t** object.

301 to:

302 The `pthread_once()` function shall synchronize memory for the first call in each thread for a given
 303 **pthread_once_t** object. If the `init_routine` called by `pthread_once()` is a cancellation point and is canceled,
 304 a call to `pthread_once()` for the same **pthread_once_t** object made from a cancellation cleanup handler
 305 shall also synchronize memory.

306 *Rationale:* Austin Group Defect Report(s) applied: 863. See <http://austingroupbugs.net/view.php?id=863>.

307

308 **Change Number: XBD/TC2/D4/0023** [541,649,825]

309 On Page: 112 Line: 3026 Section: 4.12 Pathname Resolution

310 Change from:

311 In all other cases, the system shall prefix the remaining pathname, if any, with the contents of the symbolic
312 link. If the combined length exceeds {PATH_MAX}, and the implementation considers this to be an error,
313 *errno* shall be set to [ENAMETOOLONG] and an error indication shall be returned.

314 to:

315 In all other cases, the system shall prefix the remaining pathname, if any, with the contents of the symbolic
316 link, except that if the contents of the symbolic link is the empty string, then either pathname resolution
317 shall fail with functions reporting an [ENOENT] error and utilities writing an equivalent diagnostic
318 message, or the pathname of the directory containing the symbolic link shall be used in place of the
319 contents of the symbolic link. If the contents of the symbolic link consist solely of <slash> characters, then
320 all leading <slash> characters of the remaining pathname shall be omitted from the resulting combined
321 pathname, leaving only the leading <slash> characters from the symbolic link contents. In the cases where
322 prefixing occurs, if the combined length exceeds {PATH_MAX}, and the implementation considers this to
323 be an error, pathname resolution shall fail with functions reporting an [ENAMETOOLONG] error and
324 utilities writing an equivalent diagnostic message.

325 *Rationale:* Austin Group Defect Report(s) applied: 541,649,825. See

326 <http://austingroupbugs.net/view.php?id=541>.

327 See <http://austingroupbugs.net/view.php?id=649>.

328 See <http://austingroupbugs.net/view.php?id=825>.

329 The previous text was not historic practice on implementations that support //hostname as a special case in
330 pathname resolution. For implementations that do not treat // as special, the change in handling of all-slash
331 symbolic links has no effect on pathname resolution.

332 **Change Number: XBD/TC2/D4/0024** [825]

333 On Page: 112 Line: 3032 Section: 4.12 Pathname Resolution
334 (2013 edition Page: 112 Line: 3056 Section: 4.12)

335 Change from:

336 If the system detects a loop in the pathname resolution process, it shall set *errno* to [ELOOP] and return an
337 error indication.

338 to:

339 If the system detects a loop in the pathname resolution process, pathname resolution shall fail with
340 functions reporting an [ELOOP] error and utilities writing an equivalent diagnostic message.

341 *Rationale:* Austin Group Defect Report(s) applied: 825. See <http://austingroupbugs.net/view.php?id=825>.

342

343 **Change Number: XBD/TC2/D4/0025** [543]

344 On Page: 116 Line: 3205 Section: 4.19 Treatment of Error Conditions for Mathematical Functions

345 Add a new paragraph before the last paragraph:

346 On implementations that support the IEC 60559 Floating-Point option, whether or when functions in the
 347 `<math.h>` header raise an undeserved underflow floating-point exception is unspecified. Otherwise, as
 348 implied by [xref to XSH *feraiseexcept()*] the `<math.h>` functions do not raise spurious floating-point
 349 exceptions (detectable by the user), other than the inexact floating-point exception.

350 *Rationale:* Austin Group Defect Report(s) applied: 543. See <http://austingroupbugs.net/view.php?id=543>.

351 **Change Number: XBD/TC2/D4/0026** [584]

352 On Page: 123 Line: 3411 Section: 5 File Format Notation

353 Change from:

354 indicates either a `<plus-sign>` or `<minus-sign>`,

355 to:

356 indicates either a `<plus-sign>` or `<hyphen-minus>`,

357 *Rationale:* Austin Group Defect Report(s) applied: 584. See <http://austingroupbugs.net/view.php?id=584>.

358 **Change Number: XBD/TC2/D4/0027** [584,967]

359 On Page: 125 Line: 3454 Section: 6.1 Portable Character Set
 360 (2013 edition Page: 125 Line: 3479)

361 Change from:

362 The first eight entries in [xref to Table 6-1] are defined in the ISO/IEC 6429:1992 standard and the rest of
 363 the characters are defined in the ISO/IEC 10646-1:2000 standard.

364 to:

365 The first eight entries in [xref to Table 6-1] and all characters in [xref to Table 6-2] are defined in the
 366 ISO/IEC 6429:1992 standard. The rest of the characters in [xref to Table 6-1] are defined in the ISO/IEC
 367 10646-1:2000 standard.

368 On Page: 125 Line: 3458 Section: 6.1 Portable Character Set
 369 (2013 edition Page: 125 Line: 3483)

370 Change from:

371 **Symbolic Name**

372 to:

373 Symbolic Name(s)

374 On Page: 125 Line: 3460-3466 Section: 6.1 Portable Character Set
375 (2013 edition Page: 125 Line: 3485-3491)

376 Change from:

<alert>	<U0007>	BELL (BEL)
<backspace>	<U0008>	BACKSPACE (BS)
<tab>	<U0009>	CHARACTER TABULATION (HT)
<carriage-return>	<U000D>	CARRIAGE RETURN (CR)
<newline>	<U000A>	LINE FEED (LF)
<vertical-tab>	<U000B>	LINE TABULATION (VT)
<form-feed>	<U000C>	FORM FEED (FF)

377

378 to (note the description column changes to match the Unicode spec, and the change in line order):

<alert>, <BEL>	<U0007>	BELL
<backspace>, <BS>	<U0008>	BACKSPACE
<tab>, <HT>	<U0009>	CHARACTER TABULATION
<newline>, <LF>	<U000A>	LINE FEED (LF)
<vertical-tab>, <VT>	<U000B>	LINE TABULATION
<form-feed>, <FF>	<U000C>	FORM FEED (FF)
<carriage-return>, <CR>	<U000D>	CARRIAGE RETURN (CR)

379

380 On Page: 125 Line: 3480-3485 Section: 6.1 Portable Character Set
381 (2013 edition Page: 125 Line: 3505-3510)

382 Change from:

IEEE Std 1003.1™-2008/Cor 2-2016
IEEE Standard for Information Technology—Portable Operating System Interface (POSIX®)
Base Specifications, Issue 7—Technical Corrigendum 2

<hyphen-minus>	-	<U002D>	HYPHEN-MINUS
<hyphen>	-	<U002D>	HYPHEN-MINUS
<full-stop>	.	<U002E>	FULL STOP
<period>	.	<U002E>	FULL STOP
<slash>	/	<U002F>	SOLIDUS
<solidus>	/	<U002F>	SOLIDUS

383

384 to (note that the glyph used for <hyphen-minus>, <hyphen> should be the same one that is used in the
385 construct "<->" in the rest of the standard):

<hyphen-minus>, <hyphen>	-	<U002D>	HYPHEN-MINUS
<full-stop>, <period>	.	<U002E>	FULL STOP
<slash>, <solidus>	/	<U002F>	SOLIDUS

386 On Page: 126 Line: 3531-3532 Section: 6.1 Portable Character Set
387 (2013 edition Page: 126 Line: 3556-3557)

388 Change from:

<backslash>	\	<U005C>	REVERSE SOLIDUS
<reverse-solidus>	\	<U005C>	REVERSE SOLIDUS

389

390 to:

<backslash>, <reverse-solidus>	\	<U005C>	REVERSE SOLIDUS
--------------------------------	---	---------	-----------------

391

392 On Page: 126 Line: 3534-3537 Section: 6.1 Portable Character Set
393 (2013 edition Page: 126 Line: 3559-3562)

394 Change from:

<circumflex-accent>	^	<U005E>	CIRCUMFLEX ACCENT
---------------------	---	---------	-------------------

<circumflex>	^	<U005E>	CIRCUMFLEX ACCENT
<low-line>	—	<U005F>	LOW LINE
<underscore>	—	<U005F>	LOW LINE

395

396 to:

<circumflex-accent>, <circumflex>	^	<U005E>	CIRCUMFLEX ACCENT
<low-line>, <underscore>	—	<U005F>	LOW LINE

397

398 On Page: 127 Line: 3566-3567 Section: 6.1 Portable Character Set
399 (2013 edition Page: 127 Line: 3591-3592)

400 Change from:

<left-brace>	{	<U007B>	LEFT CURLY BRACKET
<left-curly-bracket>	{	<U007B>	LEFT CURLY BRACKET

401

402 to:

<left-brace>, <left-curly-bracket>	{	<U007B>	LEFT CURLY BRACKET
------------------------------------	---	---------	--------------------

403

404 On Page: 127 Line: 3569-3570 Section: 6.1 Portable Character Set
405 (2013 edition Page: 127 Line: 3594-3595)

406 Change from:

<right-brace>	}	<U007D>	RIGHT CURLY BRACKET
<right-curly-bracket>	}	<U007D>	RIGHT CURLY BRACKET

407

408 to:

IEEE Std 1003.1™-2008/Cor 2-2016
IEEE Standard for Information Technology—Portable Operating System Interface (POSIX®)
Base Specifications, Issue 7—Technical Corrigendum 2

<right-brace>, <right-curly-bracket>	}	<U007D>	RIGHT CURLY BRACKET
--------------------------------------	---	---------	---------------------

409

410 On Page: 127 Line: 3576-3578 Section: 6.1 Portable Character Set
411 (2013 edition Page: 127 Line: 3601-3603)

412 Delete the sentence:

413 The table contains more than one symbolic character name for characters whose traditional name differs
414 from the chosen name.

415 *Rationale:* Austin Group Defect Report(s) applied: 584,967. See
416 <http://austingroupbugs.net/view.php?id=584>.
417 See <http://austingroupbugs.net/view.php?id=967>.

418 **Change Number: XBD/TC2/D4/0028** [745]

419 On Page: 128 Line: 3589 Section: 6.1 Portable Character Set

420 Add a sentence as a new bullet item:

- 421 • The encoded values associated with <period>, <slash>, <newline> and <carriage-return> shall be
422 invariant across all locales supported by the implementation.

423 *Rationale:* Austin Group Defect Report(s) applied: 745. See <http://austingroupbugs.net/view.php?id=745>.
424 This is a layered change on XBD/TC1/D5/0019 [291].

425 **Change Number: XBD/TC2/D4/0029** [663,967]

426 On Page: 128 Line: 3596 Section: 6.2 Character Encoding
427 (2013 edition Page: 128 Line: 3623)

428 Change from:

429 The POSIX locale contains the characters in [xref to Table 6-1], which have the properties listed in [xref to
430 7.3.1]. In other locales, the presence, meaning, and representation of any additional characters are locale-
431 specific.

432 to:

433 The POSIX locale shall contain 256 single-byte characters including the characters in [xref to Table 6-1]
434 and [xref to Table 6-2], which have the properties listed in [xref to 7.3.1]. It is unspecified whether
435 characters not listed in those two tables are classified as **punct** or **cntrl**, or neither. Other locales shall
436 contain the characters in [xref to Table 6-1] and may contain any or all of the control characters identified
437 in [xref to Table 6-2]; the presence, meaning, and representation of any additional characters are locale-
438 specific.

439 *Rationale:* Austin Group Defect Report(s) applied: 663,967. See
440 <http://austingroupbugs.net/view.php?id=663>.
441 See <http://austingroupbugs.net/view.php?id=967>.

- 442 This is a layered change on XBD/TC1/D5/0020 [216].
443 The intention was always that the POSIX locale should have an 8-bit-clean single-byte encoding. The
444 omission of an explicit statement to that effect was an oversight.
- 445 **Change Number: XBD/TC2/D4/0030 [745]**
- 446 On Page: 128 Line: 3619 Section: 6.2 Character Encoding
- 447 Add a sentence:
- 448 Likewise, the byte values used to encode <period>, <slash>, <newline> and <carriage-return> shall not
449 occur as part of any other character in any locale.
- 450 *Rationale:* Austin Group Defect Report(s) applied: 745. See <http://austingroupbugs.net/view.php?id=745>.
451 This is a layered change on XBD/TC1/D5/0021 [291].
- 452 **Change Number: XBD/TC2/D4/0031 [967]**
- 453 On Page: 129 Line: 3655 Section: 6.4 Character Set Description File
454 (2013 edition Page: 129 Line: 3683)
- 455 Change from:
- 456 Each symbolic name specified in [xref to Table 6-1] shall be included in the file and shall be mapped to a
457 unique coding value, except as noted below. The glyphs represented by the C character constants '{', '}',
458 '_, '- ', '/ ', '\\ ', '. ', and '^ ' have more than one symbolic name; all symbolic names for each such
459 glyph shall be included, each with identical encoding. If some or all of the control characters identified in
460 [xref to Table 6-2] are supported by the implementation, the symbolic names and their corresponding
461 encoding values shall be included in the file. The encoding values shall each be represented in a single
462 byte. Some of the encodings associated with the symbolic names in [xref to Table 6-2] may be the same as
463 characters found in [xref to Table 6-1]; both names shall be provided for each encoding.
- 464 to:
- 465 Each symbolic name specified in [xref to Table 6-1] shall be included in the file. Each character in [xref to
466 Table 6-1] (each row in the table) shall be mapped to a unique coding value. For each character in [xref to
467 Table 6-2] that exists in the character set described by the file, the character's symbolic name(s) from [xref
468 to Table 6-2] and the character's single-byte encoding value shall be included in the file.
- 469 On Page: 130 Line: 3664-3670 Section: 6.4 Character Set Description File
470 (2013 edition Page: 130 Line: 3692-3698)
- 471 Change from:
- 472 **Table 6-2** Control Character Set
473
- | | | | | | |
|-------|-------|-------|------|-------|-------|
| <ACK> | <DC2> | <ENQ> | <FS> | <IS4> | <SOH> |
| <BEL> | <DC3> | <EOT> | <GS> | <LF> | <STX> |

IEEE Std 1003.1™-2008/Cor 2-2016
 IEEE Standard for Information Technology—Portable Operating System Interface (POSIX®)
 Base Specifications, Issue 7—Technical Corrigendum 2

<BS> <DC4> <ESC> <HT> <NAK> <SUB>

<CAN> <ETB> <IS1> <RS> <SYN>

<CR> <DLE> <ETX> <IS2> <SI> <US>

<DC1> <FF> <IS3> <SO> <VT>

474 to:

475 **Table 6-2** Non-Portable Control Characters
 476

Symbolic Name(s)	UCS	Description
<SOH>	<U0001>	START OF HEADING
<STX>	<U0002>	START OF TEXT
<ETX>	<U0003>	END OF TEXT
<EOT>	<U0004>	END OF TRANSMISSION
<ENQ>	<U0005>	ENQUIRY
<ACK>	<U0006>	ACKNOWLEDGE
<SO>	<U000E>	SHIFT OUT
<SI>	<U000F>	SHIFT IN
<DLE>	<U0010>	DATA LINK ESCAPE
<DC1>	<U0011>	DEVICE CONTROL ONE
<DC2>	<U0012>	DEVICE CONTROL TWO
<DC3>	<U0013>	DEVICE CONTROL THREE
<DC4>	<U0014>	DEVICE CONTROL FOUR
<NAK>	<U0015>	NEGATIVE ACKNOWLEDGE
<SYN>	<U0016>	SYNCHRONOUS IDLE
<ETB>	<U0017>	END OF TRANSMISSION BLOCK

<CAN>	<U0018>	CANCEL
	<U0019>	END OF MEDIUM
<SUB>	<U001A>	SUBSTITUTE
<ESC>	<U001B>	ESCAPE
<IS4>, <FS>	<U001C>	INFORMATION SEPARATOR FOUR
<IS3>, <GS>	<U001D>	INFORMATION SEPARATOR THREE
<IS2>, <RS>	<U001E>	INFORMATION SEPARATOR TWO
<IS1>, <US>	<U001F>	INFORMATION SEPARATOR ONE
	<U007F>	DELETE

477

478 *Rationale:* Austin Group Defect Report(s) applied: 967. See <http://austingroupbugs.net/view.php?id=967>.

479 **Change Number: XBD/TC2/D4/0032** [796]

480 On Page: 136 Line: 3846 Section: 7.2 POSIX Locale
 481 (2013 edition Page: 136 Line: 3882)

482 After:

483 Conforming systems shall provide a POSIX locale, also known as the C locale.

484 add:

485 In POSIX.1 the requirements for the POSIX locale are more extensive than the requirements for the C
 486 locale as specified in the C standard. However, in a conforming POSIX implementation, the POSIX locale
 487 and the C locale are identical.

488 *Rationale:* Austin Group Defect Report(s) applied: 796. See <http://austingroupbugs.net/view.php?id=796>.

489 **Change Number: XBD/TC2/D4/0033** [663]

490 On Page: 136 Line: 3849 Section: 7.2 POSIX locale
 491 (2013 edition Page: 136 Line: 3885)

492 Delete:

493 The tables in Section 7.3 describe the characteristics and behavior of the POSIX locale for data consisting
 494 entirely of characters from the portable character set and the control character set. For other characters, the
 495 behavior is unspecified.

IEEE Std 1003.1™-2008/Cor 2-2016
 IEEE Standard for Information Technology—Portable Operating System Interface (POSIX®)
 Base Specifications, Issue 7—Technical Corrigendum 2

- 496 On Page: 139 Line: 3996 Section: 7.3.1 LC_CTYPE
 497 (2013 edition Page: 139 Line: 4032)
- 498 Change from:
- 499 In the POSIX locale, the 26 uppercase letters shall be included:
- 500 A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
- 501 to:
- 502 In the POSIX locale, only:
- 503 A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
- 504 shall be included.
- 505 On Page: 139 Line: 4003 Section: 7.3.1 LC_CTYPE
 506 (2013 edition Page: 139 Line: 4039)
- 507 Change from:
- 508 In the POSIX locale, the 26 lowercase letters shall be included:
- 509 a b c d e f g h i j k l m n o p q r s t u v w x y z
- 510 to:
- 511 In the POSIX locale, only:
- 512 a b c d e f g h i j k l m n o p q r s t u v w x y z
- 513 shall be included.
- 514 On Page: 139 Line: 4009 Section: 7.3.1 LC_CTYPE
 515 (2013 edition Page: 140 Line: 4045)
- 516 Change from:
- 517 In the POSIX locale, all characters in the classes **upper** and **lower** shall be included.
- 518 to:
- 519 In the POSIX locale, only characters in the classes **upper** and **lower** shall be included.
- 520 On Page: 141 Line: 4091 Section: 7.3.1 LC_CTYPE
 521 (2013 edition Page: 141 Line: 4127)
- 522 Change from:
- 523 In the POSIX locale, at a minimum, the 26 lowercase characters:

- 524 to:
- 525 In the POSIX locale, the 26 lowercase characters:
- 526 On Page: 142 Line: 4105 Section: 7.3.1 LC_CTYPE
527 (2013 edition Page: 142 Line: 4141)
- 528 Change from:
- 529 In the POSIX locale, at a minimum, the 26 uppercase characters:
- 530 to:
- 531 In the POSIX locale, the 26 uppercase characters:
- 532 *Rationale:* Austin Group Defect Report(s) applied: 663. See <http://austingroupbugs.net/view.php?id=663>.
- 533 **Change Number: XBD/TC2/D4/0034** [663]
- 534 On Page: 143 Line: 4142 Section: 7.3.1.1 LC_CTYPE Category in the POSIX Locale
535 (2013 edition Page: 143 Line: 4178)
- 536 Change from:
- 537 The character classifications for the POSIX locale follow; the code listing depicts the *localedef* input, and
538 the table represents the same information, sorted by character.
- 539 to:
- 540 The minimum character classifications for the POSIX locale follow; the code listing depicts the *localedef*
541 input, and the table represents the same information, sorted by character. Implementations may add
542 additional characters to the **cntrl** and **punct** classifications but shall not make any other additions.
- 543 On Page: 143 Line: 4145 Section: 7.3.1.1 LC_CTYPE Category in the POSIX Locale
544 (2013 edition Page: 143 Line: 4181)
- 545 Change from:
- 546 # The following is the POSIX locale LC_CTYPE.
547 # "alpha" is by default "upper" and "lower"
548 # "alnum" is by definition "alpha" and "digit"
549 # "print" is by default "alnum", "punct", and the <space>
550 # "graph" is by default "alnum" and "punct"
- 551 to:
- 552 # The following is the minimum POSIX locale LC_CTYPE.
553 # "alpha" is by definition "upper" and "lower"
554 # "alnum" is by definition "alpha" and "digit"
555 # "print" is by definition "alnum", "punct", and the <space>
556 # "graph" is by definition "alnum" and "punct"
- 557 *Rationale:* Austin Group Defect Report(s) applied: 663. See <http://austingroupbugs.net/view.php?id=663>.

- 558 **Change Number: XBD/TC2/D4/0035** [584]
- 559 On Page: 143 Line: 4173 Section: 7.3.1.1 LC_CTYPE Category in the POSIX Locale
- 560 Change from:
- 561 <hyphen>
- 562 to:
- 563 <hyphen-minus>
- 564 *Rationale:* Austin Group Defect Report(s) applied: 584. See <http://austingroupbugs.net/view.php?id=584>.
- 565 **Change Number: XBD/TC2/D4/0036** [584]
- 566 On Page: 144 Line: 4243 Section: 7.3.1.1 LC_CTYPE Category in the POSIX Locale
- 567 Change from:
- 568 <hyphen>
- 569 to:
- 570 <hyphen-minus>
- 571 *Rationale:* Austin Group Defect Report(s) applied: 584. See <http://austingroupbugs.net/view.php?id=584>.
- 572 **Change Number: XBD/TC2/D4/0037** [938]
- 573 On Page: 146 Line: 4330 Section: 7.3.2 LC_COLLATE
- 574 (2013 edition Page: 147 Line: 4366)
- 575 Change from:
- 576 (*sort*, *uniq*, and so on)
- 577 to:
- 578 (*ls*, *sort*, and so on)
- 579 On Page: 147 Line: 4357 Section: 7.3.2 LC_COLLATE
- 580 (2013 edition Page: 147 Line: 4393)
- 581 Add a new paragraph and two small-font notes after the numbered list:
- 582 All implementation-provided locales (either preinstalled or provided as locale definitions which can be
- 583 installed later) should define a collation sequence that has a total ordering of all characters unless the locale
- 584 name has an '@' modifier indicating that it has a special collation sequence (for example, @icase could
- 585 indicate that each upper- and lower-case character pair collates equally).

- 586 <small>Note: a future version of this standard may require these locales to define a collation sequence that
587 has a total ordering of all characters (by changing "should" to "shall").</small>
- 588 <small>Note: users installing their own locales should ensure that they define a collation sequence with a
589 total ordering of all characters unless an '@' modifier in the locale name (such as @icase) indicates that it
590 has a special collation sequence.</small>
- 591 On Page: 149 Line: 4467 Section: 7.3.2.4 Collation Order
592 (2013 edition Page: 150 Line: 4503)
- 593 Add a new paragraph and a small-font note:
- 594 Weights should be assigned such that the collation sequence has a total ordering of all characters unless an
595 '@' modifier in the locale name indicates that it has a special collation sequence.
- 596 <small>Note: a future version of this standard may require a total ordering of all characters for
597 implementation-provided locales that do not have an '@' modifier in the locale name. See [xref to
598 7.3.2].</small>
- 599 On Page: 150 Line: 4481 Section: 7.3.2.4 Collation Order
600 (2013 edition Page: 150 Line: 4517)
- 601 Change from:
- 602 Characters specified via an explicit or implicit UNDEFINED special symbol shall by default be assigned
603 the same primary weight (that is, they belong to the same equivalence class).
- 604 to:
- 605 Characters specified via an explicit or implicit UNDEFINED special symbol shall by default be assigned
606 the same primary weight (that is, they belong to the same equivalence class) if the collation order has more
607 than one weight level. If the collation order has only one weight level, these characters should be assigned
608 unique primary weights, equal to the relative order of their character in the character collation sequence,
609 but may be assigned the same primary weight.
- 610 <small>Note: a future version of this standard may require these characters to be assigned unique primary
611 weights if the collation order has only one weight level.</small>
- 612 On Page: 150 Line: 4503 Section: 7.3.2.4 Collation Order
613 (2013 edition Page: 151 Line: 4539)
- 614 Delete the first entry in the example collation order:
- 615 UNDEFINED IGNORE; IGNORE
- 616 On Page: 150 Line: 4516 Section: 7.3.2.4 Collation Order
617 (2013 edition Page: 151 Line: 4552)
- 618 Add the following as the last entry in the example collation order:
- 619 UNDEFINED IGNORE; . . .

IEEE Std 1003.1™-2008/Cor 2-2016
IEEE Standard for Information Technology—Portable Operating System Interface (POSIX®)
Base Specifications, Issue 7—Technical Corrigendum 2

- 620 On Page: 151 Line: 4519 Section: 7.3.2.4 Collation Order
621 (2013 edition Page: 151 Line: 4555)
- 622 Delete item 1 in the numbered list:
- 623 The **UNDEFINED** means that all characters not specified in this definition (explicitly or via the ellipsis)
624 shall be ignored for collation purposes.
- 625 and renumber items 2-4 to be 1-3.
- 626 On Page: 151 Line: 4527 Section: 7.3.2.4 Collation Order
627 (2013 edition Page: 151 Line: 4563)
- 628 Add a new item 4 to the numbered list:
- 629 The **UNDEFINED** means that all characters not specified in this definition (explicitly or via the ellipsis)
630 shall be ignored when comparing primary weights, and have individual secondary weights based on their
631 ordinal encoded values.
- 632 *Rationale:* Austin Group Defect Report(s) applied: 938. See <http://austingroupbugs.net/view.php?id=938>.
- 633 **Change Number: XBD/TC2/D4/0038** [663]
- 634 On Page: 151 Line: 4531 Section: 7.3.2.6 LC_COLLATE Category in the POSIX Locale
635 (2013 edition Page: 151 Line: 4567)
- 636 Change from:
- 637 The collation sequence definition of the POSIX locale follows; the code listing depicts the *localedef* input.
638 to:
- 639 The minimum collation sequence definition of the POSIX locale follows; the code listing depicts the
640 *localedef* input. All characters not explicitly listed here shall be inserted in the character collation order
641 after the listed characters and shall be assigned unique primary weights. If the listed characters have ASCII
642 encoding, the other characters shall be in ascending order according to their coded character set values;
643 otherwise, the order of the other characters is unspecified. The collation sequence shall not include any
644 multi-character collating elements.
- 645 On Page: 151 Line: 4534 Section: 7.3.2.6 LC_COLLATE Category in the POSIX Locale
646 (2013 edition Page: 151 Line: 4570)
- 647 Change from:
- 648 # This is the POSIX locale definition for the LC_COLLATE category.
649 # The order is the same as in the ASCII codeset.
- 650 to:
- 651 # This is the minimum input for the POSIX locale definition for the
652 # LC_COLLATE category. Characters in this list are in the same order
653 # as in the ASCII codeset.

654 *Rationale:* Austin Group Defect Report(s) applied: 663. See <http://austingroupbugs.net/view.php?id=663>.

655 **Change Number:** XBD/TC2/D4/0039 [584]

656 On Page: 152 Line: 4582 Section: 7.3.2.6 LC_COLLATE Category in the POSIX Locale

657 Change from:

658 <hyphen>

659 to:

660 <hyphen-minus>

661 *Rationale:* Austin Group Defect Report(s) applied: 584. See <http://austingroupbugs.net/view.php?id=584>.

662 **Change Number:** XBD/TC2/D4/0040 [912]

663 On Page: 163 Line: 5073 Section: 7.3.5.3 LC_TIME Category in the POSIX Locale
664 (2013 edition Page: 163 Line: 5109)

665 In the LC_TIME category definition, change from:

666 <percent_sign>

667 to:

668 <percent-sign>

669 *Rationale:* Austin Group Defect Report(s) applied: 912. See <http://austingroupbugs.net/view.php?id=912>.

670 **Change Number:** XBD/TC2/D4/0041 [584]

671 On Page: 179 Line: 5728 Section: 8.3 Other Environment Variables

672 In the description of TZ change from:

673 <plus-sign> ('+') character, or the minus-sign

674 to:

675 <plus-sign> ('+') character, or the <hyphen-minus>

676 *Rationale:* Austin Group Defect Report(s) applied: 584. See <http://austingroupbugs.net/view.php?id=584>.

677 **Change Number:** XBD/TC2/D4/0042 [554]

678 On Page: 182 Line: 5842-5848 Section: 9.2 Regular Expression General Requirements

679 Change from:

IEEE Std 1003.1™-2008/Cor 2-2016
 IEEE Standard for Information Technology—Portable Operating System Interface (POSIX®)
 Base Specifications, Issue 7—Technical Corrigendum 2

In the regular expression processing described in POSIX.1-2008, the <newline> is regarded as an ordinary character and both a <period> and a non-matching list can match one. The Shell and Utilities volume of POSIX.1-2008 specifies within the individual descriptions of those standard utilities employing regular expressions whether they permit matching of <newline> characters; if not stated otherwise, the use of literal <newline> characters or any escape sequence equivalent produces undefined results.

to:

In the functions processing regular expressions described in the System Interfaces volume of POSIX.1-2008, the <newline> is regarded as an ordinary character and both a <period> and a non-matching list can match one. The Shell and Utilities volume of POSIX.1-2008 specifies within the individual descriptions of those standard utilities employing regular expressions whether they permit matching of <newline> characters; if not stated otherwise, the use of literal <newline> characters or any escape sequence equivalent in either patterns or matched text produces undefined results .

Change Number: XBD/TC2/D4/0043 [554]

On Page: 183 Line: 5875 Section: 9.3.2 BRE Ordinary Characters

Change from:

The interpretation of an ordinary character preceded by a <backslash> (\\) is undefined, except for:

to:

The interpretation of an ordinary character preceded by an unescaped <backslash> (\\) is undefined, except for:

On Page: 183 Line: 5887 Section: 9.3.3 BRE Special Characters

Change from:

that is not preceded by a <backslash>

to:

that is unescaped

On Page: 184 Line: 5894-5896 Section: 9.3.3 BRE Special Characters

Change from:

The <circumflex> shall be special when used as:

- An anchor (see Section XXX on page YYY)
- The first character of a bracket expression (see Section AAA on page BBB)

to:

The <circumflex> shall be special when used as an anchor (see Section XXX, on page YYY). The <circumflex> shall signify a non matching list expression when it occurs first in a list, immediately following a <left-square-bracket> (see Section AAA on page BBB).

- 713 *Rationale:* Austin Group Defect Report(s) applied: 554. See <http://austingroupbugs.net/view.php?id=554>.
- 714 **Change Number:** XBD/TC2/D4/0044 [938]
- 715 On Page: 184 Line: 5902 Section: 9.3.5 RE Bracket Expression
716 (2013 edition Page: 184 Line: 5944)
- 717 Change from:
- 718 A bracket expression (an expression enclosed in square brackets, "[]") is an RE that shall match a single
719 collating element contained in the non-empty set of collating elements represented by the bracket
720 expression.
- 721 to:
- 722 A bracket expression (an expression enclosed in square brackets, "[]") is an RE that shall match a specific
723 set of single characters, and may match a specific set of multi-character collating elements, based on the
724 non-empty set of list expressions contained in the bracket expression.
- 725 On Page: 184 Line: 5907 Section: 9.3.5 RE Bracket Expression
726 (2013 edition Page: 184 Line: 5949)
- 727 In list item 1, change from:
- 728 It consists of one or more expressions: collating elements, collating symbols, ...
- 729 to:
- 730 It consists of one or more expressions: ordinary characters, collating elements, collating symbols, ...
- 731 On Page: 184 Line: 5921 Section: 9.3.5 RE Bracket Expression
732 (2013 edition Page: 184 Line: 5963)
- 733 In list item 2, change from:
- 734 A matching list expression specifies a list that shall match any single-character collating element in any of
735 the expressions represented in the list. The first character in the list shall not be the <circumflex>; for
736 example, "[abc]" is an RE that matches any of the characters 'a', 'b', or 'c'.
- 737 to:
- 738 A matching list expression specifies a list that shall match any single character that is matched by one of
739 the expressions represented in the list. The first character in the list can not be the <circumflex>. An
740 ordinary character in the list should only match that character, but may match any single character that
741 collates equally with that character; for example, "[abc]" is an RE that should only match one of the
742 characters 'a', 'b', or 'c'.
- 743 <small>Note: a future version of this standard may require that an ordinary character in the list only
744 matches that character.</small>
- 745 *Rationale:* Austin Group Defect Report(s) applied: 938. See <http://austingroupbugs.net/view.php?id=938>.

746 **Change Number: XBD/TC2/D4/0045** [872]

747 On Page: 184 Line: 5926 Section: 9.3.5 RE Bracket Expression
 748 (2013 edition Page: 184 Line: 5968)

749 In list item 3, change from:

750 A non-matching list expression begins with a <circumflex> (^), and specifies a list that shall match any
 751 single-character collating element except for the expressions represented in the list after the leading
 752 <circumflex>.

753 to:

754 A non-matching list expression begins with a <circumflex> (^), and the matching behavior shall be the
 755 logical inverse of the corresponding matching list expression (the same bracket expression but without the
 756 leading <circumflex>).

757 *Rationale:* Austin Group Defect Report(s) applied: 872. See <http://austingroupbugs.net/view.php?id=872>.

758 **Change Number: XBD/TC2/D4/0046** [938]

759 On Page: 184 Line: 5928 Section: 9.3.5 RE Bracket Expression
 760 (2013 edition Page: 184 Line: 5970)

761 In list item 3, change from:

762 For example, "[^abc]" is an RE that matches any character except the characters 'a', 'b', or 'c'.

763 to:

764 For example, if the RE "[abc]" only matches 'a', 'b', or 'c', then "[^abc]" is an RE that matches any character
 765 except 'a', 'b', or 'c'.

766 On Page: 185 Line: 5953 Section: 9.3.5 RE Bracket Expression
 767 (2013 edition Page: 185 Line: 5995)

768 In list item 6, change from:

769 The set of single-character collating elements whose characters belong to the character class

770 to:

771 The set of single characters that belong to the character class

772 *Rationale:* Austin Group Defect Report(s) applied: 938. See <http://austingroupbugs.net/view.php?id=938>.

773 **Change Number: XBD/TC2/D4/0047** [584]

774 On Page: 185 Line: 5972 Section: 9.3.5 RE Bracket Expression

775 Change from:

776 <hyphen>
777 to:
778 <hyphen-minus>
779 *Rationale:* Austin Group Defect Report(s) applied: 584. See <http://austingroupbugs.net/view.php?id=584>.
780 **Change Number: XBD/TC2/D4/0048** [584]
781 On Page: 186 Line: 5982,5989,5992 Section: 9.3.5 RE Bracket Expression
782 Change from:
783 <hyphen>
784 to:
785 <hyphen-minus>
786 *Rationale:* Austin Group Defect Report(s) applied: 584. See <http://austingroupbugs.net/view.php?id=584>.
787 **Change Number: XBD/TC2/D4/0049** [595]
788 On Page: 186 Line: 6016 Section: 9.3.6 BREs Matching Multiple Characters
789 Change rule 3 from:
790 For example, the expression "`^(.*)\1$`" matches lines consisting of two adjacent appearances of the same
791 string,
792 to:
793 For example, the expression "`^(.*)\1$`" matches strings consisting of two adjacent appearances of the
794 same substring,
795 On Page: 187 Line: 6053 Section: 9.3.8 BRE Expression Anchoring
796 Change from:
797 A BRE can be limited to matching strings that begin or end a line; this is called "anchoring".
798 to:
799 A BRE can be limited to matching expressions that begin or end a string; this is called "anchoring".
800 *Rationale:* Austin Group Defect Report(s) applied: 595. See <http://austingroupbugs.net/view.php?id=595>.
801

- 802 **Change Number: XBD/TC2/D4/0050 [554]**
- 803 On Page: 188 Line: 6082-6083 Section: 9.4.2 ERE Ordinary Characters
- 804 Change from:
- 805 The interpretation of an ordinary character preceded by a <backslash> ("\") is undefined.
- 806 to:
- 807 The interpretation of an ordinary character preceded by an unescaped <backslash> ("\") is undefined, except
 808 in the context of a bracket expression (see XREF to ERE bracket expression).
- 809 On Page: 188 Line: 6092 Section: 9.4.3 ERE Special Characters
- 810 Add the following text after line 6092:
- 811 A <left-square-bracket> that is unescaped and is not part of a bracket expression also produces undefined
 812 results.
- 813 On Page: 188 Line: 6098-6099 Section: 9.4.3 ERE Special Characters
- 814 Change from:
- 815 If these characters appear first in an ERE, or immediately following a <vertical-line>, <circumflex>, or
 816 <left-parenthesis>
- 817 to:
- 818 If these characters appear first in an ERE, or immediately following an unescaped <vertical-line>,
 819 <circumflex>, <dollar-sign>, or <left-parenthesis>
- 820 On Page: 189 Line: 6106-6109 Section: 9.4.3 ERE Special Characters
- 821 Change from:
- 822 The <circumflex> shall be special when used as:
 823 - An anchor (see Section XXX on page YYY)
 824 - The first character of a bracket expression (see Section AAA on page BBB)
- 825 to:
- 826 The <circumflex> shall be special when used as an anchor (see Section XXX, on page YYY). The
 827 <circumflex> shall signify a non matching list expression when it occurs first in a list, immediately
 828 following a <left-square-bracket> (see Section AAA on page BBB).
- 829 *Rationale:* Austin Group Defect Report(s) applied: 554. See <http://austingroupbugs.net/view.php?id=554>.
- 830

- 831 **Change Number: XBD/TC2/D4/0051** [595]
- 832 On Page: 190 Line: 6175 Section: 9.4.9 ERE Expression Anchoring
- 833 Change from:
- 834 An ERE can be limited to matching strings that begin or end a line; this is called "anchoring".
- 835 to:
- 836 An ERE can be limited to matching expressions that begin or end a string; this is called "anchoring".
- 837 *Rationale:* Austin Group Defect Report(s) applied: 595. See <http://austingroupbugs.net/view.php?id=595>.
- 838 **Change Number: XBD/TC2/D4/0052** [554]
- 839 On Page: 192 Line: 6233 Section: 9.5.1 BRE/ERE Grammar Lexical Conventions
- 840 For token SPEC_CHAR delete the phrase:
- 841 or when first in a bracket expression
- 842 On Page: 195 Line: 6379-6380 Section: 9.5.3 ERE Grammar
- 843 Change from:
- 844 The ERE grammar does not permit several constructs that previous sections specify as having undefined
- 845 results:
- 846 to:
- 847 The ERE grammar does not permit several constructs that previous sections specify as having undefined
- 848 results. Additionally, there are some constructs which the grammar permits but which still give undefined
- 849 results:
- 850 On Page: 195 Line: 6381 Section: 9.5.3 ERE Grammar
- 851 Change from:
- 852 ORD_CHAR preceded by a <backslash> character
- 853 to:
- 854 ORD_CHAR preceded by an unescaped <backslash> character
- 855 On Page: 195 Line: 6383 Section: 9.5.3 ERE Grammar
- 856 Add '\$' to the list of characters.
- 857 *Rationale:* Austin Group Defect Report(s) applied: 554. See <http://austingroupbugs.net/view.php?id=554>.

IEEE Std 1003.1™-2008/Cor 2-2016
 IEEE Standard for Information Technology—Portable Operating System Interface (POSIX®)
 Base Specifications, Issue 7—Technical Corrigendum 2

858 **Change Number: XBD/TC2/D4/0053** [916]

859 On Page: 195 Line: 6387 Section: 9.5.3 ERE Grammar
 860 (2013 edition Page: 195 Line: 6433)

861 Change from:

862 Conforming applications cannot use such constructs.

863 to:

864 Strictly conforming applications cannot use such constructs.

865 *Rationale:* Austin Group Defect Report(s) applied: 916. See <http://austingroupbugs.net/view.php?id=916>.

866 **Change Number: XBD/TC2/D4/0054** [967]

867 On Page: 198 Line: 6438-6454 Section: 10.2 Output Devices and Terminal Types
 868 (2013 edition Page: 198 Line: 6484-6500)

869 Delete the two **Symbolic Name** columns from Table 10-1.

870 *Rationale:* Austin Group Defect Report(s) applied: 967. See <http://austingroupbugs.net/view.php?id=967>.

871 **Change Number: XBD/TC2/D4/0055** [745]

872 On Page: 204 Line: 6682,6684 Section: 11.1.9 Special Characters

873 On line 6682, for CR change from:

874 carriage-return

875 to:

876 <carriage-return>

877 On line 6684, append a sentence to the description of CR:

878 It cannot be changed.

879 *Rationale:* Austin Group Defect Report(s) applied: 745. See <http://austingroupbugs.net/view.php?id=745>.

880 **Change Number: XBD/TC2/D4/0056** [584]

881 On Page: 213 Line: 7006 Section: 12.1 Utility Argument Syntax

882 Change from:

883 <hyphen>

884 to:

885 <hyphen-minus>

886 *Rationale:* Austin Group Defect Report(s) applied: 584. See <http://austingroupbugs.net/view.php?id=584>.

887 **Change Number: XBD/TC2/D4/0057** [813]

888 On Page: 214 Line: 7056 Section: 12.1 Utility Argument Syntax

889 After the third bullet item, add a new bullet item:

- 890 • When the utility description states that the number is a file size-related value (such as a file size or
891 offset, line number, or block count), numerals in the range 0 to the maximum file size supported
892 by the implementation are syntactically recognized as numeric values (see XCU 1.5
893 Considerations for Utilities in Support of Files of Arbitrary Size). Where negative values are
894 permitted, any value in the range -(maximum file size) to the maximum file size is accepted.

895 *Rationale:* Austin Group Defect Report(s) applied: 813. See <http://austingroupbugs.net/view.php?id=813>.
896 The normative requirement in XCU 1.5 does not match the syntax utility guidelines which suggest very
897 large values may be supported but are not required to be.

898 **Change Number: XBD/TC2/D4/0058** [579]

899 On Page: 220 Line: 7211 Section: < aio.h>

900 In the DESCRIPTION section, change from:

901 The tag **sigevent** shall be declared as naming an incomplete structure type, the contents of which are
902 described in the <**signal.h**> header.

903 to:

904 The <**aio.h**> header shall define the **sigevent** structure and **sigval** union as described in <**signal.h**>.

905 *Rationale:* Austin Group Defect Report(s) applied: 579. See <http://austingroupbugs.net/view.php?id=579>.

906 **Change Number: XBD/TC2/D4/0059** [496]

907 On Page: 236 Line: 7737 Section: <errno.h>

908 In the DESCRIPTION section, change from:

909 [ENOSYS] Function not supported.

910 to:

911 [ENOSYS] Functionality not supported.

912 *Rationale:* Austin Group Defect Report(s) applied: 496. See <http://austingroupbugs.net/view.php?id=496>.