

ISO

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION

ISO RECOMMENDATION R 1117

BONDED ABRASIVE PRODUCTS
GRINDING WHEEL DIMENSIONS
(PART 2)

1st EDITION
September 1969

COPYRIGHT RESERVED

The copyright of ISO Recommendations and ISO Standards belongs to ISO Member Bodies. Reproduction of these documents, in any country, may be authorized therefore only by the national standards organization of that country, being a member of ISO.

For each individual country the only valid standard is the national standard of that country.

Printed in Switzerland

Also issued in French and Russian. Copies to be obtained through the national standards organizations.

BRIEF HISTORY

The ISO Recommendation R 1117, *Bonded abrasive products – Grinding wheel dimensions (Part 2)*, was drawn up by Technical Committee ISO/TC 29, *Small tools*, the Secretariat of which is held by the Association Française de Normalisation (AFNOR).

Work on this question led to the adoption of a Draft ISO Recommendation.

In June 1968, this Draft ISO Recommendation (No. 1596) was circulated to all the ISO Member Bodies for enquiry. It was approved, subject to a few modifications of an editorial nature, by the following Member Bodies :

Australia	Italy	Switzerland
Belgium	Japan	Thailand
Czechoslovakia	Netherlands	Turkey
France	New Zealand	U.A.R.
Germany	Peru	United Kingdom
Greece	Poland	U.S.A.
Hungary	Portugal	U.S.S.R.
India	South Africa, Rep. of	Yugoslavia
Ireland	Spain	
Israel	Sweden	

No Member Body opposed the approval of the Draft.

The Draft ISO Recommendation was then submitted by correspondence to the ISO Council, which decided, in September 1969, to accept it as an ISO RECOMMENDATION.

CONTENTS

	page
Introduction	5
1. Threaded insert disks	6
1.1 Dimensions	6
1.1.1 Workpieces held in hand	6
1.1.2 Workpieces held mechanically	6
1.2 Drillings	7
1.2.1 Drillings : metric series	8
1.2.2 Drillings : inch series	15
2. Wheels for tool and cutter grinding	22
2.1 Plain wheels – Type 1	22
2.2 Straight cup wheels – Type 6	22
2.3 Taper cup wheels – Type 11	23
2.4 Dish wheels – Type 12	23
3. Internal grinding wheels	24
3.1 Plain wheels – Type 1	24
3.2 Wheels with one recess – Type 5	25
4. Cutting off wheels with fabric reinforcements	26
5. Segments of isosceles trapezoidal sections	26

BONDED ABRASIVE PRODUCTS

GRINDING WHEEL DIMENSIONS

(PART 2)

INTRODUCTION

This ISO Recommendation is a continuation of ISO Recommendation R 603, *Bonded abrasive products – Grinding wheel dimensions (Part 1)*.

Save for the exceptions indicated by a reference mark, the dimensions retained for the wheels specified in this ISO Recommendation are those provided in ISO Recommendation R 525, *Bonded abrasive products – General features – Designation – Ranges of dimensions – Profiles* and in its Addendum 1, *Dimensions of the wheel holes for special applications and tolerances*.


The numerical values retained in this ISO Recommendation are given in both systems of units (metric and inch). The holes being identical, wheels of the metric series and those of the inch series can be mounted on the same machines; however, the overall dimensions possibly being slightly different, wheels of both series can only be considered as equivalent.

The symbols for dimensions used in the figures and tables are those provided in ISO Recommendation R 603. They may be replaced in national standards by those in conformity with the rules prevailing in the country concerned, until international agreement regarding a single reference system is reached.

The figures accompanying the tables are only rough sketches which permit reference to the useful dimensions; particularly, for cup grinding wheels and for plain grinding wheels with a recess, the inset angles should be replaced by a fillet to avoid any initiation of rupture, but permitting, however, correct application of the pieces on the shaft.

1. THREADED INSERT DISKS

1.1 Dimensions



1.1.1 Workpieces held in hand

Dimensions in millimetres				Dimensions in inches					
<i>D</i>	<i>E</i>		Drillings See clause 1.2	<i>D</i>	<i>E</i>		Drillings See clause 1.2		
	Speed not exceeding 35 m/s	Speed higher than 35 m/s			Speed not exceeding 115 ft/s	Speed higher than 115 ft/s			
300	50	50	Nuts M10	12	2	2	Nuts $\frac{3}{8}$ UNC		
350				14					
400				16					
450				18					
500				20					
600				24					
750				30					
900				36					
1060				42					
1346*				53*					
1829*				72*					

1.1.2 Workpieces held mechanically – Speed not exceeding 35 m/s (115 ft/s).

Dimensions in millimetres			Dimensions in inches		
<i>D</i>	<i>E</i>	Drillings See clause 1.2	<i>D</i>	<i>E</i>	Drillings See clause 1.2
300	90*	Nuts M10	12	3 ½*	Nuts 3/8 UNC
350			14		
400			16		
450			18		
500			20		
600			24		
750			30		
900			36		
1060	42		2		
1346*	53*				
1829*	72*				

* Dimensions not included in ISO Recommendation R 525, *Bonded abrasive products – General features – Designation – Ranges of dimensions – Profiles*.

1.2 Drillings

The drawings on pages 8 to 21 correspond to the drillings and to the boring of the fixing plate seen from the face.


Some of the nuts may be omitted in the wheels but it is recommended that such as are used should correspond to one point of the drillings provided for.

For wheels with a diameter D of 300, 350, 400, 450, 500, 600 and 750 mm, or of 12, 14, 16, 18, 20, 24 and 30 in, the nuts are equally spaced on the corresponding circle.

The dimensions of the nuts should be indicated on the wheels.


1.2.1 Drillings : metric series

Dimensions in millimetres
 $D = 300, 350$ and 400 mm




$D = 300$ mm

Drilling circles		Number of holes
Indexes	Diameters	
①	120.65	3 at 120°
②	266.70	6 at 60°



$D = 350$ mm


Drilling circles		Number of holes
Indexes	Diameters	
①	177.80	4 at 90°
②	304.80	8 at 45°



$D = 400$ mm

Drilling circles		Number of holes
Indexes	Diameters	
①	190.50	5 at 72°
②	323.85	10 at 36°


Dimensions in millimetres
 $D = 450, 500$ and 600 mm



$D = 450$ mm


Drilling circles		Number of holes
Indexes	Diameters	
①	101.60	3 at 120°
②	203.20	5 at 72°
③	279.40	5 at 72°
④	374.65	10 at 36°

Drilling circles		Number of holes
Indexes	Diameters	
①	107.95	3 at 120°
②	203.20	6 at 60°
③	304.80	6 at 60°
④	431.80	12 at 30°



$D = 500$ mm

Drilling circles		Number of holes
Indexes	Diameters	
①	203.20	6 at 60°
②	330.20	6 at 60°
③	457.20	6 at 60°
④	558.80	12 at 30°



$D = 600$ mm