

ISO

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION

ISO RECOMMENDATION R 1685

SHIPBUILDING DETAILS

MULTI-PURPOSE CHOCKS OF CAST STEEL

1st EDITION

October 1971

Withdrawn in 1984

COPYRIGHT RESERVED

The copyright of ISO Recommendations and ISO Standards belongs to ISO Member Bodies. Reproduction of these documents, in any country, may be authorized therefore only by the national standards organization of that country, being a member of ISO.

For each individual country the only valid standard is the national standard of that country.

Printed in Switzerland

Also issued in French and Russian. Copies to be obtained through the national standards organizations.

BRIEF HISTORY

The ISO Recommendation R 1685, *Shipbuilding details – Multi-purpose chocks of cast steel*, was drawn up by Technical Committee ISO/TC 8, *Shipbuilding details*, the Secretariat of which is held by the Netherlands Normalisatie-instituut (NNI).

Work on this question led to the adoption of Draft ISO Recommendation No. 1685, which was circulated to all the ISO Member Bodies for enquiry in October 1968. It was approved by over 60 % of the votes cast.

However, in view of important comments involving the technical substance of this Draft, the ISO/TC 8 Secretariat decided to withdraw the document, and drew up a second Draft ISO Recommendation No. 1685. The latter was circulated to all the ISO Member Bodies for enquiry in January 1971. It was approved, subject to a few modifications of an editorial nature, by the following Member Bodies :

Australia	India	Norway
Belgium	Israel	Poland
Czechoslovakia	Italy	Romania
France	Japan	Thailand
Germany	Netherlands	U.A.R.
Greece	New Zealand	United Kingdom

No Member Body opposed the approval of the second Draft.

This second Draft ISO Recommendation was then submitted by correspondence to the ISO Council, which decided to accept it as an ISO RECOMMENDATION.

SHIPBUILDING DETAILS

MULTI-PURPOSE CHOCKS OF CAST STEEL

1st Edition – October 1971

ERRATUM

Page 3 :

In the section A-A, the radius r_1 applies to the working surface of the chock as shown in the following drawing, and not to the non-working surface.

