

First edition
1997-12-15

Boron treated engineering steels for quenching and tempering

Aciers de construction mécanique traités au bore pour trempe et revenu



Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The main task of technical committees is to prepare International Standards, but in exceptional circumstances a technical committee may propose the publication of a Technical Report of one of the following types:

- type 1, when the required support cannot be obtained for the publication of an International Standard, despite repeated efforts;
- type 2, when the subject is still under technical development or where for any other reason there is the future but not immediate possibility of an agreement on an International Standard;
- type 3, when a technical committee has collected data of a different kind from that which is normally published as an International Standard ("state of the art", for example).

Technical Reports of types 1 and 2 are subject to review within three years of publication, to decide whether they can be transformed into International Standards. Technical Reports of type 3 do not necessarily have to be reviewed until the data they provide are considered to be no longer valid or useful.

ISO/TR 11637, which is a Technical Report of type 2, was prepared by Technical Committee ISO/TC 17, *Steel* Subcommittee SC 4, *Heat treatable and alloy steels*.

© ISO 1997

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland
Internet central@iso.ch
X.400 c=ch; a=400net; p=iso; o=isos; s=central

Printed in Switzerland

This document is being issued in the Technical Report (type 2) series of publications (according to subclause G.3.2.2 of part 1 of the ISO/IEC Directives, 1995) as a “prospective standard for provisional application” in the field of boron treated engineering steels because there is an urgent need for guidance on how standards in this field should be used to meet an identified need.

This document is not to be regarded as an “International Standard”. It is proposed for provisional application so that information and experience of its use in practice may be gathered. Comments on the content of this document should be sent to the ISO Central Secretariat.

A review of this Technical Report (type 2) will be carried out not later than three years after its publication with the options of: extension for another three years; conversion into an International Standard; or withdrawal.

Annex A forms an integral part of this Technical report. Annex B is for information only.

Introduction

For the following two reasons the attempt to establish an International Standard for boron treated engineering steel for quenching and tempering has proved especially difficult.

- a) The number of types of these steels, applied until now mostly as company grades, is very great world-wide, so that concentration on a reasonable number of internationally standardized steels has caused problems.
- b) The hardenability of these steels can, even for types with the same specified chemical composition, vary greatly because of differences in the effectiveness of the boron and in the content of residual elements. Consequently, it seemed reasonable to specify tight limits for only the most important characteristic of these steels, namely the hardenability, and to permit relatively wide ranges for the carbon, manganese and chromium contents. In this way manufacturers have the possibility of complying with the tight hardenability requirements independent of the melting procedure applied.

For the reasons given under b) the proposals of the various members for the hardenability of the individual steels differed significantly. The hardenability scatterbands specified in table 5 and figure 1 were therefore mainly derived with the help of formulae established by what is considered world-wide as the greatest customer of boron treated steels and published in ASTM A 255.

It is to be expected that the application of the specifications in this document will not cause any problems. Nevertheless, it was agreed to publish this first edition not as an International Standard but as an ISO Technical Report of type 2 so that for a trial period of three years information and experience of its use in practice can be gathered.

Boron treated engineering steels for quenching and tempering

1 Scope

1.1 This Technical Report gives the technical delivery requirements for

- semi-finished products, for example blooms, billets, slabs (see note 3 below);
- bars (see note 3 below);
- wire rod;
- hot or cold rolled sheet/plate and strip (see note 2 below);
- hammer or drop forgings (see note 3 below).

These articles are manufactured from the boron alloy steels listed in table 3 and supplied in one of the heat-treatment conditions given for the different types of products in table 1, lines 2 to 5 for columns 4 to 8 and in one of the surface conditions given in table 2.

The steels are in general intended for the fabrication of quenched and tempered or austempered (see 3.3 and note 1 below) machine parts.

This Technical Report is not applicable for steels for cold heading which are covered by ISO 4954.

NOTES

1 For the purpose of simplification the term “quenched and tempered” is, unless otherwise indicated, used in the following also for the austempered condition.

2 The terms “plate” or “flat product” in the following also include, unless otherwise stated, wide flats.

3 Hammer-forged semi-finished products (blooms, billets, slabs, etc.) and hammer-forged bars are in the following covered under semi-finished products or bars and not under the term “hammer and drop forgings”.

1.2 In special cases, variations in these technical delivery requirements or additions to them may form the subject of an agreement at the time of enquiry and order (see annex A).

1.3 In addition to this Technical Report, the general technical delivery requirements of ISO 404 are applicable.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this Technical Report. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this Technical Report are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

- ISO 148:1983, *Steel — Charpy impact test (V-notch)*.
- ISO 377:1997, *Steel and steel products — Location and preparation of test pieces for mechanical testing*.
- ISO 404:1992, *Steel and steel products — General technical delivery requirements*.
- ISO 642:1979, *Steel — Hardenability test by end quenching (Jominy test)*.
- ISO 643:1983, *Steels — Micrographic determination of the ferritic or austenitic grain size*.
- ISO 1035-1:1980, *Hot-rolled steel bars — Part 1: Dimensions of round bars*.
- ISO 1035-2:1980, *Hot-rolled steel bars — Part 2: Dimensions of square bars*.
- ISO 1035-3:1980, *Hot-rolled steel bars — Part 3: Dimensions of flat bars*.
- ISO 1035-4:1982, *Hot-rolled steel bars — Part 4: Tolerances*.
- ISO 3887:1976, *Steel, non-alloy and low-alloy — Determination of depth of decarburization*.
- ISO 4948-1:1982, *Steels — Classification — Part 1: Classification of steels into unalloyed and alloy steels based on chemical composition*.
- ISO 4948-2:1981, *Steels — Classification — Part 2: Classification of unalloyed and alloy steels according to main quality classes and main property or application characteristics*.
- ISO 4954:1993, *Steels for cold heading and cold extruding*.
- ISO 4967:—¹⁾, *Steel — Determination of content of non-metallic inclusions — Micrographic method using standard diagrams*.
- ISO 6506-1:—²⁾, *Metallic materials — Brinell hardness tests — Part 1: Test method*.
- ISO 6892:—³⁾, *Metallic materials — Tensile testing at ambient temperature*.
- ISO 6929:1987, *Steel products — Definitions and classification*.
- ISO 7452:1984, *Hot-rolled structural steel plates — Tolerances on dimensions and shape*.
- ISO 7788:1985, *Steel — Surface finish of hot-rolled plates and wide flats — Delivery conditions*.
- ISO 9443:1991, *Heat-treatable and alloy steels — Surface quality classes for hot-rolled round bars and wire rods — Technical delivery conditions*.
- ISO 10474:1991, *Steel and steel products — Inspection documents*.
- ISO 14284:1996, *Steel and iron — Sampling and preparation of samples for the determination of chemical composition*.

1) To be published. (Revision of ISO 4967:1979)

2) To be published. (Revision of ISO 6506:1981 and ISO 410:1982)

3) To be published. (Revision of ISO 6892:1984)

3 Definitions

For the purposes of this Technical Report the following definitions apply:

3.1 different forms of product: See ISO 6929 and the notes to 1.1.

3.2 ruling section: That section for which the specified mechanical properties shall apply.

NOTE — Independent of the actual shape and dimensions of the cross-section of the product the size of its ruling section is always given by a diameter. This corresponds to the diameter of an “equivalent round bar”. That is a round bar which, at the position of its cross-section specified for taking the test pieces for the mechanical tests, will, when being cooled from austenitizing temperature, show the same cooling rate as the actual ruling section of the product concerned at its position for taking the test pieces.

3.3 austempering: Austenitization of a steel with subsequent cooling to a temperature in the bainite region and holding at this temperature until a desired degree of transformation is obtained.

The subsequent cooling to room temperature can be carried out in any manner desired.

3.4 alloy steel: See clause 3 of ISO 4948-1:1982.

3.5 special steel: See 4.2.4 of ISO 4948-2:1981.

4 Ordering and designation

The designation of the product in an order shall cover the following.

- a) The designation of the product form (bloom, bar, rod, etc.) followed by
 - either the designation of the dimensional standard and the dimensions and tolerances selected from this (see 5.7), or
 - in the case of drop forgings, by the designation of the drawing or any other document covering the dimensions and tolerances required for the product.
- b) If a surface condition other than “hot worked” or a special surface quality is required
 - the surface condition (see table 2);
 - the surface quality (see 5.6).
- c) A description of the steel comprising
 - 1) a reference to this Technical Report;
 - 2) the designation of the steel type given in table 3;
 - 3) if a heat-treatment condition other than the untreated condition is required, the symbol for this other condition (see table 1, column 3);

NOTE — If the quenched and tempered condition is ordered, the mechanical properties should also be agreed when ordering (see 5.2.3).

- 4) if an inspection document is required, the type of inspection document (see ISO 10474);
- 5) if any supplementary requirement shall be complied with, the symbol and, where necessary, the details of this supplementary requirement (see annex A).