
**Nanotechnologies — Overview
of available frameworks for the
development of occupational
exposure limits and bands for nano-
objects and their aggregates and
agglomerates (NOAAs)**

*Nanotechnologies — Vue d'ensemble des cadres disponibles pour la
définition de limites et bandes d'exposition professionnelle applicables
aux nano-objets, à leurs agrégats et agglomérats (NOAA)*





COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	3
5 Description of available processes for setting OELs and OEBs	5
5.1 General considerations	5
5.2 Description of evidence-based process	6
5.3 Substance-specific OELs	8
5.4 Categorical OELs	8
5.5 Initial or default occupational exposure bands	9
6 Substance-specific OELs for nanomaterials	10
6.1 General overview	10
6.2 Available substance-specific OELs	10
6.2.1 Carbon nanotubes	10
6.2.2 Nanoscale TiO ₂	11
6.2.3 Fullerenes	12
6.3 Evaluation of OEL methods	12
6.3.1 Similarities and differences	12
6.3.2 Influence of methods on derived OEL values for nanomaterials	13
6.3.3 State of the science in support of risk assessment methods for nanomaterials OELs	14
7 Categorical OELs for nanomaterials	15
7.1 Summary of options proposed	15
7.1.1 United Kingdom	15
7.1.2 Germany	15
7.1.3 NIOSH	17
7.1.4 Japan's (AIST's) approaches	17
7.1.5 OECD	18
7.2 Evaluation of categorical OEL	19
7.2.1 Similarities and differences	19
7.2.2 State of the science supporting categorical OELs	20
8 OEBs and control banding for nanomaterials	21
8.1 Overview of current hazard and control banding schemes	21
8.1.1 Comparison of hazard bands and OEBs as applied to inhaled NOAAs	22
8.1.2 ISO hazard banding scheme for NOAAs	25
8.2 Case studies on banding NOAAs	26
8.3 Evaluation of the evidence for initial (default) OEBs for categories of NOAAs	28
8.3.1 Categorical analyses and read-across	28
8.3.2 Utility of <i>in vitro</i> data in OEL/OEB development for NOAAs	29
8.3.3 Options for deriving an OEL or OEB for NOAAs	30
9 Feasibility considerations in the OEL and OEB setting process	30
Annex A (informative) Standard processes for OEL setting	32
Bibliography	62

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

The committee responsible for this document is ISO/TC 229, *Nanotechnologies*.

Introduction

Nano-objects and their aggregates and agglomerates (NOAAs) represent a subset of particulate materials that can be dispersed in the air and can represent health risks via inhalation exposures. NOAAs include structures with one, two or three external dimensions in the nanoscale from approximately 1 nm to 100 nm, which may be spheres, fibres, tubes and others as primary structures. NOAAs can consist of individual primary structures in the nanoscale and aggregated or agglomerated structures, including those with sizes larger than 100 nm. An aggregate comprises strongly bonded or fused particles (structures). An agglomerate is a collection of weakly bound particles (structures)^{[1][2][3][4]}.

The purpose of this document is to describe a general framework for the development of occupational exposure limits (OELs) or occupational exposure bands (OEBs) for individual NOAAs or categories of NOAAs with different levels of available data. OELs and OEBs are important tools in the prevention of occupational illness. OELs have a long history in industrial hygiene and are based on observations of workers or studies of laboratory animals. OELs are established to minimize the likelihood of adverse effects from exposure to potentially hazardous substances in the workplace^{[5][6]}. An OEL is generally substance-specific (although sometimes generically expressed, such as dust). Sufficient data to develop an OEL may not be available, especially for substances such as NOAAs used in emerging technologies. To aid in hazard communication and exposure control decisions for substances without OELs, hazard banding has been used for many years^{[7][8][9]}. Substances are assigned to a hazard band based on limited toxicity data usually from animal studies. Hazard banding schemes typically consist of qualitative bands ranging from low to high severity of effects. Thus, a hazard band represents a range of potential toxicities for a particular substance or category of substances. Some hazard banding schemes include associated OEBs^[10]. The term OEB is a general term for exposure concentration ranges used in some hazard banding schemes that are related to the ranges of hazard potentials. In contrast to an OEB, an exposure band is a range of potential concentrations of a substance (or category of substances) to which workers may be exposed in a defined occupational scenario and which is based on factors such as the amount of NOAA processed or used, the nature of the process, and the form of the NOAA including dustiness^[3]. In control banding, the hazard band and the exposure band are combined to determine the control band for any particular occupational scenario (e.g. ISO/TS 12901-2).

OELs and OEBs are part of an overall occupational safety and health (OSH) program and are not intended to identify and address all safety and health risks associated with a specific process or task. OELs and OEBs are intended to provide occupational safety and health professionals with a health basis for assessing the effectiveness of exposure controls and other risk management practices. The exposure assessment of nanomaterials including carbon nanomaterials [such as fullerene, graphene, single-walled carbon nanotube (SWCNTs) and multi-walled carbon nanotube (MWCNTs)], metal oxides (TiO₂, SiO₂, zinc oxide, iron oxide), and metals (silver and gold nanoparticles) remains a challenge in the field of occupational hygiene, as there have been relatively few studies on the characterization of workplace exposures to NOAA. Sampling and analytical methods that have the capabilities to accurately measure nanomaterials are still under development. Most sampling devices that measure airborne particle count concentrations, such as condensation particle counters and optical particle counters, cannot differentiate ambient exposures to background nanoparticles from NOAA in the workplace environment. Airborne measurements of carbon nanotubes (CNTs) and carbon nanofibres (CNFs) using mobility particle sizers also sometimes could present a unique challenge due to the arcing caused by the charged airborne CNT and CNF agglomerates in the differential mobility analyser^[11]. Although several groups have attempted to measure and count CNT structures using transmission electron microscopy or other microscopic methods^{[12][13]}, there are still no standard methods for measuring and counting CNT structures. In addition, determining the mass concentration of CNTs and CNFs based on measuring the elemental carbon (EC) remains a challenge due to other sources of elemental carbon in the workplace, such as organic composite materials and air and diesel pollution that could interfere in the determination of CNT and CNF exposures.

Scientific and technical methodologies used to set exposure limits may differ from one entity to another, which can lead to disparities in worker protection from country to country^[14]. Therefore, harmonizing the scientific methodologies used in developing OELs, including using the best available evidence for interspecies extrapolation and specifying the type of data and uncertainties involved in the OEL determination is necessary for a robust health and safety evaluation framework for NOAAs.

This document provides a collaborative, science-based platform to describe and evaluate the state-of-the-art in such data and methods.

Current risk assessment methods are likely to apply to NOAAs^[15], although the limited health hazard data for many NOAAs and the considerable variety in the types of manufactured NOAAs present a challenge to the efficient development of OELs for individual NOAAs. To date, few OELs and OEBs have been developed for specific NOAAs and none have been formally regulated by a government agency. Standard OEL and OEB methodologies for NOAAs are needed to evaluate the evidence on the hazard potential of NOAAs in the workplace to provide a health basis for risk management decisions, including selection and evaluation of engineering control options. One of the goals of this document is to identify both the similarities and differences in the methods used to develop OELs. This evaluation may lead to improvements in methods for setting exposure limits or bands.

This document presents an overview of the state-of-the-art in the development of OELs and OEBs for NOAAs. Current approaches for assigning default hazard bands in the absence of NOAA-specific toxicity data are described. These approaches build on current hazard and control banding strategies, such as those developed in ISO/TS 12901-2. The current state of the methods and data to develop OELs and OEBs for NOAAs is described in this document, along with an evaluation of those methods used in developing the current OELs for NOAAs. Categorical approaches to derive OEBs for NOAAs with limited data are also discussed, such as those based on biological mode-of-action (MOA) and physico-chemical (PC) properties. The basis for the framework described in this document is the U.S. NIOSH Current Intelligence Bulletin *Approaches to Developing Occupational Exposure Limits or Bands for Engineered Nanomaterials*^[16]. This document also takes into consideration other state-of-the-science reports, including outputs of the workshop “Strategies for Setting Occupational Exposure Limits for Engineered Nanomaterials,” which was held on September 10-11, 2012 in Washington, DC, USA^[6] and the OECD Working Party on Manufactured Nanomaterials Expert Meeting on Categorization of Manufactured Nanomaterials, September 17-19, 2014^[17].

The primary target audience of this document is occupational safety and health professionals in government, industry, and academia, who have the expertise to develop OELs or OEBs based on the guidance in this document. In addition, the evidence-based approach described in this document may be useful in the evaluation and/or verification of current hazard and control banding schemes and for identifying the key data gaps. Control banding requires information on both the applicable hazard category and exposure category. Appropriately verified control banding tools would be broadly useful, as these tools require less specialized expertise and resources (than for a comprehensive risk assessment) and are accessible to a wider group of individuals and small businesses. Therefore, this document can be considered complementary to ISO/TS 12901-2 on control banding for nanomaterials as it describes the state-of-the-art in the process of assigning nanomaterials to hazard bands/OEBs when the scientific evidence is not sufficient to develop an individual OEL.

Some of the cited methods lead to results that are not necessarily consistent and this may be due to method selection biases of the authors. In these cases, diverse results will also make it difficult to use information to confidently establish exposure and band levels. It is beyond the scope of this document to attempt to identify the methods which lead to both correct and consistent results. In the event that methods lead to diverse results, it is hoped that this report will lead to additional methods development that will lead to improvements and that these improvements can be relied on for setting exposure and banding levels.

The objectives of this document include

- a) describing an evidence-based state-of-the-art framework to develop OELs or OEBs for manufactured NOAAs, and
- b) examining the currently available data and other approaches and methods used (e.g. benchmark substances and benchmark exposure levels) in the occupational risk management decision-making for NOAAs.

It is anticipated that this document will contribute to the development of standard hazard and risk assessment methods and facilitate the systematic evaluation of the potential health risk of occupational exposure to NOAAs.

Nanotechnologies — Overview of available frameworks for the development of occupational exposure limits and bands for nano-objects and their aggregates and agglomerates (NOAAs)

1 Scope

This document provides an overview of available methods and procedures for the development of occupational exposure limits (OELs) and occupational exposure bands (OEBs) for manufactured nano-objects and their aggregates and agglomerates (NOAAs) for use in occupational health risk management decision-making.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/TS 80004-2 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

agglomerate

collection of weakly or medium strongly bound particles where the resulting external surface area is similar to the sum of the surface areas of the individual components

Note 1 to entry: The forces holding agglomerates together are weak forces, for example, van der Waals forces or simple physical entanglement.

Note 2 to entry: Agglomerates are also termed secondary particles and the original source particles are termed primary particles.

[SOURCE: ISO 26824:2013, 1.2]

3.2

aggregate

particle comprising strongly bonded or fused particles where the resulting external surface area is significantly smaller than the sum of surface areas of the individual components

Note 1 to entry: The forces holding an aggregate together are strong forces, for example, covalent or ionic bonds, or those resulting from sintering or complex physical entanglement, or otherwise combined former primary particles.

Note 2 to entry: Aggregates are also termed secondary particles and the original source particles are termed primary particles.

[SOURCE: ISO/TS 80004-2:2015, 3.5]

3.3

bulk material

material of the same chemical composition as the NOAA, at a scale greater than the nanoscale

3.4

exposure

contact with a chemical, physical or biological agent by swallowing, breathing, or touching the skin or eyes

Note 1 to entry: Exposure can be short-term (acute exposure), of intermediate duration, or long-term (chronic).

3.5

health hazard

potential source of harm to health

[SOURCE: ISO 10993-17:2002, 3.7]

3.6

health risk

combination of the likelihood of occurrence of harm to health and the severity of that harm

[SOURCE: ISO 10993-17:2002, 3.8]

3.7

nanofibre

nano-object with two external dimensions in the nanoscale and the third dimension significantly larger

Note 1 to entry: The largest external dimension is not necessarily in the nanoscale.

Note 2 to entry: The terms nanofibril and nanofilament can also be used.

Note 3 to entry: See [3.9](#) Note 1 to entry.

[SOURCE: ISO/TS 80004-2:2015, 4.5]

3.8

nano-object

discrete piece of material with one, two or three external dimensions in the nanoscale

Note 1 to entry: The second and third external dimensions are orthogonal to the first dimension and to each other.

[SOURCE: ISO/TS 80004-1:2010, 2.2]

3.9

nanoparticle

nano-object with all external dimensions in the nanoscale where the lengths of the longest and the shortest axes of the nano-object do not differ significantly

Note 1 to entry: If the dimensions differ significantly (typically by more than 3 times), terms such as nanofibre or nanoplate may be preferred to the term nanoparticle.

[SOURCE: ISO/TS 80004-2:2015, 4.4]

3.10

nanoscale

length range approximately from 1 nm to 100 nm

Note 1 to entry: Properties that are not extrapolations from a larger size are predominantly exhibited in this length range.

[SOURCE: ISO/TS 80004-1:2010, 2.1]

3.11**particle**

minute piece of matter with defined physical boundaries

Note 1 to entry: A physical boundary can also be described as an interface.

Note 2 to entry: A particle can move as a unit.

Note 3 to entry: This general particle definition applies to nano-objects.

[SOURCE: ISO 26824:2013, 1.1]

3.12**solubility**

maximum mass of a nanomaterial that is soluble in a given volume of a particular solvent under specified conditions

Note 1 to entry: Solubility is expressed in grams per litre of solvent.

[SOURCE: ISO/TR 13014:2012, 2.27]

3.13**occupational exposure limit**

maximum concentration of airborne contaminants deemed to be acceptable, as defined by the authority having jurisdiction

[SOURCE: ISO 16972:2010, 3.133]

3.14**occupational exposure band**

quantitative representation of hazard band which describes hazard potential of a particular material or class of materials in workplace air

3.15**breathing zone**

space around the face of a worker from where he or she takes his or her breath

[SOURCE: ISO 24095:2009, 3.1.2.1]

4 Symbols and abbreviated terms

ACGIH	American Conference of Governmental Industrial Hygienists
AGS	Ausschuss für Gefahrstoffe (German Committee on Hazardous Substances)
AGW	Arbeitsplatzgrenzwert (occupational exposure limit)
AIST	Japanese National Institute of Advanced Industrial Science and Technology
BALF	bronchoalveolar lavage fluid
BAuA	Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (German Federal Institute for Occupational Safety and Health)
BEI	biological exposure index
BEL	benchmark exposure level
BMD	benchmark dose
BMDL	benchmark dose estimate, 95 % lower confidence limit

BSI	British Standards Institution
CMAR	carcinogenic, mutagenic, asthmagenic, or reproductive toxicant
CNF	carbon nanofibre
CNT	carbon nanotube
DFG	Deutsche Forschungsgemeinschaft (German Research Foundation)
DMEL	derived minimum exposure level
DNEL	derived no-effect level
EPA	United States Environmental Protection Agency
EU	European Union
EU-OSHA	European Agency for Safety and Health at Work
GBP	granular biopersistent particle
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
IARC	International Agency for Research on Cancer
IFA	Institut für Arbeitsschutz (German Institute for Occupational Safety and Health)
ILV	indicative limit value
JSOH	Japan Society for Occupational Health
LC50	concentration associated with 50 % lethality
LOAEL	lowest observed adverse effect level
MAK	Maximale Arbeitsplatzkonzentration (maximum workplace concentration)
MOA	biological mode of action
MOEL	Korean Ministry of Employment and Labour
MSHA	United States Mine Safety and Health Administration
MWCNT	multi-walled carbon nanotube
NIOSH	United States National Institute for Occupational Safety and Health
NOAAs	nano-objects, and their aggregates and agglomerates including those larger than 100 nm
NOAEL	no observed adverse effect level
NRV	nano-reference value
OECD	Organization for Economic Cooperation and Development
OEB	occupational exposure band
OEL	occupational exposure limit
OEL (PL)	period-limited occupational exposure limit

OELV	occupational exposure limit value
OSH	occupational safety and health
OSHA	United States Occupational Safety and Health Administration
PC	physico-chemical
PCM	phase contrast microscopy
PEL	permissible exposure limit
QRA	quantitative risk assessment
REACH	Regulation, Evaluation, Authorization and Restriction of Chemicals
REL	recommended exposure limit
SCENIHR	Scientific Committee on Emerging and Newly Identified Health Risks
SCOEL	Scientific Committee on Occupational Exposure Limits
STEL	short-term exposure limit
STOT-SE	Specific target organ toxicity — single exposure
STOT-RE	Specific target organ toxicity — repeated exposure
SWCNT	single-walled carbon nanotube
TLV	threshold limit value
TSCA	Toxic Substances Control Act
TWA	time-weighted average
UF	ultrafine
VLEP	Valeur Limite d'Exposition Professionnelle (occupational exposure limit)
WHO	World Health Organization
WHS	Work Health and Safety

5 Description of available processes for setting OELs and OEBs

5.1 General considerations

Exposure to substances or mixtures in the workplace can occur through inhalation, absorption through the skin or ingestion. Most exposure occurs through the inhalation of vapours, dusts, fumes or gases. For some chemicals, absorption through the skin may also be a significant source of exposure.

The response of the body to exposure from substances and mixtures depends on the nature of the substance, the health effects it can cause and the amount of the substance or mixture absorbed by the body. Individuals also have differing abilities to metabolize chemicals which can cause considerable variation in the toxic effects between people. The extent to which a person is exposed mainly depends on the concentration of the substance or mixture in the air and the amount of time exposed and, of course, on the effectiveness of controls. Substances and mixtures may cause immediate acute health effects or it may be decades before effects on the body become evident.

Occupational exposure limits are intended to prevent adverse health effects in “nearly all workers”^[18] even with repeated or daily exposures over a working lifetime. Some OELs are based on health effects data only (e.g. ACGIH TLV), and other OELs also include consideration of the technological feasibility (e.g. NIOSH RELs) or economic feasibility (e.g. OSHA PEL) of measuring and controlling exposures.

For a few substances, usually the more potent probable and established human carcinogens, it is not currently possible to assign an appropriate exposure limit. For these substances, exposure should be controlled to the lowest practicable level. Biological monitoring may provide a more reliable indication of workplace exposure for these substances.

The evaluation of hazards posed by atmospheric contaminants in the working environment is often a complex task, taking into account the potentially large variability of exposure at the workplace requiring sound occupational hygiene exposure assessment strategies. For this reason, it is essential that those persons responsible for such assessments are knowledgeable and experienced professionals, who are fully aware of all issues canvassed in this document and have appropriate qualifications and experience in occupational hygiene.

NOTE A knowledgeable and experienced professional is an individual who will properly perform a specific job. This person utilizes a combination of knowledge, skills and behaviour to improve performance. More generally, competence is the state or quality of being adequately or well qualified, having the ability to perform a specific role^[3].

The relationship between various exposure limits should not be used as a general measure of their relative toxicity. This is because, among other things, the values for different substances are often established with regard to different biological effects, such as irritation or systemic toxicity. Similarly, the exposure limits should not be used as a basis for the evaluation of community air quality, or for long term, non-occupational exposures.

Most substances used in industry have not been assigned exposure limits. This does not imply that these substances are safe or non-hazardous. In many cases there is insufficient information on the health effects of these unlisted substances to allow national regulatory bodies to assign an exposure limit, even on a tentative basis. In other instances, the use of the substance does not lead to significant airborne levels of contaminant, or its use is so restricted that an exposure limit is not warranted.

It is a good general policy to keep the exposure to any substance as low as is practicable, irrespective of whether present information indicates it is hazardous or not. Some substances previously thought to be comparatively safe have subsequently been found to pose serious long term health risks.

There are three types of exposure limits:

- time-weighted average (TWA) limit;
- short term exposure limit (STEL);
- peak or ceiling limit.

These limits and other technical aspects of setting OELs are further described in [A.1.2](#).

5.2 Description of evidence-based process

The methods for developing OELs depend on the available data. Schulte, et al.^[5] describe three general scenarios for varying amounts of toxicological data. This framework was refined to describe linkages between the evidence basis for these general categories through benchmark substances. Benchmark substances are well-characterized materials (e.g. airborne particles or fibres) with sufficient dose-response data from animal and/or human studies to develop quantitative risk estimates and health-based OELs ([Figure 1](#))^{[19][20]}. Benchmark materials also provide a reference (e.g. as a positive or negative control) in comparative toxicity assays with new NOAAs that have limited toxicological data but similar physico-chemical properties and inferred biological mode-of-action (MOA)^{[19][20][21]}. The focus of this document is on occupational airborne exposures to nanomaterials since inhalation is the major route of exposure to potentially hazardous substances, including NOAAs, in the workplace.

As shown in [Figure 1](#), in the first case, if dose-response data are sufficient, an OEL for an individual NOAA can be developed using quantitative risk assessment (QRA). The definition of sufficient will ultimately be based on a judgment about the available data, and may include weight of evidence evaluations, including the availability of adequate data for benchmark dose modelling[22] or no observed adverse effect levels (NOAELs) or lowest observed adverse effect levels (LOAEL) from well-conducted studies. Second, if data are insufficient for QRA for a specific substance, but adequate information is available on a similar substance in the same mode-of-action category, then a categorical OEL may be assigned by qualitative or quantitative methods including read-across and structure-bioactivity modelling, with comparisons between NOAAs and benchmark substances. Third, if data are insufficient to develop a substance-specific or categorical OEL, then initial (default) hazard and control bands may be derived by comparing NOAA properties to that of similar materials in broad categories. The objective of this evidence-based approach is to facilitate decision-making about exposure control strategies for NOAAs in the workplace based on best available evidence. The framework allows for iteration and revision of an OEB or OEL as new data become available based on standard criteria for data and methods. At this time, more examples of OELs developed for NOAAs are available than of categorical OELs or OEBs for NOAAs.

The data available for developing OELs or OEBs for NOAAs may include

- a) data from *in vivo* and *in vitro* testing of specific NOAAs (e.g. from the OECD testing program, manufacturers of NOAAs, and non-regulatory government agencies such as the NIOSH and the NTP in the US), and
- b) existing toxicology or epidemiology studies of lung effects from inhaled particles and fibres for comparative toxicity analyses.

General chemical hazard databases (e.g. as used in GHS[23] hazard classification) are also available for some of the parent or bulk materials with similar chemical composition to the NOAA for use in hazard band/OEB allocation and control banding (e.g. see ISO/TS 12901-2). [Table 1](#) summarizes the type of data and methods needed to develop OELs or OEBs.




Figure 1 — Evidence-based strategy to develop exposure control limits and bands for NOAAs, based on level of evidence

Table 1 — Data and methods needed to develop exposure limits or bands

Guidance value	Level of evidence	Data, analysis tools and methods
Substance-specific OEL	Sufficient	Substance-specific dose-response data for quantitative risk assessment; availability of substance-specific sampling and analytical method
Categorical OEL	Limited (focused)	Comparative toxicity, clustering and categorization to estimate hazard or risk based on physico-chemical properties and biological mode-of-action data
OEB	Minimal or inadequate	Analogy; default hazard categories and exposure control options are applied.

5.3 Substance-specific OELs

The substance-specific OELs typically do not take separate account of the nanoparticle size, although some of these OELs do specify the particle size sampling criteria associated with regional respiratory tract deposition. These sampling criteria include inhalable (total), thoracic (airways), and respirable (pulmonary) size fractions. Nanoparticles are capable of depositing anywhere in the respiratory tract region, including the pulmonary region where gas exchange takes place. Some of the individual OELs are specific to the dust and/or fume forms, and fumes by nature consist of nanostructured particles. The OELs for fumes may be lower mass concentrations than the OELs for dust of the same chemical substance (e.g. the NIOSH REL and OSHA PEL for copper is 1 mg/m³ for the dust and 0,1 mg/m³ for the fume)[24]. In other cases the OEL applies to both the dust and fume (e.g. iron oxide, NIOSH REL is 5 mg/m³ and OSHA PEL is 10 mg/m³; cobalt metal dust and fume, NIOSH REL is 0,05 mg/m³ and the OSHA PEL is 0,1 mg/m³). It is relevant to note that those OELs vary at least as much by chemical composition as by descriptors of particle size (dust, solid particles generated by any mechanical processing of materials such as crushing, grinding, and handling or fume, airborne dispersion consisting of small solid particles created by condensation from the gaseous state).

[Clause 6](#) and [Table 2](#) provide a description and list of the OELs that have been developed for specific nanomaterials by non-regulatory government agencies, companies, and nongovernmental organizations. To date, no regulatory standards have been circulated for NOAAs.

5.4 Categorical OELs

Historically, many airborne particulate materials were regarded as a “nuisance” or as “low toxicity” dusts and categorical OELs, such as a generic inhalable OEL of 10 mg/m³ and a respirable OEL of 4 mg/m³ were set for many low-toxicity poorly-soluble dusts including aluminium oxides, graphite, titanium dioxide and others[25]. In Germany, the DFG MAK commission recently reduced the OEL for biopersistent granular particles from 3 mg/m³ to 0,3 mg/m³ (respirable fraction), reflecting concerns about a possible carcinogenic potential for this category of substances[26]. All these values, however, were not intended for particulate materials with specific known inhalation or systemic toxicity (e.g. asbestos and lead, respectively) for which substance-specific OELs were also determined.

Advantages of categorical approaches include:

- more efficient use of data;
- reduced costs;
- reduced animal use;
- increased sample size;
- greater robustness of results;
- increased biological plausibility for other materials in the same mode of action category[27].

Categorical approaches are compatible with hazard and risk assessment frameworks proposed for NOAAs (e.g. References [5], [20] and [28]) and with a standard risk assessment paradigm[29].

to derive OELs for NOAAs using categorical approaches may include quantitative or qualitative read-across[27]; comparative potency analyses of NOAAs to benchmark (reference) particles in the same mode-of-action (MOA) category[19][20], e.g. using a “parallelogram” approach[19][30][31][32]; and assigning an untested substance to the low end of the distribution of OELs for materials in the same hazard class[33].

Other risk analysis and categorization approaches include both occupational and environmental components, such as screening tools of potential risks over the NOAA lifecycle[34][35]. The multi-criteria decision analysis (MCDA) approach includes evaluation of the risks and benefits with weightings obtained through expert elicitation[28]. This process has been used to assign NOAAs to qualitative risk categories (low, medium, high)[36].

[Clause 7](#) summarizes the categorical OELs that have been proposed by governmental and nongovernmental organizations. These categories are based on broad groups of physico-chemical properties that influence toxicity (soluble, biopersistent low toxicity, biopersistent high toxicity, and fibres). The BSI and IFA categories are provisional exposure limits based on existing OELs for particles and fibres in these categories, which includes in some cases a precautionary downward adjustment for the nanoscale form. The extent to which chemical substance-specific data are available would allow refinement of the categorical OELs to an individual OEL that may be more applicable to an individual substance.

5.5 Initial or default occupational exposure bands

When data are not sufficient to develop an individual OEL, hazard banding approaches are often used to facilitate decision-making among engineering control options[5]. Control banding typically utilizes a matrix approach to categorize substances according to their hazard and exposure potential[37][38][39][40][41][42] to determine an appropriate control technology (such as general ventilation, local exhaust, or containment)[39][41][42][43]. The combination of the selected hazard and exposure bands determines the control band and associated engineering control options. However, the utility of such an approach is frequently limited by the availability of adequate toxicological data for use in hazard assessment. The absence of such data makes workplace risk characterization and the subsequent selection of appropriate control measures problematic. Another suggested approach is the utilization of initial default hazard categories or OEBs for NOAAs based on the physico-chemical properties associated with point-of-entry or systemic toxicity, including particle surface chemistry and area, shape, diameter, and solubility, as well as any evidence on the mutagenicity, carcinogenicity, or reproductive toxicity of the nanomaterial or parent material[20][42][44][45][46].

ISO/TS 12901-2 also incorporates available toxicological information and physico-chemical properties to designate nanomaterials into hazard bands. In this method, nanomaterials are grouped into one of five inhalation hazard groups (A to E) according to increasing severity described in GHS hazard classification applicable to chemicals[23].

- Category A (no significant risk to health) corresponds to an OEB of 1 mg/m³ to 10 mg/m³ (as 8 h time-weighted average)
- Category B (slight hazard; slightly toxic) — 0,1 mg/m³ to 1 mg/m³
- Category C (moderate hazard) — 0,01 mg/m³ to 0,1 mg/m³
- Category D (serious hazard) — <0,01 mg/m³
- Category E (severe hazard) has no concentration ranges provided in ISO/TS 12901-2 and other hazard allocation schemes ([8.1](#))

The decision logic for assigning NOAAs into these hazard bands includes considerations of solubility, fibrous nature and hazardous properties of bulk and analogous materials[3].

Hazard and control banding approaches were developed to facilitate risk management decision-making in small business. A key research need for hazard and control banding strategies in general, and those specific to NOAAs, is evaluation and validation of the utility of these strategies to provide adequate

health protection to workers in a variety of jobs and workplaces. A study evaluating the general hazard and control banding strategies found little or no margin of safety between worker exposures and the effect levels in animal studies[47].

6 Substance-specific OELs for nanomaterials

6.1 General overview

Currently, there are no specific regulatory OELs established for manufactured NOAAs. Interim or draft OELs have been proposed for certain NOAAs, including “benchmark exposure levels” based on analogy with OELs for other particles or fibres[44]. Since no epidemiology data are available on adverse health effects of exposures to most manufactured NOAAs, dose-response data from animal studies are typically used to estimate risk in humans. Experimental studies in animals and *in vitro* studies are also used to evaluate hazard and understand mechanisms of toxicity.

More recently, non-regulatory OELs for some specific NOAAs have been developed (see Table 2). These include OELs proposed by governmental agencies, researchers, and producers of specific nanomaterials.

Table 2 — Examples of OELs proposed for NOAAs

Nanomaterial	OEL ($\mu\text{g}/\text{m}^3$, unless stated otherwise)	Reference
Titanium dioxide (ultrafine)	610 ^a	Gamo 2011[48]; Nakanishi 2011[49]
	300	NIOSH 2011[50]; JSOH 2013[51]
	17	Aschberger, et al. 2011[52]
Fullerene (C ₆₀)	390 ^a	Shinohara 2011[53]; Nakanishi 2011[49]
	7,4	Aschberger, et al. 2011[52]
MWCNT (Baytubes®)	50	Pauluhn 2010[54]
Carbon nanotubes	30 ^a	Nakanishi 2011[55]
MWCNT	1 to 2	Aschberger, et al. 2010, 2011[52][56], Nanocyl 2009[57]
Carbon nanotubes and nano-fibres		NIOSH 2013[58]
Carbon nanotubes and nano-fibres	0,01 f/cm ³	SUVA 2015[59]
Silver (nanoparticles)	0,33 to 0,67	Aschberger, et al. 2011[52]
^a Period-limited (15 years) OEL.		

Differences among OELs for the same or similar NOAAs in Table 2 are due to differences in the data and/or risk assessment methods used to derive the OEL. Some differences could be related to differences in chemical compositions and physical dimensions of similar NOAAs. The proposed OELs vary by up to an order of magnitude or more for the same or similar type of NOAAs, indicating that differences in the data and/or methods used to derive the OEL can influence the basis for risk management decisions such as selection of engineering controls. This illustrates the critical need to develop standardized risk assessment procedures that are based on the best available scientific evidence and methodologies.

6.2 Available substance-specific OELs

6.2.1 Carbon nanotubes

Carbon nanotubes (CNTs) are an example of manufactured nanomaterials that have been the subject of several recent risk assessments producing interim and voluntary occupational exposure limits. CNTs can have wide variations in structure, size, shape and chemistry (including impurities) affecting their hazard properties, exposure potential and ultimately risk. CNT and CNF are in growing use in a lot

of industry sectors, including construction as concrete reinforcement, for medical treatments, as fuel additives, and so on.

To date, there was limited information regarding adverse health effects in workers using or producing CNT or CNF. Few epidemiological studies have shown that some detectable biomarkers were related to exposure to CNT or CNF or other nanoparticles[60][61][62][63]. However, there are studies of animals exposed to CNT and CNF that are informative in predicting potential human health effects consistent with ways in which scientists traditionally have used such data in recommending risk management strategies.

In 2013, NIOSH recommended a REL of 1 µg/m³ (8 h TWA) for CNT and CNF. The NIOSH REL for CNT and CNF is based on preventing the development of earlier adverse lung responses of pulmonary inflammation and fibrosis over a 45-year working lifetime. The REL for CNT and CNF is based on animal data, although since no chronic studies were available, the dose-response data from short-term and subchronic studies in rats and mice were extrapolated to humans. Since the REL for CNT was set at the limit of quantification of the sampling and analytical method for measuring airborne elemental carbon in the workplace, the 45-year working lifetime excess risk estimates for developing early-stage pulmonary inflammation or fibrosis exceed 10 % for some end points and assumptions[58]. Methodology used to derive this exposure limit is described in [Clause 5](#) and further details can be found in [A.11](#).

In 2011, the Japanese National Institute of Advanced Industrial Science and Technology (AIST) published a series of reports containing risk assessments of several nanomaterials: carbon nanotubes[55], titanium dioxide[48] and fullerenes[53]. The reports put forward period-limited (PL) OELs for SWCNT set at 0,03 mg/m³ and for MWCNT set at 0,08 mg/m³. These OELs (PL) were derived using inflammation as an end point observed in sub-acute inhalation exposure tests. The working exposure period employed in OEL calculations was set at 15 years. Further details about derivation of these OELs can be found in [A.7](#).

6.2.2 Nanoscale TiO₂

Titanium dioxide, TiO₂, is a noncombustible, white, crystalline, solid, odourless powder. It exists in several crystal forms of which anatase and rutile are commercially the most relevant. TiO₂ is used extensively in many commercial products, including paints and varnishes, cosmetics, plastics, paper, and food as an anticaking or whitening agent.

Titanium dioxide is produced and used in the workplace in varying particle size fractions including fine (which is defined as all particle sizes collected by respirable particle sampling) and ultrafine or nanoparticles (defined as the fraction of respirable particles with a primary particle diameter of <0,1 µm [<100 nm]).

In 2011, NIOSH recommended separate RELs for ultrafine (nanoscale) and fine (microscale) titanium dioxide (TiO₂), i.e. 0,3 mg/m³ for ultrafine TiO₂ and a REL of 2,4 mg/m³ for fine-sized TiO₂ (8 h TWA respirable concentrations)[50]. These RELs were set at the 45-year working lifetime exposure concentration associated with a 1/1 000 excess risk of lung cancer (95 % lower confidence limit) estimated from nonlinear models of dose-response data from animal chronic inhalation bioassays of fine or ultrafine TiO₂. The rat-based risk estimates were extrapolated to humans by estimating an equivalent retained lung burden after a 45-year working lifetime, with adjustment for the differences in alveolar surface area in rats and humans and the use of human lung dosimetry modelling to account for interspecies differences in the long term clearance and retention of respirable particles. For both lung cancer and inflammation responses, ultrafine (nanoscale) TiO₂ was more potent on a mass basis than fine (microscale) TiO₂, which is the reason for the lower mass-based REL for ultrafine TiO₂[50]. Methodology used to derive this exposure limit is described in [Clause 5](#) and further details can be found in [A.11](#).

In 2013, the Japan Society for Occupational Health (JSOH) newly set the provisional OEL-M, 0,3 mg/m³, for nanoparticles of titanium dioxide[51]. In addition AIST conducted subchronic inhalation studies using rats and derived OELs based on pulmonary inflammation end point. The OEL (PL) was determined to be 0,6 mg/m³ (respirable dust, 8 h TWA, 15-year working period)[48]. Further details about derivation of this OEL can be found in [A.7](#).

6.2.3 Fullerenes

Fullerenes are a form of spherical carbon structures. The AIST report[53] focuses on one fullerene configuration composed of 60 carbon atoms, C₆₀. Diameter of C₆₀ is approximately 1 nm. C₆₀ is a solid under normal temperature and pressure, and is commonly sold as a black powder. C₆₀ is insoluble in water and other polar solvents, but can be dispersed in the form of agglomerates between 25 nm and 500 nm. It is soluble in organic aromatic solvents.

In 2011, fullerenes were mostly used as additives for resins used in glassware, bowling balls, a metal additive, a lubricant additive, and in cosmetics. Future applications may include resin additives for solar cell electrodes and fuel cell electrodes as well as pharmaceutical-related raw material such as for drug delivery. Fullerenes are also generated as bi-products in any combustion process of carbon-containing material.

Similar to CNTs and TiO₂, the AIST study used the inflammation end point and subchronic inhalation animal data. After taking into account uncertainty factors, the occupational exposure limit (period-limited) was set at 0,39 mg/m³. Further details about derivation of this OEL can be found in [A.7](#).

6.3 Evaluation of OEL methods

6.3.1 Similarities and differences

Presently most OELs for manufactured NOAAs are developed using standard risk assessment methods involving five steps:

- a) evaluating the available data;
- b) selecting the adverse response (non-reversible, clinically significant);
- c) determining the critical dose (e.g. NOAEL or BMDL);
- d) calculating the human equivalent dose (accounting for species-specific differences that affect the target tissue dose, e.g. ventilation rates and particle deposition and clearance kinetics);
- e) determining the working lifetime exposure concentration that would result in that dose (including consideration of deposition, uptake, and clearance)[5][64].

Use of uncertainty factors is a simple, default approach often used to derive an OEL from a NOAEL in the absence of sufficient resources (information or expertise) to perform quantitative risk assessment with dose-response modelling and dosimetry-based extrapolation methods. Since human health effects data for manufactured nanomaterials are not available for risk assessments at this time, dose-response data in animals are used in the risk assessment analyses reviewed in this report.

Without a globally harmonized approach to OEL setting process, OELs established by different groups for the same manufactured NOAAs using traditional QRA methods even for the same toxicity data can vary by orders of magnitude. For example, recommended OELs for nano-TiO₂ include 0,017 mg/m³[65], 0,3 mg/m³[50] and 0,6 mg/m³[48][49]. Such differences arise from differences in the interpretation of the supporting toxicity data, selection of health end points, and use of uncertainty and modifying factors[6]. [Table 3](#) summarizes these differences for recommended OELs for TiO₂.

Table 3 — Parameters and uncertainty factors used in developing OELs for nanoscale TiO₂

Parameter/ uncertainty factor	Analysis and reference		
	Stone, et al. 2010 ^[65] Christensen, et al., 2011 ^[66]	Gamo 2011 ^[48] Nakanishi 2011 ^[49]	NIOSH 2011 ^[50]
Health end point	Pulmonary inflammation	Pulmonary inflammation	Lung tumours
Level of risk	NOAEL	NOAEL	1/1 000 excess risk
Study data reference	Bermudez, et al. 2004 ^[67]	Bermudez, et al. 2004 ^[67]	Lee, et al. 1985; ^[68] Muhle, et al. 1991; ^[69] Heinrich, et al. 1995 ^[70]
Rat effect level	0,5 mg/m ³	2 mg/m ³	0,044 m ² /g of lung ^d
Human (occupational) adjustment of rat effect level	0,5 ^a	0,91 ^b	Internal dose estimation
Human-equivalent effect level	0,25	1,82 mg/m ³	17 m ² (per lung) (0,35 g per lung) ^e
Interspecies extrapolation	1,5 (UF)	3 (UF) ^c	Pulmonary surface area adjustment: 102 m ² human; 0,4 m ² rat (no UF)
Interspecies variation	5 (UF)	1 (UF)	95 % lower confidence limit estimate (no UF)
Exposure duration (subchronic to chronic)	2 (UF)	1 (UF)	45-year working lifetime (no UF) ^f
OEL (8 h TWA)	0,017 mg/m ³	0,61 mg/m ³	0,3 mg/m ³
^a Adjusts for daily exposure duration (rat/human) and for human ventilation (in 8 h) at rest vs. light activity (work): (6 h/8 h) × (6,7 m³/10 m³)^[65], based on ECHA 2008^[71]. ^b Adjusts for the pulmonary deposited dose in rats and humans, based on the respiratory minute volume (RMV), time (T), deposition fraction (DF), per unit body weight (BW), in each species^[49]. ^c Reference ^[49]. ^d Table 4-5 of NIOSH 2011;^[50] benchmark dose estimate, 95 % lower confidence limit (BMDL) associated with 1/1 000 excess risk of lung cancer in rats, based on the dose-response model average (MA). NOTE The value of 0,029 in Table 4-5 of NIOSH 2011^[50] is not the correct value that was used to derive the human BMDL estimate in Table 4-6. The correct value is 0,044, which is the accelerated bias-corrected bootstrap estimate. ^e Table 4-6 of NIOSH 2011;^[50] the human-equivalent lung dose to the rat BMDL MA estimate (see footnote ^d) is calculated as follows: 0,044 m² TiO₂/g rat lung × 1,5 g [reference rat lung weight] × (102 m²/0,4 m²) [human/rat pulmonary surface area] = 17 m² TiO₂/lung [humans] (as described in 4.2.3 and 4.3.2.3); to obtain the human lung mass dose of ultrafine TiO₂ of 0,35 g, the TiO₂ surface area dose (m²) is divided by the specific surface area of ultrafine TiO₂ (48 m²/g). ^f Table 4-6 of NIOSH 2011;^[50] the recommended exposure concentration (REL) of 0,29 (rounded to 0,3) mg/m³ for ultrafine TiO₂ is the 45-year working lifetime mean airborne exposure (8 h TWA concentration) associated with the human-equivalent retained lung dose at a 1/1 000 excess risk of lung cancer (95 % LCL estimate). The mean airborne exposure was estimated using the Multiple-Path Particle Deposition (MPPD) human model;^[72] details in Reference ^[50].			

6.3.2 Influence of methods on derived OEL values for nanomaterials

As shown in Table 3, OEL derivation methods for TiO₂ include a simple uncertainty factor approach;^[65] ^[66] a combined dosimetry-based and uncertainty factor approach^[48]^[49]; and quantitative risk assessment and dosimetry modelling methods^[50]. In the first two analyses, a NOAEL for pulmonary inflammation is selected as the critical health end point from a subchronic (13 weeks) inhalation study in rats; however, the interpretation of which dose is the NOAEL differed in the analyses in References ^[65] and ^[66] and References ^[48] and ^[49]. The third analysis^[50] used lung tumours as the

critical health end point. The first two analyses estimated a human-equivalent NOAEL, while the third analysis derived a risk-based exposure concentration (associated with 1/1 000 excess risk).

The first analysis simply adjusts the rat NOAEL by the difference in the daily exposure duration in rats vs. workers (6 h vs. 8 h) and the difference in a human resting vs. light work ventilation rate (6,7 m³/8 h-d vs. 10 m³/8 h-d)[65][66]. No dosimetry adjustments are made, and uncertainty factors are used for interspecies, intra-species, and exposure duration[65][66]. The second analysis includes dosimetry adjustments to account for differences in rat and human ventilation rates and particle size specific pulmonary deposition fraction of the inhaled dose; this dose is normalized to body weight[48][49]. No dosimetry adjustments are made to account for differences in the rat and human clearance and retention kinetics of the inhaled dose; and an uncertainty factor is used for interspecies (toxicokinetic) extrapolation[48][49].

The third analysis[50] uses quantitative modelling methods to describe the dose-response relationship in rats and to estimate the human-equivalent working lifetime exposure concentration. The dose-response modelling approach used to derive the REL was a three-model average of nonlinear models including multistage, Weibull, and log-probit (fit to the rat nonlinear dose-response data for lung tumours). The variability in the rat dose-response data was taken into account in the confidence interval estimates of the critical dose. The dose metric used in these analyses was the retained particle surface area dose in the lungs (estimated from the measured mass of TiO₂ and particle specific surface area) following chronic inhalation exposure to either fine or ultrafine TiO₂. A human lung dosimetry model was used to estimate the working lifetime mean exposure concentration associated with the human retained lung dose that is equivalent to the critical lung dose in rats (BMDL estimate). An assumption in this analysis is that humans would be equally sensitive to the rat at an equivalent retained lung dose. No uncertainty factors were used in the derivation of this risk-based REL.

Interestingly, the NIOSH dose-response modelling also used the same rat pulmonary inflammation data (Reference [67]) as used in the first two analyses[48][49][66][73], but different estimates were derived, resulting in a human-equivalent mean exposure of approximately 0,1 mg/m³, which is the dose associated with minimal pulmonary inflammation [4 % increase in polymorphonuclear leukocytes (Table 4-3 of NIOSH 2011[50])]. This working lifetime exposure associated with pulmonary inflammation is lower than that associated with the estimated 1/1 000 risk of lung cancer — which is consistent with the evidence that TiO₂ is an indirect carcinogen acting through persistent pulmonary inflammation. In the third analysis[50], a major difference in methods compared to the first and second analyses[48][49][66][73] in Table 3 is that NIOSH used dosimetry modelling to account for differences in the long term particle retention kinetics in the lungs of rats and humans. The NIOSH REL is intended to minimize the risk of lung cancer in workers exposed to TiO₂ over a full working lifetime.

Despite the differences in the health end points and methods and assumptions in these three risk assessments, two of the three OELs are within a factor of two (0,3 mg/m³ and 0,61 mg/m³). These OELs would fall within a 0,1 mg/m³ to 1 mg/m³ control band, and thus the selection of workplace exposure controls may be similar based on each of those analyses. The third OEL is more than an order of magnitude lower and would indicate the need to use tighter containment and control options.

6.3.3 State of the science in support of risk assessment methods for nanomaterials OELs

Ideally, the best available scientific evidence and methods should be used to derive OELs. However, resource limitations may preclude a full quantitative risk assessment in every case, even if sufficient data are available. More often, data are limited and so simple default risk assessment methods will be needed for many NOAAs. The development of a framework in which full quantitative risk assessments are performed for selected benchmark (reference) particles within biological mode-of-action (MOA) categories, combined with simplified risk assessments and comparative analyses with NOAAs in the same category, may facilitate OEL development for NOAAs. Such an approach is described further in this document. Conceptual categories have been proposed as described in Clause 7, although more analyses involving structure-activity relationships based on physico-chemical properties of NOAAs will be needed to develop a reliable and predictive risk assessment framework.

7 Categorical OELs for nanomaterials

7.1 Summary of options proposed

7.1.1 United Kingdom

The BSI “Guide to safe handling and disposal of manufactured nanomaterials”^[44] provides simple precautionary risk guidance in the form of a Public Document for the development, manufacture, and use of nanomaterials. In this document, all nanomaterials are grouped into four hazard categories with assigned Benchmark Exposure Levels (BEL). Similar to the IFA recommendations, BELs are described as “pragmatic guidance levels only” and are derived from OELs for larger particle forms “on the assumption that the hazard potential of the nanoparticle form is greater than the large particle form.” First, there is the “fibrous” category, defined as an insoluble nanomaterial with a high aspect ratio (ratio >3:1 and length >5 000 nm), which is assigned a BEL of 0,01 f/cm³ (one tenth of the asbestos OEL prescribed in the US and elsewhere). Second, there is the “CMAR” category, defined as any nanomaterial which is already classified in its larger particle form as a Carcinogenic, Mutagenic, Asthmagenic, or Reproductive toxicant. Nanomaterials in the CMAR category are assigned BELs at one tenth of the mass-based OEL for its larger particle form. Third, there is the “insoluble” category, defined as insoluble or poorly soluble nanomaterials not in the fibrous or CMAR category. Nanoparticles in this category are assigned BELs at one fifteenth of the mass-based OEL for its larger particle form or 20 000 p/cm³. Fourth, there is a “soluble” category, defined as a soluble nanomaterial not in fibrous or CMAR category, which is assigned a BEL at one half of the mass-based OEL for its larger particle form.

7.1.2 Germany

7.1.2.1 Federal Ministry of Labour and Social Affairs

In the Announcement on Hazardous Substances 527 “Manufactured Nanomaterials” from May 2013 by the Federal Ministry of Labour and Social Affairs^[46] in Germany, nanomaterials are grouped into four categories:

- a) soluble nanomaterials;
- b) biopersistent nanomaterials without specific toxicity (granular biopersistent nano-particles – nano-GBP);
- c) biopersistent nanomaterials with specific toxicity;
- d) biopersistent fibre-like nanomaterials.

Interestingly, concerning the **first category**, the terms soluble/insoluble or biopersistent are commonly used in particle toxicology but no exact definition or measurement method for these terms is at hand. Therefore as a proxy the solubility of nanomaterials in water is used and substances with a solubility less than 100 mg/l are coined “practically insoluble” and nanomaterials with solubility in water greater than 100 mg/l belong to the category of soluble nanomaterials. Fully aware of the discussions on the possible enhanced proliferation or changed pathways of soluble nanomaterials to different targets in the body, the advice has been given to perform the risk assessment for nanomaterials in this category per default in treating them like bulk materials and neglecting possible nano-related properties.

For the **second category** (nano-GBP), reference was made to the study by Gebel^[74] comparing the carcinogenicity of GBP micromaterials (micro-GBP) and nano-GBP in chronic rat inhalation studies. Gebel concluded that the difference in carcinogenic potency between GBP nanomaterials and GBP micromaterials is low and can be described by a factor of 2 to 2,5 referring to the dose metric mass concentration. The statistical methods for pooling data across studies, such as in the Gebel^[74] study, have been discussed^{[66][75][76]}.

In July 2011, the Permanent Senate Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area of the German Research Foundation proposed a reduced value of 0,3 mg/m³ for a density of 1 kg/m³^[77] for the respirable dust fraction (GBP) of the general dust limit

value. This value is intended to prevent high concentrations of these dusts from having a carcinogenic effect. Aware of this proposal and the on-going discussion, the recommendation is given in the announcement 527 to correct for the slightly higher potency of nano-GBP by applying a factor of 1/2 on the current occupational exposure limit for respirable dust in Germany, which is 3 mg/m³ for materials with a density of 2 500 kg/m³. For the time being this would result in a limit value of 1,5 mg/m³. As this was regarded too high a value in terms of particle number concentration, it was stated that the REL for nano-GBP should not exceed 0,5 mg/m³ for a density of 2 500 kg/m³, measured as the respirable dust fraction. It is highlighted that all other options to utilize REL for the risk management are still available for the companies. They may use the recommendations given by NIOSH or other organisations/companies, use the benchmark levels proposed by DGUV-IFA or set their own in-house standards.

Concerning the **third category** (biopersistent nanomaterials with a specific toxicity), reference is made to the handling of the bulk (non-nano) forms of these materials. With regard to existing OELs for most of these nanomaterials, it is stated that companies of course have to comply with the existing OELs. In Germany these OELs are usually below 0,1 mg/m³. In fact, in the discussion on deriving exposure-risk relationships and the corresponding concentrations for carcinogenic metals or metal compounds, like cobalt or nickel, mass concentrations in the range of 0,000 1 mg/m³ to 0,01 mg/m³ are proposed. Announcement 527 states that in complying with OELs in this range of concentrations a strict regime of control measures with a high efficacy has to be employed and in the case of handling the nanomaterial a further discrimination of control measures is not feasible.

For materials belonging to the **fourth category** (biopersistent fibre-like nanomaterials), the distinction is made between biopersistent, rigid nanofibres adhering to the World Health Organization (WHO) fibre paradigm, for which one has to assume an asbestos-like effect, and biopersistent, entangled or spaghetti-like nanofibres. For the latter asbestos-like effects can only be excluded in the risk assessment, if the manufacturer or supplier of the given nanomaterial can provide evidence that the nanomaterial does not exhibit asbestos-like effects. Overall companies are strongly discouraged to use biopersistent, rigid nanofibres and a very strict regime of control measures has to be followed, if these materials are handled.

In conclusion, one can summarize Announcement 527 on “Manufactured Nanomaterials” in the way that at least for the time being and for the handling of the first, passive generation of nanomaterials these materials are mostly treated at the workplace like ordinary hazardous substances. The only exception being the evaluation of control measures for nano-GBP, as in this case a factor of 1/2 is applied to the respirable dust limit values may be used. The Announcement will be adapted if new evidence on toxicological properties of manufactured nanomaterials emerges or if future generations of active nanomaterials find its way to the workplace and pose new hazards.

7.1.2.2 German Social Accident Insurance

In Germany, the Institute for Occupational Safety and Health of the German Social Accident Insurance (IFA)^[78] recommended the following benchmark limits to be used for an 8 h work shift and to be used for monitoring the effectiveness of protective measures in the workplace^[78].

- For metals, metal oxides and other biopersistent granular nanomaterials with a density of >6 000 kg/m³, a particle number concentration of 20 000 p/cm³ in the range of measurement between 1 nm and 100 nm should not be exceeded.
- For biopersistent granular nanomaterials with a density below 6 000 kg/m³, a particle number concentration of 40 000 p/cm³ in the measured range between 1 nm and 100 nm should not be exceeded.
- For CNT for which no such manufacturer’s declaration is available, a provisional fibre concentration of 0,01 f/cm³ should not be exceeded, based upon the exposure risk ratio for asbestos. It is recommended that only carbon nanotubes that have been tested for adverse health effects similar to those of asbestos (according to the manufacturer’s declaration) be used.

- For nanoscale liquid particles (such as fats, hydrocarbons, siloxanes), the applicable maximum workplace limit (MAK) or workplace limit (AGW) values should be employed owing to the absence of effects of solid particles.

These recommended benchmark limits are geared to minimizing the exposure in accordance with the state of the art in measurements. Since these limits are not based on observed health effects, a health risk may still exist for workers, even where these recommended limits are followed. Therefore, benchmark limits should not be confused with health-based OELs[78].


7.1.3 NIOSH

NIOSH has not formally proposed a categorical approach to developing OELs for nanomaterials, although efforts are underway to evaluate the available science and methodologies for developing categorical OELs or OEBs for nanomaterials (described in Reference [20]). In some respects, the NIOSH RELs for nanoscale titanium dioxide[50] and carbon nanotubes and nanofibres[58] are categorical since these RELs are intended to apply to various forms of these substances, which may include variability in their hazard potential.

7.1.4 Japan's (AIST's) approaches

7.1.4.1 Biaxial approach

Under a NEDO project (P06041) "Research and Development of Nanoparticle Characterization Methods", Nakanishi[55][79] adopted a method called the biaxial approach. Figure 2 shows a conceptual diagram of the biaxial approach.



NOTE See Reference [49].

Figure 2 — Biaxial approach


The idea was to fill up the whole diagram by conducting detailed examinations of the representative test samples along the horizontal axis, and obtained relative values of many nanomaterials through fairly simple tests on the vertical axis. On the horizontal axis, *in vivo* tests (intratracheal instillation and inhalation exposure tests) using rats, biokinetics and gene expression analyses were conducted, and the NOAELs regarding the inhalation exposure of rats were computed. Then, the knowledge accumulated thus far was used to extrapolate the extent of the effects on humans, i.e. OELs were derived. Meanwhile, along the vertical axis, Nakanishi, et al.[55][79] conducted as simple a test as possible to find out the values of the materials relative to one another, which was to determine harmful effect values and then the OEL of various materials. They had initially considered *in vitro* tests for the vertical axis tests, but they decided to use the intratracheal instillation method instead.

7.1.4.2 Equivalence criteria

The Ministry of Economy, Trade and Industry of Japan launched a five-year program for the “Development of Innovative methodology for Safety Assessment of Industrial Nanomaterials” in September 2011, which aims to develop fundamental hazard assessment methodology leading to a tiered risk assessment approach for industrial nanomaterials. The program has two R&D themes:

- a) establishment of “equivalence criteria” of nanomaterials;
- b) establishment of an intratracheal (IT) administration method as a low-cost and convenient method for hazard assessment to acquire basic hazard information, both of which are for regulatory purposes[80].

The Japanese National Institute of Advanced Industrial Science and Technology (AIST) is developing the “equivalence criteria” based on the data from a set of IT administration tests using nanomaterials with different physico-chemical properties such as size, surface area, shape, surface chemistry, composition, etc., when focusing on effects in the lungs. If the toxicity of nanomaterials is insensitive to a property, two nanomaterials can be regarded equivalent regardless of large difference in the property. On the other hand, if a property is found dominating toxicity, slight difference in the property would compromise equivalence between two nanomaterials. Figure 3 explains a possible use of “equivalence criteria” in an efficient hazard assessment framework of nanomaterials[80].



NOTE See <http://metinanoen.aist-riss.jp/>.

Figure 3 — Equivalence criteria used in an efficient hazard assessment framework of nanomaterials

7.1.4.3 Possible index of comparative potency of nanomaterials

The Japanese National Institute of Advanced Industrial Science and Technology (AIST) has selected the rate of increase in neutrophil in bronchoalveolar lavage fluid (BALF) as a biomarker indicating potency of pulmonary toxicity of nanomaterials. Nakanishi, et al.[49] further showed a future possibility that BET specific surface area, a physical property of nanomaterials, could be used as an index of comparative potency of nanomaterials.

7.1.5 OECD

OECD defines a categorical approach as follows. Chemicals whose physico-chemical, toxicological and eco-toxicological properties are likely to be similar or follow a regular pattern as a result of structural similarity may be considered as a group, or “category” of chemicals[27]. The assessment of chemicals by

using this category approach differs from the approach of assessing them on an individual basis, since the properties of the individual chemicals within a category are assessed on the basis of the evaluation of the category as a whole, rather than based on measured data for any one particular chemical alone. The increasing amount of toxicology data for NOAAs provides opportunities to develop criteria for hazard- and risk-categories for NOAAs[27][81][82][83].

The OECD Working Party on Manufactured Nanomaterials (WPMN) organized an expert meeting in September 2014 to further develop categorization approach for manufactured NOAAs and to provide recommendations on how manufactured NOAAs should be categorized for the purposes of testing, read across/Structure-Activity Relationship models, risk assessment and risk management[17]. It also analysed information collected by a questionnaire-based survey about OECD member countries' approaches to develop or use concepts of grouping, equivalence and read-across based on physico-chemical properties of NOAAs for their hazard assessment in regulatory regimes[84].

The OECD Working Party on Manufactured Nanomaterials expert meeting also discussed differences in hazard properties possibly arising from differences in shape (e.g. fibre, plate), physical properties (e.g. zeta potential, solubility) and bio-persistence and if this could be addressed in a categorization scheme.

7.2 Evaluation of categorical OEL

7.2.1 Similarities and differences

All approaches to derivation of categorical OEL presented in 7.1 are based on the anticipated primary mode of action and arrive at very similar categories and values of categorical OELs. They differ in details of category descriptions and scaling factors applied to OELs for corresponding bulk materials (see Table 4).

Table 4 — Comparison of categorical OELs

	BSI[44]	BAuA[46]	IFA[78]
Low toxicity immune effects			
Category description	insoluble or poorly soluble nanomaterials not in the fibrous or CMAR category	nanomaterials with density of 2 500 kg/m ³ , measured as the respirable dust fraction	High Density: biopersistent granular nanomaterials with a density of >6 000 kg/m ³ Low Density: biopersistent granular nanomaterials with a density below 6 000 kg/m ³
Categorical OEL value	20 000 p/cm ³	1,5 mg/m ³ (0,5 mg/m ³ recommended)	0,1 mg/m ³ High Density: 20 000 p/cm ³ Low Density: 40 000 p/cm ³
Scale factor for bulk OELs	0,067	0,5 (0,167 recommended)	0,333
Toxicity of dissolved ions/molecules			
Category description	soluble nanomaterial not in fibrous or CMAR category	nanomaterials with solubility in water greater than 100 mg/l	High Density: biopersistent granular nanomaterials with a density of >6 000 kg/m ³ Low Density: biopersistent granular nanomaterials with a density below 6 000 kg/m ³