

ITU-R

Radiocommunication Sector of ITU

Recommendation ITU-R M.2031-1 (09/2015)

Characteristics and protection criteria of receiving earth stations and characteristics of transmitting space stations in the radionavigation-satellite service (space-to-Earth) operating in the band 5 010-5 030 MHz

M Series
**Mobile, radiodetermination, amateur
and related satellite services**



International
Telecommunication
Union

Documents

Document Sharing Hub

Foreword

The role of the Radiocommunication Sector is to ensure the rational, equitable, efficient and economical use of the radio-frequency spectrum by all radiocommunication services, including satellite services, and carry out studies without limit of frequency range on the basis of which Recommendations are adopted.

The regulatory and policy functions of the Radiocommunication Sector are performed by World and Regional Radiocommunication Conferences and Radiocommunication Assemblies supported by Study Groups.

Policy on Intellectual Property Right (IPR)

ITU-R policy on IPR is described in the Common Patent Policy for ITU-T/ITU-R/ISO/IEC referenced in Annex 1 of Resolution ITU-R 1. Forms to be used for the submission of patent statements and licensing declarations by patent holders are available from <http://www.itu.int/ITU-R/go/patents/en> where the Guidelines for Implementation of the Common Patent Policy for ITU-T/ITU-R/ISO/IEC and the ITU-R patent information database can also be found.

Series of ITU-R Recommendations

(Also available online at <http://www.itu.int/publ/R-REC/en>)

Series	Title
BO	Satellite delivery
BR	Recording for production, archival and play-out; film for television
BS	Broadcasting service (sound)
BT	Broadcasting service (television)
F	Fixed service
M	Mobile, radiodetermination, amateur and related satellite services
P	Radiowave propagation
RA	Radio astronomy
RS	Remote sensing systems
S	Fixed-satellite service
SA	Space applications and meteorology
SF	Frequency sharing and coordination between fixed-satellite and fixed service systems
SM	Spectrum management
SNG	Satellite news gathering
TF	Time signals and frequency standards emissions
V	Vocabulary and related subjects

Note: This ITU-R Recommendation was approved in English under the procedure detailed in Resolution ITU-R 1.

Electronic Publication
Geneva, 2015

© ITU 2015

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without written permission of ITU.

RECOMMENDATION ITU-R M.2031-1¹**Characteristics and protection criteria of receiving earth stations and characteristics of transmitting space stations in the radionavigation-satellite service (space-to-Earth) operating in the band 5 010-5 030 MHz**

(Questions ITU-R 217-2/4 and ITU-R 288/4)

(2012-2015)

Scope

Characteristics and protection criteria for radionavigation-satellite service (RNSS) receiving earth stations, and characteristics of RNSS transmitting space stations planned or operating in the band 5 010-5 030 MHz are presented in this Recommendation. This information is intended for performing sharing and compatibility analyses of radiofrequency interference impact on systems and networks in the RNSS (space-to-Earth) operating in the band 5 010-5 030 MHz from radio sources other than in the RNSS.

Keywords

RNSS, protection criteria, radiofrequency interference impact

Abbreviations/Glossary

AWGN	additive white Gaussian noise
PDC	pulse duty cycle
PNT	position, navigation and timing
PRF	pulse repetition frequency
RHCP	Right-hand circular polarization
SQPN	Staggered quadrature pseudo-random noise
SQPSK	Staggered quadrature phase-shift keying
SSC	Spectral separation coefficient

Related ITU Recommendations, Reports

- Recommendation ITU-R M.1318-1 Evaluation model for continuous interference from radio sources other than in the radionavigation-satellite service to the radionavigation-satellite service systems and networks operating in the 1 164-1 215 MHz, 1 215-1 300 MHz, 1 559-1 610 MHz and 5 010-5 030 MHz bands
- Recommendation ITU-R M.1787-2 Description of systems and networks in the radionavigation-satellite service (space-to-Earth and space-to-space) and technical characteristics of transmitting space stations operating in the bands 1 164-1 215 MHz, 1 215-1 300 MHz and 1 559-1 610 MHz
- Recommendation ITU-R M.1831-1 A coordination methodology for RNSS inter-system interference estimation

¹ This Recommendation should be brought to the attention of ITU-R Study Group 5 and the International Civil Aviation Organization (ICAO).

- Recommendation ITU-R M.1901-1 Guidance on ITU-R Recommendations related to systems and networks in the radionavigation-satellite service operating in the frequency bands 1 164-1 215 MHz, 1 215-1 300 MHz, 1 559-1 610 MHz, 5 000-5 010 MHz and 5 010-5 030 MHz
- Recommendation ITU-R M.1902-0 Characteristics and protection criteria for receiving earth stations in the radionavigation-satellite service (space-to-Earth) operating in the band 1 215-1 300 MHz
- Recommendation ITU-R M.1903-0 Characteristics and protection criteria for receiving earth stations in the radionavigation-satellite service (space-to-Earth) and receivers in the aeronautical radionavigation service operating in the band 1 559-1 610 MHz
- Recommendation ITU-R M.1904-0 Characteristics, performance requirements and protection criteria for receiving stations of the radionavigation-satellite service (space-to-space) operating in the frequency bands 1 164-1 215 MHz, 1 215-1 300 MHz and 1 559-1 610 MHz
- Recommendation ITU-R M.1905-0 Characteristics and protection criteria for receiving earth stations in the radionavigation-satellite service (space-to-Earth) operating in the band 1 164-1 215 MHz
- Recommendation ITU-R M.1906-1 Characteristics and protection criteria of receiving space stations and characteristics of transmitting earth stations in the radionavigation-satellite service (Earth-to-space) operating in the band 5 000-5 010 MHz
- Recommendation ITU-R M.2030-0 Evaluation method for pulsed interference from relevant radio sources other than in the radionavigation-satellite service to the radionavigation-satellite service systems and networks operating in the 1 164-1 215 MHz, 1 215-1 300 MHz and 1 559-1 610 MHz frequency bands

The ITU Radiocommunication Assembly,

considering

- a) that systems and networks in the radionavigation-satellite service (RNSS) provide worldwide accurate information for many positioning, navigation and timing applications, including safety aspects for in some frequency bands and under certain circumstances and applications;
- b) that there are various operating and planned systems and networks in the RNSS;
- c) that studies are being conducted on the interference into RNSS systems and networks from other radio services,

recognizing

- a) that the band 5 010-5 030 MHz is allocated on a primary basis to the RNSS (space-to-Earth and space-to-space) in all three Regions;
- b) that the band 5 010-5 030 MHz is also allocated on a primary basis to the aeronautical radionavigation service (ARNS) in all three Regions;
- c) that the band 5 010-5 030 MHz is also allocated on a primary basis to the aeronautical mobile-satellite (route) service (AMS(R)S) in all three Regions subject to RR No. **9.21**;