



Report ITU-R RA.2188
(10/2010)

**Power flux-density and e.i.r.p.
levels potentially damaging to
radio astronomy receivers**

RA Series
Radio astronomy



Documents
Document Sharing Hub

Foreword

The role of the Radiocommunication Sector is to ensure the rational, equitable, efficient and economical use of the radio-frequency spectrum by all radiocommunication services, including satellite services, and carry out studies without limit of frequency range on the basis of which Recommendations are adopted.

The regulatory and policy functions of the Radiocommunication Sector are performed by World and Regional Radiocommunication Conferences and Radiocommunication Assemblies supported by Study Groups.

Policy on Intellectual Property Right (IPR)

ITU-R policy on IPR is described in the Common Patent Policy for ITU-T/ITU-R/ISO/IEC referenced in Annex 1 of Resolution ITU-R 1. Forms to be used for the submission of patent statements and licensing declarations by patent holders are available from <http://www.itu.int/ITU-R/go/patents/en> where the Guidelines for Implementation of the Common Patent Policy for ITU-T/ITU-R/ISO/IEC and the ITU-R patent information database can also be found.

Series of ITU-R Reports

(Also available online at <http://www.itu.int/publ/R-REP/en>)

Series	Title
BO	Satellite delivery
BR	Recording for production, archival and play-out; film for television
BS	Broadcasting service (sound)
BT	Broadcasting service (television)
F	Fixed service
M	Mobile, radiodetermination, amateur and related satellite services
P	Radiowave propagation
RA	Radio astronomy
RS	Remote sensing systems
S	Fixed-satellite service
SA	Space applications and meteorology
SF	Frequency sharing and coordination between fixed-satellite and fixed service systems
SM	Spectrum management

***Note:** This ITU-R Report was approved in English by the Study Group under the procedure detailed in Resolution ITU-R 1.*

Electronic Publication
Geneva, 2010

© ITU 2010

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without written permission of ITU.

REPORT ITU-R RA.2188

**Power flux-density and e.i.r.p. levels potentially damaging
to radio astronomy receivers**

(Question ITU-R 145/7)

(2010)

TABLE OF CONTENTS

Page

1	General explanation of concerns	2
2	Conversion from empirically-determined, device-specific damaging power input levels to corresponding incident pfd and e.i.r.p.....	2
3	Values of the damaging input power levels P_d and corresponding incident pfd F_d	3
A	Frequencies up to 90 GHz: HFET amplifiers.....	3
B	Frequencies above 90 GHz: SIS mixer input stages	3
4	Summary: Threshold levels of the incident power flux-density.....	4
	Annex 1 – Operational concerns relevant to avoidance of damage	5