



COVERING NOTE

GENERAL SECRETARIAT INTERNATIONAL TELECOMMUNICATION UNION

Subject: Erratum

Geneva, 7 December 2000

Recommendation ITU-T G.108 (09/99)

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

ITU-T Recommendation G.108 (09/99)

Application of the E-model: A planning guide

1. The following Table of Figures and Table of Tables should be inserted under "Contents".

TABLE OF FIGURES

	Page
Figure 1/G.108 – Basic configuration for the interconnection between private and public network.....	12
Figure 2/G.108 – Standard configuration with a fully digital routing within the private network.....	13
Figure 3/G.108 – Private Network with 4-wire/2-wire Conversion.....	14
Figure 4/G.108 – Digitally connected wireless telephone set.....	14
Figure 5/G.108 – Basic connection between the PSTN and an IP network with its H.323 terminal and a PBX connected via an IWF.....	15
Figure 6/G.108 – The E-Model in the environment of subjective and objective testing.....	17
Figure 7/G.108 – General configuration for calls via public networks.....	17
Figure 8/G.108 – Example for the addition of impairments on a "Psychological scale".....	18
Figure 9/G.108 – Relation between OLR and E-Model Rating R.....	21
Figure 10/G.108 – E-Model Rating R due to talker echo.....	22
Figure 11/G.108 – Relation between absolute delay (Ta) and E-Model Rating R.....	23
Figure 12/G.108 – Relation between the number of qdu and E-Model Rating R.....	26
Figure 13/G.108 – Reference connection for the calculation of SLR and RLR.....	36
Figure 14/G.108 – Reference connection for echo calculations with one echo path.....	39
Figure 15/G.108 – Reference connection for echo calculations with two echo paths.....	40
Figure 16/G.108 – Details inside a cordless telephone with respect to echo control.....	41
Figure 17/G.108 – Basic reference configuration of the E-Model.....	44
Figure 18/G.108 – Working configuration for 2-wire/2-wire connections.....	45
Figure 19/G.108 – Working configuration for 4-wire/2-wire connections.....	47

Union internationale des télécommunications

Place des Nations 1211 GENEVE 20 Suisse – Switzerland – Suiza



Documents

Document Sharing Hub

Figure 20/G.108 – Working configuration for 2-wire/4-wire connections	48
Figure 21/G.108 – Working configuration for fully digital connections	48
Figure 22/G.108 – Echo canceller.....	55
Figure 23/G.108 – Application of a pair of echo cancellers within the private network.....	57
Figure 24/G.108 – Options for the location of an echo canceller	58
Figure 25/G.108 – Use of echo cancellers in an internetwork or international connection	59
Figure 26/G.108 – Judgement of a connection on a linear quality scale.....	63
Figure A.1/G.108 – Echo cancellers in a private network and their echo paths.....	74
Figure A.2/G.108 – Access and routing in public networks	76
Figure A.3a/G.108 – Configurations and transmission characteristics for the far-end termination – Europe	79
Figure A.3b/G.108 – Configurations and transmission characteristics for the far-end Termination – North America	81
Figure B.1/G.108 – Basic structure of the private network.....	83
Figure B.2/G.108 – Reference configuration 1	84
Figure B.3/G.108 – Reference configuration 2	84
Figure B.4/G.108 – Reference configuration 3	85
Figure B.5/G.108 – Use of low bit-rate equipment for a leased line.....	87
Figure B.6/G.108 – Basis for calculation of reference configuration 1	89
Figure B.7/G.108 – Basis for calculation of reference configuration 2	93
Figure B.8/G.108 – Basis for calculation of reference configuration 3	95
Figure B.9/G.108 – Application of echo control devices in the private network.....	99
Figure B.10/G.108 – Reference configuration 1	100
Figure B.11/G.108 – Reference configuration 2	100
Figure B.12/G.108 – Reference configuration 3	101
Figure B.13/G.108 – Basis for calculation for reference configuration 1a	102
Figure B.13a/G.108 – Analogue set @ A & analogue set @ B as perceived @ side A.....	105
Figure B.13b/G.108 – Analogue set @ A & analogue set @ B as perceived @ side B.....	106
Figure B.14/G.108 – Basis for calculation of reference configuration 1b	107
Figure B.14a/G.108 – Digital set @ A & analogue set @ B as perceived @ side A	110
Figure B.14b/G.108 – Digital set @ A & analogue set @ B as perceived @ side B	110
Figure B.15/G.108 – Basis for calculation of reference configuration 2	111
Figure B.15a/G.108 – Unlicensed: Wireless processing delay: 7 ms avg.....	115
Figure B.15b/G.108 – Licensed: Wireless processing delay: 100 ms avg	115
Figure B.16/G.108 – Basis for calculation of reference configuration 3a.....	116
Figure B.16a/G.108 – Unlicensed: Wireless processing delay: 7 ms avg.....	120
Figure B.16b/G.108 – Licensed: Wireless processing delay: 100 ms avg	120
Figure B.17/G.108 – Basis for calculation of reference configuration 3b	121
Figure B.17a/G.108 – Unlicensed: Wireless processing delay: 7 ms avg.....	124
Figure B.17b/G.108 – Licensed: Wireless processing delay: 100 ms avg	125
Figure C.1/G.108 – Possible echo paths for a cordless telephone.....	128
Figure C.2/G.108 – Echo control devices in a DECT cordless telephone.....	129
Figure C.3/G.108 – TCLw and artificial echo loss	130