



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

G.745

GENERAL ASPECTS OF DIGITAL TRANSMISSION SYSTEMS

TERMINAL EQUIPMENTS

SECOND ORDER DIGITAL MULTIPLEX EQUIPMENT OPERATING AT 8448 kbit/s AND USING POSITIVE/ZERO/NEGATIVE JUSTIFICATION

ITU-T Recommendation G.745

(Extract from the *Blue Book*)

NOTES

1 ITU-T Recommendation G.745 was published in Fascicle III.4 of the *Blue Book*. This file is an extract from the *Blue Book*. While the presentation and layout of the text might be slightly different from the *Blue Book* version, the contents of the file are identical to the *Blue Book* version and copyright conditions remain unchanged (see below).

2 In this Recommendation, the expression “Administration” is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

© ITU 1988, 1993

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the ITU.



Documents
Document Sharing Hub

Recommendation G.745

SECOND ORDER DIGITAL MULTIPLEX EQUIPMENT OPERATING AT 8448 kbit/s AND USING POSITIVE/ZERO/NEGATIVE JUSTIFICATION

(Geneva, 1976; amended at Geneva, 1980 and at Melbourne, 1988)

1 General

The second order digital multiplex equipment using positive/zero/negative justification, considered below, is intended for use on digital paths between countries using 2048 kbit/s primary multiplex equipments, such as the PCM multiplex equipment described in Recommendation G.732 or any identical equipment.

2 Bit rate

The nominal bit rate should be 8448 kbit/s. The tolerance on that rate should be ± 30 parts per million (ppm).