International Telecommunication Union

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

G.8112/Y.1371

Amendment 1

(08/2017)

SERIES G: TRANSMISSION SYSTEMS AND MEDIA, DIGITAL SYSTEMS AND NETWORKS

Packet over Transport aspects – MPLS over Transport aspects

SERIES Y: GLOBAL INFORMATION INFRASTRUCTURE, INTERNET PROTOCOL ASPECTS, NEXT-GENERATION NETWORKS, INTERNET OF THINGS AND SMART CITIES

Internet protocol aspects – Transport

Interfaces for the MPLS transport profile layer network

Amendment 1

Recommendation ITU-T G.8112/Y.1371 (2015) – Amendment 1

Copyright International Telecommunication Union/ITU Telcommunication Sector
Provided by IHS Markit under license with ITU-T
No reproduction or networking permitted without license from IHS
Full document details: ITU-T G.8112 AMD 1 2017

Licensee=/, User=,
Not for Resale,

ITU-T G-SERIES RECOMMENDATIONS

TRANSMISSION SYSTEMS AND MEDIA, DIGITAL SYSTEMS AND NETWORKS

INTERNATIONAL TELEPHONE CONNECTIONS AND CIRCUITS	G.100–G.199
GENERAL CHARACTERISTICS COMMON TO ALL ANALOGUE CARRIER-TRANSMISSION SYSTEMS	G.200–G.299
INDIVIDUAL CHARACTERISTICS OF INTERNATIONAL CARRIER TELEPHONE SYSTEMS ON METALLIC LINES	G.300–G.399
GENERAL CHARACTERISTICS OF INTERNATIONAL CARRIER TELEPHONE SYSTEMS ON RADIO-RELAY OR SATELLITE LINKS AND INTERCONNECTION WITH METALLIC LINES	G.400–G.449
COORDINATION OF RADIOTELEPHONY AND LINE TELEPHONY	G.450–G.499
TRANSMISSION MEDIA AND OPTICAL SYSTEMS CHARACTERISTICS	G.600–G.699
DIGITAL TERMINAL EQUIPMENTS	G.700–G.799
DIGITAL NETWORKS	G.800–G.899
DIGITAL SECTIONS AND DIGITAL LINE SYSTEM	G.900–G.999
MULTIMEDIA QUALITY OF SERVICE AND PERFORMANCE – GENERIC AND USER-RELATED ASPECTS	G.1000–G.1999
TRANSMISSION MEDIA CHARACTERISTICS	G.6000–G.6999
DATA OVER TRANSPORT – GENERIC ASPECTS	G.7000–G.7999
PACKET OVER TRANSPORT ASPECTS	G.8000–G.8999
Ethernet over Transport aspects	G.8000–G.8099
MPLS over Transport aspects	**G.8100–G.8199**
Synchronization, quality and availability targets	G.8200–G.8299
Service Management	G.8600–G.8699
ACCESS NETWORKS	G.9000–G.9999

For further details, please refer to the list of ITU-T Recommendations.

Documents
Document Sharing Hub

--`,,```,,,,````-`-`,,`,,`,`,,`---
Copyright International Telecommunication Union/ITU Telcommunication Sector
Provided by IHS Markit under license with ITU-T
No reproduction or networking permitted without license from IHS
Licensee=/, User=,
Not for Resale,
Full document details: ITU-T G.8112 AMD 1 2017

Recommendation ITU-T G.8112/Y.1371

Interfaces for the MPLS transport profile layer network

Amendment 1

Summary

Recommendation ITU-T G.8112/Y.1371 specifies the interfaces for the multi-protocol label switching transport profile (MPLS-TP) layer network. The interfaces for the MPLS-TP layer network use various server layer networks, like the plesiochronous digital hierarchy (PDH), synchronous digital hierarchy (SDH), optical transport hierarchy (OTH) and the Ethernet MAC layer network (ETH).

Amendment 1 avoids redefining terms already defined in Recommendations ITU-T G.8001/Y.1354 and ITU-T G.8101/Y.1355 by referencing these Recommendations.

History

Edition	Recommendation	Approval	Study Group	Unique ID*
1.0	ITU-T G.8112/Y.1371	2006-10-07	15	11.1002/1000/8783
1.1	ITU-T G.8112/Y.1371 (2006) Cor. 1	2007-01-09	15	11.1002/1000/9006
2.0	ITU-T G.8112/Y.1371	2012-10-29	15	11.1002/1000/11772
2.1	ITU-T G.8112/Y.1371 (2012) Amd. 1	2014-04-04	15	11.1002/1000/12187
2.2	ITU-T G.8112/Y.1371 (2012) Cor. 1	2015-01-13	15	11.1002/1000/12385
3.0	ITU-T G.8112/Y.1371	2015-08-13	15	11.1002/1000/12547
3.1	ITU-T G.8112/Y.1371 (2015) Amd. 1	2017-08-13	15	11.1002/1000/13315

* To access the Recommendation, type the URL http://handle.itu.int/ in the address field of your web browser, followed by the Recommendation's unique ID. For example, http://handle.itu.int/11.1002/1000/11830-en.

Documents
Document Sharing Hub

Copyright International Telecommunication Union/ITU Telcommunication Sector
Provided by IHS Markit under license with ITU-T
No reproduction or networking permitted without license from IHS
Licensee=/, User=,
Not for Resale,
Full document details: ITU-T G.8112 AMD 1 2017

FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications, information and communication technologies (ICTs). The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure, e.g., interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementers are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database at http://www.itu.int/ITU-T/ipr/.

© ITU 2017

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

Documents
Document Sharing Hub
Copyright International Telecommunication Union/ITU Telcommunication Sector
Provided by IHS Markit under license with ITU-T
No reproduction or networking permitted without license from IHS
Licensee=/, User=,
Not for Resale,
Full document details: ITU-T G.8112 AMD 1 2017

Table of Contents

		Page
1	Scope	1
2	References	1
3	Definitions	3
	3.1 Terms defined elsewhere	3
	3.2 Terms defined in this Recommendation	3
4	Abbreviations and acronyms	4
5	Conventions	6
6	MPLS transport profile layer network interface structure	6
	6.1 NNI basic signal structure	7
	6.2 Information structure for the MPLS-TP network node interfaces	10
	6.3 MPLS-TP labels	17
	6.4 MPLS-TP shim header	17
7	Multiplexing/mapping principles	18
	7.1 Mapping	18
	7.2 MPLS-TP multiplex	18
	7.3 MPLS-TP tandem connection monitoring	18
8	Physical specification of the MPLS-TP interfaces	18
Appendix I – Example of layer networks in ETH UNI and MPLS-TP NNI		19
Appendix II – Bandwidth requirements for MPLS-TP transport		20

Documents
Document Sharing Hub
Copyright International Telecommunication Union/ITU Telcommunication Sector
Provided by IHS Markit under license with ITU-T
No reproduction or networking permitted without license from IHS
Full document details: ITU-T G.8112 AMD 1 2017
Licensee=/, User=,
Not for Resale,

Documents
Document Sharing Hub

Copyright International Telecommunication Union/ITU Telcommunication Sector
Provided by IHS Markit under license with ITU-T
No reproduction or networking permitted without license from IHS
Full document details: ITU-T G.8112 AMD 1 2017

Licensee=/, User=,
Not for Resale,

Recommendation ITU-T G.8112/Y.1371

Interfaces for the MPLS transport profile layer network

Amendment 1

Editorial note: This is a complete-text publication. Modifications introduced by this amendment are shown in revision marks relative to Recommendation ITU-T G.8112/Y.1371 (2015).

1 Scope

This Recommendation specifies the interfaces for the multi-protocol label switching transport profile (MPLS-TP) layer network, in particular the:

- encapsulation of MPLS-TP client signals into the MPLS-TP characteristic information that will be present on MPLS-TP network-to-network interface (NNI) links in the transport network;
- encapsulation of MPLS-TP characteristic information into the MPLS-TP link frames that will be present on MPLS-TP NNI links in the transport network;
- MPLS-TP layer network within the transport network and associated MPLS-TP multiplexing;
- MPLS-TP nested connection monitoring per layer network level within the transport network;
- MPLS-TP operation, administration and maintenance (OAM) associated with nested connection monitoring in the transport network;
- encapsulation of MPLS-TP control plane information.

The MPLS-TP network uses various server layer networks like optical transport hierarchy (OTH), synchronous digital hierarchy (SDH), plesiochronous digital hierarchy (PDH) and Ethernet MAC layer network (ETH). The detailed requirements are specified in a number of ITU-T Recommendations, ANSI Standards, IEEE Standards and IETF RFCs, which are cited.

This Recommendation specifies point-to-point label-switched paths (LSPs); point-to-multipoint LSPs are for further study.

This Recommendation does not cover inter-operator control plane aspects of the MPLS-TP NNI.

This Recommendation provides a representation of the MPLS-TP technology using the methodologies that have been used for other transport technologies [e.g., SDH, optical transport network (OTN) and Ethernet].[1]

2 References

The following ITU-T Recommendations and other references contain provisions which, through reference in this text, constitute provisions of this Recommendation. At the time of publication, the editions indicated were valid. All Recommendations and other references are subject to revision; users of this Recommendation are therefore encouraged to investigate the possibility of applying the most recent edition of the Recommendations and other references listed below. A list of the currently

[1] This Recommendation is intended to be aligned with the IETF MPLS RFCs normatively referenced by this Recommendation.

Documents
Document Sharing Hub
Copyright International Telecommunication Union/ITU Telcommunication Sector
Provided by IHS Markit under license with ITU-T
No reproduction or networking permitted without license from IHS
Licensee=/, User=,
Not for Resale,
Full document details: ITU-T G.8112 AMD 1 2017

valid ITU-T Recommendations is regularly published. The reference to a document within this Recommendation does not give it, as a stand-alone document, the status of a Recommendation.

[ITU-T G.704] Recommendation ITU-T G.704 (1998), *Synchronous frame structures used at 1544, 6312, 2048, 8448 and 44 736 kbit/s hierarchical levels*.

[ITU-T G.705] Recommendation ITU-T G.705 (2000), *Characteristics of plesiochronous digital hierarchy (PDH) equipment functional blocks*.

[ITU-T G.707] Recommendation ITU-T G.707/Y.1322 (2007), *Network node interface for the synchronous digital hierarchy (SDH)*.

[ITU-T G.709] Recommendation ITU-T G.709/Y.1331 (2012), *Interfaces for the optical transport network*.

[ITU-T G.832] Recommendation ITU-T G.832 (1998), *Transport of SDH elements on PDH networks – Frame and multiplexing structures*.

[ITU-T G.951] Recommendation ITU-T G.951 (1988), *Digital line systems based on the 1544 kbit/s hierarchy on symmetric pair cables*.

[ITU-T G.7041] Recommendation ITU-T G.7041/Y.1303 (2011), *Generic framing procedure*.

[ITU-T G.7043] Recommendation ITU-T G.7043/Y.1343 (2004), *Virtual concatenation of plesiochronous digital hierarchy (PDH) signals*.

[ITU-T G.7712] Recommendation ITU-T G.7712/Y.1703 (2010), *Architecture and specification of data communication network*.

[ITU-T G.8001] Recommendation G.8001/Y.1354 (~~2013~~2016), *Terms and definitions for Ethernet frames over transport*.

[ITU-T G.8012] Recommendation G.8012/Y.1308 (2004), *Ethernet UNI and Ethernet NNI*.

[ITU-T G.8040] Recommendation ITU-T G.8040/Y.1340 (2005), *GFP frame mapping into Plesiochronous Digital Hierarchy (PDH)*.

[ITU-T G.8101] Recommendation G.8101/Y.1355 (~~2015~~2016), *Terms and definitions for MPLS transport profile*.

[ITU-T G.8110.1] Recommendation ITU-T G.8110.1/Y.1370.1 (2011), *Architecture of the Multi-Protocol Label Switching transport profile layer network*.

[ITU-T G.8151] Recommendation ITU-T G.8151/Y.1374 (2015), *Management aspects of the MPLS-TP network element*.

[ITU-T Y.1415] Recommendation ITU-T Y.1415 (2005), *Ethernet-MPLS network interworking – User plane interworking*.

[ITU-Y Y.1711] Recommendation ITU-T Y.1711 (2004), *Operation & Maintenance mechanism for MPLS networks*.

[ANSI T1.107] ANSI T1.107[2]-2002, *Digital hierarchy – Formats Specifications*.

[IEEE 802.3] IEEE 802.3-2012, *IEEE Standard for Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Carrier Sense Multiple Access with Collision Detection (CSMA/CD) Access Method and Physical Layer Specifications*.

[IETF RFC 3031] IETF RFC 3031 (2001), *Multiprotocol Label Switching Architecture*.

[2] T1 standards are maintained since November 2003 by ATIS.

Documents
Document Sharing Hub
Copyright International Telecommunication Union/ITU Telcommunication Sector
Provided by IHS Markit under license with ITU-T
No reproduction or networking permitted without license from IHS
Licensee=/, User=,
Not for Resale,
Full document details: ITU-T G.8112 AMD 1 2017

[IETF RFC 3032] IETF RFC 3032 (2001), *MPLS Label Stack Encoding*.

[IETF RFC 5586] IETF RFC 5586 (2009), *MPLS Generic Associated Channel*.

[IETF RFC 5921] IETF RFC 5921 (2010), *A Framework for MPLS in Transport Networks*.

[IETF RFC 5960] IETF RFC 5960 (2010), *MPLS Transport Profile Data Plane Architecture*.

[IETF RFC 6215] IETF RFC 6215 (2011), *MPLS Transport Profile User-to-Network and Network-to-Network Interfaces*.

[IETF RFC 7213] IETF RFC 7213 (2014), *MPLS Transport Profile (MPLS-TP) Next-Hop Ethernet Addressing*.

3 Definitions

3.1 Terms defined elsewhere

This Recommendation uses the following terms defined elsewhere:

3.1.1 customer edge: [IETF RFC 5921] The client function that sources or sinks native service traffic to or from the MPLS-TP network. CEs on either side of the MPLS-TP network are peers and view the MPLS-TP network as a single link.

3.1.2 inter-domain interface: [ITU-T G.8101]

3.1.3 intra-domain interface: [ITU-T G.8101]

3.1.4 MPLS-TP characteristic information (MPLS-TP_CI) traffic unit: [ITU-T G.8101]

3.1.5 MPLS-TP provider edge LSR (MPLS-TP PE): See clauses 1.3.5 and 1.3.5.2 of [IETF RFC 5921].

3.1.6 network-to-network interface (NNI): [ITU-T G.8001]

3.1.7 user-to-network interface (UNI): [ITU-T G.8001]

3.2 Terms defined in this Recommendation

None.

~~**3.1.1 customer edge (CE)** [IETF RFC 5921]: The client function that sources or sinks native service traffic to or from the MPLS-TP network. CEs on either side of the MPLS-TP network are peers and view the MPLS-TP network as a single link.~~

~~**3.1.2 MPLS-TP characteristic information (MPLS-TP_CI) traffic unit** [ITU-T G.8101]: An instance of characteristic information and a unit of usage, which consists of an MPLS-TP_AI traffic unit or of a MPLS-TP OAM traffic unit, extended with an MPLS-TP_CI header containing the time-to-live (TTL) field of the MPLS shim header.~~

~~NOTE – See more details in [ITU-T G.8110.1].~~

~~**3.1.3 MPLS-TP provider edge LSR (MPLS-TP PE)**: See clauses 1.3.5 and 1.3.5.2 of [IETF RFC 5921].~~

~~**3.1.4 network-to-network interface (NNI)** [ITU-T G.8001]: An interface that is used for the interconnection of networks elements within a transport network.~~

~~**3.2 Terms defined in this Recommendation**~~

~~This Recommendation defines the following terms:~~

~~**3.2.1 multi-protocol label switching transport profile network-to-network interface (MPLS-TP NNI)**: An NNI for the transfer of a MPLS-TP characteristic information (MPLS-TP_CI) traffic unit over a transport layer network referred to in this Recommendation.~~

Documents
Document Sharing Hub
Copyright International Telecommunication Union/ITU Telcommunication Sector
Provided by IHS Markit under license with ITU-T
No reproduction or networking permitted without license from IHS
Licensee=/, User=,
Not for Resale,
Full document details: ITU-T G.8112 AMD 1 2017