

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

G.989.1

Amendment 1

(08/2015)

SERIES G: TRANSMISSION SYSTEMS AND MEDIA,
DIGITAL SYSTEMS AND NETWORKS

Digital sections and digital line system – Optical line
systems for local and access networks

40-Gigabit-capable passive optical networks
(NG-PON2): General requirements

Amendment 1

Recommendation ITU-T G.989.1 (2013) –
Amendment 1

ITU-T

ITU-T G-SERIES RECOMMENDATIONS

TRANSMISSION SYSTEMS AND MEDIA, DIGITAL SYSTEMS AND NETWORKS

INTERNATIONAL TELEPHONE CONNECTIONS AND CIRCUITS	G.100–G.199
GENERAL CHARACTERISTICS COMMON TO ALL ANALOGUE CARRIER-TRANSMISSION SYSTEMS	G.200–G.299
INDIVIDUAL CHARACTERISTICS OF INTERNATIONAL CARRIER TELEPHONE SYSTEMS ON METALLIC LINES	G.300–G.399
GENERAL CHARACTERISTICS OF INTERNATIONAL CARRIER TELEPHONE SYSTEMS ON RADIO-RELAY OR SATELLITE LINKS AND INTERCONNECTION WITH METALLIC LINES	G.400–G.449
COORDINATION OF RADIOTELEPHONY AND LINE TELEPHONY	G.450–G.499
TRANSMISSION MEDIA AND OPTICAL SYSTEMS CHARACTERISTICS	G.600–G.699
DIGITAL TERMINAL EQUIPMENTS	G.700–G.799
DIGITAL NETWORKS	G.800–G.899
DIGITAL SECTIONS AND DIGITAL LINE SYSTEM	G.900–G.999
General	G.900–G.909
Parameters for optical fibre cable systems	G.910–G.919
Digital sections at hierarchical bit rates based on a bit rate of 2048 kbit/s	G.920–G.929
Digital line transmission systems on cable at non-hierarchical bit rates	G.930–G.939
Digital line systems provided by FDM transmission bearers	G.940–G.949
Digital line systems	G.950–G.959
Digital section and digital transmission systems for customer access to ISDN	G.960–G.969
Optical fibre submarine cable systems	G.970–G.979
Optical line systems for local and access networks	G.980–G.989
Metallic access networks	G.990–G.999
MULTIMEDIA QUALITY OF SERVICE AND PERFORMANCE – GENERIC AND USER-RELATED ASPECTS	G.1000–G.1999
TRANSMISSION MEDIA CHARACTERISTICS	G.6000–G.6999
DATA OVER TRANSPORT – GENERIC ASPECTS	G.7000–G.7999
PACKET OVER TRANSPORT ASPECTS	G.8000–G.8999
ACCESS NETWORKS	G.9000–G.9999

For further details, please refer to the list of ITU-T Recommendations.



Recommendation ITU-T G.989.1

40-Gigabit-capable passive optical networks (NG-PON2): General requirements

Amendment 1

Summary

Amendment 1 to Recommendation ITU-T G.989.1 (2013) provides additional information on protection and/or restoration in NG-PON2 networks using flexible wavelength scheduling, which is not covered in clause 9.4, as well as other new requirements of the ITU-T G.989-series systems not captured in ITU-T G.989.1 (2013).

Requirements identified for inclusion in this amendment are:

- Network protection in the case of a multi-wavelength access system. In particular, the possibility of ODN topologies that appear to be type B (shared splitter), but that provide additional capabilities. Also, the potential for 1:n protection in addition to the 1:1 protection previously described.
- Transport of wireless fronthaul links over the access system. Such links have exceptional service requirements and these are evolving as the application develops in the industry.

History

Edition	Recommendation	Approval	Study Group	Unique ID*
1.0	ITU-T G.989.1	2013-03-09	15	11.1002/1000/11810
1.1	ITU-T G.989.1 (2013) Amd. 1	2015-08-13	15	11.1002/1000/12557

* To access the Recommendation, type the URL <http://handle.itu.int/> in the address field of your web browser, followed by the Recommendation's unique ID. For example, <http://handle.itu.int/11.1002/1000/11830-en>.

FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications, information and communication technologies (ICTs). The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure, e.g., interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementers are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database at <http://www.itu.int/ITU-T/ipr/>.

© ITU 2016

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

Table of Contents

	Page
1) Clause 2, References.....	1
2) Clause 3, Definitions	1
3) Clause 4, Abbreviations and acronyms	1
4) Clause 7.6, High data rate services	1
5) Clause 9.4, Resilience and redundancy requirements	1
6) Clause 9.6, Power reduction	9
7) Clause 9.12, Transport of wireless fronthaul links over the access system.....	11
8) Appendix I, OLT resilience configuration.....	12
9) Appendix II, Transmission technique for mobile fronthaul	13
10) Bibliography	13

.....

Recommendation ITU-T G.989.1

40-Gigabit-capable passive optical networks (NG-PON2): General requirements

Amendment 1

1) Clause 2, References

Add the following new reference to clause 2:

[ITU-T G.989] Recommendation ITU-T G.989 (2015), *40-Gigabit-capable passive optical network (NG-PON2): Definitions, abbreviations and acronyms.*

2) Clause 3, Definitions

Replace clause 3 with the following text:

See [ITU-T G.989] for the definitions used in this Recommendation.

3) Clause 4, Abbreviations and acronyms

Replace clause 4 with the following text:

See [ITU-T G.989] for the abbreviations and acronyms used in this Recommendation.

4) Clause 7.6, High data rate services

Add new clause 7.6 with the following text:

7.6 High data rate services

To accommodate the prospective increase in customer bandwidth demand, NG-PON2 systems may support an optional extension for services in excess of 10 Gbit/s upstream and/or downstream towards one PON client.

5) Clause 9.4, Resilience and redundancy requirements

Replace clause 9.4 with the following text:

9.4 Resilience and redundancy requirements

PON resilience will become more important in supporting business applications and high value consumer applications, such as IPTV, especially in the node consolidation scenario. Node consolidation/bypass creates a high number of subscriber lines on the highly centralized access node. A redundancy mechanism is required to avoid service disruption to potentially thousands of users in the event of fibre cable or equipment failure. Besides the usual hardware redundancy requirements at the OLT and in the backhaul transmission equipment (towards the metro/core), networks require feeder and/or OTL line redundancy options to avoid large scale customer outages as well as full redundancy for business services requiring end-to-end type C protection. NG-PON2 systems must support the resilience options defined in clause 14 of [ITU-T G.984.1] including duplex and dual parenting duplex system configuration as well as the extensions described in Appendices II and III of [ITU-T G.984.1]. For PON redundancy, use cases and guidelines are defined in [b-ITU-T G-Sup.51].