

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

H.248.81

Amendment 2
(04/2015)

SERIES H: AUDIOVISUAL AND MULTIMEDIA SYSTEMS
Infrastructure of audiovisual services – Communication
procedures

Gateway control protocol: Guidelines on the use of
the international emergency preference scheme
(IEPS) call indicator and priority indicator in ITU-T
H.248 profiles

Amendment 2: DiffServ signalling approach

Recommendation ITU-T H.248.81 (2011) –
Amendment 2

ITU-T H-SERIES RECOMMENDATIONS
AUDIOVISUAL AND MULTIMEDIA SYSTEMS

CHARACTERISTICS OF VISUAL TELEPHONE SYSTEMS	H.100–H.199
INFRASTRUCTURE OF AUDIOVISUAL SERVICES	
General	H.200–H.219
Transmission multiplexing and synchronization	H.220–H.229
Systems aspects	H.230–H.239
Communication procedures	H.240–H.259
Coding of moving video	H.260–H.279
Related systems aspects	H.280–H.299
Systems and terminal equipment for audiovisual services	H.300–H.349
Directory services architecture for audiovisual and multimedia services	H.350–H.359
Quality of service architecture for audiovisual and multimedia services	H.360–H.369
Telepresence	H.420–H.429
Supplementary services for multimedia	H.450–H.499
MOBILITY AND COLLABORATION PROCEDURES	
Overview of Mobility and Collaboration, definitions, protocols and procedures	H.500–H.509
Mobility for H-Series multimedia systems and services	H.510–H.519
Mobile multimedia collaboration applications and services	H.520–H.529
Security for mobile multimedia systems and services	H.530–H.539
Security for mobile multimedia collaboration applications and services	H.540–H.549
Mobility interworking procedures	H.550–H.559
Mobile multimedia collaboration inter-working procedures	H.560–H.569
BROADBAND, TRIPLE-PLAY AND ADVANCED MULTIMEDIA SERVICES	
Broadband multimedia services over VDSL	H.610–H.619
Advanced multimedia services and applications	H.620–H.629
Ubiquitous sensor network applications and Internet of Things	H.640–H.649
IPTV MULTIMEDIA SERVICES AND APPLICATIONS FOR IPTV	
General aspects	H.700–H.719
IPTV terminal devices	H.720–H.729
IPTV middleware	H.730–H.739
IPTV application event handling	H.740–H.749
IPTV metadata	H.750–H.759
IPTV multimedia application frameworks	H.760–H.769
IPTV service discovery up to consumption	H.770–H.779
Digital Signage	H.780–H.789
E-HEALTH MULTIMEDIA SERVICES AND APPLICATIONS	
Interoperability compliance testing of personal health systems (HRN, PAN, LAN, TAN and WAN)	H.820–H.859
Multimedia e-health data exchange services	H.860–H.869

For further details, please refer to the list of ITU-T Recommendations.

Recommendation ITU-T H.248.81

Gateway control protocol: Guidelines on the use of the international emergency preference scheme (IEPS) call indicator and priority indicator in ITU-T H.248 profiles

Amendment 2

DiffServ signalling approach

Summary

Recommendation ITU-T H.248.81 provides guidelines on the use of the international emergency preference scheme (IEPS) call indicator and priority indicator in ITU-T H.248 profiles for ITU-T H.323 and NGN systems. These guidelines may be used by other standards development organizations (SDOs) when defining their profiles in support of priority services, e.g., the emergency telecommunications service (ETS) and the multimedia priority service (MPS).

Amendment 1 to Recommendation ITU-T H.248.81 (2011/05) introduces additions and corrections to the Recommendation and adds Appendix II, "Use of ECN in the context of ETS traffic".

Amendment 2 to Recommendation ITU-T H.248.81 (2011/05) includes additions to the Recommendation in support of marking priority calls using the DiffServ signalling package as defined in Recommendation ITU-T H.248.52.

History

Edition	Recommendation	Approval	Study Group	Unique ID*
1.0	ITU-T H.248.81	2011-05-14	16	11.1002/1000/11292
1.1	ITU-T H.248.81 (2011) Amd. 1	2013-03-16	16	11.1002/1000/11862
1.2	ITU-T H.248.81 (2011) Amd. 2	2015-04-29	16	11.1002/1000/12454

* To access the Recommendation, type the URL <http://handle.itu.int/> in the address field of your web browser, followed by the Recommendation's unique ID. For example, <http://handle.itu.int/11.1002/1000/11830-en>.

FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications, information and communication technologies (ICTs). The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure, e.g., interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementers are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database at <http://www.itu.int/ITU-T/ipr/>.

© ITU 2015

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

Table of Contents

		Page
1	Scope.....	1
2	References.....	2
3	Definitions	3
3.1	Terms defined elsewhere	3
3.2	Terms defined in this Recommendation.....	3
4	Abbreviations and acronyms	3
5	Conventions	4
6	Relation to other ITU-T Recommendations	4
6.1	Recommendation ITU-T E.106: International emergency preference scheme for disaster relief operations	4
6.2	Recommendation ITU-T Q.1950 Annex F: Call bearer control – Emergency call indication	4
6.3	Recommendation ITU-T Q.1950 Annex G: Call bearer control – International emergency preference scheme	4
6.4	ITU-T H-series Recommendations – Supplement 12: Gateway control protocol: Priority traffic treatment by ITU-T H.248 gateways	4
7	Functional requirements	4
8	ITU-T H.248 profile specification guidelines	5
8.1	Profile identification.....	5
8.2	Summary.....	5
8.3	Gateway control protocol version	5
8.4	Connection Model	6
8.5	Context Attributes	6
8.6	Terminations.....	6
8.7	Descriptors.....	6
8.8	Command API.....	7
8.9	Generic command syntax and encoding.....	8
8.10	Transactions.....	9
8.11	Messages.....	9
8.12	Transport.....	9
8.13	Security	9
8.14	Packages	9
8.15	Mandatory support of SDP and ITU-T H.248.1 Annex C information elements.....	9
8.16	Optional support of SDP and ITU-T H.248.1 Annex C information elements.....	10
8.17	Procedures	10

	Page
9 Explicit congestion notification (ECN) and ETS	11
Appendix I – Overall example traffic model for decomposed gateways.....	12
I.1 Overview	12
I.2 Traffic processing stages – Model subcomponents.....	14
Appendix II – Use of ECN in the context of ETS traffic.....	16
II.1 Introduction	16
II.2 Use case examples.....	17
II.3 Observations	19
Bibliography.....	21

Recommendation ITU-T H.248.81

Gateway control protocol: Guidelines on the use of the international emergency preference scheme (IEPS) call indicator and priority indicator in ITU-T H.248 profiles

Amendment 2

DiffServ signalling approach

1 Scope

[ITU-T H.248.1] defines the international emergency preference scheme (IEPS) call indicator and priority indicator in support of priority services, e.g., the emergency telecommunications service (ETS) and the multimedia priority service (MPS). Use of the IEPS call indicator and priority indicator, as defined in [ITU-T H.248.1], satisfies the ETS requirements of indicating an ETS context and carrying the priority level.

Any prioritization of ITU-T H.248 procedures in the media gateway controller (MGC) and the transport of ITU-T H.248 control signalling towards the media gateway (MG) is based on the identification of ETS.

The IEPS call indicator, identifying an ETS call/session, indicates to the MG that the context is an ETS context and enables prioritization of ITU-T H.248 control signalling once received. In addition, it enables prioritized resource allocation in the MG for an ETS context.

The priority indicator, carrying the priority level, provides the MG with a means to distinguish different priority handling of resources on the MG when ETS is used.

This Recommendation provides guidelines on the use of the IEPS call indicator and priority indicator in ITU-T H.248 profiles for [ITU-T H.323] and NGN systems. These guidelines may be used by other standards development organizations (SDOs) when defining their ITU-T H.248.1 profiles in support of priority services (e.g., ETS and the MPS). Further details on how these guidelines are used by other networks are outside the scope of this Recommendation. It is up to other SDOs to decide their use when defining their profiles.

ETS and IEPS are defined in [ITU-T E.107] and [ITU-T E.106], respectively. ETS and IEPS involve authority-to-authority communication. The emergency indicator, as defined in [ITU-T H.248.1], is used for identification of emergency calls (i.e., individual-to-authority communication). The IEPS call indicator is used for the identification of a priority call/session (e.g., ETS call/session, IEPS call/session), allowing differentiation from an emergency call/session. The specification of profile procedures for the emergency indicator is outside the scope of this Recommendation.

National regulators may implement ETS in various ways. This Recommendation describes an implementation where the IEPS call indicator and priority indicator are supported. In addition, it describes the DiffServ signalling [ITU-T H.248.52] approach for marking ETS calls/sessions.

NOTE 1 – National, regional or local emergency and public safety services, where an individual from the general public is seeking assistance (i.e., individual-to-authority communication), are outside the scope of this Recommendation.

NOTE 2 – [b-ITU-T Q-Sup.53] provides the signalling requirements to support the IEPS. It is also applicable for ITU-T H.248 entities, but does not indicate any requirement in addition to clause 7.

NOTE 3 – [b-ITU-T Q-Sup.57] provides the signalling requirements to support the ETS in IP networks. It is also applicable for ITU-T H.248 entities, but does not indicate any requirement in addition to clause 7.

2 References

The following ITU-T Recommendations and other references contain provisions which, through reference in this text, constitute provisions of this Recommendation. At the time of publication, the editions indicated were valid. All Recommendations and other references are subject to revision; users of this Recommendation are therefore encouraged to investigate the possibility of applying the most recent edition of the Recommendations and other references listed below. A list of the currently valid ITU-T Recommendations is regularly published. The reference to a document within this Recommendation does not give it, as a stand-alone document, the status of a Recommendation.

- [ITU-T E.106] Recommendation ITU-T E.106 (2003), *International Emergency Preference Scheme (IEPS) for disaster relief operations*.
- [ITU-T E.107] Recommendation ITU-T E.107 (2007), *Emergency Telecommunications Service (ETS) and interconnection framework for national implementations of ETS*.
- [ITU-T H.225.0] Recommendation ITU-T H.225.0 (2009), *Call signalling protocols and media stream packetization for packet-based multimedia communication systems*.
- [ITU-T H.248.1] Recommendation ITU-T H.248.1 (2013), *Gateway control protocol: Version 3, including its Amendment 2* (2009).
- [ITU-T H.248.4] Recommendation ITU-T H.248.4 (2009), *Gateway control protocol: Transport over Stream Control Transmission Protocol (SCTP)*.
- [ITU-T H.248.10] Recommendation ITU-T H.248.10 (2001), *Gateway control protocol: Media gateway resource congestion handling package*.
- [ITU-T H.248.11] Recommendation ITU-T H.248.11 (2013), *Gateway control protocol: Media gateway overload control package*.
- [ITU-T H.248.32] Recommendation ITU-T H.248.32 (2013), *Gateway control protocol: Detailed congestion reporting package*.
- [ITU-T H.248.52] Recommendation ITU-T H.248.52 (2008), *Gateway control protocol: QoS support packages*.
- [ITU-T H.248.54] Recommendation ITU-T H.248.54 (2007), *Gateway control protocol: MPLS support package*.
- [ITU-T H.248.56] Recommendation ITU-T H.248.56 (2007), *Gateway control protocol: Packages for virtual private network support*.
- [ITU-T H.248.63] Recommendation ITU-T H.248.63 (2009), *Gateway control protocol: Resource management packages*.
- [ITU-T H.248.82] Recommendation ITU-T H.248.82 (2013), *Gateway control protocol: Explicit congestion notification support*.
- [ITU-T H.323] Recommendation ITU-T H.323 (2009), *Packet-based multimedia communications systems*.
- [ITU-T Q.1950] Recommendation ITU-T Q.1950 (2002), *Bearer independent call bearer control protocol*.
- [ITU-T Q.1950 Amd.1] Recommendation ITU-T Q.1950 (2002) Amendment 1 (2006), *New Annex G – Call bearer control – International Emergency Preference Scheme*.

3 Definitions

3.1 Terms defined elsewhere

This Recommendation uses the following term defined elsewhere:

3.1.1 emergency telecommunications service (ETS) [ITU-T E.107]: A national service providing priority telecommunications to the ETS authorized users in times of disaster and emergencies.

3.2 Terms defined in this Recommendation

This Recommendation defines the following term:

3.2.1 subject to profile specification: When used, this term indicates that the ITU-T H.248 profile template section requires further specification by a profile specification.

4 Abbreviations and acronyms

This Recommendation uses the following abbreviations:

AQM	Active Queue Management
DSCP	DiffServ Code Point
ECN	Explicit Congestion Notification
ETS	Emergency Telecommunications Service
GoS	Grade of Service
IEPS	International Emergency Preference Scheme
IP	Internet Protocol
IPDV	IP Packet Delay Variation
IPLR	IP Packet Loss Rate
ISUP	ISDN User Part
LSP	Label Switched Path
LTE	Long Term Evolution
Lx	Layer number
MG	Media Gateway
MGC	Media Gateway Controller
MLPP	Multi-Level Precedence and Pre-emption
MPLS	Multi-Protocol Label Switching
MPS	Multimedia Priority Service
N/A	Not Applicable
NGN	Next Generation Network
PHB	Per-Hop Behaviour
QoE	Quality of Experience
QoS	Quality of Service
RPH	Resource Priority Header