



INTERNATIONAL TELECOMMUNICATION UNION

# ITU-T

TELECOMMUNICATION  
STANDARDIZATION SECTOR  
OF ITU

# I.525

(08/96)

SERIES I: INTEGRATED SERVICES DIGITAL  
NETWORK

Internetwork interfaces

---

**Interworking between networks operating at bit  
rates less than 64 kbit/s with 64 kbit/s-based  
ISDN and B-ISDN**

ITU-T Recommendation I.525

(Previously CCITT Recommendation)

ITU-T I-SERIES RECOMMENDATIONS  
INTEGRATED SERVICES DIGITAL NETWORK

|                                                                         |                    |
|-------------------------------------------------------------------------|--------------------|
| <b>GENERAL STRUCTURE</b>                                                | <b>I.100–I.199</b> |
| Terminology                                                             | I.110–I.119        |
| Description of ISDNs                                                    | I.120–I.129        |
| General modelling methods                                               | I.130–I.139        |
| Telecommunication network and service attributes                        | I.140–I.149        |
| General description of asynchronous transfer mode                       | I.150–I.199        |
| <b>SERVICE CAPABILITIES</b>                                             | <b>I.200–I.299</b> |
| Scope                                                                   | I.200–I.209        |
| General aspects of services in ISDN                                     | I.210–I.219        |
| Common aspects of services in the ISDN                                  | I.220–I.229        |
| Bearer services supported by an ISDN                                    | I.230–I.239        |
| Teleservices supported by an ISDN                                       | I.240–I.249        |
| Supplementary services in ISDN                                          | I.250–I.299        |
| <b>OVERALL NETWORK ASPECTS AND FUNCTIONS</b>                            | <b>I.300–I.399</b> |
| Network functional principles                                           | I.310–I.319        |
| Reference models                                                        | I.320–I.329        |
| Numbering, addressing and routing                                       | I.330–I.339        |
| Connection types                                                        | I.340–I.349        |
| Performance objectives                                                  | I.350–I.359        |
| Protocol layer requirements                                             | I.360–I.369        |
| General network requirements and functions                              | I.370–I.399        |
| <b>ISDN USER-NETWORK INTERFACES</b>                                     | <b>I.400–I.499</b> |
| Application of I-series Recommendations to ISDN user-network interfaces | I.420–I.429        |
| Layer 1 Recommendations                                                 | I.430–I.439        |
| Layer 2 Recommendations                                                 | I.440–I.449        |
| Layer 3 Recommendations                                                 | I.450–I.459        |
| Multiplexing, rate adaption and support of existing interfaces          | I.460–I.469        |
| Aspects of ISDN affecting terminal requirements                         | I.470–I.499        |
| <b>INTERNETWORK INTERFACES</b>                                          | <b>I.500–I.599</b> |
| <b>MAINTENANCE PRINCIPLES</b>                                           | <b>I.600–I.699</b> |
| <b>B-ISDN EQUIPMENT ASPECTS</b>                                         | <b>I.700–I.799</b> |
| ATM equipment                                                           | I.730–I.749        |
| Management of ATM equipment                                             | I.750–I.799        |

*For further details, please refer to ITU-T List of Recommendations.*

## **ITU-T RECOMMENDATION I.525**

### **INTERWORKING BETWEEN NETWORKS OPERATING AT BIT RATES LESS THAN 64 kbit/s WITH 64 kbit/s-BASED ISDN AND B-ISDN**

#### **Source**

ITU-T Recommendation I.525 was revised by ITU-T Study Group 13 (1993-1996) and was approved under the WTSC Resolution No. 1 procedure on the 27th of August 1996.

## FOREWORD

ITU (International Telecommunication Union) is the United Nations Specialized Agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of the ITU. The ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Conference (WTSC), which meets every four years, establishes the topics for study by the ITU-T Study Groups which, in their turn, produce Recommendations on these topics.

The approval of Recommendations by the Members of the ITU-T is covered by the procedure laid down in WTSC Resolution No. 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

## NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

## INTELLECTUAL PROPERTY RIGHTS

The ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. The ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, the ITU had/had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementors are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database.

© ITU 1997

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the ITU.

## CONTENTS

|                                                                                                                             | Page |
|-----------------------------------------------------------------------------------------------------------------------------|------|
| 1 General.....                                                                                                              | 1    |
| 2 Scope .....                                                                                                               | 1    |
| 3 Principles .....                                                                                                          | 1    |
| 4 Interworking configurations .....                                                                                         | 1    |
| 4.1 General interworking configuration .....                                                                                | 1    |
| 4.2 Interworking configurations between ISDN and access networks operating at bit rates of less than 64 kbit/s .....        | 2    |
| 5 Examples of applications.....                                                                                             | 3    |
| 6 Interworking between B-ISDN and networks operating at bit rates of less than 64 kbit/s .....                              | 3    |
| 6.1 Interworking principles.....                                                                                            | 3    |
| 6.2 Interworking configurations .....                                                                                       | 3    |
| 6.2.1 Indirect interworking scenario.....                                                                                   | 3    |
| 6.2.2 Direct interworking scenario .....                                                                                    | 4    |
| Annex A – Network interworking between an ISDN and an integrated digital network at a basic rate of 32 kbit/s (IDN-32)..... | 4    |
| A.1 General.....                                                                                                            | 4    |
| A.2 Scope .....                                                                                                             | 4    |
| A.3 Interworking configuration and network characteristics .....                                                            | 4    |
| A.3.1 Interworking configuration.....                                                                                       | 4    |
| A.3.2 Key IDN-32 and ISDN characteristics and related interworking functions..                                              | 5    |
| A.3.3 Services suitable for IDN-32-ISDN interworking.....                                                                   | 5    |
| A.3.4 Connection types suitable for IDN-32-ISDN interworking .....                                                          | 6    |
| A.3.5 Functional requirements for IDN-32-ISDN interworking.....                                                             | 7    |
| A.3.6 Handling of non-voice calls between IDN-32 and ISDN subscribers.....                                                  | 8    |
| Appendix A.1 – Integrated digital network at a basic rate of 32 kbit/s (IDN-32) .....                                       | 8    |
| A.I.1 General .....                                                                                                         | 8    |
| A.I.2 Scope .....                                                                                                           | 8    |
| A.I.3 Principles.....                                                                                                       | 8    |
| A.I.4 Access configuration .....                                                                                            | 9    |
| Annex B – Network interworking between an ISDN and a Digital Public Land Mobile Network (D-PLMN) .....                      | 9    |
| B.1 General.....                                                                                                            | 9    |
| B.2 Scope .....                                                                                                             | 9    |

|                                                                                       | Page |
|---------------------------------------------------------------------------------------|------|
| B.3 Interworking configuration and network characteristics .....                      | 9    |
| B.3.1 Interworking configuration.....                                                 | 9    |
| B.3.2 Key D-PLMN and ISDN characteristics and related<br>interworking functions ..... | 9    |
| B.3.3 Services suitable for D-PLMN-ISDN interworking.....                             | 10   |
| B.3.4 Functional requirements for D-PLMN-ISDN interworking.....                       | 10   |
| Appendix B.I – D-PLMN .....                                                           | 12   |
| B.I.1 General .....                                                                   | 12   |
| B.I.2 Scope .....                                                                     | 12   |
| B.I.3 Principles.....                                                                 | 12   |