

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

Q.1912.5 F

(03/2011)

SERIES Q: SWITCHING AND SIGNALLING

Specifications of signalling related to Bearer Independent
Call Control (BICC)

**Interworking between session initiation protocol
(SIP) and bearer independent call control
protocol (BICC) or ISDN user part (ISUP):
Abstract test suite (ATS) and partial protocol
implementation extra information for testing
(PIXIT) for profile C**

Recommendation ITU-T Q.1912.5 F



International
Telecommunication
Union
Documents

Document Sharing Hub

ITU-T Q-SERIES RECOMMENDATIONS
SWITCHING AND SIGNALLING

SIGNALLING IN THE INTERNATIONAL MANUAL SERVICE	Q.1–Q.3
INTERNATIONAL AUTOMATIC AND SEMI-AUTOMATIC WORKING	Q.4–Q.59
FUNCTIONS AND INFORMATION FLOWS FOR SERVICES IN THE ISDN	Q.60–Q.99
CLAUSES APPLICABLE TO ITU-T STANDARD SYSTEMS	Q.100–Q.119
SPECIFICATIONS OF SIGNALLING SYSTEMS No. 4, 5, 6, R1 AND R2	Q.120–Q.499
DIGITAL EXCHANGES	Q.500–Q.599
INTERWORKING OF SIGNALLING SYSTEMS	Q.600–Q.699
SPECIFICATIONS OF SIGNALLING SYSTEM No. 7	Q.700–Q.799
Q3 INTERFACE	Q.800–Q.849
DIGITAL SUBSCRIBER SIGNALLING SYSTEM No. 1	Q.850–Q.999
PUBLIC LAND MOBILE NETWORK	Q.1000–Q.1099
INTERWORKING WITH SATELLITE MOBILE SYSTEMS	Q.1100–Q.1199
INTELLIGENT NETWORK	Q.1200–Q.1699
SIGNALLING REQUIREMENTS AND PROTOCOLS FOR IMT-2000	Q.1700–Q.1799
SPECIFICATIONS OF SIGNALLING RELATED TO BEARER INDEPENDENT CALL CONTROL (BICC)	Q.1900–Q.1999
BROADBAND ISDN	Q.2000–Q.2999
SIGNALLING REQUIREMENTS AND PROTOCOLS FOR THE NGN	Q.3000–Q.3999

For further details, please refer to the list of ITU-T Recommendations.



Recommendation ITU-T Q.1912.5 F

Interworking between session initiation protocol (SIP) and bearer independent call control protocol (BICC) or ISDN user part (ISUP): Abstract test suite (ATS) and partial protocol implementation extra information for testing (PIXIT) for profile C

Summary

Recommendation ITU-T Q.1912.5 F specifies the abstract test suite (ATS) and partial protocol implementation extra information for testing (PIXIT) for the interworking between session initiation protocol (SIP) and bearer independent call control protocol or ISDN user part for the profile C described in Recommendation ITU-T Q.1912.5.

History

Edition	Recommendation	Approval	Study Group
1.0	ITU-T Q.1912.5 F	2011-03-16	11