



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

Q.2762

(12/1999)

SERIES Q: SWITCHING AND SIGNALLING

**Broadband ISDN – B-ISDN application protocols for the
network signalling**

General functions of messages and signals of the B-ISDN user part (B-ISUP) of Signalling System No. 7

ITU-T Recommendation Q.2762

(Formerly CCITT Recommendation)

ITU-T Q-SERIES RECOMMENDATIONS
SWITCHING AND SIGNALLING

SIGNALLING IN THE INTERNATIONAL MANUAL SERVICE	Q.1–Q.3
INTERNATIONAL AUTOMATIC AND SEMI-AUTOMATIC WORKING	Q.4–Q.59
FUNCTIONS AND INFORMATION FLOWS FOR SERVICES IN THE ISDN	Q.60–Q.99
CLAUSES APPLICABLE TO ITU-T STANDARD SYSTEMS	Q.100–Q.119
SPECIFICATIONS OF SIGNALLING SYSTEMS No. 4 AND No. 5	Q.120–Q.249
SPECIFICATIONS OF SIGNALLING SYSTEM No. 6	Q.250–Q.309
SPECIFICATIONS OF SIGNALLING SYSTEM R1	Q.310–Q.399
SPECIFICATIONS OF SIGNALLING SYSTEM R2	Q.400–Q.499
DIGITAL EXCHANGES	Q.500–Q.599
INTERWORKING OF SIGNALLING SYSTEMS	Q.600–Q.699
SPECIFICATIONS OF SIGNALLING SYSTEM No. 7	Q.700–Q.849
DIGITAL SUBSCRIBER SIGNALLING SYSTEM No. 1	Q.850–Q.999
PUBLIC LAND MOBILE NETWORK	Q.1000–Q.1099
INTERWORKING WITH SATELLITE MOBILE SYSTEMS	Q.1100–Q.1199
INTELLIGENT NETWORK	Q.1200–Q.1699
SIGNALLING REQUIREMENTS AND PROTOCOLS FOR IMT-2000	Q.1700–Q.1799
BROADBAND ISDN	Q.2000–Q.2999
General aspects	Q.2000–Q.2099
Signalling ATM adaptation layer (SAAL)	Q.2100–Q.2199
Signalling network protocols	Q.2200–Q.2299
Common aspects of B-ISDN application protocols for access signalling and network signalling and interworking	Q.2600–Q.2699
B-ISDN application protocols for the network signalling	Q.2700–Q.2899
B-ISDN application protocols for access signalling	Q.2900–Q.2999

For further details, please refer to the list of ITU-T Recommendations.

ITU-T RECOMMENDATION Q.2762

GENERAL FUNCTIONS OF MESSAGES AND SIGNALS OF THE B-ISDN USER PART (B-ISUP) OF SIGNALLING SYSTEM No. 7

Summary

This Recommendation is one of a set of Recommendations that describe the Broadband ISDN User Part. It describes the elements of signalling information and their function used by the B-ISDN User Part protocol to support basic bearer services and supplementary services for Capability Set 1 B-ISDN applications.

Source

ITU-T Recommendation Q.2762 was revised by ITU-T Study Group 11 (1997-2000) and was approved under the WTSC Resolution No. 1 procedure on 3 December 1999.

FOREWORD

ITU (International Telecommunication Union) is the United Nations Specialized Agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of the ITU. The ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Conference (WTSC), which meets every four years, establishes the topics for study by the ITU-T Study Groups which, in their turn, produce Recommendations on these topics.

The approval of Recommendations by the Members of the ITU-T is covered by the procedure laid down in WTSC Resolution No. 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

INTELLECTUAL PROPERTY RIGHTS

The ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. The ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, the ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementors are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database.

© ITU 2001

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the ITU.

CONTENTS

	Page
1 Scope.....	1
2 References.....	1
3 Relationships to other Recommendations.....	1
4 Abbreviations.....	1
5 Signalling messages	3
5.1 Address Complete Message (ACM).....	4
5.2 Answer Message (ANM)	4
5.3 Application Transport Message (APM).....	4
5.4 Blocking message (BLO).....	4
5.5 Blocking Acknowledgement message (BLA).....	4
5.6 Call Progress message (CPG).....	4
5.7 Call Transfer Message (CTM).....	5
5.8 Confusion message (CFN).....	5
5.9 Connection Available message (COA).....	5
5.10 Consistency Check End message (CCE)	5
5.11 Consistency Check End Acknowledge message (CCEA)	5
5.12 Consistency Check Request message (CSR)	5
5.13 Consistency Check Request Acknowledge message (CSRA)	5
5.14 Facility message (FAC)	5
5.15 Forward Transfer message (FOT).....	5
5.16 Identification Request message (IDR)	6
5.17 Identification Response message (IRS)	6
5.18 Initial Address Message (IAM).....	6
5.19 IAM Acknowledgement message (IAA).....	6
5.20 IAM Reject message (IAR).....	6
5.21 Loop Prevention message (LOP)	6
5.22 Modify Acknowledge message (MOA)	6
5.23 Modify Reject message (MOR)	6
5.24 Modify Request message (MOD)	6
5.25 Network Resource Management message (NRM).....	6
5.26 Pre-release Information message (PRI)	6
5.27 Release message (REL)	6
5.28 Release Complete message (RLC).....	7
5.29 Reset Message (RSM).....	7



5.30	Reset Acknowledgement Message (RAM).....	7
5.31	Resume message (RES).....	7
5.32	Segmentation Message (SGM) (national use)	7
5.33	Subsequent Address Message (SAM).....	7
5.34	Suspend message (SUS)	7
5.35	Unblocking message (UBL).....	7
5.36	Unblocking Acknowledgement message (UBA).....	7
5.37	User Part Available message (UPA).....	7
5.38	User Part Test message (UPT).....	7
5.39	User-to-User information message (USR).....	7
6	Signalling information	8
6.1	Parameters.....	8
6.1.1	AAL parameters.....	8
6.1.2	AAL Prime parameters	8
6.1.3	Access delivery information	8
6.1.4	Additional calling party number	8
6.1.5	Additional ATM cell rate	8
6.1.6	Additional connected number.....	8
6.1.7	AESA for additional calling party	8
6.1.8	AESA for additional connected party.....	8
6.1.9	AESA for called party.....	8
6.1.10	AESA for calling party	8
6.1.11	AESA for connected party.....	9
6.1.12	Alternative ATM cell rate.....	9
6.1.13	Application generated identifier	9
6.1.14	Application transport Parameter (APP).....	9
6.1.15	ATC setup parameters	9
6.1.16	ATM cell rate.....	9
6.1.17	Automatic congestion level	9
6.1.18	Automatic re-routing	9
6.1.19	Backward GVNS	9
6.1.20	Backward narrow-band interworking indicator	9
6.1.21	Broadband bearer capability	9
6.1.22	Broadband high layer information.....	10
6.1.23	Broadband low layer information	10
6.1.24	Call diversion information.....	10
6.1.25	Call diversion may occur	10
6.1.26	Call diversion treatment indicators.....	10

	Page
6.1.27 Call history information.....	10
6.1.28 Call offering treatment indicators	10
6.1.29 Call transfer number	10
6.1.30 Call transfer reference.....	10
6.1.31 Called IN number	10
6.1.32 Called party number	10
6.1.33 Called party sub-address	10
6.1.34 Called party's indicators.....	10
6.1.35 Calling party number	11
6.1.36 Calling party sub-address.....	11
6.1.37 Calling party's category.....	11
6.1.38 Cause indicator	11
6.1.39 CCSS	11
6.1.40 Cell delay variation tolerance (CDVT).....	11
6.1.41 Charge indicator.....	11
6.1.42 Charged party identification	11
6.1.43 Closed user group information	11
6.1.44 Collect call request	11
6.1.45 Conference treatment indicators	11
6.1.46 Connected line identity request	11
6.1.47 Connected number	11
6.1.48 Connected sub-address	12
6.1.49 Connection element identifier	12
6.1.50 Connection identifier	12
6.1.51 Consistency check result information.....	12
6.1.52 Correlation ID.....	12
6.1.53 Destination connection link identifier	12
6.1.54 Destination signalling identifier	12
6.1.55 Display information	12
6.1.56 Echo control information.....	12
6.1.57 End-to-end transit delay network generated indicator	12
6.1.58 Extended quality of service	12
6.1.59 Exclusive connection element identifier.....	12
6.1.60 Forward GVNS.....	13
6.1.61 Forward narrow-band interworking indicator.....	13
6.1.62 Hop counter	13
6.1.63 In-band information indicator.....	13
6.1.64 Leaf party type	13
6.1.65 Link layer core parameters.....	13
6.1.66 Link layer protocol parameters	13

	Page
6.1.67 Location number	13
6.1.68 Loop prevention indicators	13
6.1.69 MCID request indicator	13
6.1.70 MCID response indicator.....	13
6.1.71 Minimum ATM cell rate.....	13
6.1.72 Maximum end-to-end transit delay.....	14
6.1.73 MLPP Precedence.....	14
6.1.74 MLPP user information	14
6.1.75 Narrow-band bearer capability	14
6.1.76 Narrow-band high layer compatibility.....	14
6.1.77 Narrow-band low layer compatibility.....	14
6.1.78 National/international call indicator	14
6.1.79 Network call correlation identifier.....	14
6.1.80 Network look-ahead indicators.....	14
6.1.81 Network management controls	14
6.1.82 Notification.....	14
6.1.83 OAM traffic descriptor	14
6.1.84 Original called number	15
6.1.85 Origination Connection Link Identifier	15
6.1.86 Origination ISC point code.....	15
6.1.87 Origination signalling identifier	15
6.1.88 Quality of service.....	15
6.1.89 Priority	15
6.1.90 Progress indicator	15
6.1.91 Propagation delay counter	15
6.1.92 Redirecting number	15
6.1.93 Redirection information.....	15
6.1.94 Redirection number	15
6.1.95 Redirection number restriction	15
6.1.96 Remote operations	16
6.1.97 Report type.....	16
6.1.98 Report type prime	16
6.1.99 Resource identifier.....	16
6.1.100 SCF ID	16
6.1.101 Service activation	16
6.1.102 Segmentation indicator (national use)	16
6.1.103 Soft PVC called endpoint	16
6.1.104 Soft PVC calling endpoint.....	16
6.1.105 Subsequent number.....	16
6.1.106 Suspend/Resume indicators.....	16

	Page
6.1.107 Transit network selection (national use).....	17
6.1.108 UID action indicators.....	17
6.1.109 UID capability indicators.....	17
6.1.110 User-to-user indicators.....	17
6.1.111 User-to-user information	17
6.2 Parameter information	17
6.2.1 Access delivery indicator.....	17
6.2.2 Address presentation restricted indicator.....	17
6.2.3 Address signal.....	17
6.2.4 APM segmentation indicator	17
6.2.5 Application context identifier	17
6.2.6 Application transport instruction indicators (ATII).....	17
6.2.7 Binary code	18
6.2.8 Broadband/Narrow-band interworking indicator.....	18
6.2.9 Call diversion may occur indicator	18
6.2.10 Call identifier	18
6.2.11 Call to be diverted indicator	18
6.2.12 Call to be offered indicator	18
6.2.13 Called party's category indicator.....	18
6.2.14 Called party's status indicator	18
6.2.15 Calling party address request indicator.....	18
6.2.16 Calling party number incomplete (national use).....	18
6.2.17 Cause value.....	18
6.2.18 CCSS call indicator	18
6.2.19 Charge indicator.....	18
6.2.20 Cell rate identifier	19
6.2.21 Closed user group call indicator	19
6.2.22 Coding standard.....	19
6.2.23 Component ID tag.....	19
6.2.24 Component type.....	19
6.2.25 Component type tag.....	20
6.2.26 Conference acceptance indicator	20
6.2.27 Connection identifier	20
6.2.28 Control ID.....	20
6.2.29 Diagnostic	20
6.2.30 Discard message indicator	20
6.2.31 Discard parameter indicator.....	20
6.2.32 Encapsulated application information	20
6.2.33 Extension indicator	20
6.2.34 Feature code.....	21



	Page
6.2.35 Filler.....	21
6.2.36 GVNS user group identification	21
6.2.37 Hold provided indicator.....	21
6.2.38 Holding indicator	21
6.2.39 Incoming echo control device request indicator	21
6.2.40 Incoming echo control device indicator.....	21
6.2.41 Instruction indicator.....	21
6.2.42 Internal network number indicator	21
6.2.43 Interworking indicator	21
6.2.44 ISDN access indicator.....	21
6.2.45 ISDN User Part indicator.....	21
6.2.46 ISDN User Part preference indicator	21
6.2.47 Location	22
6.2.48 Look-ahead for busy indicator	22
6.2.49 MLPP service domain.....	22
6.2.50 MLPP user indicator	22
6.2.51 More data indicator.....	22
6.2.52 Nature of address indicator	22
6.2.53 Network discard indicator.....	22
6.2.54 Network identification (national use)	22
6.2.55 Network identification plan (national use)	22
6.2.56 Network identity	22
6.2.57 Notification indicator.....	22
6.2.58 Notification subscription option	22
6.2.59 Numbering plan indicator	22
6.2.60 Odd/even indicator	23
6.2.61 Originating participating service provider identification.....	23
6.2.62 Original redirection reason	23
6.2.63 Outgoing echo control device request indicator	23
6.2.64 Outgoing echo control device indicator.....	23
6.2.65 Party type indicator.....	23
6.2.66 Pass on not possible indicator.....	23
6.2.67 Point code	23
6.2.68 Precedence level	23
6.2.69 Priority	23
6.2.70 Priority level	23
6.2.71 Protocol profile	23
6.2.72 QoS Class	23
6.2.73 Redirecting indicator	23
6.2.74 Redirecting reason	24

	Page
6.2.75 Redirection counter.....	24
6.2.76 Redirection reason	24
6.2.77 Release call indicator.....	24
6.2.78 Repeat indicator	24
6.2.79 Re-routing counter	24
6.2.80 Re-routing indicator.....	24
6.2.81 Resource indicator	24
6.2.82 Resource value.....	24
6.2.83 Routing label.....	24
6.2.84 Screening indicator	24
6.2.85 Send notification indicator.....	24
6.2.86 Segmentation local reference (SLR).....	24
6.2.87 Sequence indicator.....	25
6.2.88 Simple segmentation indicator	25
6.2.89 T9 timer indicator	25
6.2.90 T9 timer instruction indicator	25
6.2.91 Temporary alternative routing indicator	25
6.2.92 Terminating access indicator	25
6.2.93 Terminating network routing number.....	25
6.2.94 Through-connection indicator	25
6.2.95 Through-connection instruction indicator	25
6.2.96 Transit at intermediate exchange indicator.....	25
6.2.97 Type	25
6.2.98 Type of network identification (national use).....	25
6.2.99 Virtual channel identifier.....	25
6.2.100 Virtual path connection identifier.....	26
6.2.101 VPCI check result indicator.....	26

