



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

Q.2931 D

(12/2000)

SERIES Q: SWITCHING AND SIGNALLING

Broadband ISDN – B-ISDN application protocols for
access signalling

**Broadband integrated services digital network
(B-ISDN) – Digital subscriber signalling system
No. 2 (DSS2) – User-network interface (UNI)
Layer 3 specification for basic call/connection
control: Abstract test suite (ATS) and partial
Protocol Implementation eXtra Information for
Testing (PIXIT) proforma for the user**

ITU-T Recommendation Q.2931 D

(Formerly CCITT Recommendation)

ITU-T Q-SERIES RECOMMENDATIONS
SWITCHING AND SIGNALLING

SIGNALLING IN THE INTERNATIONAL MANUAL SERVICE	Q.1–Q.3
INTERNATIONAL AUTOMATIC AND SEMI-AUTOMATIC WORKING	Q.4–Q.59
FUNCTIONS AND INFORMATION FLOWS FOR SERVICES IN THE ISDN	Q.60–Q.99
CLAUSES APPLICABLE TO ITU-T STANDARD SYSTEMS	Q.100–Q.119
SPECIFICATIONS OF SIGNALLING SYSTEMS No. 4 AND No. 5	Q.120–Q.249
SPECIFICATIONS OF SIGNALLING SYSTEM No. 6	Q.250–Q.309
SPECIFICATIONS OF SIGNALLING SYSTEM R1	Q.310–Q.399
SPECIFICATIONS OF SIGNALLING SYSTEM R2	Q.400–Q.499
DIGITAL EXCHANGES	Q.500–Q.599
INTERWORKING OF SIGNALLING SYSTEMS	Q.600–Q.699
SPECIFICATIONS OF SIGNALLING SYSTEM No. 7	Q.700–Q.799
Q3 INTERFACE	Q.800–Q.849
DIGITAL SUBSCRIBER SIGNALLING SYSTEM No. 1	Q.850–Q.999
PUBLIC LAND MOBILE NETWORK	Q.1000–Q.1099
INTERWORKING WITH SATELLITE MOBILE SYSTEMS	Q.1100–Q.1199
INTELLIGENT NETWORK	Q.1200–Q.1699
SIGNALLING REQUIREMENTS AND PROTOCOLS FOR IMT-2000	Q.1700–Q.1799
BROADBAND ISDN	Q.2000–Q.2999
General aspects	Q.2000–Q.2099
Signalling ATM adaptation layer (SAAL)	Q.2100–Q.2199
Signalling network protocols	Q.2200–Q.2299
Common aspects of B-ISDN application protocols for access signalling and network signalling and interworking	Q.2600–Q.2699
B-ISDN application protocols for the network signalling	Q.2700–Q.2899
B-ISDN application protocols for access signalling	Q.2900–Q.2999

For further details, please refer to the list of ITU-T Recommendations.

ITU-T Recommendation Q.2931 D

Broadband integrated services digital network (B-ISDN) – Digital subscriber signalling system No. 2 (DSS2) – User-network interface (UNI) Layer 3 specification for basic call/connection control: Abstract test suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma for the user

Summary

This Recommendation specifies Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma for the user attached to the T_B reference point or coincident S_B and T_B reference point (as defined in ITU-T I.413 [4]) of implementations conforming to the procedures for the support of point-to-point release 1 switched virtual channel connections between the calling party and the called party of the Digital Subscriber Signalling System No. 2 (DSS2) protocol for the Broadband Integrated Services Digital Network (B-ISDN), ITU-T Q.2931 [1].

Other Recommendations of the Q.2931 family specify the Protocol Implementation Conformance Statement (PICS) proforma and Test Suite Structure and Test Purposes (TSS & TP) based on this Recommendation.

NOTE – This Recommendation related to protocol conformance is published only in English; it is based on an external SDO's standard published in English.

Source

ITU-T Recommendation Q.2931 D was prepared by ITU-T Study Group 11 (2001-2004) and approved under the WTSA Resolution 1 procedure on 6 December 2000.