



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

Q.2963.1 F

(12/2000)

SERIES Q: SWITCHING AND SIGNALLING

Broadband ISDN – B-ISDN application protocols for
access signalling

**Digital subscriber signalling system No. 2 –
Connection modification: Peak cell rate
modification by the connection owner: Abstract
test suite (ATS) and partial protocol
implementation extra information for testing
(PIXIT) proforma for the network**

ITU-T Recommendation Q.2963.1 F

(Formerly CCITT Recommendation)

ITU-T Q-SERIES RECOMMENDATIONS
SWITCHING AND SIGNALLING

SIGNALLING IN THE INTERNATIONAL MANUAL SERVICE	Q.1–Q.3
INTERNATIONAL AUTOMATIC AND SEMI-AUTOMATIC WORKING	Q.4–Q.59
FUNCTIONS AND INFORMATION FLOWS FOR SERVICES IN THE ISDN	Q.60–Q.99
CLAUSES APPLICABLE TO ITU-T STANDARD SYSTEMS	Q.100–Q.119
SPECIFICATIONS OF SIGNALLING SYSTEMS No. 4 AND No. 5	Q.120–Q.249
SPECIFICATIONS OF SIGNALLING SYSTEM No. 6	Q.250–Q.309
SPECIFICATIONS OF SIGNALLING SYSTEM R1	Q.310–Q.399
SPECIFICATIONS OF SIGNALLING SYSTEM R2	Q.400–Q.499
DIGITAL EXCHANGES	Q.500–Q.599
INTERWORKING OF SIGNALLING SYSTEMS	Q.600–Q.699
SPECIFICATIONS OF SIGNALLING SYSTEM No. 7	Q.700–Q.799
Q3 INTERFACE	Q.800–Q.849
DIGITAL SUBSCRIBER SIGNALLING SYSTEM No. 1	Q.850–Q.999
PUBLIC LAND MOBILE NETWORK	Q.1000–Q.1099
INTERWORKING WITH SATELLITE MOBILE SYSTEMS	Q.1100–Q.1199
INTELLIGENT NETWORK	Q.1200–Q.1699
SIGNALLING REQUIREMENTS AND PROTOCOLS FOR IMT-2000	Q.1700–Q.1799
BROADBAND ISDN	Q.2000–Q.2999
B-ISDN application protocols for access signalling	Q.2900–Q.2999

For further details, please refer to the list of ITU-T Recommendations.

**Digital subscriber signalling system No. 2 – Connection modification:
Peak cell rate modification by the connection owner:
Abstract test suite (ATS) and partial protocol implementation extra
information for testing (PIXIT) proforma for the network**

Summary

This Recommendation specifies the Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma for the network at the T_B reference point or coincident S_B and T_B reference point (as defined in ITU-T I.413 [6]) of implementations conforming to the procedures for the modification of the peak cell rate traffic parameter by the connection owner in the active phase of the call of the Digital Subscriber Signalling System No. 2 (DSS2) protocol for the Broadband Integrated Services Digital Network (B-ISDN), ITU-T Q.2963.1 [1].

Other Recommendations of the Q.2963.1 family specify the Protocol Implementation Conformance Statement (PICS) proforma and Test Suite Structure and Test Purposes (TSS & TP) based on this Recommendation.

NOTE – This Recommendation related to protocol conformance is published only in English; it is based on an external SDO's standard published in English.

Source

ITU-T Recommendation Q.2963.1 F was prepared by ITU-T Study Group 11 (2001-2004) and approved under the WTSA Resolution 1 procedure on 6 December 2000.