



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

Q.2963.3

(05/98)

SERIES Q: SWITCHING AND SIGNALLING

**Broadband ISDN – B-ISDN application protocols for
access signalling**

**Digital Subscriber Signalling System No. 2 –
Connection modification: ATM traffic descriptor
modification with negotiation by the connection
owner**

ITU-T Recommendation Q.2963.3

(Previously CCITT Recommendation)

ITU-T Q-SERIES RECOMMENDATIONS
SWITCHING AND SIGNALLING

SIGNALLING IN THE INTERNATIONAL MANUAL SERVICE	Q.1–Q.3
INTERNATIONAL AUTOMATIC AND SEMI-AUTOMATIC WORKING	Q.4–Q.59
FUNCTIONS AND INFORMATION FLOWS FOR SERVICES IN THE ISDN	Q.60–Q.99
CLAUSES APPLICABLE TO ITU-T STANDARD SYSTEMS	Q.100–Q.119
SPECIFICATIONS OF SIGNALLING SYSTEMS No. 4 AND No. 5	Q.120–Q.249
SPECIFICATIONS OF SIGNALLING SYSTEM No. 6	Q.250–Q.309
SPECIFICATIONS OF SIGNALLING SYSTEM R1	Q.310–Q.399
SPECIFICATIONS OF SIGNALLING SYSTEM R2	Q.400–Q.499
DIGITAL EXCHANGES	Q.500–Q.599
INTERWORKING OF SIGNALLING SYSTEMS	Q.600–Q.699
SPECIFICATIONS OF SIGNALLING SYSTEM No. 7	Q.700–Q.849
DIGITAL SUBSCRIBER SIGNALLING SYSTEM No. 1	Q.850–Q.999
PUBLIC LAND MOBILE NETWORK	Q.1000–Q.1099
INTERWORKING WITH SATELLITE MOBILE SYSTEMS	Q.1100–Q.1199
INTELLIGENT NETWORK	Q.1200–Q.1999
BROADBAND ISDN	Q.2000–Q.2999
General aspects	Q.2000–Q.2099
Signalling ATM adaptation layer (SAAL)	Q.2100–Q.2199
Signalling network protocols	Q.2200–Q.2299
Common aspects of B-ISDN application protocols for access signalling and network signalling and interworking	Q.2600–Q.2699
B-ISDN application protocols for the network signalling	Q.2700–Q.2899
B-ISDN application protocols for access signalling	Q.2900–Q.2999

For further details, please refer to ITU-T List of Recommendations.

ITU-T RECOMMENDATION Q.2963.3

DIGITAL SUBSCRIBER SIGNALLING SYSTEM No. 2 – CONNECTION MODIFICATION: ATM TRAFFIC DESCRIPTOR MODIFICATION WITH NEGOTIATION BY THE CONNECTION OWNER

Summary

The Q.2963 series of Recommendations belongs to the DSS 2 family of ITU-T Recommendations and specifies the procedure of the modification of traffic parameters of a call/connection in the active state.

Recommendation Q.2963.3 defines the procedure of the ATM Traffic Descriptor modification with negotiation which is equivalent to that specified in Recommendation Q.2962.

Source

ITU-T Recommendation Q.2963.3 was prepared by ITU-T Study Group 11 (1997-2000) and was approved under the WTSC Resolution No. 1 procedure on the 15th of May 1998.

Keywords

MBS, modification, negotiation, PCR, SCR.

FOREWORD

ITU (International Telecommunication Union) is the United Nations Specialized Agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of the ITU. The ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Conference (WTSC), which meets every four years, establishes the topics for study by the ITU-T Study Groups which, in their turn, produce Recommendations on these topics.

The approval of Recommendations by the Members of the ITU-T is covered by the procedure laid down in WTSC Resolution No. 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

INTELLECTUAL PROPERTY RIGHTS

The ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. The ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, the ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementors are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database.

© ITU 1998

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the ITU.

CONTENTS

	Page
1 Scope	1
2 References	1
3 Definitions	2
4 Abbreviations	2
5 Description	2
5.1 Modifiable connections	2
5.2 Modification of a point-to-point connection	3
5.3 Negotiation during modification	3
6 Operational requirements	3
6.1 Provision and withdrawal	3
6.2 Requirements on the originating network side	4
6.3 Requirements on the destination network side	4
7 Primitive and state definitions	4
7.1 Primitive definitions	4
7.2 State definitions	4
8 Coding requirements	4
8.1 Messages.....	4
8.1.1 MODIFY REQUEST	4
8.1.2 MODIFY ACKNOWLEDGEMENT.....	5
8.1.3 MODIFY REJECT.....	5
8.1.4 CONNECTION AVAILABLE.....	5
8.2 Coding of specific message types and specific information element.....	5
8.2.1 Coding of specific message type.....	5
8.2.2 Coding of specific information elements	5
9 Signalling procedures at the coincident S _B and T _B reference point	6
9.1 Modification procedure at the requesting entity	6
9.1.1 Modification request	6
9.1.2 Modification acknowledgment.....	6
9.1.3 Indication of modification rejection.....	6
9.1.4 Response to STATUS messages while in the modify request state.....	6
9.1.5 No response to modification request.....	6

	Page
9.2 Modification procedures at the responding entity	7
9.2.1 Modification indication	7
9.2.2 Modification acceptance	7
9.2.3 Modification confirmation	8
9.2.4 Modification rejection	8
9.3 Transit entity conveyance of CONNECTION AVAILABLE messages	9
10 Procedures at the T _B reference point for interworking with private B-ISDNs	9
11 Interworking with other networks	9
12 Interworking with supplementary services	9
13 Parameter values	9
14 Dynamic description SDLs	9
Appendix I – Example configuration of user and network behaviour during modification procedures	10
Appendix II – Guidelines for the use of the instruction indicator	12