

ITU-T

Y.1416/Q.3150

(06/2007)

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

SERIES Y: GLOBAL INFORMATION
INFRASTRUCTURE, INTERNET PROTOCOL ASPECTS
AND NEXT-GENERATION NETWORKS

Internet protocol aspects – Interworking

SERIES Q: SWITCHING AND SIGNALLING

Signalling requirements and protocols for the NGN –
Bearer control signalling

Use of virtual trunks for ATM/MPLS client/server control plane interworking

ITU-T Recommendation Y.1416/Q.3150

ITU-T

ITU-T Y-SERIES RECOMMENDATIONS

GLOBAL INFORMATION INFRASTRUCTURE, INTERNET PROTOCOL ASPECTS AND NEXT-GENERATION NETWORKS

GLOBAL INFORMATION INFRASTRUCTURE

General	Y.100–Y.199
Services, applications and middleware	Y.200–Y.299
Network aspects	Y.300–Y.399
Interfaces and protocols	Y.400–Y.499
Numbering, addressing and naming	Y.500–Y.599
Operation, administration and maintenance	Y.600–Y.699
Security	Y.700–Y.799
Performances	Y.800–Y.899

INTERNET PROTOCOL ASPECTS

General	Y.1000–Y.1099
Services and applications	Y.1100–Y.1199
Architecture, access, network capabilities and resource management	Y.1200–Y.1299
Transport	Y.1300–Y.1399
Interworking	Y.1400–Y.1499
Quality of service and network performance	Y.1500–Y.1599
Signalling	Y.1600–Y.1699
Operation, administration and maintenance	Y.1700–Y.1799
Charging	Y.1800–Y.1899

NEXT GENERATION NETWORKS

Frameworks and functional architecture models	Y.2000–Y.2099
Quality of Service and performance	Y.2100–Y.2199
Service aspects: Service capabilities and service architecture	Y.2200–Y.2249
Service aspects: Interoperability of services and networks in NGN	Y.2250–Y.2299
Numbering, naming and addressing	Y.2300–Y.2399
Network management	Y.2400–Y.2499
Network control architectures and protocols	Y.2500–Y.2599
Security	Y.2700–Y.2799
Generalized mobility	Y.2800–Y.2899

For further details, please refer to the list of ITU-T Recommendations.

ITU-T Recommendation Y.1416/Q.3150

Use of virtual trunks for ATM/MPLS client/server control plane interworking

Summary

The virtual trunk approach provides a mechanism in which pseudo wires function as trunks through which ATM switches can transparently establish and maintain virtual channel connections (VCCs) and virtual path connections (VPCs). The virtual trunk approach decouples control plane activity in the ATM and MPLS control planes, and pseudo wire setup or teardown is requested explicitly.

Source

ITU-T Recommendation Y.1416/Q.3150 was approved on 13 June 2007 by ITU-T Study Group 13 (2005-2008) under the ITU-T Recommendation A.8 procedure.

FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure e.g. interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementers are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database at <http://www.itu.int/ITU-T/ipr/>.

© ITU 2008

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

CONTENTS

Page

1	Scope	1
2	References.....	1
3	Definitions	1
3.1	Terms defined elsewhere	1
3.2	Terms defined in this Recommendation.....	2
4	Abbreviations and acronyms	2
5	Conventions	3
6	Requirements	3
7	Introduction to virtual trunks	3
7.1	Pseudo wire emulation and related terminology	3
7.2	Virtual trunks.....	4
7.3	Implementation options	6
8	Virtual trunk procedures – distributed implementation.....	7
8.1	Definition of virtual trunks on an ATM interface	7
8.2	ME procedures.....	8
8.3	Simplified assignments.....	9
8.4	QoS	11
9	Virtual trunk data plane procedures – integrated implementation.....	12
9.1	Encapsulation	12
9.2	ATM control interface	12
9.3	QoS	12
9.4	Usable VPIs within a VT.....	12
10	Signalling procedures between ATM switches connected through a virtual trunk.....	13
11	Virtual trunk setup and maintenance	13
11.1	Virtual trunk configuration.....	13
12	Virtual trunk OAM	14
12.1	Defects and consequent actions.....	14
Annex A – Support of both virtual trunks and individual VCs on the same ATM interface ..		16
Appendix I – VPI range as local parameter		17
Bibliography.....		18

Introduction

Many network providers are offering and delivering VC-based services across dedicated frame relay and ATM networks. Many of these same providers have embarked upon a strategy of convergence where many per-service networks and their attendant technologies and services are migrated to a single IP/MPLS packet-switched network (PSN). It is envisaged that existing network services such as frame relay and ATM and emerging new services including IP VPN will operate over this multi-service converged PSN.

ATM networks employ dynamic signalling and routing protocols to expedite connection setup and recovery. PNNI is an example of one such protocol used to dynamically set up switched ATM connections across a native ATM network [ATM pnni-0055]. When transitioning to a PSN, service providers will expect their existing ATM operations infrastructure to work with minimal modification. In particular, control protocols for routing and signalling must continue to work end-to-end.

The Internet Engineering Task Force (IETF) has developed pseudo wire (PW) technology [b-IETF RFC 3985] to emulate services over a PSN. Specifically, [IETF RFC 4717] defines how to emulate ATM connections over a PSN. These specifications, however, only describe the data plane behaviour. They do not define how an ATM connection setup interacts with PW setup.

The virtual trunk approach provides a mechanism in which pseudo wires function as trunks through which ATM switches can transparently establish and maintain virtual channel connections (VCCs) and virtual path connections (VPCs). The virtual trunk approach decouples control plane activity in the ATM and MPLS control planes, and pseudo-wire setup or teardown is requested explicitly.

Other methods enabling switched connection setup across an MPLS network have been defined in [b-ITU-T Y.1417] and [b-ATM cs-0197]. In these approaches, each connection setup or teardown in the client control plane triggers the setup or teardown of a corresponding pseudo wire.

The terminology used in this Recommendation is based upon the terminology associated with the control and user plane protocols of the organization responsible for them. For example, within the MPLS core network IETF terminology is used (e.g., pseudo wire, PE).

This Recommendation covers issues with virtual trunks. It is one of a set of documents addressing control plane interworking of MPLS with ATM and frame relay. See also [b-ITU-T Y.1417].

ITU-T Recommendation Y.1416/Q.3150

Use of virtual trunks for ATM/MPLS client/server control plane interworking

1 Scope

This Recommendation defines virtual trunks, their mapping to pseudo wires, and the way ATM switches establish connections through them.

The virtual trunk approach provides a mechanism in which pseudo wires function as trunks through which ATM switches can transparently establish and maintain virtual channel connections (VCCs) and virtual path connections (VPCs). This approach has two objectives:

- Minimize the amount of interactions between the ATM control plane and the MPLS control plane.
- Enable a distributed interworking approach in which ATM control plane and PW control plane may be on different interworking devices. This enables separation of the MPLS network routing domains and the ATM routing domains.

The following items are not within the scope of this Recommendation:

- Peer-partition interworking between ATM and frame relay control planes.
- Peer-partition interworking between ATM (or frame relay) and IP/MPLS control planes for setting up and managing switched connections between ATM (or frame relay) and IP/MPLS end-points.
- L2TPv3 pseudo wires [b-IETF RFC 3931].
- Signalling to establish virtual trunks.

2 References

The following ITU-T Recommendations and other references contain provisions which, through reference in this text, constitute provisions of this Recommendation. At the time of publication, the editions indicated were valid. All Recommendations and other references are subject to revision; users of this Recommendation are therefore encouraged to investigate the possibility of applying the most recent edition of the Recommendations and other references listed below. A list of the currently valid ITU-T Recommendations is regularly published. The reference to a document within this Recommendation does not give it, as a stand-alone document, the status of a Recommendation.

- [ATM cs-0125] ATM Forum af-cs-0125.001 (2002), *ATM Inter-Network Interface (AINI) Specification Version 1.1*.
- [ATM pnni-0055] ATM Forum af-pnni-0055.002 (2002), *Private Network-Network Interface Specification Version 1.1*.
- [ATM tm-0121] ATM Forum af-tm-0121.000 (1999), *Traffic Management 4.1*.
- [IETF RFC 4447] IETF RFC 4447 (2006), *Pseudowire Setup and Maintenance using the Label Distribution Protocol (LDP)*.
- [IETF RFC 4717] IETF RFC 4717 (2006), *Encapsulation Methods for Transport of Asynchronous Transfer Mode (ATM) over MPLS Networks*.

3 Definitions

3.1 Terms defined elsewhere

None.

3.2 Terms defined in this Recommendation

This Recommendation defines the following term:

3.2.1 virtual trunk: A virtual trunk is a logical connection between two client networks.

4 Abbreviations and acronyms

This Recommendation uses the following abbreviations and acronyms:

AC	Attachment Circuit
AINI	ATM Inter-Network Interface
ATM	Asynchronous Transfer Mode
BFD	Bidirectional Forwarding Detection
CCA	Client Connection Aggregation
IP	Internet Protocol
L2E	Layer 2 Edge
LDP	Label Distribution Protocol
LER	Label Edge Router
LSP	Label Switched Path
ME	MPLS Edge
MPLS	Multi-Protocol Label Switching
NNI	Network Node Interface
OAM	Operations, Administration and Management
PE	Provider Edge
PNNI	Private Network-Network Interface
PSN	Packet Switched Network
PW	Pseudo Wire
PWE	Pseudo Wire Emulation
PWE3	Pseudo Wire Emulation Edge-to-Edge (an IETF working group)
RSVP-TE	Resource Reservation Protocol – Traffic Engineering
RVPI	Relative VPI
UNI	User Network Interface
VC	Virtual Connection
VCC	Virtual Channel Connection
VCI	Virtual Connection Identifier
VP	Virtual Path
VPC	Virtual Path Connection
VPI	Virtual Path Identifier
VPN	Virtual Private Network