



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

R.38 B

TELEGRAPHY

TELEGRAPH TRANSMISSION

**STANDARDIZATION OF FMVFT SYSTEMS
FOR A MODULATION RATE OF 200 BAUDS
WITH CHANNELS SPACED AT 360 Hz
USABLE ON LONG INTERCONTINENTAL
BEARER CIRCUITS GENERALLY USED WITH
A 3-kHz SPACING**

ITU-T Recommendation R.38 B

(Extract from the *Blue Book*)

NOTES

1 ITU-T Recommendation R.38 B was published in Fascicle VII.1 of the *Blue Book*. This file is an extract from the *Blue Book*. While the presentation and layout of the text might be slightly different from the *Blue Book* version, the contents of the file are identical to the *Blue Book* version and copyright conditions remain unchanged (see below).

2 In this Recommendation, the expression “Administration” is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

© ITU 1988, 1993

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the ITU.



Documents
Document Sharing Hub