



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

G.709.3/Y.1331.3

(06/2018)

SERIES G: TRANSMISSION SYSTEMS AND MEDIA,
DIGITAL SYSTEMS AND NETWORKS

Digital terminal equipments – General

SERIES Y: GLOBAL INFORMATION
INFRASTRUCTURE, INTERNET PROTOCOL ASPECTS
AND NEXT-GENERATION NETWORKS, INTERNET OF
THINGS AND SMART CITIES

Internet protocol aspects – Transport

Flexible OTN long-reach interfaces

CAUTION !

PREPUBLISHED RECOMMENDATION

This prepublication is an unedited version of a recently approved Recommendation. It will be replaced by the published version after editing. Therefore, there will be differences between this prepublication and the published version.

FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications, information and communication technologies (ICTs). The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure, e.g., interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU [had/had not] received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementers are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database at <http://www.itu.int/ITU-T/ipr/>.

© ITU 2018

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

Recommendation ITU-T G.709.3/Y.1331.3 (ex. G.709.flexo-lr/Y.1331.flexo-lr)

Flexible OTN long-reach interfaces

Summary

This Recommendation defines flexible OTN (FlexO) long-reach interfaces that support bonding (i.e. grouping) of multiple of these interfaces such that an OTUC_n ($n \geq 1$) can be transferred via one or more optical tributary signals (OTSi) over one or more physical interfaces. The Recommendation specifies the frame structure for FlexO long reach interfaces using forward error correction codes with a higher coding gain than used in the FlexO short reach interfaces that are specified in G.709.1.

NOTE – In this first edition only a 100G FlexO long reach interface is specified. Other FlexO long reach interface specifications are for further study.

Keywords:

FlexO, OTN, FEC, long reach

Recommendation ITU-T G.709.3/Y.1331.3 (ex. G.709.flexo-lr/Y.1331.flexo-lr)

Flexible OTN long-reach interfaces

1 Scope

This Recommendation defines flexible OTN (FlexO) long-reach interfaces that support bonding (i.e. grouping) of multiple of these interfaces such that an OTUCn ($n \geq 1$) can be transferred via one or more optical tributary signals (OTSi) over one or more physical interfaces.

The optical parameters associated with FlexO long reach interfaces are provided by application codes, which will be in a future edition of [ITU G.698.2].

A FlexO long reach interface group complements the OTN functionality specified in [ITU G.709] and [ITU-T G.709.1] such as B100G OTUCn frame, ODUk/flex, optical interface bonding for short reach interfaces, FlexO interface group management and OTUCn (de)mapping into/from FlexO group payload area, with new functionalities supporting optical interface bonding for long reach interfaces.

This Recommendation provides specifications for new functionalities that are specific to FlexO long reach interface groups and refers to [ITU-T G.709], [ITU-T G.709.1], [ITU-T G.709.2] and [ITU-T G.798] for already existing functionalities. In addition, some introduction material for the addressed applications are included.

2 References

The following ITU-T Recommendations and other references contain provisions, which, through reference in this text, constitute provisions of this Recommendation. At the time of publication, the editions indicated were valid. All Recommendations and other references are subject to revision; users of this Recommendation are therefore encouraged to investigate the possibility of applying the most recent edition of the Recommendations and other references listed below. A list of the currently valid ITU-T Recommendations is regularly published. The reference to a document within this Recommendation does not give it, as a stand-alone document, the status of a Recommendation.

- [ITU-T G.698.2] Recommendation ITU-T G.698.2 (2018), *Amplified multichannel dense wavelength division multiplexing applications with single channel optical interfaces*.
- [ITU-T G.709] Recommendation ITU-T G.709/Y.1331 (2016), *Interfaces for the optical transport network*.
- [ITU-T G.709.1] Recommendation ITU-T G.709.1/Y.1331.1 (2017), *Flexible OTN short-reach interface*.
- [ITU-T G.709.2] Recommendation ITU-T G.709.2/Y.1331.2 (2018), *OTU4 long-reach interface*.
- [ITU-T G.798] Recommendation ITU-T G.798 (2017), *Characteristics of optical transport network hierarchy equipment functional blocks*.
- [ITU-T G.872] Recommendation ITU-T G.872 (2016), *Architecture of optical transport networks (OTN)*.
- [IEEE 802.3] IEEE Std. 802.3-2015, *IEEE Standard for Information Technology – Telecommunications and Information Exchange Between Systems – Local and Metropolitan Area Networks – Specific Requirements Part 3: Carrier Sense Multiple Access With Collision Detection (CSMA/CD) Access Method and Physical Layer Specifications*.

3 Definitions

3.1 Terms defined elsewhere:

This Recommendation uses the following terms defined elsewhere:

3.1.1 Terms defined in [ITU-T G.709]:

- completely standardized OTUCn (OTUCn)
- optical data unit (ODUCn)
- optical payload unit (OPUCn)
- optical transport network (OTN)
- optical data unit k (ODUk)
- optical tributary signal assembly (OTSiA)

3.1.2 Terms defined in [ITU-T G.709.1]:

- FlexO
- FlexO-x
- FlexO-x-RS
- FlexO-x-RS interface
- FlexO-x-RS-m interface group
- FOICx.k-RS
- FOICx.k-RS lane.

3.1.2 Terms defined in [ITU-T G.709.2]:

- Base Block

3.1.3 Terms defined in [ITU-T G.975.1]:

- coding gain
- net coding gain.

3.2 Terms defined in this Recommendation

This Recommendation defines the following terms:

3.2.1 FlexO-x-SC: Information structure consisting of a FlexO-x plus Staircase FEC parity and overhead.

3.2.2 FlexO-x-SC interface: Refers to an individual member interface that is part of a FlexO-x-SC-m interface group.

3.2.3 FlexO-x-SC-m interface group: Refers to the group of $m \times$ FlexO-x-SC interfaces.

NOTE – The text may use “FlexO group” as short-hand for FlexO-x-SC-m interface group.

3.2.4 FOICx.k-SC: Refers to a FlexO-x-SC interface using k parallel FOICx.k-SC lanes.

NOTE – “FOICx.k” is the FlexO equivalent of “OTLk.m” for OTUk as defined in [ITU-T G.709].

3.2.5 FOICx.k-SC lane: Refers to an electrical/optical lane of a FlexO-x-SC.

3.2.6 FEC Block Group (FBG): Refers to a group of 1,305,430 contiguous bits in consecutive FlexO-x-SC rows which maps to five Base Blocks.

4 Abbreviations and acronyms

This Recommendation uses the following abbreviations and acronyms:

AM	Alignment Marker
B100G	Beyond 100G
BCH	Bose-Chaudhuri-Hocquengham
DWDM	Dense Wavelength Division Multiplex
ED	Error Decorrelator
EDI	Error Decorrelator Interleaver
EDD	Error Decorrelator De-interleaver
FBA	FEC Block Alignment
FBG	FEC Block Group
FEC	Forward Error Correction
FlexO	Flexible OTN information structure
FlexO-x	FlexO interface information structure of order x
FlexO-x-SC	FlexO interface signal of order x with Staircase FEC
FOI	FlexO Interface
FOICx.k	FlexO Interface of order Cx with k lanes
LR	Long Reach
MOTU	Multi-OTU
MOTUm	Multi-OTU with management
NCG	Net Coding Gain
NNI	Network Node Interface
OCC	Overhead Communication Channel
ODU	Optical Data Unit
ODU k	ODU order k
ODUC n	ODU order Cn
OSMC	OTN synchronization messaging channel
OTN	Optical Transport Network
OTSi	Optical Tributary Signal
OTU	Optical Transport Unit
SC FEC	Staircase FEC
SOTU	Single OTU
SOTUm	Single-OTU with management
RS	Reed Solomon

5 Conventions

This Recommendation uses the following conventions defined in [ITU-T G.709]:

- k
- C_n
- m
- n

Transmission order: The order of transmission of information in all the diagrams in this Recommendation is first from left to right and then from top to bottom. Within each byte the most significant bit is transmitted first. The most significant bit (bit 1) is illustrated at the left in all the diagrams.

Value of reserved bit(s): The value of an overhead bit, which is reserved or reserved for future international standardization, shall be set to "0".

Value of non-sourced bit(s): Unless stated otherwise, any non-sourced bits shall be set to "0".

6 Introduction and applications

The FlexO long reach interface groups specified in this Recommendation provide a longer reach version of the FlexO short reach interface groups specified in [ITU-T G.709.1]. In order to mitigate the impairments of accumulated noise it uses FEC types with a higher coding gain than the FEC type deployed in FlexO short reach interfaces.

Example applications are shown in Appendix I.

This Recommendation specifies FlexO- x -<fec>- m interface groups, of which $x \geq 1$, $m \geq 1$ and <fec> represents a FEC with a net coding gain higher than the RS(544,514) FEC in FlexO- x -RS- m interface groups specified in [ITU-T G.709.1].

Edition 1.0 of this Recommendation specifies the ($m \times 100$ G) FlexO-1-SC- m interface group, with $m = n$.

NOTE – The FOIC $x.k$ -SC specified in this Recommendation is not envisaged to be reused on a system internal interface (i.e. a Module Framer Interface), instead such interface can deploy the FOIC $x.k$ as specified in [b-ITU-T G.sup58].

7 Structure and processes

This clause introduces the functions associated with a FlexO- x -SC- m interface group and the basic signal structure, processes and atomic functions.

7.1 FlexO- x -SC- m signal structure

The FlexO- x -SC- m interface group in this recommendation is only specified for long-reach applications. For short reach applications, refer to [ITU-T G.709.1]. The FlexO- x -SC- m interface group functional model is specified in [ITU-T G.872].

NOTE – The physical optical interface specifications are beyond the scope of this recommendation.

The information structure for FlexO- x -SC- m interface groups is represented by information containment relationships and information flows. The principal information containment relationship is shown in Figure 7-1.

One OTUC n signal (consisting of n OTUC instances) is mapped into the payload of n FlexO signals, each FlexO signal containing the bits of one OTUC signal. The n FlexO signals are mapped into m ($m = \lceil n/x \rceil$) FlexO- x -SC signals, each FlexO- x -SC signal containing “ x ” (frame/multi-frame aligned interleaved) FlexO signals ($x \geq 1$) plus FEC parity and FlexO- x -SC overhead. Each FlexO-

x-SC signal is split into k FlexO-x-SC lane signals (FOIC_{x,k-SC}). The k lane signals are modulated onto one OTSi, which is transported via one media element.




Figure 7-1 – FlexO-x-SC-m interface group principal information containment relationship

7.2 Processing and information flow

Functions and information flows are specified in [ITU G.798].

8 FlexO frame

Refer to clause 8 of [ITU-T G.709.1].

9 Alignment Markers, PAD and FlexO Overhead

Refer to clause 9 of [ITU-T G.709.1].

NOTE - G.709 excludes the use of a SOTUm to carry time synchronization information. This implies that the FlexO OSMC overhead is not applicable and reserved for the FlexO-x-F interface