



JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS B 8373 : 2015

(JFPA/JSA)

**Pneumatic fluid power — Solenoid
operated valves**

ICS 23.060.40;23.100.50

Reference number : JIS B 8373 : 2015 (E)

PROTECTED BY COPYRIGHT

B 8373 : 2015

Date of Establishment: 1972-12-01

Date of Revision: 2015-03-20

Date of Public Notice in Official Gazette: 2015-03-20

Investigated by: Japanese Industrial Standards Committee

Standards Board for ISO area

Technical Committee on Machine Elements

JIS B 8373 : 2015, First English edition published in 2016-06

Translated and published by: Japanese Standards Association
Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2016

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

PROTECTED BY COPYRIGHT

Contents

	Page
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Graphic symbols	1
5 Types of valve	2
5.1 General	2
5.2 Classification by number of ports	2
5.3 Classification by drive system	2
5.4 Classification by nominal bore of port and designation of screwed joint	2
5.5 Classification by state of flow path of valve	2
5.6 Classification by sealing mechanism for three-port valve, four-port valve and five-port valve	3
6 Rated voltage and rated frequency	3
7 Working conditions	3
7.1 General	3
7.2 Ambient temperature and working air temperature	3
7.3 Working pressure	3
7.4 Impact and vibration	3
7.5 Actuation frequency	3
7.6 Quality of working air	3
8 Performances	4
8.1 Actuation	4
8.2 Flow characteristic	4
8.3 Internal leakage	4
8.4 Endurance	4
8.5 Dynamic performances	4
8.6 Temperature rise	4
8.7 Insulation resistance	4
8.8 Withstand voltage	4
8.9 Proof pressure	5
9 Construction	6
9.1 General	6
9.2 Solenoid	6
9.3 Manual override	6
9.4 Screwed joint and flange joint	6

10	Appearance and material	7
11	Tests	7
11.1	Actuation test	7
11.2	Dynamic performance test	7
11.3	Temperature rise test	8
11.4	Insulation resistance test	8
11.5	Withstand voltage test	8
11.6	Internal leakage test	8
11.7	Proof pressure test	9
11.8	Endurance test	9
12	Inspection	9
12.1	Type inspection	9
12.2	Delivery inspection	10
13	Packaging	10
14	Marking	10

Foreword

This translation has been made based on the original Japanese Industrial Standard revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by Japan Fluid Power Association (JFPA)/Japanese Standards Association (JSA) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law applicable to the case of revision by the provision of Article 14.

Consequently, **JIS B 8373:2009** is replaced with this Standard, and **JIS B 8374:1993** has been withdrawn and replaced with this Standard.

This **JIS** document is protected by the Copyright Law.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, applications for a patent after opening to the public or utility model rights. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, applications for a patent after opening to the public or utility model rights.

