



JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS C 5101-2 : 2009

(IEC 60384-2 : 2005)

(JEITA)

Fixed capacitors for use in electronic equipment—Part 2: Sectional specification: Fixed metallized polyethylene-terephthalate film dielectric d.c. capacitors

ICS 31.060.30

Reference number : JIS C 5101-2 : 2009 (E)

PROTECTED BY COPYRIGHT

Date of Establishment: 1998-07-20

Date of Revision: 2009-02-20

Date of Public Notice in Official Gazette: 2009-02-20

Investigated by: Japanese Industrial Standards Committee
Standards Board

Technical Committee on Electronics Technology

JIS C 5101-2:2009, First English edition published in 2009-05

Translated and published by: Japanese Standards Association
4-1-24, Akasaka, Minato-ku, Tokyo, 107-8440 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

PROTECTED BY COPYRIGHT

Contents

	Page
Introduction.....	1
1 General	1
1.1 Scope	1
1.2 Object	1
1.3 Normative references	2
1.4 Information to be given in a detail specification	2
1.5 Terms and definitions	4
1.6 Marking	4
2 Preferred ratings and characteristics	5
2.1 Preferred characteristics	5
2.2 Preferred values of ratings	5
3 Quality assessment procedures	6
3.1 Primary stage of manufacture	6
3.2 Structurally similar components	6
3.3 Certified records of released lots	6
3.4 Qualification approval	6
3.5 Quality conformance inspection	16
4 Test and measurement procedures	17
4.1 Visual examination and check of dimensions	17
4.2 Electrical tests	17
4.3 Robustness of terminations	20
4.4 Resistance to soldering heat	21
4.5 Solderability	21
4.6 Rapid change of the temperature	21
4.7 Vibration	21
4.8 Bump	22
4.9 Shock	22
4.10 Climatic sequence	23
4.11 Damp heat, steady state	24
4.12 Endurance	24
4.13 Charge and discharge	25
4.14 Component solvent resistance	26
4.15 Solvent resistance of the marking	26

Foreword

This translation has been made based on the original Japanese Industrial Standard revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by Japan Electronics and Information Technology Industries Association (JEITA) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law applicable to the case of revision by the provision of Article 14.

Consequently **JIS C 5101-2**:1998 is replaced with this Standard.

This **JIS** document is protected by the Copyright Law.

Attention is drawn to the possibility that some parts of this Standard may conflict with a patent right, application for a patent after opening to the public, utility model right or application for registration of utility model after opening to the public which have technical properties. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying the patent right, application for a patent after opening to the public, utility model right or application for registration of utility model after opening to the public which have the said technical properties.

JIS C 5101 consists of the following 43 parts under the general title “*Fixed capacitors for use in electronic equipment*”:

JIS C 5101-1 *Part 1: Generic specification*

JIS C 5101-2 *Part 2: Sectional specification: Fixed metallized polyethylene-terephthalate film dielectric d.c. capacitors*

JIS C 5101-2-1 *Part 2: Blank detail specification: Fixed metallized polyethylene-terephthalate film dielectric d.c. capacitors Assessment level E*

JIS C 5101-3 *Part 3: Sectional specification: Fixed tantalum chip capacitors*

JIS C 5101-3-1 *Part 3: Blank detail specification: Fixed tantalum chip capacitors Assessment level E*

JIS C 5101-4 *Part 4: Sectional specification: Aluminium electrolytic capacitors with solid and non-solid electrolyte*

JIS C 5101-4-1 *Part 4: Blank detail specification: Aluminium electrolytic capacitors with non-solid electrolyte Assessment level E*

JIS C 5101-4-2 *Part 4: Blank detail specification: Aluminium electrolytic capacitors with solid electrolyte Assessment level E*

JIS C 5101-8 *Part 8: Sectional specification: Fixed capacitors of ceramic dielectric, Class 1*

JIS C 5101-8-1 *Part 8-1: Blank detail specification: Fixed capacitors of ceramic dielectric, Class 1 Assessment level EZ*

JIS C 5101-9 *Part 9: Sectional specification: Fixed capacitors of ceramic dielectric, Class 2*

JIS C 5101-9-1 *Part 9-1: Blank detail specification: Fixed capacitors of ceramic dielectric, Class 2 Assessment level EZ*

- JIS C 5101-11 *Part 11: Sectional specification: Fixed polyethylene-terephthalate film dielectric metal foil d.c. capacitors*
- JIS C 5101-11-1 *Part 11: Blank detail specification: Fixed polyethylene-terephthalate film dielectric metal foil d.c. capacitors Assessment level E*
- JIS C 5101-13 *Part 13: Sectional specification: Fixed polypropylene film dielectric metal foil d.c. capacitors*
- JIS C 5101-13-1 *Part 13: Blank detail specification: Fixed polypropylene film dielectric metal foil d.c. capacitors Assessment level E*
- JIS C 5101-14 *Part 14: Sectional specification: Fixed capacitors for electromagnetic interference suppression and connection to the supply mains*
- JIS C 5101-14-1 *Part 14: Blank detail specification: Fixed capacitors for electromagnetic interference suppression and connection to the supply mains Assessment level D*
- JIS C 5101-14-2 *Part 14-2: Blank detail specification: Fixed capacitors for electromagnetic interference suppression and connection to the supply mains—Safety tests only*
- JIS C 5101-14-3 *Part 14-3: Blank detail specification: Fixed capacitors for electromagnetic interference suppression and connection to the supply mains—Assessment level DZ*
- JIS C 5101-15 *Part 15: Sectional specification: Fixed tantalum capacitors with non-solid or solid electrolyte*
- JIS C 5101-15-1 *Part 15: Blank detail specification: Fixed tantalum capacitors with non-solid electrolyte and foil electrode Assessment level E*
- JIS C 5101-15-2 *Part 15: Blank detail specification: Fixed tantalum capacitors with non-solid electrolyte and porous anode Assessment level E*
- JIS C 5101-15-3 *Part 15: Blank detail specification: Fixed tantalum capacitors with solid electrolyte and porous anode Assessment level E*
- JIS C 5101-16 *Part 16: Sectional specification: Fixed metallized polypropylene film dielectric d.c. capacitors*
- JIS C 5101-16-1 *Part 16: Blank detail specification: Fixed metallized polypropylene film dielectric d.c. capacitors Assessment level E*
- JIS C 5101-17 *Part 17: Sectional specification: Fixed metallized polypropylene film dielectric a.c. and pulse capacitors*
- JIS C 5101-17-1 *Part 17: Blank detail specification: Fixed metallized polypropylene film dielectric a.c. and pulse capacitors Assessment level E*
- JIS C 5101-18 *Part 18: Sectional specification: Fixed aluminium electrolytic chip capacitors with solid (MnO₂) and non-solid electrolyte*
- JIS C 5101-18-1 *Part 18: Blank detail specification: Fixed aluminium electrolytic chip capacitors with solid (MnO₂) electrolyte Assessment level E*
- JIS C 5101-18-2 *Part 18: Blank detail specification: Fixed aluminium electrolytic chip capacitors with non-solid electrolyte Assessment level E*

- JIS C 5101-20 *Part 20: Sectional specification: Fixed metallized polyphenylene sulfide film dielectric chip d.c. capacitors*
- JIS C 5101-20-1 *Part 20: Blank detail specification: Fixed metallized polyphenylene sulfide film dielectric chip d.c. capacitors Assessment level EZ*
- JIS C 5101-21 *Part 21: Sectional specification: Fixed surface mount multilayer capacitors of ceramic dielectric, Class 1*
- JIS C 5101-21-1 *Part 21-1: Blank detail specification: Fixed surface mount multilayer capacitors of ceramic dielectric, Class 1—Assessment level EZ*
- JIS C 5101-22 *Part 22: Sectional specification: Fixed surface mount multilayer capacitors of ceramic dielectric, Class 2*
- JIS C 5101-22-1 *Part 22-1: Blank detail specification: Fixed surface mount multilayer capacitors of ceramic dielectric, Class 2—Assessment level EZ*
- JIS C 5101-23 *Part 23: Sectional specification—Fixed surface mount metallized polyethylene naphthalate film dielectric DC capacitors*
- JIS C 5101-23-1 *Part 23-1: Blank detail specification—Fixed surface mount metallized polyethylene naphthalate film dielectric DC capacitors—Assessment level EZ*
- JIS C 5101-24 *Part 24: Sectional specification—Surface mount fixed tantalum electrolytic capacitors with conductive polymer solid electrolyte (to be published)*
- JIS C 5101-24-1 *Part 24-1: Blank detail specification—Surface mount fixed tantalum electrolytic capacitors with conductive polymer solid electrolyte—Assessment level EZ (to be published)*
- JIS C 5101-25 *Part 25: Sectional specification—Surface mount fixed aluminium electrolytic capacitors with conductive polymer solid electrolyte (to be published)*
- JIS C 5101-25-1 *Part 25-1: Blank detail specification—Surface mount fixed aluminium electrolytic capacitors with conductive polymer solid electrolyte—Assessment level EZ (to be published)*

Fixed capacitors for use in electronic equipment—Part 2: Sectional specification: Fixed metallized polyethylene-terephthalate film dielectric d.c. capacitors

Introduction

This Japanese Industrial Standard has been prepared based on the third edition of **IEC 60384-2** published in 2005 without modifying the technical contents.

The portions given sidelines or dotted underlines are the matters not stated in the original International Standard.

1 General

1.1 Scope

This Standard is a sectional specification associated with the generic specification **JIS C 5101-1** and applies to fixed capacitors (hereafter referred to as “capacitors”) for direct current, with metallized electrodes and polyethylene-terephthalate dielectric for use in electronic equipment.

These capacitors may have “self-healing properties” depending on conditions of use. They are primarily intended for applications where the a.c. component is small with respect to the rated voltage. Two performance grades of capacitors are covered, Grade 1 for long-life application and Grade 2 for general application.

Capacitors for electromagnetic interference suppression and surface mount fixed metallized polyethylene-terephthalate film dielectric d.c. capacitors are not included, but are covered by **JIS C 5101-14** and **IEC 60384-19**, respectively.

NOTE : The International Standard corresponding to this Standard is as follows.

IEC 60384-2:2005 *Fixed capacitors for use in electronic equipment—Part 2: Sectional specification: Fixed metallized polyethylene-terephthalate film dielectric d.c. capacitors* (IDT)

In addition, symbols which denote the degree of correspondence in the contents between the relevant International Standard and **JIS** are IDT (identical), MOD (modified), and NEQ (not equivalent) according to **ISO/IEC Guide 21**.

1.2 Object

The object of this Standard is to prescribe preferred ratings and characteristics and to select from **JIS C 5101-1** the appropriate quality assessment procedures, tests and measuring methods, and to give general performance requirements for this type of capacitor. Test severities and requirements prescribed in detail specifications referring to this sectional specification shall be of equal or higher performance level, because lower performance levels are not permitted.

1.3 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this Standard. For standards with the year indication, only the editions of the indicated year shall apply but the revisions (including amendments) made thereafter shall not apply. The normative reference without the indication of the year shall apply only to the most recent edition (including amendments).

JIS C 5063:1997 *Preferred number series for resistors and capacitors*

NOTE : Corresponding International Standard: IEC 60063:1963 *Preferred number series for resistors and capacitors*, Amendment 1:1967, and Amendment 2:1977 (IDT)

JIS C 5101-1:1998 *Fixed capacitors for use in electronic equipment Part 1: Generic specification*

NOTE : Corresponding International Standard: IEC 60384-1:1982 *Fixed capacitors for use in electronic equipment—Part 1: Generic specification*, Amendment 2:1987, Amendment 3:1989 and Amendment 4:1992 (MOD)

In addition, **JIS C 5101-1:1998** does not correspond to the latest edition **IEC 60384-1:1999**, so the numbering system of applicable items may not correspond with each other. In the case of discrepancy in the numbering, the number of **IEC 60384-1:1999** is shown in NOTE.

JIS C 5101-2-1:2009 *Fixed capacitors for use in electronic equipment—Part 2-1 Blank detail specification: Fixed metallized polyethylene-terephthalate film dielectric d.c. capacitors—Assessment levels E and EZ*

NOTE : Corresponding International Standard: IEC 60384-2-1:2005 *Fixed capacitors for use in electronic equipment—Part 2-1: Blank detail specification: Fixed metallized polyethylene-terephthalate film dielectric d.c. capacitors—Assessment levels E and EZ* (IDT)

JIS C 60068-1:1993 *Environmental testing Part 1: General and guidance*

NOTE : Corresponding International Standard: IEC 60068-1:1988 *Environmental testing—Part 1: General and guidance* and Amendment 1:1992 (IDT)

JIS Z 8601:1954 *Preferred numbers*

NOTE : Corresponding International Standard: ISO 3:1973 *Preferred numbers—Series of preferred numbers* (MOD)

JIS Z 9015-1 *Sampling procedures for inspection by attributes—Part 1: Sampling schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection*

NOTE : Corresponding International Standard: IEC 60410:1973 *Sampling plans and procedures for inspection by attributes* (MOD)

1.4 Information to be given in a detail specification

Detail specifications shall be derived from the relevant blank detail specification.

Detail specifications shall not specify requirements inferior to those of the generic, sectional or blank detail specification. When more severe requirements are included,

they shall be listed in **1.9** of the detail specification and indicated in the test schedules, for example by an asterisk (*).

NOTE : The information given in **1.4.1** may for convenience, be presented in tabular form.

The following information shall be given in each detail specification and the values quoted shall preferably be selected from those given in the appropriate clause of this sectional specification.

1.4.1 Outline drawing and dimensions

These shall be an illustration of the capacitor as an aid to easy recognition and for comparison of the capacitor with others. Dimensions and their associated tolerances, which affect interchangeability and mounting, shall be given in the detail specification. All dimensions shall preferably be stated in millimetres.

Normally, the numerical values shall be given for the length of the body, the width and height of the body and the wire spacing, or for cylindrical types, the body diameter, and the length and diameter of the terminations. When necessary, for example when a number of items (capacitance values/voltage ranges) are covered by a detail specification, the dimensions and their associated tolerances shall be placed in a table below the drawing.

When the configuration is other than described above, the detail specification shall state such dimensional information as will adequately describe the capacitor. When the capacitor is not designed for use on printed boards, this shall be clearly stated in the detail specification.

1.4.2 Mounting

The detail specification shall specify the method of mounting to be applied for normal use. Mounting for the application of tests and measurements (if required) shall be in accordance with **4.1**.

1.4.3 Rating and characteristics

The ratings and characteristics shall be in accordance with the relevant clauses of this specification, together with the following:

1.4.3.1 Rated capacitance range

See **2.2.1**.

NOTE : In the case of International Electrotechnical Commission Quality Assessment System for Electronic Components (IECQ), when products approved to the detail specification may have different ranges, the following statement should be added:

“The range of values available in each voltage range is given in the qualified products list (QPL).”

1.4.3.2 Particular characteristics

Additional characteristics may be listed, when they are considered necessary to specify adequately the component for design and application purposes.

1.4.3.3 Soldering

The detail specification shall prescribe the test methods, severities and requirements applicable for the solderability and the resistance to soldering heat test.

1.4.4 Marking

The detail specification shall specify the content of the marking on the capacitor and on the package. Deviations from **1.6** of this Standard shall be specifically stated.

1.5 Terms and definitions

For the purpose of this Standard, the definitions given in **JIS C 5101-1** and the following apply.

1.5.1 performance grade 1 capacitors (long-life)

capacitors for long-life applications with stringent requirements for the electrical parameters

1.5.2 performance grade 2 capacitors (general purpose)

capacitors for general application where the stringent requirements for Grade 1 capacitors are not necessary

1.5.3 rated voltage (U_R)

maximum d.c. voltage which may be applied continuously to a capacitor at the rated temperature

NOTE : The sum of the d.c. voltage and the peak a.c. voltage applied to the capacitor must not exceed the rated voltage. The value of the peak a.c. voltage must not exceed the following percentages of the rated voltage at the frequencies stated and must be not greater than 280 V:

50 Hz:	20 %
100 Hz:	15 %
1 kHz:	3 %
10 kHz:	1 %

unless otherwise specified in the detail specification.

1.6 Marking

See **2.4** of **JIS C 5101-1**, with the following details:

1.6.1 Marking on the capacitor and the package

The information given in the marking is normally selected from the following list; the relative importance of each item is indicated by its position in the list:

- rated capacitance;
- rated voltage (d.c. voltage may be indicated by the symbol --- or —);
- tolerance on rated capacitance;
- category voltage;