



JAPANESE  
INDUSTRIAL  
STANDARD

Translated and Published by  
Japanese Standards Association

---

---

**JIS C 60068-2-6** : 2010

(IEC 60068-2-6 : 2007)

(RCJ/JSA)

**Environmental testing—Part 2-6:  
Tests—Test Fc: Vibration  
(sinusoidal)**

---

**ICS 19.040**

**Reference number : JIS C 60068-2-6 : 2010 (E)**

PROTECTED BY COPYRIGHT

Date of Establishment: 1987-03-01

Date of Revision: 2010-02-22

Date of Public Notice in Official Gazette: 2010-02-22

Investigated by: Japanese Industrial Standards Committee  
Standards Board

Technical Committee on Electricity Technology

---

JIS C 60068-2-6:2010, First English edition published in 2010-10

Translated and published by: Japanese Standards Association  
4-1-24, Akasaka, Minato-ku, Tokyo, 107-8440 JAPAN

---

In the event of any doubts arising as to the contents,  
the original JIS is to be the final authority.

© JSA 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

PROTECTED BY COPYRIGHT

## Contents

|                                                                                        | Page |
|----------------------------------------------------------------------------------------|------|
| Introduction.....                                                                      | 1    |
| 1 Scope.....                                                                           | 1    |
| 2 Normative references .....                                                           | 2    |
| 3 Terms and definitions .....                                                          | 2    |
| 4 Requirements for testing.....                                                        | 5    |
| 4.1 Required characteristics .....                                                     | 5    |
| 4.2 Control strategy .....                                                             | 7    |
| 4.3 Mounting.....                                                                      | 8    |
| 5 Severities .....                                                                     | 9    |
| 5.1 Frequency range .....                                                              | 9    |
| 5.2 Vibration amplitude .....                                                          | 9    |
| 5.3 Duration of endurance .....                                                        | 10   |
| 6 Preconditioning .....                                                                | 13   |
| 7 Initial measurements .....                                                           | 13   |
| 8 Testing .....                                                                        | 13   |
| 8.1 General.....                                                                       | 13   |
| 8.2 Vibration response investigation.....                                              | 14   |
| 8.3 Endurance procedures .....                                                         | 15   |
| 9 Intermediate measurements .....                                                      | 16   |
| 10 Recovery .....                                                                      | 16   |
| 11 Final measurements.....                                                             | 16   |
| 12 Information to be given in the relevant specification.....                          | 16   |
| 13 Information to be given in the test report .....                                    | 17   |
| Annex A (informative) Guide to test Fc.....                                            | 19   |
| Annex B (informative) Examples of severities primarily intended for<br>components..... | 34   |
| Annex C (informative) Examples of severities primarily intended for<br>equipment.....  | 36   |

## Foreword

This translation has been made based on the original Japanese Industrial Standard revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by Reliability Center for Electronic Components of Japan (RCJ)/Japanese Standards Association (JSA) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law applicable to the case of revision by the provision of Article 14. Consequently **JIS C 60068-2-6:1999** is replaced with this Standard.

This **JIS** document is protected by the Copyright Law.

Attention is drawn to the possibility that some parts of this Standard may conflict with a patent right, application for a patent after opening to the public, utility model right or application for registration of utility model after opening to the public which have technical properties. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying the patent right, application for a patent after opening to the public, utility model right or application for registration of utility model after opening to the public which have the said technical properties.

**JIS C 60068** consists of the following 58 parts;

JIS C 60068-1 *General and guidance*

JIS C 60068-2-1 *Part 2-1: Tests—Test A: Cold*

JIS C 60068-2-2 *Part 2-2 : Tests—Test B: Dry heat*

JIS C 60068-2-6 *Part 2-6: Tests—Test Fc: Vibration (sinusoidal)*

JIS C 60068-2-7 *Test Ga and guidance: Acceleration, steady state*

JIS C 60068-2-11 *Test Ka: Salt mist*

JIS C 60068-2-13 *Test M: Low air pressure*

JIS C 60068-2-17 *Test Q: Sealing*

JIS C 60068-2-18 *Part 2-18: Tests—Test R and guidance: Water*

JIS C 60068-2-20 *Test T: Soldering*

JIS C 60068-2-21 *Part 2-21: Tests—Test U: Robustness of termination and integral mounting devices*

JIS C 60068-2-27 *Test Ea and guidance: Shock*

JIS C 60068-2-29 *Test Eb and guidance: Bump*

JIS C 60068-2-30 *Test Db: Damp heat, cyclic (12 + 12-Hour cycle)*

JIS C 60068-2-31 *Test Ec: Drop and topple, primarily for equipment-type specimens*

JIS C 60068-2-32 *Test Ed: Free fall*

JIS C 60068-2-38 *Test Z/AD: Composite temperature/humidity cyclic test*

JIS C 60068-2-39 *Test Z/AMD: Combined sequential cold, low air pressure, and damp heat test*

JIS C 60068-2-40 *Test Z/AM: Combined cold/low air pressure tests*

- JIS C 60068-2-41 *Test Z/BM: Combined dry heat/low air pressure tests*
- JIS C 60068-2-42 *Test Kc: Sulphur dioxide test for contacts and connections*
- JIS C 60068-2-43 *Test Kd: Hydrogen sulphide test for contacts and connections*
- JIS C 60068-2-45 *Testing procedures of resistance to solvents (immersion in cleaning solvents)*
- JIS C 60068-2-46 *Guidance to Test Kd: Hydrogen sulphide test for contacts and connections*
- JIS C 60068-2-47 *Part 2-47: Tests—Mounting of specimens for vibration, impact and similar dynamic tests*
- JIS C 60068-2-48 *Part 2: Tests. Guidance on the application of the tests of JIS environmental testing series to simulate the effects of storage*
- JIS C 60068-2-49 *Guidance to Test Kc: Sulphur dioxide test for contacts and connections*
- JIS C 60068-2-50 *Tests Z/AFc: Combined cold/vibration (sinusoidal) tests for both heat-dissipating and non-heat-dissipating specimens*
- JIS C 60068-2-51 *Tests Z/BFc: Combined dry heat/vibration (sinusoidal) tests for both heat-dissipating and non-heat-dissipating specimens*
- JIS C 60068-2-52 *Test Kb: Salt mist, cyclic (sodium, chloride solution)*
- JIS C 60068-2-53 *Guidance to tests Z/AFc and Z/BFc: Combined temperature (cold and dry heat) and vibration (sinusoidal) tests*
- JIS C 60068-2-54 *Test Ta: Soldering. Solderability testing by the wetting balance method*
- JIS C 60068-2-57 *Time-history vibration test method*
- JIS C 60068-2-58 *Test Td: Test methods for solderability, resistance to dissolution of metallization and to soldering heat of surface mounting devices (SMD)*
- JIS C 60068-2-59 *Test Fe: Vibration—Sine-beat method*
- JIS C 60068-2-60 *Test Ke: Flowing mixed gas corrosion test*
- JIS C 60068-2-61 *Test Z/ABDM: Climatic sequence*
- JIS C 60068-2-64 *Test Fh: Vibration, broad-band random (digital control) and guidance*
- JIS C 60068-2-65 *Part 2-65: Vibration, acoustically induced*
- JIS C 60068-2-66 *Test Cx: Damp heat, steady state (unsaturated pressurized vapour)*
- JIS C 60068-2-67 *Test Cy: Damp heat, steady state, accelerated test primarily intended for components*
- JIS C 60068-2-68 *Dust and sand test*
- JIS C 60068-2-69 *Part 2-69: Tests—Test Te: Solderability testing of electronic components for surface mounting devices (SMD) by the wetting balance method*
- JIS C 60068-2-70 *Test Xb: Abrasion of markings and letterings caused by rubbing of fingers and hands*

- JIS C 60068-2-75 *Part 2-75: Tests—Test Eh: Hammer tests*
- JIS C 60068-2-77 *Test 77: Body strength and impact shock*
- JIS C 60068-2-78 *Part 2-78: Tests—Test Cab: Damp heat, steady state*
- JIS C 60068-2-80 *Part 2-80: Tests—Test Fi: Vibration—Mixed mode*
- JIS C 60068-2-81 *Part 2-81: Shock—Shock response spectrum synthesis*
- JIS C 60068-2-82 *Part 2-82: Tests—Test XW<sub>1</sub>: Whisker test methods for electronic and electric components*
- JIS C 60068-3-1 *Background information, Section One—Cold and dry heat tests*
- JIS C 60068-3-2 *Part 3: Background information Section Two—Combined temperature/low air pressure tests*
- JIS C 60068-3-3 *Guidance Seismic test method for equipments*
- JIS C 60068-3-4 *Part 3-4: Supporting documentation and guidance—Damp heat tests*
- JIS C 60068-3-5 *Part 3-5: Supporting documentation and guidance—Confirmation of the performance of temperature chambers*
- JIS C 60068-3-6 *Part 3-6: Supporting documentation and guidance—Confirmation of the performance of temperature/humidity chambers*
- JIS C 60068-3-7 *Part 3-7: Supporting documentation and guidance—Measurements in temperature chambers for tests A and B (with load)*
- JIS C 60068-3-8 *Part 3-8: Supporting documentation and guidance—Selecting amongst vibration tests*

## Environmental testing—Part 2-6: Tests—Test Fc: Vibration (sinusoidal)

### Introduction

This Japanese Industrial Standard has been prepared based on the seventh edition of **IEC 60068-2-6** published in 2007 without modifying the technical contents.

The portions with continuous sidelines or dotted underlines are the matters not given in corresponding International Standard.

This Standard gives a method of test applicable to components, equipment and other articles which, during transportation or in service, may be subjected to conditions involving vibration of a harmonic pattern, generated primarily by rotating, pulsating or oscillating forces, such as occur in ships, aircraft, land vehicles, rotorcraft and space applications or are caused by machinery and seismic phenomena.

This Standard consists basically of subjecting a specimen to sinusoidal vibration over a given frequency range or at discrete frequencies, for a given period of time. A vibration response investigation may be specified which aims at determining critical frequencies of the specimen.

The relevant specification shall indicate whether the specimen shall function during vibration or whether it suffices that it still works after having been submitted to vibration.

It is emphasized that vibration testing always demands a certain degree of engineering judgement, and both the supplier and purchaser should be fully aware of this fact. However, sinusoidal testing is deterministic and, therefore, relatively simple to perform. Thus it is readily applicable to both diagnostic and service life testing.

The main part of this Standard deals primarily with the methods of controlling the test at specified points using either analogue or digital techniques, and gives, in detail, the testing procedure. The requirements for the vibration motion, choice of severities including frequency ranges, amplitudes and endurance times are also specified, these severities representing a rationalized series of parameters. The relevant specification writer is expected to choose the testing procedure and values appropriate to the specimen and its use.

### 1 Scope

This Standard gives a method of test which provides a standard procedure to determine the ability of components, equipment and other articles, hereinafter referred to as specimens, to withstand specified severities of sinusoidal vibration. If an item is to be tested in an unpackaged form, that is without its packaging, it is referred to as a test specimen. However, if the item is packaged then the item itself is referred to as a product and the item and its packaging together are referred to as a test specimen.

The purpose of this test is to determine any mechanical weakness and/or degradation in the specified performance of specimens and to use this information, in conjunction with the relevant specification, to decide upon the acceptability of the specimens. In

some cases, the test method may also be used to demonstrate the mechanical robustness of specimens and/or to study their dynamic behaviour. Categorization of components can also be made on the basis of a selection from within the severities quoted in the test.

NOTE : The International Standard corresponding to this Standard and the symbol of degree of correspondence are as follows.

IEC 60068-2-6:2007 *Environmental testing—Part 2-6: Tests—Test Fc: Vibration (sinusoidal)* (IDT)

In addition, symbols which denote the degree of correspondence in the contents between the relevant International Standard and **JIS** are IDT (identical), MOD (modified), and NEQ (not equivalent) according to **ISO/IEC Guide 21-1**.

## 2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this Standard. The most recent editions of the standards (including amendments) indicated below shall be applied.

JIS B 0153 *Glossary of terms used in mechanical vibration and shock*

NOTE : Corresponding International Standard: ISO 2041 *Vibration and shock—Vocabulary* (MOD)

JIS C 60068-1 *Environmental testing Part 1: General and guidance*

NOTE : Corresponding International Standard: IEC 60068-1 *Environmental testing. Part 1: General and guidance* (IDT)

JIS C 60068-2-47 *Environmental testing—Part 2-47: Tests—Mounting of specimens for vibration, impact and similar dynamic tests*

NOTE : Corresponding International Standard: IEC 60068-2-47 *Environmental testing—Part 2-47: Test—Mounting of specimens for vibration, impact and similar dynamic tests* (IDT)

## 3 Terms and definitions

For the purposes of this Standard, the terms and definitions given in **JIS B 0153** and **JIS C 60068-1** together with the following apply.

### 3.1 fixing point

part of the specimen in contact with the fixture or vibration table at a point where the specimen is normally fastened in service

NOTE 1 If a part of the real mounting structure is used as the fixture, the fixing points are those of the mounting structure and not of the specimen.

NOTE 2 Where the specimen consists of a packaged product, fixing point may be interpreted as the surface of the specimen which is in contact with the vibration table.

### 3.2 measuring points

specific points at which data are gathered conducting the test

NOTE 1 These are of two main types, the definitions of which are given below.

NOTE 2 Measurements may be made at points within the specimen in order to assess its behaviour, but these are not considered as measuring points in the sense of this Standard. For further details, see **A.2.1**.

#### 3.2.1 check point

point located on the fixture, on the vibration table or on the specimen as close as possible to one of its fixing points, and in any case rigidly connected to it

NOTE 1 A number of check points are used as a means of ensuring that the test requirements are satisfied.

NOTE 2 If four or fewer fixing points exist, each is used as a check point. For packaged products, where a fixing point may be interpreted as the packaging surface in contact with the vibration table, one check point may be used, provided that there are no effects due to resonances of the vibration table or the mounting structure in the frequency range specified for the test. If this is the case, multipoint control may be necessary, but see also NOTE 3. If more than four fixing points exist, four representative fixing points will be defined in the relevant specification to be used as check points.

NOTE 3 In special cases, for example for large or complex specimens, the check points will be prescribed in the relevant specification if not close to the fixing points.

NOTE 4 Where a large number of small specimens are mounted on one fixture, or in the case of a small specimen where there are several fixing points, a single check point (i.e. the reference point) may be selected for the derivation of the control signal. This signal is then related to the fixture rather than to the fixing points of the specimen(s). This is only valid when the lowest resonance frequency of the loaded fixture is well above the upper frequency of the test.

#### 3.2.2 reference point

point, chosen from the check points, whose signal is used to control the test, so that the requirements of this Standard are satisfied

#### 3.2.3 fictitious reference point

point, derived from multiple check points, either manually or automatically, the result of which is used to control the test, so that the requirements of this Standard are satisfied

### 3.3 control methods

#### 3.3.1 single point control

control method using the signal from the transducer at the reference point in order to maintain this point at the specified vibration level (see **4.1.4.1**)

### 3.3.2 multipoint control

control method achieved by using the signals from each of the transducers at the check points

NOTE : The signals are either continuously averaged arithmetically or processed by using comparison techniques, depending upon the relevant specification (see 4.1.4.1).

### 3.4 sweep cycle

traverse of the specified frequency range once in each direction, for example 10 Hz to 150 Hz to 10 Hz

### 3.5 signal tolerance

ratio of the frequency other than the fundamental driving frequency to the fundamental driving frequency

The signal tolerance is given by:

$$T = \left( \frac{NF}{F} - 1 \right) \times 100$$

where,  $T$ : signal tolerance (%)

$NF$ : the r.m.s value of the unfiltered signal

$F$ : the r.m.s value of the filtered signal

NOTE : This parameter applies to whichever signal, i.e. acceleration, velocity or displacement, is being used to control the test (see A.2.2).

### 3.6 basic motion

motion at the driving frequency of vibration at the reference point (see also 4.1.1)

### 3.7 actual motion

motion represented by the wideband signal returned from the reference point transducer

### 3.8 damping

generic term ascribed to the numerous energy dissipation mechanisms in a system

NOTE : In practice, damping depends on many parameters, such as the structural system, mode of vibration, strain, applied forces, velocity, materials, joint slippage, etc.

### 3.9 critical frequencies

frequencies at which

- malfunctioning and/or deterioration of performance of the specimen are exhibited which are dependent on vibration, and/or
- mechanical resonances and/or other response effects occur, for example, chatter

### 3.10 centred resonance frequency

frequency automatically centred on the actual resonance frequency derived from the vibration response investigation

### 3.11 restricted frequency sweeping

sweeping over a restricted frequency range between 0.8 and 1.2 times the critical frequency

### 3.12 $g_n$

standard acceleration due to the earth's gravity, which itself varies with altitude and geographical latitude

NOTE : For the purposes of this Standard, the value of  $g_n$ , is rounded up to the nearest whole number, that is 10 m/s<sup>2</sup>.

## 4 Requirements for testing

### 4.1 Required characteristics

The required characteristics apply to the complete vibration system, which includes the power amplifier, vibrator, test fixture, specimen and control system when loaded for testing.

#### 4.1.1 Basic motion

The basic motion shall be a sinusoidal function of time and such that the fixing points of the specimen move substantially in phase and in straight parallel lines, subject to the limitations of 4.1.2 and 4.1.3.

#### 4.1.2 Spurious motion

##### 4.1.2.1 Cross-axis motion

The maximum vibration amplitude at the check points in any axis perpendicular to the specified axis shall not exceed 50 % of the specified amplitude up to 500 Hz or 100 % for frequencies in excess of 500 Hz. The measurements need only cover the specified frequency range. In special cases, e.g. small specimens, the amplitude of the permissible cross axis motion may be limited to 25 %, if required by the relevant specification. In some cases, for example for large size or high mass specimens or at some frequencies, it may be difficult to achieve the figures quoted above. In such cases, the relevant specification shall state which of the following requirements apply:

- a) any cross-axis motion in excess of that stated above shall be noted and stated in the test report; or
- b) cross-axis motion which is known to offer no hazard to the specimen need not be monitored.

##### 4.1.2.2 Rotational motion

In the case of large size or high mass specimens, the occurrence of spurious rotational motion of the vibration table may be important. If so, the relevant specification shall prescribe a tolerable level. The achieved level shall be stated in the test report (see also A.2.4).

#### 4.1.3 Signal tolerance

Acceleration signal tolerance measurements shall be performed if stated in the relevant specification. They shall be carried out at the reference point and shall cover the frequencies up to 5 000 Hz or five times the driving frequency whichever is the lesser. However, this maximum analysing frequency may be extended to the upper test frequency for the sweep, or beyond, if specified in the relevant specification. Unless otherwise stated in the relevant specification, the signal tolerance shall not exceed 5 % (see **3.5**).

If stated in the relevant specification, the acceleration amplitude of the control signal at the fundamental driving frequency shall be restored to the specified value by use of a tracking filter (see **A.4.4**).

In the case of large or complex specimens, where the specified signal tolerance values cannot be satisfied at some parts of the frequency range, and it is impracticable to use a tracking filter, the acceleration amplitude need not be restored, but the signal tolerance shall be stated in the test report (see **A.2.2**).

NOTE : If a tracking filter is not used and the signal tolerance is in excess of 5 %, the reproducibility may be significantly affected by the choice of either a digital or analogue control system (see **A.4.5**).

The relevant specification may require that the signal tolerance, together with the frequency range affected, is stated in the test report whether or not a tracking filter has been used (see **A.2.2**).

#### 4.1.4 Vibration amplitude tolerances

The basic motion amplitude in the required axis at the check and reference points shall be equal to the specified value, within the following tolerances. These tolerances include instrumentation errors. The relevant specification may require that the confidence level used in the assessment of measurement uncertainty is stated in the test report.

At low frequencies or with large size or high mass specimens it may be difficult to achieve the required tolerances.

In these cases, it is expected that a wider tolerance or the use of an alternative method of assessment shall be prescribed in the relevant specification and stated in the test report.

##### 4.1.4.1 Reference point

Tolerance on the control signal at the reference point shall be  $\pm 15$  % (see **A.2.3**).

##### 4.1.4.2 Check points

Tolerance on the control signal at each check point:

$\pm 25$  % up to 500 Hz;

$\pm 50$  % above 500 Hz.

(See **A.2.3**.)

#### 4.1.5 Frequency tolerances

The following frequency tolerances apply.

#### 4.1.5.1 Endurance by sweeping

- $\pm 0.05$  Hz up to 0.25 Hz;
- $\pm 20$  % from 0.25 Hz to 5 Hz;
- $\pm 1$  Hz from 5 Hz to 50 Hz;
- $\pm 2$  % above 50 Hz.

#### 4.1.5.2 Endurance at fixed frequency

- a) Fixed frequency:
  - $\pm 2$  %.
- b) Almost fixed frequency:
  - $\pm 0.05$  Hz up to 0.25 Hz;
  - $\pm 20$  % from 0.25 Hz to 5 Hz;
  - $\pm 1$  Hz from 5 Hz to 50 Hz;
  - $\pm 2$  % above 50 Hz.

#### 4.1.5.3 Measurement of critical frequency

When the critical frequencies before and after endurance have to be compared, i.e. during vibration response investigations, the following tolerances shall apply:

- $\pm 0.05$  Hz up to 0.5 Hz;
- $\pm 10$  % from 0.5 Hz to 5 Hz;
- $\pm 0.5$  Hz from 5 Hz to 100 Hz;
- $\pm 0.5$  % above 100 Hz.

#### 4.1.6 Sweep

The sweeping shall be continuous and the frequency shall change exponentially with time (see **A.4.3**). The sweep rate shall be one octave per minute with a tolerance of  $\pm 10$  %. This may be varied for a vibration response investigation (see **8.2**).

NOTE : With a digital control system, it is not strictly correct to refer to the sweeping being “continuous”, but the difference is of no practical significance.

### 4.2 Control strategy

#### 4.2.1 Single/multipoint control

The relevant specification shall state whether single point or multipoint control shall be used. If multipoint control is prescribed, the relevant specification shall state whether the average amplitude of the signals at the check points or the amplitude of the signal at a selected point (for example, that with the largest amplitude) shall be controlled to the specified level, see also **A.2.3**.

If it is not possible to achieve single point control, as required by the relevant specification, then multipoint control shall be used by controlling the average or extreme value of the signals at the check points. In either of these cases of multipoint control, the reference point is a fictitious reference point. The method used shall be stated in the test report.

Use of multipoint control does not assure that the tolerances of each checkpoint are met. In general it reduces the deviation from the nominal values, when compared with single-point control, at the fictitious reference point.

The following strategies are available.

#### 4.2.1.1 Averaging strategy

In this method, the control amplitude is computed from the signal from each check point. A composite control amplitude is formed by arithmetically averaging the signal amplitudes from the check points. This arithmetically averaged control amplitude is then compared with the specified amplitude.

#### 4.2.1.2 Weighted averaging strategy

The control amplitude is formed by averaging the signal amplitude from the check point according to their weighting:

$$a_c = \frac{(w_1 \times a_1 + w_2 \times a_2 + \dots + w_n \times a_n)}{(w_1 + w_2 + \dots + w_n)}$$

where,  $a_c$  : the control amplitude  
 $a_n$  : the signal amplitude from each check point  
 $w_n$  : the weighting of each check point  
 $n$  : the number of check points

This control strategy offers the possibility that different check point signals contribute a different portion to the control.

#### 4.2.1.3 Extremal strategy

In this method, a composite control amplitude is computed from the maximum (MAX) or the minimum (MIN) extreme amplitudes of the signal amplitude measured at each check point. This strategy will produce a control amplitude that represents the envelope of the signal amplitudes from each check point (MAX) or a lower limit of the signal amplitudes from each check point (MIN).

### 4.2.2 Multi-reference control

If specified by the relevant specification, multiple reference spectra may be defined for different check points or measuring points or different types of controlled variables, for example, for force limited vibration testing.

When multi-reference control is specified, the control strategy shall be prescribed as follows:

- Limiting: All control signals shall be beneath their appropriate reference;
- Superseding: All control signals shall be above their appropriate reference.

### 4.3 Mounting

Unless otherwise stated in the relevant specification, the specimens shall be mounted on the test apparatus in accordance with the requirements in **JIS C 60068-2-47**. For specimens normally mounted on vibration isolators, see NOTE in **8.3.2** as well as **A.3.1**, **A.3.2** and clause **A.5**.