

Table

Dia. of steel wire rope (mm)	[6]	6 ³	8	9	10	11 ²	(12)	12 ⁵	14	16	18	20	(22)	(24)	(26)	28	30	31 ⁵	(32)	(34)	(36)	(38)	40	(42)	(44)	(46)	(48)	(50)	(52)	(54)	(58)	(62)	(65)
Where used																																	
Tow line												②					④										④ or ⑥						
Mooring line												② or ④									④ or ⑥												
Stay																① or ③																	
Cargo runner															④ or ⑥																		
Wire sling												④																					
Guy pendant for derrick																	④ or ⑥																
Boat fall												③ , ④ or ⑥																					
Davit guy							③ , ④ or ⑥																										
Fall for accommodation ladder						④ or ⑥																											
Antenna fall	③				④																												
Anchor stopper											④ or ⑥																						
Fastening rope	③									④																							
Ridge rope of awning						④																											
Driving rope	③											④ or ⑥																					
Stream anchor rope																			② , ④ or ⑥														
Wire rope of buoy hook											④																						
Driving wire for topping unit										④ or ⑥																							
Anchor heaving rope															④ or ⑥																		
Fire line																	④ or ⑥																

Remarks: 1. In above Table, ① denotes No.1 (6×7), ② No.2 (6×12), ③ No.3 (6×19), ④ No.4 (6×24), ⑥ No.6 (6×37) wire rope respectively.

2. In above Table, dimensions in brackets [] denote that they are not specified in the Japanese Industrial Standards and those in parentheses () denote that "it is recommended that they are not to be used as much as possible" in JIS G 3525.