

JIS

JAPANESE INDUSTRIAL STANDARD

**Freight containers—
Lifting and securing fittings**

JIS Z 1629—1996

Translated and Published

by

Japanese Standards Association

**In the event of any doubt arising,
the original Standard in Japanese is to be final authority**

Errata for JIS (English edition) are printed in *Standardization Journal*, published monthly by the Japanese Standards Association.

Errata will be provided upon request, please contact:

**Business Department,
Japanese Standards Association**
4-1-24, Akasaka, Minato-ku,
Tokyo, JAPAN 107
TEL. 03-3583-8002
FAX. 03-3583-0462

Errata are also provided to subscribers of JIS (English edition) in *Monthly Information*.

JAPANESE INDUSTRIAL STANDARD

J I S

Freight containers—
Lifting and securing fittings

Z 1629-1996

1. **Scope** This Japanese Industrial Standard specifies lifting fittings used for lifting the freight containers for international trade or domestic trade (hereafter referred to as "containers") at their upper parts by means of corner fittings specified in JIS Z 1610 and JIS Z 1616, and fittings used for securing the containers on motor truck or freight-train car by means of those corner fittings or the securing fittings.

This Standard does not apply to the fittings for lashing the containers loaded on ship.

Remarks 1. The following standards are cited in this Standard:

JIS Z 1610 External dimensions and common specifications of freight containers for domestic trade

JIS Z 1614 Freight containers for international trade – External dimensions and ratings

JIS Z 1616 Freight containers for international trade—Corner fittings

2. The units and numerical values given in { } in this Standard are based on the traditional unit system and are appended for informative reference.

2. **Type, symbol and use** The type, symbol and use of the lifting and securing fittings shall be as shown in Table 1.

Table 1.

Name	Type		Symbol	Use	
Lifting fittings	Those equipped with detent locking during lifting	Twist type	A-TL	Used for lifting container at its top fittings using a cargo handling equipment	
Securing fittings	Those suitable to be made by die forging and the like		B-TF	Used for positioning or securing containers when loading on motor truck, freight-train car, etc.	Used for corner fittings
		Fixed type	B-PF		
	—	Catcher type	B-C		Used for securing fittings (anchors)