

**KES**

## **Change Knob & Booth Design Rule**

**KES L – I010**

**(EST.) 1991 – 09 – 27**

### **Contents**

- 1. Scope of Application**
- 2. Purpose**
- 3. Definition of Terms**
- 4. Managing Department of Standard.  
Design Rule**
- 5. Opening / Closing Procedures**
- 6. Change Knob Types**
- 7. Structure and Material**
- 8. Parting Line Setting**
- 9. Corrosion and Electroforming  
Condition**
- 10. Booth types**
- 11. Booth Material**

## **1. Scope of Application**

This rule shall be applied for change knob and booth inside car.

## **2. Purpose**

This rule is to consistently and effectively operate the preceding work, when developing car interior material, by setting the design standard for change knob and booth design, which are important elements to make inside image good.

## **3. Definition of Terms**

Change knob is the handle grip of gear transmission located on the center console beside the driver. It shall give good touching feel to driver when operating. It shall not need much power when operating.

Booth is the one that covers gear shaft that is shown from change knob to center console. As it covers the machinery elements, it gives driver comfort.

## **4. Managing Department of Standard**

Design Department shall be in charge of management of this standard.

## **5. Opening / Closing Procedure**

The head of design department shall execute opening / closing with approval from related departments.

## **6. Change Knob Types**

### **(1) Manual Type**

As it is the knob for manual transmission, letters 1, 2, 3, 4, 5, and R, are engraved on it.

Generally its length is 80 ~ 90mm.