

KES

Analysis of Manganese for Gasoline

KES T – M025

(EST.) 1988 – 05 – 09

Contents

1. Scope of Application
2. Meaning
3. Summary of Method
4. Equipment
5. Reagent
6. Framing Measuring Line
7. Operation
8. Measuring Absorbing Light Intensity
9. Calculation and Result
10. Allowances



1. Scope of application

This standard shall prescribe analysis of quantitative consistency of manganese of the range from 0.25 mg / ℓ to 30 mg / ℓ in gasoline .

Besides, this standard shall be able to be applied to the sort of materials like gasoline.

2. Meaning

Methyl cyclo pentadienyl manganese tri carbonyl : M.MT was used as octane number elevation instead of lead in the early period of smokeless gasoline, however, nowadays U.S prohibits it because manganese cause speech defect

3. Summary of method

After treating gasoline sample with iodine solvent, dilute it with methyl iso butylene ketone(MIBK).

Analyze manganese content with standard sample with atom-absorbing analysis while using air-acetylene flame at 279.5 nm

4. Equipment

- (1) Atom-absorbing spectrometer
- (2) Pipette : 1 mL content
- (3) Micro pipette

5. Reagent

- (1) MIBK
- (2) Iso octane
- (3) Iodine solvent : Needed 100 mL with 5 g of iodine dissolved in methyl alcohol
- (4) Standard Original sum of manganese (1 mg / mL)
- (5) Standard solvent of manganese : Take 1 mL standard solvent of manganese with