

# **UK National Annex to Eurocode 3: Design of steel structures –**

## **Part 2: Steel bridges**

ICS 91.010.30; 91.080.10; 93.040

## **Publishing and copyright information**

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2012  
Published by BSI Standards Limited 2012

ISBN 978 0 580 78489 7

The following BSI references relate to the work on this standard:  
Committee reference B/525/10  
Draft for comment 07/30128148 DC, 12/30260810 DC

## **Publication history**

First published May 2008

## **Amendments issued since publication**

| <b>Amd. no.</b> | <b>Date</b>  | <b>Text affected</b> |
|-----------------|--------------|----------------------|
| A1              | 31 July 2012 | See Introduction.    |

# Contents

Introduction 1

**NA.1** Scope 1

**NA.2** Nationally Determined Parameters 2

**NA.3** Decision on the status of the informative annexes 10

**NA.4** References to non-contradictory complementary information 11

Bibliography 12

## List of tables

Table NA.1 – Additional sacrificial thickness 4

## Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, pages 1 to 12, an inside back cover and a back cover.



# National Annex (informative) to BS EN 1993-2:2006, Eurocode 3 – Design of steel structures – Part 2: Steel bridges

## Introduction

This National Annex is published by BSI Standards Limited, under licence from The British Standards Institution. This National Annex has been prepared by BSI Subcommittee B/525/10, *Bridges*, in consultation with B/525/31, *Structural use of steel*.

The start and finish of text introduced or altered by National Amendment No.1 is indicated in the text by tags **A1** and **A1**. Minor editorial changes are not tagged.

National Amendment A1 has introduced changes to **NA.2.7** and **NA.3**.

## NA.1 Scope

This National Annex gives:

- a) the UK decisions for the Nationally Determined Parameters described in the following subclauses of BS EN 1993-2:2006:

- |                         |                         |
|-------------------------|-------------------------|
| • 2.1.3.2(1)            | • 8.2.1.6(1)            |
| • 2.1.3.3(5)            | • 8.2.10(1)             |
| • 2.1.3.4(1)            | • 8.2.13(1)             |
| • 2.1.3.4(2)            | • 8.2.14(1)             |
| • 2.3.1(1) (two places) | • 9.1.2(1)              |
| • 3.2.3(2)              | • 9.1.3(1)              |
| • 3.2.3(3)              | • 9.3(1)P               |
| • 3.2.4(1)              | • 9.3(2)P               |
| • 3.4(1)                | • 9.4.1(6)              |
| • 3.5(1)                | • 9.5.2(2)              |
| • 3.6(1)                | • 9.5.2(3)              |
| • 3.6(2)                | • 9.5.2(5)              |
| • 4(1)                  | • 9.5.2(6)              |
| • 4(4)                  | • 9.5.2(7)              |
| • 5.2.1(4)              | • 9.5.3(2) (two places) |
| • 5.4.1(1)              | • 9.6(1) (two places)   |
| • 6.1(1)P               | • 9.7(1)                |
| • 6.2.2.3(1)            | • A.3.3(1)P             |
| • 6.2.2.5(1)            | • A.3.6(2)              |
| • 6.3.2.3(1)            | • A.4.2.1(2)            |
| • 6.3.4.2(1)            | • A.4.2.1(3)            |
| • 6.3.4.2(7)            | • A.4.2.1(4)            |
| • 7.1(3)                | • A.4.2.4(2)            |
| • 7.3(1)                | • C.1.1(2)              |
| • 8.1.3.2.1(1)          | • C.1.2.2(1)            |
| • 8.1.6.3(1)            | • C.1.2.2(2)            |
| • 8.2.1.4(1)            | • E.2(1)                |
| • 8.2.1.5(1)            |                         |

- b) the UK decisions on the status of BS EN 1993-2:2006 informative annexes; and
- c) references to non-contradictory complementary information.

## **NA.2 Nationally Determined Parameters**

### **NA.2.1 Design working life [BS EN 1993-2:2006, 2.1.3.2(1)]**

Unless otherwise specified for a particular project, the design working life should be 120 years.

### **NA.2.2 Durability [BS EN 1993-2:2006, 2.1.3.3(5)]**

Additional requirements for durable details should be specified for a particular project.

### **NA.2.3 Robustness and structural integrity [BS EN 1993-2:2006, 2.1.3.4(1)]**

Components which need to be designed for accidental design situations should be specified for a particular project.

### **NA.2.4 Robustness and structural integrity [BS EN 1993-2:2006, 2.1.3.4(2)]**

The safe life design method of fatigue assessment should be used unless specified otherwise for a particular project.

### **NA.2.5 Actions and environmental influences [BS EN 1993-2:2006, 2.3.1(1)]**

Actions not included in various parts of BS EN 1991 which need to be considered in the design should be specified for a particular project.

Transient situations for maintenance and repair which need to be considered should be specified for a particular project.

### **NA.2.6 Fracture toughness [BS EN 1993-2:2006, 3.2.3(2)]**

The example in Table 3.1 should not be used and NA to BS EN 1993-1-10:2005, **NA.2.1**, should be followed.

### **NA.2.7 Fracture toughness [BS EN 1993-2:2006, 3.2.3(3)]**

**A1** For components in compression, the value given in NA to BS EN 1993-1-10 should be used.

*NOTE* Complementary guidance is given in PD 6695-1-10. **A1**