

UK National Annex to Eurocode 6: Design of masonry structures –

Part 3: Simplified calculation methods for unreinforced masonry structures

ICS 91.010.30; 91.080.30



NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2014.
Published by BSI Standards Limited 2014

ISBN 978 0 580 86309 7

The follow BSI references relate to the work on this standard:
Committee reference B/525/6
Draft for comment 14/30299660 DC

Publication history

First (present) edition, May 2007

Amendments issued since publication

Date	Text affected
-------------	----------------------

31 August 2014	See tagged text.
----------------	------------------

Contents

Introduction 1

NA.1 Scope 1

NA.2 Nationally Determined Parameters 1

NA.3 Decisions on the status of the informative annexes 3

NA.4 References to non-contradictory complementary information 7

Bibliography 8

List of tables

Table NA.1 – Values of γ_M for ultimate limit state 2

Table NA.2 – Values for f_{ks} 3

Table NA.3 – Characteristic flexural strength of masonry, $f_{xk1,s}$ and $f_{xk2,s}$ 6

Table NA.4 – Values of the initial shear strength of masonry, f_{vko} 7

This page deliberately left blank

National Annex (informative) to BS EN 1996-3:2006, Eurocode 6: Design of masonry structures – Part 3: Simplified calculation methods for unreinforced masonry structures

Introduction

This National Annex has been prepared by BSI Subcommittee B/525/6, *Use of masonry*. It is to be used in conjunction with BS EN 1996-3:2006. A1 National Annex (informative) to BS EN 1996-3:2006 has been revised following amendment to National Annex to BS EN 1996-1-1, concerning partial factors and the value of the K factor for concrete blockwork. A1

The start and finish of text introduced or altered by national amendment A1:2014 is indicated in the text by A1 A1. Minor editorial changes are not tagged.

NA.1 Scope

This National Annex gives:

- a) decisions for the Nationally Determined Parameters for the following subclauses of BS EN 1996-3:2006:
 - 2.3(2) P** Verification by the partial factor method;
 - 4.1(P)** Verification of the overall stability of a building;
 - 4.2.1.1(1) P** General conditions;
 - 4.2.2.3(1)** Capacity reduction factor;
 - D.1(1)** Characteristic compressive strength;
 - D.2(1)** Characteristic flexural strength;
 - D.3(1)** Characteristic initial shear strength.
- b) decisions on the use of informative Annexes A and C;
- c) references to non-contradictory complementary information to assist the user to apply BS EN 1996-3:6 (see **NA.4**).

NA.2 Nationally Determined Parameters

NA.2.1 Verification by partial factor method: values of γ_M [see BS EN 1996-3:2006, **2.3(2)P**]

The values for γ_M for the ultimate state limit are given in Table NA.1.

The recommended value for γ_M in the serviceability limit state for all of the materials listed in Table NA.1 is 1,0.