

MAT'LS / ADHESIVES & SEALANTS**FNHA-2-E-001.50****5.3 PACKAGING**

The container shall contain 0.473 liters. There shall be 6 containers to a package.

5.4 MANUFACTURING PROCESSES

For manufacturing application see specification 86513273(FNHA-4-C-001.00) STD Adhesive Application.

6. APPROVAL OF MATERIALS

Materials defined by this specification must have prior approval by the responsible Materials Engineering Activity. Suppliers desiring approval of their materials shall first obtain an expression of interest from the effected Purchasing, Design or Supplier shall submit to the affected Materials Engineering Activity its own Laboratory report to the specification (test results, not nominal values), the material designation and code number, and test specimens for Ford New Holland Inc. evaluation. Upon approval, the material will be added to the Materials Engineering Activity. Upon request, the Engineering Materials Approved Source List.

7. SUPPLIER'S RESPONSIBILITY

All materials supplied to this specification shall be equivalent in all characteristics to the material upon which approval was originally granted. Prior to the making of any changes in the properties, composition, construction, color, dimensions, processing or labeling of the material originally approved under this specification, the supplier shall notify Purchasing and the affected Materials Engineering activity of the proposed changes and obtain the written acknowledgement of the Material Engineering activity. Test data, test samples and a new identification code are to be submitted with the request.

 NEW HOLLAND	NAME STD PRIMER 205			PART NUMBER 86509008	
	ENGINEERING SPECIFICATION			REV. B	FRAME 2