

Parts in this list must meet the requirements of **STD 1015 - 1018 HR PL**, standard 9842898 (FNHA-2-A-251.00). Dimensions are inches, unless otherwise specified. When requesting a new part number, refer to the instructions in standard 86505922 (FNHA 3-A-005.00).

Part Number	Thick.	Width	Length	Special Instructions	U/M
8401037	.125	37.0	123.0		PC
290643	.250	48.0	120.0	P&O, supplied as A36	10.2096 LB/FT2
86500093	.250	30.0	39.25		10.2096 LB/FT2
291524	.250	39.25	coil	cut edge, aim for max.Rockwell B 75	2.7828 LB/IN
86500094	.250	39.25	39.25	restricted, use 9861264	10.2096 LB/FT2
9823649	.250	41.25	87.375	mill edge, temper rolled, no oil	10.2096 LB/FT2
9823650	.250	41.25	108.75	mill edge, temper rolled, no oil	10.2096 LB/FT2
86639949	.250	48.0	96.0	P&O, laser blank added 07/01	10.2096 LB/FT2
86523583	.250	48.0	96.0	laser steel, 96" +0.5 / -0, 4.4K max bundle weight	10.2096 LB/FT2
86600571	.250	48.0	96.0	laser steel, 96" +0.5 / -0, 4.4K max bundle weight	10.2096 LB/FT2
9603963	.250	50.0	coil	mill edge, 20K max. coil weight	3.5450 LB/IN
9861264	.250	50.0	51.25		10.2096 LB/FT2
86500095	.250	50.0	74.625		10.2096 LB/FT2
291409	.250	50.0	88.0		10.2096 LB/FT2
9823651	.250	52.63	114.0	mill edge, temper rolled, no oil	10.2096 LB/FT2
9823652	.250	56.53	78.75	mill edge, oiled	10.2096 LB/FT2
9823653	.250	56.75	112.75	mill edge, temper rolled, no oil	10.2096 LB/FT2
291036	.250	59.75	coil	mill edge, 20K max. coil weight	4.2362 LB/IN
86500096	.250	59.75	26.46	restricted, use 86500097	10.2096 LB/FT2
86500097	.250	59.75	32.0		10.2096 LB/FT2
291415	.250	59.75	49.0		10.2096 LB/FT2
291411	.250	59.75	62.0		10.2096 LB/FT2
291498	.250	59.75	67.5	aim for max. Rockwell B 75	10.2096 LB/FT2
291416	.250	59.75	73.0	mill edge	10.2096 LB/FT2
291497	.250	59.75	89.5		10.2096 LB/FT2
291493	.250	59.75	103.0		10.2096 LB/FT2
86533496	.250	59.75	119.75	Length change 2-99	10.2096 LB/FT2
291501	.250	59.75	127.0		10.2096 LB/FT2
9823654	.250	60.37	92.0	mill edge, temper rolled, no oil	10.2096 LB/FT2
9823655	.250	66.75	101.81	mill edge, temper rolled, no oil	10.2096 LB/FT2

ALL	H	TH	117009	OCT 01	NAME	MATL LIST 9842898	
ALL	G	TH	116316	07-01			
ALL	F	TH	114278	01-00	 NEW HOLLAND	ENGINEERING SPECIFICATION	
ALL	E	TH	113837	9-99			
ALL	D	TH	113232	2-99			
ALL	C	TH	112834	12-98			
ALL	B	RE	112499	9-98			
FRAME NO.	REV	BY	ECN NO.	DATE	THE INFORMATION HEREON IS THE CONFIDENTIAL AND PROPRIETARY PROPERTY OF NEW HOLLAND NORTH AMERICA, INC. AND/OR NEW HOLLAND CANADA, LTD. ANY USE, EXCEPT THAT FOR WHICH IT MAY BE LOANED, IS PROHIBITED.	FRAME 1	OF 3
APP. GES 9-98	DRAWN	TH	6-98			PART NUMBER	
	CHECKED					Documents 26574385 Document Sharing H	

9823656	.250	68.44	96.94	mill edge, temper rolled, no oil	10.2096 LB/FT2
9823657	.250	70.31	111.375	mill edge, temper rolled, no oil	10.2096 LB/FT2
9823658	.250	72.0	114.75	mill edge, temper rolled, no oil	10.2096 LB/FT2
9823644	.312	44.01	90.375	mill edge, oiled	12.7416 LB/FT2
86505475	.312	48.0	96.0	P&O	12.7416 LB/FT2
86639950	.312	48.0	96.0	P&O, laser blank added 07/01	12.7416 LB/FT2
86523585	.312	48.0	96.0	laser steel, 96" +0.5 / -0, 4.4K max bundle weight	12.7416 LB/FT2
86600572	.312	48.0	96.0	laser steel, 96" +0.5 / -0, 4.4K max bundle weight	12.7416 LB/FT2
9823645	.312	48.75	110.25	mill edge, temper rolled, no oil	12.7416 LB/FT2
9823646	.312	57.75	114.75	mill edge, temper rolled, no oil	12.7416 LB/FT2
291044	.312	58.25	coil	mill edge, 20K max. coil weight	5.1541 LB/IN
86533661	.312	58.25	120.0	Length change on 12-98	12.7416 LB/FT2
291502	.312	58.25	55.0		12.7416 LB/FT2
9823647	.312	60.0	83.25	mill edge, temper rolled, no oil	12.7416 LB/FT2
9823648	.312	66.0	85.75	mill edge, temper rolled, no oil	12.7416 LB/FT2
93811	.375	37.25	77.25	mill edge, oiled	15.3144 LB/FT2
86531436	.375	40.0	120.0	cut edge, P&O, change to cut sheet 10/01	15.3144 LB/FT2
86639951	.375	48.0	96.0	P&O, laser blank added 07/01	15.3144 LB/FT2
86523586	.375	48.0	96.0	laser steel, 96" +0.5 / -0, 4.4K max bundle weight	15.3144 LB/FT2
86600573	.375	48.0	96.0	laser steel, 96" +0.5 / -0, 4.4K max bundle weight	15.3144 LB/FT2
290897	.375	49.25	97.25	mill edge, temper rolled, no oil	15.3144 LB/FT2
290898	.375	57.0	99.0	mill edge, temper rolled, no oil	15.3144 LB/FT2
291041	.375	58.5	coil	mill edge, 20K max. coil weight	6.2214 LB/IN
9861206	.375	58.5	31.0	restricted, use 291496	15.3144 LB/FT2
291496	.375	58.5	38.688		15.3144 LB/FT2
86533654	.375	58.5	119.75	Length change 2-99	15.3144 LB/FT2
290929	.375	66.5	106.5	mill edge, temper rolled, no oil	15.3144 LB/FT2
290475	.438	78.25	105.0		17.8872 LB/FT2
93711	.500	9.5	104.5		20.4192 LB/FT2
89439	.500	10.0	120.0	10 - 12 foot random length	20.4192 LB/FT2
86514644	.500	12.086	29.875	blank for 86512978	PC
8401040	.500	15.0	120.0		PC
86533806	.500	48.0	120.0	laser steel, P&O, 5K max bundle weight, length change 07/01	20.4192 LB/FT2
290347	.500	94.0	111.0		20.4192 LB/FT2
292459	.500	96.0	120.0	mill edge, no oil, 10K max. bundle weight	20.4192 LB/FT2
291708	.562	71.0	127.0		22.9511 LB/FT2
292140	.625	11.0	110.0	mill edge, no oil	25.5240 LB/FT2
292476	1.250	96.0	120.0		51.0480 LB/FT2



NAME

MATL LIST 9842898

ENGINEERING SPECIFICATION

REV.
HFRAME
2OF
3

PART NUMBER

Documents

Document Sharing Hub

86574385